

Index

- ACPR, 159–61, 167
- adiabatic tracking, 152
- adiabatic variation, 172
- adjacent channel power ratio, *see* ACPR
- admittance matrix, 14
- AM-to-AM, 136, 155, 162, 167, 183
- AM-to-PM, 155, 167, 183
- analytic functions, 51
- analyticity, 46
- auxiliary variables, 169

- bandwidth-limited noise, 162
- bare transistors, 112
- baseband, 150
- baseband memory, 168, 203
- behavioral model, 2, 36, 38
 - black-box, 16
 - hierarchical, 16
- bias, 168
- bias current, 165
- bias modulation, 163, 165
- bias supply, 165
- bias voltage, 165
- biasing scheme, 24
- bias-line interaction, 152
- boundary conditions, 25–6

- cascadability, 11, 20
- cascade, 25, 27
- chaotic system, 151
- coherent cross-frequency phase measurement, 89
- commensurability condition, 138
- commensurate frequency, 112, 151
- commensurate signal, 30–2, 34
- complementary large-signal step response, 202
- complex amplitudes, 21–2, 24
- complex map, 47
- composite design, 11
- compression, 7, 20, 155, 177, 183
- constant envelope, 80
- constitutive relation, 169
- convolution, 170, 197
- cross-frequency phase, 30–1, 34, 140–1
- cross-frequency transfer functions, 62
- current bias, 37
- cutoff frequency, 15

- DC behavior, 36
- DC equations, 29
- DC operating point, 45
- DC response, 23
- DC stimuli, 23
- DC-bias stimuli, 23
- DC-current bias, 23
- DC-voltage bias, 23
- demodulation, 150
- differential equations, 30
- digital pre-distortion, 167
- digitally modulated signal, 159
- distortion, 16, 160
 - harmonic, 18
 - intermodulation, 18
 - source harmonics, 120
- distributed representation, 15
- drain lag, 163
- dynamic compression characteristic, 177
- dynamic load lines, 124
- dynamic range, 100
- dynamic X-parameters, 150

- efficiency, 167
- eight-term error model, 96
- electro-thermal effects, 152
- ellipse, 78, 84
- envelope analysis, 159
- envelope domain, 150–1, 160
- envelope representation, 154
- envelope simulation, 152
- equivalent circuit
 - linearized elements, 13
- equivalent stimuli, 38
- equivalent-time samplers, 92
- ergodic principle, 184
- error vector magnitude, *see* EVM
- EVM, 161
- experimental validation, 158, 169

- feedback, 170
- fifth-order intermodulation, *see* IM5
- figure of merit, 159, 167
- Fourier analysis, 32
- Fourier decomposition, 40
- Fourier series, 32, 34, 84, 155
- frequency domain, 30, 32
- frequency grid, 20, 22, 30
- functional relationship, 22
- fundamental frequency, 30, 34–5, 112, 138

- gain, 177
- generalized power waves, 24
- GSM amplifier, 80

- harmonic balance, 29
- harmonic frequency, 45
- harmonic grid, 22, 29, 34, 46
- harmonic indices, 27
- harmonic load pull, 57
- harmonic superposition, 118, 125
- hidden variable, 169–70
- hot S-parameters, 68
- hot-S₂₂, 69, 74
- hysteresis, 179
- hysteretic behavior, 169

- IM3, 157, 166, 186
- IM5, 157, 186
- IMD sweet spot, 179
- impulse response, 170, 172
- incident waves, 34
- incommensurate frequencies, 112, 138
- inductor, 165
- input envelope, 160
- input matching, 78
- input reflection coefficient, 78
- intermediate frequency
 - incommensurate, 113
- intermodulation, 139, 151, 157, 167, 177, 187
- internal node, 28
- interpolation, 118
- inter-stage interaction, 64
- intrinsic behavior, 34
- IP3, 161
- iso-thermal characteristics, 183

- Kirchhoff's current law, *see* KCL
- Kirchhoff's voltage law, *see* KVL
- KCL, 11, 25
- kernel
 - bivariate, 187
 - trivariate, 187
- KVL, 11, 25

- large-signal input reflection coefficient, 63
- large-signal operating point, *see* LSOP

- large-signal response, 56
- large-signal step response, 202
- large-signal S-parameters, 68
- large-signal stimulus, 61
- linear memory, 168
- linear region of operation, 61
- linearity, 167
- linearization, 169
- linearized map, 45, 50
- load boundary conditions, 27
- load match, 83
- load mismatch, 40
- load pull, 112
 - active, 112
 - active source injection, 118–19
 - fundamental load, 119
 - harmonic impedances, 119–20
 - hybrid, 112
 - independent harmonic impedance tuning, 134
 - nonlinear validation, 120
 - passive, 116, 119
 - passive tuners, 112
 - time-domain, 112
 - uncontrolled harmonic impedances, 119, 135
- local oscillator, 113
- long-term-evolution signal, *see* LTE signal
- long-term memory, 168
- lower sideband, 160, 162
- LSOP, 48–9
 - multi-tone, 113
- LSOPR, 50
- LSOPS, 50
- LTE signal, 159
- lumped approximations, 15

- McLaurin series, 196, 198–9
- matched device, 6
- matched load, 29
- measured data, 158
- measurement errors, 105
- memory, 150, 161
- memory effects, 162–3
- memory kernel, 168, 171, 174, 176
 - identification of, 171
- mismatch, 25, 28, 46, 55, 64, 113
 - harmonic, 123
 - large, 113
 - multi-frequency, 120
 - small, 45
- mixer, 113, 144
 - conversion gain, 147
 - isolation, 147
 - LO leakage, 147
- mixer-based systems, 88
- model validation, 175
- modulation, 150, 160, 165, 168, 177
- monomial, 202

- multi-harmonic, 34
- multi-harmonic spectral maps, 22
- multi-port network, 38
- multi-port stimulus, 34, 38
- multi-tone map, 115
- multi-tone stimulus, 139
- multi-valuedness, 162

- narrow-band limit, 160
- noise, 162
- noise floor, 100, 185
- non-analytic functions, 53
- non-analytic maps, 46
- non-analytic spectrum, 48
- non-commensurate signals, 30
- nonlinear equations, 27
- nonlinear functions, 35
- nonlinear map, 45
- nonlinear mappings, 29
- nonlinear measurement calibration, 93
- nonlinear operation, 64
- nonlinear operators, 35
- nonlinear process, 20
- nonlinear solver, 30
- nonlinear spectral map, 20, 22, 44
- nonlinear vector network analyzer, *see* NVNA
- NVNA, 91

- offset frequency, 162
- offset-frequency method, 102
- offset-phase method, 104
- operating point DC, 12
 - large-signal, *see* LSOP
- output envelope, 160
- output power, 166
- output reflection coefficient, 69

- PAE, 124
- parallel Hammerstein model, 182, 202
- partial derivatives, 51, 53
- passive load, 28
- PDF, 168, 184, 204
- peak-to-average ratio, 169
- perfect step, 163
- perturbation, 46, 51, 117
- perturbation theory, 45, 51
- perturbation tones, 120
- phase reference, 97, 100
 - golden device, 100
 - repetitive pulse generator, 100
- phase-reference signal, 89, 97
- phase shift, 39
- phasor, 3–5, 139
- physical interpretation, 39
- physical meaning, 38, 55
- polynomial, 196–7

- power-added efficiency, *see* PAE, 124
- power amplifier, 159, 167, 169
 - AM-to-AM, 136
 - auxiliary for Doherty, 131, 135
 - Doherty, 112, 119, 129–30
 - drain efficiency, 137
- power dissipation, 163
- power distribution, 29
- power transistor, unmatched, 114
- power wave, 2
- probability density function, *see* PDF

- quasi-static approximation, 151, 154, 158, 161, 165

- radio-frequency integrated circuit, *see* RFIC
- radio-frequency signal, *see* RF signal
- real-time samplers, 92
- reference impedance, 2
- reference LSOP stimulus, 114
- reference response, 38–9, 60
- reference stimulus, 38–9
- reflection coefficient, 113, 116
- relative phase, 34
- resonances, 177
- response at DC, 23
- RF interaction terms, 51
- RF signal, 113
- RF solution, 29
- RFIC, 162
- RF-to-DC interaction terms, 51
- Riemann integral, 205
- Riemann sum, 204

- sampler-based systems, 91
- scalar loss correction, 94
- scattering parameters, *see* S-parameters
- self-heating, 163, 168, 183
- sensitivity, 55
 - harmonic, 124
 - to mismatch, 55
- sensitivity functions, 117, 142
 - harmonic load sensitivities, 120
- series expansion, 51, 53
- short-term memory, 168
- signal bandwidth, 160
- simulation-based extraction, 106
- small signal, 16
- small-signal interactions, 52
- small-signal operating conditions, 168
- small-signal response, 56
- small-signal transfer function, 56
- source boundary conditions, 26
- source harmonics, 68
- source mismatch, 40, 68
- source pull, 128
- S-parameter calibration, 94

- S-parameter matrix, 4
- S-parameters, 1
 - hot, 17
 - large-signal, 17
 - for linear component
 - definition, 5
 - for nonlinear component
 - definition, 7
- spectral components, 29
- spectral Jacobian, 60
- spectral linearization, 45, 60, 112, 142
- spectral map, 7, 45
 - non-analytic, 117
- spectral mapping, 20, 55
- spectral re-growth, 179
- spectrum analyzer, 161
- state space, 36
- steady state, 27, 36, 45, 152
- step excitation, 181
- step response, 172, 184
- step transition, 172
- stochastic signal, 184
- superposition, 8
- sweet spot, 179
- symmetry conditions, 157

- temperature change, 163
- ten-term error model, 95
- test stimulus, 39
- thermal capacitance, 163
- thermal circuit, 163
- thermal relaxation, 163, 183
- thermal resistance, 163
- thermal response, 183
- thermal transient, 172
- third-order intercept, 161
- third-order intermodulation, *see* IM3
- time derivative, 172
- time invariance, 10, 20, 24, 35–6, 197
- time reference, 33
- time shift, 34, 39, 115
- time domain, 29, 32
- time-invariant components, 45
- time-invariant map, 44
- time-invariant systems, 35–6
- time-varying envelope, 152
- trajectory, 72
- transfer functions, 62
- transient measurement, 168

- transistor, 24
 - above/below turn-on, 133
 - cutoff, 133
 - GaAs FET, 120
 - GaN, 123, 129
 - GaN HEMT, 123
 - output impedance, 133
- transistor models, compact, 120
- transit time, 163
- transportable model, 168
- trapping effects, 163, 168
- turn-on transient, 182
- two-stage amplifier design, 64
- two-tone excitation, 161
- two-tone experiment, 158, 175
- two-tone measurement, 160
- two-tone signal, 181
- two-tone simulation, 166

- upper sideband, 160, 162

- validation, 175
- vector network analyzer, *see* VNA
- vector signal analyzer, 168
- vector signal generator, 131
- VNA, 88
- voltage bias, 37
- Volterra theory, 196–7

- wave variables, 2
- WCDMA, 181
- wide-band memory approximation, 204
- wide-band modulation, 150, 182, 184, 204
- wide-band X-parameters, 185

- .xnp files, 106
- X-parameter correction, 106
- X-parameter files, 106
- X-parameter measurement, 101
 - offset-frequency method, 102
 - offset-phase method, 104
- X-parameters
 - arbitrary load-dependent, 112
 - load-dependent, 119
 - measurement hardware, 88
 - type S, 52
 - type T, 52
- Y-parameters, 14