

Index

- Abrasion resistance of borided steel, 283–284
 Abrasion resistance of vanadised steel, 283–284
 Abrasion wear, 278–287
 Abrasion wear resistance of diffusion hardened steels, 283–285
 Abrasion wear resistance of hard anodised aluminium, 233
 Abrasion wear resistance of plasma sprayed WC-Co, 284–285
 Abrasion wear resistance of plasma sprayed coatings, 280–283
 Abrasion wear resistance of PVD-TiN, CVD-TiC & PVD-Cr-B, 285–287
 Active screen nitriding, 57–60
 Adhesive coating failure (in-vivo), 472–473
 Adhesive fracture wear (coated tools in machining), 369–372
 Adhesive wear, 369–372, 401–402, 412–414
 Air intake (GTE), 423–425
 Aluminising (calorising), 91–100
 Aluminising (hot dip), 127–134
 Aluminium oxide (Al_2O_3) coating wear, 274–285, 357–363, 363–369
 Anodic coating/cathodic substrate (corrosion of), 305–309
 Anodic current variation during sliding contact, 315–317
 Anodising (Anodizing), 231–238
 Antagonism (in corrosion-wear), 314–315
 Appendix A, 481–487
 Applications – *see* SE Applications
 Aqueous corrosion pathways (Cr-Ni plated steel), 140–141
 Arc source (for PVD ion plating), 179–182
 Arc wire spraying, 201–202
 Archard wear equation, 278
 Atmospheric corrosion, 125–130
 Atmospheric plasma spraying (APS), 203–207
 Attrition wear (adhesive fracture wear in machining), 369–372, 373–376
 Auto catalytic plating, 149–152
 Auto engine applications, 387–422
 Average stresses on cutting tools, 331–334
 Axial fed plasma torch, 205–207
 Bias (electrical) effect on PVD coating microstructure, density and substrate adhesion, 174–176, 191–192
 Binary phase diagrams, 481–487
 Bio-medical implants, 449–480
 Blister formation in coated materials due to internal compressive stress, 307–314, 412–414, 428–430, 475–476
 Bone integration (implants), 462–463
 Boost diffuse (aluminising), 99–100
 Boost diffuse (carburising), 70–74
 Boride coating via PVD, 378–380
 Boriding, 81–90
 Boriding technology, 86–90
 Boron excess (after boriding), 88–90
 Boundary lubrication, 388–389
 Built-up-edge (during machining two phased metals), 330–333
 Bypass air flow (GTE), 424
 Cadmium plating, 146
 Calorising (aluminising), 91–100
 Cam follower wear, 406–408
 Carbonitriding, 75–76, 298
 Carburising of steels, 57, 59, 70–75, 276, 291, 293–300
 Case depth (definitions), 38–39
 Cast-irons, 373–376, 389–390, 392, 406–407
 Cathodic coating/anodic substrate (corrosion of), 303–309
 Ceramic dip (slurry) coating, 153–154
 Chemical conversion coatings (other), 242–243
 Chemical vapour deposition, 154–172
 Chip morphology (in machining), 330–331
 Chromating, 243
 Chromising (chromiding), 107–108

- Chromium boride coating (wear & corrosion of), 285–287, 379–380
- Chromium carbonitride (CrCN) coated Co-Cr in-vitro wear, 473–475
- Chromium nitride (Cr₂N) by PVD – wear of, 414–417
- Chromium nitride (CrN) coated Co-Cr in-vitro wear, 473–475
- Chromium nitride (CrN) coated stainless steel (corrosion wear), 310–313, 317–320
- Chromium nitride (CrN) deposition by PVD, 182–183
- Chromium plating, 138, 392, 394, 395
- CKS coating, 393–395
- Cladding, 250–254
- Closed field magnetron sputtering, 185–187
- Closed loop partial pressure control (used in reactive sputtering), 182–183
- CMAS attack (of GTE blades), 441–444
- Coated cutting tool wear patterns, 326–328
- Coated hip resurfacing implant device, 472–473
- Coated sialon tools, 352
- Coating defects (PVD), 181–182
- Coating defects (thermal spray), 195–198
- COC biomedical implants, 452
- Co-deposited electrolytic-electrophoretic coating, 152–153, 393–394
- Coefficient of friction (μ), 18–19, 287–288, 388–389
- Cohesive fracture wear (coated tools in machining), 369–373
- Cold spraying, 210–211
- Columnar grains in CVD and PVD coatings, 187–193
- Columnar porosity (Zone 1) in thick PVD coatings, 187–193
- Columnar porosity anodised aluminium, 231–233
- Combined deposition/diffusion surface engineering, 10–13, 212–213, 438–441
- Combustion section (GTE), 423–427
- Compound layer (nitride and nitrocarburised steels, influence on RCF), 31, 42, 55, 67, 283, 284, 290–295, 299–300
- Compression section (GTE), 423–427
- Cone cracks, 271–273, 307–309, 310–314
- Conformal contacts, 19–21
- Contact mechanics, 13–25
- Contaminants in GTE fuels, 423–424
- Conventional anodising of aluminium, 231–234
- COP biomedical implants, 452
- Corrosion, 303–309
- Corrosion (in-vivo) of Morse taper/trunnion, 450–452
- Corrosion-wear, 309–320
- Counterformal contacts, 19–21
- Crack dimension ($2c$), 221–223
- Cracks due to tensile residual stress in CVD coatings, 218–221
- CrN or Cr₂N, 182–183, 402–405, 414–417, 473–475
- Crooke's dark space, 52, 57, 58
- Crystal orientation (texture) of CVD/PVD coatings, 170–172
- Cutting edge plastic deformation during machining, 327–328, 344–347
- Cutting tool applications, 324–386
- Cutting tool wear, 327–329, 343–373
- CVD coated carbides, 160–162, 343–350
- CVD-Al₂O₃ (alumina), 163–165
- CVD-boron, 168–169
- CVD-coating material types, 155, 156–157
- CVD-coating nucleation, growth, microstructure & topography, 167–172
- CVD-coating set-up – schematic, 158
- CVD-cubic boron nitride (CBN), 167
- CVD-diamond, 167
- CVD-Ti(C,N), 163–164
- CVD-TiC, 159–162
- CVD-TiN, 162–163
- CVD-W₂C & W+W₂C, 165–166
- Dark space, 52, 57, 58
- Delamination wear, 412–414
- Delta ceramic, 459
- Depth-property profiles, 10–13
- Detonation (D) gun spraying, 198–199, 207–208
- Diamond-like-carbon (DLC) coated Ti-6Al-4V bio-implant failure, 475–476
- Diamond-like-carbon (DLC) coating – friction in lubricated contacts, 419
- Diamond-like-carbon coating wear, 411–420, 475–476
- Diffusion coatings, 91–111, 427–438
- Diffusion profile (effect of time), 37–39
- Diffusion rate comparison, 35–36
- Diffusion theory, 35–39
- Diffusion/dissolution wear, DDW, of cutting tools, 350–357
- DLC hardness, 29–32, 410–411
- Dry contact wear, 289–293
- Duplex surface engineering, 212–213, 439
- Dynamic saturation zone (in metal machining), 350–357
- EB-PVD t-ZrO₂, 438–441
- Elastic contacts, 13–26
- Elastohydrodynamic lubrication (EHL), 388–389
- Electric arc vapour source, 179–182
- Electrode potential (effect on aqueous corrosion-wear), 315–320
- Electrode potential (effect on sulphidation), 431–433
- Electro-galvanizing, 147–148
- Electroless nickel plating, 149–152
- Electrolytic-electrophoretic plating, 152
- Electron beam cross-linking, 255–256
- Electron beam surface alloying (EBSA) – *see* laser surface alloying
- Electron beam vapour sources, 179–180

- Electrophoretic coating, 152
 Electroplating, 136–149
 Electroplating topography, 169–172
 Enabling surface engineering, 5–9
 Enamel coating, 153
 Engineering surfaces in reality, 5–9
 Enhanced substrate current density in PVD, 184–187
 Enthalpy content of plasmas for spray deposition, 203–205
 Equiaxed grains in CVD coatings, 161, 217
 Equilibrium diagrams (phase diagrams), 481–487
 Erosion wear, 270–278, 441–446
 Eta phase (η -phase), 161–162, 373–375
 Evaporant source poisoning, 182–183
 Evaporation versus ion plating, 173–176
 Exhaust section (GTE), 423–424
- Faience tiles, 1–2
 Fan blade (GTE), 423–424
 FEM analysis of SE surfaces, 20–24
 Fick's 1st Diffusion law, 356
 Fick's 2nd Diffusion law, 38
 First yield (position of), 13–20
 Flame hardening, 243–244
 Flame spraying, 199–201
 Flank face wear, 343–345
 Flow chart for hot dip processing, 121
 Flow chart for materials manufacture (before SE), 4–5
 Formability of hot dip aluminised steel, 130–134
 Fretting of bio-implants, 453, 463–464
 Fretting wear, 301–302, 363–369, 453, 463–464
 Frictec, 250
 Friction coefficient, 18–19, 287–288, 388–389
- Galfan (hot dip), 125–126
 Gallium (scuffing), 400–401
 Galvalume (hot dip), 126–128
 Galvanic corrosion, 303–309
 Galvanic series, 303–305
 Galvanising (hot dip), 123–125
 Galvannealing, 124–125
 Gas turbine engine (GTE) applications, 423–448
 Gaseous boriding, 88–90
 Gaseous carbonitriding, 75–76
 Gaseous carburising, 70–75
 Gaseous nitriding, 48–50
 Gaseous two-stage aluminising, 99–100
 Gear contacts, 19–21, 293–300
 Glow discharge plasma to arc transition, 55–57
 Gold plating, 148–150
 Grain pull-out of ceramic implant bearing surfaces – *see also* attrition wear, 459–461
 GTE (gas turbine engine) basics, 423–427
 GTE chemical attack of, 427–438, 441–443
 GTE erosion, 442–446
 GTE pressure ratio, 426
 GTE temperature profile, 425
- Hard anodising of aluminium, 233–234
 Hardfacing – *see* Weld hardfacing
 Hardfacing materials, 252
 Hardness testing, 29–33
 Hardness-depth profiles (characteristic shapes), 10–13, 47, 61, 466
 Hertz cone cracks, 271–273
 Hertz contact stresses, 15–25
 Hertz contacts, 13–25
 Hertz pressure, 15–25
 Hertz shear stress (τ), tau, 15–20
 Hertzian failure, 13–14, 20–25, 467–468
 High speed galvanising, 123–125
 High speed tin plating, 141–143
 High velocity spraying – *see* HVOF and HVAF
 HIPIMS, 183–184
 Homologous temperature, 156–157, 187–193
 Hot corrosion, 427–438
 Hot dip aluminising (Types 1 & 2), 127–136
 Hot dip coating, 116–136
 Hot dip galvanised steel microstructure, 123–127
 Hot dip tin, 136
 Hot hardness, 341–343
 Hot spot formation in sliding contacts, 289–291
 Hot stamping (process chain), 131–134
 HVAF, 209–210
 HVOF, 209–210
 Hybrid PVD-CVD, 193–194
 Hydrodynamic lubrication (HL), 388–389
 hydroxylapatite – also termed hydroxyapatite (HA), 462–463
- Industrial applications of CVD and PVD, 194–195, 324–386, 399–406
 Internal stress, 214–221
 Interstitial diffusion, 35–53
 In-vivo damage, 454–460
 Ion implantation, 60–61, 263–265
 Ion plating, 173–178
 Ionic bombardment, 52–53
 Iridite process, 243
 Ivadising, 175
- Kirkendall porosity (after plasma boriding), 88–90
 Knoop hardness (Hk) – *see* nomenclature list
- Lambda ratio (λ), 389
 Large area electron beam surfacing, 255–256
 Laser alloyed cast iron auto engine rocker arm, 257–259
 Laser alloying steel with boron, 260–262
 Laser glazing, 262–263
 Laser nitrided titanium, 259–260
 Laser peening (shock hardening), 246–250
 Laser power density/interaction time effect, 247
 Laser scanning during SE, 254–255
 Laser shock hardening – *see* laser peening
 Laser solidification regimes, 257–258
 Laser surface alloying (LSA), 257–262

- Laser surface engineering & EBSA, 243–244, 246–250, 254–263
 Laser vitrification, 262–263
 Lateral cracks, 274
 Lead plating, 146–147
 Lead-tin plating, 146–147
 LIH (Load invariant hardness), 29–31
 Low temperature carburising, 77–80
 Low temperature CVD (without plasma), 165–166
 Low temperature nitriding, 77–80
 LSA – *see* Laser surface alloying
 Lubricated sliding contacts, 293–300
 Lubrication and lubrication regimes, 293, 388–389
- Machining metals and composites, 324–386
 Macro-particles (in arc source PVD), 180–182
 Magnetron sputtering & sputter deposition, 178
 MAO – *see* micro-arc oxidation
 Maps showing friction, pressure and temperature operational regimes, 287–288
 Market price of metals, 118–119
 Mechanical surface hardening, 244–250
 Median cracks, 271, 274
 Medium temperature CVD, 164–165
 Meijering equation, 44
 Metal transfer (galling), 400–401
 Micro examination of worn cutting tools, 327–329
 Micro-pitting in rolling/sliding contacts, 293–297, 300, 414–419
 Micro-arc oxidation (MAO), 234–238
 Microhardness, 29–31
 Microstructure and topography zone models (vapour deposited coatings), 187–193
 Microwave CVD, 166–167
 Mixed lubrication, 388–389
 Modified aluminising, 100–107
 MOM biomedical implants, 452
 MOP biomedical implants, 452
 MTCVD-Ti(C,N) and Al₂O₃, 164–165
 Multicomponent boriding, 90
- Nanocomposite thermal sprayed coatings, 395–398
 Nanohardness, 31–33
 Nd-YAG (Neodymium yttrium aluminium garnate laser), 255
 Nickel alloy development to resist creep, 91–95
 Nickel plating, 138–140
 Nickel plus chromium plating, 140–141
 Nickel with particles (plating), 149–152
 Nitriding (effect on fatigue), 40, 65
 Nitriding (of *other materials*), 61–66
 Nitriding (of steels), 40–48
 Nitrocarburising of steels, 67–68
 Nitrocarburising technology, 68–70
 Notch wear (cutting tools), 363–369
 Nozzle guide vanes (NGVs), 430
 Nucleation & growth of coatings, 116, 167–172, 187–188
- Oil additives, 390, 400, 408, 410
 Oil lubricated contacts, 19–25, 293–300, 388–390
 Open circuit potential (variation during sliding contact), 315–317
 Open field magnetron sputtering, 185
 Operating maps for surface engineered materials, 287–288
 Osseo integration, 462–463
 Overlay coating, 146–147, 438–441
 Oxidation, 194, 238, 427–428
 Oxidational (oxidation) wear, 240–242, 289–293
 Oxinium, 465–470
 Oxyfuel thermal spraying, 199–201
 Oxygen diffusion hardening, 238–242, 470–471
- Pack aluminising (calorising), 91–107
 Pack boriding, 87–88
 Pack chromising, 107–108
 Particle velocities in thermal spraying, 196, 205–206
 Peening, 244–245, 246–250
 PEO (plasma electrolytic oxidation), 233–238
 Phase diagrams, 481–487
 Phosphating, 242–243
 Pin-on-disc testing & wheel on wheel, 23–25, 212–213, 287–293
 Piston ring applications, 388–406
 Piston ring coating wear, 392–406
 Piston ring coatings, 388–406
 Piston ring PVD coatings, 399–406
 Plasma assisted CVD, 166–167
 Plasma boriding, 88–90
 Plasma carburising, 71–74
 Plasma diffusion technologies (basics), 50–57
 Plasma enhanced CVD, 166–167
 Plasma immersion ion implantation (PIII), 60–61
 Plasma nitriding, 50–60
 Plasma nitrocarburising, 69–70
 Plasma power density, 53–57
 Plasma spraying, 203–207
 Plasma temperature distribution in plasma spraying, 204–206
 Platinum modified aluminising, 100–104, 427–433
 Platinum plating, 148–149
 PMMA (cementing), 450–452
 Polishing wear, 356–357, 365–367, 376, 402, 455
 Polymer/aluminium stack machining, 377
 Porosity in surface engineered layers, 195–199, 221–223
 Powder coating, 211
 Precious metal plating, 148–149
 Precipitation hardening of electroless Ni-P coatings, 149–152
 Pull-out – *see* grain pull-out
 PVD, 173–193
 PVD-coating material types, 156–157
- Quick-stop method, 329–330

- R_a , 27
 Radio and high frequency plasma PVD, 183–184
 Rake face (tool) wear and its development, 345–350
 Rates of wear on flank compared to rake face, 349, 353, 375
 Reactive PVD (ion plating or sputtering), 176–178, 182–183
 Real engineering surfaces, 5–9
 Residual (internal) stress, 214–221
 Revision of human joint replacements, 452–453
 Reynold's number (N_{Re}) – effect on CVD, 167–169
 RF CVD, 166–167
 RF Plasma, 183–184
 RF sputtering, 183–184
 Robot assisted APS, 197–199
 Roll hardening, 244–246
 Rolling contacts and RCF, 25–26, 293–300, 415–420
 Rolling/sliding contacts, 25–26, 292–300, 406–420
 Roughness (of surfaces), 26–28
 R_t , 27
 Running-in, 26–28

 Salt bath nitrocarburising, 68–69
 Scratch damage in-vivo & in-vitro, 454–460
 Scratch test damage to coated materials, 175–176, 281–283
 Scuffing (galling), 390, 394–395, 400–401
 SE Applications (specific), Chapters 7 to 10
 SE Applications (across the board), 2–3, 5, 10–13, 40–42, 58–59, 62–64, 74, 79, 83, 88, 92–94, 96, 100–111, 127, 129–136, 138–144, 146–154, 159, 163–165, 167, 174–175, 194–195, 202–203, 208, 212–213, 232–234, 237, 239, 241–250, 252, 255–256, 259
 SE charts, diagrams, maps, 14–17, 288
 Silicon modified aluminising, 104–107
 Siliconising, 109–111
 Silver plating, 116, 117, 148
 Sliding contacts, 20–26, 287–293, 464–476
 Sliding/rolling contacts, 25–26, 406–415
 Slurry coating, 104–107, 153–154
 Slurry erosion of SE and untreated materials, 277–278
 S-N behaviour, 40, 64–65, 293–300, 414–420
 Sol-gel coating, 211–212
 Solubility of tool materials in iron, 351
 Solution nitriding, 80–81
 Special carburising and nitriding for stainless steels, 77–81
 S-Phase surfaces via deposition, 80, 183, 312, 318, 319, 400
 S-Phase surfaces via diffusion, 77–80
 Spray & fuse, 252–254
 Sputter cleaning, 52–53
 Sputter coating, 173–178
 Sputter target poisoning, 182–183
 Steam blued steel, 194, 238–239

 Stress distribution on cutting tools, 331–334
 Substitutional diffusion processes, 91–111, 427–438
 Sulphidation, 423–438
 Surface degradation, 269–323
 Surface engineering – aluminium alloys, 5, 15, 17, 64–66, 231–237
 Surface engineering – cemented carbides, 5, 324–386
 Surface engineering – ceramics, 2, 5, 380
 Surface engineering – cobalt alloys, 5, 78, 461
 Surface engineering – composites, 5, 109–111
 Surface engineering – magnesium alloys, 5, 17, 238
 Surface engineering – nickel alloys, 5, 16, 91–100, 423–448
 Surface engineering – polymers (plastics), 5, 66, 117, 255–257
 Surface engineering – steels, 5, 14, 17, 35–90, 107–109, 326
 Surface engineering – titanium alloys, 5, 15, 61–64, 237–241, 259–260, 460–461, 470–472
 Surface engineering – zirconium alloys, 5, 240–242, 465–470
 Surface engineering applications – *see* 'SE Applications'
 Surface engineering background, 1–3
 Surface engineering basics, 4–34
 Surface engineering by other means, 231–268
 Surface engineering deposition technologies, 116–230
 Surface engineering depth-property profiles, 10–13
 Surface engineering diffusion technologies, 35–115
 Surface engineering process selection charts, 17
 Surface engineering routes/paths, 5, 7, 8
 Surface engineering triangle, 2–3
 Surface engineering, where & when, 4–5
 Surface preparation (before & after SE), 5–10, 121–122, 195–197
 Surface roughness, 26–28

 Table 2.1, 28
 Table 2.2, 32
 Table 3.1, 41
 Table 3.2, 43
 Table 3.3, 50
 Table 3.4, 55
 Table 3.5, 73
 Table 3.6, 78
 Table 3.7, 82
 Table 3.8, 82
 Table 3.9, 86
 Table 3.10, 90
 Table 3.11, 92
 Table 3.12, 93
 Table 3.13, 94
 Table 3.14, 97
 Table 3.15, 101
 Table 3.16, 102
 Table 4.1, 117
 Table 4.2, 117

- Table 4.3, 120
 Table 4.4, 122
 Table 4.5, 137
 Table 4.6, 139
 Table 4.7, 144–145
 Table 4.8, 150
 Table 4.9, 151
 Table 4.10, 155
 Table 4.11, 156–157
 Table 4.12, 175
 Table 4.13, 178
 Table 4.14, 196
 Table 4.15, 202
 Table 4.16, 203
 Table 4.17, 208
 Table 4.18, 215
 Table 4.19, 220
 Table 5.1, 252
 Table 6.1, 271
 Table 6.2, 283
 Table 6.3, 302
 Table 6.4, 304
 Table 6.5, 318
 Table 7.1, 326
 Table 7.2, 326
 Table 7.3, 335
 Table 7.4, 338
 Table 7.5, 342
 Table 7.6, 350
 Table 7.7, 351
 Table 7.8, 367
 Table 7.9, 381
 Table 8.1, 391
 Table 8.2, 397
 Table 8.3, 407
 Table 8.4, 410
 Table 8.5, 417
 Table 9.1, 425
 Table 9.2, 426
 Table 9.3, 428
 Table 10.1, 450
 Table 10.2, 452
 Table 10.3, 454
 Target poisoning, 182–183
 TEM images of CVD/PVD coatings, 171, 190, 216, 217
 Texture (crystal orientation) of CVD/PVD coatings, 170–172
 Thermal barrier coatings & systems, 438–446
 Thermal conductivity (K), 440, 446
 Thermal oxidation (of steels, titanium & zirconium alloys), 61, 238–242, 470–471
 Thermal spraying, 195–210
 Thermal stress, 214–215
 Thermal transformation hardening, 243–244
 Thermo (flame) spraying, 199–201
 Thin ice effect, 13–14, 20–25, 467–468
 Thornton diagram, 187–193
 Thrust bearing tests, 408–420
 Ti(Al)N coating, 352–354
 Tin plating, 141–143
 Tin-nickel alloy plating, 143–144
 Tin-zinc alloy plating, 148
 Titanium carbide (TiC) coating wear, 343–373
 Titanium carbonitride coating wear, 352–354
 Titanium nitride (TiN) coating, 162–163, 170–172, 176–183, 194–195, 214–221
 Titanium nitride (TiN) coating wear, 275, 286, 348–378, 472–473
 TML (antagonism and mechanical material loss components), 319
 TML (influence of hardness on), 317–320
 TML and TML rates (TMLR), 26–28, 309–317, 352–354
 Tool contact stresses in machining, 331–334
 Tool temperatures in machining, 334–340
 Tool temperatures when cutting Ni & Ti alloys, 378–380
 Tool wear mechanisms (cutting other materials), 373–380
 Tool wear mechanisms (cutting steel), 350–373
 Tool wear rates – rake and flank comparison, 348, 349, 375
 Tool wear zones, 327–329
 Total hip replacement (THR), 450–454
 Total knee replacement (TKR), 450–454
 Total material loss – *see* TML and TML rates
 Traction stress, 20
 Transformation hardening, 243–244
 Tresca (shear) yield criterion, 29
 TRD process, 108–109
 Tribocorrosion, 309–320
 Triode ion plating, 179–182, 184–185
 Triode sputtering, 184–187
 Turbine blade alloy composition & types, 426 (Table 9.2)
 Turbine blade internal cooling, 426–427
 Turbine blades and vanes (GTE), 423–427
 Turbine section (GTE), 423–427
 Turn cutting, 326–330
 Type I HTHC (high temperature hot corrosion), 427–438
 Type II LTHC (low temperature hot corrosion), 427–438
 Types 1 & 2 hot dip aluminising, 127–136
 Types I, II & III corrosion-wear, 309–315
 UHMWPE (polyethylene) wear in-vitro, 254–257
 UHMWPE (polyethylene) wear in-vivo, 454–457
 Unbalanced magnetron sputtering, 184–187
 Uncoated Co-Cr-Mo bearing surface wear, 468–470
 Uncoated Co-Cr-Mo condyle wear, 468–470
 Vacuum plasma spraying (VPS), 203–207
 Valve lifters (wear), 406–413
 Vanadising, 108–109

Index**495**

- Vapour pathways in evaporation and ion plating, 173–175
 VHN (see Vickers hardness), 28–33
 Vickers hardness and microhardness, 28–33
 Vingsbo et al method, 30–31
 Vitreous enamel coating, 153
 VPN (see Vickers hardness)
 VPS – *see* vacuum plasma spraying
- Wear – abrasion, 278–287
 Wear – adhesive (delamination) and cohesive fracture, 369–372, 373–376, 401–402, 412–414
 Wear – attrition, 369–372, 373–376
 Wear – discrete plastic deformation (DPD), 357–360
 Wear – dissolution/diffusion (DDW), 351–357
 Wear – erosion, 270–278, 441–446
 Wear – fretting, 301–302, 363–369, 453
 Wear – microabrasion wear (MAW), 360–363, 411–412
 Wear – notch wear (cutting tools), 363–369
- Wear – oxidation (oxidational) wear, 289–293, 363–367
 Wear – pin holing, 414–416
 Wear – polishing wear, 356–357, 365–367, 376, 402–403, 456
 Wear – sliding contacts, 287–293, 388–406
 Wear of piston rings, 388–406
 Wear – RCF (rolling contact fatigue pitting), 299–300, 415–420
 Weld hardfacing (cladding), 252–254
 Wheel on wheel testing, 287–293
 Wire arc (arc wire) spraying, 201–202
- Z (position of t_{\max}), 13–25, 468
 Zinal process, 213
 Zinc phosphated steel, 242–243
 Zinc plating, 147–148
 ZrO₂ coatings – *see* ‘Thermal barrier coatings & systems’
 ZrO₂ radio-opaque particles in PMMA cement, 458–459
 ZTA (zirconia toughened alumina), 452, 459, 460