

INDEX

- actuating signal, 155
- agility (of a target), 83
- anchoring, 63
- automatic target recognition, 171
  
- base-state innovations, 44
- base-state model
  - JTS, 10
  - time-continuous, 7
  - time-discrete, 24
- base-state process, 3, 5
- base-state sensor, 43
- Bayes' Theorem, conditional, 200
- binary phase shift keying, 211
  
- canonical moment, 48
- causal, 2
- certainty equivalence principle, 47, 157, 159, 166
- change-of-measure (COM) estimator, 199
- coquadratic variation, 43
- coarser  $\sigma$ -field, xvi
- cognitive metaspace, 70
  - metastate aggregates, 70
  - metastates, 70
- COM-estimator, 204
  - base-state recurrence, 205
  - modal mixing, 207
  - updated distribution, 208
- composite martingale, xviii
- conditional expectation, xvi, xvii
- conditional mean, *see* conditional expectation
- control, 1
  - dual control, 160
  - feedback, 1
  - feedforward, 5
  - gain scheduling, 158
  - LQ-regulator, 157
  - open-loop-optimal-feedback control, 161
  - regulation signal, 3
- corlol* (continuous on right, limits on left), xx
  
- data frame, 34
- data fusion
  - low-level, 35
  - track, 35
- discernibility matrix, 39
- discrete time state, xx
- Doob–Meyer Decomposition Theorem, xx
  
- endogenous actuating signal, 155
- environmental process, 2
- error covariance
  - conditional, 11
- estimation, 41
  - modal, 44
  - moment formulation, 47
- estimation problem, 3
- estimator
  - metastate probability, 59
- evasion, 83
- excess error, 13
- expectation, conditional, *see* conditional expectation
- eye chart, 211
  
- feather plot, 15
- filtration, xvi
  - left continuous, xvi
- finer  $\sigma$ -field, xvi
- FLIR, forward-looking infrared, 86
  
- gain scheduling, 158
- gamma probability density, 106
- Gaussian minimum shift keying, 209
- Gaussian wavelet distribution, 28
- generator (of a Markov process), xvii
  
- Hadamard product, xv
- hybrid system, 8
  
- IMM, 198
  - base-state estimator, 29
  - interacting-multiple-model filter, 28
  - mixing probability, 31
  - modal-state estimator, 30
- impact point, 187
- impact point prediction, 187

- information matrix, 29
- information state, 160
- infrared sensor, 86
- innovations process, xix, 44
  - base-state, 44
  - modal-state, 44
- intersymbol interference, 211
  
- JTS, 7, 10
- jump-translating-system, 7
  
- Kalman filter, 4, 11, 41
  - covariance form, 29
  - extended, 15
  - information filter, 29
  - time-continuous state, time-continuous measurement, 11
  - time-continuous state, time-discrete measurements, 12
  - time-continuous state, time-discrete measurements; endogenous actuating signal, 155
  - time-discrete state, time-discrete measurement, 25
  
- linear jump system, 7
- LJS, 7
- low-level data fusion, 35
- LQ-regulator, 157
  
- Markov process, xvii
  - generator, xvii
- martingale
  - composite, xviii
  - predictable compensator, xx
  - purely discontinuous, 10
- Martingale Representation Theorem, xx
- matrix
  - square root, xvi
- matrix square root, xvi
- mean-square-error, 3
- measurement
  - modal, 34, 35
- measurement residual, 10
- metastate, 2, 56, 58
- metastate aggregates, 68
- metastate probability estimator, 59
- metastates, 70
- modal estimation, 44
- modal observations, 34
- modal-state
  - innovations, 44
  - measurement error
    - nearest neighbor error, 90
    - projection error, 91
    - uniformly distributed errors, 90
- modal-state measurement, 34, 35
  - time-continuous
    - additive noise, 36
    - classifier, 40
  - time-discrete
    - additive noise, 36
    - classifier, 40
- modal-state model
  - time-continuous, 8
  - time-discrete, 23
- modal-state process, 5
- modal-state sensor, 43
- mode dependent measurements, 142, 144
- model
  - base-state
    - JTS, 10
    - time-discrete, 24
  - linear-Gauss–Markov, 4
  - modal-state
    - time-discrete, 23
  - plant, 1, 2
  - polymorphic, 6
  - system, 1
- moment
  - canonical, 48
  - PD-moment, 48
  - sequent, 48
- multiple model filter, 26
  - IMM, 28
  - path-length-one, 26
  
- NNE, nearest neighbor error, 90
  
- observation noise, xix
- observation process, xix
- observations
  - discrete time, xix
  - modal-state, 34
- open-loop-optimal-feedback control, 161
- optional cross quadratic variation, xviii
- optional quadratic variation, xviii
- order bias, 60
- output latency, 40
- output process, xix
  
- PD-moment, 48
- PE, projection error, 91
- perturbation variables, 3
- plant, 1
  - input, 2
  - model, 2
  - output, 2
  - state, 2
- plant linearization, 8
- plant model, 1
- plant state
  - measurement
    - mode dependence, 142
- plant state measurement
  - time-continuous, 4, 10
  - time-discrete, 10
- plant state process, 3
- PME
  - base-state rotation;  $\chi = 0$ , 119
  - continuous base-state, time-discrete measurements, 96
  - continuous base-state; time-discrete measurements, 174

- continuous plant state;  $\chi \neq 0$ , 135
- impact point prediction, 187
- LJS with control, 162
- mode dependence in the plant state sensor, 144
- plant state translation;  $\chi = 0$ , 127
- time-continuous plant; time-continuous measurement, 50
- time-continuous plant; time-discrete measurement, 54
- polymorphic estimator, 49
- polymorphic model, 6
- predictability, 63
- predictable compensator, xx, 46
- predictable quadratic variation, xvii
- predictor, 2
- probability space, xvi, 2
- process
  - adapted, xvi
  - Brownian motion, xvii
  - intensity, xvii
  - Gaussian white noise, xiv
  - increments, xvii
  - innovations, xix, 44
  - Markov, xvii
  - martingale, xvii
    - increments, xx
    - predictable compensator, xx
    - purely discontinuous, xviii
  - optional quadratic variation, xviii
  - predictable, xvi
  - predictable compensator, 46
  - predictable quadratic variation, xvii
  - renewal process, 106
  - semimartingale, 43
- progressive deepening, 70
- pseudonoise, 18
- purely discontinuous martingale, 10
- quadratic covariation, *see* coquadratic variation, 43
- quadratic variation
  - optional, xviii
  - optional cross, xviii
  - predictable, xvii
- random process, xvi
- random variable, xvi
  - Gaussian, xv
- recognition-primed decision making, 56
- regime, 3
- remotely piloted vehicle (RPB), 164
- renewal process, 106
- rotation (of base-state), 119
- sanguinity, 61
- semimartingale, 43
- sensor
  - base-state, 43
  - modal-state, 43
- separation principle, 158
- sequent moment, 48
- set point, 3
- $\sigma$ -field, xvi
- situation assessment, 56
  - uncertainty, 59
  - complexity, 58
  - anchoring, 63
  - complexity, 68
  - order-bias, 61
  - progressive deepening, 70
  - tempo, 58, 68
  - uncertainty, 71
- small-noise approximation, 54
- square root
  - matrix, xvi
- state
  - discrete time, xx
- stochastic differential equation, xiv
- subscripts, xv
- system model, 1
- tempo, 58
- track data fusion, 35
- UDE, uniformly distributed error, 90
- uncertainty, 59
- uncertainty matrix, 12, 29
- unimodal, 6
- unimorphic, 6
- unnormalized probability density, 22
- white-noise equivalent, 18
- zygostate, 5, 42