

## Index

- aging, 21
- application of Laplace transform
  - beam on a viscoelastic support, 197–199
  - correspondence principle
    - beams, 188
    - boundary value problems, 235
  - free oscillations of a mass, 229–230
  - mechanical analog
    - $N$  Maxwell elements in parallel, 45
    - three-parameter solid, 40
  - relating characteristic creep and stress relaxation times, 73–74
  - relating creep compliance and stress relaxation function, 71
  - solving for strain in terms of stress history; Problem 4.6, 84
  - Stieltjes convolution algebra, 305
  - three bar structure
    - cooling induced warping, 291
    - frozen-in forces, 283
  - three-dimensional constitutive equation, 163
- asymptotic behavior
  - beam on viscoelastic support, 198
  - relating material properties, 68, 69; Problems 4.12–4.19, 85–87
  - response to specific histories, 81, 82
- axial loads on structures, 172
- beam deflections under transverse loads
  - correspondence principle, 185, 189
  - delayed contact, 190
  - extrusion, 199
  - formulation of equations, 182
  - hard supports, 185
  - moment–deflection relation, 185
  - shear stresses, 184
  - traveling load, 202
  - viscoelastic support, 195
- bolt and tube example, 172
- boundary value problems, 232
- boundary conditions, 233–234
- correspondence principle
  - breakdown, 237
  - example: pressurized cylinder, 238
  - example: torsion of non-circular bars, 240
  - statement, 235–236
- direct solution method: circular shear, 243
- field equations, 233
  - in Cartesian coordinates, 308–309
  - in cylindrical coordinates, 308–309
- butadiene–styrene copolymers, 250
- cellulose acetate, 11
- characteristic times, general linear response
  - definitions, creep and stress relaxation times, 72–75
  - influence of temperature, 256
  - material and process times
    - influence on constant strain rate histories, 92, 99, 100
    - influence on constant stress rate histories, 108
    - influence on forced oscillations, 225–228
    - influence of temperature, 258
    - rapidly applied histories, 75–77, 80
    - slowly applied histories, 77–80
  - process times, 75, 77
  - relations, creep and stress relaxation times, 73, 74
- characteristic times, mechanical analogs
  - appearance in complex moduli, 126–130
- creep
  - Kelvin–Voigt model, 38
  - three-parameter solid, 44
  - relation between times, 44
  - stress relaxation
    - Maxwell model, 33
    - three-parameter solid, 43
- complex compliance
  - general linear material, 122
  - influence of temperature, 258
  - Kelvin–Voigt model, 127
  - low and high frequency limits, 133, 134
  - Maxwell model, 126
  - three-parameter solid, 129–130
- complex modulus
  - general linear material, 118, 119
  - general mechanical analog, 127
  - influence of temperature, 258
  - Kelvin–Voigt model, 127
  - low and high frequency limits, 130–132
  - Maxwell model, 126
  - three-parameter solid, 129
- constant strain rate histories, 88
- deformation
  - strain rate relative to process time, 92
  - stress–strain plot, 89, 92
- deformation and recovery, 92–97
  - influence of strain rate, 98, 99
  - properties of stress–time response, 94–96

## 314 INDEX

- constant strain rate histories (*cont.*)
  - repeated cycles, 100
  - stress-strain plot, 97
  - work done, 98–100
- limit case: step strain, 103–105
- limit case: step strain and recovery 100–103
- constant stress rate histories, 105
  - loading, 106
  - stress-strain plot, 107
  - loading and unloading, 106–109
  - properties of strain-time response, 106–108
  - stress-strain plots, 109
- constitutive equation, general linear material
  - continuity assumption, 57
  - creep form, 64, 65; Problem 3.1, 65
  - equivalent forms, 64–65
  - fading memory, 62, 63
  - linearity assumption, 58
  - non-aging assumption, 55
  - response function, step strain, 59
  - strain jump assumption, 56
  - stress relaxation form, 61, 64, 65
  - superposition of step strains, 58–60
  - superposition of strain pulses, 62, 63
- constitutive equation, influence of temperature
  - history, 268
- constitutive equation, mechanical analogs
  - differential form
    - Kelvin–Voigt model, 36
    - Maxwell model, 29
    - N Kelvin–Voigt elements in series, 50
    - N Maxwell elements in parallel, 47
    - three-parameter solid, 41
  - integral form, in terms of strain history
    - Kelvin–Voigt model, 39
    - Maxwell model, 34
    - N Maxwell elements in parallel, 49
    - three-parameter solid, 45
  - integral form, in terms of stress history
    - Kelvin–Voigt model, 39
    - Maxwell model, 35
    - N Maxwell elements in parallel, 50
    - three-parameter solid, 45
  - linear elastic solid, 1
  - linear viscous fluid, 3
- constitutive equation, three-dimensional response
  - isotropy, 150, 152, 153, 154, 155–157
  - Laplace transform, 163
  - linearity, 149
  - material properties, definition
    - bulk, 158
    - extension, 151
    - Poisson's ratio, 151
    - shear, 154
  - Poisson's ratio, extension and bulk relations
    - functions of frequency, 163
    - functions of time, 158
    - Laplace transform, 164
  - Poisson's ratio, extension and shear relations
    - functions of frequency, 164
    - functions of time, 156–157
    - Laplace transform, 164
  - shear response, 153
  - sinusoidal histories, 160
    - bulk complex compliance, 163
    - bulk complex modulus, 163
    - complex Poisson's ratio, 161–162
    - extensional complex compliance, 161
    - extensional complex modulus, 161
    - relations among properties, 162
    - shear complex compliance, 162
    - shear complex modulus, 162
    - strain amplitudes in terms of stress amplitudes, 162
    - strain in terms of stress history, 154
    - stress in terms of strain history, 160
    - summary of relations, 166–168
    - uniaxial extension, 150
      - transverse strains, 151
    - volumetric response, 158
      - special assumptions, 159–160
- correspondence principle
  - beams, 185, 189
  - boundary value problems, 234–236
  - breakdown, 277
  - example: pressurized cylinder, 238
  - example: torsion of non-circular bars, 240
- creep compliance
  - in terms of complex compliance, 138, 139, 140
  - Kelvin–Voigt model, 38
  - Maxwell model, 33
  - N Kelvin–Voigt elements in series, 50
  - N Maxwell elements in parallel, 49
  - three-parameter solid, 43
- creep response
  - Kelvin–Voigt model, 38
  - Maxwell model, 33
  - N Maxwell elements in parallel, 49
  - three-parameter solid, 43
- deviatoric stress components, 157
- differential operator algebra, 293–294
- dynamics of rigid bodies
  - forced oscillations
    - amplitudes, displacement, and force
      - elastic support, 224
      - general linear support, 221–224
      - spring-damper (Kelvin–Voigt) support, 225
      - three-parameter solid support, 225
    - equation of motion, 221
    - influence of stress relaxation on resonance, 224–228
  - free oscillations
    - equation of motion, 229
    - solutions
      - spring-damper (Kelvin–Voigt) support, 228–229
      - three-parameter solid, 229–230
  - properties of supports, 219–221
- experimental results, 10
  - butadiene–styrene copolymers, 250
  - cellulose acetate, 11
  - GR-S, 13
  - low density polyethylene, 15
  - oriented polypropylene, 20
  - PBAA solid rocket propellant, 14
  - polyethylene, influence of temperature, 260–262
  - polyisobutylene, 254

- polymethyl methacrylate, 13
- rayon laminate, 11
- $\tan \delta$  vs. frequency, 131
- fading memory, 62, 63
  - strain history example, 81
  - stress history example, 82
- fluid-like response, 7, 8, 9
  - complex moduli, low and high frequency limits, 131–133
  - creep compliance, 69
  - viscosity–stress relaxation function relation, 70
- Fourier integral theorem, Fourier transform, 135, 136
  - even functions, 136, 137
  - odd functions, 135, 138
- glass transition temperature, 255
- GR-S, 13
- initial (jump) conditions
  - Kelvin–Voigt model, 36, 37
  - Maxwell model, 30–32
  - $N$  Maxwell elements in parallel, 47
  - three-parameter solid, 41
- isochrones, 19, 20, 21, 22; Problem 1.2, 25; Problem 1.7, 27
  - creep, 19, 20, 22
  - stress relaxation, 22, 25
- isotropy, 150, 152, 153, 154, 155–157
- Kelvin–Voigt model, 35
  - arbitrary strain history, 39
  - arbitrary stress history, 39
  - characteristic creep time, 38
  - comments, 39
  - complex compliance, 127
  - complex modulus, 127
  - constitutive relation
    - differential form, 36
    - integral form in terms of strain history, 39
    - integral form in terms of stress history, 39
  - creep compliance, 38
  - creep response, 38–39
  - dynamics of a rigid body, 220, 225
  - initial (jump) conditions, 36–37
  - mechanical analog, 35
  - stress relaxation function, 38
  - stress relaxation response, 37, 38
- Laplace transforms
  - common functions, 295–296
  - convolution, 297
  - limit theorems, 297
  - transforms of derivatives, 296
- linear elastic response, 1
- linear viscous fluid response, 3
- linearity, three-dimensional stress states, 150
- linearity, uniaxial response, 17; Problem 1.1, 24
  - constitutive equation, arbitrary temperature histories, 268
  - general constitutive equation, 58
  - scaling, 17
  - superposition, 19
- loss modulus, 125
- low density polyethylene, 15
- material properties
  - connection diagram for properties, 140
  - properties for creep, 16
  - properties for sinusoidal oscillations, 16
    - complex compliance, 122
    - complex modulus, 118
  - properties for stress relaxation, 16
- three-dimensional response
  - bulk complex compliance, 163
  - bulk complex modulus, 163
  - bulk creep compliance, 158
  - bulk relaxation modulus, 158
  - complex Poisson's ratio, 161–162
  - extensional complex compliance, 161
  - extensional complex modulus, 161
  - extensional creep compliance, 151
  - extensional relaxation modulus, 151
  - Poisson's ratio as function of time, 151–152
  - Poisson's ratio, extension and bulk relations, 158, 163
  - Poisson's ratio, extension and shear relations, 156–157, 163
  - shear complex compliance, 162
  - shear complex modulus, 162
  - shear creep compliance, 154
  - shear relaxation modulus, 154
  - strain amplitudes in terms of stress amplitudes, 162
- Maxwell model, 28
  - arbitrary strain history, 34
  - arbitrary stress history, 34–35
  - characteristic stress relaxation time, 33
  - comments, 35
  - complex compliance, 126
  - complex modulus, 126
  - complex viscosity, 127
  - constitutive relation
    - differential form, 29
    - integral form in terms of strain history, 34
    - integral form in terms of stress history, 35
  - creep compliance, 34
  - creep response, 33
  - initial (jump) conditions, 30–32
  - mechanical analog, 29
  - stress relaxation function, 33
  - stress relaxation response, 32–33
- mean hydrostatic stress, 157
- mechanical analog
  - comments, 51
  - Kelvin–Voigt model, 35
  - linear elastic solid, 2
  - linear viscous fluid, 3, 4
  - Maxwell model, 29
  - $N$  Kelvin–Voigt elements in series, 50
  - $N$  Maxwell elements in parallel, 45
  - three-parameter solid, 40
  - viscoelastic response, 10
- microstructure, 6
- $N$  Kelvin–Voigt elements in series, 50
  - constitutive relation
    - differential form, 50
    - integral form in terms of strain history, 50

## 316 INDEX

- N Kelvin–Voigt elements in series (*cont.*)
  - integral form in terms of stress history, 50
  - creep compliance, 50
  - mechanical analog, 50
- N Maxwell elements in parallel, 45
  - arbitrary strain history, 49
  - arbitrary stress history, 50
  - comments, 50
  - constitutive relation
    - differential form, 47
    - integral form in terms of strain history, 49
    - integral form in terms of stress history, 50
  - creep compliance, 49
  - creep response, 49
  - initial (jump) conditions, 47
  - mechanical analog, 45
  - stress relaxation function, 48
  - stress relaxation response, 48
- oriented polypropylene, 20
- PBAA solid rocket propellant, 14
- Poisson's ratio
  - function of frequency, 161–162
  - function of time, 151
  - relation with bulk and extension properties
    - functions of frequency, 163
    - functions of time, 158–159
  - relation with shear and extension properties
    - functions of frequency, 163
    - functions of time, 156–157
- polyethylene, temperature increase during work, 260–262
- polyisobutylene, 254
- polymethyl methacrylate, 13, 251, 255
- polyvinyl acetate, 248
- principal directions of stress and strain, 164
- Prony series, 49
- pulses, 62
- pure bending, 176–182
  - moment–curvature relation, 182
  - moment–stress relation, 182
  - neutral axis, 178, 181
- rapidly applied histories, 75–77, 80
- rayon laminate, 11
- reduced time
  - calculation in examples, 267, 272–274, 277–278, 286–287
  - derivation, 262–266
  - intrinsic or pseudo-time, 266
- relation between creep and relaxation properties
  - frequency dependence, 124
  - Laplace transform, 71
  - time dependence, 67–72
- Riemann–Lebesgue Theorem, 132
- Riemann–Stieltjes integral, 61
- scaling, 17; Problem 1.2, 25
  - isochrones, 19–22
  - tests for scaling, 18–19
  - use in developing general linear constitutive equation, 59, 60
- shift function, 253
- polyisobutylene, 254
- polymethyl methacrylate, 255
- sinusoidal strain histories, 115
  - complex modulus, 118
    - low and high frequency limits, 131, 132
  - mechanical analogs, 125–130
  - complex viscosity, 125
  - dynamics of a rigid body, 223
  - stress history, 116, 117
  - three-dimensional response (*see* Constitutive equation, three-dimensional response)
- sinusoidal stress histories, qualitative features
  - linear elastic solid, 3
  - linear viscous fluid, 5
  - viscoelastic response, 9
- sinusoidal stress histories, 120
  - complex compliance, 122
    - low and high frequency limits, 125–130
  - mechanical analogs, 125–130
  - strain history, 121
  - three-dimensional response (*see* Constitutive equation, three-dimensional response)
- slowly applied histories, 77, 80
- solid-like response, 7, 8, 9, 68
  - complex moduli, low and high frequency limits, 132, 133
- spectra, relaxation and creep, 51, 52
- standard linear solid (*see* Three-parameter solid)
- step strain response
  - general linear material, 59
  - Kelvin–Voigt model, 37
  - linear elastic solid, 2–3
  - linear viscous fluid, 4–5
  - Maxwell model, 32
  - N Maxwell elements in parallel, 48
  - three-parameter solid, 42
  - viscoelastic response, 7
- step stress response
  - Kelvin–Voigt model, 38
  - linear elastic solid, 2–3
  - linear viscous fluid, 3–4
  - Maxwell model, 33
  - N Kelvin–Voigt elements in series, 50
  - N Maxwell elements in parallel, 49
  - three-parameter solid, 33
  - viscoelastic response, 7
- Stieltjes convolution, 305
  - algebra, 305–306
- storage modulus, 125
- stress relaxation function
  - general linear material, 59
  - in terms of complex modulus, 138, 139
  - Kelvin–Voigt model, 38
  - Maxwell model, 33
  - N Maxwell elements in parallel, 48
  - three-parameter solid, 42
  - time–temperature superposition, 251
- stress relaxation response
  - Kelvin–Voigt model, 37
  - Maxwell model, 32
  - N Maxwell elements in parallel, 48
  - three-parameter solid, 42, 43
- stress–strain plot
  - constant strain rate deformation, 89–92
  - and recovery, 97
  - constant stress rate load and unload, 109

- linear elastic response, 2
- linear viscous fluid, 5
- sinusoidal oscillations; Problem 6.16, 144
- step strain and recovery history, 102–103
- viscoelastic response, 9
- structural analysis
  - correspondence principle, 185, 189
  - direct methods
    - bolt and tube example, 172
    - delayed contact example, 190
    - extrusion example, 199
    - traveling load example, 202
    - viscoelastic support example, 195
  - dynamics of a rigid body, 219
- superposition, 19
  - two-step test, 20, 21, 24
- temperature effects
  - influence on characteristic stress relaxation time, 256
  - influence on complex compliance, 258
  - influence on complex modulus, 258
  - influence on creep compliance, 257
  - influence on stress relaxation, 248–250
  - polyethylene, work and temperature increase, 260–262
  - polymethyl methacrylate, 251
  - time–temperature superposition, 251
  - time-varying temperatures, 262
- thermal expansion function, 247
- thermal histories
  - constitutive equation for uniaxial response, 268
  - influence on stress relaxation, 262
- thermal strain, 247
- three bar structure examples, thermo-viscoelastic response
  - formulation, 269
  - frozen-in deformation, 271–276
  - frozen-in forces, 276–285
  - frozen-in warping, 285–292
- three-parameter solid, 40
  - arbitrary strain history, 44
  - arbitrary stress history, 45
- characteristic times
  - appearance in complex moduli, 129
  - creep, 44
  - relation between times, 44
  - stress relaxation, 43
- comments, 45
- complex compliance, 129, 130
- complex modulus, 129
- constitutive relation
  - differential form, 41
  - integral form in terms of strain history, 45
  - integral form in terms of stress history, 45
- creep compliance, 43
- creep response, 43–44
- initial (jump) conditions, 41
- mechanical analog, 40
- stress relaxation function, 42
- stress relaxation response, 42
- structural examples
  - bolt and tube example, 172
  - delayed contact example, 190
  - forced oscillations, 225
  - free oscillations, 229
  - three bar structure, 269–271, 271–272, 276, 278, 280, 284
  - traveling load example, 202
  - viscoelastic support example, 195
- time–temperature superposition
  - amorphous polymers, 253
  - definition, 251
  - experimental support, 253
- torsion of circular bars, 207–212
  - moment–angle of twist relation, 211
  - moment–stress relation, 212
  - sinusoidal oscillations, temperature increase in polyethylene, 260–262
- transformation of coordinate axes
  - strain transformation, 156
  - stress transformation, 156
- pt>
- viscoelastic response, qualitative features
  - creep, 7, 8
  - fluid-like response, 8, 9
  - solid-like response, 8, 9
  - stress relaxation, 9
- Volterra integral equation
  - bolt and tube example, 174
  - delayed contact example, 195
  - free oscillations, 229
- methods of solution
  - Laplace transform, 301
  - numerical methods, 302
  - successive approximations, 300
- relating creep compliance and stress relaxation function, 68
- three bar structure examples, 279, 282, 290–291
- viscoelastic support example, 197
- volumetric strain, 158
- WLF equation, 256
- work
  - general linear material
    - constant strain rate deformation and recovery, 98–100
  - general deformation history, 140–142; Problem 6.22, 147
  - influence of temperature, sinusoidal histories, 259
  - sinusoidal stress or strain histories, 124; Problem 6.5, 142
  - step strain and recovery, 102, 103
- linear elastic solid, 3
- linear viscous fluid, 5
- polyethylene, temperature increase during work, 260–262