

Index

- 2G, xv
- 3G, xxi
- 3GPP, 142, 201
- 4G, xv, 36
- 5G, xv, xxi, 36
- a-posteriori probability, 30
- a-posteriori probability decoder, 29
- acoustic communication, 649
- ad hoc networks, 647
- adaptive array, xix, 176
- adaptive modulation and coding, 228
- additive noise, 61
- additive white Gaussian noise, *see* AWGN
- affine transformation, 667
- Amitay, xx
- amplitude constraint, 86
- analog feedback, 248, 364, 365, 538
- analog-to-digital conversion, 66, 71, 380, 633
- angle diversity, 186
- angle spread, 147, 182, 183, 191, 203, 452, 492, 633
- antenna, 59, 72, 85
- antenna array, 136, 171, 173, 185, 302, 306, 380, 633, 634
- antenna correlation, 408, 461, 583, 628
 - base station, 629, 630, 635
 - beamforming, 310
 - capacity, 324, 334
 - channel estimation, 200, 347
 - channel normalization, 302
 - Kronecker model, 120, 180, 312, 330, 334, 340
 - link adaptation, 361
 - polarization diversity, 186
 - receiver, 336
 - steering vectors, 173
 - transmitter, 313, 315, 390, 394, 405, 409, 461, 492
 - users, 636
 - virtual channel model, 185, 188
- antenna height
 - base station, 140, 141, 143, 598
 - user, 140, 142, 143
- antenna pattern, 150, 151, 154, 173
- antenna tilt, 204, 628
- APP decoder, 29, 34
- array factor, 174
- array manifold, 173
- array response, 306
- array steering vector, 171, 191
- array topology, 173, 179, 191
- asymptotic eigenvalue distribution, 336, 675
- autocorrelation, 138, 154, 677
- autocovariance, 72, 677
- autoregressive process, 158, 167
- AWGN, 72
- AWGN channel, 212, 217, 220, 222, 245, 305, 360
- azimuth, 147, 151, 173, 182
- Bahl–Cocke–Jelinek–Raviv, *see* BCJR
- ban, 7
- bandwidth, 196, 329, 430, 647
 - bandlimited signal, 58
 - bandpass filter, 63
 - capacity, 22, 216, 219, 220, 226
 - Doppler spread, 200
 - FDMA, 421
 - frequency selectivity, 159, 160, 194
 - frequency-division multiplexing, 432
 - in-phase and quadrature signals, 59
 - latency, 36
 - noise power, 440
 - OFDM, 108, 109, 236, 428
 - sampling theorem, 64
 - SNR, 72, 74, 144
 - spectral efficiency, 211, 214
 - TDMA, 422
- bandwidth-limited regime, 217
- base station, 452, 466, 469, 527, 539, 547, 549–551, 557, 582, 585, 586, 598, 603, 605, 629, 631
 - antenna correlation, 191, 192
 - antenna gain, 144
 - antenna tilt, 628
 - channel estimation, 585, 586, 588
 - correlation matrices, 182, 628
 - energy, 73, 584, 633
 - form factor, 633
 - massive MIMO, 601, 632, 634, 635
 - power angle spectrum, 148
 - receiver, 182, 439, 459, 590, 593–595, 611, 614
 - transmit power, 143
 - transmitter, 182, 481, 487, 489, 490, 492, 619, 621
- Bayes’ theorem, 23, 27, 40, 41, 665
- BCJR algorithm, 29
- beam steering, 176

- beamforming, 174, 176, 306, 310, 311, 326, 327, 331, 367, 372, 380, 433, 440, 450, 557, 595, 629
- Bell Laboratories, xx
- Bell Labs layered space–time, *see* BLAST
- bell-shape Doppler spectrum, 155
- Bello, 166
- Bernoulli distribution, 7
- Bessel function, 151, 682
- bi-unitary invariance, 667, 669
- bias, 40, 43, 48, 114, 117, 119, 120
- BICM, 32, 38, 229, 355, 358, 361, 362, 418
- binary codeword, 25
- binary entropy function, 7
- binary phase-shift keying, *see* BPSK
- bit, 6, 22
- bit error probability, 30
- bit rate, 22, 211, 221, 428
- bit-interleaved coded modulation, *see* BICM
- BLAST, 354
- blind channel estimation, 619
- block error probability, 21
- block fading, 158, 167, 168, 197, 274, 341–344, 346, 531, 583
- block Toeplitz matrix, 80, 91
- block-diagonal, 440, 446, 492, 501
- block-diagonalization, 508, 558, 574, 635
- Boltzmann, 7
- BPSK
- MMSE, 43, 45
 - mutual information, 14, 15
 - signal, 5, 6, 35, 38, 43, 70
 - spectral efficiency, 33, 227, 260, 261, 330
- branch-and-bound, 572
- broadcast channel, 417, 418
- broadside, 173
- building height, 143
- building penetration losses, 138
- building-to-building distance, 143
- byte, 7
- cable losses, 138
- calibration, 244, 248, 365, 490, 634
- canonical channel, 178
- capacity
- AWGN channel, 222, 229
 - codeword length, 36
 - CSI, 246, 305
 - ergodic, 258, 271, 309, 316
 - fading channel, 260, 263, 309, 322, 324
 - frequency-selective channel, 232, 239, 240
 - interference, 282, 348
 - number of codewords, 351
 - outage, 253
 - per-symbol vs per-bit, 217
 - Shannon, 3, 21, 25, 253, 419
 - spectral efficiency, 212, 213
 - capacity boundary, 419, 424, 429, 435, 442, 443, 445, 464, 472, 475, 482, 483, 486, 490, 492
 - capacity per unit cost, 212
 - capacity region, 419
 - capacity-effective SNR mapping, *see* CESM method
 - carrier frequency, 58–60, 140, 142, 154, 156, 170, 380, 633
 - causal MMSE, 51
 - causality, 76, 79
 - CDF, 666
 - CDMA, xx, 300, 343, 422
 - cell-free, 647
 - cell-less, 647
 - central limit theorem, 137, 145, 146, 668, 673, 676
 - centroid, 370
 - CESM method, 243, 245, 270, 360, 362
 - chain rule
 - differential entropy, 10
 - entropy, 8
 - mutual information, 17, 268, 275, 353, 534
 - channel capacity, 222
 - channel diagonalization, 305, 307, 308, 326, 361, 362, 449, 450, 461, 521
 - channel dispersion, 109
 - channel estimation, 111–113, 117, 121, 123, 195, 275, 364, 410, 532, 534, 583, 585, 628, 630
 - channel hardening, 336, 583, 593, 619, 622, 631
 - channel inversion power control, 251
 - channel law, 18, 19, 22, 31, 38, 39, 222, 252, 357
 - channel order, 76, 79
 - channel-state information, *see* CSI
 - channel-state information at the receiver, *see* CSIR
 - channel-state information at the transmitter, *see* CSIT
 - Chase combining, 37
 - Chernoff bound, 682
 - chi distribution, 672
 - chi-square distribution, 313, 322, 393, 504, 521, 524, 671
 - chip period, 107, 108
 - Cioffi, xx
 - circuit power consumption, 266, 380, 633
 - circulant matrix, 239, 659
 - circular array, 173
 - circular convolution, 98–100, 105, 106, 655
 - circular polarization, 186
 - circular symmetry, 667, 669
 - Clarke, 148, 151, 153, 155, 182, 191, 198, 201, 273, 277, 279, 344
 - clipped Gaussian distribution, 87
 - clipping, 87
 - cloud, 647
 - code-division multiple access, *see* CDMA
 - codebook, 18, 25, 38, 74, 366, 442, 471, 475
 - coded bit, 25
 - coded modulation, 25
 - coded modulation library, 229

- codeword, 17, 69, 76, 104, 446
 - BICM, 30, 355, 358
 - complex Gaussian, 405
 - dirty-paper coding, 474, 482
 - error probability, 20
 - latency, 36
 - layered architecture, 355
 - length, 35, 211
 - memoryless channel, 19
 - MIMO, 38
 - minimum-distance decoding, 24
 - OFDM, 243
 - power constraint, 81, 85
 - random coding, 25
 - single vs multiple, 350, 351, 389, 447, 501
- coding rate, 25, 355, 420
- coherence bandwidth, 160, 168, 169, 196, 197, 267, 269, 271, 275, 281, 282, 343, 344, 367, 463, 541
- coherence distance, 151, 173, 176, 196
- coherence time, 153, 157, 634
 - block fading, 168, 196, 282, 343, 344, 463, 541
 - feedback, 248, 365, 367
 - OFDM, 236, 269
 - pilot overhead, 281, 535
 - power control, 516
 - precoding, 516, 574
- collaborative upper bound, 454, 469, 484, 492
- column rank, 90, 658
- column space, 657, 661
- complex baseband equivalent, 59, 77
- complex baseband equivalent channel, 62
- complex envelope, 59
- complex Gaussian
 - differential entropy, 10
 - dirty-paper coding, 475
 - distribution, 668
 - interference, 282
 - ML estimation, 113
 - MMSE estimation, 41
 - signal distribution, 4, 13, 84, 223, 282, 308, 313, 343, 394, 405, 442, 475
 - Wishart distribution, 670
- complex Gaussian matrix, 669
- complex Gaussian vector, 669
- complex pseudo-baseband equivalent, 63, 77, 144
- complexity, 36, 99, 100, 104, 109, 211, 321, 332, 351, 358, 364, 389, 574, 618, 633
- compressed sensing, 123
- concave function, 685, 688
 - capacity, 219, 226
 - mutual information, 241, 308
 - power allocation, 523
 - power control, 515
 - precoding, 449, 469, 479, 480, 515
 - spectral efficiency, 265, 277, 279, 344
 - xESM methods, 244
- conditional Gaussian distribution, 670
- conditional-mean estimator, 40, 41, 44, 50, 276, 277
- confidence interval, 598, 612
- conjugate beamforming, 620
- constant envelope, 86
- constellation-constrained capacity, 226
- constrained capacity, 226
- contours of constant weighted sum spectral efficiency, 424
- convergence
 - almost surely, 250, 259, 265, 310, 336, 408, 674
 - in distribution, 406, 673
 - in probability, 113, 673
 - mean-square sense, 674
- convex function, 49, 265, 279, 284, 685, 688
- convex hull, 478, 479
- convex optimization, 685
 - BC power allocation, 523, 563, 574
 - dual-MAC precoding, 466, 480, 487, 526, 561
 - MAC power control, 517
 - MAC precoding, 445, 449, 460, 464
 - pilot overhead, 541, 555
 - single-user power allocation, 318
 - single-user precoding, 316
 - waterfilling, 237
- convex relaxation, 572
- convex set, 478, 685
- convolution, 62, 65, 66, 77, 89, 98–100, 105, 106, 160, 231, 655
- convolution matrix, 77, 231
- cooperation, 632, 647
- Cooperation in Science and Technology, *see* COST
- coordination, 629
- coprimeness, 90
- corner point, 443, 444, 447, 448, 452, 456, 457, 472
- correlation, 368, 666
- correlation coefficient, 666
- correlation distance, 138
- correlation matrix, 120, 180, 334, 461, 629, 630, 666
- COST-231, 201
 - Hata, 141
 - Walfisch–Ikegami, 142
- COST-273, 201
- Costa, 475
- covariance matrix, 666
- crest factor, 86
- cross-polar discrimination, 185, 186, 339
- CSI, 81, 85, 247, 263, 305, 321, 340, 389, 462, 463, 490, 531, 543, 550, 581, 585, 599
- CSIR, 247, 248
 - BC with CSIT, 471, 521, 557
 - duality, 305, 466, 467, 471, 517
 - MAC with CSIT, 442, 444, 448
 - MAC without CSIT, 462, 463
 - pilot-assisted, 273, 275, 279, 283
 - SDMA, 452

- side information, 267, 268, 270, 490
- single-user with CSIT, 247, 305, 431
- single-user without CSIT, 252, 260, 279, 321, 389, 390, 431
- CSIT, 248
 - BC, 471, 485, 491, 492, 523, 531, 554, 557, 574, 621
 - duality, 305, 466, 467, 469, 471, 517, 521
 - MAC, 442, 444, 513
 - single-user, 247, 305, 311, 321, 364, 389, 431
- cubic metric, 86
- cumulative distribution function, *see* CDF
- cyclic permutation, 662
- cyclic prefix, 77, 98–100, 102, 104, 105, 107, 110, 116, 162, 168, 171, 233, 235, 236, 239, 269, 287
- cyclostationarity, 158
- D-BLAST, 355
- data stream, 81
- decimation, 197
- decision region, 23
- decoder, 18, 23, 31, 35, 38, 84, 472
- decoding order, 353, 446–448, 454, 466, 479
- decorrelator, 390, 503
- degradedness, 477
- degrees of freedom, *see* DOF
- delay, 63, 64, 66, 76, 88, 91, 93, 95, 171, 193, 365
- delay spread, 164, 166, 170, 203, 236, 269, 272, 441, 628
- delay-limited capacity, 249
- delta function, 63, 145, 147, 155, 160, 163, 335, 653, 677
- demodulation, 24, 26, 66
- determinant, 662
- deterministic equivalent, 335
- device-to-device, 204, 647
- DFT, 98, 100, 102, 104, 107, 234, 239, 655
- diagonal BLAST, *see* D-BLAST
- differential entropy, 9, 11, 442
- diffraction, 134, 144
- digamma function, 312, 670, 681
- digital feedback, 248, 364, 366
- digital subscriber lines, 649
- digital-to-analog conversion, 66, 71, 380, 633
- dimensional overloading, 321, 327, 333, 423, 444, 452
- Dirac delta function, *see* delta function
- direction of arrival, xix
- direction of departure, xix
- dirty-paper coding, *see* DPC
- discrete constellations, 4
 - BICM, 30, 358
 - coded modulation, 25
 - entropy, 8
 - extended constellation, 472
 - link adaptation, 228, 263
 - MMSE estimation, 43
 - mutual information, 15, 396
 - precoding, 307, 309, 325, 445, 448, 450, 462, 482
 - signal-space coding, 25
 - spatial modulation, 379
- discrete Fourier transform, *see* DFT, 185, 191, 655
- discrete-time Fourier transform, 239, 655
- dispersive channel, 61, 66, 67, 70, 160
- diversity, xix, 81, 173, 183, 186, 255, 313, 315, 398, 634
- diversity–multiplexing tradeoff, *see* DMT
- DMT, 255, 315, 355, 398, 407
- DOF
 - BC, 484, 487, 489–491, 529, 538, 549, 554
 - MAC, 451, 452, 457, 459, 462–464, 508, 516
 - multiuser, 433, 492, 519, 583
 - single-user, 221, 266, 280, 307, 311, 313, 315, 332, 333, 342, 347, 350, 398, 406
- Doppler spectrum, 153, 158, 168, 197, 198, 200, 246, 267, 269, 275, 277, 279, 343, 344, 346
- Doppler-delay spreading function, 167
- downconversion, 59, 61, 63, 75, 77
- DPC, 475–477, 480, 482, 490, 493
- drop, 201, 598
- duality, 305, 417, 464, 471, 472, 479–482, 485, 486, 490, 517, 521, 526, 561, 567, 621, 636
- duplexing, 490, 531, 550, 582, 583, 634
- dynamic programming, 250
- EESM method, 243, 245, 270, 360, 362
- eigenfunction, 184
- eigenvalue, 47, 403, 659, 660, 662, 675, 676
 - channel, 305, 306, 308, 309, 323, 337, 468
 - correlation, 184, 325–327, 330, 331, 394, 492
 - LOS component, 317
 - precoded channel, 335, 340, 361, 393, 559
 - precoder, 376
- eigenvalue decomposition, 184, 317, 659, 660
- eigenvector, 184, 189, 306, 309, 315, 317, 320, 326, 327, 376, 393, 394, 403, 492, 659, 660
- electrically-steerable parasitic array radiator, *see* ESPAR
- elevation, 147, 151, 173, 204
- empirical eigenvalue distribution, 335, 337, 340
- encoder, 17, 25, 38, 84, 472
- encoding order, 466, 474, 477, 478, 480
- endfire, 173, 182, 185
- energy, 73
- energy per bit, 212, 218, 226, 227, 251, 261, 265, 310, 326, 330, 342, 350, 397
- energy per symbol, 74, 85, 282, 439
- entropy, 7, 9
- entropy rate, 10
- equal spectral efficiencies, 426
- equalization, 70, 88, 161, 241
- equalizer, 240
- ergodic capacity, 259–261, 263, 270, 271, 284, 309, 316, 322, 337, 339, 348, 360, 362, 457, 460

- ergodic setting, 247, 249, 258, 271, 309, 316, 439, 456, 460, 486
 ergodicity, 21, 72, 85, 123, 155, 677
 error function, 683
 error probability, 20, 22, 35, 360, 361, 418
 ESPAR, 380
 estimation, 113
 estimation bias, 40, 117, 120
 estimation theory, 39
 Euclidean distance, 662
 Euclidean norm, 662
 Euler, 59
 Euler–Mascheroni constant, 262, 280, 681
 excess antennas, 584, 589, 599, 612, 627, 633
 excess bandwidth, 22, 70, 74, 75, 108, 109, 287
 excess kurtosis, 668
 expectation, 666
 exponential correlation model, 183
 exponential distribution, 10, 146, 393, 504, 522, 672
 exponential integral, 251, 259, 260, 263, 322, 323, 681
 exponential-effective SNR mapping, *see* EESM method
 extended constellation, 473
 extrinsic information, 27, 34
 factorial function, 680
 fading, 144
 fairness, 424, 426–429, 444, 508
 Fano, 237
 far field, 61, 139, 172
 fast-Fourier transform, *see* FFT, 655
 favorable propagation, 584, 635
 FDD, xxiv, 246, 248, 365, 490, 538, 549, 582, 583, 634
 FDMA, 421, 424, 431, 451, 452
 feedback, 532
 feedback symbols, 490, 491, 549, 557
 FFT, 98, 100, 105, 110, 235, 655
 filtered noise, 391, 592
 filtering, 51
 finite impulse response, *see* FIR
 finite-length coding, 36, 243, 351, 360, 418
 FIR, 76, 79, 88, 93, 95, 99
 forward link, 182, 191, 417, 465, 582, 583, 618, 621, 630, 631
 forward–reverse SNR ratio, 544, 582, 584
 Foschini, xx, 300, 354, 355
 Fourier, 653
 Fourier codebooks, 373
 Fourier matrix, 100, 185, 189, 375, 659
 Fourier transform, 58, 59, 62, 63, 98, 154–156, 166, 168, 187, 653, 677
 fractional power control, 599, 609, 612, 622
 fractional reuse, 603
 frame error probability, 21
 free probability, 676
 free space, 139
 frequency band, 421, 428
 frequency correlation, 159
 frequency offset, 109
 frequency selectivity, 159
 frequency-division, 421, 424, 433, 451, 452
 frequency-division duplexing, *see* FDD
 frequency-division multiple access, *see* FDMA
 frequency-domain equalization, 98
 frequency-flat channel, 76, 79, 97, 107, 110, 115, 118, 172
 frequency-flat fading, 159
 BC, 470
 channel estimation, 197, 199, 274
 MAC, 439
 single-user, 246, 248, 253, 263, 264, 277, 313, 341, 343, 346, 362, 389, 390
 frequency-selective channel, 76, 79, 230
 frequency-selective fading, 160, 190, 269, 271, 360, 389
 Friis, 139
 Frobenius norm, 79, 662
 front-end, 72, 73, 77
 full duplexing, xxiv, 246, 248, 364, 490, 550, 634
 full-dimension MIMO, 636
 full-rank, 92, 98, 113, 190, 305, 307, 311, 331, 376, 452, 484, 485, 658, 660
 Gallager, 25
 game theory, 572
 gamma distribution, 405
 gamma function, 146, 260, 286, 314, 369, 670, 672, 680, 681
 Gans, xx
 Gauss, 40
 Gauss–Markov, 158, 167, 274
 Gaussian, 223, 240, 282, 668
 Gaussian channel, 212, 217, 220, 222
 Gaussian noise, *see* noise
 Gaussian random process, 676, 677
 generalized decision-feedback equalizer, 353
 generalized proportional fairness, 427
 generalized spatial modulation, 380
 geometric programming, 517, 574
 Girko, 675
 Gold codes, 115
 Golden, 354
 gradient, 46, 49, 92, 678
 Grassmann manifold, 368, 370
 Grassmannian codebook, 371, 376
 Grassmannian packing, 369
 Gray mapping, 8, 28, 32, 34, 357
 gross spectral efficiency, 593, 595, 609, 614, 616, 626
 group detection, 360
 GSM, xv, 161
 Hadamard product, 185
 hallway, 189

- Hankel matrix, 112, 115, 659
 hard decision, 24
 hardware, 633
 Hata, 140
 Hermitian matrix, 658, 660, 663, 675
 hexagonal network, 586, 598, 603, 605, 612, 623
 high-SNR regime, 217
 capacity, 220, 225, 240, 306, 311, 331, 337, 342, 440, 451, 454, 461, 482, 484, 487
 MMSE, 43
 mutual information, 13, 14, 16
 spectral efficiency, 240, 280, 281, 286, 346, 396, 406, 433, 484, 528, 543, 562, 563, 581
 Householder codebook, 376
 Householder matrix, 376
 hybrid precoding, 380, 633
 hybrid-ARQ, 37, 271, 273, 289, 361, 364
 hypergeometric function
 Gauss, 638, 683
 Kummer confluent, 639, 683
 hyperplane, 421, 425, 444, 447
 I-MMSE relationship, 45, 241, 308, 450
 IDFT, 100, 102, 104, 107, 234, 655
 IEEE 802.11ac, xxi
 IEEE 802.11ad, xxi, 204
 IEEE 802.11ax, xxi
 IEEE 802.11ay, xxi, 204
 IEEE 802.11n, xxi
 IEEE 802.16, xxi, 201
 IIR, 88
 ill-conditioned, 393
 impulse response, 62, 108
 in-phase, 4, 5, 31, 32, 43, 59
 incomplete gamma function, 260, 286, 314, 680
 incremental redundancy, 37
 independence, 533
 additive impairments, 632
 channel entries, 120, 184, 188, 189, 200, 321, 407, 508, 675
 channel matrices, 189
 coded bits, 27, 38
 codeword symbols, 19, 22, 30, 73, 264, 341, 342, 475
 fading, 285, 289, 336
 fading blocks, 159
 interference, 283
 MMSE estimation, 532, 585, 592, 597
 multipath components, 145, 150
 noise, 78, 539
 pilot and data symbols, 275
 precoders, 522, 540, 626
 random variables, 8, 10, 12, 137, 666, 669, 674
 ray delays, 164
 real and imaginary parts, 5, 32
 reverse and forward fading, 248
 signal and noise, 13, 16, 44, 45, 222
 signal streams, 240, 300, 305
 signals, 463, 470, 511
 subcarrier fading, 270
 WSSUS, 166
 indicator function, 675
 indoor environment, 143, 147, 149, 163, 164, 166, 170, 189
 infinite impulse response, *see* IIR
 infinite-PSK, 5, 13
 infinite-QAM, 5, 14
 information, 6, 11, 18, 21
 information density, 35
 information divergence, 11, 12
 information stability, 21, 231, 255, 271, 273
 INR, 286, 348
 intercarrier interference, 171
 intercept, 139, 142
 interference, 519, 611
 colored, 410
 data upon pilot symbols, 590
 multiantenna, 88, 93, 94, 328, 585
 other-beam, 492
 other-cell, 418, 592, 599, 602, 605, 606, 619, 625, 628, 631
 other-stream, 406, 409, 491, 512
 other-user, 71, 282, 347, 431, 433, 446–449, 453, 474–476, 480, 511, 595, 602, 625, 631
 pilot contamination, 586
 interference alignment, 648
 interference-to-noise ratio, *see* INR
 interleaving, 25, 30, 32, 34
 interpolation, 51, 123
 intersymbol interference, *see* ISI
 intrinsic information, 27
 inverse discrete Fourier transform, *see* IDFT
 Iospan Wireless, xx
 irregular pilot sequences, 589
 ISI, 66, 69, 70, 88, 107, 160, 171, 241, 353, 472
 isotropic matrix, 341
 isotropic signaling, 82
 isotropic vector, 265, 341
 iterative decoding, 27, 35
 iterative waterfilling, 449, 450, 457, 480
 Jakes, 148, 151, 153, 155, 182, 191, 198, 201, 273, 277, 279, 344
 Jensen's inequality, 260, 268, 284, 313, 321, 331, 537, 538, 688
 joint spatial division and multiplexing, 557
 k-means clustering, 370
 Kailath, xx
 Kalman filter, 51
 Karhunen–Loève expansion, 184
 Karush–Kuhn–Tucker conditions, *see* KKT conditions
 Kerdock codebooks, 375
 keyhole channel, 189, 317
 KKT conditions, 686

- Kronecker model, 120, 180, 184, 187, 309, 312, 315, 317, 330, 334–336, 340, 409, 461
 Kronecker product, 112, 114, 181, 663
 Kullback–Leibler divergence, 11, 12
 kurtosis, 86, 261, 265, 310, 327, 328, 667
 L-value, 26, 29, 34, 357, 358, 360, 361
 Lagrange multipliers, 235, 240, 484, 687
 Lagrangian, 237, 483, 527, 570
 Landau symbols, 13, 217, 684
 Laplace transform, 675
 Laplacian, 149, 183, 192, 193
 large city, 141
 large-dimensional regime, 300, 320, 335, 340, 349, 407, 419, 462, 493, 581, 585, 611, 675
 large-scale channel gain, 138, 145, 150, 173, 186, 195, 212, 429, 439, 539
 large-scale phenomena, 135, 177, 195, 302
 latency, 25, 34, 36, 429, 434, 508
 law of large numbers, 276, 336, 585, 673, 674
 layered architecture, xx, 354
 LDPC code, 25, 30, 36
 least mean-squares, 117
 least-squares error, 114
 least-squares estimation, 114, 122
 left singular vector, 661
 left unitary invariance, 370, 667
 Legendre, 40
 likelihood function, 24, 27, 39, 113
 likelihood ratio, 26, 29
 limited feedback, 364, 366
 Linde–Buzo–Gray algorithm, 370
 line-of-sight, 134, 143, 146, 155, 172, 174, 176, 179, 202, 635
 linear array, 173, 176
 linear convolution, 62, 65, 66, 77, 89, 98, 99, 106, 160, 231, 655
 linear estimation, 42
 linear estimator, 48
 linear minimum mean-square error, *see* LMMSE
 linear polarization, 186
 link adaptation, 26, 243, 245, 248, 270, 271, 306, 308, 355, 360, 370, 410, 420
 link budget, 138
 list sphere decoder, 357
 Lloyd algorithm, 370
 LMMSE
 BC, 482
 channel estimation, 196
 dual-MAC, 464, 466
 equalization, 94, 390
 estimation, 48, 49
 MAC, 446–448, 453, 456
 single-user receiver, 352–355, 358, 362, 389, 398, 400, 402, 404–407, 409
 local neighborhood, 135
 local oscillator, 59, 75, 108
 local stationarity, 135
 log-likelihood ratio, 26, 27, 29
 log-normal, 137, 143
 long-term evolution, *see* LTE
 low-density parity check code, *see* LDPC code
 low-noise amplifier, 93
 low-SNR regime, 217
 capacity, 217, 225, 240, 260, 306, 309, 326, 337, 341, 431, 461
 MMSE, 43, 46
 mutual information, 13–16
 spectral efficiency, 240, 278, 281, 285, 346, 396, 406, 431, 433
 low-SNR slope, 218, 226, 261, 265, 309, 326, 342, 406, 432, 433
 lower incomplete gamma function, 680
 lowpass filter, 60, 63, 64, 69
 LTE, xv, xxi, 36, 109, 161, 228, 229, 236, 244, 248, 272, 273, 278, 360, 362, 375, 376, 428, 599, 636
 machine learning, 204, 628
 macrocell, 140, 142, 166, 201
 magnitude constraint, 86, 115
 Marconi, xix
 Marzetta, 583, 602
 Marčenko–Pastur, 338, 408, 675
 Massey, xxii
 massive MIMO, xxi, 123, 136, 173, 177, 196, 341, 343, 389, 419, 462, 490, 502, 510, 551, 581, 583
 matched filter, 176, 389, 399, 502, 511, 565, 582, 583, 585, 595, 620
 matrix inversion lemma, 50, 399, 400, 511, 567, 663
 max-log approximation, 357
 maximum a-posteriori, 23, 30
 maximum a-posteriori estimation, 39, 42
 maximum-eigenvalue eigenvector, 306, 309, 326, 327, 367, 393, 403, 492
 maximum likelihood, 23, 113, 358
 maximum-likelihood estimation, 40, 42, 113, 358
 maximum-ratio combining, 310, 595
 maximum-ratio transmission, 310, 565, 620
 MCS, 228, 245, 271, 360, 362
 mean doubly regular, 339
 media-based communication, 380
 memoryless channel, 19, 21, 24, 27, 30, 31, 38, 66, 222, 231, 233, 247, 252, 264
 mercury/waterfilling, 241, 251, 308, 523
 message, 23, 25, 34
 microcell, 142, 192, 201
 MIESM method, 243, 245, 270, 360, 362
 millimeter wave, 204, 380, 633, 647
 minimum distance, 5, 16
 minimum-distance decoding, 24, 276, 278, 283, 535
 minimum energy per bit, 218, 226, 227, 251, 261, 265, 309, 326, 330, 341, 342, 350, 397, 406, 433
 minimum mean-square error, *see* MMSE
 minimum-norm equalizer, 92, 97

- minimum spectral efficiency, 426
- MISO, 310, 314, 369, 480, 481
- mixing matrix, 82–84
- MMSE, 40, 45, 48, 94, 117, 122, 197, 200, 240, 276, 305, 318, 344, 353, 398, 532, 573, 582, 611, 630
- MMSE beamformer, 569
- MMSE matrix, 44, 46, 49, 118, 318, 399, 630
- modified Bessel function, 146, 189, 192, 682
- modulation, 25, 66
- modulation and coding scheme, *see* MCS
- modulo operation, 655
- Monte-Carlo, 248, 311, 324, 334, 395, 405, 598, 611, 612, 626, 638
- Moore–Penrose pseudoinverse, 92, 94, 391, 503, 521, 565, 663
- MU-MISO, 423, 490, 517, 520, 521, 523, 524, 624
- MU-SIMO, 423, 441, 502, 504, 505, 517, 593
- MU-SISO, 423
- multicarrier, 98, 105, 108, 168, 171
- multicell, 586, 619, 621, 629
- multidimensional symbol mapping, 35
- multipath, 61, 380
 - fading, 145, 154
 - propagation, 144
- multiple codewords, 358
- multiple-access channel, 353, 417, 418, 431, 439, 464, 501, 517
- multiple-input single-output, *see* MISO
- multiplexing gain, 255, 315, 398, 460
- multiplicative noise, 246, 632
- multitone, 105
- multiuser detection, xx, 300, 409
- multiuser diversity, 429, 439
- multiuser eigenmode transmission, 562
- multiuser MISO, *see* MU-MISO
- multiuser SIMO, *see* MU-SIMO
- multiuser SISO, *see* MU-SISO
- multivariate impulse response, 78
- mutual coupling, 302, 380, 633
- mutual information, 12, 25, 313, 343, 348, 351, 442, 460, 534
 - BICM, 31, 35
 - BPSK, 14
 - complex Gaussian signal, 13, 282
 - discrete constellations, 15, 16, 226, 229, 308, 325, 450
 - Gaussian noise, 13, 282
 - I-MMSE relationship, 45
 - infinite PSK, 13
 - infinite QAM, 14
 - information stability, 21
 - large-dimensional regime, 315
 - link adaptation, 361
 - nonsingle-letter formulation, 231, 232
 - precoding, 84, 304
 - QPSK, 15
 - single-letter formulation, 222
- mutual-information-effective SNR mapping, *see* MIESM method
- mutually unbiased bases, 375
- Nakagami fading, 146, 178, 260, 263, 429
- narrowband, 58, 159
- nat, 7
- near–far effect, 448
- nearest-neighbor decoding, 24, 276, 278, 283
- new radio, *see* NR
- noise, 13, 71, 75, 80, 300, 328, 341, 342, 348, 350, 397, 405, 410, 421, 422, 431, 440, 442, 446
 - bandwidth, 72, 74
 - BICM, 31, 33
 - channel law, 19, 20
 - enhancement, 102, 398, 525, 632
 - equalization, 93, 94, 100, 104
 - estimation, 40
 - figure, 72, 73, 547
 - filtered, 390, 391, 592
 - Gaussian, 71, 276, 282, 308, 668
 - I-MMSE relationship, 45, 46
 - log-likelihood ratio, 29
 - ML decoding, 24
 - MMSE estimation, 39, 41, 43, 50, 120, 588
 - OFDM, 107
 - power, 144, 398, 466, 473, 475, 491, 589
 - spectral density, 72
- NOMA, 423
 - noncausal MMSE, 51, 123
 - non-line-of-sight, 134, 143
 - nonmemoryless, 264, 341
 - non-orthogonal multiple access, *see* NOMA
 - nonregular fading, 11, 157, 266
 - nonregular random process, 11, 51
 - nonsingle-letter formulation, 20, 21, 231, 264, 341
 - nonsquare QAM, 5
 - nonuniform linear array, 173
- normalization
 - antenna pattern, 173
 - capacity, 335
 - channel, 75, 79, 139, 145, 177, 179, 185, 230, 300, 302, 439
 - power angle spectrum, 147, 149
 - power delay profile, 163, 164
 - precoder, 81, 467, 470, 479, 567
 - receiver, 517
 - signal, 341
 - SNR, 212
- NR, xv, 36, 109, 230, 236, 273, 278, 428, 599
- null space, 181, 558, 657, 658, 661
- Nyquist, 69
- Nyquist criterion, 69, 70, 72
- OFDM, 20, 37, 70, 79, 104, 269, 390, 422, 441, 655
 - channel estimation, 121, 199
 - chip, 107

- cyclic prefix, 233
- equalization, 107, 241
- link adaptation, 361
- LTE, 161, 236
- multicarrier, 105, 171
- multitone, 105, 171
- peakedness, 87
- power constraint, 85, 620
- resource element, 110, 168, 171, 196, 197, 200, 211, 212, 222, 246, 271, 282, 428, 583, 589
- symbol, 107, 109, 110, 121, 234–236, 239, 240, 243, 244, 270, 287, 428, 589
- symbol period, 107
- xESM methods, 361, 362
- OFDMA, 422, 423
- Okumura–Hata, 140
- on–off keying, 6, 264
- one-ring model, 191
- one-shot BICM, 29, 34, 38, 357
- one-step prediction error, 158
- opportunistic transmissions, 429
- orthogonal frequency-division multiple access, *see* OFDMA
- orthogonal frequency-division multiplexing, *see* OFDM
- orthogonality principle, 40, 49, 55
- outage, 253, 439
- outage capacity, 254, 273, 313, 355, 460
- outage probability, 253, 273, 313, 460
- output SINR, 400, 512, 596, 611, 626
- output SNR, 392, 504
- over-the-air calibration, 365
- oversampling, 72
- PAM signal, 472
- PAPR, 86, 109, 223
- parallel interference cancelation, 618
- parallel subchannels, 234, 240, 305, 309, 469, 521, 559
- parasitic antenna arrays, 380
- PARC, 353, 362
- passband, 58
- pathloss, 137, 195, 203, 212, 380, 598, 603, 605, 612, 623
- pathloss exponent, 139, 142, 638
- pathloss intercept, 139, 142
- pattern diversity, 186
- Paulraj, xx
- PDF, 665
- peak-to-average power ratio, *see* PAPR
- peakedness, 5, 86, 264, 281, 342
- pedestrian setting, 153, 163, 170, 278, 279, 344, 345, 541, 542, 548, 549, 555, 582, 616, 627
- pentagonal region, 443, 445, 450, 476
- per-antenna rate control, *see* PARC
- perfect reconstruction, 90
- phase, 59
- phase invariance, 368
- phase noise, 61, 71, 109, 632
- phased array, xix, 176
- picocell, 143, 147, 201
- pilot clustering, 603
- pilot contamination, 586, 590, 603, 611, 613, 614, 621, 624
- pilot hopping, 603
- pilot pollution, 586
- pilot power boosting, 280, 282, 347, 464, 550, 585, 589, 618, 627, 636
- pilot reuse, 557, 586, 611, 629
- pilot reuse cluster, 611, 625, 629
- pilot reuse pattern, 603
- pilot symbols, 111, 197
 - common, 196, 246, 273, 282, 343, 410, 463, 531, 536, 543, 551, 557, 585, 618
 - dedicated, 533, 536, 543, 551, 557, 582, 619, 627
 - precoded, 347, 533, 536, 543, 551, 557, 582, 619, 627
 - unprecoded, 531, 536, 543, 551, 557, 585
- pilot word, 102
- pinhole channel, 189, 317
- planar wavefront, 171
- PMF, 665
- Poincaré, 135
- Poisson distribution, 164
- Poisson point process, 638
- polarization, 185, 339
 - diversity, 186
 - mismatch, 138
- polyhedron, 444
- polytope, 444
- positive-definite, 660
- positive-semidefinite, 660
- post-processing SNR, 392
- posterior probability, 39, 41
- power, 73, 85, 137
- power allocation
 - BC, 470, 483, 484
 - frequency-division multiplexing, 422, 432
 - hardening-based, 622
 - matrix, 82, 369, 461
 - outage capacity, 314
 - parallel subchannels, 237, 469, 521
 - single-user without CSIT, 318
 - uniform, 327, 433, 492
 - waterfilling, 237, 523, 559, 627
- power amplifier, 74, 85
- power angle spectrum, 147, 183, 380, 557, 628
- power azimuth spectrum, 147
- power constraint, 466, 480
 - per-antenna, 85, 302, 440, 469–471, 519, 521, 527, 562
 - per-codeword, 74, 81, 84, 222, 231, 270, 280, 302, 313, 440, 442, 460, 470, 489, 619, 625

- per-symbol, 85, 222, 231, 280, 302, 313, 410, 440, 442, 460, 470, 489, 521, 527, 567, 589, 619
- power control
 - ergodic setting, 250
 - fractional, 599, 610, 612, 622
 - MAC, 440, 442, 470, 501, 515–517, 577, 584, 585
 - near–far effect, 448
 - single-user, 74, 81, 138, 212, 260, 301, 303, 422
 - waterfilling, 251
- power cosine, 148
- power delay profile, 163, 168, 628
- power efficiency, 212, 218, 226, 241, 266, 289, 309, 633
- power-limited regime, 217
- power offset
 - BC, 485, 486, 488, 529, 538, 563, 574
 - MAC, 452, 508, 517
 - single-user, 221, 262, 286, 307, 311, 312, 315, 331–334, 343, 398, 406, 458
- power spectral density, 72, 154, 677
- power spectrum, 72, 154, 677
- pre-log factor, 220
- precoding, 37, 81, 98, 335, 362, 440, 444, 492
 - block-diagonalization, 508, 558, 559
 - capacity, 305, 316, 321, 326, 331, 390, 449, 461, 479, 480
 - collaborative upper bound, 454, 484
 - discrete constellations, 308, 325
 - duality, 466, 467, 469, 479, 480
 - LMMSE receiver, 408
 - matched filter, 585, 619
 - outage probability, 314
 - pilot symbols, 347
 - regularized ZF, 513, 565, 625
 - semiunitary, 369
 - statistical beamforming, 492
 - total channel gain, 302
 - unitary, 406
 - ZF, 520, 557
 - ZF receiver, 394
- prediction, 51
- prior probability, 39
- priority, 424
- probability boxes, 195
- probability density function, *see* PDF
- probability mass function, *see* PMF
- product correlation model, *see* Kronecker model
- propagation clutter, 134, 139, 148, 182, 191, 492
- properness, 6, 15, 16, 43, 227, 241, 261, 310, 330, 667, 669
- proportional fairness, 427, 428, 430, 435, 482
- PSK
 - mutual information, 15
 - signal, 5, 86
 - spectral efficiency, 226, 240, 325
- pulse shaping, 22, 66, 72, 76, 87, 107, 108
- pulse-amplitude modulation, *see* PAM
- pulse-position modulation, 6
- Q-function, 14, 35, 149, 223, 668, 682
- QAM
 - mutual information, 15
 - signal, 5, 28, 34, 87
 - spectral efficiency, 226, 240, 263
- QPSK
 - MMSE, 43, 45, 46
 - mutual information, 15, 450
 - signal, 5, 35, 38, 43, 82
 - spectral efficiency, 33, 227, 260, 450
- QR decomposition, 661
- quadrature, 4, 5, 15, 31–33, 43, 59
- quantization, 366, 367
 - noise, 632
 - scalar, 475
 - vector, 370, 475
- quasi-static setting, 247, 248, 252, 271, 303, 313, 360, 362, 398, 442, 454, 460, 475
- radio front-end, 61
- radio propagation, 133
- raised-cosine filter, 70, 76, 109
- Raleigh, *xx*
- random coding, 25
- random matrix theory, 336
- random process, 10, 50, 72, 676
- random set theory, 195
- rank, 92, 179, 189, 300, 305, 307, 311, 315, 321, 331, 333, 367, 375, 403, 452, 658, 660, 661
- rank adaptation, 370, 375
- rank-deficient, 658
- rate control, 228, 360
- rate region, 419
- ray tracing, 135, 204
- Rayleigh distribution, 669, 672
- Rayleigh fading
 - BC block-diagonalization power offset, 563, 564
 - BC capacity, 487, 488
 - BC pilot-assisted transmission, 555
 - BC ZF power offset, 529, 530
 - BC ZF spectral efficiency, 524, 530
 - channel matrix, 178, 309
 - distribution, 145
 - DMT, 315
 - interference, 284, 286, 350
 - large-dimensional capacity, 338
 - LMMSE spectral efficiency, 404–406, 410
 - MAC capacity, 456, 459, 461
 - MAC ZF spectral efficiency, 504, 505, 508, 510
 - Monte-Carlo simulation, 598
 - multiuser diversity, 429, 439
 - outage probability, 313
 - pilot-assisted transmission, 277, 344
 - power offset, 311
 - precoding, 314

- ray, 164
- single-user capacity, 251, 253, 254, 259, 261, 265, 266, 268, 322, 323, 328, 332, 334, 341
- throughput, 249, 272, 362
- ZF spectral efficiency, 393, 395
- reciprocity, 248, 364, 466, 532, 550, 619, 634
- recursive least-squares, 117
- reference distance, 139, 142
- reference symbols, 111
- reflection, 134, 144
- regular fading, 11, 157, 158, 267, 343
- regular pilot sequences, 589
- regular random process, 11, 51
- regularization, 98, 102, 120, 565, 624, 627
- regularized zero-forcing, 565, 582, 625
- regulatory agencies, 85
- relative entropy, 11, 12
- relay, 647
- resource allocation, 428, 429, 439
- resource block, 272, 428, 430, 439
- resource element, 110
- reverse link, 182, 417, 439, 465, 469, 539, 543, 549, 550, 583, 585, 590, 631
- Rice fading, 146, 179, 186, 256, 263, 317, 324, 330, 334–336, 340, 394, 405, 409, 429, 439, 461
- rich scattering, 179
- right singular vector, 661
- right unitary invariance, 667
- rolloff factor, 70
- roof-edge diffraction, 189
- root raised-cosine filter, 70
- row rank, 658
- row space, 657, 661
- rural area, 141, 183
- saddle point, 276, 282, 308, 535, 565
- Saleh–Valenzuela, 164, 193
- Salz, xx
- sampling, 18, 64–67, 69, 70, 75, 78, 108, 144, 171
- sampling offset, 66
- sampling period, 108, 157, 197
- sampling rate, 70
- scalar metric, 424, 435
- scattering, 134, 144
- scattering function, 168
- scheduling, 430, 435
- SDMA, 452, 492, 557
- sectorization, 492, 557, 634, 636
- self-calibration, 365
- self-interference, 594, 597
- semicircle law, 675, 676
- semiunitary matrix, 341, 559
- semiunitary precoding, 370
- separable correlation model, *see* Kronecker model
- shadow fading, 137, 143, 195, 203, 212, 440, 583, 598, 599, 603, 605, 607, 609, 612, 623, 635, 638
- shadow fading correlation distance, 138, 196, 635
- shadow fading correlation process, 583
- Shannon, 3, 4, 6, 11, 12, 17, 18, 22, 25, 218, 237, 253, 254
- Shannon bandwidth, 22
- shaping gain, 228
- SIC, 353, 354, 358, 362, 389, 409, 446–448, 453, 456, 464, 466, 472–477, 480, 482, 618
- side information, 246, 252, 267, 274, 342, 389, 490, 491, 534, 582
- signal streams, 82
- signal-space coding, 25, 30, 33, 34, 38
- signal-to-interference ratio, *see* SIR
- signal-to-interference-plus-noise ratio, *see* SINR
- signal-to-leakage-plus-noise ratio, *see* SLNR
- signal-to-noise ratio, *see* SNR
- Silverstein, 676
- SIMO, 310, 313, 322, 324, 328, 333, 341, 393, 395
- single carrier, 100, 108
- single-carrier frequency-domain equalization, 98
- single-carrier transmission, 240, 241
- single codeword, 356
- single-input multiple-output, *see* SIMO
- single-letter formulation, 20, 22, 27, 36, 38, 222, 223, 252, 264, 276, 282, 300, 439, 470
- singular matrix, 662
- singular value, 506, 525, 527, 558, 661
- singular-value decomposition, *see* SVD
- SINR, 197
 - local-average, 283, 285, 349
 - per-stream, 352, 400, 402, 404, 408, 512, 517, 566–568, 570, 585, 594, 596, 600, 611, 620, 626
 - per-subcarrier, 362
- SIR, 283, 598, 600, 606, 609, 612, 614, 623, 626
- SLNR, 568, 625
- SLNR-maximizing precoder, 569
- slope, 218, 226, 261, 265, 309, 326, 332, 342, 406, 432
- small-scale fading, 144, 429
- small-scale phenomena, 135, 177, 195, 302
- small-to-medium cities, 141
- smart antenna, xix
- smoothing, 51
- snapshot, 201
- SNR, 13
- SNR gap, 241
- soft-input soft-output, 30
- space correlation, 150
- space diversity, 173
- space selectivity, 146
- space-division multiple access, *see* SDMA
- space-time coding, 81
- sparsity, 123, 628
- spatial aliasing, 176
- spatial channel model, 201, 245
- spatial correlation, 176

- spatial DOF, *see* DOF
 spatial modulation, 379
 spatial multiplexing, xx
 special functions, 680
 spectral broadening, 157
 spectral efficiency, 22, 25, 212, 213
 cyclic prefix, 239
 discrete constellations, 226, 260, 263, 308, 325
 energy efficiency, 217
 excess bandwidth, 75, 109
 finite blocklength, 225
 link adaptation, 228, 245, 362
 per-stream, 353, 362, 394, 404
 power control, 251
 region, 418, 420, 424, 432
 single-user, 240, 241, 265, 266, 275, 278, 280, 281, 318, 324, 335, 340, 343, 409
 speed of light, 150, 160, 169
 speed of sound, 169
 sphere decoder, 357
 spherical wavefront, 171
 square QAM, 5
 square-root raised-cosine filter, 70
 staggered pilots, 590
 standard Gaussian, 13, 223, 668, 669
 Stanford University, xx
 stationarity, 11, 20, 21, 30, 38, 51, 72, 135, 145, 155, 158, 166, 168, 223, 250, 677
 statistical beamforming, 326, 330, 331, 433, 461, 492
 statistical CSI, 246
 statistical waterfilling, 320
 steering matrix, 82, 300, 304, 308, 314, 316–318, 347, 369, 408, 434, 461, 559
 Stieltjes transform, 675, 676
 Stirling's formula, 266, 644
 stochastic geometry, 638
 stochastic modeling, 135
 street width, 143
 strict-sense stationarity, 11, 20, 21, 30, 51, 135, 145, 155, 168, 223, 250, 677
 strong law of large numbers, 674
 subcarrier, 104, 105, 110, 235, 243
 channel estimation, 121, 122
 fading, 107, 269, 271, 389
 link adaptation, 243, 244, 271, 361
 number of subcarriers, 85, 168, 270, 428
 parallel subchannels, 234, 235, 240
 power constraint, 281
 resource allocation, 422
 shape, 107, 171
 spacing, 107–109, 162, 236, 272, 428
 subspace distance, 368, 372, 373
 suburban area, 141, 182, 183
 successive interference cancelation, *see* SIC
 sum spectral efficiency, 424, 428, 429
 BC, 523, 525, 528, 530, 555, 560–563, 565, 570, 571, 574
 forward link, 622, 626
 MAC, 441, 444, 456, 458, 505, 508, 509, 513
 reverse link, 600, 609, 614
 sum-capacity, 424
 BC, 481, 482, 484, 487, 489, 527, 555, 561, 571
 MAC, 443, 446–451, 453, 454, 456–458, 460, 462
 superposition, 423, 475–477
 superposition coding, 423
 support of a distribution, 7, 11, 666
 SVD, 82, 232, 304, 389, 449, 450, 467, 558, 661
 symbol period, 22, 66, 74, 76, 107, 157, 161, 190, 197, 200
 symbol rate, 69, 72, 74
 synchronization, 22, 66, 70, 72, 100, 111, 441, 471
 TDD, xxiv, 246, 248, 364, 490, 550, 582, 583, 633
 TDMA, 420–422, 424, 426, 427, 431, 444, 451, 452, 476
 Telatar, xx, 314
 telephony, 428
 tensor, 180, 184
 terrain types, 142
 thermal noise, 71
 throughput, 36, 229, 244, 245, 249, 287, 360–362, 430
 time correlation, 152, 197
 time-division, 420, 422, 424, 426, 433, 444, 447, 451, 452, 476
 time-division duplexing, *see* TDD
 time-division multiple access, *see* TDMA
 time–frequency correlation, 167, 168
 time–frequency double selectivity, 167
 time selectivity, 152, 177
 time slot, 420, 422, 423, 428, 430
 time-varying transfer function, 171
 Toeplitz matrix, 77, 80, 96, 232, 239, 659
 Tomlinson–Harashima, 472, 474
 total channel gain, 212, 251, 301, 341
 trace, 662
 training symbols, 111
 transmit Wiener filter, 569
 treat interference as noise, 276, 283, 344, 418, 535, 592, 593, 611, 620, 625, 630
 tree decoder, 358
 trellis coded modulation, 25
 truncated channel inversion power control, 251
 truncated Gaussian, 148
 truncated Laplacian, 149, 183, 192, 193, 201
 tunnel, 189
 turbo BLAST, 360
 turbo code, 25, 30, 36, 229
 two-ring model, 192
 two-slope model, 139
 typical urban, 163, 272
 UTU model, 183, 339
 ultrawideband, 6, 59

- uncoded, 25, 354
- uncorrelated scattering, 166, 188
- uncorrelatedness, 120, 166, 188, 189, 276, 317, 344, 462, 535, 585, 588, 630, 666, 669
- underspread fading, 169, 248, 252, 264–270, 273, 278, 321, 327, 333, 340–343, 463, 490, 628
- underwater channel, 169, 172
- underwater communication, 649
- Ungerboeck, 25
- uniform circular array, 173
- uniform linear array, 173, 176
- unit-rank, 189, 367
- unitary invariance, 107, 314, 317, 406, 408, 559, 667
- unitary matrix, 82, 85, 116, 120, 183, 184, 300, 304, 317, 376, 406, 408, 559, 563, 658, 661, 662
- unitary rotation, 658
- unitary-independent-unitary model, *see* UIU model
- upconversion, 59, 61, 75, 77
- upper incomplete gamma function, 680
- urban area, 142, 147, 166
- user association, 636
- user selection, 428, 435, 492, 502, 508, 527, 562, 610, 629, 635, 636
- V-BLAST, 354
- Valenti, 229
- Valenzuela, xx, 164, 193, 354
- Varanasi, 353
- vector coding, 234, 235, 239, 240, 269
- vector perturbation, 474
- vector quantization codebook, 370
- vectorization, 112, 520
- vehicular setting, 163, 170, 196, 268, 277, 279, 344, 345, 463, 541–555, 582, 617
- velocity, 152, 156
- vertical BLAST, *see* V-BLAST
- virtual channel model, 185, 191
- visible-light communication, 649
- Voiculescu, 676
- von-Mises, 149, 192
- Walfisch-Ikegami, 141, 142
- waterfilling, 237, 241, 250, 251, 305, 306, 320, 442, 449–451, 468, 523–529, 545, 559–562, 627
- waveform, 58, 87, 107
- waveguide, 189
- wavelength, 134, 135, 139, 140, 145, 150, 151, 380, 633
- weak law of large numbers, 673
- Weichselberger model, 183
- weighted sum-capacity, 426
 - BC, 477, 479, 480, 486
 - MAC, 445, 449, 450, 456, 461
- weighted sum spectral efficiency, 424, 430, 435
 - BC, 478, 523, 527, 535, 540, 560, 570, 574
 - forward link, 627, 628
 - MAC, 445, 447, 449, 450, 505, 513
 - reverse link, 599
- whitening filter, 72
- wide-sense stationarity, 135, 145, 155, 166, 168, 677
- wide-sense stationary uncorrelated scattering, *see* WSSUS
- wideband, 160
- Wiener, 51, 94
- Wiener filter, 51
- Wigner, 675, 676
- windowing, 109
- WINNER models, 201, 204
- Winters, xx
- wireless local-area network, *see* WLAN
- Wishart, 309, 312, 323, 333, 350, 459, 488, 564, 670
- Wishart distribution, 178, 309, 312, 323, 333, 350, 564, 670
- Wishart matrix, 309, 312, 323, 333, 350, 459, 488, 564, 670
- WLAN, xxi, 143, 201
- Woodbury matrix identity, 663
- word error probability, 21
- WSSUS, 166, 168, 188
- X-codes, 308
- Z-transform, 88, 89, 655
- Zadoff-Chu sequences, 115, 343, 589
- zero-forcing, *see* ZF
- ZF
 - equalizer, 88, 89, 92, 98
 - layered architecture, 355
 - OFDM, 107
 - receiver, 390, 399, 405, 406, 503–505, 508, 509, 513, 516
 - single-carrier frequency-domain equalizer, 99, 100, 102
 - transmitter, 520, 521, 524, 525, 528, 529, 531, 536, 540, 543, 546, 550, 553, 554, 565, 627