

Index

- a posteriori probability (APP), and turbo equalizer, 365
 Abramson, N., 462
 access layer design, and ad hoc wireless networks, 544–7
 ad hoc on-demand distance vector routing (AODV), 550
 ad hoc wireless networks: applications of, 536–40;
 and cross-layer design, 554–6; definition of, 535;
 design principles and challenges of, 540–2; and
 energy-constrained networks, 558–64; and network
 capacity limits, 556–8; and protocol layers, 542–54
 adaptive coded modulation, 303–5
 adaptive coding, 288
 adaptive equalizers, 353, 366–8
 adaptive loading, 382–3
 adaptive modulation: in adaptive transmission systems,
 284–5; in combined fast and slow fading, 314–15;
 definition of, 283; and general M -ary modulations,
 305–13; and hybrid techniques, 288; practical
 constraints on, 283–4; and variable-coding techniques,
 288; and variable error probability, 287; and
 variable-power techniques, 286–7; and variable-rate
 techniques, 285–6; and variable-rate variable-power
 MQAM, 288–305. *See also* modulation
 adaptive rate, and variable-rate variable-power MQAM,
 290–1
 adaptive transmission system, 284–5
 additive white Gaussian noise channel. *See* AWGN
 channels
 Advance Mobile Phone Service (AMPS), 12, 595
 Alamouti code: and multiple-input multiple-output
 (MIMO) systems, 339; and transmitter diversity, 217,
 219–20
 ALOHNET (University of Hawaii), 2
 ALOHA protocol, and random access systems, 462–4,
 466
 alternate Q -function representation, and digital
 modulation, 182
 Amitay, N., 37
 amplify-and-forward strategy, for routing protocols, 551
 amplitude and phase modulation, in digital
 communications, 142–53
 analog cellular systems, 3, 11
 analog equalizer, 352
 angle of arrival (AOA), and space-time channel models,
 93–4
 antenna(s). *See* antenna arrays; directional antennas;
 multiple antennas; multiple-input multiple-output
 systems; multiple-input single-output channels;
 sectorized antennas; single-input multiple-output
 channels; smart antennas
 antenna arrays, and multiple-input multiple-output
 systems, 344
 Antheil, George, 407n1
 application layer design, and ad hoc wireless networks,
 553–4
 area spectral efficiency (ASE), and fundamental rate
 limits, 525–8
 Asynchronous Connection-Less (ACL), 19
 AT&T Bell Laboratories, 3
 attenuation factors, and path loss in indoor environments,
 45–6
 auction process, and spectrum allocation, 13, 21
 autocorrelation functions: and direct-sequence spread
 spectrum, 413; and fading models, 71–7, 84–5, 91–2;
 and random processes, 583
 automatic gain control (AGC), and MQAM modulation,
 178
 automatic repeat request (ARQ) protocol, for access layer
 design, 546
 average BER target, and general M -ary modulations,
 310–13
 average dB path loss, and shadowing, 49
 average fade duration, and narrowband fading models,
 79–81
 average fade region duration (AFRD), and adaptive
 MQAM, 298–300
 average probability of error, and fading channels, 184–92.
 See also bit error rate; error probability
 “aware homes,” and home networks, 537
 AWGN channels: and area spectral efficiency, 527f;
 capacity of, 99, 100–1, 470–6, 484–8; coding gain in,
 229f; and digital modulation, 172–92; probability of
 error for hard decision decoding in, 240–2; probability of
 error for soft decision decoding in, 242–4; and
 spread spectrum, 405

- backbone infrastructure, and ad hoc wireless networks, 540
- balanced property, of spreading codes, 414
- bandpass channels, representation of, 574
- bandpass signals, representation of, 573–6
- base stations: for cellular phone systems, 9–10; for cordless phones, 14; handing off from, 506. *See also* infrastructure-based wireless networks
- batteries, and ad hoc wireless networks, 558. *See also* energy constraints
- Bayes' rule, and probability theory, 578
- beamforming, and multiple-input multiple-output diversity gain, 334–5, 496, 497
- belief propagation, and low-density parity-check codes, 262
- BER. *See* bit error rate
- Bergmans, P. P., 471
- Bernoulli random variable, 582
- Berrou, C., 259, 260
- binary linear block codes, 231–2
- binary UEP codes, 272. *See also* unequal error protection codes
- binomial distribution, and random variables, 582
- bit error rate (BER): and general M -ary modulations, 310–13; and voice and data targets, 5. *See also* error probability
- bit-interleaved coded modulation (BICM), 271
- bit/symbol energy, and AWGN channels, 172–3
- BLAST (Bell Labs Layered Space Time) architectures, 340–2
- blind equalizer, 366
- block coding: and space-time codes for multiple-input multiple-output systems, 339; with interleaving, 267–70
- block fading channels, capacity of, 102, 116–17
- Bluetooth, 19–20, 601–3
- Bose–Chadhuri–Hocquenghem (BCH) codes, 244, 245*f*
- BPSK modulation, and error probability, 173–5
- branch metric, and maximum likelihood decoding, 249
- broadband wireless access, overview of current systems, 17
- broadcast channels, and downlink channel capacity, 470
- broadcasting, and satellite systems, 4, 19. *See also* entertainment and entertainment systems
- building penetration loss, and indoor systems, 46
- busy-tone transmission, and random access, 465–6
- capacity, of wireless channels: ad hoc wireless networks and limits of, 556–8; in AWGN, 100–1; and cellular system design, 514–18; and code performance, 230; determination of, 99–100; and downlink channels in multiuser systems, 469–84; and flat fading channels, 102–16; and frequency-selective fading channels, 116–21; and multiple-input multiple-output channels, 325–34; and uplink channels in multiuser systems, 484–90. *See also* ergodic capacity; outage capacity; rate region
- capacity with outage: and flat fading channels, 105–6; and multiple-input multiple-output channels, 332–3
- capacity per unit energy, and energy constraints, 562–4
- capacity region, of multiuser systems, 469
- capture effect, and random access, 462
- carrier phase recovery, and digital modulation, 144, 160–7
- carrier-sense multiple access (CSMA), 464–6
- CDMA. *See* code-division multiple access
- cdma2000 standard, 599–600
- cell clustering, and cellular system design, 509, 511–13
- cell coverage area, and path loss, 53–6
- cell shape and cell size, and cellular system design, 507, 508, 509–13
- cellular digital packet data (CDPD) system, 17, 245
- cellular phones: growth in use of, 1, 6; history of, 3–4; overview of current systems, 8–13; and standards, 24, 595–600
- cellular system design: and channel reuse, 508–13; and dynamic resource allocation, 520–4; and fundamental rate limits, 524–8; fundamentals of, 505–8; and interference reduction techniques, 518–20; SIR and user capacity in, 514–18. *See also* infrastructure-based wireless networks
- central limit theorem (CLT), and random variables, 582
- centralized route computations, and network layer design, 549
- channel(s): adaptive MQAM and estimation error or delay of, 300–3; cellular system design and assignment of, 509, 510, 512*f*; cellular system design and reuse or set of, 506, 508–13; downlink capacity and models of, 470; and unequal error protection codes, 274–5; vector coding for multicarrier modulation and knowledge of, 392; wideband fading models and coherence time of, 90–1. *See also* AWGN channels; block fading channels; capacity, of wireless channels; channel distribution information; channel equalizer; channel inversion; channel side information; downlink channels; finite-state Markov channels; flat fading channels; multipath channels; single-input single-output channels; static channels; time-invariant channels; time-varying channels; uplink channels
- channel distribution information (CDI), and capacity of flat fading channels, 102–3
- channel equalizer, and multiple-input multiple-output systems, 342
- channel inversion: and adaptive MQAM, 292–3; and multiuser DSSS systems, 437; and zero-outage capacity, 111–13
- channel-optimized source coding, 275
- channel-optimized vector quantizer (COVQ), 275
- channel side information (CSI): and capacity of flat fading channels, 102, 103–13; and channel capacity in multiuser systems, 478, 488; and multiple-input multiple-output systems, 333–4
- channel side information at receiver (CSIR), and multiple-input multiple-output systems, 322, 329
- channel side information at transmitter (CSIT): and diversity, 217–18; and multiple-input multiple-output systems, 322, 329
- characteristic equation, and matrix decomposition, 592
- characteristic function, and random variables, 579

- characteristic polynomial, and matrix decomposition, 592
 chip rate, and spread spectrum, 405
 chip sequences, and spreading codes, 413–14
 chip time, and spread spectrum, 405
 circular convolution, and discrete implementation of multicarrier modulation, 383–4
 Clarke, Arthur C., 4
 coarse synchronization: and direct-sequence spread spectrum, 418; and frequency-hopping spread spectrum, 422
 co-channel cells, and cellular system design, 506
 code characterization, and trellis diagrams for convolutional codes, 246–9
 code(s) and code design: channel capacity and performance of, 230; and coded modulation, 263–7; and concatenated codes, 258–9; and convolutional codes, 246–58; definition of, 228; and energy constraints for ad hoc wireless networks, 559–60; and interleaving for fading channels, 267–71, 381; joint source and channel coding, 274–5; and linear block codes, 230–46; and low-density parity-check codes, 262; and multicarrier modulation, 381; overview of, 229–30; and space-time codes for multiple-input multiple-output systems, 337–42; and turbo codes, 259–62; and unequal protection codes, 271–4; and variable-coding techniques for adaptive modulation, 288. *See also* adaptive coding; Alamouti code; block coding; coding gain; dirty paper coding; Gold codes; Gray coding; Kasami codes; long spreading code; maximal linear codes; network coding; nonorthogonal codes; orthogonal codes; Reed-Solomon code; short spreading code; spreading codes; trellis codes; vector coding; Walsh–Hadamard codes
 code-division multiple access (CDMA): and cellular phone systems, 11; and cellular system design, 516–18; and multiuser systems, 424, 441–3, 458–9, 460
 coded modulation, and code design, 263–7. *See also* adaptive coded modulation; bit-interleaved coded modulation; lattice coded modulation; symbol-interleaved coded modulation; trellis coded modulation
 codeword symbols, 231
 coding gain: and adaptive coded modulation, 303–5; definition of, 229–30
 cofactor, of matrix, 591
 coherence bandwidth, and wideband fading models, 88–90
 coherent detection, and amplitude/phase modulation, 144
 coherent modulations, error probability approximation for, 180
 collision avoidance, and random access, 465
 column vector, of matrix, 589
 combined fast and slow fading, adaptive techniques in, 314–15
 common data, and downlink channel capacity in multiuser systems, 476–7
 common linear block codes, 244
 complex envelope, and representation of bandpass signals, 573
 complex lowpass representation, of bandpass signals, 573
 computers. *See* Internet
 concatenated codes, and code design, 258–9, 261–2
 constant envelope modulation, 127
 constellation expansion factor, and coded modulation, 264
 constellation shaping, and amplitude/phase modulation, 152
 continuous-phase FSK (CPFSK): error probability for, 179; and frequency modulation, 156
 continuous random variable, 578
 continuous-rate adaptation, and coding for adaptive modulation, 305–9
 convolutional codes, and code design, 246–58, 270, 271f
 convolutional interleavers, 269, 270
 cooperative diversity, and routing protocols, 551
 cooperative MIMO, 560–1
 co-phasing, and receiver diversity, 206
 cordless telephones: and equalization, 351; overview of, 13–15; and spread spectrum, 403
 correlation coefficients, and random variables, 581
 coset coding, and coded modulation, 263, 265
 cosine pulses, and Nyquist criterion, 158
 cost: of base stations for cellular phone systems, 9–10; and spectrum allocation, 21
 COST 231 extension, to Hata model, 44
 Costa, M., 520
 covariance, and random variables, 581
 Cover, T. M., 471
 CPFSK. *See* continuous-phase FSK
 cross-correlation: and multiuser DSSS systems, 425; and narrowband fading models, 71–7
 cross-layer design, and ad hoc wireless networks, 543, 554–6, 562
 CSI. *See* channel side information
 CT-2 (cordless telephone, second generation), 14
 cumulative distribution function, 578
 cyclic codes, design of, 236–8
 cyclic prefix, and multicarrier modulation, 384–6
 D-BLAST, and multiple-input multiple-output systems, 336, 341–2
 data networks, 537. *See also* ad hoc wireless networks
 decision-directed parameter estimation, and digital modulation, 165
 decision-feedback equalization (DFE), 353, 364–5
 decision-feedback phase-locked loop, 165
 decision regions, and signal space analysis, 134–7
 decode-and-forward strategy, and routing protocols, 550
 decoding. *See* hard decision decoding; maximum likelihood decoding; minimum distance decoding; multistage decoding; soft decision decoding
 decomposition, of matrix, 592–3
 decorrelation distance, and shadowing, 51
 deep interleaver, 268
 Defense Advanced Research Projects Agency (DARPA), 2, 535, 537
 degraded broadcast channel, 470
 deinterleaver, 268. *See also* interleaving

- delay constraints, and power control for multiple access, 469
- delay spread, and equalization, 351
- design process, and technical challenges for wireless networks, 7–8. *See also* access layer design; application layer design; cellular system design; code(s) and code design; cross-layer design; network layer design; physical layer design; transport layer design
- determinant, of matrix, 591
- determinant criterion, and pairwise error probability for multiple-input multiple-output systems, 339
- deterministic scattering function, and wideband fading models, 84
- device networks, 538. *See also* ad hoc wireless networks
- DFT. *See* discrete Fourier transform
- diagonal elements, of matrix, 588
- diagonal encoding, and multiple-input multiple-output systems, 341–2
- diamond cell shape, 508, 509–10, 511, 512*f*
- dielectric canyon, 37–8
- differential modulation: error probability for, 180–2; and signal space analysis, 149–51
- Digital Enhanced Cordless Telecommunications (DECT), 14, 598
- digital modulation: amplitude and phase modulation and, 142–53; and AWGN channels, 172–82; considerations in choosing techniques for, 126; and Doppler spread, 192–5; and fading, 182–92; and frequency modulation, 153–7; and intersymbol interference, 195–7; main categories of, 127; and passband modulation, 142; and pulse shaping, 157–60; and signal space analysis, 127–41; symbol synchronization and carrier phase recovery, 160–7. *See also* digital systems
- digital radio, 2
- digital systems, advantages of over analog systems, 11. *See also* digital modulation
- digital television, 22
- direct sequence (DS), and spread spectrum, 405
- direct-sequence spread spectrum (DSSS): and code division for multiple users, 474–6; and hybrid techniques for multiple access, 460; and modulation, 405, 408–21; and multiuser systems, 424–43
- directional antennas: and diversity, 205; and multiple-input multiple-output systems, 343–4
- dirty paper coding (DPC): and downlink channel capacity, 483; and interference reduction, 520
- discrete Fourier transform (DFT), and multicarrier modulation, 383–4
- discrete implementation, of multicarrier modulation, 383–93
- discrete random variable, 578
- discrete-rate adaptation: and adaptive MQAM, 293–8; and general M -ary modulations, 309–13
- discrete-time model, and multipath channels, 92–3
- distance properties, and convolutional codes, 253–4
- distance vector routing, and network layer design, 549
- distributed control systems, and ad hoc wireless networks, 539–40
- distributed route computation, and network layer design, 549
- diversity: coding and interleaving as forms of, 267; and cross-layer design in ad hoc wireless networks, 555–6; definition of, 204; and independent fading paths, 204–6; and moment generating functions, 220–5; and receivers, 206–17; and transmitters, 217–20. *See also* cooperative diversity; diversity gain; diversity–multiplexing trade-offs
- diversity gain, and beamforming in multiple-input multiple-output systems, 334–5
- diversity–multiplexing trade-offs, and multiple-input multiple-output systems, 335–7
- Doppler power spectrum, and wideband fading models, 90–1
- Doppler shift: and signal models, 30–1; and time-varying channel impulse response, 65
- Doppler spread, and digital modulation, 192–5
- downlink channels, and multiuser systems, 424–5, 428–33, 452–4, 469–84, 490–4
- DPSK modulation, error probability of, 194
- DSSS. *See* direct-sequence spread spectrum
- dual-slope model, of path loss, 44
- duality, of uplink and downlink channels in multiuser systems, 490–4
- duplexing, and downlink/uplink channels in multiuser systems, 454
- dynamic channel assignment (DCA), 521–2
- dynamic resource allocation, and cellular system design, 520–4
- dynamic source routing (DSR), and network layer design, 550
- early–late gate synchronizer, 166–7
- Echo-1*, 4
- economics. *See* cost
- effective data rate, of random access systems, 462
- effective noise vector, and multiuser fading channels, 478
- eigenvalue, 592
- eigenvector, 592
- 802.11a/b/g standards, 601, 602*t*
- empirical path-loss models, 42–6
- encryption, and security, 7
- energy constraints, in ad hoc wireless networks, 542, 558–64
- Enhanced Data rates for GSM Evolution (EDGE), 13, 598–9
- entertainment and entertainment systems: and home networks, 538; and satellite systems for broadcast, 4. *See also* broadcasting; radio(s) and radio communications; television
- equal-gain combining (EGC), and diversity analysis, 216–17, 224
- equalization and equalizers: and adaptive equalizers, 353, 366–8; decision-feedback, 353, 364–5; definition of, 351; and equalizer training and tracking, 366–8; and equalizer types, 353–4; folded spectrum and ISI-free transmission, 354–7; and linear equalizers, 353, 357–62; and maximum likelihood sequence

INDEX

637

- estimation, 362–4; multicarrier modulation and frequency, 381; and noise enhancement, 351, 352–3; and turbo equalizer, 365–6. *See also* analog equalizer; blind equalizer; channel equalizer; decision-feedback equalization; fractionally spaced equalization
- equivalent branch metric, and maximum likelihood decoding, 250
- equivalent lowpass channel, and representation of bandpass channels, 574
- equivalent lowpass signal, and representation of bandpass signals, 573
- ergodic capacity: and channel side information at receiver, 103–5; and multiple-input multiple-output channels, 330–2; and multiuser fading channels, 478, 482
- ergodicity, and random processes, 585
- error coefficient, and coded modulation, 264
- error probability: adaptive modulation and variable, 287; and adaptive MQAM, 300; for BPSK and QPSK modulation, 173–5; and code design, 230; for coherent modulations, 180; for concatenated codes, 259; for convolutional codes, 257–8; for differential modulation, 180–2; and hard decision decoding in AWGN, 240–2; for MPAM and MQAM modulation, 176–9; for MPSK modulation, 175–6; and signal space analysis, 137–41; and soft decision decoding in AWGN, 242–4; and space-time codes for multiple-input multiple-output systems, 337–9; and variable-rate variable-power MQAM, 289–90. *See also* average probability of error; bit error rate; probability theory; symbol error
- Ethernet technology, 2
- Euclidean norm, 589
- Europe: and broadband wireless access, 17; and cellular phone systems, 12, 13, 595, 596, 598; and cordless phone systems, 14; and WLANs, 16
- European Cooperative for Scientific and Technical Research (EURO-COST), 44
- European Telecommunications Standards Institute (ETSI), 21, 23
- exposed terminal problem, and random access, 465
- extended Golay code, 244. *See also* Golay code
- fade region, and adaptive MQAM, 298–300
- fading: adaptive techniques in, 285–8, 314–15; and coding with interleaving, 267–71; and digital modulation, 182–92; diversity and realization of independent fading paths, 204–6; and downlink channel capacity, 477–82; multicarrier modulation and mitigation of subcarrier, 380–3; and multipath channels, 69, 70–92; and multiple-input multiple-output channels, 329–34; and shadowing, 48–51; and uplink channel capacity, 488–90. *See also* Nakagami fading; Rayleigh fading; Rician fading
- fading state, and multiuser fading channels, 478
- fast Fourier transform (FFT), and multicarrier modulation, 383
- fast frequency hopping (FFH), and spread spectrum, 407–9
- FDMA. *See* frequency-division multiple access
- Federal Communications Commission (FCC), 3, 21
- Fessenden, Reginald, 28
- FFT. *See* fast Fourier transform
- FHSS. *See* frequency-hopping spread spectrum
- fine synchronization, and direct-sequence spread spectrum, 418–19
- finite-state Markov channels (FSMCs): and capacity of flat fading channels, 103; and narrowband fading models, 82
- first-generation analog systems, and cellular phones, 595–6
- fixed rate, adaptive MQAM and channel inversion with, 292–3
- FLASH-OFDM, 374
- flat fading, and narrowband signals, 89
- flat fading channels, capacity of, 102–16
- flooding, and routing protocols, 548–9, 550
- floor attenuation factor, and indoor path-loss models, 45–6
- flow control, and network layer design, 551–2
- folded spectrum, and equalization, 354–7
- Foschini–Miljanic power control algorithm, 468
- Fourier transform. *See* discrete Fourier transform; fast Fourier transform; inverse FFT
- fractionally spaced equalization, 355
- free-space path loss, 31–2
- frequency: cellular systems and reuse of, 8–9, 506; digital systems and modulation of, 153–7; equalization of and multicarrier modulation, 381, 387; independent fading paths and diversity of, 205–6; and timing offset in multicarrier modulation, 395–6. *See also* fast frequency hopping; frequency-hopping spread spectrum; slow frequency hopping
- frequency division (FD): and downlink channel capacity, 469; and uplink channel capacity, 486
- frequency-division duplexing (FDD), 454
- frequency-division multiple access (FDMA), 11, 455–6, 460, 514–16
- frequency-hopping spread spectrum (FHSS): definition of, 405, 407; and multiuser systems, 408–9, 421–3, 443
- frequency-selective fading channels: capacity of, 116–21; and intersymbol interference, 195; and multiple-input multiple-output systems, 342–3; and wideband fading models, 89
- frequency-shift keying (FSK): error probability for, 179; and frequency modulation, 155
- Fresnel–Kirchhoff diffraction parameter, 40
- Fresnel knife-edge diffraction model, 39
- Frobenius norm, 338, 591
- FSMCs. *See* finite-state Markov channels
- fully connected network, and network layer design, 547
- fundamental rate limits, and cellular system design, 524–8
- Gallager, R. G., 262
- game-theoretic approach, to energy-efficient access for ad hoc wireless networks, 561
- Gaussian approximation, and multiuser DSSS systems, 431–2, 436–7
- Gaussian distribution, and random variables, 581–2

- Gaussian processes, and properties of random processes, 586–7
- general M -ary modulations, and adaptive modulation, 305–13
- General Packet Radio Service (GPRS), 598
- general ray tracing (GRT), 38–41
- generator matrix, for linear block code, 232–4
- generator polynomial, for cyclic codes, 236
- geometric representation, of signals, 129–32
- geometrical theory of diffraction (GTD), 39
- geosynchronous orbit (GEO) satellite systems, 4
- Glavieux, A., 259
- Globalstar LEO system, 19
- GLOMO (global mobile information systems), 537
- Golay code, and linear block codes, 244
- Gold codes, and multiuser DSSS systems, 425–6
- Golomb, S. W., 414
- GPRS standard, 12–13
- Gram–Schmidt orthogonalization procedure, 129
- Gray coding: and amplitude/phase modulation, 145; and signal space analysis, 141
- Green, Paul, 419n4
- GSM (Global Systems for Mobile Communications) standard, 12, 596
- Gupta, P., 556
- Hadamard matrix, and multiuser DSSS systems, 427–8
- Hamming code, and common linear block codes, 244
- Hamming distance, and code design, 230, 232
- handing off, from base station, 506, 597
- hard decision decoding (HDD), and linear block codes, 238–42
- Hata model, 43–4
- Hayes, J. F., 287
- Hermitian matrix, 590
- Hertz, Heinrich, 28
- hexagon cell shape, 508, 509–13
- hidden terminal problem, in random access systems, 464–5
- high data rate (HDR), and time-division multiple access, 521
- High Speed Circuit Switched Data (HSCSD), 598
- HIPERLAN (high-performance radio LAN) standards, 16
- home networks, 537–8, 539. *See also* ad hoc wireless networks
- hybrid techniques: for adaptive modulation, 288; for multiple access, 460–1
- IEEE (Institute of Electrical and Electronics Engineers) standards, 23, 396–8, 601, 602
- incremental redundancy, and access layer design, 547
- independent fading paths, 204–6
- indoor path-loss models, 45–6
- Industrial, Scientific, and Medical (ISM) frequency bands, 2
- infrastructure-based wireless networks, 505. *See also* cellular system design
- Inmarsat (satellite network), 18
- inner product, of vector, 591
- in-phase component, and representation of bandpass signals, 573
- intelligent appliances, and home networks, 538
- intercell dynamic channel allocation (DCA), 521
- interference: intercell, 9, 507, 522; precancellation of, 520; reduction technique for cellular system design, 518–20. *See also* interference limited; interference signal; intersymbol interference; intracell interference; multiple access interference; narrowband interference; symbol interference cancellation
- interference limited: and cellular phone systems, 12; and cellular system design, 507; and multiuser spread-spectrum systems, 432
- interference signal, and spread spectrum, 405
- interleaving, and coding for fading channels, 267–71, 381. *See also* bit-interleaved coded modulation; symbol-interleaved coded modulation
- International Mobile Telephone (IMT-2000) standard, 599
- International Telecommunications Union (ITU), 13, 21, 22, 599
- Internet: growth in use of, 6; and quality of service concerns, 553
- Internet protocol (IP), and ad hoc wireless networks, 542–3
- intersymbol interference (ISI): and digital modulation, 195–7; and equalization, 351; and maximal linear codes, 416–17; spread spectrum and rejection, 406–7; and wideband fading models, 83. *See also* ISI-free transmission
- intracell interference: and cellular phone systems, 11; and cellular system design, 507
- inverse FFT (IFFT), and multicarrier modulation, 383
- invertible matrix, 592
- IS-54 standard, 596
- IS-95 standard, 596–7, 598, 599
- ISI. *See* intersymbol interference
- ISI-free transmission, and folded spectrum, 354–7
- ISM bands, for WLANs, 15
- iterative decoding. *See* turbo codes
- J-Phone 3G system, 600
- Japan: and cellular phone systems, 12, 13, 595, 597–8, 600; and cordless phone systems, 15
- joint source, and channel code design, 274–5
- Kasami codes, and multiuser DSSS systems, 426, 431
- Kronecker product, 593
- Kumar, P. R., 556
- Lamarr, Hedy, 407n1
- Laplace transforms, and moment generating functions, 187
- large-scale propagation effects, and path loss, 27
- lattice coded modulation, 264, 265, 266
- LDPC. *See* low-density parity-check codes
- least mean square (LMS) algorithm, and equalizer training and tracking, 367–8
- left singular vectors, 593
- level crossing rate, and narrowband fading models, 79–81
- linear block codes, and code design, 230–46, 262

INDEX

639

- linear equalizers, 353, 357–62
- linearly independent set, of matrix rows or columns, 591
- linear modulation, 127
- linear path loss, 31
- line-of-sight (LOS) channel, 31, 34
- link layer, and physical layer design for ad hoc wireless networks, 543
- link state routing, and network layer design, 549
- local mean attenuation (LMA), and path loss, 42
- local mean received power, and path loss from ray-tracing models, 41
- local multipoint distribution service (LMDS), 17
- Lodge, Oliver, 28
- log likelihood ratio (LLR), and turbo equalizer, 365
- log-normal random variable, and shadowing, 49
- log-normal shadowing, 48–9
- long spreading code, 416
- low-density parity-check (LDPC) codes, and code design, 262
- low-earth orbit (LEO) satellite systems, 4, 18–19
- lower triangular matrix, 588

- m*-sequences, and spreading codes, 414–16
- Mackay, D. J. C., 262
- macrocells, 9
- macrodiversity, 204
- MANs. *See* metropolitan area networks
- Marconi, Guglielmo, 1–2, 28
- Marcum *Q*-function, and diversity analysis, 224
- Markov model, and Rayleigh fading, 74
- matched filter: and direct-sequence spread spectrum (DSSS), 410; signal space analysis and receiver structure, 136–7
- matrices: definitions, operations, and properties of, 588–94; and representation of OFDM, 388–90
- matrix. *See* generator matrix; Hadamard matrix; parity-check matrix
- maximal linear codes, 415, 416–17
- maximal-ratio combining (MRC), and diversity analysis, 214–16, 221–4
- maximum a posteriori (MAP) equalizer, 365
- maximum likelihood decision criterion, and signal space analysis, 134–7
- maximum likelihood decoding, and code design, 239, 249–51, 272–3
- maximum likelihood (ML) detection, and pairwise error probability, 337–9
- maximum likelihood phase estimation, 163–5
- maximum likelihood receiver, 135–6
- maximum likelihood sequence estimation (MLSE), and equalization, 353, 362–4
- maximum likelihood timing estimation, 165–7
- Maxwell, James Clerk, 28
- Maxwell's equations, 28–9
- medium-earth orbit (MEO) satellite systems, 4
- metropolitan area networks (MANs), 540
- microcells, 10
- military, and ad hoc wireless networks, 535, 536, 538
- MIMO. *See* multiple-input multiple-output systems
- minimum distance, of signal constellation, 140
- minimum distance decoding, and hard decision decoding, 238–9
- minimum free distance, of convolutional codes, 254
- minimum mean-square error (MMSE) detector, 440
- minimum mean-square error (MMSE) equalizer, 357, 358–62
- minimum rate capacity: and downlink channel capacity, 482; and uplink channel capacity, 489
- minimum-shift keying (MSK), and frequency modulation, 155
- mobile telephone switching office (MTSO), 10
- mobility, and routing protocols, 550
- modulation, and energy constraints for ad hoc wireless networks, 559–60. *See also* adaptive modulation; BPSK modulation; coded modulation; coherent modulations; constant envelope modulation; differential modulation; digital modulation; DPSK modulation; general *M*-ary modulation; linear modulation; multicarrier modulation; nonlinear modulation; passband modulation; pulse amplitude modulation; QPSK modulation; quadrature amplitude modulation; unitary space-time modulation
- moment generating function (MGF): and average error probability, 187–91; and diversity analysis, 220–5; and random variables, 580
- Morse, Samuel, 1
- MPAM. *See* pulse amplitude modulation
- MPSK. *See* phase-shift keying
- MQAM. *See* quadrature amplitude modulation
- MUD. *See* multiuser detector
- multicarrier CDMA (MC-CDMA), and direct-sequence spread spectrum, 441–3
- multicarrier modulation: and data transmission, 375–8; definition of, 374; and discrete implementation, 383–93; frequency and timing offset in, 395–6; and overlapping subchannels, 378–80; and peak-to-average power ratio, 393–5; and subcarrier fading, 380–3
- multicarrier transmitter, 375–6
- multichannel multipoint distribution services (MMDS), 17
- multihop routing, and ad hoc wireless networks, 535, 541
- multilevel encoder, 272–3
- multipath channels: characteristics of, 64; and discrete-time model, 92–3; and frequency-hopping spread spectrum (FHSS), 422; and narrowband fading models, 70–82; and space-time channel models, 93–4; and time-varying channel impulse response, 65–70; and wideband fading models, 82–92
- multipath intensity profile, and wideband fading models, 86–8
- multipath routing, and network layer design, 550
- multipath signal components, and ray tracing, 33
- multiple access: and cellular system design, 506–7; and code-division multiple access, 458–9; and frequency-division multiple access, 455–6; hybrid techniques for, 460–1; primary methods of, 452, 454–5; and space-division multiple access, 459–60; and time-division multiple access, 456–7. *See also* multiuser systems

- multiple access channel (MAC), 469
- multiple access interference (MAI), and multiuser DSSS systems, 438–41
- multiple antennas: and downlink channel capacity, 483–4; and uplink channel capacity, 490
- multiple description coding (MDC), and application layer design, 553
- multiple-input multiple-output (MIMO) systems: and ad hoc wireless networks, 560–1; and channel capacity, 325–34; and channel equalization, 342; definition of, 321; diversity gain and beamforming, 334–5; and diversity–multiplexing trade-offs, 335–7; and frequency-selective MIMO channels, 342–3; and IEEE 802.11n wireless LAN standard, 602*t*; and multiuser systems, 496–7; and narrowband MIMO channel model, 321–3; and parallel decomposition of channel, 323–5; and smart antennas, 343–4; and space-time codes, 337–42
- multiple-input single-output (MISO) channels, 327
- multiplexing gain, and multiple-input multiple-output systems, 323–7, 496
- multislope model, of path loss, 44–5
- multistage decoding, 273
- multiuser detection: and direct-sequence spread spectrum (DSSS), 438–41; and interference reduction, 520
- multiuser detector (MUD), 438–41, 459
- multiuser diversity, 480, 494–6
- multiuser systems: definition of, 452; and downlink channel capacity, 469–84; and DSSS, 424–43; and FHSS, 443; and multiple access, 454–61; and multiple-input multiple-output systems, 496–7; and multiuser diversity, 494–6; and power control, 466–9; and random access, 461–6; uplink and downlink channels for, 452–4; and uplink–downlink duality, 490–4; and uplink channel capacity, 484–90. *See also* multiple access
- mutual information: and capacity in AWGN, 100–1; and multiple-input multiple-output channels, 328
- Nakagami fading: and capacity of flat fading channels, 115*f*; and digital modulation, 186–7; and multipath channels, 79
- narrowband AMPS (N-AMPS), 595
- narrowband fading models, 70–82
- narrowband interference, and spread spectrum, 405
- narrowband MIMO model, 321–3
- Neal, R. M., 262
- near–far effect: and code-division multiple access systems, 488–9; and uplink channels for multiuser DSSS systems, 433, 437
- nearest neighbor approximation, and signal space analysis, 140
- negative coding gain, 240
- neighbor discovery, and network layer design, 547–8
- network capacity limits, and ad hoc wireless networks, 556–8
- network coding, and network layer design, 551
- network layer design, and ad hoc wireless networks, 547–52
- noise enhancement, and equalization, 351, 352–3
- noise-whitening filter, and minimum mean-square error equalizer, 359–60
- nonbinary block codes, 245–6
- noncoherent detection, of FSK, 156–7
- non–decision-directed parameter estimation, and digital modulation, 165
- noninvertible matrix, 592
- nonlinear equalizers, 353
- nonlinear modulation, 127
- nonlinear multiuser detectors, 440–1
- nonnegative definite matrix, 593
- nonorthogonal codes: and code-division multiple access, 458; and multiuser DSSS systems, 425, 475–6
- nonorthogonal systems, and cellular system design, 516–18
- nonsingular matrix, 592
- Nordic Mobile Telephone (NMT) standard, 595
- norm, of vector, 589
- normal matrix, 590
- North American Digital Cellular standard, 596
- Nyquist criterion, 158
- observation interval, and receiver structure with carrier and timing recovery, 162
- OFDM. *See* orthogonal frequency division multiplexing
- off-diagonal elements, of matrix, 588
- Office of Spectral Management (OSM), 21
- Okumura model, 42–3
- OmniTRACS, 18
- open systems interconnect (OSI) network model, 452*n*₁, 542
- opportunistic beamforming, and multiple-input multiple-output systems, 497
- opportunistic scheduling, and multiuser diversity, 495
- optimal power allocation, and capacity of flat fading channels, 109–10
- orthogonal codes: and code-division multiple access, 458; and multiuser DSSS systems, 425, 428–9, 431, 474–5
- orthogonal frequency division multiplexing (OFDM): and hybrid techniques for multiple access, 460; and multicarrier modulation, 374, 385–90; and multiple-input multiple-output systems, 343
- orthogonal systems, and cellular system design, 514–16
- outage capacity: and multiuser fading channels, 478, 482; and truncated channel inversion, 112–13. *See also* capacity, of wireless channels
- outage probability: and capacity of flat fading channels, 105–6, 112–13; and digital modulation, 183–4, 191–2; of multiple-input multiple-output systems, 332–3; under path loss and shadowing, 52, 54
- overlapping subchannels, and multicarrier modulation, 378–80
- packet error rate (PER), 461, 544
- packet radio, 2, 461
- packet-reservation multiple access (PRMA), 466
- paging systems: overview of current systems, 17–18; and sleep periods, 562

INDEX

641

- pairwise error probability, and ML detection, 337–9
 parallel concatenated coding, 261–2
 parallel decomposition, of MIMO channel, 323–5
 parity-check matrix, and linear block codes, 234–5
 partial band noise jammer, and frequency-hopping spread spectrum, 423
 partition loss, and indoor path-loss models, 45–6
 passband modulation, 142
 path loss: and cell coverage area, 53–6; definition of, 27; empirical models of, 42–6; free-space, 31–2; and outage probability, 52; and radio wave propagation, 28–9; and ray tracing, 33–41; and shadowing, 28*f*, 51–2; and signal models, 29–31; simplified model for, 46–8
 path metric, and maximum likelihood decoding, 250–1
 peak-to-average power ratio (PAR), and multicarrier modulation, 393–5
 perfect code, 240
 Personal Access Communications System (PACS), 598
 Personal Communication Service (PCS), 598
 personal digital assistants (PDAs), and ad hoc wireless networks, 537
 Personal Digital Cellular (PDC) standard, 597–8
 Personal Handyphone System (PHS), 15, 598
 phase and timing recovery, and amplitude/phase modulation, 161–3
 phase-shift keying (MPSK), and amplitude/phase modulation, 143, 146–8, 176–9
 phased antennas, and multiple-input multiple-output systems, 343
 physical layer design, and ad hoc wireless networks, 543–4
 piecewise linear model, of path loss, 44–5
 Poisson processes, and random access, 461
 positive definite and semidefinite matrices, 593
 power constraints, and home network design, 538
 power control: and cellular system design, 522–4; and multiuser systems, 466–9
 power delay profile, and wideband fading models, 86–8
 power distributions, and narrowband fading models, 78–9
 power schemes, for variable-rate variable-power MQAM, 290–1
 power spectral density (PSD): and equalization, 352; and narrowband fading models, 71–7; and random processes, 584
 precoding, and multicarrier modulation, 381–2. *See also* Tomlinson–Harashima precoding; transmit precoding
 Price, Bob, 419*n*4
 private branch exchange (PBX), 14
 probability density function (pdf), 578
 probability theory, 577–8. *See also* error probability
 processing gain, and spread-spectrum systems, 405
 proportional fair scheduling, and multiuser diversity, 495–6
 protocol layers, of ad hoc wireless networks, 542–54
 PSD. *See* power spectral density
 pseudo-random sequence, and spreading codes, 414
 public switched telephone network (PSTN), 10
 pulse amplitude modulation (MPAM), 143, 144–6, 176–9
 pulse shaping, and digital modulation, 157–60
 puncturing, and adaptive coding, 288
 pure ALOHA, 462–3
Q-function representation, and digital modulation, 182
 QPSK modulation, and error probability, 173–5
 quadrature amplitude modulation (MQAM): definition of, 143, 148; and error probability, 176–9; and signal constellations, 148–9; variable-rate variable-power and adaptive modulation, 288–305
 quadrature component, and representation of bandpass signals, 573
 quadrature offset, and amplitude/phase modulation, 152–3
 Qualcomm, 18, 596
 quality-of-service (QoS): and ad hoc wireless networks, 550, 553–4; and dynamic resource allocation, 520; and home networks, 538
 quasi-convex function, and flow control for network layer design, 551
 radar cross-section (RCS), and radio wave propagation, 29
 radio(s) and radio communications: and device networks, 538; history of, 1–2; overview of current systems, 19–21; and spectrum, 7
 radio wave propagation, and path loss, 28–9
 Radiocom 2000 (RC2000), 595–6
 raised cosine pulses, and Nyquist criterion, 158
 RAKE receivers: and discrete-time model of multipath channels, 92, and spread spectrum, 403, 418, 419–21
 random access: definition of, 454; and energy constraints for ad hoc wireless networks, 561; and multiuser systems, 461–6
 random backoff, and carrier-sense multiple access, 464
 random processes, 583–6
 random sequences, and spread spectrum, 404
 random variables, 578–82
 rank criterion, and pairwise error probability for multiple-input multiple-output systems, 339
 rate-compatible punctured convolutional (RCPC) channel codes, 274–5, 288
 rate–delay trade-off curve, and application layer design, 554
 rate region, and multiuser channel capacity, 452, 469. *See also* capacity, of wireless channels
 ray-tracing techniques, and path loss, 29, 33
 Rayleigh fading: and adaptive MQAM, 299–300; and capacity of flat fading channels, 103, 112, 115*f*; and digital modulation, 185–7; and multipath channels, 74, 78–9; and receiver diversity, 210
 reactive routing, and network layer design, 549–50
 receiver(s): and capacity of flat fading channels with diversity, 113–14; and channel side information, 103–13; and diversity, 206–17; parallel decomposition of MIMO channel and shaping of, 323, 324; phase and timing recovery and structure of, 161–3; signal space analysis and structure of, 132–4. *See also* channel side information at receiver; maximum likelihood receiver; RAKE receivers

- rectangular pulses, and Nyquist criterion, 158
- reduced-complexity MLSE equalizers, 365
- Reed Solomon (RS) codes, 245–6, 259
- remote sensing, and sensor networks, 539
- rescue operations, and sensor networks, 539
- resource allocation, and network layer design, 551–2
- reuse distance: and cellular phone systems, 9; and cellular system design, 509–11
- reverse channel. *See* uplink channels
- rich scattering environment, and parallel decomposition of MIMO channel, 323
- Rician fading, 78–9, 194
- right singular vectors, 593
- routing protocols, for ad hoc wireless networks, 548–51, 561–2
- row vector, 589
- run-length property, of spreading code, 414
- satellite networks: history of, 4; overview of current systems, 18–19
- scalability, of ad hoc wireless networks, 541–2
- scattering functions, and fading models, 85, 91–2
- scatternets, 603
- scheduling: and dynamic resource allocation, 520–1; for multiuser systems, 466, 495–6
- second-generation (2G) digital systems, for cellular phones, 596–9
- second moment, and random processes, 583
- sectorization, and reduction of interference, 519
- sectorized antennas, and multiple-input multiple-output systems, 343–4
- security, and technical challenges for wireless systems, 7
- selection combining (SC), and diversity analysis, 204, 208–11, 224
- sensor networks, and ad hoc wireless networks, 538–9
- sequence estimators (SEs), and equalization, 353
- sequence space, and coded modulation, 264
- serial concatenated coding, 262
- shadowing: and cell coverage area, 53–6; and fading, 48–51; and outage probability, 52; and path loss, 28*f*, 51–2
- Shannon, Claude, 99, 100–1
- Shannon capacity: and coded modulation, 263; and flat fading channels 103–5, 107–11; and frequency-selective fading channels, 120; and fundamental rate limits, 524–5; and multiple-input multiple-output channels, 325–34
- shift property, of spreading codes, 414, 415
- short spreading code, 416
- signal combinations, and pre-industrial wireless networks, 1
- signal-to-interference-plus-noise power ratio (SINR), and ad hoc wireless networks, 540–1
- signal models, and path loss, 29–31
- signal-to-noise power ratio (SNR): and AWGN channels, 172–3; and path loss, 30
- signal space analysis, and digital modulation, 127–41
- signal space representation, 131
- signal and system model, and signal space analysis, 128–9
- simplified path-loss model, 46–8
- Singelton bound, and linear block code, 235
- single-bit parity-check code, 230–1
- single-input multiple-output (SIMO) channels, 327
- single-input single-output (SISO) channels, 323, 331–2
- singular matrix, 592
- singular value decomposition (SVD): and matrix decomposition, 593; and parallel decomposition of MIMO channels, 323; and vector coding for multicarrier modulation, 392
- SINR. *See* signal-to-interference-plus-noise power ratio
- sleep modes, and ad hoc wireless networks, 542, 559, 562
- slotted ALOHA, 463–4
- slow frequency hopping (SFH), and spread spectrum, 407
- small-scale propagation effects, and path loss, 27
- smart antennas: and interference reduction, 519; and multiple-input multiple-output systems, 343–4
- smart rooms, and home networks, 537
- smoke detectors, and sensor networks, 539
- SNR. *See* signal-to-noise power ratio
- soft decision decoding (SDD), 242–4
- soft handoff (SHO), and cellular phones, 597
- source coding, and unequal error protection codes, 274
- source-driven routing, and network layer design, 549
- space diversity, 204
- space-division multiple access (SDMA), 459–60
- space-time block codes (STBCs), 339
- space-time channel models, and multipath channels, 93–4
- space-time code, and multiple-input multiple-output systems, 337–42
- space-time trellis codes (STTCs), 339
- spatial multiplexing, and BLAST architectures, 340–2
- spectrum: cellular phone systems and sharing of, 11–12; ISI-free transmission and folded, 354–7; overview of issues in allocation of, 21–3. *See also* direct-sequence spread spectrum; Doppler power spectrum; frequency-hopping spread spectrum; spread spectrum
- spread spectrum: definition of, 403; direct-sequence spread spectrum, 409–21; frequency-hopping spread spectrum, 405, 407, 408–9, 421–3, 443; and multiuser DSSS systems, 424–43; principles of, 403–9
- spread-spectrum multiple access (SSMA), 424
- spreading codes: for ISI rejection, 413–17; for multiuser DSSS systems, 425–8; and spread-spectrum modulation, 403
- Sputnik*, 4
- standards: for cellular phone systems, 12–13; and IEEE, 23, 396–8, 601, 602; overview of current, 23–4; summary of, 595–603; for WLANs, 16
- state diagrams, and convolutional codes, 254–7
- static channels, and capacity of MIMO channels, 325–9
- statistical models, of radio wave propagation, 29. *See also* multipath channels
- steady state, and trellis diagrams, 248
- subcarrier fading, and multicarrier modulation, 380–3
- sublattice, and channel coding, 265
- submatrices, 589
- successive cancellation, and downlink channel capacity, 472

- sum-rate (SR) capacity, 473–4
- superposition code division, and downlink channel capacity, 469, 472, 473
- survivor path, and Viterbi algorithm, 252–3
- switch-and-stay combining (SSC), and receiver diversity, 211–13
- symbol-by-symbol (SBS) equalizers, 353
- symbol error: and fading, 182–3; and frequency-hopping spread spectrum, 422–3
- symbol interference cancellation, and spatial multiplexing for multiple-input multiple-output systems, 341
- symbol-interleaved coded modulation (SICM), 271
- symbol synchronization, and digital modulation, 160–7
- synchronization and synchronizers: and digital modulation, 144, 160–7; and direct-sequence spread spectrum, 410, 417–19; and frequency-hopping spread spectrum, 422. *See also* coarse synchronization
- Synchronous Connection Oriented (SCO), 19
- syndrome polynomial, and cyclic codes, 238
- syndrome testing, and linear block codes, 235
- system model, of receiver diversity, 206–8
- systematic linear block codes, 233, 237
- TDMA. *See* time-division multiple access
- Telecommunications Industry Association (TIA), 23
- telegraph, 1
- telephones. *See* cellular phones; cordless telephones
- telepoint service, 14
- television, and spectrum allocation, 22
- ten-ray model, of path loss, 37–8
- tessellating cell shape, 508, 511
- Third Generation Partnership Project 2 (3GPP2), 599
- third-generation systems, of cellular phones, 599–600
- Thitimajshima, P., 259
- 3G standard, for cellular phone systems, 13
- threshold diversity, and receiver diversity, 211–13
- throughput, of random access, 462
- time diversity, and independent fading paths, 206
- time division: and downlink channel capacity, 469; and uplink channel capacity, 486–7
- time-division duplexing (TDD), 454
- time-division multiple access (TDMA), 11, 456–7, 460, 514–16, 521
- time-invariant channels, and capacity of frequency-selective fading channels, 116–19
- time-multiplexed coding method, for unequal error protection codes, 273–4
- time-varying channels: and capacity of frequency-selective fading channels, 119–21; and impulse response of multipath channels, 65–70
- timing offset, and frequency of multicarrier systems, 395–6
- timing recovery, and amplitude/phase modulation, 144
- Tomlinson–Harashima precoding, 366
- Total Access Communication System (TACS), 12, 595
- total offered load, and random access, 462
- traffic load, and random access, 461–2
- transfer functions, and state diagrams for convolutional codes, 254–7
- transmission control protocol (TCP), and ad hoc wireless networks, 542–3
- transmit power, and design of ad hoc wireless networks, 544, 545–6
- transmit precoding, and parallel decomposition of MIMO channels, 323, 324
- transmitters: and channel side information, 107–13; and diversity, 217–20
- transport layer design, and ad hoc wireless networks, 552–3
- trellis coded modulation, 264, 266, 267
- trellis coded quantization, 275
- trellis codes, and multiple-input multiple-output systems, 339
- trellis diagrams, and convolutional codes, 246–9
- truncated channel inversion, and outage capacity, 112–13
- turbo codes, and code design, 259–62
- turbo equalizer, 365–6
- turbo trellis coded modulation, 267. *See also* trellis coded modulation
- two-ray model, of path loss, 29, 34–7
- ultrawideband (UWB), 20–1, 601–3
- underlay systems, in spectrum allocation, 21–2
- unequal error protection (UEP) codes, and code design, 271–5
- Ungerboeck, G., 263
- uniform distribution, and random variables, 582
- uniform power allocation, and multiple-input multiple-output systems, 328–9
- uniform scattering environment, and narrowband fading models, 73–4
- union bound: and probability theory, 578; and signal space analysis, 137–41
- unit vector, 589
- unitary matrix, 592
- unitary space-time modulation, for block fading channels, 339
- Universal Mobile Telecommunications System (UMTS), 600
- unlicensed bands, and spectrum allocation, 21, 23*t*
- Unlicensed National Information Infrastructure (U-NII) bands, 15
- uplink channels, and multiuser systems, 424–5, 433–8, 443, 452–4, 484–94
- upper triangular matrix, 588
- V-BLAST, 341
- variable-coding techniques, and adaptive modulation, 288
- variable error probability, and adaptive modulation, 287
- variable-power techniques, for adaptive modulation, 286–7
- variable-rate techniques, for adaptive modulation, 285–6
- variable-rate variable-power MQAM, 288–305
- vector(s), definitions and operations of, 588–92
- vector codeword, 392
- vector coding (VC), and multicarrier modulation, 390–3
- vectorization, of matrix, 593
- Verdú, S., 438

- vertical encoding, and multiple-input multiple-output systems, 341
- Viterbi, A. J., 252
- Viterbi algorithm, and convolutional codes, 252–3
- voice activity factor, and code-division multiple access systems, 518
- Walsh–Hadamard codes, and multiuser DSSS systems, 427–8
- WANs. *See* wide area networks
- water-filling formula, and capacity of wireless channels, 109–10, 120–1, 326–7, 330
- white noise, and random processes, 584–5
- Wiberg, N., 262
- wide area networks (WANs), and ad hoc wireless networks, 540
- wide area wireless data services, overview of current systems, 16–17
- wideband CDMA (W-CDMA) standard, 599, 600
- wideband fading models, and multipath channels, 82–92
- wide-sense stationarity (WSS), and random processes, 584
- WiFi (wireless fidelity), 601
- WiMax, 17
- windows, and penetration loss in indoor systems, 46
- wireless communications: adaptive modulation and coding, 283–315; and ad hoc wireless networks, 535–64; and capacity of wireless channels, 99–121; and code design, 228–75; definition of, 5–6; and digital modulation, 126–67, 172–97; and diversity, 204–25; and equalization, 351–68; growth in use of, 1; history of, 1–4; and infrastructure-based wireless networks, 505–28; and multicarrier modulation, 374–98; and multiple-input multiple-output systems, 321; and multiuser systems, 452–97; overview of current systems, 8–21; and path loss, 27–56; and spectrum allocation, 21–3; and spread spectrum, 403–43; and standards, 23–4, 595–603; and statistical multipath channel models, 64–94; technical challenges of, 6–8; vision of, 4–6
- wireless local area networks (WLANs): and ad hoc wireless networks, 537; growth in use of, 1; history of, 2–3; overview of current systems, 15–16; and standards, 24, 396–8, 600–1
- wireless metropolitan area networks, and ad hoc wireless networks, 537, 540
- Wireless Personal Area Networks (WPANs), 602
- wireless short-distance networking standards, 601–3
- WLANs. *See* wireless local area networks
- worst-case interferers, and intercell interference, 519–20
- WPANs. *See* Wireless Personal Area Networks
- Wyner, A., 524
- zero-forcing (ZF) equalizers, 357–9
- zero-mean, circularly symmetric complex Gaussian (ZMCSCG) random vector, 326
- zero-mean spatially white (ZMSW) model, and multiple-input multiple-output channels, 322, 328–9, 331–2
- zero-outage capacity: and flat fading channels, 111–12; and multiuser fading channels, 478
- ZigBee, 20, 601–3
- zone routing protocol (ZRP), 550