

Index

- absorption filter, 365
- acousto-optic filter, 364
- active components, 357
- acyclic network, 391
- adjacency matrix, 390
- algorithm for finding all cycles, 82
- all-optical wavelength conversion, 11
- all-optical traffic grooming, 172
- all-to-all uniform traffic, 176
- alternate-path routing (APR), 17
- amplitude modulation, 379
- analysis of a multi-hop single wavelength path, 189
- analysis of single wavelength two-hop path, 188
- approaches to network design, 383
- a priori efficiency, 64
- arbitrary topology design, 413
- architecture-independent mapping, 276
- architecture-dependent mapping, 277
- arrayed waveguide grating, 366
- asynchronous transfer mode (ATM), 2, 13, 382
- ATM block transfer (ABT), 13, 31
- ATM burst switching, 31
- augmentation path, 405
- automatic design process, 384
- automatic sequential overlapping fault coverage, 165
- available shortest-path routing (ASPR), 296
- avalanche photodiodes (APD), 371
- average nodal connectivity, 81
- average path length, 120, 124, 301
- average redundancy, 81
- average shortest path length, 302
- backbone nodes, 175
- backup lightpath, 26
- backup multiplexing, 37, 46, 77, 89
- backup sharing in TSN, 250
- backward edge, 403
- base network, 161
- Bellman's equations, 394
- best-effort
 - class constraints, 92
 - protection, 39, 87, 91, 92
- best-fit
 - decreasing packing order, 340
 - increasing packing order, 340
- bidirectional line-switched ring (BLSR), 172
- binomial distribution, 386
- bit-error rates, 1
- blocking
 - in TSN, 261
 - networks, 406
 - performance, 78, 300
 - probability, 14, 120, 123
- Boltzmann's constant, 53
- Boolean cube, 412
- bottleneck link, 104
- breadth-first order, 402
- broadcast-and-select networks, 4, 5
- buffering technology, 30
- cable cost, 41
- cable TV, 5
- capacitated multi-commodity flow design problem, 316
- capacity
 - allocation, 67
 - fairness, 201, 203
 - minimization, 86–8, 96
 - planning, 39
 - utilization, 76, 81
- centralized restoration, 36
- centralized vs. distributed control, 36
- channel, 29
- channel access protocol, 6
- channel capacity, 185
- channel-space
 - switching, 242, 284
 - switch modeling, 273
- chromatic dispersion, 360
- circuit-switched network, 381
- circulator, 373
- closed walk, 391
- code-division multiplexing (CDMA), 379
- completely connected topologies, 409

- computing disjoint paths, 34
- connected component of a graph, 392
- connection admission control (CAC), 202, 206
- connection establishment in TSN, 243, 252
- connectionless service, 382
- connection-oriented service, 382
- connectivity information, 248
- connectivity of a graph, 392
- constrained grooming networks, 180, 295
- constrained minimum spanning tree, 401
- constrained sub-graph routing, 130, 163
- constraint for topological diversity, 90, 91
- cost model, 41
- couplers, 372
- coverage computation, 163
- cross-connect
 - constraint, 45
 - cost, 41
 - node architecture, 21
- cross-point switching element, 49
- cycle in a graph, 391
- cycle selection algorithms, 63
- cycle-based protection, 62
- data burst, 31
- degree, 390
- delays in networks, 386
- demand
 - constraint, 46, 90, 91
 - normalization technique, 93
- demultiplexors, 362
- dense network, 82
- depth-first search, 64, 402
- design and upgrade problem, 51
- detouring
 - end-to-end, 34
 - local, 34
- diameter of a graph, 391
- dielectric
 - constant, 360
 - thin-film filter, 363
- differentiated services (DiffServ), 4
- diffraction gratings, 366
- digging cost, 41
- Dijkstra's method, 395
- directed graph, 390
- dispersion-compensated fiber, 362
- dispersy routing, 298
- distance-vector protocols, 244
- distributed feedback laser, 368
- distributed routing in TSN, 244
- double-hub ring, 174
- dual-failure restorability, 166
- dual-link
 - failure coverage, 157, 159, 161
 - sub-graph routing, 161
- dynamic
 - programming, 394
 - routing, 17, 293
 - topologies, 411
 - traffic, 14, 178
- economy of scale, 49
- edge-emitting LED (ELED), 368
- edge-disjoint shortest path, 71
- effect of cost and technology trends, 50
- effect of dispersy routing, 303
- effect of grooming granularity, 221
- effect of number of alternate paths, 221
- effect of traffic grooming, 218
- effect of wavelength assignment and topology, 218
- effective utilization, 125
- electrical-to-optical (O-E-O) conversions, 16
- electronic switching, 9
- electro-optic filter, 365
- elimination test, 261
- end-to-end
 - delay, 385
 - detouring, 34
- enhanced hypercube, 412
- erbium-doped silica fiber, 369
- erbium-doped fiber amplifier (EDFA), 369
- European ACT KEOPS, 12, 30
- exponential distribution, 387
- extended Dijkstra's shortest path, 293
- external modulators, 370
- Fabry–Perot etalon filter, 363
- Fabry–Perot laser, 368
- facility cost, 42
- failure-dependent path restoration, 144
- fairness
 - analysis, 184
 - definition, 202
 - performance of RWA algorithms, 205
- fault tolerance, 26, 118, 385
- fiber Bragg gratings, 365
- fiber cost, 41, 42
- fiber delay lines, 29
- fiber dispersion, 360
- fiber loss, 362
- fiber nonlinearities, 361
- fiber optic cables, 357
- find all cycles (G), 82
- first-fit (FF), 19, 20
- fixed alternate-path routing, 216, 243
- fixed-path least-congestion routing (FPLCR), 243
- fixed-path routing, 10, 17, 186
- fixed-wavelength conversion, 11
- flow control algorithms, 381
- Floyd–Warshall method, 398
- forward edge, 403
- forward error correction, 42
- four-wave mixing (FWM), 361
- free and busy trunks, 241
- frequency modulation, 379
- frequency-division multiplexing, 379
- full information restoration (FIR), 38
- full permutation switching, 242, 282
- full protection, 39, 87, 91
- full-channel interchanger (FCI), 241
- full-channel permutation switch, 273
- full-wavelength conversion, 11

- generalized folding cube, 412
- generic circle grooming algorithms, 177
- GMPLS network, 37
- graph algorithms, 393
- graph model for network, 390
- graph representations, 390
- greedy algorithms, 384
- grooming analysis of single wavelength link, 187
- grooming connection setup and release, 180
- grooming factor, 194
- grooming granularity, 185
- grooming policy, 215
- grouping of channels, 239

- Hamiltonian cycle, 63
- Hamming distance, 411
- helical cube, 413
- heterogeneous grooming networks, 241
- heterogeneous switch architecture model, 274
- heuristic methods, 51, 177, 382
- hierarchical network, 378
- hierarchical ring, 174
- homogeneous grooming networks, 241
- hop-length constraint, 317
- hub ring, 174
- hypercube, 411

- incidence matrix, 390
- incremental costs, 59
- incremental ring, 175
- in-degree, 390
- insertion loss, 5
- installation costs, 48
- instant redundancy (IR), 67
- integer programming problem (IPP), 382
- internal modulators, 370
- Internet, 1
- internet protocol (IP), 1
- IP over WDM, 309–17
- isolators, 373

- just-enough-time (JET), 13, 32
- just-in-time (JIT), 13, 32

- K* disjoint permutation, 407
- K* generalized shortest cycles, 54
- knapsack problem, 338
- Kruskal algorithm, 400
- K*-shortest paths, 341

- label edge router (LER), 311
- label switch path (LSP), 311
- laser, 367
- leasing cost, 41
- least-congestion routing (LCR), 17
- least-loaded routing (LLR), 25, 70
- least-used wavelength assignment, 20
- length of a light trail, 350
- light-emitting diode, 368
- light propagation, 358
- light sources, 367

- light trail, 330
 - characteristics, 333
 - design, 334
 - protection, 348
 - restoration, 347
- lightpath, 7
- limited grooming capability, 180
- limited-wavelength conversion, 10, 11
- line-speed, 185
- link capacity constraint, 45, 89
- link independence model, 189–90
- link information, 247
- link load, 121
- link provisioning
 - constraint, 45
 - cost, 41
- link-based restoration, 34
- liquid crystal Fabry–Perot filter, 365
- local area network, 5
- local detouring, 34
- long-term reconfiguration, 86, 87
- loss probability, 385
- low-rate traffic stream, 169
- LP
 - heuristic algorithm, 110
 - relaxation technique, 102, 103

- M/M/m queue, 389
- Mach–Zehnder
 - filter, 363
 - modulator, 371
 - interferometer grating, 366
- managing large networks, 102
- managing multiple link failures, 143
- managing online reconfiguration, 88
- manual design process, 384
- Markov process, 187
- Markovian correlation, 266
- material dispersion, 360
- maximum communication delay, 391
- medium-term reconfiguration, 86
- meshes, 411
- MICRON framework, 243, 247
- minimize link-primary-sharing (MLPS), 225
- minimum spanning tree (MST), 399
- minimum sum (MS), 25
- mixed grooming policy, 217
- modal dispersion, 359
- modeling switches in TSN, 273
- modes, 359
- modulators, 370
- Monte Carlo approach, 51
- most-free routing (MFR), 70
- most-used wavelength assignment, 20
- multi-failure protection, 143–55
- multi-fiber networks, 10, 23
- multimode fiber, 358
- multimode graded index fiber, 359
- multiple rings, 62
- multiple shortest paths, 399
- multiplexors, 362

- multi-protocol label switching (MPLS), 4
- multi-protocol lambda switching, 311
- multi-stage interconnection network (MIN), 43
- mutation scheme, 57
- network (Max) flow, 403
- network and fault model, 127
- network control and management, 87
- network design, 14, 377
- network evolution, 56
- network flow analysis algorithm, 403
- network management techniques, 381
- network model, 15
- network operation, 86
- network redundancy (NR), 67
- network topology, 377, 385
 - design, 408
- network upgrade, 55
- network utilization, 121, 300
- no protection, 39, 87, 91
- node connectivity of a graph, 392
- node-based subgraph routing, 130
- non-overlapping traffic demands, 177
- non-zero dispersion-shifted fiber, 362
- normal distribution, 386
- OAM channel, 38
- optical add/drop multiplexers, 7, 374
- optical amplifiers, 7, 369
- optical burst switching, 1, 31
- optical channel routing, 3
- optical couplers, 4
- optical cross-connect (OXC), 7, 16
- optical fibers, 362
- optical filters, 362
- optical modules, 357
- optical network components, 357
- optical packet switching, 12, 30
- optical pump, 369
- optical shutter, 331
- optical switches, 374
- optical terminating equipment, 16
- optical trail, 330
- optical transmsion, 2
- optimal set of p-cycles, 68
- optimization problems, 14
- opto-electronic wavelength conversion, 11
- out-degree, 390
- overprovisioning, 50
- packet-switched network, 381
- partial information restoration (PIR), 38
- passive component, 4, 357
- path in a graph, 391
- path information, 250
 - vector, 253
- path-selection algorithms, 243, 253, 296
- path-based restoration, 34
- p-cycle-based design for dynamic traffic, 66
- permutation, 407
- permutation routing, 407
- phase modulation, 379
- photodetectors, 371
- physical topology, 314
- point-to-point WDM ring, 174
- polarization mode dispersion (PMD), 361
- positive intrinsic negative photodiodes (PIN), 371
- power equilization, 42
- precomputed paths, 36, 38
- preconfigured protection cycles (p-cycles), 37, 62, 71
- preprocessing step for light trail design, 335
- preselection heuristic, 66
- pre-wavelength set assignment, 104
- Prim's algorithm, 400
- primary lightpath, 26
- primary path wavelength usage constraint, 46, 89
- primary-backup multiplexing, 28
- primitive rings, 177
- principle of optimality, 394
- pro-active restoration, 34
- pro-active subgraph fault tolerance, 167
- probability distributions, 386
- probability of path reassignment, 121
- processing time delay, 388
- propagation characteristics, 360
- propagation delay, 388
- protected working capacity envelopes, 66
- public switched telephone network (PSTN), 1
- quality of service (QoS), 382, 385
- queuing
 - delay, 388
 - models, 389
 - theory, 386
- Raman amplifiers, 370
- random shuffling, 52
- random wavelength assignment, 19
- Rayleigh scattering, 362
- reactive restoration, 34
- reactive subgraph fault tolerance, 167
- rearrangeable networks, 406
- reconfigurable topologies, 412
- recovery, 26
- refractive index, 360
- regenerators, 42
- regular topologies, 408
- rejection probability for fairness, 209
- relative capacity loss (RCL), 25
- relaxation methods, 103
- reliability and scalability, 31
- repeaters, 373
- resource assignment in TSN, 244
- resource reservation protocol (RSVP), 4
- restoration, 26
 - guarantee, 27, 39
 - method, 34
 - model, 38
 - time, 26
- retiming elements, 32
- revenue maximization, 86, 97, 98
- right-of-way cost, 41

438

rings and multi-rings, 410
routing algorithms, 17, 18, 70, 406
RWA algorithms, 172

segregated grooming policy, 217
segment-based restoration, 34
selecting a set of p-cycles, 67
self-phase modulation (SPM), 361
semiconductor optical amplifier, 369
shared backup path protection (SBPP), 80
shared mesh restoration, 37
shared risk link group (SRLG), 127
shared-wavelength TDM (SW-TDM), 30
sharing backup capacity 214
shortest path, 391–5
shortest-cycle approach, 35
shortest-path restoration (SPR), 38
shortest-widest path routing (SWPR), 296
short-term reconfiguration, 86
shuffling of request demands, 53
signal format, 3
signal regeneration, 7
signal-to-noise ratio, 23
simplex method, 382
simulated annealing, 51–9
single-link failure 210
single-mode fiber, 358
sink capacity, 377
solving for excess demands, 110
source capacity, 377
source routing in TSN, 244
sparse grooming networks, 180, 194, 294
star and tree topologies, 410
static routing, 17
static traffic grooming in rings, 173
static traffic matrix, 14
stationary probability, 187
stimulated Brillouin scattering (SBS), 361
stimulated Raman scattering (SRS), 361
store and forward operation, 381, 406
straddling link algorithm, 65
strictly non-blocking networks, 406
strongly connected graph, 392
subgraph shadowing, 141
subgraph-based protection strategy, 116
subgraph-based routing, 28, 117, 166
subtrunk, 247
 assignment in TSN, 254
subwavelength service, 169
surface-emitting LED (SLED), 368
survivability, 25
survivable light trail design, 350
survivable traffic grooming 210
synchronous control, 6
synchronous digital hierarchy (SDH), 2
synchronous optical networks (SONET), 2

tell-and go (TAG), 13, 31
tell-and-wait (TAW), 13, 31
thermalization, 52
time-division multiplexing (TDM), 2, 379

Index

time-slot interchanger (TSI), 29
topology sparsening effect, 47
total facility cost (TFC), 43
total internal reflection, 359
total spare capacity, 76
total working capacity, 77
traffic aggregation algorithm for IP over WDM, 318
traffic control and network management, 381
traffic grooming
 in WDM networks, 28, 169
 in WDM rings, 173
traffic stream
 multiplexing 211
 path 211
 switching, 169, 201
transit wavelength, 175
transmission delay, 388
transmission speed, 3
transmission technology, 379
transport networking, 3
tree traversal, 402
trunk, 237
trunk grooming node, 258
trunk-switched networks, 236
tunable receiver scheme, 6

ultra-long haul WDM networks, 169
undirected graph, 390
unidirectional path-switched ring (UPSR), 170
uniform traffic pattern, 176
unit line-speed, 186
upgradeable network design, 38, 39
upgraded network, 48

validation of the TSN model, 280
vertical cavity surface-emitting lasers (VCSELs), 368
virtual topology, 314

walk in a graph, 391
waveguide dispersion, 360
wavelength add/drop multiplexers (WADMs), 16
wavelength assignment, 18
wavelength capacity correlation model, 189–90
wavelength chirping, 368
wavelength continuity constraint, 9, 10, 71
wavelength conversion, 9, 20, 22, 30, 376
wavelength-division multiplexing, 2
wavelength drift, 367
wavelength grooming cross-connects (WGXC), 178
wavelength interchanger (WI), 11
wavelength routing, 7
wavelength-level grooming networks, 294
wavelength-routed networks, 8
wavelength-selective (WS) network, 11
wavelength-selective cross-connects (WSXC), 178
WDM-TDM switch, 29
widest-shortest path routing (WSPR), 296

zero-dispersion wavelength, 362
z-link path model, 264