

Index

- A-law, 28, 159
- A/D converter, *see* analogue-to-digital conversion
- AC coefficient, of DCT, 197
- accumulator, 305
- adaptive delta pulse-code modulation, 157
- adder, 313
- additive noise, 111
- additive white Gaussian noise, 112, 276
- ADPCM, *see* adaptive delta pulse-code modulation
- aliasing, 11, 16
 - in audio, 21, 150
 - in images, 184
 - in video, 232
- ALU, *see* arithmetic logic unit
- AM, *see* amplitude modulation
- amplitude, 43
- amplitude modulation, 254
 - receiver, 255
- analogue electronics, 5, 100, 150, 256
- analogue-to-digital conversion, 25, 173
 - non-ideal, 32
 - timing, 33
- angle, represented by complex number, 7
- aperture, 32, 35
- application-specific integrated circuit, 307
- architecture, processor, 302
- argument, 7, 43
- arithmetic logic unit, 306
- artefact
 - from aliasing in video, 233, 236, 238
 - when compressing an image, 200, 202
 - when filtering an image, 187, 209
 - when scaling an image, 209
- ASIC, *see* application-specific integrated circuit
- audio, 5, 21, 149
 - bits per sample, 30, 151, 175
 - compression, 154
 - processing in the frequency domain, 152
 - frequency resolution, 152
 - time resolution, 152
 - quantisation, 28, 33
 - sample rate, 149
 - telephone, 28, 30
- autocorrelation, 76, 293, 298
- automatic gain control, 144, 260, 285
- average
 - decaying, *see* filter, decaying-average
 - moving, *see* filter, moving-average
 - of points in untwisted frames, 42
 - of sample values, 64
 - weighted, of angles, 9
- AWGN, *see* additive white Gaussian noise
- backwards motion, apparent, 15, 22
- band-pass filter, *see* filter, band-pass
- Barker sequence, 293, 298
- base station, for mobile telephony, 296, 298
- baseband, 263, 275
- basis function
 - of one-dimensional discrete cosine transform, 195
 - of one-dimensional Fourier transform, 44
 - of two-dimensional discrete cosine transform, 196
 - of two-dimensional Fourier transform, 183
- Bayer pattern, 227
- Bayes' theorem, 109, 172, 225
- Bayesian, 104
- bearing, 9
- belief, 105
- bias, in exponent of floating-point number, 140
- big-endian, 314
- binary phase-shift keying, 269, 277
 - in DSSS, 292
- binary point, 124
- biquad section, 97
- bit reversal, 61, 305
- bit-serial
 - addition, 313
 - arithmetic, 313
 - FIR filter, 316
 - multiplication, 314
 - multiplication by constant, 316
- bitstream conversion, 172
- block, 242, 243
 - intra-coded, 249, 250
- block diagram, 7

330

block floating point, 142
 block matching, 242, 251
 block size for audio processing, choice of, 152
 blockiness, in JPEG-compressed images, 201
 BPF, *see* filter, band-pass
 BPSK, *see* binary phase-shift keying
 brightness, 214
 bubble, in pipeline, 303
 burst error, 287, 289
 butterfly, 56

cache, 305
 capacitor, 9
 carrier lock, 276
 in BPSK, 278
 in OFDM, 291
 in QPSK, 279
 carrier wave, 260, 267, 275
 in AM, 254
 in OFDM, 291
 carry, 313
 CD, *see* compact disc
 CDMA, *see* code division multiple access
 centre frequency, 63, 254, 256, 268
 centre of gravity, 38
 cepstrum, 169
 channel, 253
 channel state information, 291
 channel width, 253
 chip, *see also* integrated circuit
 in DSSS, 292
 chrominance, 178, 198, 232, 264
 clamping, 126
 clipping, 30, 126, 143
 clock speed and power, 320
 closing, of bilevel image, 218, 229
 CMOS, *see* complementary metal-oxide semiconductor
 code division multiple access, 296
 coded orthogonal frequency-division multiplexing,
 see orthogonal frequency-division multiplexing
 coefficient
 Fourier, 42
 of filter, 64
 direct calculation, 80, 94
 negative, 79
 COFDM, *see* orthogonal frequency-division multiplexing
 coherence, 276
 colour difference, 178
 communications, 253
 compact disc, 22, 30, 35, 149, 175
 compander, 29
 compass, 9
 compilation, just-in-time, 301
 compiler, 300, 301
 complementary metal-oxide semiconductor,
 320
 complex
 arithmetic, 60
 conjugate, 44, 62
 complex number, 6

Index

representing angle, 7
 rotation, 42
 compression
 JPEG, 198
 MP3, 159
 MPEG-2, 246
 of audio, 154
 of data, 5
 of images, 198, 209
 of video, 246
 compression, of range of signal values, 29
 conditional probability, 107
 constellation diagram, 266
 rotation of, 277
 constraints on system design, 299
 continuous-phase frequency-shift keying, 271
 contrast enhancement, 30, 213
 convergence, quadratic, 145
 convolution, 102
 and long multiplication, 102
 as commutative operation, 70
 circular, 75
 fast, 75, 102
 one-dimensional, 68, 102
 one-dimensional, using Fourier transform, 102
 two-dimensional, 189, 226
 two-dimensional, using Fourier transform, 190
 correlation, 76, 293
 fast, 77, 193
 two-dimensional, 191, 225, 230, 242
 cosine wave, 46, 47
 Costas loop, 278
 CPFSK, *see* continuous-phase frequency-shift keying
 cross-correlation, 76, 296
 crosstalk, 254
 crystal set, 255
 CSI, *see* channel state information
 cutoff frequency, 63, 88, 90, 211, 213

D, in block diagrams, 8
 D/A converter, *see* digital-to-analogue conversion
 DAB, *see* digital audio broadcasting
 DBPSK, *see* differential binary phase-shift keying
 DC coefficient, of DCT, 197
 DC component, 43
 DC gain of a filter, 66, 81, 134
 DCT, *see* discrete cosine transform
 decimation, 53, 86
 decision feedback, for carrier lock, 280
 decomposition, of Fourier transform, 55
 dedicated signal processor, 305
 deinterlacing, 234
 frequency domain analysis, 237
 delta pulse-code modulation, 155, 176
 delta-sigma conversion, 172, 177
 demodulation, 254
 desktop processor, 302
 detail, 203
 differential binary phase-shift keying, 286
 differential coding, 286, 297
 differential quadrature phase-shift keying, 286
 differentiator, 156

- digital audio broadcasting, 289
- digital versatile disc, 246, 305
- digital video broadcasting – terrestrial, 289
- digital-to-analogue conversion, 25, 259
 - delta-sigma, 173
 - timing, 33
- dilation
 - of bilevel image, 218
 - of greyscale image, 221
 - using convolution, 229
- diode, 256
- direct memory access, 307
- direct sequence spread spectrum, 292
- direct structure of FIR filter, 70
- discontinuity, 48, 82, 126, 193
- discrete cosine transform, 51, 163, 193
 - inverse one-dimensional, 195
 - inverse two-dimensional, 196
 - one-dimensional, 193, 307
 - two-dimensional, 195
 - using distributed arithmetic, 318
- discrete wavelet transform, 202, 227
 - one-dimensional, 202
 - two-dimensional, 207
- distortion, 144, 150, 175
 - due to quantisation, 28
 - multipath, 287, 291, 298
- distributed arithmetic, 316
- distribution, 111
 - double exponential (Laplace), 116
 - normal (Gaussian), 111
- dither, 30
- divide-and-conquer, 53
- dividend, 130
- division, avoiding, 130, 144
- divisor, 130
- DjVu, 217
- DMA, *see* direct memory access
- domain of a signal, 3
- Doppler effect, 276
- double exponential distribution, 116
- double-precision floating point, 140
- downconversion, 255
- downsampling, 86, 199, 209
 - by arbitrary ratio, 89
 - by integer ratio, 86
 - by simple fractional ratio, 88
 - of an image, 210
- DPCM, *see* delta pulse-code modulation
- DQPSK, *see* differential quadrature phase-shift keying
- DSSS, *see* direct sequence spread spectrum
- DTMF, *see* dual tone multi-frequency
- dual tone multi-frequency, 98
- dual-ported memory, 306
- DVB-T, *see* digital video broadcasting – terrestrial
- DVD, *see* digital versatile disc
- DWT, *see* discrete wavelet transform
- ear, human, 22, 149, 175
 - frequency sensitivity curve, 160
- early-late gate, 282, 294
- edge detection, 215, 221
- embedded system, 33, 300
- endianity, 314
- envelope, 256
- erosion
 - of bilevel image, 218
 - of greyscale image, 222
 - using convolution, 229
- error
 - covering up, 18, 23
 - systematic, in rounding, 132
- error correction, 276, 287–289
 - in OFDM, 290, 291
- events
 - independent, 106
 - intersection of, 105
 - mutually exclusive, 105
 - union of, 106
- excitation waveform, 167
- expansion, of range of signal values, 29, 213
- exponent, 139
- eye, human, 179, 198, 213, 233
 - response to luminance and chrominance information, 179
- fading, 287, 289, 298
- fast convolution, 75, 102
- fast Fourier transform, 53, 152, 305
 - of real signal, 57
 - operation count, 60, 226
 - speed, 58
- FFT, *see* fast Fourier transform
- field, 233
- field-programmable gate array, 307
- film, *see* movie; video
- filter, 63
 - anti-aliasing, 22, 25, 87, 150, 173, 209, 237
 - applied to complex signals, 100
 - band-pass, 63, 81, 161, 255
 - block diagram symbol, 8
 - decaying-average, 95
 - finite impulse response, *see* finite impulse response filter
 - for downsampling, 78
 - high-pass, 63, 81
 - infinite impulse response, *see* infinite impulse response filter
 - low-pass, 63, 81, 102, 187
 - matched, 76
 - median, 223, 238
 - moving-average, 64, 65
 - non-causal, 65
 - non-separable, 187, 226
 - pulse shaping, 267
 - reconstruction, 25
 - separable, 185, 226
 - two-dimensional, 185
 - for standards conversion, 240
 - two-dimensional, for standards conversion, 250
- filter bank, 161
- finite impulse response filter, 144
 - bit-serial, 316
 - block diagram, 70

332

finite impulse response filter (cont.)
 comparison with infinite impulse response filter, 99
 design, 77
 by exhaustive search, 134
 compromises, 82
 direct calculation of coefficients, 80, 94
 frequency domain analysis, 71
 time domain analysis, 66
 with complex coefficients, 101
 FIR filter, *see* finite impulse response filter
 fixed point, 124
 arithmetic using integer operations, 144
 comparison, 131
 comparison with floating point, 143
 digital oscillator, 268, 297
 discrete cosine transform, 307
 multiplication
 on general-purpose processors, 129
 on processors designed for signal processing, 128
 using integer operations, 144
 multiplication by constant, 311, 316
 range and precision, 125
 signed, 135
 two's complement representation, 138
 unsigned addition, 125
 unsigned division, 129
 with look-up tables, 131, 145
 unsigned multiplication, 127
 unsigned subtraction, 127
 flicker, 234, 250
 floating point, 9, 139
 arithmetic, 141
 block, 142
 comparison with fixed point, 143
 IEEE 754 special values, 140
 IEEE 754 standard, 140
 order of operations, 142, 146
 rounding, 142
 flute, 164
 FM, *see* frequency modulation
 Fourier coefficient, 42
 Fourier transform, 37, 166
 examples, 47
 in OFDM receiver, 292
 in-place calculation, 61
 inverse, 44, 62
 in OFDM transmitter, 291
 length of, 48, 59
 linearity, 61
 of an image, 180
 of real-valued signal, 44, 58, 59, 226
 periodicity, 43
 properties, 58
 two-dimensional, 180, 186
 FPGA, *see* field-programmable gate array
 fraction bit, 124
 fractional sample offset, 92, 177
 frame, 233
 frequency, 11
 negative, 15

Index

frequency band, 253
 frequency component, 42
 frequency domain, 37, 180
 frequency estimation, *see* pitch estimation
 frequency hopping, 288
 frequency masking, 160
 frequency modulation, 260
 receiver, 261
 frequency response
 of a one-dimensional filter, 73
 of a two-dimensional filter, 186
 frequentist, 104
 FT, *see* Fourier transform
 full adder, 313
 fundamental, 154

 gamma correction, 180
 garbage collection, 301
 gate delay, 320
 Gaussian minimum shift keying, 274
 Gaussian noise, 111, 113, 122, 276
 given, *see* conditional probability
 GMSK, *see* Gaussian minimum shift keying
 GOP, *see* group of pictures
 gradient, 215, 221
 graphic equaliser, 63, 152
 grid
 hexagonal, 19
 polar, 20
 group of pictures, 247
 GSM (Groupe Spécial Mobile or Global System for Mobile Communications) mobile telephony, 274, 289
 guard interval, 291

 half adder, 313
 Hamming window, 52, 59, 79, 103, 166, 188
 hard requirement, 299
 hardware implementations of signal processing algorithms, 307
 harmonic, 154, 166
 helicopter, 298
 heterodyne, 255, 261, 275
 heteroscedasticity, 115
 high-pass filter, *see* filter, high-pass
 histogram equalisation, 215, 229
 homodyne, 275
 hopping pattern, 288
 HPF, *see* filter, high-pass

 I, *see* in-phase component
 IC, *see* integrated circuit
 IEEE 754, *see* floating-point
 IEEE 802.11, *see* wireless Ethernet
 IF, *see* intermediate frequency
 IIR filter, *see* infinite impulse response filter
 image
 bilevel, 178, 217
 bits per sample, 30
 colour, 3, 10, 178
 compression, 198, 209
 continuous tone, 178

- enhancement, 213
- filtering, 185
- Fourier transform, 180
 - examples, 182
 - properties, 182, 229
- greyscale, 3, 10, 178
- medical, 30
- printing, 30
- processing in the frequency domain, 180
 - frequency resolution, 181
 - periodicity, 181
- rotation, 228
- scaling, 209, 212
- impulse, 66
- impulse response, 66
 - two-dimensional, 186
- in-phase component, 46, 263
- independence, 106
- infinite impulse response filter, 94
 - and pipelining, 100
 - comparison with finite impulse response filter, 99
 - frequency response, 96
 - stability, 96
- infinity, IEEE 754 floating-point representation, 141
- initial cost, of ASIC versus FPGA, 307
- integrated circuit, 6, 307
- integrator, 155, 174
- inter-symbol interference, 267, 297
- interference, 254, 269, 275, 276
 - destructive, 287
 - impulsive, 287, 294
 - inter-symbol, 267, 297
 - narrow-band, 287, 294
- interlace, 233
 - as compromise between vertical and temporal resolution, 234
 - conversion to progressive scan, 234
- intermediate frequency, 257
- interpolation, 18, 19, 83, 209, 227, 235, 266, 269–271
 - first-order, 18
 - linear, 18, 93
 - polyphase, 89
 - spatial for deinterlacing, 235
 - temporal for deinterlacing, 235
 - zero-order, 18
- interrupt service routine, jitter resulting from timing of, 33
- intonation, 164
- inverse discrete cosine transform, *see* discrete cosine transform, inverse
- inverse Fourier transform, *see* Fourier transform, inverse
- isotropic, 187, 209

- jaggies, 184, 209
- jamming, 287
- JBIG (Joint Bilevel Image Experts Group), 217
- jitter, 33, 35
 - in polyphase interpolation, 92
- JPEG (Joint Photographic Experts Group), 198, 248
- JPEG 2000, 202, 209

- kernel of a convolution, 69

- language
 - assembly, 301
 - general-purpose, 300
 - numerical simulation, 300
- Laplace distribution, 116
- latch, 309
- latency of pipelined operation, 303
- least significant bit, 124
- library, 300, 301
- likelihood method, 18, 170, 223
- likelihood ratio, 110
 - sensitivity to standard deviation, 115
- little-endian, 314
- LO, *see* local oscillator
- local oscillator, 256, 277, 297
- log-likelihood, 110
- logarithm, to express probability, 110, 118, 123
- logarithmic search, 245
- logical operations
 - on bilevel images, 217
 - on greyscale images, 221
- long wave, 259
- look-up table
 - and distributed arithmetic, 318
 - for division, 131, 145
 - for morphological operations, 222, 230
 - for sinewave generation, 268
 - in DPCM decoder, 155
 - in FPGA, 320
 - of squares, for multiplication, 322
- loop filter, 174, 262, 279
- lossless compression, 154, 176
- lossy compression, 154
- low-pass filter, *see* filter, low-pass
- low-power design, 320
- LPF, *see* filter, low-pass
- luminance, 178, 198

- MAC, *see* multiply–accumulate
- MAE, *see* mean absolute error
- magnitude, 7, 43
 - of filter frequency response, 73
- main data, 163
- mantissa, 139
- matched filter, 76
- mean
 - of double exponential distribution, 116
 - of normal distribution, 112
- mean absolute error, 244
- mean square error, 244
- median filter, 223, 238
- medium wave, 259
- merge sort, 53
- microcontroller, 302
- minimum shift keying, 272
- minus zero, 136, 141
- mixer, 255, 258
- model, 18, 170, 224
 - evaluating, 116
 - of noise, 115, 275, 291

model (cont.)
 parameters, 119
 perceptual, 160
 modulation, 254
 module, 7
 modulo, 145
 morphological gradient
 of bilevel image, 221
 of greyscale image, 222
 morphological operations
 on bilevel images, 217
 on greyscale images, 221
 using a look-up table, 222, 230
 using SIMD instructions, 304
 Morse code, 260
 motion
 in a circle, 15, 37
 sum of two circular motions, 39
 motion estimation, 241
 for deinterlacing, 239
 motion JPEG, 251
 motion vector, 242, 248, 251
 sub-pixel, 247
 movie, 4
 of motion in a circle, 37
 moving-average filter, *see* filter, moving-average
 MP3 (MPEG-2 layer 3) audio compression, 159
 MPEG (Moving Picture Experts Group), 159
 MPEG-1, 159
 MPEG-2, 159, 242, 246, 289
 MPEG-4, 242
 MSE, *see* mean square error
 MSK, *see* minimum shift keying
 mu-law, 28, 159
 multi-rate processing, 94
 multipath distortion, 287
 multiplicand, 128
 multiplier, 128
 multiply-accumulate, 305
 multiply-add, 305
 mutually exclusive events, 105

 NaN, *see* not-a-number
 narrow-band interference, 289
 near-far problem, 297
 neighbourhood, 222
 Newton-Raphson iteration, 145
 NICAM (near instantaneous companded audio multiplex), 22
 noise, 111, 275-277
 for dithering, 31
 noise shaping, 174
 noncoherence, 276
 normal distribution, 111
 normalisation of probability density function, 113
 normalised floating-point number, 139
 not-a-number, 141
 notation, 6
 NTSC (National Television Standards Committee), 232
 Nyquist limit, 16, 22, 25, 81, 149, 205, 226

oboe, 164
 octave, 149
 odometer, 126, 136
 OFDM, *see* orthogonal frequency-division multiplexing
 on-off keying, 260
 one-bit conversion, 172
 opening, of bilevel image, 218, 229
 operating system, 305
 orbit, 39
 orthogonal frequency-division multiplexing, 289
 receiver, 292
 transmitter, 291
 oscillator
 digital, 267
 local, 256
 overflow, 138, 146, 301, 321
 in fixed-point arithmetic, 126
 overlapping blocks, 152
 oversampling, 151, 172
 oversampling factor, 173

 PAL (Phase Alternation Line), 232
 partial product, 315
 pattern recognition, 223
 PDF, *see* probability density function
 pendulum, 15
 pepper noise, 218
 phase, 43
 of filter frequency response, 73
 phase accumulator, 268, 297
 phase comparator, 262
 phase correction, 54
 phase trellis, 273, 297
 phase-locked loop, 261, 279, 281
 piano, 164
 picture in MPEG-2 compression, 247, 251
 order of transmission, 250, 251
 pilot signal, 291
 pipeline, 302, 308
 and dependent operations, 303
 pitch estimation, 59, 163
 pixel
 faulty, 18, 23
 square, 180
 PLL, *see* phase-locked loop
 PN, *see* pseudo-noise
 polar coordinates, 20
 polyphase interpolation, 89, 103, 228, 282, 285
 combined with arbitrary filtering, 93
 two-dimensional, 209, 213, 229, 240
 posterior probability, 109
 power consumption, 299, 308
 dependency on clock speed and supply voltage, 320
 of desktop processor, 302
 power of 2, 53, 152, 311
 power spectrum, 76
 precision, machine, 9
 prior probability, 109
 probability, 104
 conditional, 107

- expressed using logarithms, 110, 118, 123
- posterior, 109
- prior, 109
- probability density function, 112
- processor architecture, 302
- product, 127
- programming language, *see* language
- progressive scan, 233
- pseudo-noise sequence, 293, 296
- pseudo-random, 288, 289

- Q, *see* quadrature component
- QAM, *see* quadrature amplitude modulation
- QPSK, *see* quadrature phase-shift keying
- quadratic convergence, 145
- quadrature, 264
- quadrature amplitude modulation, 263
 - in OFDM, 291
 - receiver, 274
- quadrature component, 46, 263
- quadrature phase-shift keying, 270, 277, 289
 - in DSSS, 293
- quality, 122
- quantisation, 113, 199
 - coarse, at high sample rate, 31, 151, 173
 - linear, 26, 33
 - logarithmic, 28, 34
 - non-linear, 28
- quantisation noise, 175
- quantiser, 157
- quantiser, inverse, 155
- quefrency, 169
- quotient, 130

- radar, 19
- random access to compressed video, 248
- range of a signal, 3
- ratio, simple, 13, 88
- real time, 299, 301
- reciprocal, 145
- reconstruction, 13, 25
- recording studio, 30
- rectification, 256
- reflection, 51, 193
- remainder, 145
- requirement, hard, 299
- resolution, 10
- resonator, 98
- rotation
 - of complex number, 42, 58
 - of frame, 41
 - of image, 228
 - of wheel, 13
- round-to-nearest, 132
- rounding, 132, 138, 145
 - of FIR filter coefficient values, 133
 - of IIR filter coefficient values, 134
- SAD, *see* sum of absolute differences
- salt noise, 218

- sample rate, 10
 - choice of, 16
 - conversion, 85
 - of an image, 180
- sample value, 10, 26
- sample, with non-integer offset, 90, 92
- sampling, 10
 - image, 10
 - irregular, 17, 225
 - non-rectangular, 233
 - spatial, 10
 - sub-Nyquist, 23, 35, 161, 205, 259
- saturation, 126
- scaling, of image, 209, 212
- scrambler, 283, 297
- search for motion vectors
 - constrained to window, 245
 - exhaustive, 243, 251
 - logarithmic, 245
- security through obscurity, 288
- sensor
 - image, 18, 19, 23, 227
 - video, 251
- share price, 17
- shear, 228
- short wave, 259
- shutter, camera, 11, 13
- side information, 163
- sigma-delta conversion, 172
- sign extension, 138, 311
- sign-magnitude representation, 136
 - addition, 146
- signal
 - complex-valued, 6, 16
 - non-periodic, 48
 - periodic, 37
 - real-valued, 16, 44
- SIMD, *see* single instruction multiple data
- similarity, of signals, 76
- sinc function, 80, 94
- sine wave, 11, 46
- single instruction multiple data, 304
- single-precision floating point, 140
- six sigma methodology, 122
- smooth, 203
- smoothing, 63
- software implementations of signal processing
 - algorithms, 300
- sound, *see* audio
- spatial domain, 180
- spectrogram, 153
- spectrum, 76
 - shifting, 255, 263, 267, 275
- spiral, 38
- spread spectrum, 287
 - direct sequence, 292
 - frequency hopping, 288
- standard deviation, of normal
 - distribution, 112
- standards conversion, 239
- stroboscope, 13

- structuring element, 217
- subnormal floating-point numbers, 141
- sum of absolute differences, 244
- superheterodyne, 256
- symbol, 265, 270
 - rate, 266
 - synchronisation, 276, 281
 - in OFDM, 291
- symmetry
 - in finite impulse response filter response, 78, 102
 - exploiting, 308
 - in Fourier transform of real signal, 44, 58
 - of set of representable numbers using two's complement, 137, 138
- synchronous hardware, 307
- synthesiser, music, 13, 261, 310

- tails of normal distribution, thinness of, 112, 115, 116
- taps of a filter, 64
- telephone, 28, 159
- television, *see* video
- throughput of pipelined operation, 303
- tile, 181, 190, 199, 242
- time constant, 95
- time domain, 37
- time-division multiplex, of hardware, 310, 313
- tolerance of analogue components, 5, 150
- tone control, 5, 6, 63
- transducer, 4
- transfer function, 26, 213
- transition tracking for symbol synchronisation, 284
- transposed structure of FIR filter, 70
- trellis, 273, 297
- tuning, 256
- tuning fork, 22
- twiddle factor, 54
- twist, 38
- two's complement
 - arithmetic, 137
 - conversion between formats, 138
 - multiplication via unsigned multiplication, 146
 - representation, 136
 - significance of most significant bit, 137
- untwist, 38
- upconversion, 255, 263
- upsampling, 83, 86, 209, 266
 - by arbitrary ratio, 89
 - by integer ratio, 86
 - by simple fractional ratio, 88
 - of an image, 211
- very long instruction word, 307
- video, *see also* movie, 231, 246
 - analogue, 231–233
 - bits per sample, 30
 - compression, 242, 246
 - sampling resolution, 231
 - standard formats, 231
 - standards conversion, 239
- VLIW, *see* very long instruction word
- vocal cords, 167
- vowel, 48, 164, 168

- waveform, speech, 48
- wheel, wagon, 22
- white noise, 111, 122, 175
- WiFi, *see* wireless Ethernet
- window, 51, 79, 152, 163, 166, 188
 - in search for motion vectors, 245
- windowing method for filter design, 77
- wireless Ethernet, 276, 289, 292
 - error in carrier frequency, 276
- wrap-around, 126, 143, 268

- zero padding, 76, 102, 190
- zero, IEEE 754 floating-point representation, 141
- zero-crossing, 165, 176, 284
- zig-zag, 200