

Cambridge University Press

978-0-521-86985-0 - Hands-On Networking: From Theory to Practice

Maria Luisa Merani, Maurizio Casoni and Walter Cerroni

Index

[More information](#)

## Index

- 1000BASE-CX, 79
- 1000BASE-LX, 79
- 1000BASE-SX, 79
- 1000BASE-T, 79
- 100BASE-FX, 77
- 100BASE-T2, 77, 78
- 100BASE-T4, 77, 78
- 100BASE-TX, 77
- 10BASE-T, 75
- 4B/5B encoding scheme, 77
- 5-4-3 rule, 77
- 568 Commercial Building Telecommunication Standard, 80
- 802.11, 97
  - ACK frames, 129
  - authentication frame, 132
  - beacon frame, 131
  - deauthentication frame, 132
  - probe request, 131
  - RTS/CTS frames, 129
- 802.11 1999 edition, 98
- 802.11a, 98, 100
- 802.11b, 98, 99
- 802.11e, 98, 107
- 802.11g, 98, 100
- 802.11i, 98
- 802.11n draft, 112
- 802.16, 113
  - best effort service, 123
  - common part sublayer, 118
  - convergence sublayer, 118
  - downlink communication, 64
  - FDD, 115
  - MAC PDU, 122
  - management connections, 121
  - mesh topology, 114
  - non-real-time polling service, 123
  - point-to-multipoint, 114, 121, 123
  - privacy sublayer, 118
  - real-time polling service, 123
  - TDD, 115
  - transport connections, 121
  - unsolicited grant service, 123
  - uplink communication, 64
- 802.16e, 113
- 8B/10B encoding scheme, 79
- access network, 8, 14
- ACK, in TCP, 57
- acknowledgment, 40, 74
- acknowledgment number, in TCP header, 55
- ACR, 86
- ACRF, 86
- ad-hoc network, 102
- adaptive modulation, 114
- address resolution protocol, *see* ARP
- addressing, 40
- ADSL, 38, 220
  - discrete multi-tone modulation, 221
- ADSL modem, 9
- ADSL2, 221
- ADSL2+, 221
- AIFS, 108
- Aloha, 62
- American wire gage, *see* AWG
- amplitude spectrum, 3
- application layer, 33, 37
- arbitration IFS, *see* AIFS
- ARP, 38, 40, 88
  - arp command, 89
  - cache, 90
  - table, 89
- asymmetric digital subscriber line, *see* ADSL
- asymmetric service, 19
- asynchronous transfer mode, *see* ATM
- ATM, 231
  - adaptation layer, 234
  - cell, 233
  - classes of service, 234
  - virtual channel, 231
  - virtual path, 231
- attenuation, 84, 85
- attenuation to cross-talk ratio, *see* ACR
- attenuation to cross-talk ratio far-end, *see* ACRF
- auto-negotiation, 80
- AWG, 84

- B-ISDN, 231
- back-off interval, 104
- bandpass transmission, 4
- bandwidth, 5
- baseband transmission, 4
- basic rate set, 107
- BE, 123
- beacon frame, 105
- BER, 75
- bidirectional service, 19
- binary transmission, 1
- bit error rate, *see* BER
- bit rate, 1
- bit time, 1
- block acknowledgments, in 802.11n, 112
- Bluetooth, 97, 98, 124
- bridge, 137
  - filtering bridge, 137
  - learning process, 137
  - plug-and-play, 137
  - transparent bridges, 137
- broadband ISDN, *see* B-ISDN
- broadcast service, 19
- broadcast transmission, 14, 15
- burstiness factor, 18, 27, 28
- bus topology, 12, 27
  
- cable modem, 6
- cable quality, 81
- cabling standards, 80
- cabling system, 61, 80, 81
- carrier sense, 103
- carrier sense multiple access, *see* CSMA
- carrier sense strategies, 65
- Category 3, 76
- Category 5, 86
- Category 5 UTP, 77
- Category 5e, 81, 86
- Category 6, 87
- Category 6a, 87
- Category 7, 76, 87
- CBR, 18
- CCK modulation, 100
- CD, 66
- CF-pollable stations, 107
- CFP, 102, 105, 106
- channel access, 32
- channel access strategies, 61
- checksum field, in TCP header, 55
- checksum field, in UDP header, 58
- CID, 118, 121
- CIDR, 46, 50
- CIDR notation, 50
- circuit-switched network, 9
- class A addresses, 43
- class B addresses, 43
- class D addresses, 43
- class E, 87
- class E addresses, 43
- class F, 87
- class Fa, 87
- classful addressing scheme, 44, 46, 48
- classless addressing scheme, 46, 47
- classless inter-domain routing, *see* CIDR
- clear-to-send, *see* CTS
- coaxial cable, 5, 6, 75
- collision, 62, 66, 71, 74, 103
- collision detection, *see* CD
- collision domain, 68, 69
- collision domain, diameter, 76
- collision domain, in fast Ethernet, 77
- collision phenomenon, 62
- communication channel, 4
- congestion, 21
- connection identifier, in 802.16, *see* CID
- connection-oriented, 36
- connectionless, 36, 40
- connectionless MAC, 74
- constant bit rate source, *see* CBR
- contention period, *see* CP
- contention-based strategies, 63
- contention-free period, *see* CFP
- core network, 9, 14
- CP, 102
- cross-talk, 84, 85
- CSMA, 63
  - one-persistent, 65
  - non-persistent, 65
  - p*-persistent, 65
- CSMA/CA, 102
- CSMA/CD, 70
  - one-persistent, 68, 70
- CTS, 103
  
- data encapsulation, 33
- data field, 73
- data-link layer, 32
- datagram, 10, 32, 39
  - network, 10
  - technology, 10
- DCF, 102–104
- DCF IFS, *see* DIFS
- delay, 14
- delay-sensitive application, 19, 20
- delivery traffic indication message, *see* DTIM
- destination port number, 58
- DHCP, 91
- DIFS, 104–106
- direct delivery, 52, 88
- direct sequence spread spectrum, *see* DSSS
- directed broadcast, 44, 46, 49
- distributed coordinated function, *see* DCF

- DNS, 92
- dotted decimal notation, 42, 49
- DSSS, 98, 99
- DTIM, 105
- duration/ID field, 103
- dynamic control access schemes, 63
  
- EDCA, 108, 109
  - access category, 108
  - back-off times, 108
  - transmission opportunities, 108
  - transmission opportunity, 108
- EIA/TIA 568
  - advantages, 82
  - fault detection, 82
- EIA/TIA 568-B.2 standard, 86
- EIA/TIA TSB67, 84
- EIA/TIA-568-B.2-1, 87
- EIFS, 104
- EN 50173, 81
- endpoint, 54
- end-to-end control, 33
- ether, 7
- Ethernet, 61, 68
  - bus topology, 69
  - MAC frame format, 61
  - point-to-point connection, 70
  - star topology, 69
- ETSI, 30
- European Telecommunications Standards Institute, *see* ETSI
- extended IFS, *see* EIFS
  
- fast Ethernet, 61
- fast link pulses, 80
- FCS, 74
- FDD, 15, 64
- FDMA, 62
- FEXT, 85, 86
- FIN, in TCP header, 55, 57
- firewall, 168
  - application-level gateway, 168
  - packet filter, 168
  - stateful, 168
  - stateless, 168
- fixed channel assignment, 62
- flow control, 71, 79
- FLP, 80
- Fourier transform, 2
- fragmentation, 40
- frame aggregation, in 802.11n, 112
- frame check sequence, 74
- frame format, in Ethernet LAN, 72
- frame relay, 227
  - congestion control, 230
  - traffic control, 229
- frequency bandwidth, 3
- frequency channel plan, 99, 100
- frequency division duplex, *see* FDD
- frequency domain, 1
- frequency hopping, 98, 99
- FTP, 39
- full duplex, 70
- full-duplex transmission, 15
- full-duplex transmission, in Ethernet networks, 71
  
- gateway, 39
- generalized multi-protocol label switching, *see* GMPLS
- gigabit Ethernet, 61
  - NIC, 79
- GMPLS, 239
- guided propagation, 5
  
- half duplex, 70
- half-duplex transmission, 15
- half-duplex transmission, in Ethernet networks, 70
- hardware address, 72
- HC, 108
- HCCA, 108, 109
  - transmission opportunities, 108
- HCF, 108
- HDSL, 221
- header, 33
- Hertz, 3
- hidden terminals, 103
- high bit rate digital subscriber line, *see* HDSL
- high rate DSSS, 99
- horizontal communication, 34
- host-ID, 43, 49
- host-to-network interface, 37
- hub, 69, 137
- hybrid coordination function, *see* HCF
  
- IANA, 45
- IBSS, 102
- ICMP, 38, 39
- IEC, 30
- IEEE, 30
- IEEE 802 project, 67
- IEEE 802.11, 97
  - frame format, 110
- IEEE 802.11i, 133
- IEEE 802.15, 124
- IEEE 802.16, 36, 64
- IEEE 802.1Q, 140
- IEEE 802.3, 61, 67, 68
- IEEE 802.3u, 77
- IEEE 802.4, 67
- IEEE 802.5, 67
  - MAC sublayer, 67

- IETF, 30, 37
- ifconfig command, Linux, 93
- IFS, 104, 106
- impedance, 84, 86
- independent basic set, *see* IBSS
- indirect delivery, 52
- infrared, 99
- infrared region, 7
- initial sequence number, *see* ISN
- initial sequence number, in TCP header, 55
- insertion loss, 85
- integrated services digital network, *see* ISDN
- interframe space, *see* IFS
- inter-building backbone, 81
- interface, 36
- intermediate cross-connect, 81
- International Electrotechnical Commission, *see* IEC
- International Organization for Standardization, *see* ISO
- International Telecommunication Union, *see* ITU
- Internet, 8
  - infrastructure, 8
- Internet control message protocol, *see* ICMP
- Internet Engineering Task force, *see* IETF
- Internet layer, 37
- Internet service provider, *see* ISP
- intra-building backbone, 81
- IP, 38, 40
  - checksum, 42
  - current version, 40
  - header, 40
  - identification field, 41
  - options, 42
  - padding, 42
  - private addresses, 45
  - TOS, 41
  - total length field, 41
  - TTL, 42
  - type of service, in header field, 40
- IP address, 43, 87
- IP address translation, 45
- IP alias, 95
- IP packet delivery, 52
- IP private addresses, 48
- IP-TV, 109
- IPv4, 40, 42
- IPv6, 45
- ISDN, 225
- ISM band, 99
- ISM frequency band, 98
- ISN, 57
- ISO, 30
- ISO 7498, 31
- ISO-OSI model, 31
- ISO/IEC 11801, 81
- ISO/IEC 24750, 87
- ISP, 9, 46
- ITU, 29
- jitter, 21
- LAN, 6, 11, 12, 30, 61
  - layer-1 bandwidth, 5
  - layer-2 bandwidth, 5, 20
  - layer-2 switch, 78
  - length field, in UDP header, 58
  - length/type, 73
  - limited broadcast, 44
  - Linux box, 89
  - local area network, *see* LAN
  - local loop, 6
  - loopback address, 44
  - loss-sensitive application, 19, 20
- MAC, 32
  - address, 72
  - connection, 37
  - correspondence between MAC and IP addresses, 87
- MAC frame format, in Ethernet, 72
- main cross-connect, 81
- MAN, 12, 61
- man-in-the-middle attacks, in LAN, 90
- Manchester encoding, 75
- maximum segment size, *see* MSS
- medium access control, *see* MAC
- mesh clients, 126
- mesh network, 12
- mesh routers, 126
- mesh topology, 12, 27
- metropolitan area network, *see* MAN
- middlebox, 168
- MIMO, in 802.11n, 112
- minimum frame size, 73
- modulation, 4
- MPLS, 237
  - label distribution protocol, 237
  - label edge router, 237
  - label information base, 237
  - label switch-router, 237
  - label switched path, 238
  - router configuration, 239
  - traffic engineering, 244
- MSS, 55, 57
- multi-protocol label switching, *see* MPLS
- multi-home host, 94
- multi-mode fiber, 7
- multicast transmission, 15
- multiple access, 61
- multiple-input–multiple-output, *see* MIMO
- multipoint service, 19

- NAT, 169
  - basic NAT, 169
  - IP masquerading, 171
  - NAPT, 171
  - network address and port translation, 171
  - PAT, 171
  - port address translation, 171
  - port forwarding, 172
- NAV, 103
- Net-ID, 43, 49
- netmask, 49, 52, 92
- network address translator, *see* NAT
- network allocation vector, *see* NAV
- network bandwidth, 5
- network interface card, *see* NIC
- network layer, 32
- NEXT, 85
- NIC, 68, 87, 92
  - configuration, 92
- non-CF-pollable, 107
- nrtPS, 123
  
- OFDM, 100
- OFDMA, 114, 115
- optical fiber, 5, 7, 75
- options field, in TCP header, 55
- organization unique identifier, *see* OUI
- OSI
  - interface, 35
  - layer-1, 32
  - layer-2, 32
  - layer-3, 32
  - layer-5, 33
  - layer-6, 33
  - layer-7, 33
  - PCI, 35
  - PDU, 35
  - primitives, 35
  - protocol, 35, 37
  - SAP, 35
  - SDU, 35
  - service, 35
  - terminology, 35
- OSI Model, 31
- OUI, 73
  
- packet, 9, 10
- packet delay, in a network, 15, 17, 19, 20
- packet delay, on a link, 16
- packet loss rate, 20
- packet-switched network, 9, 10
- pad field, 73
- padding field, in TCP header, 56
- pair-to-pair far-end cross-talk, *see* FEXT
- pair-to-pair near-end cross-talk, *see* NEXT
  
- PAN, 11
- patch cord, 82
- PC, 105
- PCF, 102, 103
- PCF IFS, *see* PIFS
- peer communication, 34
- personal area network, *see* PAN
- phase spectrum, 3
- physical address, 72
- physical layer, 32
- physical layer bandwidth, 5
- piconet, 125
- PIFS, 104, 105
- ping, 22
- point coordinated function, *see* PCF
- point coordinator, *see* PC
- point-to-point communication, 14
- point-to-point link, 32, 47, 48
- point-to-point protocol, *see* PPP
- point-to-point service, 19
- polling, 106
- PPP, 48
- preamble, 72
- prefix, 46, 51
- prefix length, 46
- presentation layer, 33
- priority classes, 21
- processing delay, 15
- propagation delay, 16
- protocol, 36
- protocol control information, *see* OSI PCI
- protocol data unit, *see* OSI PDU
- proxy ARP, 90
- pseudoheader, 55
- PSTN, 9, 30
- public switched telephone network, *see* PSTN
- PUSH, in TCP header, 55
  
- QoS, 21, 41
- QSTA, 108
- QTag prefix, 74
- quality of service, *see* QoS, 41
- quality of service in WLAN, 107
- queueing delay, 16
  
- radio channel, 5, 7
- random access category, 63
- RARP, 91
- regional Internet registries, *see* RIR
- repeater, 69, 136
  - multiport, 69
- request for comments, *see* RFC
- request-to-send, *see* RTS
- reserved field, in TCP header, 55
- reset, in TCP header, 55

- retransmission, 75
- retransmissions, after a collision, 71
- reverse ARP, *see* RARP
- RFC, 30
- ring network, 12
- ring topology, 12, 27
- RIR, 46
- RJ-45, 76
- RJ45, 82
- round-trip time, *see* RTT
- route command, 93
- router, 9, 161
  - architecture, 164
  - default route, 164
  - forwarding information base, 166
  - forwarding table, 163
  - forwarding table look-up, 163
  - functions, 163
  - longest prefix match, 163
  - Patricia trie, 167
  - routing table, 163
  - trie, 166
- routing, 187
  - autonomous system, 197
  - centralized, 188
  - deflection, 188
  - deterministic, 187
  - distributed, 188
  - dynamic, 188
  - flooding, 188
  - graph representation, 188
  - hierarchical, 196
  - hot potato, 188
  - probabilistic, 187
  - routing area, 197
  - shortest path, 189
  - static, 187
- routing algorithm, 187
  - Bellman–Ford, 189
  - Dijkstra, 192
- routing protocol, 193
  - BGP, 198
  - border gateway protocol, *see* BGP
  - comparison, 195
  - count to infinity, 193
  - distance vector, 193
  - exterior, 197
  - interior, 197
  - intermediate system to intermediate system, *see* IS–IS
    - IS–IS
  - IS–IS, 197
  - link state, 194
  - link state packet, *see* LSP
  - LSP, 195
  - open shortest path first, *see* OSPF
  - OSPF, 200
  - path vector, 194
  - RIP, 198
  - routing information protocol, *see* RIP
  - split horizon, 194
  - triggered update, 194
- routing tables, 51
- rtPS, 123
- RTS, 103
  - frame, 102
- RTT, 17, 20, 22, 23, 25
- SACK option, 57
- service, 36
- service access point, *see* OSI SAP
- service data unit, *see* OSI SDU
- service level agreement, *see* SLA
- session layer, 33
- SHDSL, 222
- short IFS, *see* SIFS
- SIFS, 104, 106
- signal analysis, 1
- simple network management protocol, *see* SNMP
- simplex transmission, 15
- single-mode fiber, 7
- single-pair high-speed digital subscriber line, *see* SHDSL
- SLA, 20
- SNMP, 58
- socket, 54
- source burstiness, 27
- source port number, 58
- spanning tree algorithm, 138
- standards, 29
- star topology, 12, 27
- start of frame delimiter, 72
- stateless operating mode, in routers, 11
- static resource assignment, 62
- station supporting QoS in 802.11e, *see* QSTA
- statistical multiplexing, 10, 18
- store-and-forward, 137
- subnet, 48–50, 52
  - address, 49
  - field, 49
- subnet-ID, 49
- subnetting, 45, 48–50
  - variable size, 50
- superframe, 125
- supernetting, 45, 50, 51
- switch, 69, 78, 139
  - cut-through, 139
  - management, 151
  - store-and-forward, 139
- switch-router, 236
- symmetric service, 19
- SYN flag, 57
- SYN, in TCP header, 55

- tail, 33
- TC, 81
- TCP, 36, 38, 39, 54
  - active close, 57
  - active open, 57
  - destination port number, 54
  - header, 54
  - ISN, in TCP header, 55
  - passive close, 57
  - passive open, 57
  - pseudoheader, 55
  - segment, 56
  - sequence number, in TCP header, 55
  - source port number, 54
- TCP/IP
  - protocol suite, 8, 37, 38, 40
- TDD, 15
- TDMA, 62
- telecommunication closet, *see* TC
- three-way handshake, 56
- throughput, 20, 63, 66, 78, 97, 109, 118
- TIA TSB-155, 87
- TIA/EIA-568-B.2-Addendum 10, 87
- time division duplex, *see* TDD
- time domain, 1
- time to live, *see* TTL
- token, 67
- traceroute, 25
- transmission delay, 16
- transmission types, 14
- transport layer, 37
- transport service provider, 33
- transport service user, 33
- tree topology, 12, 27
- truncated binary exponential back-off,
  - algorithm, 71
- TSB95, 86
- twisted pair, 5, 75
  
- UDP, 36, 38, 39, 54, 58
  - header, 58
  - length, 58
- UGS, 123
- UHF, 7
- ultra-high frequency, *see* UHF
- UMTS, 7, 30, 38
- unacknowledged MAC, 74
- unicast transmission, 15
- unidirectional service, 19
- universal addressing scheme, 72
- unshielded twisted pair, *see* UTP
- URG, in TCP header, 55
  
- urgent pointer field, in TCP header, 55
- UTP, 6, 75
  
- variable bit rate source, *see* VBR
- VBR, 18
- VDSL, VDSL2, 222
- very high-speed digital subscriber line, *see* VDSL
- virtual carrier sense, 102, 103
- virtual circuit, 18, 32
  - numbering, 26
  - translation table, 26
- virtual circuit network, 10
- virtual local area networks, *see* VLAN
- VLAN, 139
  - benefits, 141
  - dynamic, 142
  - IEEE 802.1Q tagging, 147
  - inter-VLAN connectivity, 149
  - static, 141
  - tagging, 146
- VLAN tagging, 74
- voice over IP, *see* VoIP
- VoIP, 18
  
- WAN, 12
- WANs, 220
- WEP, 111, 132
- Wi-Fi Alliance, 113
- Wi-Fi Multimedia, 113
- Wi-Fi protected access, *see* WPA
- WiMAX Forum, 114, 124
- wide area networks, *see* WAN
- window field, in TCP header, 55
- wired bus, 14
- wired equivalent privacy, *see* WEP
- wireless LAN, *see* WLAN
- wireless mesh networks, 125
- Wireshark, 127
- WLAN, 7, 12–14, 30, 32, 97
  - 5 GHz band, 100
  - architecture, 101
  - modulation schemes, 99, 100
  - multirate support, 107
  - output power, maximum allowable, 101
  - QoS, 109
- WMAN, 32, 36
- WPA, 132
- WPA2, 132, 133
- WPA2-PSK, 133
  
- X.25, 222
- xDSL, 220