

Index

Note: Terms followed by asterisks are found on the Web at www.cambridge.org/Kundu

- A-weighted scale, 479
- acceleration
 - gravity, 46, 47
- active control technology, 403, 405, 413
- actuator disc, 349
- advanced tactical support*
- aerofoil, 58, 60, 61
 - camber, 60
 - characteristics, 65
 - chord, 60
 - comparison, 66
 - four-digit, 59
 - five-digit, 60
 - GAW, 61
 - mean line, 60, 94
 - section,* 60
 - selection, 60
 - thickness-to-chord, 58
 - thickness ratio, 81
 - supercritical, 69
 - Whitcomb, 61, 69
- after-burning gas turbine, 322
- aileron, 78, 82, 87, 88, 176, 389, 503
- airborne early warning*
- Airbus, 11, 115, 122, 170, 194, 496, 500
- aircraft (*see also* NACA)
 - civil mission, 104
 - classification, 101, 102
 - classification – military*
 - component, 113, 153, 193, 225, 226, 229, 265
 - component groups – mass, 236
 - design choices – civil, 133
 - evolution, 100
 - family variants, 114, 164, 462
 - force, 56, 57
 - load, 108, 138, 141, 225, 228
 - moment, 58, 62, 389, 392, 393
 - motion, 56, 389, 390, 393
 - sizing, 363, 369
 - specification, 35, 36, 39
 - speed, 148, 414
 - statistics – civil, 105
 - statistics – military*
 - system, 21, 502
 - turning, 195, 201
 - variant, 163, 183, 397, 399, 458
- aircraft cost, 372, 461, 522, 526, 528
- aircraft lighting, 510, 511
- aircraft performance,
 - balanced field length, 426, 427
 - climb, 426, 427, 431, 443, 444
 - constant speed climb, 432
 - descent, 430, 434, 447
 - landing, 282, 381, 425, 429, 481
 - military mission profile, 451
 - payload range, 435, 448
 - takeoff, 373, 375, 376, 379, 421, 425, 426, 433, 437
- aircraft price, 524, 529, 545, 546
- aircraft structural consideration, 494
- air defense,* 452
- air speed
 - calibrated, 419
 - equivalent, 419
 - indicated, 419
 - true, 419
- air superiority,* 101, 385
- air-to-air refueling*
- AJT (*see worked-out examples*),
- AJT undercarriage layout, 219
- AJT and growth potential, 385
- AJT performance, 452
- aluminum alloy,* 490, 491
- amortization,* 527, 539
- angle
 - downwash, 72, 393
 - effective, 72
 - incidence, 67, 72, 393
- anhedral, 79, 90, 128, 175, 176, 395
- antenna location, 510

- anti-icing, 506, 513, 515
- approach velocity, 379
- area rule, 68, 69, 70
- ARINC, 416, 510
- aspect ratio
 - correction, 73, 283
- aspiration design space, 19, 40
- AST, 35
- atmosphere, 46
- automatic riveting, 557
- avionics, 499, 509

- B2 (F), 10, 145
- balanced field length, 425, 427, 428, 441
- bel, 479
- Bernoulli's equation, 50
- beyond visual range (BVR), 101, 104
- Bizjet (*see* worked-out examples)
- blade element theory, 349, 351
- Blanchard, Jean-Pierre, 3
- blended wing body, 13, 88, 115, 122, 132, 486
- Bleriot, 5
- Boeing 737 variants, 151
- Boeing 787 (F), 10
- Boeing Sonic Cruiser (F), 10, 98
- BPR (*see* by-pass ratio)
- boundary layer, 50, 51, 52
- Brayton (Joule) cycle, 324
- Breguet range equation, 437
- buffet, 140
- BWB (*see* blended wing body)
- by-pass ratio (turbofan), 318

- Cabin
 - air flow, 515
 - crew, 121, 246
 - width, 113
- CAD, 16
- CAS,* 219, 419, 422, 458, 462
 (*see* worked-out examples)
- canard, 90, 140, 396, 398
- candidate aircraft, 114, 151
- cargo container, 124, 168
 - sizes, 124, 169
- caster angle, 197
- caster length, 197
- Cayley, 3
- center
 - aerodynamic, 64, 91, 229
 - pressure, 64
- center of gravity (CG)
 - position, 228, 252
 - range, 196, 228, 230
- chord
 - mean aerodynamic, 79
 - root, 79, 178
 - tip, 77
- chronology – fighter aircraft*
- circulation, 64
- civil aircraft configuration, 152, 187
- climb, 426
 - first segment, 427
 - second segment, 427
 - gradient, 375, 427, 431, 441, 452, 456
 - initial climb, 377, 380
- close air support*
- cockpit layout (*see* flight deck)
- coefficient
 - drag, 61, 62, 260, 262
 - friction, 53
 - lift, 61, 62
 - moment, 62, 394, 396
 - pressure, 62, 63, 348
- comparison
 - civil versus military, 40
- component, aircraft, 113, 152
- compressibility effect, 80
- computational fluid dynamics, 464
 - case studies, 471
 - hierarchy of CFD, 472
 - postprocessor, 470
 - preprocessor, 470
- conceptual study, 24, 26, 152
- concrete surface, 207
- Congrave, William, 7
- conservation equations
 - energy, 49
 - mass, 49
 - momentum, 49
- container
 - cargo, 124
 - standard, 125
- control augmented system (CAS), 413
- control configured vehicle (CCV), 387
- control subsystem, 503
 - electromechanical, 504
 - mechanical control linkage, 504
 - optical signal, 504
 - push–pull rod type, 504
 - wire–pulley type, 504
- control surface layout, 176
- control volume (CV), 49, 326
- cost
 - fraction, 528
 - frame, 26
- cost methodology, 532
- Curtiss, 5, 192, 315
- customer, 34

- DBT, 15, 24, 551
- d'Arlandes, Francois Laurent, 3
- da Vinci, Leonardo, 2
- decibel, 475
- de-icing, 516
- deflection under load, 206
- de Rozier, Pilatre, 3
- design
 - driver, 34, 200, 233
 - process, 21, 191, 557

- design consideration
 - technology-driven, 563
 - manufacture-driven, 564
 - management-driven, 551, 564
 - operator-driven, 565
- design for customer, 565
 - index, 566
- design for manufacture/assembly, 551
 - DFM/A steps, 9, 527, 531, 554
- digital manufacturing process management (MPM), 568
- dihedral angle, 79, 395
- direct operating cost (DOC), 544
 - breakdown, 544
 - formulation, 546
 - fixed-cost element, 544, 545, 546
 - trip-cost element, 545, 548, 550
- directional divergence, 406
- dive brake, 98, 286
 - (*see* speed brake)
- doors
 - emergency egress, 495
 - types, 495
- downwash angle, 72, 393, 398
- drag
 - base, 274
 - boat tail, 274
 - breakdown, 262
 - canopy, 269
 - dive brake/spoiler, 286
 - excrescence, 277
 - flat-plate equivalent, 262, 266
 - form, 261
 - formulation, 263
 - high-lift device, 282
 - induced, 73, 262, 299, 306
 - intake, 274
 - low speed, 282
 - methodology, 265
 - minimum parasitic, 265, 268, 280
 - nacelle, 273
 - one-engine inoperative, 288
 - parasitic, 54, 261, 265, 268, 278, 299, 305
 - polar, 260, 262, 286, 302, 308, 378
 - profile, 54, 261, 289
 - propeller, 288
 - spillage, 274, 275
 - supersonic, 290
 - total, 262
 - undercarriage, 286
- Dumas, Santos, 5
- Duralumin, 6, 223, 488

- EASA, 6, 41, 476
- ECS, 499, 503, 513
- EFIS, 498
- effective noise level, 480
- efficiency
 - overall, 318, 320
 - propulsive, 318, 319
 - thermal, 318, 319
- ejection,* 479, 498, 521
- Ekranoplane, 14
- electrical subsystem, 510
- electronic warfare*
- elevator, 90, 140, 182, 184
- emerging scenario, 478, 498, 521
- emergency power supply, 508
- empennage, 90, 112, 128, 158, 180
- end-of-life disposal, 518
- energy absorbed, 205
- engine and fuel control subsystem, 505
 - fuel storage and flow management, 505
 - piston engine, 505
 - turbofan system, 506
- engine performance, 359
 - military gas turbofan, 370
 - piston engine, 361
 - turbofan (civil), 365
 - turboprop, 363
- engine-performance data
 - turbofan (civil), 420
 - turbofan (military)*
 - turboprop, 423
- engine position, 131, 333
- engine ratings, 359
 - idle, 361
 - maximum continuous, 360, 420, 423, 488
 - maximum climb, 360, 420, 424
 - maximum cruise, 360, 420, 424
 - takeoff, 360, 420, 423, 424
- environmental control system (*see* ECS)
- equation of state, 50
- escape slide, 496
- Euler's equation, 49

- F22 Raptor (F),* 97
- F117 Nighthawk (F),* 7
- FAA, 6, 205, 288, 430, 476, 478, 481, 495
- FADEC, 316, 415, 507
- FAR, 144, 417, 418, 425, 480, 495
- factor of safety, 143, 425, 451
- family variants, 112, 114, 164, 218
- fence, 89
- fin, 32, 129, 189
- fixtures, 494, 551
- flap, 67, 176, 203, 272, 282
- flight deck, 497
 - layout (civil), 500
 - layout (military), 499
- flutter, 140
- flotation, 206, 210
- flyaway tooling, 552, 556
- fly by light, 413
- fly by wire, 413
- force
 - aircraft, 56, 396
- fps, 17, 31
- fuel fraction, 108

- fuel load, 108, 229, 247, 373
- fuselage, 93
 - aft-closure angle, 95
 - axis, 93, 156, 252, 336
 - closure, 94
 - configure, 165
 - cross-section, 94, 97, 116, 117, 161, 164
 - fineness ratio, 94
 - front-closure angle, 94
 - height, 95
 - layout (civil), 160
 - length, 94, 114, 117, 119, 154, 164
 - multiboom, 126
 - nose cone, 32, 94, 117, 118, 266, 268
 - reference line, 93, 156
 - twin boom, 129, 133, 159
 - upsweep angle, 94, 120
 - width, 95, 114
 - zero-reference plane, 90
- galley, 123, 124
- gas turbine station number, 319, 321, 325, 326, 331
- gauges, 499, 555
- gaugeless tooling, 557
- geopotential altitude, 48
- glove, 77, 80, 127, 157
- golf ball, 54
- grass turf, 194, 206, 212
- ground attack aircraft*
- ground-effect vehicle, 13
- ground loop, 194, 201
- gust envelope, 147

- hands on throttle and stick (HOTAS), 502
- hard turf, 212
- head-up display, 500
- helmet-mounted display, 501
- Henson, Samuel, 3
- high-lift device, 32, 67, 68, 88, 282, 286
- horizontal-tail, 90, 130, 181
- hydraulic subsystem, 511
- hydrostatic equations, 46, 47
- hypersonic aircraft, 12, 101

- INCOSE, 21
- induced drag, 71, 73, 83, 262, 299
- inline assembly, 557
- intake, 96, 338
 - design (civil), 338
 - design (military)*
 - diffuser, 339
 - highlight diameter, 339
 - position (nacelle), 98, 131
 - supersonic*
 - throat, 339
 - (*see also* nacelle)*
- installation (military), 348
- integration
 - engine, 331
 - turboprop, 335
- interdiction*
- IPPD, 9, 22, 494, 527, 531, 544
- isentropic relations, 49, 325
- ISA, 46

- JAA, 6
- Jatho, Karl, 4
- jigs, 494, 555, 556
- jigless assembly, 552, 556
- joined wing aircraft, 13, 14
- Johnson, Clarence, 7
- Joule (Brayton), cycle, 325
- JUCAS,* 14

- laminar, 50, 52, 267, 331, 335
- Langley, Samuel P., 4
- LCN, 207, 208
- life cycle cost (LCC), 530
- lift, 57
 - curve slope, 74
 - dumper, 32, 88
- Lilienthal, Gustav and Otto, 3
- limit
 - load, 143
 - low speed, 146
 - high speed, 145
 - speed, 143
- lip contraction ratio, 340
- lip suction, 270
- load
 - factor, 142, 147, 205, 227, 238
 - factor, maximum limit, 154
 - limit, 144
 - negative, 146
 - positive, 146
 - ultimate, 143, 491
- load classification group, 207
- load classification number (*see* LCN)
- load on wheel, 203
- low observable*

- macadam surface, 207
- Mach
 - critical, 81, 381
 - number, 49, 50
- main wheel failed, 200
- maneuver
 - pitch, 144
 - roll, 141
 - yaw, 141
- manufacturer's empty mass, 106, 228
- manufacturing practices, 568
- maritime patrol*
- market, 33
 - military,* 39
 - survey, 33
- mass estimation, 233
- mass flow ratio, 349
- mass (weight) fraction (civil), 235, 237
- mass (weight) fraction (military)*

- material
 - aircraft, 478
 - composite, 489
 - properties, 489
 - selection, 491
 - stress–strain relationship, 490
- maximum takeoff mass (MTOM), 106, 220, 228
- MDA, 24, 29
- MDO, 17, 24, 385
- mean aerodynamic chord, 79
- military
 - aircraft component*
 - mission*
 - mission profile, 451
 - statistics*
 - transport aircraft*
- modular concept, 31, 156, 315, 510
- Montgolfier, Joseph and Etienne, 3
- motion, aircraft, 56, 503
- multifunctional display (MFD), 498, 510
- multirole fighter*

- NACA
 - four-digit aerofoil, 59
 - five-digit aerofoil, 60
 - six-digit aerofoil, 60
- nacelle/intake, 96
 - external diameter, 339
 - fuselage-mounted, 130
 - layout, 184
 - long-duct, 322, 327, 333
 - overwing, 130, 131, 332, 411
 - position, 128, 184, 332, 334
 - short-duct, 333, 337
 - underwing, 130, 332
 - wing tip, 132
- nacelle cost driver, 533
- Newton, Isaac, 3
- Night Hawk, F117, 11, 291, 415, 504
- noise, 479
 - propeller, 486
 - radiation, 484
 - source, 483
 - standards, 493
 - suppression, 335, 485
- nose wheel, 196, 201
- nose wheel failed, 200
- nozzle,* 273, 337, 338, 349, 343

- OEM fraction, 107, 234
- operating cost (OC), 529
- operational empty mass (OEM), 106, 228
- Oswald's efficiency factor, 72, 77, 261
- oxygen supply, 515

- pavement (*see* runway)
- payload range, 29, 104, 435, 448
- perceived noise level, 480
- phases of project, 23, 26
- phugoid, 404

- Piaggio, 92
- pilot seat dimension, 122
- pilot vision, 114
- piston engine, 101, 243, 289, 317, 323, 362, 505
- piston engine – supercharged, 324
- Pline, Joseph, 3
- pneumatic subsystem, 503, 513
- potato curve, 229
- power control unit, 504
- propeller, 345, 349, 355, 358
 - activity factor, 348, 353
 - advance ratio, 349
 - blade element theory, 351
 - blade-pitch angle, 346, 348
 - constant pitch, 347, 349
 - definition, 348
 - design C_L , 355
 - momentum theory, 349
 - performance, 355, 358
 - power, 348, 356
 - power coefficient, 348, 353
 - theory, 349
 - thrust, 330, 348, 352
 - thrust coefficient, 348
 - type, 346
 - variable pitch, 346
- radar cross-section*
- rain removal, 516, 517
- rake angle, 196, 197
- ram air turbine (RAT), 508
- Raptor F22*
- RD&D, 34
- reconnaissance*
- reliability and maintainability (R&M), 524, 561
- remotely piloted vehicles*
- return to base*
- Reynolds number, 51, 266
 - critical, 52
- RFP, 34
- RPM, 10
- rudder, 32, 90, 97, 389
- runway pavement classification, 206
- runway types, 206

- sea-level static thrust, 111, 420
- Sears–Haack body, 69
- seat
 - mile cost, 105
 - pitch, 123, 162
 - posture, 122
 - width, 123
- seating
 - two-abreast, 163
 - three-abreast, 164
 - four-abreast, 165
 - five-abreast, 166
 - six-abreast, 167
 - seven-abreast, 168
 - eight-abreast, 168

- seating (*cont.*)
 nine/ten-abreast, 169
 ten-abreast, 170
 separation, 52, 54, 55
 service
 galley, 114, 123
 trolley, 123
 location, 520
 shock absorber, 202
 shop-floor interface, 572
 short period, 330, 404
 silent aircraft, 486
 simple straight-through
 turbojet, 320, 325
 sizing theory, 373
 initial cruise, 378
 initial rate of climb, 377
 landing, 378
 takeoff, 374
 Six Sigma
 concept, 558
 distribution, 558
 skin friction coefficient, 52, 54, 261, 265, 295, 309
 slat, 32, 67, 88, 241, 282, 427
 sonic cruiser, 10
 sound pressure level, 479
 Space Ship One, 7, 13
 specific range, 432, 446, 459
 specific thrust, 317, 328, 366
 speed
 brake application, 203, 426
 decision, 426, 428
 minimum control, 426
 minimum unstuck, 426
 rotation, 420
 speed brake (*see* dive brake)
 spinning, 408
 spiral, 408
 spoiler, 32, 88, 96, 97, 241, 286
 square-cube law, 84
 stabilator, 505
 stability
 design considerations, 389, 413
 directional, 189, 393
 dynamic, 389, 391
 lateral, 390, 393, 406
 pitch plane, 140, 392, 396
 static, 389, 391, 396, 409
 theory, 412
 stability augmented system, 413
 stabilizer, 90, 184, 508
 STAGNAG 3838, 509
 stall, 55, 65, 82
 type, 65
 stealth considerations
 heat signature*
 radar signature*
 stowage space, 199
 strategic bomber*
 stress-strain relationship, 490
 Stringfellow, John, 4
 subsystem, 503
 supersonic transport aircraft, 12
 survivability (military aircraft)
 ejection seat*
 emergency escape*
 system
 aircraft, 21, 503
 T-s diagram, 325, 329
 tail
 asymmetric, 128
 canard, 140, 396, 412
 circular, 129
 H-tail, 90, 128, 181
 T-tail (high tee), 33, 78, 90, 128, 181
 high, 128
 low, 128
 mid, 128
 twin boom, 129
 multiboom, 128
 position, 128
 single boom, 128
 statistics, 112, 402
 V-tail, 90, 114, 128, 181, 189, 396, 402
 Y-tail, 129
 tail volume coefficient, 399
 takeoff, 379, 425, 428
 thrust loading, 110, 111, 373, 381, 382
 thrust reverser,* 332, 341
 effect on stopping distance, 429
 efflux pattern, 342
 military*
 types, 343
 thrust vectoring*
 time frame, 27
 Tippu, Sultan, 7
 Tire, 209
 braking friction, 212
 data (*see* Appendix E*)
 designation, 211
 extra-high pressure, 210
 friction with ground, 212
 low pressure, 210
 new design, 210
 pressure, 210
 rolling friction, 212
 sizing, 213, 215
 types, 210
 tolerance relaxation, 559
 tools, 555
 TQM, 15
 transonic,
 effect, 68, 80, 281
 trim drag, 65, 278
 trolley, 124
 true air speed, 419
 turbofan engine, 321, 327, 365
 turbojet engine, 325
 turboprop engine, 323, 330, 360, 363, 423
 turbulent, 56, 62, 306
 turning of aircraft, 201

- UAV*
 - undercarriage, 194
 - CG position, 195
 - data, 221
 - deflection, 199
 - energy absorbed, 202
 - layout, 213
 - layout methodology, 213
 - layout/nomenclature/definitions, 195
 - nose wheel type, 196
 - retraction, 197
 - stowage, 197
 - strut, 195
 - tail-dragging type, 196
 - turnover, 195
 - type, 195, 197
 - unit load device (ULD), 125
 - unprepared surface, 206
 - utility system, 517
- V-n* diagram, 145
- verified design space, 19, 40
- vertical tail (*see* tail – V-tail)
- voice-operated control (VOC)*
- von Braun, W., 7
- von Ohain, Hans, 6
- vortex
 - generator, 89
 - lift, 87
- vortilon*
- water and waste system, 517, 519
- weight (*see also* mass)
 - data, 251
 - driver, 227
 - estimation graphical, 234
 - semi-empirical method, 238
- Weisskopf, Gustav, 4
- wetted area, 85
- wheel
 - arrangement, 202
 - load, 202
 - shock absorber, 202
- Whitcomb aerofoil, 61, 174
- White Knight, 13
- Whitte, Frank, 6
- wing
 - anhedral, 79
 - configuration, 78
 - dihedral, 79
 - generic*
 - group,* 114, 126
 - high, 79, 120, 131
 - layout, 174
 - loading, 84, 109, 113, 180, 373
 - low, 78, 120, 131
 - reference area, 76, 176, 279
 - root chord, 77, 79
 - shape, 128
 - stall, 82
 - sweep angle, 81, 82, 176
 - taper ratio, 77
 - three-surface*
 - tip chord, 77
 - twist, 78
 - two-surface*
- wing design
 - planform shape, 86, 126
 - position, 133, 174
- wing planform
 - area, 76
 - cranked, 127
 - elliptical, 127
 - generic, 136
 - rectangular, 127
 - tapered, 127
- wing reference area, 76
- winglet, 88
- worked-out example
 - AJT
 - baseline, 294
 - (CAS), 207
 - CG location, 274
 - discussion, 475
 - drag evaluation, 314
 - fuselage layout, 204
 - growth potential, 385
 - performance, 452
 - sensitivity study, 401
 - sizing, 398
 - undercarriage layout, 219
 - variant (CAS), 399
 - wing, 204
 - Bizjet
 - baseline aircraft, 188
 - CG location, 254
 - design for customer, 567
 - discussion, 461
 - DOC estimation, 548
 - drag evaluation, 292
 - empennage layout, 182
 - finalized configuration, 383
 - fuselage layout, 171
 - nacelle design, 185
 - performance, 437
 - sizing analysis, 379, 384
 - undercarriage layout, 215
 - variants, 171, 379
 - weight and CG analysis, 226, 254
 - weight estimation, 260–263
 - wing layout, 178
 - costing of nacelle nose cowl, 536
 - design for customer, 565, 567
 - propeller performance, 358
 - supersonic drag evaluation, 299
 - turboprop performance, 636
- Wright brothers (Orville and Wilber), 2, 4
- Yeager, Chuck, 6
- Yehudi, 77
- yield point, 490
- Young's Modulus, 490