CAMBRIDGE

Cambridge University Press
978-0-521-88584-3 - Next Generation Wireless LANs: Throughput, Robustness, and Reliability in 802.11n
Eldad Perahia and Robert Stacey
Table of Contents
More information

Brief contents

Foreword by Dr. Andrew Myles *page* xix
Preface xxiii
List of abbreviations xxv

1 Introduction 1

Part I Physical layer

2 Orthogonal frequency division multiplexing 23

3 MIMO/SDM basics 29

4 PHY interoperability with 11a/g legacy OFDM devices 58

5 High throughput 101

6 Robust performance 142

Part II Medium access control layer

7 Medium access control 181

8 MAC throughput enhancements 203

9 Advanced channel access techniques 225

10 Interoperability and coexistence 238

11 MAC frame formats 266

Part III Transmit beamforming

12 Transmit beamforming 307

Index 368

© Cambridge University Press www.cambridge.org

CAMBRIDGE

Cambridge University Press
978-0-521-88584-3 - Next Generation Wireless LANs: Throughput, Robustness, and Reliability in 802.11n
Eldad Perahia and Robert Stacey
Table of Contents
More information

Contents

Foreword by Dr. Andrew Myles xix
Preface xxiii
List of abbreviations xxv

1 Introduction 1

1.1 History of IEEE 802.11 3
1.2 History of high throughput and 802.11n 5
1.2.1 The High Throughput Study Group 5
1.2.2 Formation of the High Throughput Task Group (TGn) 6
1.2.3 Call for proposals 8
1.2.4 Handheld devices 9
1.2.5 Merging of proposals 10
1.2.6 802.11n amendment drafts 10
1.3 Environments and applications for 802.11n 11
1.4 Major features of 802.11n 15
1.5 Outline of chapters 17
References 19

Part I Physical layer

2 Orthogonal frequency division multiplexing 23

2.1 Background 23
2.2 Comparison to single carrier modulation 25
References 27

3 MIMO/SDM basics 29

3.1 SISO (802.11a/g) background 29
3.2 MIMO basics 29
3.3 SDM basics 31
3.4 MIMO environment 33
3.5 802.11n propagation model 35
3.5.1 Impulse response 36

© Cambridge University Press www.cambridge.org

CAMBRIDGE

Cambridge University Press
978-0-521-88584-3 - Next Generation Wireless LANs: Throughput, Robustness, and Reliability in 802.11n
Eldad Perahia and Robert Stacey
Table of Contents
More information

3.5.2 Antenna correlation 38
3.5.2.1 Correlation coefficient 39
3.5.3 Doppler model 41
3.5.3.1 Modified Doppler model for channel model F 41
3.5.4 Physical layer impairments 43
3.5.4.1 Phase noise 43
3.5.4.2 Power amplifier non-linearity 44
3.5.5 Path loss 46
3.6 Linear receiver design 47
3.7 Maximum likelihood estimation 49
References 51
Appendix 3.1: 802.11n channel models 52

4 PHY interoperability with 11a/g legacy OFDM devices 58

4.1 11a packet structure review 58
4.1.1 Short Training field 58
4.1.2 Long Training field 61
4.1.3 Signal field 64
4.1.4 Data field 65
4.1.5 Packet encoding process 66
4.1.6 Receive procedure 68
4.2 Mixed format high throughput packet structure 70
4.2.1 Non-HT portion of the MF preamble 70
4.2.1.1 Cyclic shifts 72
4.2.1.2 Legacy compatibility 73
4.2.1.3 Non-HT Short Training field 75
4.2.1.4 Non-HT Long Training field 76
4.2.1.5 Non-HT Signal field 76
4.2.2 HT portion of the MF preamble 77
4.2.2.1 High Throughput Signal field 77
4.2.2.2 High Throughput Short training field 81
4.2.2.3 High Throughput Long Training field 82
4.2.3 Data field 84
4.2.3.1 Bit string 84
4.2.3.2 Scrambling and encoding 85
4.2.3.3 Stream parsing 85
4.2.3.4 Interleaving 86
4.2.3.5 Modulation mapping 87
4.2.3.6 Pilot subcarriers 88
4.2.3.7 Transmission in 20 MHz HT format 88
4.2.3.8 Spatial expansion 89
4.2.4 HT MF receive procedure 91
4.2.4.1 RF front end 92
4.2.4.2 Legacy part of the preamble 93

© Cambridge University Press www.cambridge.org

CAMBRIDGE

Cambridge University Press
978-0-521-88584-3 - Next Generation Wireless LANs: Throughput, Robustness, and Reliability in 802.11n
Eldad Perahia and Robert Stacey
Table of Contents
More information

4.2.4.3 High Throughput Signal field (HT-SIG) 93
4.2.4.4 High Throughput Training fields and MIMO channel estimation 94
4.2.4.5 Data field 96
4.2.4.6 Demapping, deinterleaving, decoding, and descrambling 97
References 98
Appendix 4.1: 20 MHz basic MCS tables 98

5 High throughput 101

5.1 40 MHz channel 100
5.1.1 40 MHz subcarrier design and spectral mask 102
5.1.2 40 MHz channel design 104
5.1.3 40 MHz mixed format preamble 104
5.1.4 40 MHz data encoding 109
5.1.4.1 Bit string with two encoders 110
5.1.4.2 Scrambling, encoder parsing, and encoding with two encoders 110
5.1.4.3 Stream parsing with two encoders 110
5.1.5 MCS 32: High throughput duplicate format 111
5.1.6 20/40 MHz coexistence with legacy in the PHY 114
5.1.7 Performance improvement with 40 MHz 114
5.2 20 MHz enhancements: Additional data subcarriers 116
5.3 MCS enhancements: Spatial streams and code rate 116
5.4 Greenfield (GF) preamble 121
5.4.1 Format of the GF preamble 122
5.4.2 PHY efficiency 125
5.4.3 Issues with GF 125
5.4.3.1 Network efficiency 125
5.4.3.2 Interoperability issues with legacy 127
5.4.3.3 Implementation issues 129
5.4.4 Preamble auto-detection 129
5.5 Short guard interval 131
References 135
Appendix 5.1: Channel allocation 135
Appendix 5.2: 40 MHz basic MCS tables 139
Appendix 5.3: Physical layer waveform parameters 141

6 Robust performance 142

6.1 Receive diversity 142
6.1.1 Maximal ratio combining basics 143
6.1.2 MIMO performance improvement with receive diversity 144
6.1.3 Selection diversity 147

© Cambridge University Press www.cambridge.org

CAMBRIDGE

Cambridge University Press
978-0-521-88584-3 - Next Generation Wireless LANs: Throughput, Robustness, and Reliability in 802.11n
Eldad Perahia and Robert Stacey
Table of Contents
More information

6.2 Spatial expansion 147
6.3 Space-time block coding 147
6.3.1 Alamouti scheme background 149
6.3.2 Additional STBC antenna configurations 151
6.3.3 STBC receiver and equalization 154
6.3.4 Transmission and packet encoding process with STBC 156
6.4 Low density parity check codes 159
6.4.1 LDPC encoding process 160
6.4.1.1 Step 1: Calculating the minimum number of OFDM symbols 160
6.4.1.2 Step 2: Determining the code word size and number of code words 161
6.4.1.3 Step 3: Determining the number of shortening zero bits 163
6.4.1.4 Step 4: Generating the parity bits 164
6.4.1.5 Step 5: Packing into OFDM symbols 166
6.4.1.6 Step 6: Stream parsing 170
6.4.2 Effective code rate 170
6.4.3 LDPC coding gain 172
References 172
Appendix 6.1: Parity check matrices 172

Part II Medium access control layer

7 Medium access control 181

7.1 Protocol layering 182
7.2 Management functions 183
7.2.1 Beacons 183
7.2.2 Scanning 183
7.2.3 Authentication 184
7.2.4 Association 184
7.2.5 Reassociation 185
7.2.6 Disassociation 185
7.3 Distributed channel access 185
7.3.1 Basic channel access timing 186
7.3.1.1 SIFS 186
7.3.1.2 Slot time 187
7.3.1.3 PIFS 188
7.3.1.4 DIFS 188
7.3.1.5 Random backoff time 188
7.3.1.6 Random backoff procedure 189
7.4 Data/ACK frame exchange 189
7.4.1 Fragmentation 190

© Cambridge University Press www.cambridge.org

CAMBRIDGE

Cambridge University Press
978-0-521-88584-3 - Next Generation Wireless LANs: Throughput, Robustness, and Reliability in 802.11n
Eldad Perahia and Robert Stacey
Table of Contents
More information

7.4.2 Duplicate detection 191
7.4.3 Data/ACK sequence overhead and fairness 192
7.5 Hidden node problem 192
7.5.1 Network allocation vector 193
7.5.1.1 RTS/CTS frame exchange 193
7.5.2 EIFS 194
7.6 Enhanced distributed channel access 194
7.6.1 Transmit opportunity 196
7.6.2 Channel access timing with EDCA 197
7.6.3 EDCA access parameters 198
7.6.4 EIFS revisited 198
7.6.5 Collision detect 199
7.6.6 QoS Data frame 199
7.7 Block acknowledgement 199
7.7.1 Block data frame exchange 201
References 202

8 MAC throughput enhancements 203

8.1 Reasons for change 203
8.1.1 Throughput without MAC changes 203
8.1.2 MAC throughput enhancements 205
8.1.3 Throughput with MAC efficiency enhancements 206
8.2 Aggregation 207
8.2.1 Aggregate MSDU (A-MSDU) 209
8.2.2 Aggregate MPDU (A-MPDU) 210
8.2.2.1 A-MPDU contents 211
8.2.2.2 A-MPDU length and MPDU spacing constraints 211
8.2.3 Aggregate PSDU (A-PSDU) 212
8.3 Block acknowledgement 212
8.3.1 Immediate and delayed block ack 213
8.3.2 Block ack session initiation 213
8.3.3 Block ack session data transfer 215
8.3.4 Block ack session tear down 215
8.3.5 Normal ack policy in a non-aggregate 216
8.3.6 Reorder buffer operation 216
8.4 HT-immediate block ack 217
8.4.1 Normal Ack policy in an aggregate 217
8.4.2 Compressed block ack 219
8.4.3 Full state and partial state block ack 219
8.4.3.1 Full state block ack operation 219
8.4.3.2 Motivation for partial state block ack 219
8.4.3.3 Partial state block ack operation 221
8.4.4 HT-immediate block ack TXOP sequences 222

© Cambridge University Press www.cambridge.org

CAMBRIDGE

Cambridge University Press
978-0-521-88584-3 - Next Generation Wireless LANs: Throughput, Robustness, and Reliability in 802.11n
Eldad Perahia and Robert Stacey
Table of Contents
More information

8.5 HT-delayed block ack 223
8.5.1 HT-delayed block ack TXOP sequences 224
References 224

9 Advanced channel access techniques 225

9.1 PCF 225
9.1.1 Establishing the CFP 225
9.1.2 NAV during the CFP 226
9.1.3 Data transfer during the CFP 226
9.1.3.1 Contention free acknowledgement 227
9.1.4 PCF limitations 227
9.2 HCCA 228
9.2.1 Traffic streams 228
9.2.1.1 TS setup and maintenance 229
9.2.1.2 Data transfer 229
9.2.1.3 TS deletion 229
9.2.2 Controlled access phases 230
9.2.3 Polled TXOP 230
9.2.4 TXOP requests 231
9.2.5 Use of RTS/CTS 231
9.2.6 HCCA limitations 231
9.3 Reverse direction protocol 232
9.3.1 Reverse direction frame exchange 232
9.3.2 Reverse direction rules 233
9.3.3 Error recovery 234
9.4 PSMP 234
9.4.1 PSMP recovery 235
9.4.2 PSMP burst 236
9.4.3 Resource allocation 237
9.4.4 Block ack usage under PSMP 237
References 237

10 Interoperability and coexistence 238

10.1 Station and BSS capabilities 238
10.1.1 HT station PHY capabilities 238
10.1.2 HT station MAC capabilities 239
10.1.3 BSS capabilities 239
10.1.4 Advanced capabilities 240
10.2 Controlling station behavior 240
10.3 20 MHz and 20/40 MHz operation 241
10.3.1 Beacon transmission 242
10.3.2 20 MHz BSS operation 242
10.3.3 20/40 MHz BSS operation 243

© Cambridge University Press www.cambridge.org

CAMBRIDGE

Cambridge University Press
978-0-521-88584-3 - Next Generation Wireless LANs: Throughput, Robustness, and Reliability in 802.11n
Eldad Perahia and Robert Stacey
Table of Contents
More information

10.3.3.1 20/40 MHz operation in the 5 GHz bands 244
10.3.3.2 20/40 MHz operation in the 2.4 GHz band 244
10.3.3.3 A brief history of 40 MHz in the 2.4 GHz band 245
10.3.4 Clear channel assessment in 20 MHz 247
10.3.5 Clear channel assessment in 40 MHz 247
10.3.6 Channel access for a 40 MHz transmission 248
10.3.7 NAV assertion in a 20/40 MHz BSS 248
10.3.8 OBSS scanning requirements 248
10.3.8.1 Establishing a 20/40 MHz BSS in the 5 GHz bands 248
10.3.8.2 Establishing a 20/40 MHz BSS in the 2.4 GHz band 249
10.3.8.3 OBSS scanning during 20/40 MHz BSS operation 250
10.3.8.4 Scanning requirements for 20/40 MHz stations 251
10.3.9 Signaling 40 MHz intolerance 253
10.3.10 Channel management at the AP 253
10.4 A summary of fields controlling 40 MHz operation 254
10.5 Phased coexistence operation (PCO) 255
10.5.1 Basic operation 256
10.5.2 Minimizing real-time disruption 257
10.6 Protection 257
10.6.1 Protection with 802.11b stations present 258
10.6.2 Protection with 802.11g or 802.11a stations present 258
10.6.3 Protection for OBSS legacy stations 259
10.6.4 RIFS burst protection 259
10.6.5 Greenfield format protection 259
10.6.6 RTS/CTS protection 260
10.6.7 CTS-to-Self protection 261
10.6.8 Protection using a non-HT or HT mixed PPDU with non-HT response 261
10.6.9 Non-HT station deferral with HT mixed format PPDU 262
10.6.10 L-SIG TXOP protection 263
References 265

11 MAC frame formats 266

11.1 General frame format 266
11.1.1 Frame Control field 266
11.1.1.1 Protocol Version field 266
11.1.1.2 Type and Subtype fields 266
11.1.1.3 To DS and From DS fields 267
11.1.1.4 More Fragments field 267
11.1.1.5 Retry field 267
11.1.1.6 Power Management field 269
11.1.1.7 More Data field 269
11.1.1.8 Protected Frame field 269
11.1.1.9 Order field 269

© Cambridge University Press www.cambridge.org

CAMBRIDGE

Cambridge University Press
978-0-521-88584-3 - Next Generation Wireless LANs: Throughput, Robustness, and Reliability in 802.11n
Eldad Perahia and Robert Stacey
Table of Contents
More information

11.1.2 Duration/ID field 270
11.1.3 Address fields 270
11.1.4 Sequence Control field 270
11.1.5 QoS Control field 271
11.1.5.1 TXOP Limit subfield 271
11.1.5.2 Queue Size subfield 271
11.1.5.3 TXOP Duration Requested subfield 272
11.1.5.4 AP PS Buffer State subfield 272
11.1.6 HT Control field 273
11.1.7 Frame Body field 275
11.1.8 FCS field 275
11.2 Format of individual frame types 276
11.2.1 Control frames 276
11.2.1.1 RTS 276
11.2.1.2 CTS 276
11.2.1.3 ACK 276
11.2.1.4 BAR 276
11.2.1.5 Multi-TID BAR 278
11.2.1.6 BA 278
11.2.1.7 Multi-TID BA 280
11.2.1.8 PS-Poll 280
11.2.1.9 CF-End and CF-End+CF-Ack 281
11.2.1.10 Control Wrapper 281
11.2.2 Data frames 282
11.2.3 Management frames 282
11.2.3.1 Beacon frame 283
11.2.3.2 Association and Reassociation Request frame 283
11.2.3.3 Association and Reassociation Response frame 283
11.2.3.4 Disassociation frame 284
11.2.3.5 Probe Request frame 284
11.2.3.6 Probe Response frame 284
11.2.3.7 Authentication frame 284
11.2.3.8 Deauthentication frame 284
11.2.3.9 Action and Action No Ack frames 284
11.3 Management Frame fields 288
11.3.1 Fields that are not information elements 288
11.3.1.1 Capability Information field 288
11.3.2 Information elements 288
11.3.2.1 Extended Channel Switch Announcement element 288
11.3.2.2 HT Capabilities element 290
11.3.2.3 HT Information element 291
11.3.2.4 20/40 BSS Coexistence element 291
11.3.2.5 20/40 BSS Intolerant Channel Report element 302
11.3.2.6 Overlapping BSS Scan Parameters element 302
References 302

© Cambridge University Press www.cambridge.org

CAMBRIDGE

Cambridge University Press
978-0-521-88584-3 - Next Generation Wireless LANs: Throughput, Robustness, and Reliability in 802.11n
Eldad Perahia and Robert Stacey
Table of Contents
More information

Part III Transmit beamforming

12 Transmit beamforming 307

12.1 Singular value decomposition 308
12.2 Transmit beamforming with SVD 311
12.3 Eigenvalue analysis 312
12.4 Unequal MCS 316
12.5 Receiver design 320
12.6 Channel sounding 321
12.7 Channel state information feedback 323
12.7.1 Implicit feedback 323
12.7.2 Explicit feedback 328
12.7.2.1 CSI feedback 328
12.7.2.2 Non-compressed beamforming weights feedback 329
12.7.2.3 Compressed beamforming weights feedback 330
12.8 Improved performance with transmit beamforming 335
12.9 Degradations 342
12.10 MAC considerations 349
12.10.1 Sounding PPDUs 350
12.10.1.1 NDP as sounding PPDU 351
12.10.1.2 NDP use for calibration and antenna selection 351
12.10.2 Implicit feedback beamforming 351
12.10.2.1 Calibration 352
12.10.2.2 Sequences using implicit feedback 354
12.10.3 Explicit feedback beamforming 355
12.10.3.1 Sequences using explicit feedback 357
12.10.3.2 Differences between NDP and staggered sounding 357
12.11 Comparison between implicit and explicit 358
12.12 Fast link adaptation 359
12.12.1 MCS feedback 361
12.12.2 MCS feedback using the HT Control field 361
References 362
Appendix 12.1: Unequal MCS 363
Unequal MCS for 20 MHz 363
Unequal MCS for 40 MHz 365

Index 368

© Cambridge University Press www.cambridge.org