

Cambridge University Press

978-1-107-00056-8 - Quasilinear Control: Performance Analysis and Design of Feedback Systems with Nonlinear Sensors and Actuators

ShiNung Ching, Yongsoon Eun, Cevat Gokcek, Pierre T. Kabamba and Semyon M. Meerkov

Index

[More information](#)

## Index

- absolute stability, 2
- admissible domain, 134, 136
- antiwindup, 73, 161
- application
  - hard disk servo design, 88, 141
  - hard disk servo design, LPNI, 100, 159
  - MagLev, 217
  - servomechanism design, 75
  - ship roll damping, 178, 195
- bandwidth, 82
  - random, 82, 135
  - saturating random, 96
- bisection algorithm, 10, 33, 170, 176, 186, 191
- boosting
  - a-boosting, 211
  - s-boosting, 211
  - simultaneous, 214
- clipping, 97
- computational issues, 29, 33, 84, 88
- d.c. gain, 82
  - random, 82, 135
  - saturating random, 96
- describing functions, 2, 22
- diagnostic flowchart, 99
- disturbance rejection, 114, 167
  - fundamental limitations, 114, 124
  - with nonlinear actuator, 36
  - with nonlinear actuators and sensors, 44
  - with nonlinear sensor, 37
  - with rate saturation, 128
- domain of attraction, 172, 187, 192
- equation
  - disturbance rejection quasilinear gain, 36, 38, 48
  - Fokker-Planck, 10, 53
  - Lyapunov, 29, 51, 176
  - multiple solutions, 46, 149
  - reference tracking quasilinear gain, 32, 37, 52
  - Riccati, 116, 176
  - SLOG synthesis, 174
  - SLQR synthesis, 169
  - transcendental, 20
- exogenous signals
  - disturbances, 4
  - references, 4
- filter
  - Butterworth, 80
- filter hypothesis, 55
- function
  - deadzone, 26
  - friction, 27
  - Lyapunov, 228
  - Lyapunov, 70, 229
  - piecewise-linear, 27
  - quantization, 28
  - relay, 26
  - saturation, 6, 23
  - saturation with deadzone, 27
  - saturation with quantization, 28
- gain
  - quasilinear, 4, 6, 22, 29
  - stochastically linearized, 4
- Gaussian process, 20
  - colored, 79
  - wide sense stationary, 20
- Gaussianization, 55
- harmonic balance, 2
- higher order systems, 141
- Jacobian linearization, 5, 7, 22
- jumping phenomenon, 48
- Lagrange multiplier, 241, 252
- large deviations, 48, 154

## 282 Index

- Linear Plant/Nonlinear Instrumentation, 1
- LQG, 167
  - instrumented (ILQG), 13, 167, 182
  - instrumented (LQG), 188
  - saturated (SLQG), 12, 167, 173
- LQR, 8, 167
  - instrumented (ILQR), 13, 167, 182
  - saturated (SLQR), 8, 12, 167
- performance
  - limitations, 171, 186
  - verification, 173, 177
- performance recovery, 13, 204
  - by redesign, 213
  - complete, 13, 209
  - partial, 13, 204
- Problems
  - Analysis, 3, 106, 131
  - Complete performance recovery, 3, 219
  - Narrow sense design, 3, 162, 198
  - Partial performance recovery, 3, 219
  - Wide sense design, 3, 198
- Quasilinear Control, 1
- rate saturation, 114, 125
  - bandwidth, 126
  - modeling, 126
- reference tracking, 66
  - random, in linear systems, 79
  - random, in LPNI systems, 90
  - with nonlinear actuator, 31
  - with nonlinear actuators and sensors, 40
  - with nonlinear sensor, 37
- resonance frequency, 82
  - random, 82, 135
  - satürating random, 96
- resonance peak, 82
  - random, 83, 135
  - satürating random, 96
- root locus, 134
  - calibration, 157
  - classical, 11
  - satürated, 11, 134, 143
  - rule of thumb, 207, 213, 216
- S-origination point, 150
- S-poles, 144
- S-termination point, 146
- S-truncation point, 156
- sensitivity function, 81
  - random, 10, 80, 84, 135
  - satürating, 92
  - satürating random, 10
- sensor
  - quantized, 40
- separation principle, 191, 214
- slanted step, 109
- stability
  - exponential, 172, 177, 187, 192
  - global asymptotic, 229, 230
  - global exponential, 172
  - Popov criterion, 173
  - semi-global, 169, 172
  - verification, 172, 177, 187, 192, 214
- steady state error, 66
  - with respect to parabola, 73
  - with respect to ramp, 73
  - with respect to step, 68
- stochastic linearization, 1, 4, 6, 20, 22
  - accuracy, 53, 215
  - state space equations, 49
- system types, 4, 10, 67, 74
- termination points, 134
- trackable domain, 4, 10, 66, 67, 69
- tracking error variance, 66
- tracking quality indicators, 10, 66, 79, 86, 90
  - $I_0$ , 98
  - $I_1$ , 86, 98
  - $I_2$ , 86, 98
  - $I_3$ , 86, 87
- transient performance, 66
- truncation points, 134