

## Index

- accidents, 4, 94, 97–98, 310–311, 315–316, 322–323, 326–327, 350–352
- Ackermann angle, 65–69
- active safety technologies (AST), 322–323, 350
- actuator, 7–9, 16, 25, 30, 133, 137, 152, 198, 217
- adaptive cruise control. *See* autonomous cruise control
- adhesion coefficient. *See* tire-road friction coefficient
- advanced traffic management systems (ATMS), 310–312
- advanced traveler information systems (ATIS), 312–314
- advanced vehicle control systems (AVCS), 314–318
- aerodynamic drag force, 5, 57–59, 153
- air supply system, 39–41, 43, 190, 198
- air-fuel ratio, 9, 11–16, 33–38, 49, 119
- airbags, 93–94
- algebraic Ricatti equation, 289, 291, 295
- algorithm development, 26–27
- algorithm implementation, 27–28
- algorithm in the loop testing, 29
- all-electric range, 178
- all-wheel drive (AWD), 8, 131–138, 148, 257
- anode, 188, 191–195
- anthropometry, 93
- anti-lock braking system (ABS), 8, 15–17, 93–97, 102, 232–234, 236, 241–254, 257, 263, 323
- anti-skid braking. *See* anti-lock braking system
- anti-spin acceleration, 233, 250–251. *See also* control, traction
- autocoding, 27–28
- Autocruise, 332–333, 337
- automated highway system (AHS), 4, 94, 345, 350
- automated lane following, 352–356
- automated steering, 315, 352–358
- autonomous cruise control (ACC), 213, 219, 224–229, 332, 337, 345
- autonomous guided vehicles, 323–324
- battery charge sustainability, 183
- battery tax, 158, 163
- beta ( $\beta$ ) method, 258
- bicycle model, 63–64
- biomechanics, 93
- block diagram, 363, 375–376
- body. *See* chassis
- bottom dead center (BDC), 35
- brake force, 60, 233, 257–258
- brake pressure, 16, 232–234, 258, 261
- brake specific fuel consumption (BSFC), 12, 37, 155–159, 166, 169–170
- brake steer, 257
- brakes, 7
- camber angle, 57, 389
- camshaft, 15, 34
- CAN bus, 16–17, 30, 152
- cascade studies, 25
- catalytic converter. *See* two-way catalytic converter (TWC)
- cathode, 188–198
- cell temperature, 191, 195
- center of gravity (CG), 54–55, 385
- certainty equivalence principle, 289
- characteristic speed, 66–67
- charge depleting (CD) mode, 178, 181
- charge sustaining (CS) mode, 178, 181, 183
- chassis, 6
- choked flow, 40, 47–48
- crashworthiness, 322
- circadian dip of alertness, 99
- closed-loop testing, 28–29
- closed-loop. *See* control, feedback
- cognitive engineering, 93
- collision avoidance, 102, 314–315, 322–328
- combined-slip tire model, 263–268
- combustion, 6, 9, 13, 36–37, 41, 44, 48, 119, 124
- commercial vehicle operation (CVO), 314–315
- communication network, 16–18

- communication
  - intervehicle, 317–318, 338, 340, 345
  - vehicle-to-infrastructure, 317–318, 338
- compensatory behavior, 102–103, 106
- compression stroke, 33–35
- compressor, 190–192, 196–201
- congestion, 3–5, 309–312, 332
- constant time-gap headway policy, 345
- constant-spacing headway policy, 345
- control, 363
  - adaptive, 11, 219–223, 302
  - air-fuel ratio, 8–9, 11–12, 37, 119–122
  - body, 7–8
  - clutch, 131–146
  - cruise, 5, 8, 14, 213–219, 332–337
  - derivative (D), 11
  - electronic transmission, 8–9, 14, 38
  - engine, 5–7, 33, 126, 232–233, 333
  - exhaust gas recirculation, 4, 7–9, 13, 16, 33–38, 40, 44, 126, 153, 177
  - feedback, 8, 11, 107, 119, 141, 178, 226, 290, 294, 335, 355, 364–369
  - feedforward, 14, 138, 163, 274, 335, 365
  - fuel injection, 7, 33
  - headway, 213, 224–229, 317
  - idle speed, 8–9, 14, 38, 126–128
  - Integral (I), 11
  - integrated vehicle, 132
  - lambda, 119
  - line pressure, 133
  - load-leveling, 148, 166–168
  - lockup, 131–133
  - optimal. *See* optimal control
  - piecewise, 138–146
  - point-follower, 338
  - powertrain, 7–8
  - preview, 107, 333–337
  - proportional (P), 8, 11, 369, 377–381
  - proportional plus derivative (PD), 11
  - proportional plus integral (PI), 8, 11, 14, 120–122, 141, 214–222, 333–335, 377–381
  - proportional plus integral plus derivative (PID), 8, 11, 217–219, 222–223, 377–381
  - roll. *See* rollover prevention
  - rule-based, 176, 244–248, 254
  - self-tuning, 220
  - sideslip, 267
  - sliding mode, 249–250
  - spark timing, 8–9, 13–14, 124–125, 126–128
  - state-feedback, 226–229, 290–291, 294, 382–384
  - supervisory, 17, 152–153, 157, 178–179
  - thermostat, 157–164
  - traction, 6, 232–234, 247–254
  - vehicle stability (VSC), 257–261, 266–268
  - vehicle-follower, 338
  - vehicle, 7–8
  - yaw, 266–267
- controlled system, 8
- controlled variable, 8
- controlled vehicle, 225–228
- controller, 8, 11
  - in the loop testing, 29
  - module, 21, 28
- convolution, 372
- cooling, 190, 198, 204
- cornering forces, 65
- cornering stiffness, 65–66
- corporate average fuel economy (CAFE), 322
- course angle, 55
- crank angle domain, 47–49
- crankshaft, 15, 33–34
- critical speed, 66–67
- crossover frequency, 95, 100
- crossover model principle, 95
- cycle beating, 177
- damping ratio, 121, 218, 222, 383
- dead reckoning. *See* inertial navigation
- degree-of-freedom (DOF), 70, 385
- delay, 36, 43–44, 49, 103–110, 119–122, 138–146
- development cycle, 22–24
- difference equations, 210–221
- differential, 6, 257
- differential braking, 3, 257–258, 266, 326–327, 352
- distributed computing, 17
- disturbance input, 8–9, 364
- dog actuator, 133–134
- drag torque. *See* torque, load
- drawbar force, 58
- drivability, 4, 33, 131, 178, 204
- drive cycle, 153, 160, 163, 165, 168, 203, 207–208
- driver adaptation, 94–95, 97–98
- driver model, longitudinal, 109–111
  - MacAdam's, 102, 106–107
  - predictive or preview, 106–109
  - transfer function, 102–104
- driveshaft, 6, 14–15, 62
- drivetrain, 6, 62–63, 132, 148, 205
- driving simulators, 94–95, 97–98, 100–101, 352
- earth-fixed reference frame. *See* inertial reference frame
- eigenvalue assignment. *See* pole placement
- electro-rheological fluid, 288
- electrolysis, 187
- electronic control unit (ECU), 7, 16, 21, 152–153, 177
- electronic rumble strip, 327, 352
- Electronic Stability Program (ESP). *See* control, vehicle stability
- electronic transmission control, 131–132
- emissions, 4, 9, 12–13, 35–38, 119, 124, 131, 148, 158, 180, 311
- energy management algorithms, 18
- energy storage device, 148
- engine, 6, 33–37
  - block vibrations, 124
  - control unit (ECU). *See* electronic control unit
  - crank, 38

- cycle, 33–35
- damage, 124
- diagnostics, 46–47
- four stroke, 33, 39
- friction, 36
- induction map, 44
- inertia, 36, 41, 45
- internal combustion (ICE), 6, 33–37, 39, 148–150, 155–158, 163, 166
- load, 41, 45, 126
- pumping, 36, 43
- spark ignition (SI), 6, 33–37, 39
- sweet spot, 155, 158
- volumetric efficiency, 47–48
- warm-up, 38
- Environmental Protection Agency (EPA) Cycle. *See* drive cycle
- equilibrium, 214–218
- equivalent consumption minimization strategy (ECMS), 173–175
- equivalent fuel consumption, 172
- erasable programmable read only memory (EPROM), 332
- ergonomics, 93
- error signal, 365
- exhaust gas recirculation (EGR), 7–9, 13, 16, 33–38
- exhaust stroke, 33–35
- expansion stroke. *See* power stroke
- fail-safe characteristics, 150
- final value theorem, 371
- fishhook maneuver, 262, 264
- flexible driving, 131–132
- Flexray, 16
- foolproof design, 132
- four-wheel drive (4WD), 7–8, 135–137, 232
- four-wheel-steering (4WS), 6, 8, 272–283
- frequency response, 100, 273, 278, 292, 374
- friction ellipse tire model, 57–58
- friction plate, 133–137
- front wheel drive (FWD), 7, 64, 69, 89
- front wheel steering (FWS), 272–283
- fuel
  - economy, 4, 153, 163–166, 172–178, 180–183
  - efficiency, 5, 208, 322
  - injection, 4, 16, 36, 44
  - system, 36, 48–49
- fuel-cell stack, 187–193
- fuel-cell vehicle, 4–5, 187–188, 201–208
- fuel-cell, 151, 158, 176, 187–188
- generalized coordinate, 385
- generalized force, 385
- generator, 148–152, 177–181
- global positioning system (GPS), 7, 94, 225, 312–314, 348
- grade, 59–62, 163, 213–214, 225, 333–336
- handcoding, 27
- hardware in the loop (HIL), 28–31
- heading angle, 55, 105, 328
- heave, 81
- Hough transformation, 349
- human factors engineering, 93
- humidification, 189–190, 196, 198
- hybrid electric vehicle (HEV), 5, 148, 201
- hybrid electric vehicle, micro, 149
  - parallel, 148–153, 166–172
  - power split, 148–153, 177–178
  - series, 148–153, 157–166
- hybrid electric vehicle, plug-in (PHEV), 178–183
- hybrid vehicle, 5, 17, 148–152
- hydrogen supply system, 190, 196, 198
- hysteresis, 120, 158
- ideal gas law, 35, 40, 43, 48
- ignition timing. *See* spark timing
- in-hub motors, 148–149
- incident management, 311–312
- induction stroke, 33–35
- induction-to-power (IP) delay, 36, 43–44, 138–146
- inertial navigation, 313, 328
- inertial reference frame, 55–56, 385–386
- initial value theorem, 371
- inputs, 8–9, 363
- instability, 368–369
- instrumentation, 7
- integrated motor assist (IMA), 150
- intelligent cruise control. *See* autonomous cruise control
- intelligent transportation system (ITS), 4–5, 94, 309–318, 324, 332, 348
- intelligent vehicle-highway system (IVHS). *See* intelligent transportation system
- invariant equation, 85
- ionization reaction, 189
- Kalman filter, 294–296, 351–352
- kinetic energy, 385–388
- knock, 36–37, 124–125
- Lagrange's method, 56, 385–387
- lambda-mu curve, 236–237
- lane
  - change maneuver, 281–283
  - geometry, 351–352
  - markers, 349, 351
  - sensing, 348–352
  - tracking, 348, 350–351
- lane-departure accidents. *See* single-vehicle road-departure (SVRD) accidents
- Laplace transform, 10, 370–372
- Laplace transform, properties, 371
- lateral acceleration, 15, 67–68, 74, 258, 267–268, 273–274, 284
- lead vehicle, 213, 224–230
- level-holding phase, 133
- LIN bus, 16

- linear quadratic (LQ) control. *See* optimal control
- linearization, 42, 72, 90, 214
- loop gain, 367
- lumped parameter models, 54
- Lyapunov equation, 86
- Lyapunov stability, 139, 145
- magic formula. *See* Pacejka tire model
- manifold air pressure (MAP), 8, 10, 14, 37
- manifold filling dynamics, 41, 43
- manifold, intake, 35, 41, 43  
 supply and return, 191–192
- map matching, 312
- mass airflow, 42–43, 47–48, 128
- maximum percentage overshoot, 121
- measurement noise, 368
- mechatronics, 3–5
- membrane hydration model, 193, 195
- message chips, 332–333
- minimum spark advance for best torque (MBT), 12–13, 36–37
- mobility, 3–5
- model-based design, 21–22
- motion sickness, 86
- multi-input multi-output (MIMO), 9–10, 199–203
- National Advanced Driving Simulator, 98
- National Highway Transportation Safety Association (NHTSA), 4, 232, 352
- natural frequency, 121, 382–383
- navigation, 93–94, 101, 312–313, 324
- near obstacle detection, 324
- networked control system, 18
- neutral steer, 65–67
- Newton's second law, 36, 45, 54–56, 58, 63–64, 66–67, 69–70, 234
- noise vibration harshness (NVH), 153, 167
- non-minimum phase (NMP), 273
- observer, 138–141, 356  
 disturbance, 141, 365  
 open-loop, 138
- open-loop. *See* control, feedforward
- optimal control, 8, 11, 289–290  
 dynamic programming (DP), 176–178  
 frequency shaped linear quadratic (FSLQ), 355  
 linear quadratic (LQ), 126–127, 289, 291  
 linear quadratic Gaussian (LQG), 294–295
- optimal operating points line (OOP-Line), 179–180
- Otto gasoline engine, 33
- outputs, 8–9, 363
- oversteer, 65–67
- oxygen, 187–189
- Pacejka tire model, 57, 236–238, 258–260, 264
- Padé approximation, 104
- path planning, 101
- path projection, 350–352
- percentage of road departure (PRD), 99–101
- performance index, 291
- piecewise affine system (PWA), 138–141
- pitch, 55, 386
- planetary gear, 149–151, 177–178
- plant, 10, 364
- plate friction coefficient, 140
- platooning, 224, 315, 317–318, 337–343
- plug-n-play, 18
- pneumatic tire, 55, 57, 234–235
- pole placement, 222, 226, 230, 382–384
- poles, 376–377
- power management, 176, 203–204
- power spectral density (PSD), 77–79
- power stroke, 33–35
- powertrain, 6
- precognitive behavior, 102
- primary power source, 148, 155
- proton exchange membrane (PEM), 189
- pursuit behavior, 102
- quantization, 340
- quarter-car model, 81
- ramp following, 133
- ramp-metering, 310–311
- range, 110, 213, 225–227, 324–326  
 extender, 148  
 rate, 110, 324–326
- rattle space. *See* suspension stroke
- reactant partial pressure, 191, 195
- rear-wheel drive (RWD), 64, 89
- rear-wheel steering (RWS), 272–283
- recursive least squares (RLS), 50, 219–221, 355
- reference (set-point) input, 8–9, 108, 203, 213, 224, 226, 364, 383
- regenerative braking, 148–149, 181, 184
- requirements, 21–25
- reversible power source, 148
- ride model, 81–86
- ride quality, 85–86, 287
- risk homeostasis theory, 95–97, 101
- road condition, 232, 250
- road departure accidents. *See* single-vehicle road-departure (SVRD) accidents
- road model, 77–79
- roll, 55, 385
- rolling resistance force, 57–59, 153–155, 181
- rollover prevention, 261, 266–268
- root locus method, 215, 379–382
- route planning, 312
- run-off-road. *See* single-vehicle road departure
- safe distance, 326
- safety, 4, 309–318  
 active, 322–323  
 passive, 322–323

- saturation, 340  
 sensitivity, 368  
 sensor, 8, 14, 323–326  
   acceleration, 15  
   crankshaft angular position and speed, 15  
   exhaust gas oxygen (EGO), 8, 12, 15, 37, 119–121  
   forward-looking, 324  
   infrared, 324  
   knock, 15  
   laser, 323  
   linear variable differential transformer (LVDT), 15  
   manifold absolute pressure (MAP), 8, 10, 14, 37  
   mass airflow (MAS), 15, 37  
   radar, 324  
   slip, 15  
   throttle angle, 15, 126  
   ultrasonic, 323–324  
   vehicle speed, 15  
   vision, 323, 351  
 settling time, 121, 215–216, 258, 378  
 shift map, 38  
 shift quality, 131  
 side-slip angle, 55, 257–260, 262, 264, 266–267  
 single-input single-output (SISO), 9–10, 95, 107, 198–199  
 single-vehicle-road-departure (SVRD), 97–98, 326–327, 350–352  
 site-specific information, 332–337  
 skyhook damper, 287–290  
 sliding surface, 267  
 slip, 57  
   angle, 57, 267  
   lateral, 57  
   longitudinal, 60, 237–239  
   optimal, 234  
   slip ratio, 233–234  
 Smith predictor, 120–122  
 Society of Automotive Engineers (SAE), 54–55  
 spacing, 337–345  
 spark command, 36  
 spark ignition (SI), 16, 33–35, 39, 124, 129  
 spark timing, 13, 37–38, 124–125  
   advanced, 36–37, 124–125  
   retarded, 124–125  
 speed ratio, 133–136  
 sprung mass acceleration, 85–86, 287–290  
 sprung mass, 81–82  
 stability derivatives, 73, 389  
 stack current, 191–192, 196, 200–202  
 stack voltage, 191, 193–199  
 state equation, 45–46, 82, 107, 126, 225–230, 289, 353, 369–370  
 state estimation. *See* Kalman filter and observer, state  
 state space, 369–370  
 state variable, 370  
 state-of-charge (SOC), 153, 157–166, 172–173, 176–184  
 static stability factor (SSF), 267  
 steer angle, 55, 64, 103  
 steering, 6  
 stoichiometric, 9, 12, 35–37, 119  
 stopping distance and time, 61  
 string stability, 343–345  
 suspension, 6–7, 287–288  
   active, 7, 81–82, 287–303  
   passive, 81–82, 86–88, 287–290  
   semi-active, 7, 287–288  
   strut type, 7  
 suspension actuator, 16  
 suspension stroke, 81–82, 86, 290, 292, 294–296, 299  
 swappable. *See* plug-n-play switching function, 249  
 system, 363  
 target hardware. *See* controller module  
 Taylor series, 90, 214  
 testing and validation, 21, 28–31  
 thermal capacitance, 140  
 thermal resistance, 140  
 throttle, 39–40, 126–128  
   actuator, 16, 126–128  
   angle, 39–40, 42, 126–128  
   control, 126–128  
   motor, 126  
 time delay. *See* delay  
 time to collision (TTC), 326  
 time to lane crossing (TLC), 326–327, 350–352  
 tire axis system, 55–56  
 tire deflection. *See* wheel hop  
 tire-road friction coefficient, 57, 233–235, 250  
 toll debiting, 312, 315  
 top dead center (TDC), 10, 13, 35–36, 124  
 torque converter, 7, 45, 63, 131–133, 150  
 torque, load, 41, 45, 128  
   brake, 60  
   engine, 41, 44–45, 128  
   self-aligning, 56–57  
 Toyota Hybrid System (THS), 150–151, 177  
 traction control system (TCS). *See* control, traction  
 tractive force, 56, 62  
 transfer function, 372–374  
 transmission control unit (TCU), 152–153  
 transmission, automatic, 6, 131–132  
   continuously variable (CVT), 6, 131–133, 151  
   electronically controlled (ECT), 6, 131–133  
   manual, 6, 131  
 two-way catalytic converter (TWC), 9, 12, 37, 119  
 two-wheel drive (2WD), 135–137  
 ultra low emission vehicles (ULEV), 4  
 uncertainty, 365–367, 122, 138–146

- understeer coefficient, 66
- understeer, 65–67
- unsprung mass, 81–82, 287
- upshift, 133
  
- v-diagram model, 24–25
- vehicle coordinate system, 54–58, 385–386
- vehicle dynamics control (VDC). *See* control, vehicle stability
- vehicle dynamics, lateral, 64–77
  - longitudinal, 58–64
  - vertical, 77–88
- virtual desired trajectory (VDT), 356
  
- wall-wetting, 48–49
- waterfall model, 24
- wet-friction clutch, 137
- wheel hop, 81–82, 86, 291–292, 295, 299
  
- x-by-wire, 16
  
- yaw moment, 257–261, 264, 268
- yaw rate following, 266–268
- yaw-roll model, 261–264
- yaw, 55, 386
  
- zeros, 376–377
- Ziegler-Nichols tuning rules, 377–379