

# Index

- 3D body model, 418–420
- 3D morphable model, 416–418, 421
- 3D reconstruction, 297, 305–306, 312–313, 380
  - from structured light, 314–315
  - pipeline, 376–377
  - volumetric graph cuts, 378–380
- action recognition, 501–502, 504
- activation, 133
- active appearance model, 405–410, 421
- active contour model, 389–393, 420
- active shape model, 388, 396–405, 421
  - 3D, 405
- adaboost, 160, 161, 167, *see also* boosting
- affine transformation, 327–328
  - learning, 332–333
- alignment of shapes, 397–398
- alpha-beta swap, 261, 265
- alpha-expansion algorithm, 244–247, 261
- ancestral sampling, 186
- application
  - 3D reconstruction, 297, 376–380
  - action recognition, 501–502, 504
  - animation synthesis, 449–450
  - augmented reality tracking, 324, 340, 347–350
  - background subtraction, 65, 67, 252
  - body pose estimation, 108, 129, 164–165, 220
  - body tracking, 421
  - changing face pose, 103
  - contour tracking, 453, 478
  - denoising, 227, 230–231, 239, 247
  - depth from structured light, 314–315
  - face detection, 71, 99–100, 106, 161–163, 167
  - face recognition, 102–103, 424, 430–432, 436, 447–448, 450
  - face synthesis, 259–260
  - finding facial features, 219, 223
  - fitting 3D body model, 418–420
  - fitting 3D shape model, 416–418
  - gender classification, 133, 160, 167
  - gesture tracking, 195, 216
  - image retargeting, 255–257
  - interactive segmentation, 253–254, 263
  - multiview reconstruction, 378–381
  - object recognition, 100–101, 106, 483–501
  - panorama, 349, 351
  - pedestrian detection, 161–163
  - pedestrian tracking, 476
  - Photo-tourism, 377–378
  - scene recognition, 483, 499
  - segmentation, 101–102, 220–222, 389–393
  - semantic segmentation, 163, 167
  - shape from silhouette, 316–319
  - sign language interpretation, 195, 197, 216
  - skin detection, 64–65, 67
  - SLAM, 477–478, 480
  - stereo vision, 216–219, 222, 254–255, 263
  - super-resolution, 257
  - surface layout recovery, 163–164

- application (*cont.*)
  - TensorTextures, 448–449
  - texture synthesis, 257–259, 263
  - tracking head position, 129–130
  - Video Google, 500–501
- approximate inference, 185
- AR Toolkit, 350
- argmax function, 508
- argmin function, 508
- articulated models, 414–416
  - pictorial structures, 220
- asymmetric bilinear model, 438–443
- augmented reality, 324, 340, 347–350
- augmenting paths algorithm, 234–235, 262
- author–topic model, 493–495, 503
- auto-calibration, 372
  
- back propagation, 159
- background subtraction, 65, 67, 252
- bag of words, 285–286, 484–487, 503
- Baum-Welch algorithm, 212
- Bayes' Rule, 13
- Bayesian approach to fitting, 29–30
- Bayesian belief propagation, 208–211, 223
  - loopy, 215
  - sum-product algorithm, 208–209
- Bayesian linear regression, 111–114
- Bayesian logistic regression, 138–142
- Bayesian model selection, 43, 431
- Bayesian network, 175–178
  - comparison to undirected, 181
  - learning, 189
  - sampling, 186–187
- Bayesian nonlinear regression, 117
- belief propagation, 208–211, 223
  - loopy, 215
  - sum-product algorithm, 208–209
- Bernoulli distribution, 17–18
  - conjugate prior, 24, 26
  - relation to binomial, 25
- beta distribution, 17, 19
- between-individual variation, 427
- BFGS, 515
- bilateral filter, 293
- bilinear model, 451
  - asymmetric, 438–443
  - symmetric, 443–445
- binary classification, 60–61, 133–156
- binomial distribution, 25
- bivariate distribution, 44
- block diagonal matrix, 531
- blurring, 272
- body pose estimation, 108, 129, 164–165, 220
- body tracking, 421
- boosting, 167
  - adaboost, 161
  - jointboost, 163
  - logitboost, 153
- bottom-up approach, 387
- branching logistic regression, 153–155
- Brownian motion, 463
- Broyden Fletcher Goldfarb Shanno, 515
- bundle adjustment, 374–376, 381
  
- calibration
  - from 3D object, 304–305, 311–312
  - from a plane, 337–338, 351
- calibration target, 311
  - 3D, 305
  - planar, 337
- camera
  - geometry, 319
  - orthographic, 321
  - other camera models, 319
  - orthographic, 382
  - parameters, 302
  - pinhole, 297–304
    - in Cartesian coordinates, 302
    - in homogeneous coordinates, 308–309
  - projective, 297
  - weak perspective, 321
- camera calibration
  - from 3D object, 304–305, 311–312
  - from a plane, 337–338, 351
- Canny edge detector, 279–280, 390
- canonical correlation analysis, 438
- capacity, 233
- cascade structured classifier, 162

- categorical distribution, 17, 19–20
  - Bayesian fitting, 39–41
  - conjugate prior, 24, 27
  - fitting, 38–41
  - MAP fitting, 39
  - ML fitting, 38
  - relation to multinomial, 25
- chain model, 195–202, 205–211, 453
  - directed, 196
  - learning, 212
  - MAP inference, 198
  - marginal posterior inference, 205
  - sum product algorithm in, 209
  - undirected, 196–197
- changing face pose, 103
- Chapman–Kolmogorov equation, 455
- class conditional density function, 61, 72
- classification, 55, 133–160, 166
  - adaboost, 160
  - applications of, 160–166
  - Bayesian logistic regression, 138–142
  - binary, 60–61, 133–156
  - boosting, 153
  - cascade structure, 162
  - dual logistic regression, 144–146
  - fern, 159
  - gender, 160
  - kernel logistic regression, 146–147
  - logistic regression, 60, 133–136
  - multiclass, 156–158
  - multilayer perceptron, 159
  - nonlinear logistic regression, 142
  - non-probabilistic models, 159–160
  - one-against-all, 156
  - random classification tree, 158–159
  - random forest, 159
  - relevance vector, 147–149
  - support vector machine, 160
  - tree, 153–156, 167
  - weak classifier, 153
- clique, 179, 229
  - maximal, 179
- closed set face identification, 431
- clustering, 82, 291–292
- coarse-to-fine approach, 256, 404
- collinearity, 329, *see* homography
- color model, 64, 65, 253
- combining variables, 215
- condensation algorithm, 472–476
  - for tracking contour, 478
- condition number, 524
- conditional independence, 173
  - in a directed model, 176
  - in an undirected model, 179
- conditional probability distribution, 12
  - of multivariate normal, 48
- conditional random field, 260
  - 1D, 212
  - 2D, 247–250
- conic, 321, 351, 388
- conjugacy, 24
  - Bernoulli/beta, 26
  - categorical/Dirichlet distribution, 27
  - normal/normal inverse Wishart, 27
  - normal/normal-scaled inverse gamma, 27
  - self-conjugacy of normal, 49
- conjugate gradient method, 515
- constellation model, 495–499
- constraint edge, 241, 262, 264
- continuous random variable, 9
- contour model, 389–393
- contour tracking, 453, 478
- contrastive divergence, 190–191
  - persistent, 191
- convex function, 137, 510
- convex potentials, 243, 244
- corner detection, 279, 281–282, 292
  - Harris corner detector, 281–282
  - SIFT, 282
- cost function, 509
- covariance, 15
- covariance matrix, 23, 44
  - diagonal, 44
  - full, 44
  - spherical, 44
- CRF, 260
  - 1D, 212
  - 2D, 247–250

- cross product, 519
- cross-ratio, 352
- cut on a graph, 233
  - cost, 233
  - minimum, 233
- damped Newton, 515
- data association, 396, 475
- decision boundary, 69, 134
- Delaunay triangulation, 371
- delta function, 508
- denoising, 227, 230–231
  - binary, 239
  - multilabel, 245, 247
- dense stereo vision, 216–219, 254–255, 371
- depth from structured light, 314–315
- derivative filter, 272
- descriptor, 283–287, 293
  - bag of words, 285–287
  - histogram, 283–284
  - HOG, 285
  - SIFT, 284
- determinant of matrix, 521
- diagonal covariance matrix, 44
- diagonal matrix, 520
  - inverting, 531
- dictionary of visual words, 286, 483
- difference of Gaussians, 273
- digits
  - modeling, 104
- dimensionality reduction, 287–293
  - dual PCA, 290
  - K-Means, 291–292
  - PCA, 289–290
- direct linear transformation algorithm, 333–335
- direct search method, 516
- directed graphical model, 175–178
  - chain, 196
  - comparison to undirected, 181
  - establishing conditional independence relations in, 176
  - for grids, 250–251
  - learning, 189
  - Markov blanket, 176
  - sampling, 186–187
- Dirichlet distribution, 17, 20–21
- discrete random variable, 9
- discriminative model, 56
  - classification, 133–160
  - regression, 108–131
- disparity, 217, 254
- displacement expert, 129–130
- distance transform, 390
- distribution
  - Bernoulli, 17–18
  - beta, 17, 19
  - binomial, 25
  - categorical, 17, 19–20
  - conjugate, 24
  - Dirichlet, 17, 20–21
  - gamma, 85
  - multinomial, 25
  - multivariate normal, 22–23, 44–50
  - normal, 17
  - normal inverse Wishart, 17, 23–24
  - normal-scaled inverse gamma, 17, 21–22
  - probability, 17–25
  - t-distribution, 82–88
  - univariate normal, 21
- DLT algorithm, 333–335
- dolly zoom, 320
- domain of a random variable, 17
- dot product, 519
- dual
  - linear regression, 124–126
  - logistic regression, 144–146
  - parameterization, 124, 144
  - PCA, 290
- dynamic programming, 198, 222
  - for stereo vision, 222
  - in a chain, 199–202
  - in a loop, 226
  - in a tree, 202–205
- E-step, 95, 76, 97–98
- edge detection, 279, 292
  - Canny, 279–280, 390
- edge filter, 272
- eight-point algorithm, 363–364
- EKF, 466–467
- EM algorithm, 75–77, 94–99
  - E-step, 76, 95, 97–98

- for factor analyzer, 90–93
  - for mixture of Gaussians, 79–82
  - for t distribution, 86–88
  - lower bound, 96
  - M-step, 76, 98–99
- empirical max-marginals, 186
- energy minimization, 178
- epipolar constraint, 356
- epipolar geometry, 355
- epipolar line, 356
  - computing, 359
- epipole, 356–357
  - computing, 359
- essential matrix, 357–359, 380
  - decomposition, 360–361
  - properties, 359
- estimating parameters, 28–41
- Euclidean transformation, 323–325
  - learning, 331–332
- evidence, 13, 42
  - framework, 43
- expectation, 14–15
- expectation maximization, 75–77, 94–99, 105
  - E-step, 76, 95, 97–98
  - for factor analyzer, 90–93
  - for mixture of Gaussians, 79–82
  - for t-distribution, 86–88
  - lower bound, 96
  - M-step, 76, 98–99
- expectation step, 76, 95, 97–98
- expert, 154
- exponential family, 26
- extended Kalman filter, 466–467
- exterior orientation problem, 309, 319
  - 3D scene, 304, 309–311
  - planar scene, 335–337
- extrinsic parameters, 302
  - estimation, 319
  - learning
    - 3D scene, 304, 309–311
    - planar scene, 335–337
- face
  - clustering, 431, 447
  - detection, 71, 72, 99–100, 106, 161–163, 167
  - recognition, 102–103, 424, 436, 447–448, 450
    - across pose, 103
    - as model comparison, 430–432
    - closed set identification, 431
    - open set identification, 431
    - synthesis, 259–260
    - verification, 424
- face model
  - 3D morphable, 416–418
- facial features
  - aligning, 450
  - finding, 219, 223
- factor analysis, 88, 105, 424
  - as a marginalization, 90
  - learning, 90–93
  - mixture of factor analyzers, 94
  - probability density function, 89
- factor graph, 193, 208, 223
- factorization, 374
  - of a probability distribution, 175, 178
  - Tomasi-Kanade, 380, 382
- feature, 380
  - tracking, 380
- feature descriptor, 283–287
  - bag of words, 285–287
  - histogram, 283–284
  - HOG, 285
  - SIFT, 284
- feature detector, 279
  - Canny edge detector, 279–280
  - Harris corner detector, 281–282
  - SIFT detector, 282
- fern, 159
- field of view, 301
- filter, 271
  - bilateral, 293
  - derivative, 272
  - different of Gaussian, 273
  - edge, 272
  - Gabor, 273
  - Haar, 275
  - Laplacian, 273
  - Laplacian of Gaussian, 273
  - Prewitt, 272
  - Sobel, 273
- fitting probability models, 28–41
- fixed interval smoothing, 462–463
- fixed lag smoothing, 461–462

- flow
  - optical, 255
  - through graph, 233
- focal length, 297
  - parameter, 299
- forest, 159, 165
- forward-backward algorithm, 206–208
- Frobenius norm, 530
- frustum, 348
- full covariance matrix, 44
- fundamental matrix, 361–362, 380
  - decomposition, 371
  - estimation, 362–364
  - relation to essential matrix, 362
- Gabor energy, 275
- Gabor filter, 273
- gallery face, 431
- gamma distribution, 85
- gamma function, 19
- gating function, 154
- Gauss-Newton method, 514–515
- Gaussian distribution, *see* normal distribution
- Gaussian Markov random field, 264
- Gaussian process
  - classification, 147
  - latent variable model, 410–414, 437
  - multifactor, 449–450
  - regression, 119, 131
- gender classification, 133, 160, 167
- generalized Procrustes analysis, 397–398
- generative model, 56, 57
  - comparison to discriminative model, 63
- geodesic distance, 254
- geometric invariants, 352
- geometric transformation model, 323–347
  - 2D, 323–330
  - application, 347–349
  - learning, 330
- gesture tracking, 195, 216
- Gibbs distribution, 178, 228
- Gibbs sampling, 187–188
- GPLVM, 410–414, 437
  - multifactor, 449–450
- GrabCut, 253–254
- gradient vector, 136, 511
- graph cuts, 231–247, 261
  - alpha-expansion, 244–247
  - applications of, 251–257
  - binary variables, 235–239
  - efficient reuse of solution, 262
  - multilabel, 239–247
  - reparameterization, 237–239
  - volumetric, 378–380
- graphical model, 173–192
  - applications in computer vision, 181
  - chain, 195, 453
  - directed, 175–178
    - learning, 189
    - sampling, 186–187
  - directed versus undirected, 181
  - factor graph, 193
  - grid-based, 213
  - plate notation, 177
  - tree, 195
  - undirected, 178
    - learning, 189–192
    - sampling, 187–188
- Gray codes, 315
- grid-based model, 213, 227–264
  - applications, 261
  - directed, 250–251
- Haar filter, 162, 275
- hand model, 415, 416, 422
- Harris corner detector, 281–282
- head position
  - tracking, 129–130
- Heaviside step function, 142, 153, 508
- Hessian matrix, 136, 510
- hidden layer, 159
- hidden Markov model, 182, 196, 197, 216, 223
- hidden variable, 73, 74
  - representing transformations, 104
- higher order cliques, 250, 263
- Hinton diagram, 9
- histogram equalization, 270
- histogram of oriented gradients, 285, 293

- histogram, RGB, 283
- HMM, 182, 196, 197, 223
- HOG descriptor, 285, 293
- homogeneous coordinates, 306
- homography, 328–329
  - learning, 333–335
  - properties, 339–341
- human part identification, 164–165
- human performance capture, 318, 319
- human pose estimation, 220
- hyperparameter, 18
- hysteresis thresholding, 280
  
- ICP, 395
- ideal point, 308
- identity, 424
- identity/style model, 424
  - asymmetric bilinear, 438–443
  - multifactor GPLVM, 449–450
  - multilinear, 446
  - nonlinear, 437–438
  - PLDA, 433–437
  - subspace identity model, 427–432
  - symmetric bilinear, 443–445
- identity matrix, 520
- image denoising, 227, 230–231
  - binary, 239
  - multilabel, 247
- image descriptor, 293
- image plane, 297
- image processing, 269–287, 292
- image quilting, 257–259
- image retargeting, 255–257
- image structure tensor, 281
- importance sampling, 476
- incremental fitting
  - of logistic regression, 150–152
- independence, 14
  - conditional, 173
- inference, 56
  - algorithm, 56
  - empirical max-marginals, 186
  - in graphical models with loops, 214
  - MAP solution, 184
  - marginal posterior distribution, 184
  - maximum marginals, 185
  - sampling from posterior, 185
- innovation, 458
- integral image, 275
- intensity normalization, 269
- interactive segmentation, 253–254, 263
- interest point detection, 279, 292
  - Harris corner detector, 281–282
  - SIFT, 282
- intersection of two lines, 321
- intrinsic matrix, 302
- intrinsic parameters, 302
  - learning
    - from 3D object, 304–305, 311–312
    - from a plane, 337–338
- invariant
  - geometric, 352
- inverse of a matrix, 520, 525–527
  - computing for large matrices, 530
- Ishikawa construction, 261
- iterated extended Kalman filter, 467
- iterative closest point, 395
  
- Jensen’s inequality, 96
- joint probability, 10
- jointboost, 163
- junction tree algorithm, 215
  
- K-means algorithm, 82, 291–292
- Kalman filter, 182, 455–463
  - temporal and measurement models, 463
  - derivation, 456
  - extended, 466–467
  - iterated extended, 467
  - recursions, 459
  - smoothing, 461–463
  - unscented, 467–471
- Kalman gain, 457
- Kalman smoothing, 461–463
- kernel function, 118–120, 146
- kernel logistic regression, 146–147
- kernel PCA, 290, 293
- kernel trick, 119
- Kinect, 164
- kinematic chain, 415
- Kullback-Leibler divergence, 97

- landmark point, 389
- landscape matrix, 520
- Laplace approximation, 139, 140, 148
- Laplacian filter, 273
- Laplacian of Gaussian filter, 273
- latent Dirichlet allocation, 487–492, 503
  - learning, 490–492
- latent variable, 73, 74
- LDA (latent Dirichlet allocation), 487–492, 503
  - learning, 490–492
- LDA (linear discriminant analysis), 450
- learning, 28, 56
  - Bayesian approach, 29–30
  - in chains and trees, 212
  - in directed models, 189
  - in undirected models, 189–192
  - least squares, 32
  - maximum a posteriori, 28
  - maximum likelihood, 28
- learning algorithm, 56
- least median of squares regression, 350
- least squares, 32
  - solving least squares problems, 528
- likelihood, 13
- line, 321, 351
  - epipolar, 356
  - joining two points, 321
- line search, 515
- linear algebra, 519–532
  - common problems, 528–530
- linear discriminant analysis, 450
- linear regression, 108–110
  - Bayesian approach, 111–114
  - limitations of, 110
- linear subspace, 89
- linear transformation, 522
- local binary pattern, 276, 293
- local maximum/minimum, 137, 509
- log likelihood, 31
- logistic classification tree, 153–156
- logistic regression, 60, 133–136
  - Bayesian approach, 138–142
  - branching, 153–155
  - dual, 144–146
  - kernel, 146–147
  - multiclass, 156–158
  - nonlinear, 142
- logistic sigmoid function, 133
- logitboost, 153
- loopy belief propagation, 215
  - applications, 223
- M-estimator, 350
- M-step, 76, 95, 98–99
- magnitude of vector, 519
- manifold, 287
- MAP estimation, 28
- marginal distribution, 10
  - of multivariate normal, 47
- marginal posterior distribution, 184
- marginalization, 10
- Markov assumption, 196, 453
- Markov blanket, 176, 179
  - in a directed model, 176
  - in an undirected model, 179
- Markov chain Monte Carlo, 187
- Markov network
  - learning, 189–192
  - sampling, 187–188
- Markov random field, 179, 182, 227, 228, 260
  - Gaussian, 264
  - applications, 251–257, 261
  - higher order, 250, 263
  - pairwise, 229
- Markov tree, 182
- matrix, 520
  - block diagonal, 531
  - calculus, 527–528
  - condition number, 524
  - determinant, 521
  - diagonal, 520
  - Frobenius norm, 530
  - identity, 520
  - inverse, 520, 525–527
  - inverting large, 530
  - landscape, 520
  - multiplication, 520
  - null space, 522, 525
  - orthogonal, 521
  - portrait, 520
  - positive definite, 521
  - rank, 524



- rotation, 521
- singular, 520
- square, 520
- trace, 521
- transpose, 520
- matrix determinant lemma, 532
- matrix inversion lemma, 113, 532
- max flow, 233
  - algorithms, 262
  - augmenting paths algorithm, 234–235
- max function, 508
- maximal clique, 179
- maximization step, 76, 95, 98–99
- maximum a posteriori estimation, 28
- maximum likelihood estimation, 28
- maximum marginals, 185
- MCMC, 187
- measurement incorporation step, 455
- measurement model, 453
- Mercer's theorem, 119
- min cut, 233
- min function, 508
- minimum direction problem, 310, 529
- mixture model
  - mixture of experts, 168
  - mixture of factor analyzers, 94, 105
  - mixture of Gaussians, 77–82, 105
  - mixture of PLDAs, 437
  - mixture of t-distributions, 94, 105
  - robust, 94
- ML estimation, 28
- model, 56
  - discriminative, 56
  - generative, 56, 57
- model comparison, 42
- model selection, 431
- moment, 14–15
  - about mean, 15
  - about zero, 15
- MonoSLAM, 477–478
- morphable model, 416–418
- mosaic, 349, 351
- MRF, 179, 182, 227, 228, 260
  - applications, 251–257, 261
  - Gaussian, 264
  - higher order, 250, 263
  - pairwise, 229
- multiclass classification, 156–158
  - multiclass logistic regression, 156–158
  - random classification tree, 158–159
- multifactor GPLVM, 449–450
- multifactor model, 446
- multilayer perceptron, 159, 167
- multilinear model, 446, 451
- multiview geometry, 380
- multiview reconstruction, 305–306, 313, 372, 378–381
- multinomial distribution, 25
- multiple view geometry, 354
- multivariate normal distribution, 17, 44–50
- multiview reconstruction, 312
- naïve Bayes, 65
- neural network, 159
- Newton method, 137, 512–514
- non-convex potentials, 244
- nonlinear identity model, 437–438
- nonlinear logistic regression, 142
- nonlinear optimization, 509–518
  - BFGS, 515
  - conjugate gradient method, 515
  - Gauss-Newton method, 514–515
  - line search, 515
  - Newton method, 512–514
  - over positive definite matrices, 518
  - over rotation matrices, 517
  - quasi-Newton methods, 515
  - reparameterization, 516
  - steepest descent, 511–512
  - trust-region methods, 515
- nonlinear regression, 114
  - Bayesian, 117
- nonstationary model, 461
- norm of vector, 519
- normal distribution, 17, 44–50
  - Bayesian fitting, 35
  - change of variable, 50
  - conditional distribution, 48
  - covariance decomposition, 45
  - MAP fitting, 33

- normal distribution (*cont.*)
  - marginal distribution, 47
  - ML fitting, 30
  - multivariate, 17, 22–23
  - product of normals, 48, 52
  - self-conjugacy, 49
  - transformation of variable, 47
  - univariate, 17, 21
- normal inverse Wishart distribution, 17, 23–24
- normal-scaled inverse gamma distribution, 17, 21–22
- normalized camera, 299
- normalized image coordinates, 310
- null space, 522, 525
  
- object recognition, 100–101, 106, 483–501
  - unsupervised, 492
- objective function, 509
- offset parameter, 300
- one-against-all classifier, 156
- open-set face identification, 431
- optical axis, 297
- optical center, 297
- optical flow, 255
- optimization, 509–518
  - BFGS, 515
  - conjugate gradient method, 515
  - Gauss-Newton method, 514–515
  - line search, 515
  - Newton method, 512–514
  - over positive definite matrix, 518
  - over rotation matrix, 517
  - quasi-Newton methods, 515
  - reparameterization, 516
  - steepest descent, 511–512
  - trust-region methods, 515
- orthogonal matrix, 521
- orthogonal Procrustes problem, 311, 332, 529
- orthogonal vectors, 519
- orthographic camera, 321, 382
- outlier, 82, 342
  
- pairwise MRF, 229
- pairwise term, 198, 232
- panorama, 349, 351
- parametric contour model, 389–393
  - part of object, 488
- particle filtering, 472–476
- partition function, 178
- PCA, 289–290
  - dual, 290
  - kernel, 290, 293
  - probabilistic, 89, 401–402
- PDF, 9
- PEaRL algorithm, 345, 350
- pedestrian detection, 161–163
- pedestrian tracking, 476
- per-pixel image processing, 269
- persistent contrastive divergence, 191
- perspective projection, 298
- perspective-n-point problem, 304, 319
- Phong shading model, 416
- Photo-tourism, 377–378
- photoreceptor spacing, 300
- pictorial structure, 219, 222
- pinhole, 297
- pinhole camera, 297–304, 354
  - in Cartesian coordinates, 302
  - in homogeneous coordinates, 308–309
- plate, 177
- PLDA, 433–437
- PnP problem, 304, 319
- point distribution model, 396–405
- point estimate, 29
- point operator, 269
- polar rectification, 371
- portrait matrix, 520
- pose estimation, 350
- positive definite matrix, 521
  - optimization over, 518
- posterior distribution, 13
- potential function, 178
- potentials
  - convex, 243
  - non-convex, 244
- Potts model, 244, 265
- PPCA, 401–402
  - learning parameters, 401
- prediction step, 455
- predictive distribution, 28
- preprocessing, 100, 269–292
- Prewitt operators, 272

- principal component analysis, 289–290
  - dual PCA, 290
  - probabilistic, 89, 401–402
- principal direction problem, 529
- principal point, 297
- prior, 13
- probabilistic latent semantic analysis, 503
- probabilistic linear discriminant analysis, 433–437
- probabilistic principal component analysis, 89, 105, 401–402
  - learning parameters, 401
- probability
  - conditional, 12
  - joint, 10
  - marginal, 10
- probability density function, 9
- probability distribution, 17–25
  - fitting, 28–41
- probe face, 431
- Procrustes analysis
  - generalized, 397–398
- Procrustes problem, 311, 529
- product of experts, 179
- projective camera, 297
- projective pinhole camera, 297
- projective reconstruction, 313
- projective transformation, 328–329
  - fitting, 333–335
  - properties, 339–341
- propose, expand and relearn, 345, 350
- prototype vector, 291
- pruning graphical models, 214, 219
  
- quadri-focal tensor, 373
- quadric, 415
  - truncated, 415
- Quasi-Newton methods, 515
- quaternion, 517
  
- radial basis function, 115, 151
- radial distortion, 303
- random classification tree, 158–159
- random forest, 159
- random sample consensus, 342–344, 350
  - sequential, 345
- random variable, 9
  - continuous, 9
  - discrete, 9
  - domain of, 17
- rank of matrix, 524
- RANSAC, 342–344, 350
  - sequential, 345
- Rao-Blackwellization, 476
- reconstruction, 297, 305–306, 312–313
  - from structured light, 314–315
  - multiview, 372, 381
  - projective, 313
  - two view, 364
- reconstruction error, 288
- reconstruction pipeline, 376–377, 380
- rectification, 216, 368, 380
  - planar, 368
  - polar, 371
- region descriptor, 283–286
  - bag of words, 285–287
  - histogram, 283–284
  - HOG, 285
  - SIFT, 284
- regression, 55, 108–131
  - Bayesian linear, 111–114
  - dual, 124–126
  - Gaussian process, 119, 131
  - linear, 58, 108–110
    - limitations of, 110
  - nonlinear, 114
  - nonlinear, Bayesian, 117
  - polynomial, 115
  - relevance vector, 127–128
  - sparse, 120
    - to multivariate data, 128
- relative orientation, 360, 380
- relevance vector
  - classification, 147–149
  - regression, 127–128
- reparameterization
  - for optimization, 516
  - in graph cuts, 237–239
  - multilabel case, 243
- reprojection error, 355
- resection-intersection, 374
- responsibility, 79
- robust density modeling, 82–88

- robust learning, 342, 350
  - PEaRL, 345
  - RANSAC, 342–344
  - sequential RANSAC, 345
- robust mixture model, 94
- robust subspace model, 94
- rotation matrix, 521
  - optimization over, 517
- rotation of camera, 340
- sampling
  - ancestral, 186
  - directed models, 186–187
  - Gibbs, 187
  - undirected models, 187–188
- sampling from posterior, 185
- scalar product, 519
- scale invariant feature transform, 282, 284
- SCAPE, 418–420
- scene model, 499
- scene recognition, 483
- Schur complement, 531
- segmentation, 101–102, 106, 220, 387, 389–393
  - supervised, 253–254
- semantic segmentation, 163, 167
- sequential RANSAC, 345
- seven point algorithm, 368
- shape, 387
  - alignment, 397–398
  - definition, 388
  - statistical model, 396–405
- shape and appearance models, 405–410
- shape context descriptor, 129, 286–287
- shape from silhouette, 316–319
- shape model
  - 3D, 405
  - articulated, 414–416
  - non-Gaussian, 410–414
  - subspace, 399
- shape template, 393, 395
- Sherman–Morrison–Woodbury relation, 113, 532
- shift map image editing, 255–257
- SIFT, 348
  - descriptor, 284, 293
  - detector, 282
- sign language interpretation, 195, 197, 216
- silhouette
  - shape from, 316–319
- similarity transformation, 326
  - learning, 332
- simultaneous localization and mapping, 477–478, 480
- single author–topic model, 493, 495
- singular matrix, 520
- singular value decomposition, 522–525
- singular values, 523
- skew (camera parameter), 301
- skew (moment), 15
- skin detection, 64–65, 67
- SLAM, 477–478, 480
- smoothing, 461–463
  - fixed interval, 462–463
  - fixed lag, 461–462
- snake, 220–223, 389–393, 420
- Sobel operator, 273
- softmax function, 157
- sparse classification model, 147–150
- sparse linear regression, 120
- sparse stereo vision, 297
- sparsity, 120, 127, 148, 150
- spherical covariance matrix, 44
- square matrix, 520
- squared reprojection error, 355
- statistical shape model, 396–405
- steepest descent, 511–512
- step function, 153
- stereo reconstruction, 305–306, 312–313
- stereo vision, 216–219, 222, 254–255, 263
  - dense, 216–219
  - dynamic programming, 222
  - graph cuts formulation, 254–255
  - sparse, 297
- strong classifier, 153
- structure from motion, 354, 372
- structured light, 314, 319
- Student t-distribution, 82–88
- style, 424
- style / identity model, 424
  - asymmetric bilinear, 438–443
  - multifactor GPLVM, 449–450

- multilinear, 446
  - nonlinear, 437–438
  - PLDA, 433–437
  - subspace identity model, 427–432
  - symmetric bilinear, 443–445
- style translation, 442
- submodularity, 239, 243
  - multilabel case, 243
- subspace, 89
- subspace identity model, 427–432
- subspace model, 88, 105, 399, 421, 424
  - bilinear asymmetric, 438–443
  - bilinear symmetric, 443–445
  - dual PCA, 290
  - factor analysis, 424
  - for face recognition, 450
  - multifactor GPLVM, 449–450
  - multilinear model, 446
  - PLDA, 433–437
  - principal component analysis, 289–290
  - subspace identity model, 427–432
  - subspace shape model, 399
- sum-product algorithm, 208–209, 223
  - for chain model, 209
  - for tree model, 211
- super-resolution, 257
- superpixel, 163
- supervised segmentation, 253–254
- support vector machine, 160, 167
- surface layout recovery, 163–164
- SVD, 522–525
- SVM, 160
- symmetric bilinear model, 443–445
- symmetric epipolar distance, 363
  
- t-distribution, 82–88, 105
  - mixture of, 94
  - multivariate, 85
  - univariate, 84
- t-test, 43
- temporal model, 453–480
- tensor, 522
  - multiplication, 522
- TensorTextures, 448–449
- texton, 163, 277
- textonboost, 163
- texture synthesis, 257–259, 263
  
- tied factor analysis, 438
- Tomasi-Kanade factorization, 374, 380, 382
- top-down approach, 387
- topic, 488
- trace of matrix, 521
- tracking, 453–480
  - pedestrian, 476
  - applications, 479
  - condensation algorithm, 472–476
  - displacement expert, 129–130
  - features, 380
  - for augmented reality, 347–349
  - head position, 129–130
  - particle filtering, 472–476
  - through clutter, 478
- transformation, 323–347, 350
  - 2D, 323–330
  - affine, 327–328
  - application, 347–349
  - between images, 339
  - Euclidean, 323–325
  - homography, 328–329
  - indexed by hidden variable, 104
  - inference, 334
  - inverting, 334
  - learning, 330
    - affine, 332–333
    - Euclidean, 331–332
    - homography, 333–335
    - projective, 333–335
    - similarity, 332
  - linear, 522
  - projective, 328–329
  - robust learning, 342
  - similarity, 326
- transpose, 520
- tree model, 195
  - learning, 212
  - MAP inference, 202–205
  - marginal posterior inference, 211
- tri-focal tensor, 373
- triangulation, 306
- truncating potentials, 247
- trust-region methods, 515
- two-view geometry, 355

- UKF, 467–471
- unary term, 232, 251
- undirected graphical model, 178
  - chain, 196–197
  - conditional independence relations in, 179
  - learning, 189–192
  - Markov blanket, 179
  - sampling, 187–188
- univariate normal distribution, 17
- unscented Kalman filter, 467–471
- unsupervised object discovery, 492
- variable elimination, 205
- variance, 15
- vector, 519
  - norm, 519
  - product, 519
- Vertigo, 320
- Video Google, 500–501
- virtual image, 297
- visual hull, 316
- visual word, 285, 483
- Viterbi algorithm, 198–202
- volumetric graph cuts, 378–380
- weak classifier, 153
- weak perspective camera, 321
- whitening, 269
- whitening transformation, 51
- within-individual variation, 427, 433
- Woodbury inversion identity, 113, 532
- word, 285, 483
- world state, 55