

Index

- air containment pressure,
 - calculated and measured, 157
- air partial pressure at upper and lower domes, calculated and measured, 157
- anisotropic media, treatment of flow and temperature fields in, 3
- AP-600 passive containment cooling system (PCCS)
 - analyses of large-scale tests for, 127, 150–158
 - analysis of, 170
 - improving and optimizing design and performance, 150
 - modeling as a multiphase problem, 152
 - numerical modeling for, 150, 151, 152
 - successful modeling of, 151–153
- appropriated averaging, of two surface velocities, 57
- area averages, various, 15–17
- averaging
 - basis for, 120
 - duration, 123
 - necessary for, 160
 - order of, 121
 - process, 1, 2, 6
 - relations, 12–22
 - time interval, 122–123
- axial partitioning, used in numerical model, 142, 143
- Bernoulli equation, 6
- Bernoulli relationships, for one-dimensional flow, 7
- boiling flow system, 118
- Bourdon tube pressure gauge, 4
- bubbles, in liquid in a tube, 118, 119
- bubbly liquid, in turbulent motion, 50
- buck viscosity, 63
- capillary pressure difference, 32, 33, 75
- casting processes, simulation of, 171

- cell, averaging of neighboring surface velocities of, 183
- cell volumes, construction of, 180
- characteristic length, of local averaging volume, 21
- characteristic time, of fluctuation, 164
- circumferential wall temperature distribution, 154–155
- closure problem, 172–173
- coherence component, for turbulence in single-phase fluid, 175–176
- COMMIX codes
 - analysis of natural convection phenomena, 149
 - calculated results compared with experimental data, 127, 152–153, 154–158
 - calculated results from, 143
 - capability clearly demonstrated, 159
 - capturing essential flow fields and temperature distributions, 128, 141–158
 - comparisons of streaklines and Strouhal numbers with experimental data, 133–134
 - computing detailed microflow fields, 127, 128–140, 134
 - family of, 170
 - with LECUSSO and QUICK, 128, 134
 - LECUSSO scheme giving a stable solution, 136
 - for single phase with multicomponent, 125
 - validating, 141, 150
- COMMIX computer program, 1
- computational cell, evaluating variables at the surface of, 56
- computational domain, subdividing into subdomains, 125, 169
- computational mesh representation, for LST, 151, 152
- computed heat transfers, 145
- condensation and evaporating film thickness, streamwise variation of, 158
- condensation and evaporation rates, treating as boundary conditions, 152
- condensation rate, calculated and measured, 156
- conservation equations
 - constitutive relations varying with different sets of, 8
 - different sets of for multiphase flow, 174
 - in differential-integral form, 126, 165
 - previously approximated as set of partial differential equations, 171
 - for two-phase flow analysis, 126
- consistency, of multiphase conservation equations, 175
- constant density, time-volume-averaged continuity equations with, 167
- constant local averaging volume, 12

- constitutive relations, for
 - diffusive, dispersive, turbulent, and interfacial transfer needing to be developed, 172
- continuity equation, 27, 28
- continuum formulation, 125, 169–170
- continuum mechanics, 23
- contributions, of this book, 171
- control volume, 181–182
- convection velocity, 124
- convective differencing schemes, 135
- core, temperatures in good agreement, 149
- corner vortices, 136, 140
- countercurrent stratified flow, 149
- coupled phasic equations, solving, 26
- DBA (design-based reactor accident), 127
- dependent variables, 3, 180
- derived time-volume momentum equation, 11
- derived time-volume-averaged continuity equation, 11
- design-based reactor accident (DBA), 127
- differential-integral equations, in a parallel processors program, 171–172
- differential-integral form
 - multiphase flow equations in, 171
 - time-volume-averaged conservation equations in, 165–166
- diffusion velocity, 7
- directional surface porosities
 - associated with stationary and complex solid structures, 3
 - defined, 3, 19, 168
 - improving resolution and modeling accuracy, 169
 - introduction of concept of, 177
 - reducing reliance on empirical estimation of distributed resistance, 10
- dispersed phase, 117
- dispersed systems, analysis best suited for, 52
- dissipation function, 44
- distributed flow resistance, exerted by fixed solids, 42
- distributed heat source and sink, 44, 82
- distributed resistance, 70, 169
- distributed resistance force, 30, 71
- donor flow formulation, 183
- double dot, denoting scalar product of two second-order tensors, 36, 44
- duct flow, with turbulence, 50
- dynamic phases, in a multiphase system, 121
- dynamic viscosity, 63
- eddy diffusivity, for internal energy transfer, 92
- Electric Power Research Institute (EPRI), 127

- elements, of dispersed phase k , 184–187
- energy equations
 - expressing in terms of internal energy, 36
 - not independent of one another, 167–168
- enthalpy balance equation, 26, 47
- enthalpy dissipation, shown in interfacial enthalpy balance equation, 110
- enthalpy equation, for phase k , 38
- enthalpy production, 110
- Equation (2.4.9), physical interpretation of, 184–187
- equations, of conservation for a pure phase, 23
- Eulerian time averaging, 4, 121, 124
- evaporation rate, calculated and measured, 156
- experimental observation, basics of, 117
- flotation applications for coal precleaning, 171
- flow region, 135
- flow resistance, experimentally measuring, 70
- flow system
 - observing over time, 118
 - occupying a region, 12, 13
- fluctuating axial velocity, time variation in wake region, 132, 134
- fluid
 - basic hydrostatic pressure of, 11
 - thermodynamic properties of, 5
 - fluid hydrostatics. *See* hydrostatics, basic relation of, 73, 167
 - fluid mixture
 - with phase k , 12
 - volume of, 13
 - fluid-fluid interfaces, 17, 25, 26
 - fluid-fluid interfacial heat transfer, rate of, 43
 - fluid-fluid interfacial heat transport, into phase k per unit volume, 34
 - fluidized bed combustor
 - modeling, simulation of, 171
 - fluid-solid interface, 12, 17
 - fluid-solid interfacial heat transfer into phase k , rate of, 44
 - fluid-solid interfacial heat transport, into phase k per unit volume, 34
 - fluid-structure interactions, explicitly accounted for, 9
 - fluid-to-fluid interfacial heat transfer rate, into phase k per unit volume, 76
 - fluid-to-solid structure interfacial heat transfer rate, into phase k per unit volume, 76
 - flux-related quantities, vectorial form, 20
 - formulation, consistent, 9
 - Fourier law of isotropic conduction, 80, 191
 - fractional residence time
 - equal to physical volume fraction, 4–5
 - of a phase, 121, 162

- FRAM, nonlinear damping
 - algorithm, 128, 135
- gamma beam, 4
- generalized multiphase
 - mechanics, framework of, 4
- generalized porous media
 - formulation, concept of, 2
- gravitational acceleration, 167
- gravitational acceleration vector, 73
- heat capacity effect, of steam
 - generator structures, 149
- heat exchanger analysis, 127, 170
- heat flux vector, 191
- heat transfer
 - comparison between computed and measured values, 145
 - multiphase flows with, 174
 - via phase change, 127
- higher-order differencing
 - schemes, 137–140
- high-frequency component, 49
- highly dispersed flow, 6
- high-order differencing schemes, 128, 137
- homogeneous nonstructural fluid
 - medium, approximating, 16–17
- horizontal partition, of secondary
 - cooling system, 143, 145
- horizontal partitioning, used in
 - numerical model, 143, 144
- hot legs, countercurrent fluid flow
 - in, 146
- hot wire anemometer, 4
- hydrostatics. *See* fluid
 - hydrostatics, satisfying basic relation of, 32
- ideally stratified flow, 6
- impulsive motion, 50
- instrumentation, characteristics
 - of, 4, 161–162
- integral limit, changing, 71
- integrals, 165
- interface configurations, moving
 - randomly, 5
- interface thickness, between two
 - phases assumed to be zero, 175
- interface transfer integrals,
 - evaluation of, 173
- interfaces, 1
- interfacial balance equations, 25–26, 29
- interfacial balance relations, 8
- interfacial capillary pressure
 - transfer integrals, 75
- interfacial dissipation integral (VDI), 98
- interfacial drag and diffusive
 - force on phase k , 30
- interfacial enthalpy transfer
 - integral, 106
- interfacial heat transfer, 86, 98
- interfacial heat transfer integral, 82
- interfacial integrals, vanishing, 11, 73
- interfacial internal energy
 - transfer, 98
- interfacial internal energy
 - transfer integral, 97

- interfacial mass generation rate,
 - of phase k , 10, 28
- interfacial mass transfer integral, 58
- interfacial momentum transfer
 - integral (MMTI), 68, 74, 115
- interfacial pressure transfer
 - integral (PTI), 66, 74
- interfacial pressure work integral, 83, 94
- interfacial pressure work (PWI), 98
- interfacial total energy transfer, 86
- interfacial total energy transfer
 - integral, 86
- interfacial transfer integrals, 48, 163
- interfacial velocity, 52
- interfacial viscous dissipation
 - integral, 95
- interfacial viscous stress transfer
 - integral (VSTI), 66, 74
- interfacial viscous stress work
 - integral, 84
- interfacial work by pressure force
 - and viscous force, 86
- internal energy, expressing
 - energy equation in terms of, 36
- internal energy balance, 47
- internal energy dissipation, 101
- internal energy equation, 26
- intrapphase conservation
 - equations, 2
- intrinsic area average, 15
- intrinsic averages, observation
 - on, 53–54
- intrinsic volume average, 14–15, 21
- in-vessel analysis, 127, 170
- isotropic conduction, 191–192
- lateral velocity component, 137
- LECUSO (Exact Consistent Upwind Scheme of Second Order), 128, 138, 139
- Leibnitz rule, 122, 123
- length-scale restrictions, 18, 162–163
- linear momentum equation, 29
- local area average, 15
- local averaging volume, 13–14, 21–22
- local volume average
 - defining, 21
 - derivatives only piecewise
 - continuous, 22
 - described, 14–15
 - of a fluid property of phase k , 53
 - length-scale restriction for, 162–163
 - of spatial and time derivatives
 - of a fluid property, 17
- local volume averaging
 - analyzing porous media flows, 5
 - in laminar, dispersed
 - multiphase flows, 4
 - length scale associated with, 124
 - of Navier-Stokes equations, 8
 - performed first, 26
 - performed on conservation
 - equations and interfacial
 - balance relations, 161

Index	207
preceding time averaging, 5, 162	
time averaging in relation to, 117–121	
local volume averaging theorems, 17–20	
applied to continuity equation, 28	
length-scale restrictions, 17	
well established, 4	
local volume quantities, flow and temperature field in terms of, 160	
local volume-averaged conservation equations for multiphase flow, 27	
summary of, 41–45	
local volume-averaged energy conservation equations, 43–45	
local volume-averaged enthalpy balance equation, 41, 109	
local volume-averaged enthalpy conservation equation, 101	
local volume-averaged enthalpy equation, 38–41	
local volume-averaged interfacial balance equations, summary of, 45–47	
local volume-averaged interfacial energy balance equation, 46–47	
local volume-averaged interfacial internal energy balance equation, 100	
local volume-averaged interfacial linear momentum balance equation, 32, 46	
local volume-averaged interfacial mass balance equation, 29, 45–46	
local volume-averaged interfacial total energy balance equation, 88	
local volume-averaged internal energy balance equation, 38	
local volume-averaged internal energy conservation equation, 90	
local volume-averaged internal energy equation, 36–38	
local volume-averaged linear momentum balance equations, 73	
local volume-averaged linear momentum conservation equation, 42–43, 60	
local volume-averaged linear momentum equation, 29–33	
local volume-averaged mass balance equation, 59–60	
local volume-averaged mass conservation equation, 27–29, 41–42, 54	
local volume-averaged momentum equation, 31	
local volume-averaged total energy conservation equation, 75	
local volume-averaged total energy equation, 33–35	
local volume-averaging theorems applying to enthalpy equation, 39	
applying to linear momentum equation, 29	

- local volume-averaging (*cont.*)
 - applying to phasic conservation equations, 27
 - applying to terms in internal energy equation, 36
 - applying to total energy equation, 33–34
- lower plenum, temperatures, 146
- low-frequency component, 48, 49
- main control volume, 181
- mass balance, 25
- mass flux vector, defined, 56, 81
- mean interface enthalpy, 40
- mean interface internal energy, 37
- mean interface total energy, 35
- mechanical work, 91, 95
- mixture density, 6, 7
- mixture velocity, 6
- momentum balance, 25
- momentum control volume, 182
- momentum transfer, 69
- momentum transport, test
 - problem of, 128–129
- multiphase conservation equations, 8
- multiphase flow conservation equations
 - based on a single formulation, 9
 - benefits resulting from
 - universally accepted formulation, 9
 - establishing a universally accepted formulation for, 177
 - need for universally accepted formulation for, 8–11
- multiphase flow equations,
 - formulation of closely related to staggered-grid computational system, 182
- multiphase flow system, with stationary and solid structures, 13
- multiphase flows
 - approach to turbulent, dispersed, 8
 - background information about, 2–6
 - described, 1
 - describing only in some average sense, 6
 - governing conservation equations for, 3
 - with heat transfer, 8, 174
 - importance of interfacial mass, momentum, and energy balance for, 6
 - interacting phases dispersed randomly, 160
 - lack of knowledge of mass, momentum, and energy transfer at the interface, 173
 - local volume-averaged transport equations for, 2
 - modeling with simplified approximations, 166
 - phase configurations in, 7
 - properties seen by an observer at a fixed point in, 122
 - significance of phase configurations, 6–7
 - theoretical extension of novel porous media formulation to, 171

- time averaging disadvantages, 5
- time-volume-averaged
 - conservation equations for, 8
- turbulent, dispersed, 5
- multiphase mechanics, averaging
 - procedure in, 117
- multiphase problem, reducing
 - into a single phase, 152
- multiphase system, identification
 - of a phase in, 23
- natural convection patterns, 146, 147
- natural convection phenomena, 141–149, 170
- natural convection test, schematic
 - diagrams for, 141, 142
- Navier-Stokes equations, 8, 161
- Newtonian fluids, 63, 188
- nonflow variable, control volume
 - for, 179, 180
- nonturbulent flows, equations
 - for, 172
- normalized lateral velocity
 - component, 135
- normalized temperature
 - distribution, 153
- novel porous media formulation, 168–172
 - computational cells
 - characterized by, 125
 - continuum and conventional porous media formulations
 - subsets of, 11
 - contributions from exemplified by numerous studies, 126–127
 - developed from single phase to multiphase, 126
 - for multiphase flow
 - conservation equations, 8, 177
 - in single phase and single phase with multicomponent applications, 126
 - for single-phase flows, 170
 - unique features of, 174–175
 - nuclear reactor community,
 - COMMIX suite adopted by, 170
 - numerical simulations, of
 - practical engineering problems, 169
 - observation window, 118, 119
 - order of averaging, 121
 - oscillation dumping technique,
 - agreement poor without, 138
 - PCCS. *See* AP-600 passive containment cooling system (PCCS)
 - phase change, PCCS using to remove heat, 151–152
 - phase configurations in multiphase flow, 6–7
 - phase interface, defining
 - time-averaged variables, 5
 - phase k , variable volume, 12
 - phasic conservation equations, 23–24
 - physical interpretation, of
 - Equation (2.4.9), 184–187
 - point variable, expressing, 163
 - porous media formulation, 9–11, 125, 169–170
 - postulates, basic, 48–53

- pressure work function vector, 79
- pressurized thermal shock (PTS)
 - analysis, 126–127, 170
- prototypic pressurized water reactor (PWR)
 - analysis of natural convection phenomena in, 127
 - first complete numerical simulation for a four-loop, 149
 - proper design introducing inherent and passive safety features, 149
- pure phase k , 23–24
- QUICK (Quadratic Upstream Interpolation for Convective Kinematics) scheme, 128
 - failure of, 136
 - with an oscillation dumping technique, 138
 - smaller truncation error, 139
- recirculation regions, existence of several, 135
- research, future, 172–176
- reversible work, in interfacial internal energy balance equation, 101
- Reynolds analysis, of turbulent flow, 164
- Reynolds hypothesis, adopting, 50
- scalar enthalpy function, 102
- scalar internal energy function, 91
- scalar pressure work function, 94
- scalar product, of two second-order tensors, 24, 36, 44
- scalar viscous dissipation function, defined, 95
- scalar-intensive properties, corresponding relation, 20
- schematic layout, of model of the Westinghouse experiment, 141–142
- shear stress tensor, 71
- shear-driven cavity flow analysis, 126, 134–137
- simple time averaging, 4, 121
- single-phase flow, 5
- single-phase implementation, 169–171
- solar energy applications, simulation of, 171
- spatial deviation
 - incorporation into instantaneous point-dependent variables, 177
 - of point values of dependent variables, 10
- specific heat, at constant volume, 92
- speed of sound, in the mixture, 7
- staggered grid, 181
- staggered-grid computational system, 179–183
- steam generators, 142, 143, 144
- steam mass fraction, 153
- stratification, in hot legs, 146
- streaklines, 130, 131
- streamline pattern, for corner vortices, 140
- Strouhal numbers, 132, 133

- substantive time derivative, 58, 107
- surface, appropriated averaging of
 - two neighboring cells of, 56
- surface curvature, abrupt changes
 - not expected, 52
- temperature distribution
 - calculated from the COMMIX code, 146, 148–149
 - of inside and outside vessel wall surfaces, condensation, and evaporation film interfaces, 158
 - of moist air in annulus, 155
- thermal energy, conversion of
 - mechanical work into, 44
- time average, 51, 57, 58
- time averaging
 - after local volume averaging, 164–165
 - as the basis of analysis for multiphase flows, 5
 - on both local volume-averaged conservation equations and interfacial balance relations, 8
 - of local volume-average momentum conservation equation, 61
 - of local volume-averaged internal energy conservation equation, 91
 - of local volume-averaged mass conservation equation, 54–55
 - of local volume-averaged phasic conservation equations, 161–168
 - of local volume-averaged total energy conservation equations, 77
 - in multiphase flows, 123
 - performing, 50
 - in relation to local volume averaging, 117–121
 - time scale restriction in, 163–165
- time averaging after local volume averaging, 4
- time scale restriction, in time averaging, 163–165
- time volume-averaged enthalpy balance equation, 109–110
- time volume-averaged enthalpy equation
 - obtaining, 107–108
 - writing, 108–109
- time volume-averaged internal energy conservation equation, 98–99
- time-averaged interfacial mass generation rate, 166
- time-averaged interfacial total energy source, 86
- time-averaged interfacial total momentum source, 69
- time-averaged total interfacial internal energy source, 97
- time-averaged volume fraction of phase 1, 121
- time-averaging interfacial enthalpy source, 107
- time-local volume averaging, 2
- time-volume averaging, 121–124, 161–162

time-volume-averaged conservation equations in differential-integral form, 165–166 flux-related quantities in, 20 of mass, momentum, and energy for multiphase systems, 3 summary of, 110–114 unique features of, 166–168	time-volume-averaged interfacial momentum balance equation, 73–75
time-volume-averaged conservation of mass equation, 110–111	time-volume-averaged interfacial momentum transfer rate, 66
time-volume-averaged continuity equations, with constant density, 167	time-volume-averaged interfacial of total momentum source, 115
time-volume-averaged energy conservation equation, obtaining, 87	time-volume-averaged interfacial total energy balance equation, 88–90, 115–116
time-volume-averaged enthalpy conservation equation, 101–109, 113–114	time-volume-averaged interfacial total energy transfer rate, 86
time-volume-averaged enthalpy energy balance equation, 116	time-volume-averaged internal energy conservation equation, 90–99, 113
time-volume-averaged interfacial balance equations, summary of, 114–116	time-volume-averaged internal energy equations compared to enthalpy, 167 writing, 99
time-volume-averaged interfacial internal energy balance equation, 100–101, 116	time-volume-averaged linear momentum conservation equation, 60–73, 111–112
time-volume-averaged interfacial linear momentum balance equation, 115	time-volume-averaged linear momentum equations, 71, 72, 167
time-volume-averaged interfacial mass balance equation, 59–60, 114	time-volume-averaged mass conservation equation, 54–59
time-volume-averaged interfacial mass generation rate, 10	time-volume-averaged multiphase conservation equations, 9
	time-volume-averaged total energy conservation equation, 75–88, 112–113
	TMI-2-type accidents, preventing, 149
	total energy balance, 25, 47

Index 213

- total interfacial mass generation
 - of phase k , rate of, 42
- total local volume average, 21
- total time-volume-averaged
 - interfacial momentum transfer rate, 68–69
- transient flow, with accelerating
 - flow of speed, 119
- transport properties,
 - quantification of, 173
- tubular steam generator, 143, 144
- turbulent flow, of suspension of
 - small solid particles in a gas or liquid, 53
- turbulent fluctuations, phase
 - interface subject to, 5
- upper head, temperatures, 149
- upper plenum, range of
 - temperatures, 149
- upwind cell density, knowing
 - velocity at computational cell surface, 56
- velocity components, calculated
 - for displaced or staggered locations of, 180
- velocity distribution, 153
- velocity vector
 - predicted, 130
 - for shear-driven cavity flows, 136, 138, 139
- viscosity coefficients,
 - decomposing, 188
- viscous stress tensor, for
 - Newtonian fluids, 63
- viscous stress work function
 - vector, 80
- viscous stresses, insignificant
 - relative to turbulent stresses, 65
- volume, observed, 117
- volume averages
 - of the conjugate, 65
 - information of, 26
 - of the product of dependent variables, 48
- volume averaging
 - leading to volume fraction of phases, 5
 - preceding time averaging, 121
- volume fraction
 - in one-dimensional flow, 119
 - of the phase, 121
 - of phase k in fluid mixture, 14
- volume porosity, 2, 3, 14, 168
- volume-averaged dispersive
 - enthalpy flux, 103
- volume-averaged dispersive
 - internal energy flux, 93
- volume-averaged dispersive
 - stress tensor, 62
- volume-averaged dispersive total
 - energy flux vector, 78
- volume-averaged eddy
 - diffusivity, 56
- volume-averaged Reynolds stress
 - tensor, 62
- volume-averaged turbulent,
 - dispersive enthalpy flux, 103
- volume-averaged turbulent,
 - dispersive internal energy flux, 93
- volume-averaged turbulent
 - dispersive stress tensor, 62

volume-averaged turbulent, dispersive total energy flux vector, 78	volume-time averaging, versus time-volume averaging, 121–124
volume-averaged turbulent enthalpy flux, 103	Von Karmann vortex
volume-averaged turbulent internal energy flux, 92	shedding analysis, 126, 128–134
volume-averaged turbulent total energy flux vector, 78	zero interfacial thickness assumption of, 175