

Index

- active flow control, 305, 401
- active flow control on airfoils, *see* airfoils, flow control devices
- actuator disk, 60, 93, 142, 166, 632, 637, 706, 742
- advance ratio, 95, 97, 98, 129, 159, 160, 162, 207, 219, 220, 223, 261, 262, 284, 293, 294, 295, 303, 304, 318, 359, 575, 579, 580, 658
- definition for a wind turbine, 732
- definition of, 95
- effect on airframe airloads, 663
- effect on hub wake, 677
- effect on local sweep angle, 547
- effect on wake geometry, 578, 621, 622
- effect on wake position, 661
- effect on wake relative to empennage, 680
- effects on rotor–airframe performance, 661
- for autogiro, 712
- highest value of, 710
- advancing blade, 57, 58, 129, 146, 152, 162, 183, 208, 220, 240, 290, 294, 295, 296, 302, 348, 396, 398, 399, 483, 525, 578, 709
- aerodynamic center, 375–376, 433, 440, 446, 449, 468, 482, 484, 490, 497, 788
- compressibility effects on, 375–376
- definition of, 375
- example calculation of, 377
- aerodynamic damping, 174, 180, 545–547
- Aerospatiale, *see* Eurocopter
- Agusta, 44
- Agusta–Westland, 34, 44
- airfoils
 - advanced design of, 398–400
 - aerodynamics of, 368, 374
 - at high angles of attack, 407–409
 - at low angles of attack, 401–403
 - compressibility effects on, *see* compressibility effects of ballistic damage, 412
 - forces and moments on, 371–374
 - modeling at high angles of attack, 407–409
 - modeling in attached flow, 401–403
 - modeling nonlinear characteristics, 403–407
 - modeling static characteristics, 401–409
 - pressure distributions, 363–367, 370–371, 392–394
 - synthesis of pressure distributions, 365–366
 - circulation controlled, 409–411
 - Clark-Y, 360
 - design for main rotor, 295–300
 - early developments of, 347–348, 360–361, 709
 - flow control devices, 401
 - for autogiros
 - RAF, 709
 - Göttingen, 709
 - for wind turbines, 747–750
 - future design goals, 401
 - Göttingen, 360, 709
 - laminar flow type, 363, 401
 - modifications to NACA 4- and 5-digit, 362–363
 - NACA 4-digit, 361, 398
 - NACA 5-digit, 361–362
 - NACA 6-series, 363
 - NACA HH-series, 363
 - NASA RC-series, 400
 - OA-series, 399
 - operating requirements for, 348–350
 - profile drag of, 296–300
 - RAE-series, 399–400
 - reverse flow, 408
 - supercritical, 395, 396, 399
 - unsteady, *see* unsteady aerodynamics
 - VR-series, 398–399
- airframe aerodynamics, 240, 304
 - drag, 304
 - drag reduction, 305
 - modeling of, 798–801
- angle of attack
 - mean value of blades, 155
 - of airfoil, 55, 156, 158, 184, 244, 361, 366, 369, 373, 424
 - compressibility effect on, 373
 - for zero-lift, 373
 - unsteady effective, 447
 - of rotor disk, 93, 96, 100, 161, 218, 227, 693, 698
 - importance for autogiro, 699
- anti-torque
 - coaxial rotor, 17, 28
 - difficulties in achieving, 6
 - early use of tail rotor, 19
 - pilot’s controls for, 203
 - power required for, 226
 - use on VS-300, 32
- anti-torque devices
 - fan-in-fin, 43, 321–324
 - analysis of, 321–324
 - relative size of, 315

- NOTAR, 324–325
 tail rotor, 314–321
 design requirements for, 319–320
 interactions with main rotor, 682–685
 power required, 226
 size of, 315
 types of, 318–319, 320–321
 weathercock stability of, 314
 articulated rotor, *see* rotor, types of
 articulation, *see* blade articulation
 autogiro
 airfoil sections for, *see* airfoils
 Cierva flying model of, 694
 Cierva's Autogiros, 20–21
 definition of, 20, 693
 development of drag hinge for, 701
 development of flapping hinge for, 700, 701
 directly orientable rotor, 712
 ground resonance on, 715
 jump take-off, 21, 713
 later developments of, 22, 36, 37
 loss of interest in, 716
 low-speed capabilities of, 21
 NACA research on, 710
 performance
 analogy with a parachute, 703
 Cierva-Glauert debate about, 702
 comparison with the helicopter, 708
 descent speed, 695
 disk angle of attack, 696
 horizontal flight, 705
 propeller efficiency, 706
 vertical flight, 704
 prerotating the rotor, 701
 towering take off, 714
 types of
 C-1 Autogiro, 699
 C-12 Autogiro, 701
 C-19 Autogiro, 712
 C-2 Autogiro, 699
 C-3 Autogiro, 699
 C-30 Autogiro, 712
 C-4 Autogiro, 699
 C-6 Autogiro, 701, 702
 Groen Brothers Hawk 4 gyroplane, 718
 PA-22, PA-36 autogiros, 715
 PCA-2 autogiro, 707
 Rotodyne gyroplane, 718
 XV-1 gyroplane, 32, 718
 autorotation, 20, 694
 actual autorotation, 91, 695
 autorotation diagram, 244–245
 autorotational index, 251–252
 balance of forces on blades, 244, 697
 blade element considerations, 242–245, 697
 definition of, 28, 694
 effect of rotor inertia on, 245
 estimation of rate of descent in, 246–248
 first successful, 29, 32
 height–velocity curve, 249–250
 ideal autorotation, 91
 in forward flight, 246–248
 means of recovery of safe flight, 91
 phenomenon of, 693
 piloting, 93, 245, 246–248
 rate of descent in, 92, 246
 autorotational index, 252
 axial force, 368
 by integration of pressure, 369
 azimuth angle, 55, 118, 172, 181, 222, 469, 553, 572,
 602, 609, 701
 definition of, 55
 intersection of BVI points, 505, 617
 on a wind turbine, 737
 bearingless rotor, *see* rotor, types of
 Bell Helicopter, 41–42, 48
 HSL-1 tandem, 38
 Models-30 and -40, 38
 XV-3, XV-15, V-22, 327–328
 Berliner, Émile and Henry, 16
 BERP rotor, 44
 design of, 301–304
 effects on flight envelope, 303–304
 tip shape of, 302–303
 wind tunnel experiments with, 295
 Biot–Savart law, 598, 599–601, 603, 612, 614, 617,
 629, 778, 780
 accuracy of segmentation approach, 601
 blade
 aerodynamic environment at, 55
 stalling, *see* stall
 taper, *see* taper
 tip shape, *see* swept tips
 blade articulation, 4, 21, 171, 700
 flapping hinges, 21, 57, 171, 700, 701
 lead–lag hinges, 21, 171, 701
 blade element momentum theory (BEMT), 125–152
 application to a wind turbine, 738–741
 fan-in-fin analysis, 323
 fundamental equation for wind turbine, 737
 history of, 125
 inflow equation, 127
 blade element theory
 aerodynamic environment at, 116
 application to a wind turbine, 735–738
 axial flight, 117–124
 rotor power, 122
 rotor thrust, 119–122
 definition of, 116–117
 forward flight, 156–166
 velocity components, 157–158
 fundamental equations of, 118
 history of, 115–116
 induced velocity field, *see* inflow
 inflow at blade element, *see* inflow

- profile power calculation in, 69, 140–141, 154
 simplifying approximations in, 118
 blade flapping, *see* flapping
 blade loading coefficient, 77, 258, 285, 287, 303, 712
 blade pitch, *see* pitch
 cyclic, 6
 blade twisting, 17
 early use of, 25
 servo-tabs, 27
 stabovators, 27
 blade vortex interaction, 58, 488–489, 491–492, 578–581
 CFD modeling of, 790
 blade wake, *see* wakes
 Bleecker, Maitland, 27
 Boeing Company, 38, 48
 CH-46 and CH-47 models, 38
 Boeing-Vertol, *see* Boeing Company
 boundary layers, 352–357
 equations of, 780–782
 flow visualization of, 355, 356
 pressure gradient effects on, 355–356
 shear stress, 352–355
 types of, 352–357
 Breguet
 brothers, 12
 Louis, 21, 28
 Brennan, Louis, 17
 Bristol Helicopters, 38
 Sycamore, 34
 BVI, *see* blade vortex interaction

 CAMRAD, 806
 Cayley, Sir George, 9
 ceiling, 216, 238
 center of pressure, 377, 453, 484, 534, 545, 709
 during dynamic stall, 526, 528, 559
 on airframe, 664
 on swept tip, 293
 relationship to aerodynamic center, 377
 centrifugal forces, 171, 173, 174, 176, 178, 183, 195, 700
 CFD
 Euler equations, 776–777
 finite-difference methods, 775
 finite-volume methods, 775
 grids for, 790, 791, 794, 798
 Navier–Stokes equations, 773–776
 vorticity transport equations, 777–779
 chord force, *see* axial force
 Cierva, Juan de la, 20, 22, 693, 695, 697, 699, 700, 701, 702, 709, 712, 713, 715
 books of, 21, 704
 death of, 716
 circulation control, 324, 325, 328, 409
 circulation controlled airfoils, *see* airfoils, circulation controlled
 climb power, *see* power

 Coanda effect, 324, 409
 coaxial rotors, 6, 8, 10, 14, 17, 24, 39, 46, 190, 241
 ABC concept, 328
 Cierva's first autogiro, 20
 definition of, 4
 forward flight performance of, 240–241
 hovering performance of, 101–105
 Sikorsky's first design, 12
 collective pitch, *see* pitch
 complete induced velocity curve, *see* inflow
 compound helicopters, 47, 325–327
 speed of, 325
 vertical drag on, 307
 compound rotorcraft, 36, 47, 267, 287, 307, 338, 718
 comprehensive rotor analyses, 805–808
 compressibility
 tip relief, *see* tip relief
 compressibility effects
 aerodynamic center, 375–376
 lift-curve-slope, 373–374
 Mach tuck, 395–396
 maximum lift coefficient, 394–395, 709
 rotor power, 220–223
 coning, 183
 control plane, *see* reference planes
 control system, 188, 379
 loads on, 318, 321, 525, 531, 710
 Coriolis effects, 171, 173, 197
 Cornu, Paul, 11
 cyclic pitch, *see* pitch

 d'Amécourt, Ponton, 10
 D'Ascanio, Corradino, 27
 Da Vinci, Leonardo, 8
 De Bothezat, Georges, 25
 Deadman's curve, *see* autorotation
 density altitude, 214, 215, 216, 217, 229, 231, 232, 238, 250, 259, 733
 definition of, 214
 design
 empennage, 311–313
 horizontal stabilizer, 311–312
 vertical stabilizer, 312–313
 fuselage, 304–311
 general requirements for, 277–278
 high-speed rotorcraft, 325–329
 main rotor, 280–304
 airfoil selection, *see* airfoils
 blade twist, 290–292
 diameter, 281–283
 number of blades, 288–290
 planform and tip shape, 292–295
 solidity, 285–287
 tip speed, 283–285
 performance guarantees on, 278–279
 specifications for, 278
 tail rotor, *see* anti-torque devices
 tip shape, *see* swept tips

- disk area, 62, 63, 64, 67, 69, 75, 80, 107, 110, 118, 225, 268, 285, 328, 727
 fan-in-fin, 323
 tail rotor, 318
- disk loading, 63, 64, 65, 70, 80, 144, 161, 282, 290, 315, 695, 696, 703
 definition of, 65
 design requirements, 281
 effect on autorotation, 246, 250
 effect on autorotational rate of descent, 92
 effect on height velocity diagram, 250
 effect on speed for minimum power, 235
 effect on vortex ring state, 91, 255
 effective value, 75
 for a coaxial rotor, 104
 for autogiro, 712
 human-powered helicopter, 332
 of tail rotor, 319
 of tilt-rotors, 327
 relationship to figure of merit, 71, 77
 relationship to power loading, 80
 trends versus helicopter weight, 283
 uniform, 130
 values for VTOL aircraft, 65
 variable diameter rotor, 328
- Dorand, René, 28
- download recovery, *see* drag
- drag
 airfoil
 by integration of pressure, 368–371
 divergence, 396–398
 Mach number effects on, 396
 Reynolds number effects on, 133–134
 viscous shear, 353–354
 wave, 359
 airframe, 240
 equivalent flat-plate area, 306, 307
 fuselage, 304–310
 parasitic, 304
 fuselage
 download recovery, 309–310
 minimization of, 304–305
 prediction of, 305–310
 strip method of estimation, 308–309
 vertical, 307–310
 panel methods, 305
 rotor
 hub, 288, 306–307
- ducted fan, *see* anti-torque devices, fan-in-fin
- Duhamel integral, 446–447, 458–459
 inclusion of time-varying velocity effects, 456
 recurrence solution of, 459–462
- dynamic stall
 aerodynamic damping in, 545–547
 CFD modeling of, 791
 definition of, 525–526
 effects of
 airfoil shape, 551–553
 Mach number, 533–534
 mean angle of attack, 532–533
 reduced frequency, 533
 sweep angle, 547–551
 three-dimensionality, 553–556
 time-varying velocity, 556–557
 flow morphology of, 527–529
 modeling, 535–543
 by CFD, 526, 535, 541, 557
 capabilities of, 541–543
 semi-empirically, 536–540
 occurrence on wind turbines, 761
 on the rotor, 529–531
 stall flutter, 526, 545
- Edison, Thomas, 10
- Ellehammer, Jens, 14
- endurance, 237–238
- engines, 240, 278
 efficiency, 232
 failure of, 246, 249
 gas turbine, 6, 40
 reciprocating, 6, 25, 239
 selection of number of, 233
 specific fuel consumption, 232
 steam, 6, 24
 turboshaft, 6, 40, 239
- equivalence of feathering to flapping, 182
- equivalent flat-plate area, *see* drag
- equivalent solidity, *see* solidity, weighted
- Euler equations, 776–777
- Eurocopter, 43
- Fairey Aviation Company, 37
- fan-in-fin, *see* anti-torque devices
 blade element momentum theory analysis of, 323
 simple momentum theory analysis of, 323
- fantail, *see* anti-torque devices, fan-in-fin
- feathering, *see* pitch
- fenestron, *see* anti-torque devices, fan-in-fin
- figure of merit, 15, 70–71, 77, 138, 216, 280, 282, 298, 299, 300, 412
 alternative form, 79, 156
 comparison to a wind turbine, 733
 definition of, 70
 effect of airfoil section on, 296
 effect of blade twist on, 290
 effect of losses on, 144
 effect of solidity on, 77, 284
 effect of stall on, 71
 effect of tip shape on, 292
 effect of twist on, 138
 example of use of, 73
 in blade element theory, 145
 maximizing, 146, 298

- maximum values of, 298
 - measured variation, 284, 292
 - of tilt-rotor, 327
 - variation in, 70, 78
 - versus year of rotor development, 280
- flapping
 - coning, 183
 - coupled with lead-lag motion, 196–198
 - effect of aerodynamics on, 179–183
 - effects of hinge offset on, 186–188
 - equation of motion, 178–179
 - equilibrium of, 171, 174–176
 - first studies of, 172
 - Fourier series representation of, 180
 - higher harmonics of, 185
 - hinge offset, 177, 178, 186–188
 - lateral flapping, 185
 - longitudinal flapping, 183
 - natural frequency of, 180, 181, 183, 186
 - physical description of, 183–186
 - with respect to reference planes, 192
- flaps, 492
 - servo flap, 331
 - tabs, 381
 - trailing edge, 492
 - unsteady aerodynamics of, 492–502
- Flettner, Anton, 31
- Florine, Nicolas, 28
- flow separation
 - leading edge type, 387
 - trailing edge type, 357, 387
- flow visualization
 - dynamic stall, 527
 - rotor wakes, 568–572
- Focke Achelis, Fa 330 Kite, 23
- Focke, Henrich, 29
- Forliani, Enrico, 10, 24
- free-vortex method, 602–604, 779
 - analysis of wind turbines, 751–757
 - governing equation, 602–603
- free-wake
 - see free-vortex method, 779
- Froude, R. E., 60
- Froude, W., 60
- fuel consumption, 47, 65, 80, 233, 235, 237–238, 240, 304
- furling, 731
- fuselage
 - design of, *see* design
 - drag of, *see* drag
- Glauert factor, 373, 392, 468
- ground effect
 - experimental studies of, 259–262
 - general description of, 257
 - in forward flight, 260–261
 - modeling of, 259–260, 803
 - rotor power, 259
 - rotor thrust, 257–259
 - wind tunnels, 261–262
- ground resonance, 715
- gyroplane, *see* autogiro
- Hafner, Raoul, 19, 22, 38
- height-velocity curve, *see* autorotation
- helicopter
 - aerodynamic complexity of, 57
 - compound design, 47, 325
 - definition of, 1
 - difficulties in attaining flight, 5
 - early historical literature on, 5
 - first mass production of, 40
 - first successes, 26–40
 - hovering flight, 55
 - human-powered, 331
 - limits in forward speed, 47, 58
 - origin of name, 10
 - time-line of development, 6
- high-speed rotorcraft, *see* design
- Hiller Company, 40
- Hiller, Stanley, 40
- hingeless rotor, *see* rotor, types of
- horizontal stabilizer, 311–312
- hover
 - flow physics of, 55, 572–575
 - momentum theory analysis of, 59–81
 - wake modeling, 604–607
- hub
 - wake, 677
- hub drag, *see* drag
- hub plane, *see* reference planes
- Hughes Aircraft, *see* McDonnell–Douglas
- human-powered helicopter, 331–333
- ideal power, 67
- ideal twist, 122, 123, 128, 129, 130, 131, 133, 740
 - of a wind turbine blade, 740
- in-ground-effect (IGE), 259, 261
 - airframe download recovery, 309
- indicial aerodynamics, 457–462
 - chordwise pressure, 446
 - definition of, 446
 - subsonic compressible flow, 465–492
 - validation with experiment, 480–483
- induced power, *see* power
- induction ratio, *see* inflow
- inflow, 83, 95, 97, 98, 115, 117, 120, 127, 128, 130, 154, 179, 217, 219, 300, 610, 698, 699, 703, 737, 738, 740
 - as affected by Prandtl tip loss, 125
 - autogiro, 706
 - calculation of, 131
 - determination by BEM theory, 125
 - dynamic, 631
 - effect of tip losses, 123
 - effect on blade coning, 183

- inflow (*cont.*)
 equation, 95
 numerical solution of, 97
 validity of, 99, 739
 evaluation of, 119
 for wind turbine, 727, 736
 gradient in, 578
 in autorotation, 245
 in decent, 243
 in ground effect, 261
 induced
 coefficient of, 67
 complete induced velocity curve, 83
 correction factor, 107
 forward flight, 95
 hover, 66
 inflow ratio, 95
 models
 dynamic, 166, 635–638
 linear, 158–160
 Mangler & Squire, 161–166
 nonuniformity of, 120
 of tail rotor, 226, 318
 prescribed wake, 604
 rigid wake, 608
 transient, 633, 713
- Jerome, Ivan, 25
 Joukowski, 14, 25
 airfoils, 348
 early helicopter, 14
 Kutta–Joukowski theorem, 138, 786
- Kaman Aircraft Corporation, 39
 Kaman, Charles, 39
 Kamov Company, 46
 Kellett Aircraft Company, 22, 36
 Kutta–Joukowski theorem, 138, 786
 Küssner's function, 448–450
 approximations to, 450
- lagging, *see* lead–lag
 laminar boundary layer, *see* boundary layers
 laminar separation bubble, *see* separation bubble
 Laplace equation, 465, 783
 lateral flapping, *see* flapping
 lead–lag
 effect of hinge offset on, 194
 equilibrium of, 176–178
 natural frequency of, 195
- lift
 by integration of pressure, 368–371
 coefficient
 maximum static value of, 79, 385–398
 compressibility effects
 lift-curve-slope, 373–374
 maximum lift coefficient, 394–395
 lifting-line model, 598, 787–789
- lifting-surface model, 598
 Lock number, 179, 181
 Loewy's problem, 441–442
 longitudinal flapping, *see* flapping
- Mach number
 critical value of, 364–365, 374
 definition of, 357
 effect of increasing, 357–359
- Mach tuck, *see* compressibility effects
 maneuvers, 525, 531, 560, 640–644
 energy methods, 263
 load factor definition, 263
- MAV, *see* micro air vehicles
 McDonnell–Douglas, 42
 mean lift coefficient, 155, 712
 Messerschmitt–Bölkow–Blohm (MBB) *see*
 Eurocopter
- micro air vehicles, 300, 334, 351, 411
 efficiency of, 280
 Reynolds number effects on, 354
- Mil Company, 44
 Miles's problem, 450–453
 subsonic flow, 490–492
- momentum theory, 60–88
 axial climb, 81–83, 87
 axial descent, 83–86, 87
 coaxial rotors, 101–105
 conservation laws, 61
 fan-in-fin analysis, 321–323
 forward flight, 93–100
 Glauert's model, 93
 hover, 61–64
 nonideal effects, 69
 predictions of power, 68, 70
 tandem rotors, 106–109
 validity of, 86–87
- natural frequency
 flapping motion, 180, 186
 lead–lag motion, 195
- Navier–Stokes equations, 773–776
 no feathering plane, *see* reference planes
 noise, 58, 277, 284, 286, 290, 315, 320, 324, 483, 488,
 489, 491, 579, 580
 of NOTAR concept, 325
- noncirculatory aerodynamics
 contribution to sharp-edged gust problem, 452
 definition of, 432–433
 in Theodorsen's result, 435, 436
- nonideal effects, 63, 68, 120
 normal working state, 90
 NOTAR, *see* anti-torque devices
 number of blades, 60, 68, 76, 288–290, 324
 aerodynamic effects of, 141, 288–290
 effects on wind turbine, 742
- numerical diffusion, 777, 790, 797, 803
 prevention of, 795

- Ehmichen, Étienne, 26
 optimum hovering rotor, 135–138
 solidity of, 154
 out-of ground-effect (OGE), 259
- panel methods
 drag prediction use of, 305
 for airfoils, 348
 for rotor–fuselage interactions, 675
 see also surface singularity methods, 783
- parasitic drag, *see* drag
 parasitic power, *see* power
- performance
 axial climb, 216–217
 definition of, 212
 forward flight, 217–240
 ceiling, 238
 density altitude effect on, 229
 endurance, 237
 gross weight effect on, 228
 in terms of D/L , 229–230
 maximum speed, 239
 minimum power, 233
 range, 235, 237
 ground effect, *see* ground effect
 hovering flight, 215–216
 density altitude effect on, 215
 gross weight effect on, 216
- Pescara, Raul, 17
 Petroczy, Stephan, 14
 Philips, W. H., 10
 Piasecki Corporation, 38
 PV-2, PV-3, 38
 Piasecki, Frank, 38
 Pitcairn Company, 22, 36
- pitch
 collective, 202
 cyclic
 servo-tabs, 39
 equivalence to flapping, 182
 lateral cyclic, 202
 longitudinal cyclic, 202
 pilot's controls for, 202
- pitching moment, 374–383
 aerodynamic center, 375–376
 airfoil shape effects on, 378–383
 by integration of pressure, 368–371
 center of pressure, 377
 evaluation by thin-airfoil theory, *see* thin-airfoil theory
 Mach tuck effect on, 396
 reference point for, 374–375
 tab effects on, 381–382
- Platt–LePage
 XR-1, 32
- potential equations, 783
- power
 forward flight, 99
 climbing, 226, 230–231
 coaxial rotors, 240–241
 compressibility losses, 220–223
 in terms of D/L , 100
 induced, 218–219
 parasitic, 100, 225–226
 profile, 219–223
 tail rotor, 226
 tandem rotors, 241–242
 total, 227–228
- hover, 63
 universal power curve, 88
- in the wind, 726
- induced
 correction factor, 68, 101
 profile, 69
 effect of airfoil shape on, 299–300
- power coefficient, definition of, 67
- power loading, 80–81
 actual, 80
 best, 81
 definition of, 80
 ideal, 80
 relationship to blade loading, 80
- power settling, *see* vortex ring state
- power-off landing, *see* autorotation
- precession, 180, 189, 317
- precessional stall, 317
- precone angle, 173
- preponderance weights, 320
- pressure
 distribution on an airfoil, *see* airfoils
 jump across rotor disk, 64
- pressure altitude
 definition of, 213
- pressure coefficient
 critical value of, 364–365
 definition of, 363–364
- profile power, *see* power
- pusher tail rotor, *see* anti-torque devices, tail rotor
- quad tilt-rotor, 329
- range, 237–238
- Rankine, William, 60
- reduced frequency
 definition of, 427
 values of, 427–428
- reduced time
 definition of, 427–428
- reference planes
 control plane, 192
 hub plane, 191
 no feathering plane, 191
 tip path plane, 191
- reseparation, *see* leading edge stall
- retreating blade, 57, 162, 184, 208, 295, 296, 302,
 348, 483, 525, 531, 560

- retreating blade stall, *see* dynamic stall
- reverse flow, 156, 219, 223, 225, 407, 409
 - effect on rotor power, 223
 - effect on section drag, 408
 - unsteady nature of, 409
- reverse flow theorems, 451–452, 490
- Reynolds number
 - definition of, 350
 - range on a rotor, 350–351
- Reynolds number effects on
 - drag, 354
 - stall characteristics, 389–392
- Richardson number, 596
- Richet, Charles, 12
- root cut-out, 128, 136
- rotor
 - acoustics
 - CFD modeling of, 801
 - aerodynamic environment in forward flight, 55, 57
 - airframe interference effects on, 58
 - compressibility effects on, 58
 - efficiency, 4, 70
 - noise
 - BVI, 58
 - high speed impulsive, 58
 - operational functions of, 4, 55
 - solidity, 69, *see* solidity
 - stalling, *see* stall
 - tip vortices, *see* vortices
 - torque coefficient
 - definition of, 67
 - types of, 172
 - articulated, 173
 - bearingless, 174
 - hingeless, 174
 - teetering, 172
 - underslung, 173
 - vibration, 58
 - CFD modeling of, 801
- rotor trim, *see* trim
- rotor wake, *see* wakes
 - CFD modeling of, 797
- rotor–airframe interaction, 657–678
 - CFD modeling of, 773, 799, 801
- Saunders-Roe, 44
- schlieren, 570
- Sears's function, 442–446
- separation bubble
 - laminar
 - long, 387
 - photograph of, 387
 - short, 355, 387, 391
 - turbulent, 394
- settling with power, *see* vortex ring state
- shadowgraphy, 570, 571, 572, 577, 581, 584
- sharp-edged gust problem
 - calculation by CFD, 490
 - incompressible flow, *see* Küssner function
 - subsonic compressible flow, 483–486
- shear stress, *see* boundary layers
- shock wave
 - interaction with boundary layer, 359
 - strength of, 395, 398
- side-by-side rotors, 6, 10, 16, 29, 44
- Sikorsky Aircraft, 41
 - early production helicopters, 40
 - RAH-66 Comanche, 41
 - S-70 (UH-60), 40
 - VS-300, 32
- Sikorsky, Igor
 - early helicopter patent, 32
 - first helicopter concept, 12
- singularity methods
 - see* surface singularity methods, 783
- sinusoidal gust, *see* Sears's function
- smart rotor systems, 330
- smoke flow visualization, 257, 569–570, 575
- solidity, 77, 118
 - effect of blade sweep on, 153
 - power/torque weighted, 153
 - thrust weighted, 153
 - weighted, 152–155
 - optimum planform, 154
 - tapered blades, 154–155
- speed
 - factors affecting maximum attainable, 239–240
 - to fly for
 - maximum endurance, 237
 - maximum range, 235–236
 - minimum power, 233–235
- square–cube law, 283, 307
- stabilator, 312
- stall
 - effects on a wind turbine, 747
 - flutter, 526
 - Mach number effects on, 392–398
 - onset of, 77, 79, 385
 - Reynolds number effects on, 389–392
 - types of, 70, 387–398
 - dynamic, *see* dynamic stall
 - leading edge, 387–388
 - shock induced, 359, 394
 - thin-airfoil, 387
 - trailing edge, 387, 389
- standard atmosphere, 212
- standard day, 214
- state-space model
 - compressible flow, 478–480
 - incompressible flow, 463–465
- static droop, 282
- strakes, 310–311, 673–674
- surface singularity methods, 783–786
 - drag prediction, 305

- swashplate, 188
 description of, 188–189
 early applications of, 20, 28, 29, 188
 for coaxial rotor, 190
- sweep, 153, 158, 292–294, 547
- swept tips, 58, 292
 BERP blade, *see* BERP rotor
 design of, 293–294
 experiments with, 294–295
 types of, 292–293
- swirl, 68
- synchropter, 31
- tabs, *see* pitching moment
- tail boom, 304, 310, 311, 674
- tail rotors, *see* anti-torque devices
 aerodynamic interactions, 682
 design requirements, 319
 direction of rotation, 316, 684
 precessional stall, 317
 thrust requirements, 315
- tandem rotors
 overlap, 108
 performance of, 241–242
- taper, 154
 effects on rotor performance, 292, 294
 hyperbolic, 136
 linear, 136, 137, 138
- teetering rotor, *see* rotor, types of
 flapping motion of, 199
- Theodorsen's theory, 431–440
 comparison with experiment, 437–438, 439–440
 limitations of, 482
- thin airfoil theory, 786–787
 modeling of trailing edge tabs, 381–382
 pitching moment, 379–380
 quasi-steady, 429–430
- thrust coefficient
 alternative definition of, 67
 definition of, 67
- tilt-rotors, 47, 48, 66, 327–328
 early developments of, 48
 XV-15, V-22, 48
- tilt-wings, 47, 48, 328
- time-varying velocity, 453–457
- tip loss, 68, 74, 122–124
 factors, 75–77, 122–124
 for a wind turbine, 743
 Prandtl method, 75
- tip path plane, *see* reference planes
- tip relief, 221–223
- tip shape, *see* swept tips
- tip speed, 320
 definition of, 66
 selection of, 80, 283–285
- tip vortices, 584–598
 aperiodic behavior of, 582
 CFD modeling of, 794
 formation, 794
 measurements of, 584–586
 models of, 586–598
 natural condensation in, 55, 568
 perturbations of, 582–584
- tower shadow, *see* unsteady aerodynamics, wind turbines
- tractor tail rotor, *see* anti-torque devices, tail rotor
- transitional boundary layer, *see* boundary layers
- translational lift, 100
- traveling sharp-edged gust, *see* Miles's problem
- trim
 equilibrium equation of, 204–207
 introduction to, 202
 types of, 203
 free-flight, 203
 wind-tunnel, 203
 variation of control angles in, 207
- TsAGI, 44
- turbulence, 86, 572
 airfoils, 385
 hub, 307
 hub wake, 677
 in vortices, 593
 in wind tunnels, 387
 modeling, 535
- turbulent boundary layer, *see* boundary layers
- turbulent wake state, 90
- twist, 120, 290–292
 effects of in forward flight, 290
 ideal, 122, 123
- underslung teetering rotor, *see* rotor, types of
- universal power curve, *see* power
- unsteady aerodynamics
 attached flow, 428–429
 blade vortex interaction, 488–489
 Duhamel integral, 446–447, 458–459
 of wind turbines, 757–763
 sources of, 424
 state-space modeling of, 463–465, 478–480
 time-varying onset velocity, 453–457
 wind turbines
 dynamic stall, 761
 tower shadow, 760
- Verne, Jules, 10
- vertical stabilizer, 312–313
- von Baumhaeur, A. G., 19
- von Doblhoff, Friedrich, 32, 718
- von Kármán, Theodore, 14
- vortex ring state, 90, 252, 638
 blade twist effects on, 255
 disk loading effects on, 255
 free-vortex solution for, 638
 implications on flight boundary, 255
 modeling of, 803
 on tail rotor, 682
 vorticity transport solution for, 638

- vortex wake models, 598–644
 acceleration methods, 617–618
 comparison with experiment, 621–627
 free-vortex wakes, 614–627
 cost of, 617
 numerical characteristics of, 618–620
 solution methodologies, 615–616
 prescribed wakes
 forward flight, 607–614
 hover, 604–607
 vortices, *see* tip vortices
 vorticity transport equations, 777–779
- Wagner's function, 446–448
 approximations to, 447–448
 wake models, *see* vortex wake models
 wakes
 blade near wake, 424–427
 CFD modeling of, 777, 797, 801, 802
 effects of maneuvers on, 640–644
 features in forward flight, 575–581
 features in hover, 572–575
 hover
 contraction ratio, 63
 slipstream velocity, 62
 other features of, 582–584
 tip vortices, *see* tip vortices
 visualization techniques for, 568–572
 natural condensation, 55, 568–569
 schlieren, 570–571
 shadowgraphy, 571–572
 smoke, 257, 569–570
- Weir Company, 21, 702
 autogiros, 22
 W-5 & W-6 helicopters, 30
 W-9, 35
 Westland Helicopters, *see* Agusta-Westland
 wind
 turbulence in, 735
 wind models, 733
 wind tunnel
 2-D testing, 387
 airfoil interference effects, 370, 387
 rotor interference effects, 262, *see also*
 ground-effect
 wind turbine
 blade element analysis of, 735–738
 blade element momentum analysis of, 738–741
 example of, 725
 furling, 731
 history of development of, 724
 momentum analysis of, 727–731
 power
 control of, 731
 efficiency of, 730
 representative power curve, 731
 power output from, 727
 yawed flow operation, 750
 windmill brake state, 90
- Yak Company, 46
 Young, Arthur, 37
 Yuriev, Boris, 13
 Zhukovskii, *see* Joukowski