

Next Generation Wireless LANs

If you've been searching for a way to get up to speed on IEEE 802.11n and 802.11ac WLAN standards without having to wade through the entire 802.11 specification, then look no further.

This comprehensive overview describes the underlying principles, implementation details, and key enhancing features of 802.11n and 802.11ac. For many of these features, the authors outline the motivation and history behind their adoption into the standard. A detailed discussion of the key throughput, robustness, and reliability enhancing features (such as MIMO, multi-user MIMO, 40\80\160 MHz channels, transmit beamforming, and packet aggregation) is given, in addition to clear summaries of the issues surrounding legacy interoperability and coexistence.

Now updated and significantly revised, this 2nd edition contains new material on 802.11ac throughout, including revised chapters on MAC and interoperability, as well as new chapters on 802.11ac PHY, and multi-user MIMO, making it an ideal reference for designers of WLAN equipment, network managers, and researchers in the field of wireless communication.

Eldad Perahia is a Principal Engineer in the Standards and Technology Group at Intel Corporation. He is Chair of the IEEE 802.11 Very High Throughput in 60 GHz Task Group (TGad), the IEEE 802.11 Very High Throughput in <6 GHz Task Group (TGac) Coexistence Ad Hoc Co-Chair, the IEEE 802.11 liaison from the IEEE 802.19 Wireless Coexistence Working Group, and the former Chair of the IEEE 802.11 Very High Throughput Study Group. He was awarded his Ph.D. in Electrical Engineering from the University of California, Los Angeles and holds 21 patents in various areas of wireless communications.

Robert Stacey is a Wireless Systems Architect at Apple, Inc. He is the IEEE 802.11 Very High Throughput in <6 GHz Task Group (TGac) Technical Editor and MU-MIMO Ad Hoc Co-Chair. He was a member of the IEEE 802.11 High Throughput Task Group (TGn) and a key contributor to the various proposals, culminating in the final joint proposal submission that became the basis for the 802.11n draft standard. He holds numerous patents in the field of wireless communications.

Cambridge University Press
978-1-107-01676-7 - Next Generation Wireless LANs: 802.11n and 802.11ac
Eldad Perahia and Robert Stacey
Frontmatter
[More information](#)

“The authors are renowned experts in the field. The book is a must read for engineers seeking knowledge of recent advances in WLAN technologies.”

Dr Osama Aboul-Magd; IEEE 802.11ac Task Group Chair.

“First edition of the book “Next Generation Wireless LANs” by Eldad and Robert is excellent and very popular. The second edition adds newly developed IEEE 802.11ac standard with the same excellence in addressing technical features and easy to read writing style.”

Vinko Erceg, Broadcom Corporation

“The 802.11 standard has been evolving for over 20 years and now contains nearly 3000 pages of information. The authors have had direct involvement in writing many of those pages. This book represents a significant accomplishment in conveying and explaining the engineering behind the features for two of the most important radio options provided by the standard. Radio engineers approaching the standard for the first time as well as those already engaged in product development will find this text remarkably rewarding.”

Bruce Kraemer, Marvell Semiconductor and Chair, IEEE 802.11 Working Group

This endorsement solely represents the views of the person who is endorsing this book and does not necessarily represent a position of either the company, the IEEE or the IEEE Standards Association.

Cambridge University Press

978-1-107-01676-7 - Next Generation Wireless LANs: 802.11n and 802.11ac

Eldad Perahia and Robert Stacey

Frontmatter

[More information](#)

Next Generation Wireless LANs

802.11n and 802.11ac

ELDAD PERAHIA

Intel Corporation

ROBERT STACEY

Apple Inc.



CAMBRIDGE
UNIVERSITY PRESS

Cambridge University Press
978-1-107-01676-7 - Next Generation Wireless LANs: 802.11n and 802.11ac
Eldad Perahia and Robert Stacey
Frontmatter
[More information](#)

CAMBRIDGE UNIVERSITY PRESS

University Printing House, Cambridge CB2 8BS, United Kingdom

Cambridge University Press is part of the University of Cambridge.

It furthers the University's mission by disseminating knowledge in the pursuit of education, learning and research at the highest international levels of excellence.

www.cambridge.org

Information on this title: www.cambridge.org/9781107016767

© Cambridge University Press 2008, 2013

This publication is in copyright. Subject to statutory exception and to the provisions of relevant collective licensing agreements, no reproduction of any part may take place without the written permission of Cambridge University Press.

First published 2008
Reprinted with corrections 2010
Second edition 2013
5th printing 2015

Printed in the United Kingdom by TJ International Ltd, Padstow, Cornwall

A catalog record for this publication is available from the British Library

Library of Congress Cataloging-in-Publication Data

Perahia, Eldad, 1967 – author.

Next generation wireless LANs : 802.11n, 802.11ac, and Wi-Fi direct / Eldad Perahia, Intel Corporation, Robert Stacey, Apple Inc. – Second edition.

pages cm

ISBN 978-1-107-01676-7 (hardback)

1. Wireless LANs. I. Stacey, Robert, 1967 – author. II. Title.

TK5105.78.P47 2013

621.39'8–dc23

2012033809

ISBN 978-1-107-01676-7 Hardback

Cambridge University Press has no responsibility for the persistence or accuracy of URLs for external or third-party internet websites referred to in this publication, and does not guarantee that any content on such websites is, or will remain, accurate or appropriate.

Cambridge University Press

978-1-107-01676-7 - Next Generation Wireless LANs: 802.11n and 802.11ac

Eldad Perahia and Robert Stacey

Frontmatter

[More information](#)

To my wife Sarah and our son Nathan

— Eldad Perahia

To my wife Celia and son Zachary

— Robert Stacey

Cambridge University Press

978-1-107-01676-7 - Next Generation Wireless LANs: 802.11n and 802.11ac

Eldad Perahia and Robert Stacey

Frontmatter

[More information](#)

Contents

<i>Foreword by Dr. Andrew Myles</i>	<i>page xv</i>
<i>Preface to the first edition</i>	xix
<i>Preface to the second edition</i>	xxi
<i>List of abbreviations</i>	xxii
Chapter 1 Introduction	1
1.1 An overview of IEEE 802.11	3
1.1.1 The 802.11 MAC	3
1.1.2 The 802.11 PHYs	4
1.1.3 The 802.11 network architecture	6
1.1.4 Wi-Fi Direct	6
1.2 History of high throughput and 802.11n	7
1.2.1 The High Throughput Study Group	7
1.2.2 Formation of the High Throughput Task Group (TGn)	8
1.2.3 Call for proposals	10
1.2.4 Handheld devices	11
1.2.5 Merging of proposals	11
1.2.6 802.11n amendment drafts	11
1.3 Environments and applications for 802.11n	12
1.4 Major features of 802.11n	14
1.5 History of Very High Throughput and 802.11ac	17
1.6 Outline of chapters	20
References	22
Part I Physical layer	25
Chapter 2 Orthogonal frequency division multiplexing	27
2.1 Background	27
2.2 Comparison to single carrier modulation	29
References	31

Chapter 3	MIMO/SDM basics	32
3.1	SISO (802.11a/g) background	32
3.2	MIMO basics	32
3.3	SDM basics	34
3.4	MIMO environment	36
3.5	802.11n and 802.11ac propagation model	38
3.5.1	Impulse response	39
3.5.2	Antenna correlation	42
3.5.3	802.11n Doppler model	45
3.5.4	802.11ac Doppler model	46
3.5.5	Physical layer impairments	47
3.5.6	Path loss	50
3.6	Linear receiver design	51
3.7	Maximum likelihood estimation	54
	References	56
	Appendix 3.1 802.11n channel models	57
Chapter 4	PHY interoperability with 11a/g legacy OFDM devices	62
4.1	11a packet structure review	62
4.1.1	Short Training field	62
4.1.2	Long Training field	65
4.1.3	Signal field	68
4.1.4	Data field	69
4.1.5	Packet encoding process	70
4.1.6	Receive procedure	72
4.2	Mixed format high throughput packet structure	74
4.2.1	Non-HT portion of the MF preamble	75
4.2.2	HT portion of the MF preamble	81
4.2.3	Data field	88
4.2.4	HT MF receive procedure	96
	References	102
	Appendix 4.1 20 MHz basic MCS tables	103
Chapter 5	High throughput	105
5.1	40 MHz channel	105
5.1.1	40 MHz subcarrier design and spectral mask	106
5.1.2	40 MHz channel design	108
5.1.3	40 MHz mixed format preamble	108
5.1.4	40 MHz data encoding	113
5.1.5	MCS 32: high throughput duplicate format	116
5.1.6	20/40 MHz coexistence with legacy in the PHY	119
5.1.7	Performance improvement with 40 MHz	120

5.2	20 MHz enhancements: additional data subcarriers	121
5.3	MCS enhancements: spatial streams and code rate	122
5.4	Greenfield (GF) preamble	127
5.4.1	Format of the GF preamble	128
5.4.2	PHY efficiency	130
5.4.3	Issues with GF	130
5.4.4	Preamble auto-detection	134
5.5	Short guard interval	136
	References	140
Appendix 5.1	Channel allocation	141
Appendix 5.2	40 MHz basic MCS tables	141
Appendix 5.3	Physical layer waveform parameters	146
Chapter 6	Robust performance	147
6.1	Receive diversity	147
6.1.1	Maximal ratio combining basics	148
6.1.2	MIMO performance improvement with receive diversity	149
6.1.3	Selection diversity	152
6.2	Spatial expansion	152
6.3	Space-time block coding	152
6.3.1	Alamouti scheme background	153
6.3.2	Additional STBC antenna configurations	156
6.3.3	STBC receiver and equalization	159
6.3.4	Transmission and packet encoding process with STBC	161
6.4	Low density parity check codes	164
6.4.1	LDPC encoding process	165
6.4.2	Effective code rate	175
6.4.3	LDPC coding gain	176
	References	177
Appendix 6.1	Parity check matrices	177
Chapter 7	Very High Throughput PHY	182
7.1	Channelization	182
7.2	Single user (SU) VHT packet structure	184
7.3	VHT format preamble	185
7.3.1	Non-VHT portion of the VHT format preamble	185
7.3.2	VHT portion of the VHT format preamble	191
7.3.3	VHT data field	200
7.4	Modulation coding scheme	212
	References	217

Part II Medium access control layer	219
Chapter 8 Medium access control	221
8.1 Protocol layering	222
8.2 Finding, joining, and leaving a BSS	223
8.2.1 Beacons	223
8.2.2 Scanning	224
8.2.3 Authentication	224
8.2.4 Association	225
8.2.5 Reassociation	226
8.2.6 Disassociation	226
8.2.7 802.1X Authentication	226
8.2.8 Key distribution	227
8.3 Distributed channel access	228
8.3.1 Basic channel access timing	229
8.4 Data/ACK frame exchange	231
8.4.1 Fragmentation	232
8.4.2 Duplicate detection	233
8.4.3 Data/ACK sequence overhead and fairness	234
8.5 Hidden node problem	234
8.5.1 Network allocation vector (NAV)	235
8.5.2 EIFS	236
8.6 Enhanced distributed channel access	236
8.6.1 Transmit opportunity	238
8.6.2 Channel access timing with EDCA	239
8.6.3 EDCA access parameters	239
8.6.4 EIFS revisited	240
8.6.5 Collision detect	240
8.6.6 QoS Data frame	241
8.7 Block acknowledgement	241
8.7.1 Block data frame exchange	243
8.8 Power management	243
8.8.1 AP TIM transmissions	244
8.8.2 PS mode operation	244
8.8.3 WNM-Sleep	246
8.8.4 SM power save	246
8.8.5 Operating Mode Notification	246
References	247
Chapter 9 MAC throughput enhancements	248
9.1 Reasons for change	248
9.1.1 Throughput without MAC changes	248

9.1.2	MAC throughput enhancements	250
9.1.3	Throughput with MAC efficiency enhancements	251
9.2	Aggregation	253
9.2.1	Aggregate MSDU (A-MSDU)	254
9.2.2	Aggregate MPDU (A-MPDU)	255
9.2.3	Aggregate PSDU (A-PSDU)	257
9.2.4	A-MPDU in VHT PPDU	258
9.2.5	VHT single MPDU	259
9.3	Block acknowledgement	259
9.3.1	Immediate and delayed block ack	259
9.3.2	Block ack session initiation	260
9.3.3	Block ack session data transfer	261
9.3.4	Block ack session tear down	262
9.3.5	Normal ack policy in a non-aggregate	262
9.3.6	Reorder buffer operation	263
9.4	HT-immediate block ack	264
9.4.1	Normal Ack policy in an aggregate	264
9.4.2	Compressed block ack	265
9.4.3	Full state and partial state block ack	265
9.4.4	HT-immediate block ack TXOP sequences	269
9.5	HT-delayed block ack	269
9.5.1	HT-delayed block ack TXOP sequences	270
	References	270
 Chapter 10 Advanced channel access techniques		 271
10.1	PCF	271
10.1.1	Establishing the CFP	271
10.1.2	NAV during the CFP	272
10.1.3	Data transfer during the CFP	272
10.1.4	PCF limitations	273
10.2	HCCA	274
10.2.1	Traffic streams	274
10.2.2	Controlled access phases	276
10.2.3	Polled TXOP	276
10.2.4	TXOP requests	277
10.2.5	Use of RTS/CTS	277
10.2.6	HCCA limitations	277
10.3	Reverse direction protocol	277
10.3.1	Reverse direction frame exchange	278
10.3.2	Reverse direction rules	279
10.3.3	Error recovery	279
10.4	PSMP	280
10.4.1	PSMP recovery	281

10.4.2	PSMP burst	281
10.4.3	Resource allocation	282
10.4.4	Block ack usage under PSMP	283
	References	283
Chapter 11 Interoperability and coexistence		284
11.1	Station capabilities and operation	284
11.1.1	HT station PHY capabilities	285
11.1.2	VHT station PHY capabilities	285
11.1.3	HT station MAC capabilities	286
11.1.4	VHT station MAC capabilities	286
11.1.5	Advanced capabilities	286
11.2	BSS operation	287
11.2.1	Beacon transmission	288
11.2.2	20 MHz BSS operation	289
11.2.3	20/40 MHz HT BSS operation	289
11.2.4	VHT BSS operation	293
11.2.5	OBSS scanning requirements	294
11.2.6	Signaling 40 MHz intolerance	298
11.2.7	Channel management at the AP	299
11.2.8	Establishing a VHT BSS in the 5 GHz band	300
11.3	A summary of fields controlling 40 MHz operation	300
11.4	Channel access in wider channels	301
11.4.1	Overlapping BSSs	302
11.4.2	Wide channel access using RTS/CTS	303
11.4.3	TXOP rules for wide channel access	304
11.4.4	Clear channel assessment	304
11.4.5	NAV assertion in an HT and VHT BSS	306
11.5	Protection	306
11.5.1	Protection with 802.11b stations present	307
11.5.2	Protection with 802.11g or 802.11a stations present	307
11.5.3	Protection for OBSS legacy stations	308
11.5.4	RIFS burst protection	308
11.5.5	HT Greenfield format protection	309
11.5.6	RTS/CTS protection	309
11.5.7	CTS-to-Self protection	310
11.5.8	Protection using a non-HT, HT mixed, or VHT PPDU with non-HT response	311
11.5.9	Non-HT station deferral with HT mixed and VHT format PPDUs	311
11.5.10	L-SIG TXOP protection	312

11.6	Phased coexistence operation (PCO)	314
11.6.1	Basic operation	314
11.6.2	Minimizing real-time disruption	315
	References	316
 Chapter 12 MAC frame formats		317
12.1	General frame format	317
12.1.1	Frame Control field	317
12.1.2	Duration/ID field	321
12.1.3	Address fields	321
12.1.4	Sequence Control field	321
12.1.5	QoS Control field	322
12.1.6	HT Control field	324
12.1.7	Frame Body field	327
12.1.8	FCS field	327
12.2	Format of individual frame types	327
12.2.1	Control frames	327
12.2.2	Data frames	336
12.2.3	Management frames	337
12.3	Management frame fields	342
12.3.1	Fields that are not information elements	344
12.3.2	Information elements	344
	References	361
 Part III Transmit beamforming, multi-user MIMO, and fast link adaptation		363
 Chapter 13 Transmit beamforming		365
13.1	Singular value decomposition	366
13.2	Transmit beamforming with SVD	369
13.3	Eigenvalue analysis	370
13.4	Unequal MCS	376
13.5	Receiver design	378
13.6	Channel sounding	379
13.7	Channel state information feedback	381
13.7.1	Implicit feedback	382
13.7.2	Explicit feedback	386
13.8	Improved performance with transmit beamforming	393
13.9	Degradations	399
13.10	MAC considerations	406
13.10.1	Sounding PPDU	407
13.10.2	Implicit feedback beamforming	410
13.10.3	Explicit feedback beamforming	413

13.11	Comparison between implicit and explicit	416
13.12	Transmit beamforming in 802.11ac	417
13.12.1	VHT sounding protocol	418
	References	419
Appendix 13.1	Unequal MCS for 802.11n	420
	Unequal MCS for 20 MHz	420
	Unequal MCS for 40 MHz	422
Chapter 14	Multi-user MIMO	424
14.1	MU-MIMO pre-coding	426
14.2	Receiver design	427
14.3	PHY considerations	428
14.3.1	VHT MU preamble	430
14.3.2	VHT MU data field	432
14.3.3	Compressed beamforming matrices	435
14.4	Group ID	435
14.4.1	Receive operation	435
14.4.2	Group ID management	435
14.5	MAC support for MU-MIMO	436
14.5.1	MU aggregation	436
14.5.2	MU acknowledgements	437
14.5.3	EDCA TXOPs for MU sequences	437
14.5.4	TXOP sharing	438
14.6	VHT sounding protocol for MU-MIMO	438
14.6.1	The basic sounding exchange	438
14.6.2	Support for fragmentation	439
	References	439
Chapter 15	Fast link adaption	440
15.1	MCS feedback	441
15.2	MCS feedback mechanisms	442
15.3	MCS feedback using the HT variant HT Control field	442
15.4	MCS feedback using the VHT variant HT Control field	443
	<i>Index</i>	445

Foreword

The first version of the 802.11 standard was ratified in 1997 after seven long years of development. However, initial adoption of this new technology was slow, partly because of the low penetration of devices that needed the “freedom of wireless.”

The real opportunity for 802.11 came with the increased popularity of laptop computers just a few years later. This popularity brought a rapidly growing user base wanting network connectivity not only while connected to an Ethernet cable at home or at work, but also in between: in hotels, airports, conference centers, restaurants, parks, etc. 802.11 provided a cheap and easy way to make laptop mobility a reality for anyone who wanted it.

However, technology by itself is rarely sufficient, particularly in the networking space, where interoperability of devices from multiple vendors is almost always the key to market success. Having been formed as WECA in 1999, the Wi-Fi Alliance was ready to provide certification of multi-vendor interoperability.

With the right technology from the IEEE 802.11 Working Group, certified interoperability from the Wi-Fi Alliance, and a real market need based on a growing installed base of laptops, the conditions were ripe for the Wi-Fi market to take off, and indeed it did. By 2007 virtually every new laptop contains Wi-Fi as standard equipment. More importantly, and unlike some other “successful” wireless technologies, many of these devices are used regularly. With this wide use came a growing understanding of the power of cheap, easy-to-deploy, and easy-to-manage interoperable Wi-Fi networks.

The natural next step was for people to ask, “What else can we use Wi-Fi for?” The answer is increasingly becoming “everything, everywhere!” Not just laptops, but now almost anything mobile and even many fixed devices contain Wi-Fi, and they are used in a phenomenal range of applications, including data, voice, games, music, video, location, public safety, vehicular, etc. In 2007, more than 300 million Wi-Fi devices were shipped. By 2012, some analysts are forecasting that more than one billion Wi-Fi devices will be shipped every year.

The 2.4 GHz 802.11b 11 Mb/s DSSS/CCK PHY and the basic 802.11 contention-based MAC provided the basis for a great industry. However, the rapid growth of the Wi-Fi market challenged the capabilities of the technology. It was not long before better security (802.11i certified by the Wi-Fi Alliance as WPA/WPA2TM) and better Quality of Service (802.11e certified by the Wi-Fi Alliance as WMMTM and WMM Power Save) were defined, certified, and deployed.

It was also not long before higher data rates were demanded for greater data density and to support the many new and exciting devices and applications. 802.11a, providing

54 Mbps based on OFDM in the 5 GHz band, failed to garner significant support because two radios were required to maintain backward compatibility with 2.4 GHz 802.11b devices; the cost of two radios was often too high. The real success story was 802.11g, which provided 54 Mbps based on OFDM in the 2.4 GHz band in a way that was backward-compatible with 802.11b.

The success of 802.11g drove the use of Wi-Fi to new heights and expanded the demands on the technology yet again; everyone wanted more. Fortunately, the technology continued to develop and in 2002 the IEEE 802.11 Working Group started defining the next generation of PHY and MAC features as part of 802.11n. 802.11n will define mechanisms to provide users some combination of greater throughput, longer range and increased reliability, using mandatory and optional features in the PHY (including MIMO technology and 40 MHz channels) and the MAC (including more efficient data aggregation and acknowledgements).

Interestingly, 802.11n operates in both the 2.4 GHz and 5 GHz bands. It is expected that 5 GHz operation will be more popular than when 802.11a was introduced, because 2.4 GHz is now more congested, the number of available channels in the 5 GHz band has been expanded with the introduction of DFS and TPC technology, there is more need for high throughput 40 MHz channels, and the cost of dual-band radios has decreased.

The 802.11n standard is not yet complete, and is unlikely to be ratified by the IEEE until at least mid 2009. Until August 2006, the Wi-Fi Alliance had a policy to not certify 802.11n products until the standard was ratified. However, some vendors decided the market could not wait for ratification of the 802.11n standard and started releasing pre-standard products. These products were often not interoperable at the expected performance levels because they were not based on a common interpretation of the draft 802.11n specification. The problem for the Wi-Fi Alliance was that these products were adversely affecting the reputation of Wi-Fi. The Wi-Fi Alliance decided the only way forward was to certify the basic features of 802.11n from a pre-standard draft. Such a decision is not without precedent. In 2003, certification of WPA started before the 802.11i standard was ratified and in 2004 certification of WMM started before 802.11e was ratified. The Wi-Fi Alliance commenced certification of 802.11n draft 2.0 on 26 June 2007.

The decision has turned out to be the right one for the industry and for users. The Wi-Fi CERTIFIED 802.11n draft 2.0 programme has been remarkably successful, with more than 150 products certified in less than five months. This represents a significantly higher number of certified products than for the 802.11g programme during a similar period after launch. The Wi-Fi Alliance's certification program has helped ensure interoperability for the many products that will be released before the ratification of the 802.11n standard. This is particularly important given that the likely ratification date of the 802.11n standard has been extended by more than a year since the decision to start a certification program was announced by the Wi-Fi Alliance. The next challenge for the Wi-Fi Alliance is to ensure a backward-compatible transition path from the 802.11n draft 2.0 as certified by the Wi-Fi Alliance to the final ratified standard.

Standards are never the most accessible of documents. The 802.11 standard is particularly difficult to understand because it has been amended so many times by different groups and editors over a long period. A draft amendment to the standard, such as

802.11n D2.0, is even harder to interpret because many clauses are still being refined and the refinement process often has technical and political aspects that are only visible to those participating full time in the IEEE 802.11 Working Group.

Books like this one are invaluable because they provide the details and the background that allow readers to answer the questions, “What is likely to be in the final standard and how does it work?” Eldad and Robert should be congratulated on taking up the challenge.

Dr. Andrew Myles
Chairman of the BoD
Wi-Fi Alliance
6 December 2007

Cambridge University Press

978-1-107-01676-7 - Next Generation Wireless LANs: 802.11n and 802.11ac

Eldad Perahia and Robert Stacey

Frontmatter

[More information](#)

Preface to the first edition

Having worked on the development of the 802.11n standard for some time, we presented a full day tutorial on the 802.11n physical layer (PHY) and medium access control (MAC) layer at the IEEE Globecom conference held in San Francisco in December 2006. Our objective was to provide a high level overview of the draft standard since, at the time, there was very little information on the details of the 802.11n standard available to those not intimately involved in its development. After the tutorial, we were approached by Phil Meyler of Cambridge University Press and asked to consider expanding the tutorial into a book.

Writing a book describing the standard was an intriguing prospect. We felt that a book would provide more opportunity to present the technical details in the standard than was possible with the tutorial. It would fill the gap we saw in the market for a detailed description of what is destined to be one of the most widely implemented wireless technologies. While the standard itself conveys details on what is needed for interoperability, it lacks the background on why particular options should be implemented, where particular aspects came from, the constraints under which they were designed, or the benefit they provide. All this we hoped to capture in the book. The benefits various features provide, particularly in the physical layer, are quantified by simulation results. We wanted to provide enough information to enable the reader to model the physical layer and benchmark their simulation against our results. Finally, with the amended standard now approaching 2500 pages, we hoped to provide an accessible window into the most important aspects, focusing on the throughput and robustness enhancements and the foundations on which these are built.

The book we came up with is divided into three parts. The first part covers the physical layer (PHY), and begins with background information on the 802.11a/g OFDM PHY on which the 802.11n PHY is based and interoperates, and proceeds with an overview of spatial multiplexing, the key throughput enhancing technology in 802.11n. This is followed by details on exactly how high throughput is achieved in 802.11n using spatial multiplexing and wider, 40 MHz channels. This in turn is followed by details on robustness enhancing features such as receive diversity, spatial expansion, space-time block codes, and low density parity check codes.

The second part covers the medium access control (MAC) layer. This part provides background on the original 802.11 MAC as well as the 802.11e quality of service (QoS) enhancements. It gives an overview of why changes were needed in the MAC to achieve higher throughput, followed by details on each of the new features introduced. Given the

large installed base of 802.11 devices, coexistence and interoperability are considered crucial to the smooth adoption of the standard. To this end, the book provides a detailed discussion on features supporting coexistence and interoperability.

In the third part we provide details on two of the more advanced aspects of the standard, transmit beamforming and link adaptation. These topics are covered in a section of their own, covering both the PHY and the MAC.

Writing this book would not have been possible without help from our friends and colleagues. We would like to thank Thomas (Tom) Kenney and Brian Hart for reviewing the PHY portion of the book and Tom Kenney and Michelle Gong for reviewing the MAC portion of the book. They provided insightful comments, suggestions, and corrections that significantly improved the quality of the book.

One of the goals of this book is to provide the reader with a quantitative feel of the benefit of the PHY features in the 802.11n standard. This would have been impossible without the extensive simulation support provided to us by Tom Kenney. He developed an 802.11n PHY simulation platform that includes most of the 802.11n PHY features and is also capable of modeling legacy 802.11a/g. The simulation includes all the 802.11n channel models. Furthermore, Tom modeled receiver functionality such as synchronization, channel estimation, and phase tracking. The simulation also included impairments such as power amplifier non-linearity and phase noise to provide a more realistic measure of performance.

The simulation supports both 20 MHz and 40 MHz channel widths. With the 40 MHz simulation capability, Tom generated the results given in Figure 5.8 in Section 5.1.5 modeling MCS 32 and Figure 5.9 in Section 5.1.7 which illustrates the range and throughput improvement of 40 MHz modes. With the MIMO/SDM capability of the simulation in both AWGN channel and 802.11n channel models, Tom produced the results for Figures 5.12–5.15 in Section 5.3. By designing the simulation with the flexibility to set the transmitter and receiver to different modes, he also produced the results given in Figure 5.18 in Section 5.4 modeling the behavior of a legacy 802.11a/g device receiving a GF transmission. Tom also incorporated short guard interval into the simulation with which the results for sensitivity to time synchronization error in Figures 5.20–5.22 in Section 5.5 were generated.

Tom designed the simulation with the ability to select an arbitrary number of transmitter and receiver antennas independent from the number of spatial streams. Using this capability he produced the results for receive diversity gain in Figures 6.2–6.4 in Section 6.1 and spatial expansion performance in Figures 6.5 and 6.6 in Section 6.2. Tom also incorporated space-time block coding and low density parity check coding into the simulation and generated the results given in Figures 6.8, 6.9, 6.14, 6.15, and 6.16 in Section 6.3 and Figure 6.24 in Section 6.4.

To accurately model the performance of a transmit beamforming system, it is important to include aspects like measurement of the channel state information, beamforming weight computation, and link adaptation. Tom incorporated all of these functions into the simulation to generate the waterfall curves in Figures 13.11–13.16 and the throughput curves in Figures 13.17 and 13.18 in Section 13.8.

We sincerely hope our book provides you with insight and a deeper understanding of the 802.11n standard and the technology upon which it is built.

Preface to the second edition

While 802.11n was a revolutionary enhancement over 802.11a/g, and necessitated an entire book for proper presentation of the new technology, 802.11ac is more of an evolutionary improvement over 802.11n by providing wider bandwidth channels and multi-user MIMO. As such we felt that the treatment of new 802.11ac features could be addressed by a few extra chapters in an update of our original 802.11n book, now an 802.11n/ac book.

The new single user Very High Throughput physical layer packet structure is described in a new Chapter 7, including a description of 80 MHz and 160 MHz waveforms. The new downlink multi-user MIMO mechanism in 802.11ac is presented in a new Chapter 14. Enhancements to channel access for 802.11ac have been added to Chapter 11. Several new basic service set and clear channel assessment rules to manage 80 MHz and 160 MHz operation and coexistence are described in Chapter 11. Modifications to 802.11n channel model Doppler component are given in Chapter 3 and Chapter 13. Furthermore, we discuss the simplification of single user transmit beamforming in 802.11ac in Chapter 13.

We would like to again thank our friends and colleagues for their help with preparing the new material for the second edition. In particular, Thomas Kenney reviewed the MAC, PHY, and MU-MIMO material. He also updated the 802.11n PHY simulation platform to 802.11ac and provided all the 802.11ac PHY simulation results illustrated in Figures 7.9, 7.10, 7.20, and 7.21. Sameer Vermani reviewed the MU-MIMO chapter and graciously provided the MU-MIMO simulation results in Figure 14.2. We are also thankful to Simone Merlin who reviewed the MAC and MU-MIMO chapters.

Abbreviations

μs	microseconds
2G	second generation (cellular)
3G	third generation (cellular)
AC	access category
ACK	acknowledgement
ADC	analog-to-digital converter
ADDBA	add block acknowledgement
ADDTs	add traffic stream
AGC	automatic gain control
AID	association identifier
AIFS	arbitration inter-frame space
A-MPDU	aggregate MAC protocol data unit
A-MSDU	aggregate MAC service data unit
AoA	angle of arrival
AoD	angle of departure
AP	access point
APSD	automatic power save delivery
A-PSDU	aggregate PHY service data unit
AS	angular spectrum
ASEL	antenna selection
AWGN	additive white Gaussian noise
BA	block acknowledgement
BAR	block acknowledgement request
BCC	binary convolution code
BF	beamforming
BICM	bit interleaved coded modulation
bps	bits-per-second
BPSCS	coded bits per single carrier for each spatial stream
BPSK	binary phase shift keying
BSS	basic service set
BSSID	BSS identifier
BW	bandwidth
CBPS	coded bits per symbol

CBPSS	coded bits per spatial stream
CBW	channel bandwidth
CCA	clear channel assessment
CCDF	complementary cumulative distribution function
CCK	complementary code keying
CFP	contention free period
CP	contention period
CRC	cyclic redundancy code
CS	carrier sense
CSD	cyclic shift diversity
CSI	channel state information
CSMA	carrier sense multiple access
CSMA/CA	carrier sense multiple access with collision avoidance
CSMA/CD	carrier sense multiple access with collision detection
CTS	clear to send
CW	contention window
DA	destination address
DAC	digital-to-analog converter
dB	decibels
dBc	decibels relative to carrier
dB _i	decibels isotropic relative to an antenna
dBm	decibel of measured power referenced to one milliwatt
DBPS	data bits per OFDM symbol
dBr	dB (relative)
DC	direct current
DCF	distributed coordination function
DELBA	delete block acknowledgement
DIFS	DCF inter-frame space
DL MU-MIMO	downlink multi-user multiple-input multiple-output
DLS	direct link session
DS	distribution system
DSL	digital subscriber line
DSSS	direct sequence spread spectrum
DTIM	delivery traffic indication message
DVD	digital versatile disc
DVR	digital video recorder
EAP	extensible authentication protocol
EDCA	enhanced distributed channel access
EIFS	extended inter-frame space
EIRP	equivalent isotropically radiated power
EOF	end of frame
ERP	enhanced rate PHY
ESS	extended service set

ETSI	European Telecommunications Standards Institute
EVM	error vector magnitude
EWC	Enhanced Wireless Consortium
FCC	Federal Communications Commission
FCS	frame check sequence
FEC	forward error correction
FFT	fast Fourier transform
FHSS	frequency hopped spread spectrum
FS	free space
FTP	file transfer protocol
GF	Greenfield
GF-HT-STF	Greenfield High Throughput Short Training field
GHz	gigahertz
GI	guard interval
GIF	graphics interchange format
GO	group owner
GPS	global positioning system
HC	hybrid coordinator
HCCA	HCF controlled channel access
HCF	hybrid coordination function
HEMM	HCCA, EDCA mixed mode
HT	high throughput
HTC	high throughput control
HT-DATA	High Throughput Data field
HT-LTF	High Throughput Long Training field
HTSG	High Throughput Study Group
HT-SIG	High Throughput Signal field
HT-STF	High Throughput Short Training field
HTTP	hypertext transfer protocol
Hz	Hertz
IBSS	independent basic service set
IC	interference cancellation
IDFT	inverse discrete Fourier transform
IEEE	Institute of Electrical and Electronic Engineers
IFFT	inverse fast Fourier transform
IFS	inter-frame space
I/O	input/output
IP	Internet Protocol
IPv6	Internet Protocol version 6
IR	infrared
ISI	inter-symbol interference
ISM	industrial, scientific, and medical
JPEG	Joint Photographic Experts Group

kHz	kilohertz
km/h	kilometers per hour
LAN	local area networking
LDPC	low density parity check
LLC	logical link control
L-LTF	Non-HT (Legacy) Long Training field
LNA	low noise amplifier
LOS	line-of-sight
LSB	least significant bit
L-SIG	Non-HT (Legacy) Signal field
L-STF	Non-HT (Legacy) Short Training field
LTF	Long Training field
m	meters
MAC	medium access control
MAI	MRQ or ASEL indication
MAN	metropolitan area networking
Mbps	megabit per second
MCS	modulation and coding scheme
MF	mixed format
MFB	MCS feedback
MFSI	MCS feedback sequence indication
MHz	megahertz
MIB	management information base
MIMO	multiple-input multiple-output
ML	maximum likelihood
MMPDU MAC	management protocol data unit
MMSE	minimum mean-square-error
MPDU	MAC protocol data unit
MPEG	Moving Picture Experts Group
MRC	maximal-ratio combining
MRQ	MCS request
Msample/s	mega-samples per second
MSB	most significant bit
MSDU	MAC service data unit
MSE	mean-square-error
MSFI	MCS feedback sequence identifier
MSI	MCS request sequence identifier
MU	multi-user
MU-MIMO	multi-user multiple-input multiple-output
NAV	network allocation vector
NDP	null data packet
NF	noise figure
NLOS	non-line-of-sight

ns	nanosecond
OBO	output back-off
OBSS	overlapping BSS
OFDM	orthogonal frequency division multiplexing
OSI	open systems interconnection
PA	power amplifier
PAR	project authorization request
PAS	power angular spectrum
PC	point coordinator
PCF	point coordination function
PCO	phased coexistence operation
PDP	power delay profile
PDU	protocol data unit
PER	packet error rate
PHY	physical layer
PIFS	PCF inter-frame space
PLCP	physical layer convergence procedure
PPDU	PLCP protocol data unit
ppm	parts per million
PSD	power spectral density
PSDU	PLCP service data unit
PSMP	power-save multi-poll
PSMP-DTT	PSMP downlink transmission time
PSMP-UTT	PSMP uplink transmission time
QAM	quadrature amplitude modulation
QoS	quality of service
QPSK	quadrature phase shift keying
QBPSK	quadrature binary phase shift keying
R	code rate
RA	receiver address
RD	reverse direction
RDG	reverse direction grant
RF	radio frequency
RIFS	reduced inter-frame space
RMS	root-mean-square
RSSI	received signal strength indication
RTS	request to send
Rx	receive
RXTIME	receive time
SA	source address
SAP	service access point
SCP	secure copy protocol
SDM	spatial division multiplexing

SDU	service data unit
SE	spatial expansion
SIFS	short inter-frame space
SIG	Signal field
SIMO	single-input, multiple-output
SISO	single-input, single-output
SMTP	simple mail transfer protocol
SNR	signal-to-noise ratio
SOHO	small-office, home-office
SS	spatial stream
SSC	starting sequence control
SSID	service set identifier
SSN	starting sequence number
STA	station
STBC	space-time block coding
STF	Short Training field
STS	space-time stream
SU	single user
SVD	singular value decomposition
SYM	symbol
TA	transmitter address
TBTT	target beacon transmission time
TC	traffic category
TCLAS	traffic classification
TCM	trellis coded modulation
TCP	transmission control protocol
TDD	time division duplexing
TG _n	Task Group n
TG _y	Task Group y
TID	traffic identifier
TIFF	tagged image file format
TRQ	training request
TS	traffic stream
TSID	traffic stream identifier
TSPEC	traffic specification
TV	television
T _x	transmit
T _x BF	transmit beamforming
TXOP	transmit opportunity
TXTIME	transmit time
UDP	user datagram protocol
USA	United States of America
VHT	very high throughput

VHT-DATA	Very High Throughput Data field
VHT-LTF	Very High Throughput Long Training field
VHT-SIG-A	Very High Throughput Signal-A field
VHT-SIG-B	Very High Throughput Signal-B field
VHT-STF	Very High Throughput Short Training field
VoIP	voice over IP
VPN	virtual private network
WEP	wired equivalent privacy
WFA	Wi-Fi Alliance
WLAN	wireless local area network
WM	wireless medium
WNG SC	Wireless Next Generation Standing Committee
WWiSE	world wide spectral efficiency
XOR	exclusive-or
ZF	zero-forcing
ZIP	ZIP file format