

Index

- 20 MHz
 - and LDPC, 164–177, **165, 167, 168, 169, 173, 174, 175, 176**
 - and spatial diversity, **154**
 - and STBC encoding, 152–164, **154, 156, 157, 158, 160, 161, 162, 163**
 - BSS, 289
 - CCA, 305
 - enhancements to 802.11n amendment, 121–126, **122, 124, 125, 126, 127**
 - MCS tables, **103, 104, 141, 142, 143, 377, 420, 421**
 - receiver sensitivity, 136–140, **138, 139, 140**
- 20/40 MHz
 - BSS, **290, 291, 292**, 292–293, 294, 295–298, **295**
 - channel interference, **107**
 - coexistence element, 351–354, **358**
 - intolerant channel report element, 354, **358**
- 40 MHz
 - BSS, 292–293
 - channel design, 106, **106**
 - fields, 300–301
 - MCS tables, **377, 378, 422, 423**
- 802.11 standard
 - ACK frame format, 231–234, **232, 234**
 - and CSMA/CA, 4, 228
 - BSS, 6, 7, 223–227, **223, 225**
 - definition of layers, 3
 - DS, 6
 - LLC, **4**
 - MAC, 3–4, **4, 222–223, 222, 248–250, 249, 250**
 - PHYs, 4–5, **4, 5, 12, 16**
- 802.11a amendment. *See also* MF packet
 - channel access timing, **240**
 - MF preamble, 62–75, **75**
 - OFDM, 27–29
 - protection mechanisms in, 307–308
 - waveform comparison, **146**
- 802.11a/g amendment. *See* legacy devices
- 802.11ac amendment. *See also* 802.11ac packet structure
 - BSS channel operation, 293, 300–304, **302, 303**
 - CCA, 305–306
 - data rate, **5, 6, 19, 183, 186, 190, 194, 195**
 - fast link adaptation, 441, 443–444
 - history of, 17–19
 - operating mode notification, 247
 - PHY features, 19–20, **20**
 - protection mechanisms in, 306–307, 309, 311, **312**
 - station capabilities, 284–286
 - transmit beamforming, 365, 417–419
 - usage models, 18
- 802.11ac packet structure. *See also* 802.11ac amendment, VHT preamble
 - data field encoding, 200–212, **201, 202, 203, 205, 206, 208, 209, 210**
 - MU, 182, 432–435, **432**
 - SU channelization, 182–183, **183, 184**
 - SU VHT, 184–185, **184**
- 802.11b amendment, 4–5, **5, 232, 307**
- 802.11e amendment
 - and channel access, 236–241, **237, 239**
 - block acknowledgement protocol, 241–243, **243**
 - MAC, **250, 252, 253**
- 802.11g amendment
 - channel access timing, **240**
 - history of, 2, 5, **5**
 - protection mechanisms in, 307–311, **312**
- 802.11h amendment, 299–300, 339
- 802.11n amendment. *See also* transmit beamforming, MFHT packet, high throughput amendment
 - CCA, 305
 - data rate, **6, 12–14, 15, 105–106, 119–128**
 - fast link adaptation, 441
 - GI in, 136–140, **138, 139, 140**
 - issues with, 16, 47–49, **47, 48, 49**
 - linear receiver design, **50, 51–53**
 - MAC, **17**
 - major features of, 14–17, **16**
 - MF preamble, 62–75

- 802.11n amendment (cont.)
 performance enhancements to, 147–181, **178**
 PHYs, 10, 14–16
 protection mechanisms in, 306–307, 309, 311–316,
313, 315
 SM power save, 246
 station capabilities, 284–286
- 802.11n amendment models, **39, 40, 41**
 channel, 38–49, **39, 40, 41, 44, 46, 47, 48, 51, 57, 58,**
59, 60
 fading multipath, 36–38, **37, 38**
 path loss, **41**, 50–51
 usage, 12–14, **13, 14, 15**
- 802.11u amendment, 246
- access point. *See* AP
- ACK frame
 exchange, 231–234, **232, 234**
 format, 330, **333, 437, 437**
- action frame format, 339–342, **340, 341, 342, 358**
- address fields, 321
- aggregation, 443. *See also* throughput
 and data rate, 251–253, **252, 253, 254**
 in 802.11ac amendment, 436–437
 in 802.11n amendment, 253–259, **254, 255, 256, 258**
- Alamouti scheme, 153–156, **154**
- ALOHA NET, 1
- A-MPDU. *See* MPDU aggregation
- A-MSDU. *See* MSDU aggregation
- antenna correlation, 443. *See also* STBC
 in 802.11n channel models, **41, 42–44, 44, 46, 47, 49, 51,**
57, 58, 59, 60
 in MIMO, 37
- AP
 802.11n antenna requirements, 11
 802.11n usage models, 12–14, **13, 14, 15**
 MAC, 223–227, 320
 MU-MIMO, 424–426, 436
 power management, 244
 transmit beamforming, 365, 384
- A-PSDU. *See* PSDU aggregation
- association/reassociation request/response frame format,
 337–338
- authentication
 frame format, 339
 in 802.11 QoS, 224–225, **225**
 in 802.1X, 227
- BA frame format, 332–334
- BAR frame format, 330–332, **337, 339**
- basic service set. *See* BSS
- BCC
 and LDPC, 175–176, **175, 176**
 interleaver in 802.11ac, 205–207, **205, 206**
 packet encoding process, 70–72
- beacon. *See also* PS mode
 CFP, 271–273, **272, 273**
 frame format, 244–246, 337
 HT transmission, 288
 in 802.11 QoS, 223, **223**
- Bell Labs, 1
- bit string encoding
 40 MHz, 114–116
 MFHT packet, 88–89
- block acknowledgement protocol. *See also* throughput
 in 802.11e amendment, 241–243, **243, 259–264, 260, 263,**
264, 265–266, 265
 in 802.11n amendment, 264, 265, 266–270, **267, 268,**
269, 270
- Broadcom, 2
- BSS
 in 802.11 standard, 6, 7, 223–227, **225**
 in 802.11ac amendment, 293, 300–304, **302, 303**
 in 802.11n amendment, 12–14, 287–300, **290, 292, 302**
- calibration
 errors, 399–402, **401, 403–406, 405, 407, 408, 409**
 transmit beamforming, 410–412, **411, 412**
- capability information field, **343, 344, 344, 345**
- capacity based performance curves
 linear receiver design, **53**
 MIMO, **37, 38**
- carrier frequency offset, 30–31
- carrier sense multiple access. *See* CSMA/CA
- carrier sense multiple access with collision detection. *See*
 CSMA/CD
- CCA, 304–306
- channel access timing
 802.11 standard, 229–231, **229, 231, 271–274, 272, 273**
 802.11e amendment, 274–277, **276**
 802.11g amendment, **240**
 802.11n amendment, **240, 277–283, 278, 279, 280, 282**
 in wider channels, 301–306, **302, 303**
- channel bandwidth. *See* data rate
- channel models, 38–49
- channel sounding, 407, **409, 418–419, 419, 443. See also**
 feedback, NDP sounding
- channel switch announcement, 299–300
- clear channel assessment. *See* CCA
- coexistence element, 351–354, **358**
- coexistence with legacy, 119, 443. *See also* PCO
- control wrapper frame format, 335
- correlation coefficient, 43–44
- cost
 MU-MIMO, 424
 of 40 MHz, 105
 of WLAN devices, 2
 OFDM, 31
 transmit beamforming, 365, 387
- CSI
 feedback, 381–392, **382, 392**
 transmit beamforming, 379–381, **380, 380, 381, 413–416,**
415, 416
- CSMA/CA, 4, 221–222, 228

- CSMA/CD, 3, 221
 CTS frame format, 327, **333**
 cyclic shifts
 and LDPC, **176**
 in 802.11ac, **186, 193**
 in 802.11n amendment, 76–77, **77, 78**
- data field encoding
 40 MHz, 113–116
 MFHT packet, 88–95, **90, 92, 95**
 MU VHT, 432–435, **432**
 SU VHT, 200–212, **201, 202, 203, 205, 206, 208, 209, 210**
- data link layer. *See* LLC, MAC frame format
 data rate. *See also* GI
 affected by MAC aggregation, 251–253, **252, 253, 254**
 affected by OFDM, 27
 and 802.11ac amendment, 6, 19, 182, **183**
 and 802.11n amendment, 5, 12–14, **15, 105–106**
 MFHT packet, 122–126, **122, 124, 125, 126, 127**
 of MIMO/SDM, 36
- DCF, 228
 DCF inter-frame space. *See* DIFS
 degradation. *See* issues
 DIFS, 230
 direct sequence spread spectrum physical layer. *See* DSSS
 disassociation, 226
 distributed coordination function. *See* DCF
 distribution system. *See* DS
 Doppler model
 802.11ac channel models, 46, 402
 802.11n channel models, **44, 45–46, 46**
- DS, 6, 7, 225
 DSSS, 5, **5**
 duplicate
 detection, 233
 HT format, 116–119, **117, 118**
 VHS format, 305–306, 314–315
- duration/ID field, 321
- EDCA, 236–241, **237, 239**
 EIFS, 236, **236, 240, 443**. *See also* NAV, RTS/CTS frame exchange
- encoding process
 LDPC, **165, 166–176, 167, 168, 169, 173, 174**
 MFHT packet, 88–92, **92, 93–95, 95**
 STBC, 152–164, **154, 156, 157, 158, 158, 160, 161, 162, 163**
 VHT preamble, 200–212, **201, 202, 204, 208, 209**
- enhanced distributed channel access. *See* EDCA
 Enhanced Wireless Consortium. *See* EWC
 enterprise usage model, 13–14, **14**
 ESS, 6, 7, 223–224
 Ethernet, 3, 4, 13–14
 EWC, 11
 extended channel switch announcement element, **358**
 extended inter-frame space. *See* EIFS
 extended service set. *See* ESS
- fast link adaptation
 and transmit beamforming, 386–387
 MCS feedback, 440–444, **441**
- FCC, 1
 FCS field, 327
 feedback. *See also* NDP sounding, channel sounding
 comparison between implicit and explicit, 416–417
 compressed beamforming weights, 388–392, **392**
 explicit, 386, 413–416, **415, 416**
 implicit, 382–386, **382, 410–413, 411, 412, 413**
 MCS in fast link adaptation, 442–444
 non-compressed beamforming weights, 387
 uses for CSI, 386–387
- FHSS, 4
 five criteria form, 8
 forty MHz intolerant bit, 298–299
 fragmentation
 802.11 transmission, 232–233, **233, 266**
 VHT, 439
- frame body field, 327
 frame check sequence field. *See* FCS field
 frame control field, 317–321, **318, 319, 320**
 frame format
 ACK, 231–234, **232, 234**
 association/reassociation request/response, 337–338
 beacon, 244–246, 337
 MAC, 317–342, **318, 319, 320, 323, 324, 325, 326, 327, 331, 340, 341, 342, 346, 357, 358**
 probe request/response, 338–339
 VHT, 335, **335**
- frequency hopped spread spectrum physical layer. *See* FHSS
 full state block acknowledgement, 265–266
- GI, 28, 136–140, **138, 139, 140, 186, 190, 194, 195, 443**. *See also* data rate
- GO, 7
 goodput, 9
 Greenfield preamble
 and STBC, 164
 compared to MF preamble, 127–130, **128**
 format auto-detection in, 134–136, **135**
 in 802.11n amendment development, 16, 127–128
 issues with, 130–134, **132, 133**
 protection mechanisms in, 309
- group owner. *See* GO
 guard interval. *See* GI
- handheld devices, 11, 130, 243–244
 HCCA, 274–277, **276, 443**. *See also* PCF
 hidden node problem, 234–236, **236**
 high throughput amendment. *See also* MFHT packet,
 802.11n amendment
 40 MHz channel expansion, 105–106
 40 MHz data encoding, 113–116

- high throughput amendment (cont.)
 channel design, 108
 coexistence with legacy in the PHYs, 119
 MCS 32 duplicate format, 116–119, **117**, **118**
 MF preamble, 108–113, **109**, **110**, **112**, **113**, **114**
 performance improvement with, 120–121
 spectral mask, **106**, **107**, 246
 subcarrier design, 106, **106**, 121, **122**
- High Throughput Study Group. *See* HTSG
- High Throughput Task Group. *See* TGN
- hotspots, 1, 14, **15**
- HT capabilities element, 344–350, 410
- HT control field, 324–327, **324**, **325**, **326**, **327**, **328**,
331, **332**
- HT operation element, 350, **358**
- HT STA. *See* 802.11n amendment
- HT-LTF, 86–88, **87**
- HT-SIG, 7–8, 82–84, **82**, **84**, **85**, 97–98
- HT-STF, 85–86, **86**, 194–195
- hybrid coordination function controlled channel access. *See*
 HCCA
- IBSS, 6, 7, 223
- IEEE standards. *See* 802.11 standard
- impairments. *See* issues
- impulse response, 39–42
- independent BSS. *See* IBSS
- indoor environments
 802.11n channel models, 38–49
 and transmit beamforming, 370–381, **371**, **373**, **374**, **375**,
377, **378**, **380**, **381**
- industrial scientific and medical radio bands. *See* ISM radio
 bands
- infrared physical layer. *See* IR
- infrastructure BSS, 6, 7, 223
- interleaver permutations encoding
 in SU VHT, 205–207, **205**, **206**
 MFHT packet, 90–91
- inter-symbol interference. *See* ISI
- intolerant channel report element, 354, **358**
- IR, 4
- ISI, 28
- ISM radio bands, 1
- issues
 Greenfield preamble, 130–134, **131**, **132**, **133**, **134**
 HCCA, 277
 hidden node problem, 234–236, **236**
 in 40 MHz channel, 105
 in 802.11 transmission, 47–49, **47**, **48**, 235, **235**
 in ML estimation, 55
 OFDM, 29–31
 PCF, **272**, 273–274, **273**
 SM power save, 246
 transmit beamforming, 399–406, **401**, **402**, **403**, **405**, **407**,
408, **409**
- key distribution, 227
- LDPC. *See also* transmit beamforming, STBC, spatial
 expansion encoding, receiver diversity
 and BCC, 175–176, **175**, **176**
 encoding process, **165**, 166–176, **167**, **168**, **169**, **173**, **174**
 in SU VHT, 207–209, **209**
- legacy devices, 10, 75–79, 127–134, 311
- limitations. *See* issues
- linear receiver design, **50**, 51–53, 443. *See also* ML
 estimation
- LLC, 3, 4, 222, 242, 254
- logical link control. *See* LLC
- low density parity check coding. *See* LDPC
- L-SIG TXOP, 311–314, **313**, **315**
- LTF. *See also* STF
 MF packet, 65–68, **67**
 non-VHT, 187
 VHT, 195–198, **197**, 431
- MAC 802.11
 basics, 222–223, **222**
 BSS, 223–227, **223**
 channel access timing, 229–231, **229**, **229**, **231**, 271–274,
272, **273**
 CSMA/CA, 228
 data transmission, 231–234, **232**, **233**, **234**
 interoperability, 294–300, **294**, **295**
 power management, 243–247
 protection mechanisms, 306–316, **310**, **311**, **312**, **313**, **315**
 throughput enhancements, 250–270, **250**, **252**, **253**, **254**,
256, **260**, **263**, **264**, **265**, **267**, **268**, **269**, **270**
- MAC 802.11ac
 aggregation, 251–253, **254**
 BSS, 293, 300
 enhancements, 17, 182
 MU-MIMO, **437**
 PPDU, 258–259
 VHT station capabilities, 286
- MAC 802.11e
 block acknowledgement, 241–243, **243**
 channel access timing, 236–241, **237**, **239**,
 274–277, **276**
- MAC 802.11n
 BSS, 12–14, 287–300, **290**, **292**, **302**
 channel access timing, **240**, 277–283, **278**, **279**,
280, **282**
 enhancements, 250–270, **250**, **252**, **253**, **254**, **255**, **256**,
260, **263**, **267**, **268**, **269**, **270**
 station capabilities, 286
- MAC frame format
 control, 327, **333**, **335**, **337**, **339**, **346**, **357**, **358**
 data, 336, **358**
 general, 317–327, **318**, **319**, **320**, **323**, **324**, **325**, **326**, **327**,
328, **331**, **332**
 in transmit beamforming, 406–416, **409**, **411**, **412**, **413**,
415, **416**
 management, **340**, **341**, **342**, **358**
- MAC protocol data unit. *See* MPDU aggregation

- management frame fields, 342–355, **343, 344, 345, 346, 347, 349, 350, 351, 352, 358**
- maximal-ratio combining. *See* MRC
- maximum likelihood estimation. *See* ML estimation
- MCS tables
- 20 MHz, **103, 104**, 120–121, **141, 142, 143, 377, 420, 421**
 - 40 MHz, **117, 144, 145, 422, 423**
 - duplicate format, 116–119, **117, 118**
 - fast link adaptation, **441**
 - spatial stream and data rate for MFHT packet, 122–126, **122, 124, 125, 126, 127**
 - transmit beamforming, 376–378, **377, 378**
 - unequal, **420, 421, 422, 423**
 - VHT, 212–216, **212, 213, 214, 215, 216**
- medium access control layer. *See* MAC frame format
- MF data field, 69–70
- MF long training field. *See* LTF
- MF packet. *See also* 802.11a amendment
- encoding process, 70–72
 - receiver procedure, **73**, 96–102
 - structure basics, 62–75, **63, 64, 65, 66, 67, 68, 69, 71, 73**
- MF preamble
- 20 MHz MCS tables, **103, 104**
 - 40 MHz MCS tables, **109, 110, 114**
 - compared to Greenfield preamble, 127–130, **128, 130, 131**
 - in 802.11a amendment, 62–75, **75**
 - in 802.11n amendment, 75–102, **75**
- MF signal field. *See* SIG
- MFHT data field, 88–95, **89, 90, 92, 95**, 100–101
- MFHT packet. *See also* 802.11n amendment, high throughput amendment
- and STBC, 161–164, **163**
 - cyclic shifts, 76–77, **77, 78, 86**
 - data field, 88–95, **89, 90, 92, 95**
 - HT-LTF, 86–88, **87**
 - HT-SIG, 82–84, **82, 84, 85**, 97–98
 - HT-STF, 85–86, **86**, 194–195
 - legacy compatibility, 77–79, **79, 85, 97**
 - non-HT LTF, 80
 - non-HT SIG, 80–81, **81**
 - non-HT STF, 194–195
 - structure basics, 74, **75**
- MFHT receiver procedure, 96–102, **96**
- MIMO
- basics, 32–34, **33**
 - channel models, 8
 - data rate in high throughput, 122–126, **122, 124, 125, 126, 127**
 - fading multipath channel in, 36–38, **37, 38**
 - history of, 2
 - receiver diversity, 147–152, **148, 149, 150, 151**
 - transmit beamforming, 370, **371**
- MIMO/SDM system
- equalizer, 36
 - equation, 35
 - mixed format. *See* MF packet
 - mixed format high throughput. *See* MFHT packet
 - ML estimation, 54–55, 443. *See also* linear receiver design models
 - channel, 8, 38–49, **39, 40, 41, 44, 46, 47, 49, 51, 57, 58, 59, 60**
 - fading multipath, 36–38, **37, 38**
 - usage, 12–14, **13, 14, 15, 18**
 - modulation and coding scheme. *See* MCS tables
 - modulation mapping encoding
 - in SU VHT, **207, 208**
 - MFHT packet, 91
 - MPDU aggregation
 - in 802.11ac amendment, 258–259
 - in 802.11n amendment, 255–257, **256**
 - MRC. *See also* receiver diversity
 - compared to STBC, 153–156, **154, 156**
 - MIMO basics, 34
 - MSDU aggregation, 254–255, **254, 255**
 - multiple-input-multiple-output concept. *See* MIMO
 - multi-TID BA frame format, 334, **337, 346, 357, 358**
 - multi-TID BAR frame format, 332
 - MU-MIMO. *See also* MIMO
 - advantages of over MIMO/SDM system, 424–426, **425**
 - data field encoding, 432–435, **436**
 - MAC, 436–437, **437**
 - packet structure, 429–432, **429, 430, 432**
 - pre-coding, 426–427
 - receiver design, 427–428, **429**
 - sounding protocol, 438–439, **438**
 - NAV, 271, 306, 307–309, 314–315, 335, 443. *See also* EIFS, RTS/CTS frame exchange
 - NDP sounding, 415–416, **416**, 438–439, 443. *See also* channel sounding, feedback
 - network allocation vector. *See* NAV
 - network architecture. *See* BSS
 - nine functional requirements of TGn, 9
 - non-HT LTF, 80
 - non-HT SIG, 80–81, **81**
 - non-HT STF, 194–195
 - null data packet. *See* NDP sounding
 - OFDM
 - 802.11 PHYs, 4–5, **5**
 - 802.11a amendment, 27–29, **29, 30**
 - legacy compatibility in 802.11n amendment, 76–81
 - operation element, 287–288
 - orthogonal frequency division multiplexing. *See* OFDM
 - overlapping BSS scan parameters element, 355, **358**
 - P2P group, 223
 - PA, 47–49
 - PAR, 7–8
 - parity check matrices, 177–181, **178**
 - PAS, 43
 - path loss models, 50–51
 - PCF, 271–274. *See also* HCCA

- PCF inter-frame space. *See* PIFS
- PCO, 443. *See also* coexistence with legacy
- peer-to-peer group. *See* P2P group
- PER, 440
- performance
- capacity curves, **37, 38, 53**
 - enhancements to 802.11n amendment, 147–181, **178**
 - high throughput amendment, 120–121
 - MIMO, 38
 - receiver diversity, 136–140, 149–152, **149, 150, 151**
 - transmit beamforming, 393–406, **393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 405, 407, 408, 409**
- phase noise
- in 802.11n channel model, 47, **47**
 - in OFDM devices, 30–31
- phased coexistence operation. *See* PCO
- PHYs
- 802.11 standard, 4–5, **4, 5, 12, 16**
 - 802.11ac amendment, 19–20, **20**
 - 802.11n amendment, 10, 14–16, **16**
 - Greenfield preamble, 130, **130, 131**
 - HT station capabilities, 284–285, **346, 347, 349, 350, 351, 352, 358**
 - MF preamble, 62–75
 - VHT MU-MIMO, 429–435, **429, 430, 432**
 - VHT station capabilities, 285
- physical layers. *See* PHYs
- PIFS, 230
- pilot subcarriers encoding
- MFHT packet, 91–92, **92**
 - SU VHT, 209–212, **210**
- point coordinator function. *See* PCF
- power amplifier. *See* PA
- power angular spectrum formulation. *See* PAS
- power management, 243–247, 443. *See also* PSMP
- power-save multi-poll. *See* PSMP
- PPDU
- 40 MHz, 285, 289, 301, 302
 - HT, 235, 254, 257
 - in channel sounding, 408–409, **409, 410–413, 411, 412, 413**
 - VHT, 258–259, 279
- probe request/response frame format, 338–339
- project authorization request form. *See* PAR
- propagation models. *See* channel models, path loss models
- protection mechanisms
- 802.11b amendment, 307
 - 802.11g amendment, 307–308, 310–311, **312**
 - Greenfield preamble, 309
 - in HT and VHT transmissions, 306–307
 - L-SIG TXOP, 311–314, **313, 315**
 - RTS/CTS frame exchange, **236, 303, 309–311, 310, 311**
 - with legacy stations present, 306–309
- protocol data unit. *See* PPDU
- PS mode, 244–246, **246, 443**. *See also* beacon
- PSDU aggregation, 257–258, **258**
- PSMP, **280, 282, 443**. *See also* power management
- PS-poll frame format, 334
- QoS
- 802.11 MAC, 223–227, **223, 225**
 - 802.11e amendment, 240–241
 - control field, 322–324, **323**
 - quality of service. *See* QoS
- radio band
- 2.4 GHz, 291–293, **292, 295–298, 295**
 - 5 GHz, 4–5, 9, 290, **290, 294, 294, 300**
 - and 802.11ac amendment, 17–18, 19
 - and 802.11n amendment, 15–17
 - channel allocation, **141, 142, 143, 182–183, 183, 184**
- random backoff time, 230–231, **231**
- reassociation, 226
- receiver design
- MU-MIMO, 427–428, **429**
 - transmit beamforming, 378–379
- receiver diversity. *See also* LDPC, transmit beamforming, STBC, spatial expansion encoding, MRC
- basics, **148**
 - performance improvement with, 136–140, 149–152, **149, 150, 151**
 - selection diversity in, **153**
 - SU VHT, **214, 215, 216**
- reduced interframe space. *See* RIFS
- residential usage model, 13, **13**
- reverse direction protocol, 277–280, **278, 279**
- RIFS, 443. *See also* SIFS
- robustness
- in MIMO system, 34
 - of 802.11n design, 15
- RTS frame format, 327, **333, 335**
- RTS/CTS frame exchange, 235–236, 303–304, 309–311, 443. *See also* EIFS, NAV
- scanning, 224
- SDM
- basics, 34–36, **34, 35**
 - in high throughput, 122–126
- sequence control field, 321
- SF
- non-VHT, 187–191, **189, 190**
 - VHT (field A), 191–194, **192**
 - VHT (field B), 198–200, **199, 202–203, 202**
- short interframe space, 443. *See* SIFS
- SIFS, 15, 229, **229, 443**. *See also* RIFS
- SIG
- MF packet, 68–69, **68, 69**
 - VHT, 430–431, **430, 432, 435, 436**
- signal-to-noise ratio. *See* SNR
- single antenna devices. *See* handheld devices

- single carrier modulation, 29–31, **30**, 443. *See also* SISO
- single user very high throughput. *See* SU VHT
- single-input single-output. *See* SISO
- singular value decomposition. *See* SVD
- SISO, 443. *See also* single carrier modulation
- SISO
- basics, 32, **33**
 - compared to MIMO, **38**, 246
 - slot time, 230
 - SM power save, 246
 - SNR, 370–375, **373**, **374**, **375**
 - space-time block coding. *See* STBC
 - spatial division multiplexing. *See* SDM
 - spatial expansion encoding. *See also* LDPC, receiver diversity, STBC
 - adding robustness to MIMO systems, 152, **154**
 - MFHT packet, 93–95, **95**
 - STBC, 15, 19, 152–164, 443. *See also* antenna correlation, transmit beamforming, spatial expansion encoding, receiver diversity, LDPC
 - STF. *See also* LTF
 - MF packet, 62–65, **63**, **65**, **66**
 - non-VHT, 187
 - VHT, 62–65, **193**, **194**, **195**, 431
 - stream parsing encoding
 - 40 MHz, 115–116
 - MFHT packet, **90**, 204–205
 - SU VHT, **203**, 204–205
 - SU VHT
 - 802.11ac packet structure, 184–185, **184**
 - interleaver permutations encoding, 205–207, **205**, **206**
 - LDPC, 207–209, **209**
 - modulation mapping encoding, 207, **208**
 - pilot subcarriers encoding, 209–212, **210**
 - receiver diversity, **214**, **215**, **216**
 - stream parsing encoding, 204–205, **204**
 - subcarrier grouping, 402–403, **402**, **403**
 - SVD, 366–370, 372–375, **373**, **374**, **375**
- tap spacing. *See* impulse response
- TGn, 7–10
- TGn Sync proposal, 10
- throughput. *See also* aggregation, block acknowledgement protocol
- throughput
 - and handheld Wi-Fi devices, 11
 - comparison criteria of TGn, **120**
 - definition of, 8
 - MAC, 250–251, **250**, **252**, **253**, **254**, 258–259
 - receive diversity, **151**
- TIM, 244
- traffic indication map. *See* TIM
- transmission. *See also* TXOP
 - MIMO in 802.11n, 231–234, **232**, **233**
 - MU in 802.11ac, 182, 432–435, **432**
 - SISO in 802.11n, 32, **33**
 - SU in 802.11ac, 184–185, **184**
 - with STBC, 152–164, **154**, **156**, **157**, **158**, **160**, **161**, **162**, **163**
- transmit beamforming. *See also* 802.11n amendment, STBC, receiver diversity, LDPC
 - advantages of, 365–366, **366**, **367**
 - and fast link adaptation, 386–387
 - CSI, 379–392, **380**, **381**, **382**, **392**, 413–416, **415**, **416**
 - in indoor environments, 370–381, **371**, **373**, **374**, **375**, **377**, **378**, **380**, **381**
 - MIMO basics, 32–34
 - MU-MIMO, 435, 437–438
 - performance, 393–406, **393**, **394**, **395**, **396**, **397**, **398**, **399**, **400**, **401**, **402**, **403**
 - receiver design, 378–379
 - SVD, 366–370
 - unequal MCS in, 376–378, **377**, **378**
- transmit opportunity. *See* TXOP
- transmit waveform generator, 12, 19
- TXOP, **236**, 238, **238**, 240, 243, 311–314, **313**, **315**, 443. *See also* transmission
- United States Federal Communications Commission. *See* FCC usage models
 - in 802.11ac amendment, 18
 - in 802.11n amendment, 12–14, **13**, **14**, **15**
- Very High Throughput task group. *See* VHT
- VHT
 - MU-MIMO, 429–435, **429**, **430**, **432**
 - PPDU, 258–259, 279
 - protection mechanisms in, 306–307
 - SIG, 430–431, **430**, 432, **432**, 435, **436**
 - station capability, 285
 - SU, 209–212, **214**, **215**, **216**
 - VHT beamforming report poll frame format, 336
 - VHT NDP announcement frame format, 335
 - VHT packet structure. *See* 802.11ac packet structure
 - VHT preamble. *See also* 802.11ac packet structure
 - basics, 184–185, **185**
 - data field encoding, 200–212, **201**, **202**, **204**, **208**, **209**
 - non-VHT portion, 185–191, **186**, **189**, **190**
 - VHT portion, 191–200, **192**, **193**, **194**, **195**, **197**, **199**
 - VHT-SIG-A, 191–194, **192**
 - VHT-SIG-B, 198–200, **199**
 - virtual private network. *See* VPN
 - voice over IP. *See* VoIP
 - VoIP, 13, 14, 130
 - VPN, 2
- WFA, 1, 2–3, 6, 24, 223
- Wi-Fi
 - handheld devices, 11, 130, 243–244
 - network, 11

WFA, 1, 2–3, 6, 18, 223

Wi-Fi Alliance. *See* WFA

Wi-Fi Direct network, 7

wireless Ethernet. *See* 802.11 standard

wireless local area networking. *See* WLAN

WLAN

and transmit beamforming, 365–366

cost of devices, 2

history of, 1–3, 2

WWiSE proposal, 10