

## Contents

<i>Foreword by Dr. Andrew Myles</i>	<i>page xv</i>
<i>Preface to the first edition</i>	xix
<i>Preface to the second edition</i>	xxi
<i>List of abbreviations</i>	xxii
<b>Chapter 1 Introduction</b>	<b>1</b>
1.1 An overview of IEEE 802.11	3
1.1.1 The 802.11 MAC	3
1.1.2 The 802.11 PHYs	4
1.1.3 The 802.11 network architecture	6
1.1.4 Wi-Fi Direct	6
1.2 History of high throughput and 802.11n	7
1.2.1 The High Throughput Study Group	7
1.2.2 Formation of the High Throughput Task Group (TGn)	8
1.2.3 Call for proposals	10
1.2.4 Handheld devices	11
1.2.5 Merging of proposals	11
1.2.6 802.11n amendment drafts	11
1.3 Environments and applications for 802.11n	12
1.4 Major features of 802.11n	14
1.5 History of Very High Throughput and 802.11ac	17
1.6 Outline of chapters	20
References	22
<b>Part I Physical layer</b>	<b>25</b>
<b>Chapter 2 Orthogonal frequency division multiplexing</b>	<b>27</b>
2.1 Background	27
2.2 Comparison to single carrier modulation	29
References	31

<b>Chapter 3</b>	<b>MIMO/SDM basics</b>	32
3.1	SISO (802.11a/g) background	32
3.2	MIMO basics	32
3.3	SDM basics	34
3.4	MIMO environment	36
3.5	802.11n and 802.11ac propagation model	38
3.5.1	Impulse response	39
3.5.2	Antenna correlation	42
3.5.3	802.11n Doppler model	45
3.5.4	802.11ac Doppler model	46
3.5.5	Physical layer impairments	47
3.5.6	Path loss	50
3.6	Linear receiver design	51
3.7	Maximum likelihood estimation	54
	References	56
	Appendix 3.1 802.11n channel models	57
<b>Chapter 4</b>	<b>PHY interoperability with 11a/g legacy OFDM devices</b>	62
4.1	11a packet structure review	62
4.1.1	Short Training field	62
4.1.2	Long Training field	65
4.1.3	Signal field	68
4.1.4	Data field	69
4.1.5	Packet encoding process	70
4.1.6	Receive procedure	72
4.2	Mixed format high throughput packet structure	74
4.2.1	Non-HT portion of the MF preamble	75
4.2.2	HT portion of the MF preamble	81
4.2.3	Data field	88
4.2.4	HT MF receive procedure	96
	References	102
	Appendix 4.1 20 MHz basic MCS tables	103
<b>Chapter 5</b>	<b>High throughput</b>	105
5.1	40 MHz channel	105
5.1.1	40 MHz subcarrier design and spectral mask	106
5.1.2	40 MHz channel design	108
5.1.3	40 MHz mixed format preamble	108
5.1.4	40 MHz data encoding	113
5.1.5	MCS 32: high throughput duplicate format	116
5.1.6	20/40 MHz coexistence with legacy in the PHY	119
5.1.7	Performance improvement with 40 MHz	120

5.2	20 MHz enhancements: additional data subcarriers	121
5.3	MCS enhancements: spatial streams and code rate	122
5.4	Greenfield (GF) preamble	127
5.4.1	Format of the GF preamble	128
5.4.2	PHY efficiency	130
5.4.3	Issues with GF	130
5.4.4	Preamble auto-detection	134
5.5	Short guard interval	136
	References	140
Appendix 5.1	Channel allocation	141
Appendix 5.2	40 MHz basic MCS tables	141
Appendix 5.3	Physical layer waveform parameters	146
<b>Chapter 6</b>	<b>Robust performance</b>	<b>147</b>
6.1	Receive diversity	147
6.1.1	Maximal ratio combining basics	148
6.1.2	MIMO performance improvement with receive diversity	149
6.1.3	Selection diversity	152
6.2	Spatial expansion	152
6.3	Space-time block coding	152
6.3.1	Alamouti scheme background	153
6.3.2	Additional STBC antenna configurations	156
6.3.3	STBC receiver and equalization	159
6.3.4	Transmission and packet encoding process with STBC	161
6.4	Low density parity check codes	164
6.4.1	LDPC encoding process	165
6.4.2	Effective code rate	175
6.4.3	LDPC coding gain	176
	References	177
Appendix 6.1	Parity check matrices	177
<b>Chapter 7</b>	<b>Very High Throughput PHY</b>	<b>182</b>
7.1	Channelization	182
7.2	Single user (SU) VHT packet structure	184
7.3	VHT format preamble	185
7.3.1	Non-VHT portion of the VHT format preamble	185
7.3.2	VHT portion of the VHT format preamble	191
7.3.3	VHT data field	200
7.4	Modulation coding scheme	212
	References	217

<b>Part II Medium access control layer</b>	219
<b>Chapter 8 Medium access control</b>	221
8.1 Protocol layering	222
8.2 Finding, joining, and leaving a BSS	223
8.2.1 Beacons	223
8.2.2 Scanning	224
8.2.3 Authentication	224
8.2.4 Association	225
8.2.5 Reassociation	226
8.2.6 Disassociation	226
8.2.7 802.1X Authentication	226
8.2.8 Key distribution	227
8.3 Distributed channel access	228
8.3.1 Basic channel access timing	229
8.4 Data/ACK frame exchange	231
8.4.1 Fragmentation	232
8.4.2 Duplicate detection	233
8.4.3 Data/ACK sequence overhead and fairness	234
8.5 Hidden node problem	234
8.5.1 Network allocation vector (NAV)	235
8.5.2 EIFS	236
8.6 Enhanced distributed channel access	236
8.6.1 Transmit opportunity	238
8.6.2 Channel access timing with EDCA	239
8.6.3 EDCA access parameters	239
8.6.4 EIFS revisited	240
8.6.5 Collision detect	240
8.6.6 QoS Data frame	241
8.7 Block acknowledgement	241
8.7.1 Block data frame exchange	243
8.8 Power management	243
8.8.1 AP TIM transmissions	244
8.8.2 PS mode operation	244
8.8.3 WNM-Sleep	246
8.8.4 SM power save	246
8.8.5 Operating Mode Notification	246
References	247
<b>Chapter 9 MAC throughput enhancements</b>	248
9.1 Reasons for change	248
9.1.1 Throughput without MAC changes	248

9.1.2	MAC throughput enhancements	250
9.1.3	Throughput with MAC efficiency enhancements	251
9.2	Aggregation	253
9.2.1	Aggregate MSDU (A-MSDU)	254
9.2.2	Aggregate MPDU (A-MPDU)	255
9.2.3	Aggregate PSDU (A-PSDU)	257
9.2.4	A-MPDU in VHT PPDU	258
9.2.5	VHT single MPDU	259
9.3	Block acknowledgement	259
9.3.1	Immediate and delayed block ack	259
9.3.2	Block ack session initiation	260
9.3.3	Block ack session data transfer	261
9.3.4	Block ack session tear down	262
9.3.5	Normal ack policy in a non-aggregate	262
9.3.6	Reorder buffer operation	263
9.4	HT-immediate block ack	264
9.4.1	Normal Ack policy in an aggregate	264
9.4.2	Compressed block ack	265
9.4.3	Full state and partial state block ack	265
9.4.4	HT-immediate block ack TXOP sequences	269
9.5	HT-delayed block ack	269
9.5.1	HT-delayed block ack TXOP sequences	270
	References	270
 <b>Chapter 10 Advanced channel access techniques</b>		 271
10.1	PCF	271
10.1.1	Establishing the CFP	271
10.1.2	NAV during the CFP	272
10.1.3	Data transfer during the CFP	272
10.1.4	PCF limitations	273
10.2	HCCA	274
10.2.1	Traffic streams	274
10.2.2	Controlled access phases	276
10.2.3	Polled TXOP	276
10.2.4	TXOP requests	277
10.2.5	Use of RTS/CTS	277
10.2.6	HCCA limitations	277
10.3	Reverse direction protocol	277
10.3.1	Reverse direction frame exchange	278
10.3.2	Reverse direction rules	279
10.3.3	Error recovery	279
10.4	PSMP	280
10.4.1	PSMP recovery	281

10.4.2	PSMP burst	281
10.4.3	Resource allocation	282
10.4.4	Block ack usage under PSMP	283
	References	283
<b>Chapter 11 Interoperability and coexistence</b>		<b>284</b>
11.1	Station capabilities and operation	284
11.1.1	HT station PHY capabilities	285
11.1.2	VHT station PHY capabilities	285
11.1.3	HT station MAC capabilities	286
11.1.4	VHT station MAC capabilities	286
11.1.5	Advanced capabilities	286
11.2	BSS operation	287
11.2.1	Beacon transmission	288
11.2.2	20 MHz BSS operation	289
11.2.3	20/40 MHz HT BSS operation	289
11.2.4	VHT BSS operation	293
11.2.5	OBSS scanning requirements	294
11.2.6	Signaling 40 MHz intolerance	298
11.2.7	Channel management at the AP	299
11.2.8	Establishing a VHT BSS in the 5 GHz band	300
11.3	A summary of fields controlling 40 MHz operation	300
11.4	Channel access in wider channels	301
11.4.1	Overlapping BSSs	302
11.4.2	Wide channel access using RTS/CTS	303
11.4.3	TXOP rules for wide channel access	304
11.4.4	Clear channel assessment	304
11.4.5	NAV assertion in an HT and VHT BSS	306
11.5	Protection	306
11.5.1	Protection with 802.11b stations present	307
11.5.2	Protection with 802.11g or 802.11a stations present	307
11.5.3	Protection for OBSS legacy stations	308
11.5.4	RIFS burst protection	308
11.5.5	HT Greenfield format protection	309
11.5.6	RTS/CTS protection	309
11.5.7	CTS-to-Self protection	310
11.5.8	Protection using a non-HT, HT mixed, or VHT PPDU with non-HT response	311
11.5.9	Non-HT station deferral with HT mixed and VHT format PPDUs	311
11.5.10	L-SIG TXOP protection	312

11.6	Phased coexistence operation (PCO)	314
11.6.1	Basic operation	314
11.6.2	Minimizing real-time disruption	315
References		316
 <b>Chapter 12 MAC frame formats</b>		317
12.1	General frame format	317
12.1.1	Frame Control field	317
12.1.2	Duration/ID field	321
12.1.3	Address fields	321
12.1.4	Sequence Control field	321
12.1.5	QoS Control field	322
12.1.6	HT Control field	324
12.1.7	Frame Body field	327
12.1.8	FCS field	327
12.2	Format of individual frame types	327
12.2.1	Control frames	327
12.2.2	Data frames	336
12.2.3	Management frames	337
12.3	Management frame fields	342
12.3.1	Fields that are not information elements	344
12.3.2	Information elements	344
References		361
 <b>Part III Transmit beamforming, multi-user MIMO, and fast link adaptation</b>		363
 <b>Chapter 13 Transmit beamforming</b>		365
13.1	Singular value decomposition	366
13.2	Transmit beamforming with SVD	369
13.3	Eigenvalue analysis	370
13.4	Unequal MCS	376
13.5	Receiver design	378
13.6	Channel sounding	379
13.7	Channel state information feedback	381
13.7.1	Implicit feedback	382
13.7.2	Explicit feedback	386
13.8	Improved performance with transmit beamforming	393
13.9	Degradations	399
13.10	MAC considerations	406
13.10.1	Sounding PPDU	407
13.10.2	Implicit feedback beamforming	410
13.10.3	Explicit feedback beamforming	413

13.11	Comparison between implicit and explicit	416
13.12	Transmit beamforming in 802.11ac	417
13.12.1	VHT sounding protocol	418
	References	419
Appendix 13.1	Unequal MCS for 802.11n	420
	Unequal MCS for 20 MHz	420
	Unequal MCS for 40 MHz	422
<b>Chapter 14</b>	<b>Multi-user MIMO</b>	<b>424</b>
14.1	MU-MIMO pre-coding	426
14.2	Receiver design	427
14.3	PHY considerations	428
14.3.1	VHT MU preamble	430
14.3.2	VHT MU data field	432
14.3.3	Compressed beamforming matrices	435
14.4	Group ID	435
14.4.1	Receive operation	435
14.4.2	Group ID management	435
14.5	MAC support for MU-MIMO	436
14.5.1	MU aggregation	436
14.5.2	MU acknowledgements	437
14.5.3	EDCA TXOPs for MU sequences	437
14.5.4	TXOP sharing	438
14.6	VHT sounding protocol for MU-MIMO	438
14.6.1	The basic sounding exchange	438
14.6.2	Support for fragmentation	439
	References	439
<b>Chapter 15</b>	<b>Fast link adaption</b>	<b>440</b>
15.1	MCS feedback	441
15.2	MCS feedback mechanisms	442
15.3	MCS feedback using the HT variant HT Control field	442
15.4	MCS feedback using the VHT variant HT Control field	443
	<i>Index</i>	445