

Index

- A-60 Lightship, simple external support system, 173
- A-60s
 - benefitting from presence of a light headwind, 334
 - compared to CargoLifter CL 160, 307
- A-150s, benefitting from presence of a light headwind, 334
- AAI Corporation, 472
- abnormal convective activity, 151
- Absolute Temperature, 392
- AC electrical generation system, in *SkyCat 20*, 470
- acceleration
 - capabilities, 672
 - load factors, 154
 - scaling for an airship, 324
- access
 - to airship’s life-support systems at all times, 289
 - gaining to underside of structure, 313
 - as a generic operational GH problem, 288–289
 - and maintenance requirements, 216, 219
 - space for engine bay, 222
 - to various parts of an airship, 253–254
- access steps (*Himmelstreppe*), into the crew/passenger accommodation, 320
- accidental overload, 164
- accidents, weather frequently reported as a major cause of airship, 328
- ACLS. *See* air cushion landing system (ACLS)
- actinic degradation, 126, 128
- active exchange sequence, 657, 658
- active load exchange system, 655
- active load frame, 650, 654–659
- activity factors, for aircraft propellers, 97
- actuator disc, 87–91
- actuator power, 227
- actuators, weight estimate for, 228
- added mass, 35
- additives, blending in adhesive system, 122
- adhesives
 - interest in alternative green, 114
 - modern making joints without stitching, 168
 - polyurethane based, 455
 - properties of materials, 114
- adiabatic compression, superheating lift gas, 290
- adiabatic heating, large airships more affected by, 670
- Adler* airship (AS 80 GD), 609
- Adler fashion company, 608
- Advanced Hybrid Aircraft (AHA), 622
- advertisement
 - activities of LZ NT 07, 555
 - banner space on sides of manned airships, 580
 - Zeppelin NT qualified for, 563
- Aereon Company, triple-hull airship, 462
- Aereon Corporation, 466
- aerial advertising, as main market for hot-air airships, 604, 607
- aerial crane, 513
- aerial exploration, by unmanned airships, 586
- aerial footage, in addition to advertising space, 581
- aerial photogrammetry, of archaeological sites, 608
- aerial vehicles, absence of rigidly-structured (1789 to 1899), 314
- Aerobatic Human Powered Airship, cycloidal propellers for, 628
- Aerocrane*
 - of All American Engineering Corporation, 22
 - concept, 477
 - rotating hybrid airship, 478
- aerodynamic assessment, of the configuration, 418
- aerodynamic considerations, for HAVs, 682
- aerodynamic control(s)
 - components, 66
 - dependence upon direct contravention of aerostatic lift, 260
 - force and movement, 66
 - inclining body axis and generating hull-lift, 432
 - lost as airspeed reduces, 374
 - not very effective at low speeds, 82
 - power, 83
 - surfaces, 65
 - of Zeppelin NT, 569

- aerodynamic data
 - first experiments collecting, 413
 - for HAVs, 681
- aerodynamic drag
 - of an airship, 2, 154
 - of the envelope, 633
 - as high, 18
 - reactions of, 269
- aerodynamic efficiency, 60
- aerodynamic force(s)
 - combating centrifugal acceleration, 39
 - divided, 25
 - function of area, 273
 - as functions of the perturbation variables, 65
 - large ships needing a serious amount of, 671
 - moments due to, 273
 - moving airship generating, 16
 - no applied, 271
 - occurrence of, 23
- aerodynamic forces and moments
 - arising from local surface pressures, 23
 - estimation method for overall, 42–44
- aerodynamic interference, differing, 31
- aerodynamic landing techniques, 374–375
- aerodynamic lift, 469, 681
 - acting at centre of pressure, 269
 - calculating, 632
 - component of pressure normal to free stream, 25
 - enhancing, 19
 - from envelope moving through the air, 632
 - of HAV, 641
 - lost at slow speed, 642
- aerodynamic loading distribution, 44
- aerodynamic loads, 586, 675
- aerodynamic parameter estimation, 48–57
- aerodynamic pressure distributions, 154
- aerodynamic properties, estimating, 60
- aerodynamic scale parameter, 324
- aerodynamic testing
 - of human powered dirigible, 635
 - using Computational Fluid Dynamics (CFD), 636
- aerodynamics
 - aerodynamics
 - of the airship, 18–19
 - as design driver, 592–593
 - general aspects, 670–672
 - interaction with thruster aerodynamics, 666
 - scaling for an airship, 324
 - unsteady, 44–48
 - aerodynamics group, estimating lift and drag characteristics, 428
 - aerodynes, 290
 - aerofoil, producing lift and drag forces, 92
 - aerological data, wind shear predictable from forecast, 332
 - Aeron 26*, aerodynamic proof of the concept prototype, 466
 - AEROS-50* semirigid airship design, 502
- Aerostat*
 - CargoLifter CL 160, 647–668
 - conventional airship of very large dimensions, 645
 - described, 640
 - SkyLifter airship, 645–647
- aerostatic lift, 307
 - dependence of the airship, 260
 - envelope volume increasing for, 488
 - mechanism of, 9, 10
 - remaining undiminished, 306
- aerostatic parameters
 - as airship ascends, 195
 - measurement of, 613
- aerostatically enhanced helicopter, 21
- aerostatics
 - of the airship, 13–18
 - appraisal of airship, 188–207
 - basic principles of, 1
 - defined, 8
 - as design driver, 592
 - principles of, 8–13
- aerostats, classed as, 290
- AEW. *See* Airborne Early Warning (AEW) role
- aft landing gear, for Zeppelin NT, 575
- aft propulsion unit, of Zeppelin NT, 568
- aggressive solvents, 130
- aimed marketing, phase of, 451
- air
 - accelerating for most airborne vehicles, 87
 - adding or exhausting to maintain constant envelope pressure, 160
 - expelling from ballonets, 194
 - keeping within the envelope, 239
 - tapping from behind the airship’s main propellers, 162
 - trying to find the lowest level, 160
 - viscosity of, 24
- air and helium valves, control of, 228
- air ballonets, 15, 488
- air barrier, between outer envelope and gas cells, 240
- air cushion landing system (ACLS)
 - functional characteristics of, 469
 - of HAV, 469
 - for *SkyCat 20*, 470
- air dams, 245
- air density
 - measurement and accurate prediction of, 290
 - at Standard sea level, 204
- air discharge, 242
- air drag, reducing, 635
- air intakes, 240
- air jets, inefficient in terms of power needed, 275
- air lines. *See* duct(s)
- air loading, in hovering flight, 512, 645
- air mass, of unity, 522
- air pressure, at Standard sea level, 204
- air speed, increasing, 362

- air storage
 - compressed, 396–398
 - in long cylindrical tubes, 396
- air supply system, with powerful fans, 162
- air supply trunking system, 161, 242
- air supported structures (air houses), 138
- air to helium rip, in manned airships, 591
- Air Transport Association of America, 422
- air turbulence, 330, 349
- air vehicle, earliest controllable, 432
- Airboat* model, with a light pressure tube structure, 503
- Airboat* pressurized tube airship, 504
- Airborne Early Warning (AEW) role, 420, 444–445
- airborne platforms, comparisons of Zeppelin NT with other, 556
- airborne surveillance, 422, 441
- aircraft
 - developments/advances, 113
 - flying onto and off flying aircraft carriers, 321
 - flying unstable, 578
- aircraft fuselage surface finish quality, 33
- aircraft piston engine, TBO (To Be Overhauled) for, 594
- aircraft propeller, operating at near peak efficiency, 90
- aircraft standards, used in design of airship fuel systems, 247
- Aircrane, functions of, 665
- AirCruiser*, 466
- Airfloat HL* rigid airships, 512, 513
- airframe, design of, 154
- Air-FTG data, recorded in a fixed-wing aircraft, 559
- air-gap wet spinning process, 126
- AirLiF project, 557–558
- airline, formed by Count Zeppelin, 439
- airliner operations, 329
- airliners, often struck by lightning, 332
- airlines, taking air into ballonets, 218
- airport authority, operations on the airfield, 305
- airship(s)
 - aerodynamics of, 18–19
 - allowing to weathervane, 287
 - always flying, 306
 - balance or trim of, 199
 - body shape, 30
 - bounding off top of cool layer, 363
 - bringing to equilibrium by addition or removal of ballast, 235
 - categories, 314, 512
 - classical layout of, 63
 - classification of all as aircraft, 306
 - climbing as fuel is consumed, 107
 - configuring with a close-coupled support system, 173
 - as constant-lift devices, 649
 - constrained by laws of physics, 285
 - contact with risking disaster, 286
 - conventional and unconventional designs, 458
 - cruising at much lower percentage powers, 381
 - delicate structures, 286
 - descending, 196
 - in disaster relief, 692
 - drag breakdown for three, 30
 - drag of, 273
 - early, 60
 - economics of, 452–455
 - empty weight versus gross weight of, 497
 - equipped for Instrument Flying, 333
 - evacuating from a region threatened by a hurricane, 347
 - evaluation of, 429
 - flights and operational deployments over water, 307
 - flown at slightly heavier than air, 359
 - flying throughout life, 306
 - flying very small, 579
 - fully testing before entering service, 150
 - incoming captured by dropping a line from the nose, 664
 - inherent instability, 40
 - with an inner hydrogen and outer helium chamber, 506
 - landing as particularly dangerous, 258
 - landing even in light gusting conditions as a challenge, 596
 - landing horizontally, 281–282
 - largest batch production in wartime, 452
 - lining up for takeoff, 334
 - loading and moving on the ground, 320
 - loading categories, 512, 645
 - main attributes offered by, 436–437
 - measuring speed of, 596
 - methods to increase control, 256
 - modern, 1, 60
 - moving, 285–286
 - night time operations on, 213
 - operational weight of, 235
 - payload of, 379
 - peculiar costs, 454–455
 - perceived to be real future of aircraft, 449
 - piloting, 357–378
 - preserving and maintaining while moored, 308
 - principles regarding structure, 150–159
 - purpose of, 221
 - reason for keeping outside, 260
 - reducing lateral profile of, 405
 - re-evaluation of true nature of, 305–309
 - regulating gas cell superpressures, 240
 - reliance on a light gas for lift, 1
 - remaining afloat, 183
 - remaining statically level, 199
 - rising beyond pressure height, 194
 - rolling during turning manoeuvres, 359
 - scaling effects on, 668–670
 - sensitivity to atmospherically derived forces, 260
 - sizing, 386–387, 416

- airship(s) (*cont.*)
 - sizing matrix, 419, 429
 - strongly built with higher percentage empty weight, 496
 - structural categories, 13, 14
 - structural failure of, 44
 - subject to aerostatic and aerodynamic forces, 306
 - supporting weight by buoyancy at rest, 306
 - systems found on, 239
 - technology of modern, 60
 - tending to drift into a large circular path, 18
 - tolerating surface wind speeds at the mooring mast, 334
 - trimming, 236
 - types of, 1
 - unmanned, 577–600
 - updating capabilities of, 425
 - upward trend in weight of modern, 215
 - used for advertising, 250
 - using takeoff power for very short periods, 381
 - utility of different types, 431–437
 - in various weather conditions, 47
 - weather conditions for 21st century, 329–333
 - weather for bringing in or out of hangar, 333
 - weather-sensitivity of, 4, 327, 328–329
 - weight of, 384–385
- Airship Alliance, 617–618
- Airship Association, 18th Annual Symposium of, 105
- airship balance, 199–202
- airship bases, 315, 316
- airship codes, no demand for, 449
- airship constructor, attempting to market, 450
- Airship Design Criteria, 590, 634
- airship equation, applying to hybrid air vehicle, 682
- airship ferrying route, 341
- airship gravity data, qualitative analysis, 559
- airship hull. *See* hull
- Airship Industries, 370, 389, 425
- Airship No. 23 and R-26, 267
- Airship no. P6, control car showing swivelling propellers, 268
- airship operations
 - favorable weather for, 333–337
 - GH as poor cousin of, 278
 - summary of, 193–196
 - time scales optimising use of weather, 354–355
 - weights aspects of, 236–238
- airship pilots. *See* pilots
- airship solution, forced upon navies, 432
- airship specific simulators, programmes for, 281
- airship steady state analytical model, schematic of, 42
- airship structures. *See* structures
- airship system
 - defined, 193
 - weight of, 193
- airship technology, offering increased lifting capabilities, 692
- Airship Z-Prize, 691
- Airships Industries (UK) Ltd., output of, 452
- airspace, operations above 65,000 ft, 584
- airspeed, including gust effects, 15
- airtight fabric, 118
- air-to-helium sleeve, 245
- Airworthiness Requirements, for hot-air airships, 613, 614
- Akron (1931–33), 389
 - 1/40th scale wind tunnel model, 41
 - accident, 449
 - comparison of theory and experimental incremental pressure coefficients for, 41
 - fin arrangements, 51
 - fin distribution on 1/40th scale model of, 46
 - isolated hull model, 50
 - mechanical equipment devised for, 321
- ALA600 Russian airship prototype, fuelled with hydrogen, 108
- albedo, 525
- Allen, Bryan, 620
- altitude
 - as design driver, 588
 - effects of, 11
 - variation of lift with, 11
- aluminium clad Varialift airship, 499
- aluminium-fluorinated-polyurethane, 122
- ambient air temperature, 333
- American Blimp Corporation Lightship, 245, 250
- American GH System, 292, 295–296
- American low-mast method, 297
- amorphous region, of cellulose, 141
- amorphous silicon solar cells, 537
- Amundsen, Roald, 607
- anabatic (upslope) winds, 351, 352
- analytical software tools, 580
- anchor points, scarcity on fragile shell surface, 289
- anchor winches. *See also* winches
 - cables routed through heavy pulley vehicles, 658
 - deployed on site, 656
 - installing on the ground, 654
 - mounting on heavy crawler vehicles, 658
- Andrews, Stuart, 622
- angle of solar incidence, 525–527
- ANR airship, 109, 110
- antenna, 422, 423
- anthropogenic and biogenic emissions, 557
- anthropometrics, 624
- anticyclones. *See* high pressure systems
- anti-submarine warfare (ASW) role, 445
- apparent increase, in net lift, 197
- apparent mass
 - components of, 63
 - determination, 34–37
 - in place of physical mass, 36

- applications, of airship technology, 1
- applied moments, response of airship to, 273
- approach path, establishing a selected, 376
- approximate model, identifying aerodynamic stability derivatives, 77
- approximate stability modes, 75
- APUs
 - driving electrical generators, 383
 - portable to power to electrically lighted signs, 250
 - providing some power, 229
 - on the Sentinel 5000, 250
 - supplying special mission power, 250
- Aramid, abrasion resistance, 127
- Aramid family (Kevlar), for envelope fabric, 416
- arched load curtains, described, 174
- Arctic-Sky expedition, 608, 611
- ARDCO, pressure contoured fin, 220
- area control role, 441
- area plot, producing smooth longitudinal distributions, 415
- aromatic heterocyclic lyotropic polymers, 126
- Arras, Bill, 620
- AS 80GD airship, 508, 604
- AS 105 GD hot-air airship, 612
 - certification by the UK CAA, 614
 - characteristics of, 614
 - cost of, 606
 - four-seater, 608, 612, 615
 - fully certified in the passenger transport category, 604
 - ground wind limit, 606
 - instruments and switch panel, 613
 - scientific research and certification programme, 612–613
 - target definition, 611
 - technical development, 610–611
- AS 105 GD/6, accepted by EASA as a six-seater, 614
- AS-400, operating for only six months in any calendar year, 510
- Ashcroft, Jeff, 691
- assembly, raising and lowering, 652
- Association of European Airlines (A.E.A.), cost structures, 424
- astronomical platform, airship as, 490
- ASW (anti-submarine warfare) role, 445
- Atlantic, attempt to cross by Zeppy 2, 622
- atmosphere, changing properties of, 189–191
- atmospheric conditions, unsteady, 659
- atmospheric disturbances, 150, 151
- atmospheric electric activity, strong, 332
- atmospheric gases, molecular diameters, 133
- atmospheric pollution, causing reduction in direct solar radiation, 523
- atmospheric pressure height, 193
- atmospheric properties, 204, 488
- atmospheric research, airship for, 468
- atmospheric temperature, increase in, 12
- atmospheric turbulence, 269
 - conditions of severe, 44
 - control to counteract effects of, 260
 - response of an airship hull to, 47
- attenuation, of direct solar radiation, 521
- attitude perturbation, of the airship, 65
- Auto Pilot (A/P) mode, 594
- Autodesk Inventor, 637
- automatic control system, 276
- automatic docking system, 275
- automatic flight control systems, 82–83, 487
- Autonomous mode, 578
- autopilot functions, 83, 252
- autostabilisation system, during gales, 151
- auxiliary fans, needed to deliver air, 162
- auxiliary fuel capacity, 213
- auxiliary power unit, for larger airships, 106
- auxiliary thrust, 256–257
- available power, versus required power, 667
- average scalar wind, over London at 5,000 feet, 387
- aviation climatological databases, 355
- avionics, weight considerations, 230
- axes, system of, 61–63
- axial force, 63, 64
- axial velocity, for a vortex, 101
- axis of symmetry, of the envelope, 61
- axisymmetric streamline form, airships of the classical, 13
- Baciu, Dan, 505
- Bacon cell, 541
- Bain, Addison, 505
- balancing weight, adding at the nose or tail, 156
- ballast
 - adding or dumping, 150
 - for airships, 248–249
 - amount of jettisonable, 231
 - carrying additional, 181
 - classical technique of dropping, 16
 - disposing from maximum certified static heaviness to a point of equilibrium in manned airships, 591
 - dump system requiring actuation, 228
 - fuel as dumpable, 386
 - gondola requirements for, 221
 - as heaviness, 360
 - overall capacity for compensating, 150
 - picking up from surface, 231, 380
 - reasons for carrying, 230
 - recovery systems, 249
 - replenishment underway, 231
 - SkyHook not needing to carry, 644
 - suitable stowage provided for, 231
 - system allowing for weight to be added or removed, 248
 - weight, adjustment of, 290
 - weight of structure, 222
- ballast group, 230–232

- ballasting, adjusting weight of an airship, 248
- ballonet(s)
 - air replenished or removed from, 240
 - air supply rate to, 161
 - avoiding rupture of in the hangar, 161
 - benefits in having fore and aft, 202
 - configuration, 215
 - construction of, 245
 - contents, 596
 - current airships all favouring, 240
 - damper controls, 251
 - determining capacity, 240
 - difficult to determine volume, 236
 - fill required as airship descends, 196
 - as a fine trim, 202
 - flexing of, 163
 - fulness determining, 253
 - functions of in Zeppelin NT, 562
 - geodesic method of design, 246
 - inflating and deflating, 245
 - lift owing to, 392
 - locating against envelope's lower surface, 160
 - maintaining pressure, 15
 - maintaining pressure differential, 194
 - membrane, differential pressure across, 161
 - methods of constructing, 160
 - minimum of two, 245
 - nearly empty at altitude, 161
 - number of, 161, 245
 - pressure and shape control principle of, 241
 - providing change in density, 194
 - reducing volume of entrapped air within, 162
 - shape, improved design for, 245
 - from similar but lighter, thinner material, 160
 - sizing, 161, 240
 - trimming, 359
 - valves under, 244
 - weight for fabric, 217–218
 - of Zeppelin NT, 562–563
- ballonet air
 - control of distribution, 228
 - moment offsets moment of the airship, 202
 - valve details on Sentinel 1000, 243–244
- ballonet ceiling, exceeding, 256
- ballonet materials, 131
 - properties of, 114
 - testing flexural properties, 139
- ballonet slosh, 131
 - inducing loads, 131
 - preventing, 160
- ballonet trunking, envelope fabric structure, 243
- ballonet volume, 15, 196, 215
- balloneted Godschmied configuration, 490
- balloon(s)
 - anchoring the top (or crown) of, 310
 - defined according to lifting medium or purpose, 314
 - incorporating a closed flexible envelope filled with a gas, 9
 - keeping away from the fire, 310
 - with a means of propulsion, 13
 - stopping from being blown sideways, 310
- balloon ground crews, 302
- balloon inflations, scenes of serious riots, 313
- ballooning, ground handling definition from the world of, 301
- banners, attached to Zeppelin NT envelope, 563
- bare hull. *See also* hull
 - aerodynamic forces and moments on, 25–30
 - of classic streamline form as directionally unstable, 18
 - effect of additions to, 30–34
- bare hull drag, 2
 - coefficient, 34, 401
 - compared to tail drag, 32
 - conditioned by behaviour of the boundary layer, 399
 - proportion of, 399
 - reducing, 401
 - total, 401
- bare suspended weight, of an airship, 210
- bare weights
 - of airships, 209
 - for engines, 226
- barrage balloons, varying exterior shapes, 240
- base fabrics
 - coated/laminated together, 117
 - made from synthetic fibres, 118
- base loading, with a fixed terminal, 512, 645
- base requirements, minimising for CargoLifter, 649
- baseline configuration, determining initial performance capability, 429
- baseline design layout, determination of, 414–416
- baseline evaluation, 417–419
- baseline method, 413, 414
- baseline model for design, 623
- baseline parametric analysis, 418
- baseline trade-study process, 412
- basic criteria, review of, 411
- basic empty weight (BEW), 210
- basic scientific/engineering principles, of airships, 1
- basic sizing plot, forming, 429
- basic suspended empty weight (BSEW), 210
- basket weave, 115
- battens, 181
- batteries
 - characteristics of, 539
 - heavy and impractical owing to limited life, 227
 - providing emergency and start-up power, 249
 - ratio of delivered to received energy, 539
 - relationship between cost and energy storage capacity, 543
 - sizing of, 230
 - underneath floor of Zeppelin NT cabin, 574
- bedding-down techniques, 318
- Bell, Hugh, 492
- Bell Geospace Air-FTG, 559

- Bell Geospace full-tensor, gravity gradiometer (Air-FTG), 558
- bending load capability, 675
- bending loads, division between soft envelope and hard keel, 661
- bending moments
 - analysis, 634
 - combined with an equal distributed internal pressure, 674
 - computing, 674
 - defined, 164
 - determining, 166
 - in flight, 163
 - formula, 163
 - increasing seriously with size, 674
- Bernoulli's equation, 23, 89
- Betty small indoor R/C model, 513
- biaxial loading, of envelope materials, 132–133
- biaxial stress, 132
- billboard, airship hull providing a natural, 440
- bi-lobe HAV model, 682, 683
- biomechanics, 624
- Biot and Savart law, 95, 101
- Bjerknes, V. and J, 339
- blade activity factor, 97
- blade element theory, 91–93
- blade plan area, ratio to disc area, 97
- blade section, 91, 92
- blades, 94, 636
- 'Blaugas,' used in the *Graf Zeppelin*, 17
- BLC airship, 111, 402
- blimps, 149. *See also* nonrigid airships
 - ground crews, 281
 - inheritance of abandoned rigid airship sheds, 317
 - putting back into service, 318
 - reaching large sizes, 13
 - technique used for, 281
 - volume from propeller slipstream scoops, 677
- blowers, 16, 240
- boarding boat, direct interdiction by means of, 442
- boarding facilities, ensuring safe personnel transfer, 152
- Bodensee, drag breakdown, 30
- bodies-of-revolution, 415
- body
 - flying at an angle to the free stream, 25
 - slender, 40
- body axes, general configuration, 61, 62
- body forces, determination of, 37–40
- body mass, modifying, 37
- body of rotation, flying steadily at incidence, 38
- Boeing 747, compared with an airship, 153
- Boer War, observation balloons, 318
- Bolster Beam, 320
- bolt ropes, continuous, 174
- bonded joints, 121
- bonding agent, 130
- bonding fabric to a film, 133
- border patrol, 583
- Botswana, diamond exploration in, 558
- bottom laid mines, distinguishing, 445
- boundary layer
 - in the form of an axisymmetrical wake, 399
 - increasing form drag, 28
 - ingestion into a power-plant, 110
 - inhibiting growth of, 399
 - injection of momentum into, 110
 - loss of air velocity in, 24
 - separating from the surface, 24
 - thickness, 24, 399
 - transition from laminar to turbulent flow in, 399
 - 'tripping,' 54
- boundary layer control, 398–403
- boundary layer growth
 - inhibited by a negative pressure gradient, 402
 - localising, 402
 - retarding leading to a significant reduction in drag, 401
- bow, needing reinforcement, 180
- bow cap
 - holding in position, 181
 - size of, 181
 - strong desirable, 181
- bow stiffening, deformed shape of, 182
- bow thruster, 369, 471
- braced frame structures, 153
- brakes
 - airships having none, 291
 - as ineffective, 185
- braking, affecting pitch angle, 281
- Brayton cycle, for the gas turbine ICE, 104
- Brazil, first cyclone ever reported off the coast of, 346
- Brazilian Caloi (1989), 622
- break-even point, estimating, 453
- British airship efforts, classes dominating, 452
- British airships
 - little serious effort at moving on the ground, 320
 - next generation employing reversing gear, 268
- British Civil Airworthiness Requirements (BCAR), 449
- British GH System
 - flying moor, 292
 - winching down the airship, 294–295
- British high mast sequence, 297
- British Naval Airship No. 1 of 1911, ground handling, 264
- brushless dc motors, 538, 544
- brute-force method, 667
- build standard, for each gondola, 234
- build weight, 234
- buildings
 - sending off thermal plumes, 349
 - structural failure owing to atmospheric turbulence, 56
- bulkheads, weight of, 222
- bulky objects, capability of carrying, 640

- buoyancy, 192. *See also* static lift
 - adjusting prior to launch, 290
 - air density affecting, 282
 - altering, 290
 - constantly changing, 286
 - deceleration affecting, 282
 - dependent upon density of displaced fluid, 193
 - of the *HALROP*, 489
 - loss of a problem for all airships, 287
 - maintained by vectored thrust, 512, 645
 - monitoring constantly, 287
 - not easily switched off, 306
 - scaling for an airship, 324
 - techniques used to control, 16
- buoyancy control
 - in an airship, 16
 - essential, 287
 - improvements, 4
 - by lifting gas manipulation, 389–398
 - required by unmanned airships, 592
- buoyancy force, 63
 - acting on all bodies within the atmosphere, 8
 - in rectilinear flight, 61
 - static, 65
- buoyancy lift, 631–632
- buoyant craft, lift of, 26
- buoyant gas, causing internal pressure in the envelope, 673
- buoyant lift (conventional), 468, 641, 681
- Burgess, C.P., 242, 506, 596, 634
- burner unit, fan system positioned under, 508
- Burney, Dennistoun, 436
- bus bars, generator distributing power to, 249
- business case, behind CargoLifter, 647–649
- butt straps, 121, 130
- butyl, properties of, 128
- C2 links, automatic switching of, 598
- cabin
 - design studies, 222
 - of LZ N 07, 549, 564–565
 - pressurisation, 171
 - weights, 222
 - Zeppelin NT support features, 556
- cable control systems, conventional, 180
- cable failures, within the envelope, 177
- cable operation system, weight of, 227
- cables, preventing crossing from rubbing together, 176
- Cadmium Sulphide (CdS) cells, stability of, 537
- calculations, example in regard to solar power, 531–532
- calibration, role of, 441
- calibration flight, carrying out, 236
- CALOI Bicycles Co., 622
- ‘The Cambridge Paper,’ GH tasks identified in, 302
- Cameron Balloons UK, 508
 - European airship marketing venture, 617
 - selling hot-air airships in 1970s, 602
 - super-pressure airship, 602
- Cameron single-seater, 603
- Cameron twin-seater gondola, 603
- Canada
 - need for heavy lift airships, 694
 - providing transport for developing northern territories, 695
 - SkyHook’s* planned operations for remote regions of, 475
- candidate concepts, 428
- Capper, Col., 318
- capture/touch-down (landing), 290–291
- car. *See* gondola
- Carbon NanoTubes (CNT), 143
- Cardington, high mast at, 316
- cargo, economics of transporting, 693
- CargoLifter
 - bending moment for, 674
 - business case for, 647–649
 - ground handling system, 664
 - hull suspensions, 669
 - load-exchange principle of, 650
 - manoeuvring, 665–667
 - overview of, 649–650
 - reacting more in a translational movement, 671
 - size compared with the Hindenburg, 649
- CargoLifter AG*, 513
- CargoLifter CL 75 AC, 665
- CargoLifter CL 160, 659–665, 689
 - discontinued after six years of theoretical development, 647
 - final configuration of, 662–664
 - GA as envisaged in September 1998, 661
 - ground handling, 664–665
 - large underslung mass making very stiff, 662
 - main structural layout of, 514, 669
 - size limited by dimensions of hangar, 660
 - transporting humanitarian and emergency aid, 689
- CargoLifter CL 160 draft GA, 662
- CargoLifter CL 160 Super Heavy-Lift Cargo Airship, 690
- Cargon Nanotube (SWNT), properties of, 142
- carpet plot, 412, 419, 429, 430
- carpets, for passenger carrying flights, 233
- cars, separate engine or power, 170
- catastrophic propagation, in coated fabrics, 136
- Category A - No lift augmentation, 431
- Category B - Partial lift augmentation, 432
- Category C - Total lift augmentation, 432
- catenary, weight of, 218
- catenary diaphragm, external distributing stresses, 16
- catenary length, driving structural design, 674
- caterpillar tracks, 293
- ceilings, weight of, 222
- cellulose, 141
- cellulose nanocrystals
 - modification and synthesis of, 141

- producing, 141
- properties of, 142
- centigrade, converting to Kelvin, 203
- central distribution chamber (Tee chest),
 - illustrated, 242
- centre ballonets, maintaining pressure using, 244
- Centre for Research on the Epidemiology of Disasters (CRED), database on emergency events, 689
- Centre National de Recherche Scientifique (CNRS), 459
- centre of buoyancy (CB), 193
 - CG position relative to, 230
 - of the envelope, 169
 - fixed, 201
 - in rectilinear flight, 61
 - relationship with centre of gravity, 199
- centre of gravity (CG), 193
 - of the envelope, 169
 - prescribed range for, 199
 - in rectilinear flight, 61
 - for SL150, 647
- centre of gravity envelope, 236
- certificate of analysis, 118
- certification
 - as design driver, 588–592
 - requirements, 582
- CFD (Computational Fluid Dynamics)
 - Simulation, 580, 668
- CFD model of an airship, schematic of, 50
- CH47 (Chinook), 440
- CH53 (Sea Stallion), 440
- Chain Number 1, moving commodities, 688
- Chain Number 2, transporting major components, 688
- Chain Number 3, moving large number of troops,
 - hardware, and material, 688
- Channel. *See* English Channel
- Charles, Jacques, 311
- Charlière gasbag, 311
- Charron, Ric, 475, 644
- chase crew (the Retrievers), 309
- Chateau d’Oex, 353
- check valves, 241
- China, earthquake in 2008, 686
- Chinook* helicopter rotor systems, 475, 644
- chlorosulphonated P.E (Hypalon), 128
- Christopher, Ute, 693
- chronological eras, of world’s airship
 - development programmes, 292
- chronological sequence, revealing need for any
 - and all GHE, 300
- cigar shaped form, designed to minimise drag, 149
- circular arc sections, shapes based on, 458
- circular cylinder
 - pressure distribution around, 24
 - steady motion of moving through a perfect fluid, 35
- circulation factor, 94, 95
- circumferential gores, 169
- cirrostratus cloud mass, 344
- cities
 - converging air towards centre of, 348
 - increased aerodynamic roughness, 348
 - location of, 349
 - micrometeorology for airship flying in, 348–350
 - thermals very strong over, 331
- civil airship, small requiring minimal access, 219
- civil authority national requirements, for the UK and USA, 157
- civil certification, 588
- civil passenger transport role, 439
- civil payloads, 213, 233
- civil power roles, of airships, 441–442, 448
- Civil Reserve Air Fleet (CRAF), 694
- civil roles, of airships, 439, 446–447
- CL 75 Aircrane, 666
- CL160* transporter, 513, 676
- classical rigid shape, for an airship, 60
- ‘classical’ state equation, 69, 71
- climate-related disasters, 689. *See also* disasters,
 - majority suffering from
- climb or descent, tendency towards uncontrolled, 18
- close coupled support system, 173, 174
- closed streamline shapes, producing, 49
- closed system
 - envelope as, 198
 - formula for, 198
 - moments in, 201
 - more convenient looking at airship trimming, 198
- cloud, high terrain in, 333
- cloud amount, variation in, 335
- cloud cover, influence on diffuse radiation, 525
- cloud shadow, 335
- cloud streets
 - extending for hundreds of miles, 344
 - very obvious in weather satellite pictures, 345
- clutter energy profile, 421
- clutter profile model, 420
- coast, crenulated, 354
- coastal classes, 452
- coastguard forces, functions of, 442
- coastguard role, 442–443, 448
- coated fabrics
 - changing shear behaviour, 133
 - stress-strain characteristics as linear elastic, 138
- coatings, reducing tear strength, 136
- Coca-Cola airship, 617
- cockpit
 - layout, 251, 252
 - of LZ N 07, 564
 - shapes, 34
- CODAG (COmbined Diesel And Gas turbine)
 - power-plant installation
 - better fuel consumption of, 106
 - endurance comparison with an all gas turbine solution, 107
- Coefficient of Performance, for an airship, 395

- cold air jets, low velocity, 110
- ‘cold and low’ case, largest power consumption, 667
- cold climate, reaching a given pressure height in, 12
- collector grid network, 538, 543
- Colt GA42, flying with electric actuators, 585
- combustion process, fuel:air ratio in, 248
- command, control, communications, intelligence (C3I) role, 446
- command and control (C2), of airship during flight, 598
- comma-shaped cloud, 341
- commercial companies, looking to market forces, 693
- commercial feasibility, of solar-powered airships, 520
- commercial operations, over Lake Constance, Lake Lucerne and Lake Geneva, 353
- commodities, moving, 688
- common earth system, electrically bonding each area via, 156
- communications, as design driver, 598–600
- communications role, of unmanned airships, 584–585
- comparative performance, 105–107
- complexity, high degree of providing a large payload, 435
- component drag data, for three airships, 30
- components, transporting major, 688
- compressed air
 - power required, 397
 - storage, 396–398
 - storage volume of, 397
- compressed storage, of lifting gas, 398
- compressor plant, reducing weight of, 397
- Computational Fluid Dynamics (CFD), 49–53
 - analysis on flying scale model(s), 592
 - producing good estimates of linear variation, 413
 - testing aerodynamic performance, 635
- computer controlled power conditioner, 521
- computer system, for an actuation system, 228
- computer technology, 2, 61
- concentrated load input, problems of dealing with points of, 259
- A concept for European Regulations for Civil Unmanned Aerial Vehicles (UAV’s)*, 589
- conceptual design
 - creating initial configuration, 409
 - phase, 409
 - precursor to preliminary design, 409
 - process, 411, 412
 - projects, 410, 415
 - receiving more attention, 409
 - typical process for, 412
- conceptual methods, employing baseline design, 413
- conceptual phase, focusing on a baseline design, 409
- conduction paths, leading to static discharge positions, 156
- conicity, of airship hulls, 42
- constant increment, at each pressure height, 205
- ‘constant-weight’ combination, of liquid fuel and natural gas, 17
- constraints, limits imposed by known, 412
- consumables, costs of, 454
- contained gas, 191–192
 - centre of gravity (CG) of, 202
 - at higher pressure, 192
- contained gas conditions, 205–207
- container weight, 397, 398
- continuity condition, 102
- control, of HAV, 684
- control and response characteristics, illustrating, 78–82
- control cars
 - drag, estimating, 34
 - large spike attached to the bottom of, 318
- control demands, poor response to on landing, 262
- control effectiveness, improved, 4
- control flaps, for lenticular geometry, 407
- control operation, manual and response sluggish, 18
- control points, establishment of, 415
- control pressure, generated by airscoops, 16
- control response, independently augmented, 83
- Control Reversal Speed, 662
- control surface actuator, failure of, 593
- control surfaces
 - actuators, 220
 - area of, 179
 - arrangements, 19
 - co-ordinated movements of all, 18
 - deflecting, 32
 - effectiveness, 671
 - forces applied by the pilot, 358
 - hinging, 179
 - locking in neutral position, 180
 - notation, 66
 - one piece or split, 220
 - operating freely each way, 180
- control system, weight considerations, 227–228
- controlled touchdown, at prearranged spot, 291
- controls, effects of, 358–359
- convection, initiated by insolation ceases at night, 337
- convective layer, limited volume of air in, 335
- convective process, negative feedback to, 335
- convective storm, 331
- conventional aircraft, exaggerated aspirations for, 449
- conventional airships
 - lift of, 463
 - as a low-speed vehicle, 1
 - payloads less than 50 tonnes, 511
 - vulnerable to wind on the ground, 463
- conventional cross-sectional shape, as body-of-revolution, 415

- conventional design, 457
- conventional shape, of the envelope, 457–459
- conventional tear testing, 137
- conversion factor, between nondimensional forms
 - for a particular class of shapes, 26
- cool air, diving positively into, 363
- copolymer (Saran), properties of, 129
- Copper Indium Selenide cells, 537
- costs
 - common to all aircraft, 454
 - for solar-powered airships, 544
- cotton
 - compared to synthetics, 119
 - plies bonded together using natural rubber, 118
 - properties of, 119
- counter insurgency/terrorism role, 443, 448
- Coutelle, Jean Marie-Joseph, 310
- crack opening, different forms of, 137
- crane lift role, 435, 440, 447
- Cranfield University, wind tunnel, 56, 682, 683
- crash landing, providing for in design, 255
- crash station, specified for military airships, 256
- CRED tables, detailed statistics for the period 1980 to 2007, 689
- crew
 - accommodations for, 250–253
 - of airships, 436
 - for a hot-air airship versus helium, 605
 - training for hot-air airships, 616–617
- crew training flight, R34 striking ground during, 284
- crimp, effects of, 136
- critical parts, making electrically nonconductive, 156
- critical point, with modern ZTOL airships, 379
- CRM 1800, 661
- cross flows, on the body, 25
- cross section, extent of kink around, 165
- crosswind
 - at cruise altitude, 329
 - descending below altitude band of, 329
- cross-valley flow element, 351
- cross-valley wind component, at Inntal, 353
- crosswind mooring, 405
- crowd control, 313
- cruise, vectoring of thrust during, 367
- cruise engine, location for, 225
- cruise power weight fraction, 678
- cruise ship operations
 - motivation of travel in style and comfort, 440
 - requirements of, 447
- cruise speed
 - of airships, 436
 - fuel consumption and, 362
 - increase in increasing ground speed, 362
- crystalline region, of cellulose, 141
- crystalline silicon (Si) cells, used in nonairship applications, 537
- CS 30N, 590
- cube v. square law, applying, 436
- cube-cube law, airships following, 671
- cumulus clouds, 335
- cumulus humilis clouds, 344
- current distribution, on Zeppelin NT, 574
- curtain suspension system, 175
- cyclist power output, 625
- Cyclo-Crane*, 479
 - of Aerolift Inc., 22
 - complete envelope system rotatable, 434
 - flight modes of, 480
 - proposed by Aerolift Inc., 477–479
- cycloidal propeller, described, 628
- cyclones, 338
- cylinder
 - mass of fluid per unit thickness displaced by, 35
 - as a tube carrying a bending moment, 675
- cylinders, portable pressurized for transportation
 - of compressed hydrogen, 314
- cylindrical air cushions, 657
- D* series (UK), 493
- D2 dirigible, 620
- D2-bis* airship, 493
- D3 (Spirit of the Forest)*, 493
- Dacron, laminated with Mylar and Tedlar, 130
- dampers, controlled by the pilot, 241
- DARPA (Defense Advanced Research Projects Agency)
 - contracts to Lockheed Martin and Raytheon for ISIS, 492
 - WALRUS project, 690
- dart shape, 461, 489
- database, essential for accurate estimate of weight, 417
- dc motors, weight of conventional, 538
- de Lome, Dupuy, 492
- dead air, large ducts needed to remove, 110
- dead time, of transit to and from operation zone, 444
- Dearborn, American trials of Ford mast at, 319
- DeBeers project, 558–559
- decals, use of, 219
- declination, 523
- decorative wall coverings, for passenger carrying flights, 233
- deep discharge, no adverse effect on secondary cell performance, 540
- deep mountain valleys, 351, 352
- Deering, Tom, 634
- defined path, in patrol surveillance, 583
- deflation, accomplishing, 254
- de-icing fluid solution, spraying envelope with, 365
- de-icing systems, for *SkyCat 20*, 471
- DELAG airline, 264
- delivery sequence, for CargoLifter, 652
- deltoid (delta planform) shape, proposed, 415
- deltoid hull, as the lifting agent, 20
- deltoid platform, low aspect ratio for the envelope, 461

- demonstration, of a workable system for MCM, 451
- density
 - changing an airship's, 290
 - dependent upon ratio between Off-Standard and Standard conditions, 190
 - of the fabric, 217
 - of the gas, 205, 206
 - at ISA, 190
- Department of Aeronautics and Astronautics, University of Southampton, 620
- depth-of-discharge, 539, 541
- derivative notation, describing aerodynamic effects, 63
- descent
 - final rate of not critical in unmanned airships, 592
 - initiating during free ballooning, 373
 - keeping rate as low as possible, 185, 373
- design
 - beginning with a brief, 630
 - commencing with definition of requirements, 428
 - continuous for Airships Industries (UK) Ltd., 452
 - data for dirigibles, 624
 - drivers for unmanned airships, 587–600
 - efforts preceded by studies, 410
 - establishing criteria, 212–214
 - issues, 625, 627
 - loads and stresses analysis, 448
 - options, establishing sensitivity of, 409
 - parameters, evaluating from various disciplines, 417
 - phases of, 410
 - principles of the Zeppelin NT, 550
 - success measured by a figure of merit, 428
 - synthesis, 409–430
 - trades and sensitivities, 419–425
 - weight considerations, 212–214
- design and operation, basic parameters of airship, 8–22
- design balance deficiencies, 230
- Design Bureau Automatica, 502
- design categories
 - capability to realise general airship attributes, 438
 - civil power roles, 446
 - civil roles, 446
 - military roles, 447
 - paramilitary roles, 447
- design phase, 200
- design pressure differential, 14
- detail design, 409
- detail method, estimating weight of each component, 418
- detection data, during searches for persons-in-the-water, 442
- detection range, prime power, weight, and cost as a function of, 421
- deterioration, of the envelope, 455
- development programmes, succession of past, 302
- development unit, completing first CargoLifter as, 663
- Dewars containers, liquid helium in, 504
- diamond exploration, 558
- dielectric welding, 117
- diesel condensate, as highly toxic, 653
- diesel cycle, 104, 105
- diesel engine, mounted on lower deck, 652
- diesel fuel, storing for *SkyCat 20*, 470
- differential constant, keeping within close limits, 15
- differential pressure, 9, 14
- diffuse irradiation, 525
- diffuse solar radiation, 525
- digital models, simulating fluid flow over, 635
- dimensional derivative symbol, 63
- Dinosaure* airship, proposed in early 1980s, 468
- Dinosaure* dynastat, 467
- dipoles, converting field energy into heat, 117
- direct current collector network, 521
- direct normal solar flux, 524, 529
- direct operating cost (D.O.C.), 423, 424
- direct radiation, contribution from, 531
- direct solar energy, 524, 529
- direct solar flux, 523
- direct solar radiation, 521, 523–524
- directional control, 264
- dirigible
 - envelope, 630–631
 - forces acting on, 631
 - resistance by various parts of, 632
 - turning on a dime, 622
- dirigible flight, pioneering attempts at, 309
- dirigible resistance, components of, 632
- disaster relief
 - funded by charitable contributions, 693
 - logistics, 687
 - supply chain management in, 688
 - supply chains, 688
- disasters
 - climate-related, 689
 - delays in delivering relief equipment and supplies, 686
- displacement thickness, 34, 400
- disposable ballast, form of, 231
- disposable lift, 12
 - determining, 418
 - falling off with increasing pressure height, 12
 - of the gasbag, 9
 - increasing, 394
 - not changing with altitude, 10
 - ratio of actual to theoretical maximum, 12
- disposable load, 211
- distribution system, weight considerations, 229
- disturbed airship axes, 65
- disturbed flight, perturbation components, 62
- disturbing moments, 273
- ditching, on water, 155

- diurnal temperature ranges, 214
- DKBA DP-800*, 502
- docking mode, 565
- docking procedure to the mast, for Zeppelin NT, 550
- docking systems, 274
- dome shaped windows, 253
- doors, weight of, 222
- down vector selection, 366
- downburst, 331
- downdrafts, 331
- downward perturbation, 433
- downwind dash, 329
- drag. *See also* aerodynamic drag
 - of bodies of revolution of constant volume, 27
 - breakdown for three airships, 30
 - of a circular cylinder, 42
 - of the duct, 102
 - equation for, 672
 - of the hull, 18
 - of primary importance, 25–34
 - reduction of by controlled blowing or suction, 110
 - semi-empirical relationship for, 682
 - of a sphere, 592
 - trend comparison, 426
- drag coefficients
 - expressing, 25
 - of a particular body, 26
 - for typical airship hulls, 29
- drag curve, for traditional ellipsoidal airships, 595
- drag force, 24
- drag model, idealised, 400
- drag or kite line, lowering with attached ballast bags, 373
- drag point-of-effectiveness, for SL150, 647
- drag power, required to stationkeep, 487
- drag trend, 426
- drain valves, high rate, 247
- drift, for any particle, 36
- drift mass, equaling the mass of fluid displaced, 36
- drive, transmitting to the propeller, 109
- dry snow, flying through, 364
- dual system, for pressurisation, 161
- duct(s)
 - approximate weight of, 226
 - as channel only for air intake, 241
 - effect on flow about a propeller, 100
 - finding the thrust of, 102
 - force generated on, 100
 - improving propulsor efficiency, 226
 - increasing thrust and thrust/power ratio at zero forward speed, 102
 - modelled as a distribution of ring vortices along its camber line, 100
- duct circulation, determining, 103
- duct drag, effect of, 102
- ducted fan system, proposed for stern propulsion, 404
- ducted propellers, 98–103, 109
- Dumont, Santos, 314, 440
- Durham, Mike, 468
- Dynairship*, 20, 461, 466, 467
- dynamic equation, of motion, 35
- dynamic forces, 34–40
- dynamic lift, 18, 38
- dynamic loads, under all operational conditions, 634
- dynamic pressure, effect of, 671
- dynamic response, at the hover, 81
- dynamic stability analysis, 71–77
- dynastat hybrid design proposals, configurations of, 464–472
- dynastats, 464–472
 - best suited for transport applications, 463
 - described, 640, 641
 - landing and loading phases far less complex, 464
 - shown in Gabrielli von Karman plot, 464
- Dyneema. *See* high performance polyethylene (HMPE)
- early morning, bringing in or out of hangar, 333
- Early Warning (Dew line) function, 437
- earth orbit satellites, low cost alternative to, 584
- earthquake
 - in China in 2008, 686
 - in Haiti in 2010, 686
 - in Japan in 2011, 687
 - in New Zealand in 2011, 687
 - in Pakistan in 2005, 686
- EASA, AS 105 GD certified for passenger transport, 614
- EASA Document # E.Y013-01 Policy Statement - Airworthiness Certification of Unmanned Aircraft Systems (UAS)*, 589
- EASA Permit to Fly, AS 105 GD/6 obtained, 615
- Eckener, Hugo, 320, 607
- Economic Exclusion Zones (EEZ), 443
- economic success, airships lack of, 431
- economic viability, of airships, 1, 7
- economics, of the airship, 452–455
- eddies, entraining fluid from the free stream, 24
- edging ring, 163
- EFCS (electronic flight control systems), 2, 60, 61
- efficiency
 - decreasing as propulsor loading increases, 90
 - defined, 97
 - of flywheel systems, 542
 - of the H₂O₂ fuel cell, 540
 - increasing as forward speed increases, 90
 - of solar cells, 535–537
- efficiency factors, comparison of fin and hull, 52
- electric motors, 538, 594
- electric servo engine, operating side rudder, 615
- electric system, of Zeppelin NT, 574
- electrical and avionics group, 228–230
- electrical and hydraulic systems, for CargoLifter CL 160, 661
- electrical block diagram, for Sentinel 1000, 249

- electrical bonding philosophy, 156–157
- electrical cables, backed by earth braids, 157
- electrical emergency equipment, 229
- electrical energy, converting to mechanical energy, 542
- electrical equipment, miscellaneous, 230
- electrical group, weight of, 228
- electrical power. *See also* power
 - for airships, 249–250, 481
 - driving systems, 383
 - percentage of total power required, 383
- electrical power generation system, weight of, 229
- electrical power supply, weight penalty of, 227
- electrical storm, unacceptable risk for airships, 332
- electrical systems
 - designed to be redundant, 249
 - on Zeppelin NT, 573–574
- electrically powered actuators, weakness in having, 227
- electrolytic cells, 538
- electronic circuitry, replacing conventional commutator, 538
- electronic equipment, shedding heat, 253
- electronic flight control systems (EFCS), 2, 60, 61
- electronic flight instrument system (EFIS), on Zeppelin NT, 571–572
- electronic power requirements, for a military payload, 213
- electrostatic effects, preventing, 152
- elevated anchor point, (Sheer-legs), 312
- elevator deflection, producing pitching moment response, 79
- elevator reversal, 671–672
- elevators, tilting hull axis in deliberate manoeuvres, 18
- ellipsoid, added mass of, 36
- ellipsoid (elliptical cross-section) shape, proposed, 415
- ellipsoid of revolution
 - inertia coefficients of, 38
 - relevant for airships, 36
 - with the same meridian cross section area and length as the hull, 37
- ellipsoid rotated about its z axis, yawing, 36
- ellipsoidal body, aerodynamic lift generated by, 460
- elliptic cylinder, added mass of, 36
- elliptically shaped envelope, Excel sheet for designing, 635
- EMC (Electromagnetic Compatibility), effort needed for, 598
- emergency conditions, rescue services problems, 155
- emergency electrical equipment, 229
- emergency escape, 151, 155
- Emergency Events Database (EM-DAT), 689
- emergency exits, 155
- emergency grappling lines, 155
- emergency systems, for airships, 254–256
- emergency takeoff manoeuvre, performing, 369
- EMI (Electromagnetic interference), 598
- empennage, of LZ N 07, 549, 563
- empirical formulae, used to assess the drag of bodies, 29
- ‘empty’ weight, about half gross lift at sea level, 12
- empty weight fraction, 677
- endurance
 - as design driver, 588
 - diagrams for Zeppelin NT, 553
 - effect of increased weight on, 209
 - effects, 154
 - extreme, 432
 - requirements, 213
 - very high, 436
 - of Zeppelin NT, 552
- energy
 - balance for CargoLifter, 667
 - sources, 107–108
 - storing as kinetic energy of rotation, 542
- engine bay, weight considerations, 222
- engine drives and propellers, 384
- engine efficiency, as paramount, 105
- engine exhaust gases
 - condensation and collection of water from, 16
 - cooling to recover water, 248
 - using to heat lifting gas, 392
- engine failure
 - problems following, 106
 - during takeoff, 371
- engine generated thrust, use of, 109
- engine specific weight, 105
- engine weights, obtaining bare, 226
- engineered materials
 - designing extreme, 142
 - emerging, 140–143
- engineering design effort, phases of, 409
- engineering students, 619, 637
- engineers’ theory of bending, 164
- engines
 - choosing a type of, 223
 - connecting to the propeller via gearing, 384
 - cruising speed with all in operation, 552
 - in a different power regime to HTA craft, 379
 - directly in line with propeller, 226
 - directly mounted to nacelles on Zeppelin NT, 568
 - with high oil consumption, 225
 - installed weight allowance, 225
 - output power of, 223
 - repairing in flight, 154
 - selecting, 381–383
 - with a small frontal area, 224
 - of Zeppelin NT, 568
- engines or propellers supported on outriggers, location of, 253
- English Channel
 - attempt to cross in a pedal-powered airship, 623
 - Nephelios* crossing in 2011, 486
- Entreprenant*, 310
- envelop materials, properties of, 114

- envelope
 - for an airship, 455
 - allowance for other items fitted to, 219
 - bonded with lightning conductors, 332
 - buckling at the end of stiffening members, 181
 - circumferential direction of, 121
 - as a closed volume, 198
 - connections at the lower surface, 176
 - design criteria, 215–216
 - design of, 633–634
 - double-skinned to reduce heat transfer coefficient, 396
 - emergency situations requiring rapid deflation of, 254
 - gas contained within, 191–192
 - geometrical attributes, 169
 - gore patterns, 634–635
 - for a human-powered dirigible, 630–631
 - ice accreting very quickly on the front of, 331
 - initiation of a tear less important than propagation, 138
 - interior of inaccessible, 253
 - kinked, 165
 - manufactured from strips of material, 167
 - material for, 633
 - as an open system, 198
 - pilot and passengers seated inside, 462
 - potential benefits and effects of pressure stabilised, 167
 - remaining under positive tension, 163
 - requirements for an airship, 13
 - scaling linear dimensions, 215
 - sealing with paraffin on inner surface, 118
 - specifying anticipated loads on, 634
 - supporting gondola’s suspended mass
 - proportional to fabric tension, 170
 - suspension/attachment to, 221
 - tension in membrane, 176
 - tension not rising as deflection or load increases, 176
 - upper portion of exterior, 253
 - weighing deflated, 235
 - wrinkle developing around the cross section, 165
 - of Zeppelin NT, 562–563
- envelope area, relative to sphere, 459
- envelope bending moments, analysing, 634
- envelope configuration, selection of, 414
- envelope fabric
 - area density versus volume, 218
 - considering, 416
 - ignited first in the Hindenburg, 505
 - weight of, 217
- envelope materials
 - joined by mix of sewn and bonded joints, 118
 - modern, 60
 - from natural fibres, 118
 - not forming membranes impervious to gases, 133
 - properties of, 131–140
 - properties of coatings suitable for, 128
 - weight effect on total envelope weight, 544
- envelope mounted (outriggers) propulsor, 225
- envelope mounted (rear of envelope) propulsor, 225
- envelope or hull structure, of an airship, 160–170
- envelope pressure
 - maintaining a constant, 162
 - operating automatically in Zeppelin NT, 549
 - at pressure height, 371
- envelope pressurisation, main components of the control of, 228
- envelope rigidity, calculating pressure required for, 163
- envelope shape
 - attempting to alter, 459
 - with rounded ends, 170
- envelope skin area, 395
- envelope stress, 634
- envelope tension, resolved components of, 176
- envelope volume
 - determined by physical measurement, 236
 - as either gross or not, 192
 - estimating weight using, 215
- envelope weight
 - absorbing a large proportion of gross lift, 14
 - components of, 391
 - versus gross lift, 544
 - increased to contain higher gas pressure, 391
 - minimising, 635
 - proportional to surface area, 457
- envelope weight fraction, 678
- environmental degradation, resistance to, 114
- epoxy resin, HMPE fibers not compatible with, 126
- equations of motion
 - assumptions reducing to a reasonably simple level, 63
 - development of, 63–67
 - six degrees of freedom, 64
- equilibrium, reached via heat exchange, 670
- Equilibrium (EQ), maintaining correct, 287
- equilibrium control, 150–151
- equipment, designed to deal with all fundamental basic GH requirements, 312
- equipment bay, weight considerations, 223
- equipment mounting, weight of within the cabin, 222
- escape slides, not suitable for airships, 155
- exchange, terminating before completion, 657
- exchange sequence, for either active frame system, 656
- exchange time, reducing required, 656
- exhaust water recovery, reducing in-flight weight loss, 389
- Exocet missiles, losses to, 444
- expedition, to the ‘Arctic Sky,’ 610
- exploration, by unmanned airships, 586
- exterior geometry, maintaining fixed, 239
- external environment, causing deterioration, 455

- external lighting, for *SkyCat 20*, 471
- external mountings, requirements for, 221
- external signatures, of airships, 437
- ‘Eye in the Sky’ EC programme, 556
- FAA, UAS airship program, 589
- FAA (US ADC), bending moment formula, 163
- FAA Memorandum AFS-400 UAS Policy 05-01*, 589
- FAA-ADC (Airship Design Criteria), 633
- fabric bag, lowered to the sea, 248
- fabric cover, attached by a system of radial catenary curtains, 500
- fabric structures
 - analysing using FE methods, 158
 - conforming with idealised shape, 159
 - interacting with essentially rigid structures, 159
 - as largest component of the hull, 216–218
 - shapes taken by, 159
 - ultimate factor of 4 usually required, 158
- fabrics, properties of, 119
- facilities
 - for specialists onboard, 252
 - to trim or change cg-cb position, 201
- fail-safe principles, applying, 153
- failure effects, 154
- fairing technique, excess volume created by, 415
- falling temperature, tending to increase densities but reduce volume, 10
- fan pressure system, 508
- fan thrust units, mounted at aft of gondola, 66
- FanWing, consisting of a cylindrical radial turbine, 629
- fanwing ideas, for human powered dirigible, 629
- FBW. *See* fly-by-wire (FBW)
- FE models, validation of, 159
- feasibility studies, carrying out, 212
- Fecher, Jurgen, 576
- feedback control loops, closing, 83
- fibre
 - schematic of molecular chain structure of, 120
 - world’s strongest, 126
- fibre optics, employing, 228
- fibrous structural integrity, protecting, 119
- field loading, with mobile handling facilities, 512
- Field of View (FOV) coverage, 583
- film, incorporating as gas barrier, 127
- fin(s)
 - on an airship, 31
 - comprising set of interlocked spars and ribs, 178
 - constructing from major sub-assemblies, 178
 - fittings to install on the envelope, 179
 - no historical agreement on correct size for, 661
 - position along the hull influences determining, 178
 - separated by a body, 43
 - subjected to large bending effects, 408
- fin and hull efficiency factors, deduced from experimental data, 45
- fin effectiveness, assessing for HAV, 684
- fin forces, estimating, 42
- fin geometry, showing, 43
- fin group, components considered with, 220
- fin loads, presenting a particular difficulty, 661
- fin planform areas, definition of, 43
- fin structure
 - supported by the fabric envelope, 60
 - weight of, 220
- final assembly weights, 235
- financial support, inconsistency of, 317
- fine mesh stocking, 55
- Fineness Ratio, of a body, 26
- finger patches, on envelope’s lower surface, 172
- finishing processes, affecting tear strength, 136
- finite element (FE) methods, employing, 158–159
- fire protection, for engines, 222
- first stab airship weight, deriving, 209
- first wave blimps and semirigids (1899-1939) era 2, 292
- fishery protection/antipiracy role, 443, 448
- fixed anchor points, on the ground, 652
- fixed docking systems, demanding precise control of the airship, 274
- fixed wake models, 95
- fixed wing aircraft, elapsed time between out and return journeys, 439
- fixed/rotary wing aircraft, adding an external payload, 586
- flat plane, in the envelope, 9
- flat plate area, plotted against wetted area, 426
- flat-body airship shapes, 461
- flattened-body airship designs, 461
- Flex Fatigue (FF), comparative testing of, 127
- flexible cylinder, theoretical buckling, 166
- flexural properties, of envelope and ballonnet materials, 139–140
- flight
 - access in provided to each nacelle, 170
 - at incidence, 38
- flight and thrust vector control system, of Zeppelin NT, 549
- flight control
 - as design driver, 596–598
 - of Zeppelin NT, 569–570
- flight control system (FCS), 84, 227
- flight management system, in *SkyCat 20*, 470
- flight mechanics, general aspects, 670–672
- flight options, constantly reviewing, 355
- flight-services, energy required for, 521
- floating shed, 315
- flooding
 - in Mozambique in 2000, 686
 - in Pakistan in 2008, 686
- floors, weight of, 222
- Flotran, used for CFD testing, 635
- flow, 24, 88
- flow batteries, 540
- flow separation, in an adverse pressure gradient, 41
- flow testing, unsteady, 56–57

- flow velocity, 92, 93
- flow visualisation photographs, 42
- fluid(s)
 - deceleration of, 24
 - gaining kinetic energy, 34
 - kinetic energy in, 34
 - requirements for, 225
- fluid particle paths, 35
- fly-by-light (FBL) control systems, 60
 - through optic fibres, 19
 - utilizing fibre optics, 252
- fly-by-wire (FBW), 60
 - design process considerations, 83
 - extending to include control and stability augmentation, 83
 - operated on a side stick on Zeppelin NT, 564
 - signals, 19
 - transferring pilot control inputs to control surfaces on Zeppelin NT, 569
- fly-by-wire or fly-by-light control systems, with electric actuation of control surfaces, 358
- fly-by-wire/power-by-wire technology, in Zeppelin NT, 549
- flying, optimum location near the central axis of a broad ridge, 343
- flying aircraft carriers, 321
- flying controls, 82, 368
- flying moor, making to a high mast, 319
- flying platform, Zeppelin NT examples as, 556–559
- flying qualities requirements, 83–84
- flying saucer. *See also* lenticular form
 - lenticular shape described as, 459
 - as a lifting body concept, 20
- flying wing delta platform shape hybrid airship, 466
- flywheel materials, characteristics for large scale energy systems, 543
- flywheel systems, characteristics of, 542
- flywheels, 542
- fog, radiation and advection, 333
- following wind, providing different problems, 362
- force
 - on the cross section per unit length, 41
 - on a small area around a point, 23
- force distribution, along the hull, 39
- force equations, writing, 64
- force estimation, for three-dimensional bodies, 37
- forces
 - acting sideways owing to crosswinds, 270
 - on an airship in curved flight, 39
 - on an airship while moored, 269–272
 - on a dirigible, 631
 - estimating, 42
- forcing function, information on, 57
- forecasting services, for storms, 337
- form (or pressure) drag, described, 25
- form drag, 26, 400, 401
- formation flight, 377
- forward and aft ballonets, 218
- forward thrust, reduced, 400
- four rotor rotastat, 473
- four rotors, 473–476
- fractional distillation, extracting helium, 504
- fracto cumulus clouds, 351
- fracture mechanics approach, 137, 138
- fragile shell, as a generic physical GH problem, 285–286
- frame, bouncing on the ground, 658
- frame formats, for CargoLifter, 650
- frame position, vertical control of, 659
- free balloon landing, 372, 373
- free ballooning, 372–374
- freedom, 6 degrees of, 291
- freight role, 447
- freight traffic, one way only, 439
- freight transport roles, 439
- French Oehmichen Heliostat, 256
- frequency clearances, 585, 598
- friction layer, mechanical turbulence in, 329
- frontal cloud band, active section of, 342
- frontal low pressure systems, mid-latitude, 338–345
- frontal lows
 - avoiding flying into central part of any, 343
 - developing from small spiral circulations, 340
 - expected to become more energetic, 343
 - having very active spiral frontal bands, 341
 - new patterns evolving in past 20 years, 339
- frontal rain, 341
- front-end process, 424
- Froude efficiency, 90
- fuel
 - and ballast storage container combination, 246
 - characteristics of various, 107
 - generating electrical power requirement, 383
 - as large part of static heaviness, 597
 - permitting as dumpable ballast, 386
 - required for power generation, 229
 - required to cover a given still-air distance, 18
 - as trim media on Zeppelin NT, 569
 - type of, 224
 - used not exceeding difference between maximum heaviness and maximum lightness, 383
- fuel and condensate, handling of, 653
- fuel bladders, stored on the surface vessel, 257
- fuel capacity and consumption, of the Zeppelin NT, 549
- fuel cells
 - advantages over batteries, 541
 - classified according to electrolyte, 541
 - described, 540–541
 - effect of size on specific energy, 541
 - lighter than batteries, 541
 - not required for operations above the Antarctic zone in summer, 489
 - as preferable to batteries, 542
 - relationship between cost and energy storage capacity, 543

- fuel cells (*cont.*)
 - reliability of, 541
 - requirements for use with solar cells, 541
 - weight and volume of, 541
 - weight of, 544
- fuel consumption, 224
 - cruise speed and, 362
 - for different aircraft types, 381
 - improvements, 4
- fuel efficiency, of dynastats compared to helicopters, 464
- fuel filler neck, on Zeppelin NT, 565
- fuel flow, at ground idle, 381
- fuel pick-up system, experimental, 246
- fuel storage tanks, construction of, 247
- fuel systems
 - for airships, 245–248
 - weight of, 227
 - of Zeppelin NT, 568–569
- fuel tankage, 221, 222
- fuel tanks, 245, 246
- fuel volume, increased for hydrogen, 108
- Full Tensor Gravity Gradiometer (Air-FTG) system, 558
- functional analysis, 626–629, 631
- functional requirements, 425
- funding, for heavy lift airships, 693–694
- fuselage, of Zeppelin NT, 559–563
- GA-42, gondola of, 172
- Gallagher, 620
- Gallium Arsenide (GaAs) solar cells, 537
- Gamma*, British Army airship vectoring propellers, 264
- gas
 - in the envelope free to expand, 10
 - venting, 196
- gas airships, as very expensive to operate, 605
- gas balloon, superior nature of, 311
- gas barrier film, search for a better, 134
- gas cell, inflating, 318
- gas constant, for air, 204
- gas container’s shape, varying, 156
- gas heating, effects of, 394
- Gas Law, 194
- gas lift
 - calculating, 386
 - for a particular volume envelope, 385–386
 - per envelope volume, 385
- gas mass properties, derivation of, 203–207
- gas pressure bending moment, 673–677
- gas pressure relief valves, 162
- gas retention component, of laminate materials, 127–128
- gas space, behaving like expandable gasbag in open atmosphere, 16
- gas temperature
 - recording, 372
 - rising, 13
- gas thrusters, 275
- Gas Transporter*, 498, 499
- gas turbines, 16
- gas valves
 - installing for control purposes, 162
 - located on the side of the envelope, 244
- gasbags
 - full at sea (level), 12
 - lift of, 9
 - lighter in rigid airships, 13
 - skin design, 10
- gas-filled balloon, first free-flight of, 311
- gas-lift, supporting only empty weight of vehicle, 432
- gastight fabric, 118
- gearboxes, weight of, 224
- GEFA-FLUG
 - airship training courses, 617
 - airships used for various purposes, 604
 - developing airships since 1970s, 604
 - developing hot-air airships, 508
 - European airship marketing venture, 617
 - hot-air airships certified for commercial passenger flying, 607
- GEFA-FLUG 6 seater airship, 616
- GEFA-FLUG airship project, in Tanzania, 509
- GEFA-Flug no. 1 airship, 603
- Geiser, Luc, 622
- general aviation air vehicle, equation for amin landing gear of, 417
- generation system, weight of, 229
- generators
 - driven by propulsion engines, 249, 383
 - horsepower required to drive, 249
 - mounted in each fin powered by pneumatics, 227
 - multiple installed, 249
 - supplying electrical power for Zeppelin NT, 549
- generic GH tasks, identifying, 302–305
- geometry
 - of an airship, 416
 - defining, 428
- geostationary meteorological observation satellites, 346
- geo-stationary position, SL150 maintaining in no-wind condition, 647
- German Aerospace Centre (DLR), flying Zeppelin NT over Bavarian capital of Munich, 557
- German GH System, 292, 293–294
- German Halle based sequence, original, 296
- German LBA, certification as a four-seater for AS 105 GD, 614
- German Lufttüchtigkeitsforderungen für Luftschiffe [LFLS], 633
- German Mining Technology, technological support from, 610
- German Navy Zeppelins, beyond prototype stage, 316
- German WDL airships, equipped with two fuel tanks, 246

- German wings airship, 617
- German Zeppelin force, in World War I, 443
- Germany, using airships to fly food, medicine and equipment from Bulgaria to East Africa in 1917, 687, 695
- GH. *See* Ground Handling (GH)
- GH Equipment (GHE), 279, 293
- GH Infrastructure (GHI), 279
- GH methods, summary of, 296
- GH requirements, fundamental, 311, 313
- GH system requirements, generic, 291–292
- GH systems
 - array of incomplete, 317
 - evolution of, 309–322
 - necessary elements intrinsic to, 279
 - used by war-time patrol blimps, 298
- GH tasks, offloading to other groups of personnel, 304
- Gibbins, R.P., 274
- Gibraltar straits area, searching visually for mines in, 445
- Giffard airship of 1851, 432
- Giffard design of 1851, 448
- glacier wind, at snout of a glacier, 353
- glass, properties of, 125, 142
- glider, compared with an airship, 153
- global upper atmospheric wind profiles, examination of, 487
- global warming
 - introducing more extreme weather events, 355
 - producing new patterns of weather, 4, 327
 - recent acceleration of influence on changes in
 - patterns of frontal lows, 343
 - steady increase in both annual average and extreme air temperatures in western European cities, 348
- global weather satellite observation system, means of testing global models, 328
- Gomes, Sergio B.V., 84
- gondola, 170–172
 - associated structure group, 221–223
 - configuration and location of, 221
 - cross sections, 171
 - depth roughly controlled by human proportions, 170
 - generally underslung some way below, 172
 - length increasingly important, 170
 - lengthening using battens, 176
 - of LZ N 07, 564
 - modification to the hull pressure caused by, 31
 - motion beneath the envelope, 176
 - mounted inboard (propulsors outboard) system, 224
 - outboard mounted propulsor, 224–225
 - partially inserted via a large aperture into lower envelope surface, 177
 - physical relationship with envelope, 428
 - placing as many systems as possible into a single, 170
 - placing partially inside the envelope, 173
 - shear force and bending considerations, 154
 - single as the norm for nonrigid airships, 170
 - sizing, 414
 - structure heavily dependent on airship’s role, 172
 - support system, 172–177
 - suspended mass, 170
 - suspended weight to length ratio, 176
 - type of, 171
 - volume, 428
 - weighing conventionally throughout it’s build, 234
 - weight prior to envelope attachment, 234–235
 - as working centre of the airship, 171
- Goodyear Aerospace, U.S. Navy airships built by, 241
- Goodyear Blimp, as long endurance camera platform, 440
- Goodyear designs, landing airships configured on, 334
- Goodyear GZ 20, polyester used in envelope of, 119
- Goodyear GZ-22, propulsive units vectored vertically, 256
- Goodyear method, 281
- Goodyear proposal, for Four Rotors, 473
- Gordon Bennett gas balloon race, hydrogen legally used in, 591
- gores, 167
 - construction methods, 634
 - making up envelope profile, 217
 - from which an envelope is constructed, 121
- government funding, of heavy lift airships, 694
- GPS-based moving-map cockpit data display systems, 355
- Graf Zeppelin* 1, minimised need for venting hydrogen, 258
- Graf Zeppelin* (1928–37), 607
 - avoiding weight loss through fuel consumption, 17
 - fuelled with a mixture of propane and hydrogen, 107
- Graf Zeppelin II*, 13
- graphite (AS4), properties of, 125, 142
- gravitational force, static, 65
- gravity gradiometer system, improved, 558
- Great Storm of October 1987, 339
- green nanoparticles, unique sources of, 141
- grid points, giving zero flow velocity normal to the surface of the body at, 49
- Griffith energy balance, form of, 138
- gross envelope volume, 217
- gross lift
 - of an airship, 194
 - decreasing, 196
 - defined, 196
 - furnishing upward force, 9
 - of the gasbag, 9
 - of a gasbag independent of shape, 9

- gross lift (*cont.*)
 - per unit volume, 9
 - required, 418
- gross static lift, 192
- gross weight
 - of an airship, 211
 - first estimate, 428
- ground crew
 - needed before first flight crew and pilots, 280
 - problems solved by, 301
 - re-evaluating role of, 279–280
 - training extremely well, 616
- ground equipment, for Zeppelin NT, 550
- ground fender, landing gear as, 183
- ground handlers, looking after moored airships, 308
- ground handling area, ideal, 334
- ground handling (GH)
 - of airships, 259–260, 454
 - as all or nothing, 305
 - CargoLifter CL 160, 664–665
 - of conventional airships, 3
 - declared to be impediment to successful development of airships, 298
 - defined, 308
 - defining, 300–309
 - effect of size on, 272–273
 - as an empirical science, 298
 - establishing in its central role, 278
 - evolution of systems, 292–298
 - few scientific studies during PGVLA development, 323
 - future systems, 274–276
 - generic problems, 285–292
 - great unsolved problem, 278
 - historical review of techniques, 263–268
 - ideas preserved in historical records, 284
 - as a key factor in heavy operation, 640
 - low regard for based on several false perceptions, 298–299
 - maintaining a temperature differential throughout, 395
 - requirements, 3, 260–263
 - role of the pilot, 368–369
 - scale model for, 323–324
 - sequence of events, 299, 300
 - survey of problem, 260
 - system for CargoLifter, 649
- Ground Handling Manuals, for airships, 298
- ground handling party, dependence on, 357
- ground idle fuel flow, self-sustaining, 381
- ground impact protection device, point loads generated by, 286
- ground manoeuvring, thrust vectoring generally not used during, 366
- ground movements, 261
- ground operation, of Zeppelin NT, 574–575
- ground power unit, maintaining onboard functions on the ground, 250
- ground proximity warning system, 333
- ground related tasks, executing from the airship, 152
- ground resistance, reduction of, 183
- ground roll, achieving takeoff or landing, 432
- ground speeds, 291, 362
- Ground Support, for expeditionary remote or temporary bases, 305
- Ground Support Equipment (GSE), 279
- ground train, of a road mobile mooring mast and several other vehicles, 454
- group weights, for structural system and propulsion system, 428
- growth discontinuity, identifying magnitude of, 435
- Growth Factor method, 417
- Grzimek, flight-expedition in Tanzania in 1958, 609
- gust fronts, reaching places out of sight of the storm, 345
- gusting
 - effects of, 19
 - vertical component of, 45
- gusting side winds, inducing side loads, 272
- gusty wind conditions, small amount of up vector, 366
- GZ22 airship, manual handling, 454
- H₂O₂ fuel cell, 541
- H₂/O₂ fuel system, regenerative, 488
- HAA prototype airship, 490
- Haiti, earthquake in 2010, 686, 691
- HALE-D (High Altitude Long Endurance Demonstrator), 490
- Halle, walking directly into, 293
- HALROP (High-Altitude Long Range Observation Platform), 461, 489, 494
- HALROP-20, 486
- HALROP-20 and -23, 489
- handles, limited number of, 281
- Handley, Alan, 502
- hangar. *See also* shed
 - facilities available for structure construction and maintenance, 152
 - mechanical turbulence generated around, 330
 - removal to for major overhauls, 253
 - weigh-off, 234, 235–236
- hangarage, large building required, 260–261
- hard profile, 400
- hardware
 - of GH, 279
 - moving large number of, 688
- Harrison's survey, 136
- hauling up circle, 320
- HAV analysis method, 684
- HAV Ltd., analysis at, 683
- HAV-3 scale demonstrator, 471
- HAV304 airship platform, 471
- head fasteners, raised, 154
- headwinds, 387, 388
- heat bonded joint, 130

- heat flow, 395
- heat loss, through the skin, 395
- heating
 - applying via air in ballonets, 392
 - penalties in time, weight and energy incurred in, 395
- heating effect, greenhouse type of, 197
- Heave Mode, 74
- heave/pitch subsidence mode, 79
- heavier-than-air (HTA) aircraft
 - APUs powered by small turbines with poor SFCs, 383
 - engines driving propellers directly, 384
 - payload limitations of, 379
 - power off-take compared with, 383
 - proposed for all roles because they existed, 449
 - way of thinking, 298
- heaviness
 - considered to be, 360
 - countered by vectored thrust, 642
 - decreasing with size, 307
 - equalling water and other disposable ballast, 386
 - increasing posing problems, 360
 - at takeoff, 105
 - throughout the mission, 597
- heaviness quotes, values of, 358
- heaviness range, 230, 684
- heavy airship
 - advantageously flown on the sunny side of a cloud line, 345
 - as close to stall during takeoff or landing, 18
- heavy equipment, external mounting of, 223
- heavy flying, 597
- heavy lift
 - in airship practice, 640
 - applications, 7
 - loading and unloading, 276
 - scale of components involved in, 653
 - by unmanned airships, 583–584
- heavy lift airships
 - Aerostat, 640, 645, 647
 - Aircrane, 645, 665
 - CargoLifter, 647–678
 - development over the past thirty years, 689
 - Dynastat, 463, 464, 466, 467, 468, 641
 - generalized performance, 641
 - HAV (Hybrid Air Vehicle), 690
 - LEMV (Long Endurance Multi-Intelligence Vehicle), 458, 468, 471, 472
 - performance generalised, 512
 - publicised need for in two countries, 694
 - Rotastat, 464, 472–477
 - Skyhook, 475
 - SkyLifter, 645, 646, 647
- heavy lift helicopter (H.L.H.), 463
- Heavy Lift (HL), pioneer in the concept of, 512
- heavy lift variant (SL 150), 513
- heavy lift version (SL150), 646
- heavy loads
 - carried by large airships or smaller size hybrid airships, 511
 - carrying directly from factory to intended destination, 689
- heavy point load, supporting in a balanced way, 645
- heavy points, 286
- heavy rainstorms, over any land surface, 341
- Hedgepeth’s model of stress concentration factors, 138
- height dependent pressure, added to pre-tension required, 673
- helical vortex, geometry of, 102
- helicopter/airship hybrid concept, 276
- helicopters
 - aerostatically enhanced, 21
 - crane lift requirements largely met by, 440
 - derivatives of military designs, 440
 - tail rotors replaced by axial thrust propellers, 22
 - technology limiting payload lifting capacity, 691
- Helio*stat, 476
- Heliship*, 476
- Heli-Stat*. *See* Piasecki Heli-Stat
- Helitruck*, 473, 474
- helium
 - availability widespread, 448
 - choosing materials with least permeability to, 134
 - compared to hydrogen, 591
 - contained gas assumed to be, 191
 - exclusive use of in current airship concepts, 258
 - high cost of, 16
 - inefficiency meaning larger airships, 506
 - lift compared to hydrogen, 506
 - as lifting gas, 504–505
 - loss effects of, 134
 - loss from an envelope, 134
 - losses, 134
 - nonflammable, 505
 - purity of, 385
 - smallest molecular diameter of all gases, 133
 - unit lift of, 9
 - unlikely to be 100% pure, 205
- helium airships, ongoing costs, 605
- helium dump, decreasing lightness in an emergency, 380
- helium permeability, 134
- helium space, blowing air directly into, 256
- helium storage, liquefied, 398
- helium valves, 251, 591
- helium vent valve, installing, 598
- Helmholtz Association, 557
- high altitude
 - applications for solar power in airships, 483
 - high fidelity optics as heavier, 582
 - ice crystal layer cloud (cirrostratus), 344
 - solar powered airships, 486–492
 - surveillance, 581
 - unmanned airships, 486

- High Altitude Airships (HAA), 486, 490
- high drag, generated by lenticular geometry, 408
- high envelope pressures, needed for turbulent weather and rapid manoeuvres, 162
- high fence, surrounding whole site, 313
- High Frequency (13-100MHz) welding, 117
- high mast, in British system, 294
- high modulus polyester film (Mylar-DuPont-Teijin), 128
- high modulus polypropylene (HMPP), properties of, 125
- high performance fibrous materials, properties of, 142
- high performance polyethylene (HMPE), 125, 126, 127
- high pressure, flying in travelling ridge of, 343
- high pressure air, available from gas turbines, 111
- high pressure systems
 - airship flying successfully completed in, 337
 - centre of, 334
 - low clouds developing within, 335
 - with macroscale, 335
 - weak horizontal pressure gradients in most, 347
- high strength coated textile materials, use in two areas, 138
- high tenacity fabric, pressed together with high modulus films, 122
- high-altitude airships, as astronomical platforms, 487
- High-Altitude Long Range Observation Platform (HALROP). *See* HALROP (High-Altitude Long Range Observation Platform)
- high-altitude long-endurance surveillance airship, fuelled by hydrogen engines, 496
- high-altitude microwave-powered airship, 495
- high-tenacity polyallylate fibre, 127
- Hindenburg
 - CargoLifter compared to, 649
 - catastrophe at Lakehurst in 1937, 258
 - crash in 1937, 296
 - disaster to, 449
 - envelope fabric ignited first, 505
 - length and gas capacity of, 14
 - lifting gas capacity of, 511, 641
 - publicised loss of, 437
 - rain gutters used in, 249
- hinge brackets, needed to carry the control surface, 179
- hinge moments, 53
- HIRF (High Intensity Radiated Fields), unmanned airship exposed to, 598
- Hi-Spot, proposed unmanned airship, 489
- Hi-Tec Zeppelin NT, 606
- HMPE. *See* high performance polyethylene (HMPE)
- HMPP. *See* high modulus polypropylene (HMPP)
- HMS Endurance, sovereignty enforcement role of, 443
- Hochstetler, Ron, 691
- hoisting station, on U.S. Navy airships, 257
- hoop stresses, directly proportional to shell diameter, 501
- horizontal and vertical energy, need to reduce to zero, 262
- horizontal fins, cantilevered out from trailing edge, 407
- horizontal force, resolution of, 269
- horizontal surfaces, synchronised to operate like a conventional elevator, 65
- horizontal tailfins, on an airship, 18
- horizontal transverse axis, 432
- horsepower, required to overcome resistance, 633
- hot air
 - as lifting medium, 507–509
 - operational and economic advantages, 13
- hot air balloon flying, short course of, 357
- hot air ballooning, as a significant sport, 440
- hot air balloons
 - definition related to GH of modern, 301
 - as an extreme case of superheat, 13
 - license, 616
 - as wind toys, 607
- hot-air airships, 602–618
 - in the 1990s as pressure airships, 602
 - ability to hover over a defined area, 607
 - carrying by road to new place of operation, 605
 - compared to gas airships, 350
 - disadvantages, 606
 - environmental monitoring as an additional market, 607–608
 - first market for, 607
 - general characteristics, 6, 606–607
 - versus helium, 605–606
 - inflated on the launch field, 606
 - low cost when not in use, 605
 - main market for, 604
 - operational experiences, 608–609
 - requiring more volume than helium ships, 508
 - ‘serious’ research on, 610
 - types of, 508
 - weather dependent, 604
- hourly component, of D.O.C., 424
- hover
 - control and response at, 81
 - dynamic response at, 81
- hover cushion
 - landing system, 469
 - with suck down capability, 682
- hovering, 367–368
- hovering position, attainable by a large airship, 653
- HTA. *See* heavier-than-air (HTA) aircraft
- hull. *See also* bare hull
 - aerodynamic drag of, 399
 - altering angle of attack, 290
 - apparent mass of affected by its geometry, 37
 - boundary layer thick at stern, 33
 - centre of gravity of, 38
 - CFD and experimental data comparison for an isolated, 52

- of the conventional airship, 1
- low drag shape for, 29
- spectrum of the lift produced on, 46
- strength of, 288
- variation of side-force coefficient with cross crosswind angle, 272
- hull assemblies, weight breakdown, 216
- hull centre line, flying with an angle of yaw, 38
- hull drag, drag of other components expressed as fractions of, 682
- hull forces, evaluating, 42
- hull geometry, defining and developing, 428
- hull group, weight estimation, 215–219, 235
- hull profile, of a pressure airship, 13
- hull rigidity, categorisation according to, 435–436
- hull shape, classical streamline problems in ground handling, 19
- hull weight, difference diminishing with size, 436
- human dirigible propulsion, functional analysis, 628
- human factors, considering, 624
- human factors engineering, 6, 623
- human figure model, in MQ Pro, 626
- human interaction, limited degree of greatly facilitating landing, 267
- human pilot, aerodynamic drag attributed to, 632
- human power, for airships, 492–494
- human powered dirigibles, 6
 - design criteria, 7
 - design of, 619
 - design study to develop, 630
 - more recent developments in, 620–623
- humanitarian relief airship, developing, 693
- humanitarian relief operations, airship suited for, 7
- humanitarian supply chains
 - fraught with uncertainty, 688
 - lacking rapid deployment abilities, 688
- human-powered aircraft, designing a propeller for, 622
- human-powered airship flight, safety considerations for, 493
- human-powered airships, characteristics of, 492
- humidity, effect of increasing, 198
- hunting motion, as position control system seeks a null point, 650
- hurricanes, 347. *See also* tropical rotating storms
- Hybrid Air Vehicles (HAV), 690
 - aerodynamic aspects of, 681–684
 - combining different types of lift, 468–469, 641
 - defined, 681
 - described, 5
 - flying demonstrator, 469, 642
 - heaviness range, 642
 - intended for operations in remote areas, 473
 - lift characteristics of, 684
 - lift provided for, 643
 - observation of flight of sub-scale demonstrator, 684
 - potential advantages of, 681–682
 - series of airships, 641
 - under technical leadership of Roger Munk, 468
 - types of lift provided for, 468
- hybrid airship-helicopter, 21
- hybrid airships
 - aerodynamics, 681–684
 - employing a type of ballonet system, 240
 - heavy lift, 277
 - improving on some features of parent heavier-than-air craft, 463
 - lift of, 463
 - types, 464
- hybrid heavy lift air vehicle (HAV)
 - in humanitarian relief mission, 691
 - impression of, 643
- hybrid hull, considered as a low aspect ratio wing, 683
- ‘hybrid’ layouts, dispensing with use of ballast, 19
- hybrids, nonconventional types of airship, 149
- hydraulic fluid, weight of, 232
- hydraulic power, as another suitable power source, 232
- hydraulic systems
 - on CargoLifter, 667
 - on Zeppelin NT, 572–573
- hydrogen
 - as acceptable alternative to oil based fuels, 108
 - compared to helium, 591
 - drawn from gas cells into engines, 496
 - as fuel for airships, 494–496
 - as a lifting gas in airships/balloons, 505–507
 - as never actually causing an airship accident, 506
 - portable metal cylinders to hold pressurised, 318
 - of special interest due to its low weight per unit heat release, 107
 - unit lift of, 9
 - venting to reduce aerostatic lift on descent, 258
- hydrogen based airships, revived interest in, 507
- hydrogen cell, based within the helium cells of a 1000 ton rigid craft, 496
- hydrogen-filled airships, prone to catastrophic fire, 258
- Hydrogen-Chloride cell, effective specific energy of, 541
- hydrogen-filled gas balloon, world’s first, 311
- hydrolysis, better resistance to, 119
- hydrolytic degradation, polyamides subject to, 125
- hypodermic tubing, inserted from inside the model, 53
- hypothetical airships, applying full model to, 51
- hysteresis effect, 40
- Hytrel, 130
- ICE. *See* internal combustion engine (ICE)
- icing
 - conditions, 331, 365
 - effects of, 197, 332
- ideal flow profile, generating a new, 400

- IFR/VFR operation, in *SkyCat 20*, 470
- ILC Dover, 472
- iMike human figure model, 625, 627
- Imperial Airship Scheme prototypes, 321
- implied payload, accounting for, 212
- inboard engine/outboard propulsor configuration, assuming, 226
- incidence
 - flight at, 38
 - as yaw angle, 39
- incident flow, along body principal axes, 37
- incident solar energy, part absorbed as heat, 537
- incident velocity, on the propulsor, 109
- inclinometer, mounted at pilot’s side at head level, 252
- incoming cable, bisecting cusp angle equally, 175
- induced drag, described, 25
- induced drag coefficient, 683
- induced velocity
 - estimation of, 93–95
 - finding, 100
 - at the propeller disc, 102
- inertia
 - of the airship, 375
 - apparent moments of, 64
 - apparent products of, 64
 - balance against, 157
 - consequent different from varying ground speed, 291
- inertia coefficients, of an ellipsoid of revolution, 38
- inertia factors, 37
- inertia forces, ultimate specified in UK and US requirements, 256
- inertial effect, 269
- inflated tube, maximum tensile stress of, 168
- inflation, on one day and flight on the next, 309
- inflation fraction, 11
 - effective, 16
 - when ‘cold’ at sea level, 392
- in-flight fuel usage, maximum, 379–380
- initial transit manoeuvre, options at the end of, 288
- initial vehicle integrator, 414
- inland tourist areas, opening, 440
- inner duct contour, use of, 103
- Innsbruck, in Austria, 353
- Inntal, U-shaped glacial valley, 353
- inspection criteria, development of workmanship, 117
- instability, of lenticular geometry, 406
- installed thrust, defined by drag at maximum speed, 672
- instructions, for sequential and concurrent tasks, 279
- Instrument Flying, pilot qualified for, 333
- instrument noise level, of an airship, 559
- instrument panel, on Zeppelin NT, 571
- insulation, weight of, 222
- intake ports, locating, 241
- integrated function, design process as, 427
- intelligence gathering mode, of P-791 Hybrid Air Vehicle, 690
- interface movements, improvements, 4
- Intergovernmental Panel on Climatic Change, 4th Assessment Report, 327
- internal cables, avoiding slosh against, 161
- internal combustion engine (ICE), 104
- internal cross bracing, holding lattice arrangement, 178
- internal engine installations, 253
- internal lighting, for *SkyCat 20*, 471
- internal loads, compared with agreed allowable loads, 157
- internal monocoque airship, details, 497
- internal monocoque structure, 500–501
- internal pressure
 - at bottom of the ship, 674
 - differential, 197
 - direct relation with dynamic pressure, 675
- internal rigid structure, 562
- internal suspension system, supporting the gondola, 173
- internal suspensions, dependency of the length of, 674
- international funding, of heavy lift airships, 694
- Internet handshake protocol, 598
- inviscid flow, 38, 49
- inviscid solution speed, attaining, 24
- Iron Horse (mobile mast), 293, 295, 320
- ISA (International Standard Atmosphere), 12, 189
 - Arctic minimum, 12
 - series of temperature gradients, 189
 - ‘tropical maximum’ condition, 12
- I.S.A. gas lift, acceptable over water, 386
- ISA Sea Level (SL) condition, 189, 191
- ISIS high altitude solar powered airship (Integrated Sensor is Structure), 491
- islands, cities located on, 350
- isobars, flying, 387
- Italia airship, 607
- Italian CRM unit, designed for use in high speed motor launches, 661
- Italian Forlanini Omnia Dir, bow and stern high pressure air jets, 256
- jammed control surface, in manned or unmanned airships, 593
- Japan, earthquake and tsunami in 2011, 687
- Jess, Peter, 475, 644
- jet, boundary of, 100
- jet aircraft, often struck by lightning, 332
- jet flap, vectored, 662
- jet stream, acting as a fast conveyor belt for air, 339
- jettison actuation, 231
- Jill, model for use in SolidWorks, 625
- jointing tapes, described, 169
- joints
 - agent responsible for making, 130

- bonding directly to the load bearing
 - component, 122
- in laminated materials stronger than materials themselves, 130
- made by butting adjacent gores together, 168
- method of making modified, 121
- Joule cycle, 104, 105
- jute, cracking genetic sequence code of, 142
- Kaempf and Well, automatic flight management and control system for RPAs, 510
- Kapton (polyimide PI film), bias modulus and unique gas barrier membrane, 122
- Karman vortex train, 330
- katabatic (downslope) winds, 352
- keel, 13
- keel design, of CargoLifter CL 160, 660
- Kelvin scale, 189
 - ice point, 203
- Kevlar
 - properties of, 125
 - specific energies for flywheels using, 542
- Kevlar flywheel, weight of, 544
- Kevlar-covered aluminium frame, housing six gasbags, 460
- kimberlites, detecting, 558
- kinetic energy
 - added to the fluid, 89
 - of descent, 183
 - effective, 542
 - rate of change equaling work done by external forces, 35
- kink, developing, 164
- kiting motion, 151, 185
- Krell, Otto, 315
- Kutta condition, satisfying at the trailing edge, 100
- Kutta-Zhukowsky theorem, 94
- L127 ‘Graf Zeppelin’ rigid airship, successful global circumnavigation, 328
- La France*, employing a 7 kW electrical motor and 460 kg of batteries, 481
- Lagrange trajectories, measurements along, 558
- Lakehurst, high mast at new Naval Air Station, 319
- laminar flow
 - all airships benefitting by landing in, 335
 - layers of air moving parallel to the surface, 24
 - throughout, 401
- laminate
 - consisting of components, 121
 - improved, 140
 - typical, 121
- laminate components, permeability of, 134
- laminate development process sequences, 116–117
- laminate joint, typical, 130
- laminate material joint, section through typical, 130
- laminate materials, 121–122
 - in ballonets, 131
 - potential, 130–131
 - properties of film materials for use in, 129
 - section through typical, 122
 - typical fibre properties, 125
- laminated envelope materials, behaviour of, 132
- laminated materials, properties of film materials for use in, 129
- laminated PVF film, comparison of fabrics with, 129
- land, temperatures exceeding I.S.A., 386
- land clutter, more powerful than sea clutter, 420
- landing, 262
 - different each time, 358
 - distances greater with static lightness, 360
 - optimum wind conditions for, 334
 - statically light, 597
 - techniques employed for, 374–378
 - vectored thrust allowing into a smaller area, 367
 - ways of changing and controlling altitude, 290
- landing gear, 182–187
 - compressing, 185
 - of the LZ N 07, 549
 - mounting of, 223
 - proposed configuration of, 221
 - as a spring, 183
 - withstanding resultant loads during forced landing, 151
 - for Zeppelin NT, 565–566
- landing leg attitude, vertical, 186
- landing site, approaching from any direction, 291
- landing zone, for Zeppelin NT, 575
- lanyards, clipped to a safety harness, 155
- Laplace transform, of the state equation, 72
- large airships, landing horizontally, 307
- large control deflections, drag effect of frequent, 362
- large oceanic airship for patrol purposes, gondola for, 172
- large rigid airships (Era3), three separate subdivisions, 292–293
- larger airships, 173, 675
- laser targeting threats, countermeasure deterrence against, 122
- latch arrangements, direct contact, 274
- lateral characteristic equation, roots of, 75
- lateral control, deceleration affecting, 282
- lateral equations, 70–71
- lateral force equilibrium, 270
- lateral mode coupling, typical in most air vehicles, 80
- lateral response
 - less sluggish than longitudinal response, 80
 - to rudder step input, 81
 - to step command input to rudder, 80
- lateral stability modes, 78
- lateral state equation, example, 73
- lateral state matrix, approximating, 75
- lateral trim, conditions for, 70
- lattice panels, containing a source and vortices lie along the edges, 49

- lattice structure, skinned with doped heat shrink fabric to provide a smooth aerodynamic profile, 178
- launch/release (takeoff), 289–290
- L-band, requiring three times number of components as UHF, 421
- Le Patrie*, torn from hands of her ground-crew and blown out to sea, 318
- lead acid batteries, providing back-up emergency power, 249
- Leipzig Airship tour, 617
- leisure role, 440, 447
- LEMV hybrid airship, Critical Design Review (CDR) for, 472
- LEMV surveillance Hybrid Air Vehicle, 472
- length/diameter ratio, in conventional airship design, 458
- leno weave, useful to create fairly open weave structures, 116
- lens-shaped wave clouds (altostratus lenticularis), appearance of, 344
- lenticular airships, 459–460
- lenticular form, symmetrical, 405
- lenticular geometry, 405–406
- lenticular hull, 466
 - aerodynamic characteristics of, 405
 - becoming unstable in pitch, 406
 - difficult to find effective positions for control surfaces, 406
 - drag of, 408
 - as a lifting body concept, 20
 - in pitched flight, 406
 - stabilisation of, 407
 - stability inadequate to balance aerodynamic pitching moment, 459
- lenticular shape
 - of the envelope, 459–460
 - of the SkyLifter, 513
 - of the SL150, 645
- Leuven University, 635
- level flight, with no control load, 359
- Liebherr load exchange system, 661
- Liebherr system, 651
 - based upon a passive load frame, 651–654
 - considered to be excessively complicated and heavy, 654
 - problems with, 653–654
 - proposed modifications, 654
- life cycle of the airship, studies concerned with, 422
- lift
 - carry-over of from, 43
 - considerations for, 463–480
 - decreasing as altitude increases, 631
 - other factors affecting, 197–198
 - proportional increase in, 392
 - proportional to volume, 457
 - sources of, 631
 - types combined by an HAV, 681
- lift (elevator), in the high mast with a gang-way, 321
- lift and drag, at higher angles of attack for unmanned airships, 593
- lift and induced drag, for HAVs, 683–684
- lift augmentation, varying by design, 434
- lift coefficient, expressing, 25
- lift curve slope, 683, 684
- lift density, 193
- lift gain, through heating, 394
- lift gas, venting with usage of hydrogen, 591
- lift loss
 - equivalent to a fuel consumption rate, 398
 - theoretical, 134
- lift reduction, owing to a pressure differential, 390
- lift spectrum, peaking when the wavelength of the turbulence equals length of the hull, 46
- lift vector, tilting backward, 25
- lift versus speed relationship, 463
- lifting blades, flow generated by, 93
- lifting bodies, as finite, 25
- lifting capacity
 - function of volume, 273
 - larger allowing greater choice of propulsion arrangements, 106
- lifting gas, 191, 503–509
 - characteristics of, 505
 - choice for unmanned airships, 592
 - compressed storage of, 398
 - controlled but rapid means to dump, 151
 - density of, 239
 - heating, 391–396
 - indication of characteristics of, 428
 - lighter than air, 205
 - management of, 258
 - pressurisation, 389–391, 392
 - releasing from an accessible position on the ground, 155
 - superheating or super cooling, 290
 - superpressure of, 239
- lifting rotors, airship with, 21
- lifting-body dynastats, 467
- lifting-gas purity, reduction in, 372
- liftoff, 262
- light aircraft, compared with an airship, 153
- light airship, flying in cloud shadows, 345
- light envelope fabric, new, 615
- light flying, 597
- light pressure tube structure, element of, 504
- lightness, at landing, 105
- lightning attachment, points with high potential for, 157
- lightning conditions, avoidance of regions of known, 156
- lightning strikes, policies, 156–157
- lights, strobe and navigation, 220
- lightweight gas holding multilayer consolidations, of laminate, 122
- limit load, 157, 634
- limiting values, constraining design solution, 419

- Linde airship, 617
- Lindstrand Balloons UK, 602
- Lindstrand GA22 Mk2 unmanned airship, 579
 - electrical and electronic tests, 598
 - gondola cutaway, 595
 - in-hangar assembly, 599
 - stroke technology for the power plant, 595
 - tethered flight trials, 579
- linear dimensions, for a volume higher than calculated, 386
- linear model, readily analysed, 61
- linear zone, where air slowly descends about a mile offshore, 354
- linearised equations of motion, 67–71
- linearised lateral equations, of motion, 70
- linearised longitudinal decoupled equations of motion, 68
- liquefied helium storage, 398
- liquid crystal fibre, microfibrillation model, 120
- liquid crystal polymer fibres, 119
- load, final relocation within airship load bay, 654
- load bearing component, of laminate materials, 122–127
- load cage arrangements, alternative, 659
- load cage variants, 656
- load cases, for a CL 160, 668
- load curtains, number of depending on cable array, 175
- load deck, 656
- load delivery, 656
- load exchange, 584
 - for CargoLifter, 650
 - categories for an Aerostat, 645
 - development of, 648
 - effecting in a single operation, 650
 - listed as being safety critical, 666
- load factors, on the airframe, 154
- load frame
 - comprising a structural box, 654–659
 - configurations, 651
 - suspended from CargoLifter, 650
- load-carrying airships, categories of, 640
- loading
 - American contribution to, 321
 - PGVLAs, 320
- Loading and Bending Moment diagram, for a nonrigid airship, 634
- loads calculation, for CargoLifter, 668
- load-sheet, 237–238
- local skin friction coefficient, variation of, 27
- local skin friction distribution, 28
- Lockheed 1011 transport aircraft, comparison of a conventional with a hydrogen fuelled, 108
- Lockheed Hercules C130 aircraft, 690
- Lockheed Martin High Altitude Solar Airship, 491
- Lockheed Martin LEMV finalist, 471
- Lockheed study, comparing a 1011 airliner using JP4 with a variant using hydrogen fuel, 107
- logarithmic scales, 415
- Logistics Airship technology development, 688
- log/log plots, 415
- loiter characteristics, of buoyant lift, 105
- London, strong local afternoon breezes, 348
- Long Endurance Manned Solar (L.E.M.S.) airship, proposed, 484
- long-endurance unmanned multi-intelligence vehicle (LEMV), for surveillance, 471
- longeron/frame connection points, in Zeppelin NT structure, 503
- longerons, aluminum in Zeppelin NT, 561
- longitudinal battens, 181
- longitudinal characteristic equation, roots of, 74
- longitudinal equations, 68–69
- longitudinal gores, 169
- longitudinal opening, in the envelope upper surface, 254
- longitudinal pendulum mode, 75, 79
- longitudinal plane, of symmetry of the airship, 61
- longitudinal response
 - to elevator, 78
 - to elevator step input, 78
 - to increase in thrust, 79
 - to step increase in thrust, 80
- longitudinal restraint method, design of the gondola's, 151
- longitudinal stability modes, 75
- longitudinal state equation, 72
- longitudinal state matrix, approximating, 74
- longitudinal surface length, of the envelope, 169
- longitudinal tension
 - in an airship, 674
 - determining, 167
 - at the envelope's opposite face, 167
- longitudinal trim, conditions for, 68
- long-term continuous surveillance, 583
- long-term measurements, 558
- Loral Goodyear GZ-22, gas turbine-powered, 17
- Loral GZ-22, vector angle, 370
- LORAN, recent developments in, 362
- Lorenz, Ralph D., 620
- Los Angeles*
 - successful landing on aircraft carrier USS 'Saratoga,' 267
 - vertical strength of, 288
- Lotte, acting in rotation due to control input, 671
- LOTTE solar cell powered airship, 483, 484
- LOTTE-I*, destroyed in hangar in a thunderstorm, 483
- LOTTE-2*, crashed into a tree, 483
- LOTTE-3*, advanced radio control, 484
- low altitude, surveillance at, 581
- low altitude applications, proposed for solar power in airships, 482
- low altitude cruise missile, vulnerability to, 444
- low altitude unmanned airships, 509–511
- low aspect ratio, 683
- low cumulus cloud, 344
- low density polyethylene, 129
- low hull drag, 31

- low infrastructure regions, airship showing an unexpected advantage, 439
- low range monitoring, 608
- low speed control, 267–268, 274–276
- low speed controllability, overcoming, 433
- low speed environment, pilots adjusting to, 357
- lower deck, rotating into a predetermined orientation, 652
- lows
 - forming close to coast of Europe, 339
 - originating as small turbulent vortices, 338
 - traveling from west to east, 339
- low-speed vehicle, airship as, 18
- low-velocity jets, thrust produced by, 110
- LTA 20-I* Magnus Aerolift airship, 479
- LTA 20-I* spherical rotating airship model, 481, 482
- LTA aerostats, difference from HTA aerodynes, 305
- LTA biased perspective, adopting a generic, 292
- LTA perspective, establishing a new, 299–300
- Lückenhaus, 615
- Luffman, Charles, 513, 645
- Luftschiffbau Zeppelin GmbH, semirigid airship design, 502
- Lunardi, Vincent, second ascent of, 312
- Lunardi's 2nd balloon, inflation of, 312
- Lunardi's system, seminal nature of, 313
- LZ N 07, 503, 548
 - empennage, 563
 - in Kalahari desert, 560
 - mission applications of, 555–559
 - photographic images in the Kalahari desert, 559
- LZ NT 07, useful load diagram, 554
- LZ-1 craft
 - constructed in a floating hangar, 263
 - ground handling given serious thought, 263
- LZ-2, destroyed at its moorings by a squall, 264
- LZ-3, successful, 264
- LZ-4, destroyed by fire breaking away from its mooring, 264
- LZ-8
 - accident coming out of shed, 320
 - lost landing and docking, 264
- LZ-10 'Schwaben'
 - destroyed by fire in the hangar, 265
 - use of handling rails, 264
- LZ126/ZRS-3 (Los Angeles)
 - experiences on sea-borne mooring system, 319
 - moored to expeditionary masts at Camp Kearney and on board *Patoka*, 319
 - prolonged experimentation with, 319
 - recorded flights for, 317
- LZ127 (Graf Zeppelin I)
 - recorded flights for, 317
 - regular visits to Brazil and Spain, 319
 - volume of, 435
- LZ129. *See also* *Hindenburg*
 - freight-carrying space on, 321
 - ground handlers using primitive manual equipment, 321
 - landing at Lakehurst as well-rehearsed event, 322
- LZ129 Hindenburg, ground crew for, 321
- LZ-NT airship, structural outline of, 500
- Machine Aerostatique*, design for, 311
- Mackenzie pipeline project, in Canada's Northern Territories, 475, 644
- Macon (1933-35), 389
 - accident, 449
 - crash in 1933, 296
 - used a large and substantial mast, 266
- macro-scale weather system, identifying type of, 354
- magnetic suspension, not requiring physical attachment, 53
- Magnus Aerolift* spherical airship, 479–480
- Magnus Aerospace Corporation, project, 22
- Magnus effect, 479
 - proportion of lift provided by, 479
 - of a rotating sphere, 22
 - on a rotating spherical gas envelope, 434
 - translating axial gusting into vertical lift fluctuations, 480
- maintenance
 - of an airship to various parts of an airship, 253–254
 - costs for aircraft, 454
- manlines, extending from mooring cone to the empennage, 253
- manned airship airworthiness code, 590
- manned airship pilots, relative scarcity of, 589
- manned airships, operated as aerial billboards, 580
- manned codes, as a guide line for unmanned aircraft, 590
- manned criteria, departing from, 590
- Manned Thunder, flying with electric actuators for fin control surfaces, 585
- manoeuvre loads, generated by control surface deflection, 60
- manual operation, providing for valves, 244
- manufacturer's empty weight (MEW), 210
- manufacturer's suspended empty weight (MSEW), 210
- Manzell on Lake Konstanz, floating shed, 315
- maritime ships, mooring, 308
- maritime vessels, airships natural affinity with, 306
- market analysis, comparing existing assets in the field, 451
- market penetration, as slow, arduous and expensive, 452
- mass
 - large concentrations bound to occur, 156
 - per enclosed volume or surface area of an airship, 153
 - spreading over as wide an area as possible, 156
- mass of air, in container before delivery starts, 396

- mass properties
 - of airships, 209–211
 - determination of, 417
- mass transport systems, operating on a round trip basis, 439
- masses, additional affecting design of landing gear, 184
- mast
 - motions at, 151–152
 - takeoff from, 294
 - uncoupling from, 334
- mast loads, cushioning, 182
- mast mooring system, 284
- Masterman Mast, double-headed, 318
- masthead, winching airship vertically down, 284
- material developments
 - aimed at conventional airframe, 113
 - continuing process, 113
- material toughness, measure of, 137
- materials
 - critical mechanical properties of, 142
 - as design driver, 593
 - of envelope of Zeppelin NT, 562
 - introduction of stronger lighter, 2
 - moving large quantity of, 688
- material/seam strength, practical limit of, 416
- mathematical model
 - of an airship, 62
 - built around equations of motion, 61
- mathematical symbols and acronyms, list of, 679
- Mattertal, in Switzerland, 353
- max fuel consumption, per engine on Zeppelin NT, 568
- maximum available (zero pressure) disposable lift, equation for, 391
- maximum design operational weight (MDOW), 211, 236, 237
- maximum design suspended weight, 211, 214, 237
- maximum direct solar energy, 531
- maximum direct solar flux, 531
- maximum expected scattered component, 531
- maximum headway, under conditions of static equilibrium, 359
- maximum in-flight fuel usage, 380
- maximum lightness, 380
- maximum operational landing weight (MOLW), 211
- maximum operational takeoff weight (MOTW), 211
- maximum operational weight, 214
- maximum performance, achieved with airship at static equilibrium, 361
- maximum projected area, 528
- maximum reaction, for a descent rate, 185
- maximum scenario, in terms of incident solar energy, 531
- maximum speed
 - of airships, 436
 - dependency on, 675
 - selecting for an airship, 596
- maximum static heaviness, 185
 - determining for unmanned airships, 593
 - landing gear absorbing potential energy owing to, 184
 - without ballast for Zeppelin NT, 553
- Maximum Static Heaviness and Lightness, 237
- Maximum Suspended Weight Moment, 237
- maximum takeoff weight, of Zeppelin NT, 550
- maximum useful load, Zeppelin NT, 552–555
- maximum weights, decided early on, 214
- maximum zero-ballast heaviness, Zeppelin NT, 552, 553, 554
- Mayfly, employing a duralumin construction, 264
- MCP, normally at least 80% of TOP, 381
- Meadows, Stephen, 493, 622
- mean density, of the local atmosphere, 8
- mean disc velocity, effective, 403
- measurements
 - of locally limited phenomena with high spatial resolution, 557
 - long-term, 558
- mechanical actuators, operating control surfaces, 180
- mechanical support features, Zeppelin NT, 556
- mechanical systems, lost motion in, 82
- Mediterranean Sea, previously unaffected by winter storms, 342
- medium altitude surveillance, employed in a military role, 581
- medium sized airship
 - for paramilitary surveillance duties, 172
 - for sightseeing purposes, 172
- medium sized unmanned airships, altitude of, 588
- Megalifter* dynastat, 20, 465, 467
- Megalifter* winged hull, 461
- melt spinning, 119, 126
- meltable bonding agent, 130
- meso-scale meteorological factors, considering, 343–345
- metal-clad airship, 14, 501–502
 - first, 501
 - replacing textile envelope of the conventional airship, 501
- METAR reports, on development of actual weather, 338
- Météo France, providing detailed Rhone Valley wind forecast for airship pilots, 351
- meteorological forecasting agencies, 355
- meteorological knowledge, development of, 448
- meteorological phenomena, apart from the wind, 288
- meteorological research, for gliding, 344
- Meteorology and Flight* (Bradbury), 337
- ‘Meteorology for Airship Pilots’ training course, 338
- methane, 507
- Methane Gas Transporter, of semi-monocoque design, 507
- Meusnier, Lt., 311
- Mexican 6-seat lenticular airship, 20

- microburst, 331
- microfibrillation nature, 119, 127
- micrometeorological processes, 347
- micrometeorology, for airship flying in cities, 348–350
- microwave energy, as a power source in airships, 494
- microwave transmission, hovering test during, 495
- mid-latitude frontal lows, 339, 340
- mid-tropospheric subsidence inversion, very stable, 335
- military, pioneering use of observation balloons, 310
- military airships
 - equipped for inflight replenishing, 257
 - requiring access, 219
 - in surveillance mode, 249
- military certification, 589
- military roles, of airships, 443–444
- military service, airship in, 420
- military supply chains, 688
- military/paramilitary payload, items, 213
- mine countermeasures (MCM) role, 445, 450
- minimum airspeed, for any practical airship, 588
- ‘Minimum Development Rotor Airship,’ 473
- minimum length, of total configuration, 415
- minimum projected area, 528
- ‘Miss Louise,’ helium-filled blimp, 623
- missed approaches, 358, 375
- mission platform, Zeppelin NT 07 as, 556
- mission profile, dictating payload and maximum lifting capability, 214
- mission takeoff weight, first estimate of, 429
- Mistral wind, seasonally strong, 350
- mobile configurations, for ground handling, 274
- mobile mast, 369
- mobile mast truck, bringing Zeppelin NT to, 575
- mobility, of airships, 454
- model, general distribution of forces on, 53
- model ships, difficult to handle with changing solar radiation, 670
- model size, limits to, 54
- model tests, data from, 401
- Mohenjo Daro, photogrammetrical survey, 608
- moisture, leading to deterioration by hydrolysis of adhesives, 455
- moment equations, 64
- moment equilibrium, 271
 - about the centre of gravity, 269
 - ensuring at all conditions, 272
- moment unbalance, of the airship, 201
- moments
 - determination of, 37–40
 - estimating, 42
 - needed to restore an airship, 273
- momentum
 - entering control volume per unit time, 88
 - rate of change in the axial direction, 89
 - rate of change of per unit length, 39
- momentum flow, imparted to the wake, 401
- Momentum Theory, applying, 637
- monocoque hull, 402
- monocoque rigid, 498–500
- monocoque shell
 - airships utilising, 149
 - as attractive solution for airship structures, 498
- Montgolfier, Etienne, 310
- Montgolfier, Joseph, first balloons built by, 310
- Montgolfier Brothers
 - first recorded deliberate free flight (1783), 508
 - hot air balloons developed by, 619
 - smoke balloons, 309
- moored airship
 - forces on, 270
 - tending to align to wind direction, 264
- mooring
 - allowing access to interior, 289
 - coupling extreme nose to a fixed mast and ballasting ship to keep a single castoring wheel, 19
 - horizontal and vertical methods, 283
 - as key to understanding of Airship Ground Handling, 306
 - lifting off vertically from, 282
 - loading and unloading, 262
 - multipoint causing large structural loads under gusting conditions, 265
 - requirements, 3
 - water based, 266
- mooring circle, airship moored indefinitely on, 665
- mooring equipment, far more airship specific, 316
- mooring height, question of, 265
- mooring lines, capturing at sea, 319
- mooring mast
 - as best way of achieving a secure mooring, 289
 - development of, 265–267
 - mounted on board a sea-going ship (*Patoka*), 307
 - snow conditions at, 365
 - of sufficient height, 265
 - UK development of, 265
 - on a wheeled platform, 664
- mooring points, use of two, 269
- mooring position
 - nose cone attached to mast truck of Zeppelin NT, 575
 - of Zeppelin NT, 575
- mooring site
 - obstacle free within a radius of 150 metres (landing zone), 575
 - service arrangements at, 151
- Mooring Tower, at Cardington, 319
- mooring wind speeds, for SL150, 515, 646
- mooring/docking, facilitating by closed circuit television, 276
- mooring-out stations, 318
- mooring-out techniques, 318
- Morse, Professor, 260
- mother ship, unmanned airship as, 585

- motion, normal equations of, 37
- motions, at the mast, 151–152
- motorised mules, 295
- mountain wind, persisting until a few hours before dawn, 352
- mountainous desert areas, temperatures exceeding I.S.A., 386
- mountainous regions, weather for flying airships in, 350–353
- Mowforth, Edwin, 512
- Mozambique, catastrophic flooding in 2000, 686
- MPPTs (Maximum Power Point Trackers), 485
- MQ Pro, typical analysis offered by, 625
- MTU diesel, 661
- multi-axis control, landing airships with, 334
- multichamber, multigas airship, 506, 507
- multi-engine airships, engines or propellers supported on outriggers, 241
- multihull airship shapes, 461
- multijunction solar cell, schematic diagram of, 534
- multilayer consolidations, typical combinations of, 123
- multilayer laminate, 116, 140
- multilayer structures, frequent inflations and deflations, 122
- multilobe nonrigid pressure airship, 468
- multiple-hull arrangements, weight penalty, 462
- Munk, Roger, 449, 468, 685
- nacelles, 170, 567
- Nano Crystalline Cellulose (NCC), 141, 143
- nanotechnology, effects of, 143
- National Aeronautics and Space Administration (NASA) Ames Research Centre, assessing technology applied to airships, 425
- National Air Space (NAS)
 - flying unmanned through, 582
 - UASs flights in, 511
- national need, justifying continued design efforts, 410
- National Physical Laboratory in England, 29
- NATO E3 Sentry aircraft, 444
- natural disasters. *See also* disasters
 - airship suited for, 7
 - over the past decade, 686
- natural fibres
 - envelope materials from, 118
 - limited strength, 118
- natural pressure system, 508
- natural rubber
 - properties of, 128
 - sealing fabric, 118
- nautical practices, applicability of, 306
- navies, success when airships handed over to, 307
- navigation lights, 220
- negative superheat, 197, 206, 207
- neoprene
 - properties of, 128
 - as a weathering component, 129
- neoprene (chloroprene) rubbers, replacing natural rubber coatings, 118
- Nephelios*
 - first manned solar powered airship, 485
 - first solar-powered manned airship, 484–486
 - solar cell arrays on, 485
- net area density
 - of the ballonet fabric, 218
 - of the fabric, 217
- net density, 194. *See also* lift density
- net gas lift, determining, 236
- net lift, 196
 - of an airship, 194
 - apparent increase in, 197
 - defined, 196
- net static lift, 192–193
- net upward lift, 9
- New or Next Generation Very Large Airships (NGVLAs)
 - ground handling of, 283
 - method for mooring, 285
 - problem facing creators, 296
- New Zealand, earthquake in 2011, 687
- Newton’s Laws, applying to the motion of a fluid, 23
- NGVLA method, theoretical streamlined, 297
- Nickel-Cadmium (Ni-Cd) batteries, 539
- Nickel-Hydrogen (Ni-H₂) batteries, 539
- Nikki* prototype, 513, 646
- nil wind conditions, 334
- no lift augmentation
 - Category A, 431
 - characteristics of, 432–433
- Nobile, Umberto, 607
- noise, isolation with inboard engines, 224
- Nomex, 125, 126
- nondimensional groups, maintaining, 53
- nondimensional pressure coefficient, defined as, 23
- nonmodularity, of a fuel cell, 543
- nonneutral buoyancy, effects of, 82
- nonpressurised gondola, 172
- nonrigid airship design, 109
- nonrigid airships, 13, 149
 - emphasis placed on, 239
 - limited in size until the 1930s, 435
 - mid-range figures for modern, 15
 - number built between 1900 and 1970, 496
 - primary structures of, 159
 - suspension system, 17
- nonrigid constructions, suited for smaller airships, 498
- nonrigid envelope weights, 216
- nonvectored thrust airship, hovering in light winds, 368
- Nordholz, revolving shed, 315
- Norge airship, 261, 607
- normal direct solar flux, function of solar altitude, 523
- normal force, equation for, 64

- normal wind conditions, maintaining station, 368
- normalised derivatives, denoted with a lower case letter, 71
- North Atlantic general aviation route, 341
- North Sea class airship NS1, 432
- Northrop Grumman, 690
- Norton, Lord Kings, 323
- nose, calculation of the pressure around the, 49
- nose down attitude, counteracting excessive buoyancy, 290
- nose of a flexible envelope, reinforcing with splines, 15
- nose reinforcement group, 219
- nose reinforcing, comprising an external set of identical members, 180
- nose splines, diffusing envelope loads, 15
- nose structures, 156, 180
- nose-mounted elevators, solving reversal problem, 662
- ‘nose-up’ ground clearance, obtaining, 18
- nose-up pitching moment, 38, 671
- notebook personal computers, 355
- nuclear powered airships, 260, 496
- nylon, properties of, 119
- nylon fabrics
 - biaxial testing on, 133
 - introduction of high tenacity, 602
 - properties of, 129
- nylon HT, properties of, 125
- Obelix* rotor rotastat, 476
 - flying Crane concept, 476
- observation balloons, 310, 318
- obstructions, planning upstream of the model, 56
- off-mast to on-mast time, for an airship, 424
- off-standard atmospheres, 190–191, 205
- Off-Standard conditions, relative density for, 191
- oil reservoirs, required to provide engine lubrication, 248
- Olympics, covert surveillance from an airship in 1984, 441
- One Giant Leap company, 622
- open and closed systems, compared, 199
- open system
 - centre of buoyancy (CB) not remaining in a constant position, 202
 - comparing to closed, 198
 - envelope as, 198
 - moments in, 203
- operating altitude, of airships, 436
- operating costs
 - of airships, 437
 - of CargoLifter, 648
 - dearth of realistic data, 453
- operating heavy, 17, 281
- operation environment (altitude and temperature ranges), 214
- operational analysis, performing for various scenarios, 450–451
- Operational Demonstrator Model airship in 1987, 444
- operational designs, deficiencies in current, 410
- operational empty weight (OEW), 210
- operational GH problems, 285
- operational infrastructure, lack of, 450
- operational items, 211, 234
- operational sequence, for CargoLifter, 652
- operational suspended empty weight (OSEW), 211
- operational takeoff weight (OTW), 211
- Operational Weight Empty (OWE) with Volume, 418
- operations analysis, inputs to vehicle designer, 410
- optically signalled flight control system, 252
- OPV (Optionally Piloted Vehicle) airship, 578
 - flying manned in NAS, 582
 - smallest possible, 593
- orthogonal axis system, defining a right handed, 61
- Oscillatory Roll Mode, 77
- oscillatory stability modes, negligible aerodynamic damping, 82
- Osprey*, flying into its own down-wash, 281
- Otto cycle, 104
- out of trim control forces, 372
- outboard mounted cooling, for inboard engines, 224
- outdoor operation, as normal mode for time in service, 253
- outriggers, engines on, 253
- outsized goods, ferrying, 583
- Over the Horizon capabilities, acting as relay stations, 585
- overall balance, difficult to achieve, 155
- overhead surveillance, by unmanned airships, 581–583
- Owens Valley, 353
- Oxfam, on climate-related disasters, 689
- ozone, formation of, 557
- P-791 Hybrid Air Vehicle, 690
- PA-97, 689
- paint, weight effect of, 219
- Pakistan
 - earthquake in 2005, 686
 - flooding in 2008, 686
- Pan Atlantic Aerospace Corporation from Canada, proposed airship, 484
- pannier balloons, 161, 218
- panniers, 245
- paper bags, held upside down over a fire, 310
- para-aramid, Kevlar, properties of, 142
- para-aramid aromatic polyamides, properties of, 126
- para-aramid laminate (or coated material), not able to disperse stress concentrations, 126
- Paralympic Games, in Sydney, 620

- parameters
 - plotting against Gross Lift, 429
 - sensitivities of basic, 412
 - variables resulting from inaccuracies in measurement of, 197
 - varying to produce a matrix, 419
- parametric analysis, conducting, 418
- parametric set, cost of each design in, 429
- parametric studies, large part in conceptual design, 409
- paramilitary roles, of airships, 442–443, 448
- Paris Storm, of 1999, 339
- partial lift augmentation
 - Category B, 432
 - characteristics of, 433–434
- pass or deep mountain valley, transiting an airship through, 350
- passage making, effect of wind on, 387
- passenger aeroplanes, advent of reliable
 - conventional, 439
- passenger carrying flights, requiring seating, 233
- passenger flying, combining with advertising, 607
- passenger services, by unmanned shuttle service, 584
- passenger transport role, 446
- passenger version, of Zeppelin NT, 565
- passengers, seats for, 250
- passengers exchange, on Zeppelin NT, 569
- Passive Load Frame, 650
- passive tethering system, critical factor for, 653
- past, lessons noted from, 150
- patches, of the envelope, 218
- path curvature, vs. rudder angle, 40
- Patoka*, 307, 319
- patrol speeds, extreme endurance at, 442
- patrol surveillance, by unmanned airships, 583
- patrol surveillance role, 581
- payload, 511–515
 - of airships limited by gas lift available in the climatic conditions prevailing, 4
 - described, 212
 - exchange without landing the airship, 648
 - exchanging for ballast, 650
 - first contact with the ground by critical, 654
 - handling in hovering flight, 649
 - as heaviness, 360
 - increase for a relatively small rise in temperature, 393
 - inserting into the frame, 656
 - limitations of heavier-than-air aircraft, 4
 - range affected by the wind, 361
 - securing to a pallet, 656
 - volume of airships, 437
- payload collection, airship arriving on site with full ballast tanks, 656
- payload module, of *SkyCat 20*, 470
- payload/mission equipment, 233
- Pb-acid batteries, best developed of all vehicle batteries, 539
- PBO., 127. *See also* Zylon, abrasion resistance, PCAS (Portable Collision Avoidance System) systems, 599
- pedal-powered machine, used by Gallagher, 620
- Pegasus*, lenticular design, 459
- pendulum effect, overcoming, 359
- pendulum stability
 - inadequate to balance aerodynamic pitching moment at a very low airspeed, 405
 - increasing, 173
 - less than a traditional nonrigid airship, 684
 - providing strong, 646
- per unit heat release, 108
- performance
 - affected by the wind, 361
 - of HAV, 684
 - requirements, 214
- performance data
 - generated for a series of design points, 429
 - for Zeppelin NT, 550
- performance engineer, 381
- performance related design drivers, for unmanned airships, 595–596
- performance trade-study, used in sizing the radar, 421
- permeability
 - of envelope materials, 133–134
 - of fabrics, 633
 - low, 114
- permeation, of laminate materials, 134
- permissible heights, of obstacles surrounding landing site of Zeppelin NT, 576
- personnel
 - making use of equipment in a cost effective manner, 280
 - operating the system, 279
 - transfer of, 257
- perturbation, motion described as, 63
- PGVLAs. *See* Previous Generation Very Large Airships (PGVLAs)
- PGVLRAs. *See* Previous Generation of Very Large Rigid Airships (PGVLRAs)
- photo-documentation, of castles of Neuschwanstein, 608
- physical GH problems, 285
- physical tests, on representative fabric structures, 159
- physics, laws constraining airships, 285
- Piasecki Heli-Stat, 21, 22, 474, 689
 - combining four helicopters with a surplus U.S. Navy ZPG-2 envelope, 256
 - derived from existing helicopters, 276
 - four helicopter rotors, 434
 - prototype destroyed in experiment, 473
- pictorial approach, to functional analysis, 627
- pile-up of ships, at the down-wind base, 439
- pilot licenses, for hot-air airships, 616–617
- piloted airship operations, extreme weather-sensitivity of, 4

- piloting, airships, 357–378
- pilots
 - actions keeping in phase with ground handling crew, 368
 - constantly steering in gusty conditions, 291
 - reducing work load of, 180
 - role in ground handling, 368–369
 - selecting for airships, 357
 - tasks of, 3, 358
 - understanding of weather processes, 328, 355, 358
- pilots and flight crew, retaining control of all events relating to flight, 305
- pioneering era, 263–265
- pipes, bringing in for pipeline construction, 644
- piston (diesel and petrol) engines, in airship applications, 223
- piston engine maintenance, 594
- pitch angle, 199, 359
- pitch attitude response, to elevator, 73
- pitch control
 - for AS 80 GD, 604
 - in low velocity conditions and during takeoff and landing, 566
 - releasing, 359
- pitch down, as a secondary effect of turning, 359
- pitch incidence oscillation, 75
- pitch load, alleviating by valving or pumping air to/from air ballonets, 359
- pitch of a propeller, 97
- pitch response, short time constant lag in, 79
- Pitch Subsidence, Heave Mode diverging to, 74
- pitching moment
 - countered in steady flight, 38
 - equations for, 64
 - from thrust, 673
- pitch-up, controlling, 370
- plain weave, providing high degree of interlacements, 115
- platform, allowing access to underside of the vessel, 313
- platform value proposition, 555–556
- pneumatic actuators, 227, 244
- pneumatic driven generators, 227
- pneumatic power, 232
- pneumatically powered actuators, 228
- pneumatics system, on *SkyCat 20*, 470
- point-to-point transport
 - airship providing, 640
 - delivering payload, 648
- police/customs and immigration role, 441
- polyamides
 - as hygroscopic, 125
 - similar specific strength to polyester, 125
- polyamides (nylon) and polyesters (DuPont’s Dacron), produced as filament yarns, 118
- polybenzaxole, 126
- polycrystalline solar cells, 537
- polyester
 - base textile of lightest envelope fabric used in Goodyear GZ 20, 119
 - as hydrophobic, 125
 - preferred fabric, 124
 - preferred material for gas retention, 128
 - produced by melt spinning process, 119
 - properties of, 119, 125, 129
- polyester and liquid crystal polymer, molecular chain orientation structure of, 119
- polyester elastomer, properties required as a bonding agent, 130
- polyester elastomer (Hytrel), properties of, 128
- polyester PET, high tenacity, properties of, 142
- polyimide PI film (Kapton), 122
- polyimides (meta-aramid), 126
- polythene, compared to high performance polyethylene (HMPE), 126
- polyurethane
 - adhesives, 121, 455
 - coating giving better weatherability, 121
 - density of, 563
 - properties of, 128, 129
 - as a weathering component, 129
- polyurethanes and polyamides polymers, joining or welding, 117
- polyvinyl fluoride
 - properties of, 129
 - as a weathering component, 129
- Polyvinylfluoride (PVF) film, as a weathering component, 128
- pontoons, as landing gear, 182
- porosity levels, at extreme cold and low atmospheric pressure, 593
- positive superheat, 206
- potential market, for airships, 448–452
- potential roles, spectrum of, 437–446
- power. *See also* electrical power
 - available from human effort as very limited, 625
 - expended in compressing air, 396
 - humans producing and sustaining, 625
 - relation with shaft speed, 105
 - required for compression as minimal, 397
 - required to compress air, 397
 - required to cruise at a given speed, 273
 - required to propel an airship at speed, 596
 - on a small airship as less than 20% of TOP, 381
 - supplied to the propulsor, 89
- power consumers, on board of a large airship, 667
- power consuming operations, for CargoLifter, 667
- power demand, optimising, 667
- power generation capacity, relating weight to, 229
- power off-take, effects of, 379, 383–384
- power per unit static thrust, versus propulsor loading, 91
- power plant, as design driver, 594–595
- power requirements
 - proportional to the cube of the airspeed, 18
 - through all stages of a flight, 223
 - of water recover systems, 232
- power sources, unconventional, 480–496

- power systems, of CargoLifter CL 160, 661
- power units, meeting basic power demands, 106
- power wing, 663
 - of CargoLifter CL 160, 662
- power wiring, relating to power requirements, 229
- powered lift
 - approaches to generation of, 434
 - supporting payload by, 434
 - well in excess of that achieved by vectored thrust, 463
- powerplant
 - choice considerations, 223–226
 - design in the large airship era, 259
 - thrust utilising, 267
- power-SFC-speed for turboprop and reciprocating engines, 382
- power-speed relation, 483, 531
- PPMMLCC (Protect, Prepare, Move, Moor, Load, Launch, Capture, and Camp-out), 309
- Prandtl shape coefficient, 632
- Prandtl’s analysis, 93
- precipitation, from above the airship, 331
- preflight weather briefing, 355
- preliminary design
 - percentage of total engineering effort, 409
 - phase, 409
- preliminary sizing, of airships, 209
- preliminary weight estimation, as problematic, 214
- Prentice, Barry, 691
- preprogrammed mode, 578
- pressure
 - of the contained pressure, 206
 - creating tension in the skin, 674
 - differential between internal and external, 194
 - internal and external falling off, 9
 - for Off-Standard and Standard atmospheres, 190
 - in the Off-Standard atmosphere, 205
 - at a pressure height, 204
- pressure airships, 13, 149
 - aerostatic characteristics of, 14
 - hull profile, 13
 - with a very thin metal skin, 14
- pressure altitude, 372. *See also* pressure height, recording,
- ‘pressure balloons,’ high-altitude research
 - involving unmanned, 10
- pressure contoured fin, 220
- pressure control system
 - described, 239–245
 - design driving case for, 677
 - in a pressure airship, 15
- pressure difference, 9, 632
- pressure differential
 - increasing as the airship ascends, 194
 - increasing density of the contained gas, 206
 - superheat reversing, 206
- pressure distribution
 - around a circular cylinder, 23
 - around several sections along the hull, 41
 - need to obtain, 55
 - wedge-shaped, 9
- pressure envelope design principle, 117
- pressure fuelling, most systems requiring, 247
- pressure height, 16, 193, 196, 371–372
 - of 1,000 feet above the required cruise height, 385
 - airship reaching, 194
 - climb performed with ballonnet damper-valves closed, 371
 - conditions at, 196
 - depending on amount of gas in the gasbag, 11
 - described, 10
 - flight to, 236
 - ISA, 12
 - maintaining a fixed, 393
 - operating at and around for long periods, 372
 - operations close to, 365
 - for a pressure airship, 16
 - regarded as an operational ceiling, 10
 - regularly performing a climb to, 372
 - of Zeppelin NT, 550
- pressure stabilised (nonrigid) hull, advantages of, 681
- pressure systems
 - controls for above and to the pilot’s side at head level, 251
 - receiving the lengthiest description, 239
- pressure tapped propeller measurements, 99
- pressure vessel theory, 164
- pressurisation
 - of lifting gas, 389–391
 - proportional reduction in lift owing to, 390
- pressurisation system, of a nonrigid airship, 161
- pressurised cabins, 252
- pressurised car, shaping, 171
- pressurised nonrigid airship envelopes, materials
 - ideal for use in, 113–118
- pressurised system, total lift of, 390
- pressurised tube, rigid airship constructed of, 503
- Previous Generation of Very Large Rigid Airships (PGVLRAs)
 - GH methods, 296–297
 - GH systems, 296
 - problems actually encountered by, 285
 - vertical methods devised for GH, 292
- Previous Generation Very Large Airships (PGVLAs)
 - bases for, 316
 - constant referral back to real events and actual circumstances encountered by, 324
 - different GH methods tried and tested by, 297
 - many still in prototype stage, 316
 - none purpose-built to be sole freight-carriers, 320
- primary flight control system, of *SkyCat 20*, 470
- primary flight controls, 227–228
- primary flying control system, components of, 83
- primary sensor (radar), sizing, 420
- prime mover, choice of, 104–107

- principle stresses, in the envelope of a nonrigid airship, 634
- prismatic coefficient, of the envelope, 169
- private enterprise funding, of heavy lift airships, 693
- producers, of helium, 505
- product performance, compromise with cost, 117
- production team, shed events, 305
- profile drag, for HAVs, 682–683
- project team, determining the baseline design layout, 414
- projected area, 527–528, 529
- projectiles, minimising effects of damage from, 160
- Projet Sol'r*, schematic outline of, 486
- promotional, camera and sightseeing role, 440, 447
- Propbike (2004), 493, 622, 623, 624
- propeller(s)
 - approximate weight of, 226
 - axis of rotation, 110
 - blade pitch control on Zeppelin NT, 573
 - blades as twisted wings, 91
 - comparison of open with a ducted, 99
 - conventional, 403
 - disc loading, 89, 403
 - driving via gearing from the engines, 384
 - ducted, 98–103
 - efficiency, 381
 - as efficient propulsor for a slow vehicle
 - operating at low altitude, 90
 - induced power of, 93
 - interconnecting, 109
 - prediction and test results, 97
 - propulsion, 635
 - propulsion system, 635
 - propulsive efficiency of a conventional, 403
 - with reversing/vectoring facility, 274
 - shrouding with a duct, 226
 - sizing, 418
 - slipstream, 109
 - at the stern, 404
 - swivelling about a lateral axis to furnish vertical thrust, 17
 - theory, 635–637
 - torque, 92
 - vectoring thrust from, 290
 - wake, 101
 - wind tunnel test results, 98
 - of Zeppelin NT, 567
- propeller performance
 - comparison of theory and practice, 96–97
 - matching with engine output RPM and airship speed, 384
 - measured on a test stand, 96
- propelling power, overcoming dirigible's resistance, 633
- proposal, determining feasibility of, 212
- propulsion, for human-powered dirigibles, 619–620
- propulsion engines, vectoring thrust of, 109
- propulsion power, depending on envelope, 635
- propulsion system
 - components of, 87
 - conflicting factors when choosing, 105
 - geometry, 66, 67
 - location of, 221
 - producing thrust efficiently in the hover, 90
 - size governed by aerodynamic/thermodynamic considerations, 418
 - of *SkyCat 20*, 470
 - weight considerations, 223–227
 - weight plus fuel weight against duration, 383
 - of Zeppelin NT, 566–569
- propulsion thrust line, 431
- propulsion unit failure, in flight, 372
- propulsion units, of the Zeppelin NT, 549
- propulsion/airframe integration, as integral part of the conceptual process, 428
- propulsive efficiency, plotted, 90
- propulsive engine thrust, varying, 290
- propulsive force, equation for, 87
- propulsive power
 - available, 530
 - doubling of, 531
 - relating heat flow to, 395
 - total maximum available, 531
- propulsive units, vectoring vertically, 256
- propulsor, 87–103
 - entraining the flow around the hull, 109
 - location of, 224–225
 - positioning at tip of tail cone, 109
 - representing by an infinitely thin disc, 87
 - tail mounting of, 110
 - weight considerations, 226
- propulsor efficiency, improvement in, 225
- propulsor loading, for standard day conditions, 91
- proto-airships (1783-1899) era 1, 292, 309
- prototype CargoLifter, final format of, 664
- prototype engineering manpower, 411
- prototype microwave powered airship,
 - photograph of, 495
- prototypes, crashes of respective, 296
- PTFE, properties of, 129
- public perception, of airships, 448–449
- Pulham mast, 265
- pure airship, drag of, 480
- PVC, properties of, 128, 129
- PVDC Copolymer (DuPont's Saran), 120, 129
- PVF laminated materials, 130, 134
- pylon structure, mounting the propulsor, 222
- quality assurance measure, per ASTM standards, 116
- quality assurance tests, standards for, 117
- quality warp, with enough ends per sections, 116
- quasi-stationary trailing frontal band, 341
- Quasi-Unidirectional/Sentinel, creating highly orthotropic laminates, 116

- R-25, swivelling gear removed, 268
- R-26, towing trials of rigid by a tank at Pulham, 320
- R28, testing high mooring mast, 318
- R.30 metal-clad pressurised airship, 498
- R-31
 - manual handling of, 259
 - reversing gear on some engines, 268
- R-33
 - conclusion of trials of, 289
 - departing Cardington, 261
 - moored at its Pulham base, 265
 - most successful British rigid airship, 268
 - at Pulham mast, 266
 - reversing gear on some engines, 268
 - structural failure while moored, 259
 - testing high mooring mast, 318
- R-34
 - across Atlantic in 1919, 284
 - break-up on three-wire mooring, 284
 - flight of, 439
 - reversing gear on some engines, 268
- R-38
 - accident, 449
 - fragile, 496
 - loss of, 150
 - reversing gear on some engines, 268
- R-38, reversing gear on some engines, 268
- R100
 - 10 flights, 317
 - equipped with 6 engines of 670 HP, 268
 - landing of, 283
 - loading, 321
 - reception after transatlantic flight to Canada, 449
 - strongly built, 496
 - use of only 12 men in 1930 to moor, 308
 - volume of, 435
- R101
 - catastrophic demise, 268
 - crash in 1930, 296
 - disaster, 150, 449
 - loading, 321
 - at mooring mast, 267
 - riding out week of 60 mph (100 km/h) storm
 - force winds on High Mast at Cardington, 283, 316
 - strongly built, 496
 - ultimate British development of high level
 - mooring mast, 266
 - use of only 12 men in 1930 to moor, 308
 - volume of, 435
- radar, detection range of, 444
- radar cross-section (RCS), at various frequencies, 420
- radar developments, 444
- radar surveillance, 489
- radar system, selecting frequency of, 420
- radial velocity, 102
- radiation cooling inversion, 337
- radio frequencies, establishing for unmanned airships, 598
- radio frequency energy, applying, 117
- radio frequency RF welding, 117
- RAE 24 foot open jet wind tunnel, 97
- rail-mounted trolleys (laufkatzen), to hold airship's mooring lines, 320
- rain
 - altering buoyancy, 288
 - effects of, 197, 363
 - flying in moderate during free ballooning, 373
 - force effects of, 363
- rain curtains, fitting of, 363
- rainwater and condensation, collection and storage of from the hull skin, 16
- raised dais, building the balloon on, 310
- raised platform, inflation on, 313
- ram air, augmented by propeller slipstream, 240
- range, of Zeppelin NT, 552
- range diagrams, with all engines in operation, 553
- rapid descend, prior to landing excess lift generated, 670
- ratio of minimum to maximum projected areas, lowest value of, 528
- ray path, length in atmosphere, 522
- RC (Radio Controlled), 578
- RC (Radio Controlled) models, 581
- RC model airships, launching in a cluster, 589
- R/C model (Betty), small indoor, 646
- RC pilot, flying within certain boundary
 - limitations and altitude, 589
- RC type flight controller, for a pilot, 594
- RCS modeling, of targets, 420
- 'real' atmosphere, 10
- rear spar, constant depth, 179
- reballasting, in flight, 105
- receptive area, as projected area, 527
- rechargeable secondary fuel cell system, 540
- recoil damping, 183
- recovery phase, 262
- recovery systems, 248
- recovery temperatures, varying to condensation values, 248
- rectilinear flight, 61–63
- recumbent position, compared to upright for a human rider, 633
- reflected solar radiation, 523, 525
- refueling, 257, 568
- regenerative fuel cells
 - powered by thin solar cells, 584
 - simplified representation of, 540
- regional pseudo-Lagrangian field experiment, 557
- regulation, of airships, 449–450
- Rehmet, Michael, 483
- reinforcement, of the envelope, 218
- relative density, 191, 205
- reliability and maintainability (R&M)
 - characteristics, assessment of, 424
- relief valves, 162
- remote actuation system, 227–228

- remote control systems, modern airships fitted with, 180
- remote land stations, ferrying goods to, 584
- remote sensing and communication functions, for earthquake relief work, 692
- remotely piloted airships (RPAs)
 - advantage over manned airships, 509
 - unmanned, 509
- remotely piloted vehicles (RPVs), 509
- removable windows, as emergency exits, 256
- replenishing, airships, 257
- rescue boat, air to surface deployment of a semi-inflatable, 442
- research-cell efficiencies, historical development of, 536
- residual down-valley (katabatic) valley wind, 352
- resistance, of a streamlined body, 632
- response acceleration, 273
- response to control factor (aerodynamics/inertia), 671
- response to elevator, as predominantly pitch, 79
- response transfer functions, obtaining, 73
- restraint, only practical during very calm conditions, 152
- restraint attachments, large loads at, 261
- retractable scoops, 162
- reversal speed, 672
- reverse flow, preventing, 241
- reverse power, opposing yaw, 376
- reverse thrust, causing nose to pitch down, 374
- revolving shed, 315
- Reynolds number, 28, 54
- Rhine and Danube valleys, survey of, 608
- Rhone valley, Venturi effect in narrower and deeper parts of, 350
- ridges, of high pressure, 343
- right hand side (RHS), terms on, 65
- right-angled gearbox, accepting penalty of, 109
- rigid airships, 13, 149
 - (1899-1939) era 3, 292
 - built between 1900 and 1940, 496
 - carrying all external loading through a lightweight structural outer shell, 13
 - effectiveness increasing with size, 13
 - fitted with reversing propellers rather than vectoring, 268
 - much more in common with Montgolfiere smoke-balloons than blimps or gas balloons, 314
 - requiring different piloting techniques, 3, 358
 - structures not required by a nonrigid, 435
 - tending to be fragile, 150
- Rigid Class 23*, beyond prototype stage, 316
- rigid constructions, more suited for larger airships, 498
- rigid free-flying balloon, concept of, 314
- rigid internal structure, of Zeppelin NT, 549, 559
- rigid monocoque shell, consisting of a sandwich panel, 499
- rigid or semirigid design, flexibility in possible mounting points, 109
- ring aerofoil, 101
- rip panel, 245, 254
- rip strength, increasing, 136
- ripstop patterns, thicker or double yarns woven at intervals, 115
- risks, relying on calculation and simulation alone, 281
- Ritchel, C.F., 492
- river catchment flooding, in west and central England in July 2007, 341
- rivers, cities located on large, 349
- road substratum, immediate and continuous heat source, 348
- robot underwater vehicles, 445, 450
- roles, suitability for, 446–448
- roll oscillation mode, 81
- rolling moment, equations for, 64
- rolling takeoff, 369–370
- rolling tendency, of aerodynamic side force, 271
- roll-on/off system, 655
- roof cranes, 313
- Rosendahl, Charles E., 301
- rotastat hybrid airships, 472, 642
- rotastats
 - best suited as a flying crane, 463
 - configurations of, 472–477
 - described, 640
- rotatable propulsion unit, inertia of, 109
- rotating hulls, 477–480
- rotating mooring mast, used for British ‘Mayfly’ airship, 265
- Rotoflex test, specified in US military airship material specifications, 139
- rotor systems, distinguished from propellers, 275
- rough ride, running through bad weather, 328
- roughened substrates, producing higher efficiencies, 537
- Rousson, Stephane, 494, 623, 624
- roving commission type tasks, employment in, 454
- RPAs. *See* remotely piloted airships (RPAs)
- RPV (Remotely Piloted Vehicle), not implying aerial vehicle, 577
- rubber matrix, integration of nano-size carbon particle fillers into, 142
- rudder control, requiring large deflections to instigate a turn, 359
- rudder control power, as low, 80
- rudder zero, airship settling into a small but steady rate of turn, 40
- rudders
 - aerodynamically balanced on LZ N 07, 563
 - used for turning in deliberate manoeuvres, 18
- ruddervator, 32, 33
- Russia
 - carrying heavy loads to remote regions, 460
 - multi purpose semirigid airship, 502
 - need for heavy lift airships, 694

- providing transport for developing northern territories, 695
- safety
 - of airships, 437
 - factors of, 157–158
 - prescribed factors of, 158
- safety factor of 4, for envelope material, 633
- safety valves, 162
 - releasing gas to protect envelope against pressure rupture, 10
- SAIC, 472
 - 80,000 cu ft unmanned airship, 587
 - SKYBUS 30K unmanned airship, 590
 - SKYBUS 80K unmanned airship, 511, 582, 587
- sailcloth for high technology racing yachts, 140
- sand and dust storms, airship operations
 - encountering, 332
- sandbags with a net, anchoring and controlling inflation of gas balloons, 311
- satellite images, identifying and tracking storms, 338
- satellites, compared to airship platforms, 487
- satin weaves, providing less crimp, 115
- SATNAV, recent developments in, 362
- saucer airship, 460
- scalar wind, coming from any direction, 387
- scale model flying, effects of, 592
- scale model tests, translating to full sized counterparts, 597
- scaled models
 - of a much larger manned or unmanned airship, 586
 - of unmanned airships, testing, 592
- scaling, difficulty when modelling large, fragile and slow moving aircraft, 323
- scaling effects, on airships, 668–670
- scaling laws, different in various aspects, 678
- scantlings, lighter, 154
- scattered radiation, total contribution from, 530
- scattered sunlight contribution, estimating, 529
- scheduling model, breaking down against head winds for airships, 439
- Schoenherr’s line, skin friction drag co-efficient, 683
- Scientific Centre of Jülich, 557
- scientific low range photogrammetry, in Germany, 610
- scientific or industrial airborne platform, Zeppelin NT as, 555
- scoop operation, 228
- scoops
 - aft mounted, 241
 - located behind propellers, 240
 - retractable, 162
- Scott, George Herbert, 284
- Scott, Major, 319
- screen structure, as rudimentary and temporary shed, 313
- screw pickets
 - ground anchors, 318
 - for mooring mast cables, 342
- scrim, as load bearing component, 140
- scrubbing action, putting a heavy load across the tyres, 186
- sea anchor, designed to hold airship into wind, 155
- sea breeze
 - airship operations and, 353–354
 - crossing a large coastal city, 354
- sea breeze fronts
 - developing over land around mid-morning, 354
 - second following the first one inland, 354
- sea skimmer, 444
- sea surface temperature surveys, 346
- sealed envelope, choosing a material with low solar absorptivity to minimise overpressurisation, 488
- seams, designing, 167
- search and rescue role, 442
- Sears-Haack distribution method, 415
- seasonal timescale, 354
- seats, type and number of, 233
- second wave blimps (1940-2000+) era 4, 292
- secondary anchor winches, 658
- secondary batteries, 538
- secondary lows, rotating around one another, 341
- see and avoid
 - meeting level of safety, 600
 - by pilot, 599
- self-briefing, for airship pilots on meteorological information, 355
- semiconductor material, 533
- semirigid airships, 13, 502
 - combining features, 149
 - concept re-defined, 547
 - new concept of, 5
 - number built, 496
- sensor arrays, deploying stationary tethered, 445
- sensor payload, attaching to an airship, 586
- sensor platform capability, of airships, 437
- sensors and missions equipment, installation on Zeppelin NT, 565
- Sentinel 1000
 - air supply ducting for, 242
 - electrical block diagram, 250
 - envelope rip system and nose rip assembly, 255
 - examining, 453
 - fitted with an optically signalled primary flying control system, 83
 - fuel system layout, 246, 247
 - gondola of, 172
 - major improvement in flight control systems, 252
 - producing power from four engine-driven generators, 249
 - roll and pitch indicators, 252
 - valve used in, 244
- Sentinel 1000 and 5000 airships, differences between, 249

- Sentinel 1000 prototype airship, 82
- Sentinel 5000
 - 50 ton lifting capacity, 641
 - blowers achieving descent of, 240
 - compared to *ZPG-3W*, 498
 - ducts along top surface of the envelope for antifreeze solution to be pumped through, 255
 - effect of gondola on pressure distribution of, 31
 - electrical power distribution, 251
 - equipped with centre ballonets, 242
 - with forward, aft, and centre ballonets, 245
 - fuel tank arrangement, 246
 - hand operated winch to assure sufficient pulling power, 255
 - incorporating rain gutters, 249
 - internal engine installations, 253
 - in its military configuration utilising five generators, 250
 - lifting capacity, 512
 - upper envelope access trunk, 253, 254
 - water recovery system, 248
 - wind tunnel model with and without gondola, 31
- Sentinel design, replenishing station located in the middle of the car, 257
- ‘Serengeti shall never die’ expedition, in Tanzania, 609
- servicing arrangements, equilibrium control affecting, 150
- servo actuators, reducing pilot effort, 19
- severe mechanical turbulence, 330
- SFC. *See specific fuel consumption (SFC)*
- shaft speed, 104
- shaft turbine engines, 105
- shape, of the envelope, 457–459
- shaping filters, 83
- shear collar, 176
- shear force, defining, 676
- shear force inputs, 156
- shear forces, transferring to the envelope, 176
- shear load capability, driving structural design, 676–677
- shear properties, of envelope materials, 133
- shear stiffness
 - factor in tear propagation, 138
 - of gas retention component, 128
- shear strain data, need for reliable, 133
- shear stress, scaling, 676
- shed. *See also* hangar
 - aligning in direction of the strongest winds, 261
 - floating, 315
 - fully developed as a concept at many military bases, 314
 - for gas balloons, 314
 - rigid as an assembly jig, 315
- shed vortex wake, 25
- Shed-exit, incontestable GH procedure, 298
- sheet arrangement, required circulation to maintain, 94
- shell surface, constructed from corrugated aluminium sheet, 501
- Shenandoah
 - accident, 449
 - on the mast, 319
 - structural failure, 44
- ship-borne mast, as a documented success, 319
- ‘ships of the air,’ previous generation projects for, 307
- ships systems, fitting of, 223
- short takeoff and landing (STOL) ‘dynastat’ hybrid, 463
- shot storage, space for, 231
- side force, equation for, 64
- side gusts
 - airship on wheels vulnerable to, 433
 - airships turning away from, 291
 - applying full rudder and high thrust on the downwind engine, 369
- side stick control, instead of a control column, 252
- side-mounted propulsion units, of Zeppelin NT, 567
- sideslip response, 80
- sideslip subsidence mode, 76–77, 81
- Siemens-Schuckert ship, 315
- Sierra Nevada, in California, 353
- signal cables, to actuators, 228
- silicone, properties of, 128
- simplified three-point-bending, 676
- Simpson’s Rule, obtaining surface area, 217
- simulation models
 - dynamic, 184
 - extremely comprehensive, 2
- simulators, putting into the right context, 281
- single pilot operation, on Zeppelin NT, 571
- single point mooring
 - concept of, 265
 - major advantage of, 272
 - situation relevant to, 271
- Single Rotor Toroidal designs, 477
- sink, as negative source, 49
- sink and climb speeds, of Zeppelin NT, 551
- site and hangarage, of airships, 454
- size effects, of an airship’s structure, 152–153
- sizing, airships, 386–387
- sizing carpet, derived by running a fixed mission profile, 419
- sizing chart, initial, 387
- skin, varying porosity of, 110
- skin friction, 632
 - for a buoyant craft, 26
 - component, 401
 - contribution to total drag, 27
 - of the envelope, 633
 - predominant contribution to drag arising from, 415
- skin friction drag
 - coefficient, 27
 - contribution to hull drag, 682
 - described, 24

- dominating hull drag, 54
- increasing, 32
- minimum, 26
- as nearly 40 times the form drag, 401
- rising with increased wetted surface area, 154
- skin heat transfer coefficient, 395
- skin weight, for a US Navy Airship, 436
- SKS 500, 452
 - original landing gear, 185
- SKS 500HL, 452
- SKS 600, 452
 - gondola for, 172
 - manual handling, 454
 - at mooring mast, 152
 - unit price for, 453
- sky transport vehicle, transforming the LEMV into, 472
- SKYBUS 30K unmanned airship, 590
- SKYBUS 80K unmanned airship, 511, 582, 587
- SkyCat 20*, nonrigid Hybrid Air Vehicle, 469–471
- SkyCat 20 hybrid air vehicle, general arrangement of, 681, 682
- SkyCat 20 - SkyKitten 1*, scale model of, 469
- SkyCat concept, developed during 1999 by Advanced Technology Group (ATG), 468
- Skycat series, of concept design, 690
- SkyHook* (JHL-40)
 - neutrally buoyant, 475, 644
 - operating in Canadian Northern Territories, 475
 - in polar heavy lift application, 644
 - rotary-airship hybrid, 690
- SkyHook rotastat, 642–644
- SkyKitten 1*, 469
- SkyKitten 2*, 469
- Skylab role, 441, 447
- SkyLifter airship
 - designed for heavy lift, 513–515
 - flying a portable hospital, 692
 - impression of, 514
 - mooring options for, 647
 - suited for emergency humanitarian relief and ongoing health service delivery, 692
- SkyLifter SL150, 645–647
- Skyship*, 9m radio-controlled model built by Thermo Skyships, 459
- Skyship 500, total airship drag coefficient of, 34
- Skyship* 500 and 600 series
 - from Airship Industries, 17
 - envelopes same strength in warp and weft directions, 121
 - single ply polyurethane coated fabric, 120
- Skyship* 500 G-BIHN, landing in light wind conditions, 366
- Skyship* 600
 - 1:75 scale models of, 54
 - 24 hours endurance or more, 436
 - delay of several seconds between control application and airship response, 358
 - with a fly-by-light control system, 585
 - fuel consumption figures for, 362
 - pressure distribution around, 55
 - rain values for, 363
- Skyship* 600 G-SKSJ, on takeoff, 364
- Skyship 600 model
 - comparison of CFD calculations & wind tunnel results for 1/75 scale, 55
 - pilot tests on, 55
- Skyship airships, symmetrical propeller arrangements, 109
- Skyship SK600, drag penalty, 27
- SLAB (Static Lifting Aerodynamic Body), 477
- slender body theory, 40–42
- slip tanks, 245, 247, 248
- slipstream, increasing deflection of, 109
- slipstream scoops, 677
- slosh. *See* ballonet slosh
- sloshing, 245
- slot suction, permitting freestream flow, 111
- slow flight, capability of, 559
- Small Aerostat Surveillance System, Low Intensity Target Exploitation airship, 510
- small airships
 - configured for light aerial duties, 173
 - for pilot training, 172
- small blimps, proliferation and dominance by Goodyear, 316
- small perturbation equations of motion, analysis of, 72
- small perturbation motion, 70–71
- small perturbations, 69
- smallest unmanned airships, altitude of, 588
- SMART (Space and Airborne Mine Area Reduction Tool), 556
- smoke-balloon inflation technique, inflating a gas balloon, 314
- SN 006, delivered, 605
- SN 0057, under construction, 605
- snow
 - effects of, 197, 364
 - high reflectance of, 525
 - producing collapse of the landing gear or cause the airship to roll on its side, 255
 - types of, 364
- Sodium-Sulphur battery, weight of, 544
- software, of GH, 279
- solar airships
 - HALROP, High Altitude (Japan), 486, 489, 490
 - Lockheed Martin, High Altitude (USA), 490, 491, 492
 - Lotte, Unmanned (Germany), 671
 - Nepheios Projet Sol'R, Manned (France), 484, 485, 486
 - Projet Sol'R (France), 485, 486
 - Sunship, 521
- solar airship
- solar airships, storage units for, 538–543
- solar altitudes
 - determining contents of the ballonnets, 523
 - at sea level, 523

- solar azimuth, angular distance of Sun from true north, 526
- solar cells, 533–538
 - air-cooling of, 533
 - characteristics of, 533–535
 - connecting in parallel, 535
 - connecting in series, 535
 - conversion efficiency, 531
 - conversion efficiency of, 482
 - efficiencies, 535
 - efficiency of, 535–537
 - on the *Nephelios*, 484
 - power output, 535
 - recharging electrical storage device, 594
 - relative efficiency of, 536
 - schematic diagram of, 534
 - types of, 537
 - weight, 543
- solar constant, 523
- Solar Egg* drone, built by Tokyo-Sanyo Co. Ltd., 483
- solar energy
 - attractive in an environmentally conscious age, 482
 - available, 529–530
 - spatially distributed, 520
- solar incidence, angle of, 525–527
- solar power
 - for airships, 481–486
 - speed function of solar cell efficiency, 531
- solar power system
 - components of, 533–545
 - efficiency of, 530
 - outline of, 522
 - replacing fuel and engines of a conventional airship, 543
- solar powered flight speed, versus cell efficiency, 532
- solar powered high altitude airship, 490
- solar radiation, 521–525
 - on upper walls of skyscrapers, 349
- solar/electrical system, weight of, 520
- solar-powered airships
 - advantages of, 520
 - as constant weight vehicles, 482
 - defined, 520
 - designated *LOTTE*, 483
- solar-powered flight speed, 525–530, 532
- solar-powered radio-controlled test models, flown in the Nevada desert, 483
- Solent, first crossing by a human powered dirigible, 620
- solid-polymer electrolyte cells, potential advantages over phosphoric acid cells, 541
- sonobuoy barrier or search patterns, deploying and monitoring, 445
- source panels
 - geometry of, 51
 - model hull and the vortex-lattice panels for the fins, 50
- South Asia, tsunami in 2004, 686
- South Downs, in England, 354
- South Indian Ocean, more tropical cyclones in, 346
- Southampton University, wind tunnel results, 97
- sovereignty enforcement role, 443, 448
- Spacial MLA-32-B Toluca*, 460
- ‘spanwise’ limits, of a lifting body, 25
- SPAS-4* spherical airship, 462
- specialists in inflation (the Preparers), 309
- specialty weave patterns, optimizing fabric performance, 115
- specific fuel consumption (SFC)
 - for cycles, 104
 - for each engine, 382
 - as a function of power, 105
 - versus power curve, 381
 - of the three cycles, 105
 - variation with power, 104
- specification, with ranked objectives, 580
- Spectra. *See* high performance polyethylene (HMPE)
- speed
 - acceptable for tourist and cruise applications, 531
 - as damped response to variations in power input, 531
 - as design driver, 588
 - increasing requiring higher internal pressure, 675
 - upper limit for an airship, 18
- speed attribute, of airships, 436
- speed change, as dominant response to thrust, 79
- speed hold, relieving pilot of monotonous flying tasks, 83
- speed response, to thrust, 73
- sphere, minimum surface area for a given volume, 26
- spherical balloon, fitted with four variable-incidence radial wings, 477
- spherical form, offering smallest surface area and lowest skin tension, 9
- spherical shape
 - proposed for lift efficiency and cost, 462
 - providing optimum lift efficiency, 458
- spin finish, on yarn, 116
- spinneret, 119
- spiral cloud bands, 340
- spiral clouds, active weather zones, 339
- spiral frontal cloud bands, 340, 342
- Spirit of the Forest*, 493
- square/cube growth law, governing displacement airships, 433
- square-cube law, 272, 671
- SS class, 452
- SSZ class, 452
- St. Petersburg, Russia, islands supporting closed thermal circulation, 350
- stabiliser
 - problems with an elevated, 407

- raised clear of the boundary layer on two (or more) vertical fins, 407
- stability
 - of HAV, 684
 - problems of panel or member, 153
- Stability Augmentation System (SAS), 252, 510
- stability characteristics, at the hover, 82
- stability modes
 - approximate and exact comparing very well, 77
 - approximate comparing with the exact solution, 77
 - approximate description of, 74, 76
 - marginally stable at the hover, 82
 - root describing, 74
- stacked cells, having up to 11 layers, 535
- stainless steel, properties of, 142
- 'stall,' if nose-up angle exceeds a critical value, 18
- stalling characteristics, 97
- standard atmosphere, density at pressure height, 204
- standard items, 210, 233
- standard operating procedures (SOPs), 117
- standard sea level, value for gravity, 204
- standardised gas volume, calculation of, 372
- standing vortices, 330
- Starship* Small Rigid Airship, 498
- state equation
 - classical, 69, 71
 - solving to obtain response transfer functions, 72
- state matrix, numerical behaviour of, 74
- state space form, equations in, 70
- static buoyancy, of any kind of body in the atmosphere, 8
- static electricity discharge, possibility of, 258
- static equilibrium, attaining in major emergency situations, 360
- static head effect, of lifting gas, 163
- static heaviness (SH), 193, 359–361, 588
 - assessment of at pressure height, 236
 - changing during free ballooning, 372
 - determining the current, 360
 - higher requiring a higher power setting, 368
 - known at takeoff, 360
 - requirement to reduce quickly, 231
 - supporting by vertical component of thrust, 367
 - wet snow adding to, 364
- static heaviness/lightness, requiring appropriate up/down thrust, 376
- static lift, 192. *See also* buoyancy
 - equation for, 390
 - not as constant in operation conditions as could be expected, 669
- static lift or weight, balancing the excess by an externally applied vertical force, 17
- static lightness
 - no problem with takeoff distance, 360
 - requiring increased approach speed, 375
- static loads, resulting from overpressure of lifting gas, 634
- static pressure
 - coefficient, 399
 - decreasing over the nose region, 24
 - increasing over the gondola, 31
- static trim, 201, 673
- static trim angle, at pressure height, 372
- station keep, 367–368, 597
- stationary mode, accurately positioning in, 262
- stationkeeping. *See also* hovering
- stationkeeping velocity, minimizing, 487
- statistical approach, example using component analysis, 417
- statistical method, of weight determination, 417
- Statistical Process Control (SPC), 116
- steady aerodynamic forces, 23
- steady flow simulation, variables considered, 53
- steady flow testing, 53–55
- steady force conditions, for a moored airship, 269
- steady stream
 - represented by parallel streamlines along flow direction, 49
 - stream line flow about a source in, 50
- steady turning flight, 38–40
- steady-state analytical model, schematic of, 42
- steel fibre, properties of, 125
- stern handling beam, 292
- stern propeller, required diameter of the single, 404
- stern propulsion, 403–405
 - aerodynamic mechanism of, 403
 - proportional reduction in power requirement, 404
 - reducing power requirement for large airships, 404
 - reduction in power requirement using, 404
 - tests inconclusive, 405
- stern-beam, 295
- Stewart, Keith, 466
- Stewart's 4-rotor rotastats, 474
- stiff shell design, skin stabilised by double curvature at all points, 498
- stitching, necessary to prevent joins from slipping apart, 118
- STOL hybrid airship, losing important VTOL capability, 464
- storage, of ballast, 231
- storage batteries, low energy-to-weight ratio of, 481
- storage systems, comparison of, 542
- storage units
 - key parameter as energy density, 544
 - potential energy densities of, 545
 - for solar airships, 538–543
- stored energy, withdrawing from a secondary battery, 539
- storms
 - forecasting, 337
 - region subject to travelling, 343
 - severe tropical and mid-latitude, 332
 - understanding and avoiding, 337–338

- stowage, for ballast, 231
- Strategic Airlift Fleet, 694
- stratocumulus clouds, 344
- stratosphere, requiring larger airships, 588
- stratospheric airships, 486
 - intended to stay aloft for a year or more, 579
 - needing solar cell technology to mature, 594
- stratospheric operations, materials challenges, 593
- stratospheric platforms, for mobile phone networks and broadband internet, 584
- streamline bodies, drag of, 29
- streamline form, of the envelope, 13
- streamlines
 - equation of, 36
 - from a source, 49
- stream tube, slope of, 102
- strength reserves, scrutinising to minimise weight, 156
- stress concentrations
 - keeping to a minimum, 167
 - at the tear tip, 138
 - unrelieved, 126
- stress intensity factor function, 137
- stress level, for envelope material, 678
- stress-strain properties, of envelope materials, 132–133
- strip theory curves, compared to experimental results, 97
- strobe lights, 220
- structural analysis, 3
- structural configuration, variations in, 496–503
- structural damage, repairing in flight, 154
- structural design
 - damage-tolerant principles, 153
 - difficult to produce a satisfactory lightweight, 258
 - factors driving, 673–677
- structural fragility, of airships, 153
- structural groups, principal, 159–187
- structural loads, lack of knowledge of, 258
- structural techniques, for gondola design, 172
- structural weight, of gondola structure, 221–223
- structure weight, excess, 156
- structures
 - of CargoLifter CL 160, 660–661
 - as design driver, 593–594
 - groups of, 149
 - of a laminate, 122
- stub mast, 292
 - coupled to, 295
- stub wings, 662
- subarrays, of solar cells, 535
- subassemblies, percentage analysis of major, 217
- subclutter visibility (SCV) limit, 421
- submerged sonar carrying bodies, towed by airships, 445
- suction
 - applied through an annular slot by a ducted propeller, 402
 - removing most of boundary layer, 110
- sun
 - altering buoyancy, 288
 - apparent motion of, 526
 - area projected by parallel rays, 528
 - as giant helium factory, 504
- sunlight, as renewable, free, non-polluting and non-inflammable fuel, 482
- sunny climates, significant speeds achieved from solar power alone, 481
- sun’s position in the sky, calculating in terms of solar altitude and solar azimuth, 526
- sunshine, effect of, 365
- Sunship* solar-powered airship, 521
 - effect of time of day, season and orientation of, 533
 - example calculations for, 483
 - outline of, 482
 - power-speed relation of, 532
 - projected area against the angle of solar incidence, 529
- super pressure, of the envelope, 160
- superconducting applications, coolant for, 505
- supercooled droplets, impacting with the envelope, 331
- superheat, 197
 - accounting for effects of, 197
 - changing during free ballooning, 372
 - contained gas at a different temperature, 192
 - effect of, 206
 - estimating for takeoff, en route and for landing, 365
 - extreme case of deliberate, 13
 - necessary to be unaware of, 206
 - present even on cloudy days, 365
 - reduced by rain, 363
 - reduced by smoke, dust, water vapour and clouds, 365
 - reducing balloonet volume, 16
 - temperature effect, 13
- superheat values, determining, 252
- superheating
 - developing much slower on large airships, 670
 - on the ground increasing lift, 385
 - highest values of, 365
 - in the solar airship, 537
- supply chains, resilience for disaster relief and readiness, 688
- surface area
 - approximation for, 217
 - for balloonets, 218
 - determining as accurately as possible, 217
 - of the envelope, 169
- surface communications, impeded during emergencies, 441
- surface friction drag, 400
- surface reflectance, 525
- surface vessel, carrying items required, 257
- surface wind, often calm by dawn, 337
- surge mode, 74, 79, 80
- surge mode pole, 79

- surveillance patrols, maintenance of standing, 442
- surveillance role, for unmanned airships, 581
- survey conditions, airship system in a wide variety of, 559
- survey role, 441, 447
- survivor recovery, by rescue winch, 442
- suspended load, shared between an internal catenary system, 16
- suspended weight, critical design criterion for airships, 210
- suspension cable array, twisting, 655
- suspension cables, 174
- suspension mechanism, of an airship, 462
- suspension point
 - in the airship, 653
 - hunting of, 653
- suspension system, 218
 - to assist with assembly/preparation and support, 313
 - details, 216
 - preventing excessive distortion of the envelope, 16
 - sizing, 214
 - supporting prior to and during assembly/inflation, 313
- swirl velocity, representing loss of propulsive momentum, 93
- swivel
 - joining upper and lower decks, 654
 - omitting for CargoLifter, 655
- swivel mechanism, consisting of hydraulic actuator on Zeppelin NT, 572
- synthetic materials
 - development of, 118
 - introduction of, 118–121
- system components, establishing characteristics, 419
- system engineering
 - approach, 625
 - methodology, 424
 - purpose of, 424
- system support features, Zeppelin NT, 556
- systems
 - for airships, 3, 691
 - defined, 239
 - developing around some stated mission, 624
- systems engineering process, 625, 628
- tail, designing to be grounded, 295
- tail arrangements, typical, 18
- tail drag, compared to bare hull drag, 31, 32
- tail group, 177–180, 219–223
- tail lift coefficient, 44
- tail structures
 - designing to accommodate counter weights, 156
 - weight of, 220
- tail surfaces
 - arrangement, 178
 - guyed in place fairly simply, 180
 - loads, 150
 - producing negative lift, 47
 - structural arrangement, 179
- tail thruster, installation, 369
- tail wheel, as helpful, 370
- tailfin rigging, 220
- tail-strike
 - avoiding during landing, 374
 - preventing, 370
- takeoff
 - determining amount of lift due to superheat, 207
 - distance increasing with heaviness, 360
 - heaviness, 379
 - improved by vectored thrust, 367
 - manoeuvre by the pilot, 369–371
 - methods of, 369
 - roll, 369
 - run path, 370
 - technique used to develop aerodynamic lift, 262
- takeoff gross weight, estimating, 417
- tank volumes, of Zeppelin NT, 568
- TAR (Transport Airship Requirements), 590
- target modeling, representing a series of low radar cross-section vehicles, 420
- targets, RCS modeling of, 420
- TBO (To Be Overhauled), increasing for airship applications, 595
- TCAS (Traffic Collision Avoidance System), 599
- TCOM company, spherical features promoted by, 462
- tear propagation
 - in coated and laminated textiles, 139
 - data obtained from uniaxial testing as sufficient, 139
 - deriving a theory for, in coated fabrics, 138
 - problem of, 138
 - rapid, 136
- tear resistance, 114, 135–139
- tear strength
 - demonstrating by test, 158
 - maximising, 158
 - measurement of, 135–137
- tear testing, uniaxial and biaxial, 138–139
- tearing, qualitative effects of, 135–136
- technical feasibility, of solar-powered airships, 520
- Technical University Aachen, wind tunnel of, 612
- technology
 - existing to build airships for disaster relief, 693
 - interdependence, 427
 - learning, 450
 - potential of new, 411
 - trends in, 425–427
- Tedlar fabric, 128
 - in Zeppelin NT, 562
- TEDLAR proprietary material, 455
- tee chest, 228
 - Sentinel 1000, 243
- tee-tail aerofoil, 434

- temperature
 - effect on pressure height, 385
 - inside the envelope higher than ambient air temperature, 197
 - variation with altitude, 189
- temperature inversions, effects of, 363–364
- temperature rise, reducing pressure height, 393
- tensile modulus, of polyester, 119
- tensile structures, for large span roofing, 138
- Terminal Area Forecasts (TAFs), for the route, 329
- terminal phase, dominant in accidents, 433
- terminology problem, creating wrong impressions to novices to LTA flight, 298
- terrestrial factors, controlling low-level airflow patterns, 347
- territorial waters, protection of national interests in, 443
- test flying, not mixing well with commercial operations, 315
- test machines, for biaxial stress, 132
- test platform, unmanned airships as, 585–586
- tether, second located near stern, 265
- tethered aerostats, as astronomical platforms, 487
- tethering arrangement, becoming necessary, 650
- tethering cable, 653
- tethering methods, alternative, 660
- tethering system, for an active grame, 657
- textile engineering, 3, 113
- textile fibres, exhibiting microfibrillation properties, 119
- textile materials
 - desirable properties for airship, 113–118
 - tearing strength of, 135
- ‘Textile Research Laboratory,’ of University of Chemnitz, 615
- textiles
 - application of fracture mechanics approach to, 138
 - development for airship use, 118–131
- Textron Lycoming IO-360/200hp engines, 568
 - on Zeppelin NT, 568
- themes, of this edition, 1
- thermal activity, avoidance seldom easy, 331
- thermal efficiency, of engines, 105
- thermal plumes, 349
- thermal turbulence, 330
 - increasing over cities, 348
 - much less predictable, 330
 - over the centre of a large city, 349
- thermals
 - airship flying amongst, 331
 - fewer over water surfaces during daytime, 331
 - multiple daytime, 335
 - reducing size and depth of, 335
- thermodynamic cycles, number of, 104
- thermodynamic efficiency, secondary fuel cells operating at, 540
- thermodynamic equilibrium, between lifting gas and outer air not established, 669
- Thermoplane* Russian lenticular design, 460
- Thermo-Skyships, model ‘saucer,’ 20
- thermotropic liquid crystal polymers, 126
- thickness, compared to radius of a circle, 676
- thickness ratio
 - adjusting, 49
 - of a body, 26
 - variation of drag as, 27
 - variation of form & skin friction drag with, 29
- thread spacing, effect of, 136
- thread strength, affecting tear strength, 136
- threats, changing, justifying continued design efforts, 411
- three-wire mooring system, 284
- thrust
 - controlled symmetrically and synchronously, 67
 - equation for, 89
 - found by integrating over the length of the lifting blade, 92
 - generating, 635
 - produced at the propeller, 98
 - produced by the duct, 99
 - role in sizing of engines, 418
 - total, 98
- thrust coefficient, against advance ratio, 97
- thrust equation, as an ideal number, 637
- thrust gain, 403
- thrust line, facility to vary, 432
- thrust pitching moment, 673
- thrust transfer function, speed response to, 79
- thrust vector system, ideal, 366
- thrust vectoring
 - achieving, 256
 - degree of, 366
 - required to remain on station, 368
 - of Zeppelin NT, 569
- thruster system
 - complication of placing a fan at, 110
 - form of internal power driving, 274
- thrust-lift ratio, 672–673
- thumbprint plot, examining all possible solutions, 412
- Thunder & Colt Balloons UK
 - first fan pressure hot-air airship, 508
 - first pressurised hot-air airship, 602
 - twin-seater AS 105MK2, 603
- thunderstorms, avoiding at all costs, 345
- time history, of a circular cylinder’s pressure distribution, 42
- time varying pressure (or velocity), at a point, 45
- time scale
 - of about 5 days ahead, 354
 - of next 24 hours, 354
- tip effects, considering for thick wings, 683
- Titan* (235m dia), lenticular design, 459
- titanium, properties of, 125
- toilet installations, for passengers, 233
- topographic obstructions, 350
- Toroidal Balloon Concept, Canadian, 477
- Toroidal Semi-Buoyant Station, Japanese, 477

- Toroidal 1-rotor airship designs, 478
- total available energy, 531
- total current, generated by a solar cell, 534
- total efficiency, 531
- total energy, falling on the Sunship, 530
- total engine thrust, in rectilinear flight, 62
- total incident velocity, 94
- total lift, obtaining, 25
- total lift augmentation
 - Category C, 432
 - characteristics of, 434–435
- total power, produced by the cell in a load, 534
- total solar radiation, at ground level, 523
- total speed, in rectilinear flight, 61
- total velocity, three components in steady flight, 62
- tourist flights, in LZ N 07, 555
- trade studies
 - as part of the design process, 421
 - process, 413
- translational airship configuration, sensitivity to crosswinds, 405
- trailing vortex pattern, 25
- training, of airship pilots, 357
- training courses, in meteorology for airship pilots, 355
- transfer function, 57
- transient aerodynamic forces, 23
- transition point position, variation of total & skin friction drag with, 28
- translational and rotational inertia, versus size, 670
- translational inertia, from the mass of the ship, 670
- translational movement, suppressing on a larger airship, 670
- transmission systems
 - complex, 226
 - mounted directly in line with propulsor, 224
 - simple, 226
 - weight considerations, 226
- Transmit/Receive (TR) modules, illustrating number of, 421
- transponder, not all airborne vehicles mandated to carry, 600
- Transport Airship Requirements, Contents List of first draft of, 298
- transport infrastructures, damaged from natural disasters, 691
- transport systems, comparison of, 466
- transport task, airship providing best compromise for, 648
- transport vehicle, P-791 Hybrid Air Vehicle as, 690
- transportation vehicle, needed to fly over
 - geographical barriers, 687
- triaxial fabrics, woven with three sets of yarns, 116
- trilaminate, permeation of, 134
- tri-lobe hull, created for HAV, 469
- tri-lobe lifting body form, pressure-stabilised structure of, 469
- trim equilibrium, 65, 66
- trim function, of ballonets, 562
- trim panels, weight of, 222
- trim states, variety of possible, 291
- trimmed axes notation, 62
- trimmed equilibrium flight condition, small perturbations about, 67
- trimmed equilibrium thrust, 67
- trimmed steady rectilinear flight, 61
- trimming
 - accompanied by a drag penalty, 595
 - to achieve a positive or negative angle of attack, 248
 - compensating for extremes of static heaviness or lightness, 375
 - important in aerodynamic landing, 374
 - required to get the airship level, 201
- troops, moving large number of, 688
- tropical climate, reaching a given pressure height in, 12
- tropical rotating storms, severe, 346–347
- troposphere, 189, 336
- tropospheric research, European lead role in, 557
- true thickness, of a boundary layer, 400
- trunks. *See* duct(s)
- tsunami
 - in Japan in 2011, 687
 - in South Asia in 2004, 686
- tubing, of filament-wound fibreglass, 397
- tunnel structure, model attached to, 53
- turbine engine exhaust, low water in suspension in, 380
- turbine engines
 - advantage for short duration flights, 382
 - in airship applications, 223
 - poor SFC at low power, 381
 - water recovery from, 231
- turboshaft engines, for all power sources, 661
- turbulence
 - design and calibration of the scale of, 56
 - random including discrete gusting, 269
 - response to each component, 45
 - stern propeller performance less than ideal, 405
- turbulence induced lift, distribution of, 48
- turbulence layer, climbing higher out of, 362
- turbulence results, response of, 57
- turbulent conditions, airship combining several movements simultaneously, 291
- turbulent flow, characteristic of, 45
- turbulent layer, growing in thickness along the hull, 399
- turbulent velocities, 46, 56
- turntable, omitting for CargoLifter, 655
- 12 MQ-9 Reaper class fixed-wing unmanned aircraft, 471
- 28V DC systems, current standard on many small airships, 249
- twill weaves, providing less crimp, 115
- twin hover cushion landing system, 681
- Twin Rotor hybrids, 476–477

- twin-hull airships, 462, 475
- Twist-Flex conditioning procedure, 139
- two-deck passive system, replacing by a single-deck active load frame, 654
- Type I crack opening, 137
- Type II crack opening, 137
- Type III crack opening, 137
- typhoons, 347. *See also* tropical rotating storms
- UAS airships
 - electric burn ring, 598
 - encompassing all classes of powered LTA vehicles, 587
- UAV systems, telemetry from, 598
- UHMWPE (Dyneema, Spectra), properties of, 142
- UK airship No. 9, direct derivative of No. 1, 267
- UK CAA CAP 722 Unmanned Aircraft System Operations in the UK Airspace*, 589
- UK Civil Aviation Authority, 449
- UK coastal shipping, protecting against submarine attack in World War I, 432
- UK winter wind speed versus altitude, 488
- ultimate acceleration factors (g's), 158
- ultraviolet light, leading to deterioration of strength filaments of fabric, 455
- unconventional, defined, 457
- unconventional designs, of airships, 19–22
- unconventionality, attributing to an airship, 5
- underway replenishment (Unrep), 213, 231
- uniaxial and biaxial tear testing, 138–139
- uniaxial slit tensile tests, giving unrepresentative results, 139
- uniaxial tensile strength, 132
- unit heat release, volume and weight required to produce, 107
- unit lift, of the combination of gas in the envelope and air outside it, 9
- unit thrust, power needed to produce, 91
- United Kingdom, development of mooring masts, 265
- United States, masts developed in, 266
- United States Air Force (USAF), high-altitude reconnaissance and surveillance platform, 491–492
- universal gas constant, for air, 396
- University of Newcastle, Australia, Faculty of Engineering, 620
- University of Stuttgart airship ‘Lotte,’ difficult to handle with changing solar radiation, 670
- unmanned aerial systems (UASs), 511, 577
- Unmanned Aerial Vehicle (UAV), 577
- Unmanned Aircraft System (UAS)
 - no formal dedicated qualifications for an unmanned aircraft pilot, 589
 - normally regarded as a piston or jet driven vehicle, 578
 - as preferred term, 577
- unmanned airships, 509–511, 577–600
 - as aerial advertising platforms, 581
 - certification activities, 589
 - design drivers for, 6
 - determining contents of the ballonets, 596
 - flying at a higher pitch, 579
 - flying heavier, 588
 - flying passengers, 584
 - limitations on, 581
 - for low altitude and high altitude applications, 6
 - potential roles for, 580–587
 - providing own see and avoid capabilities, 599
 - sizes of, 579
 - terminating flight of, 598
- unpowered landing, with no ground crews or mooring facilities, 254
- unsolved GH problem, universal acknowledgement of, 299
- unstable vehicle, configuring to make it stable, 579
- unsteady aerodynamics, 44–48
- unsteady flow
 - response of the vehicle to required, 53
 - testing, 56–57
- upper deck, remaining suspended directly from the airship, 652
- upper suspension pulleys, height within the load bay, 654
- up-ship method, of takeoff, 369
- UPship* semirigid airship design, 502
- up-ship takeoff, 371
- upthrust, applied to stabilise frame position, 653
- up-valley (anabatic) wind, 352
- up-valley air trajectories, becoming spiral in form, 351
- upward buoyancy force, 8
- urban airflow patterns, causality of, 348
- urban canyon, airflow accelerated by a Venturi effect, 348
- U.S. Army contract, to build three airships to float over a front line for up to three weeks, 690
- U.S. Department of Defense, considering Logistics Lift Airship technologies development, 688
- U.S. Navy, deficiencies in implementing MCM role, 451
- U.S. Navy, needing 157 men to ground handle the ‘Los Angeles,’ 321
- U.S. Navy Aegis ships, phased array radar of, 444
- U.S. Navy airship ZMC-2, 134
- U.S. Navy airships in World War II, searching for surfaced U-boats, 437
- U.S. Navy E2c Hawkeye carrier based aircraft, 444
- U.S. Navy rigid airships, 253
- U.S. Navy rigids ZRS-4 and 5, propulsive units vectored vertically, 256
- U.S. Navy YEZ 2A design, laminate materials in, 130
- U.S. Navy ZPG series airships, 245
- U.S. Navy ZPG-2/2W airships, cylindrical tanks mounted on the envelope, 246
- U.S. Navy ZPG-2W and -3W airships, servicing and inspection of topside radar equipment, 253

- U.S. Navy ZPG-3W, equipped with two, 1,150 gallon (U.S.) tanks, 245
- U.S. Navy's airships, apparent all-weather capability of, 328
- U.S. ODM programme, designated YEZ-2A, 172
- useful load, Zeppelin NT, 552, 555
- U.S.S. Akron. *See* Akron (1931–33)
- U.S.S. Los Angeles, drag breakdown, 30
- U.S.S. Macon, drag breakdown, 30
- UV light, stronger at higher altitudes, 593
- vacuum pumps, powered from engines, 110
- valley wind, 351
- valve functioning, reliable as essential, 244
- valve opening area, equation for, 242
- valve opening pressure, 244
- valves
 - externally mounted, 245
 - fill and purge installed in forward and aft ends of the envelope, 253
 - large diameter required to achieve flow rates, 242
 - manual operation of, 244
 - permitting differential inflation of front and rear ballonets, 16
- valves and fittings, requiring penetrations in the envelope, 162
- van Dusen project, generating powered lift, 434
- Van Treuren, Richard, 506
- vapour trails, of high flying aircraft, 25
- variable buoyancy
 - as a generic physical GH problem, 286–287
 - in *Varialift*, 502
- variable masses, located within the gondola, 171
- Varialift* aluminium clad airship, 7, 499, 502, 645
- vector angles
 - reduced to zero on landing, 378
 - selecting, 370
- vector systems, weight of, 226
- vectored landing technique, 375–378
- vectored takeoff, 370–371
- vectored thrust, 4, 389, 469, 681
 - classes of, 109
 - employing for limited climb or descent, 367
 - of HAV, 641
 - landing airships with, 334
 - necessary for ground handling phases, 259
 - overcoming heaviness, 360
 - required by CargoLifter, 650
 - swivelling propellers creating on Zeppelin NT, 566
 - uses of, 366–368
- vectored thrust airships, 433
- 'vectored thrust' system, 17
- vectoring propeller principle, first demonstrated on 'Gamma,' 267
- vectoring systems, achieving a degree of vertical thrust, 257
- vectoring thrust, decreasing effect with increased size, 672
- vectors, returning to the horizontal as airship attains flying speed, 370
- Vectran fibre, 126
 - excellent choice for airship applications, 127
 - properties of, 125, 142
 - strength of, 119
- Vectran HT, 127
- Vectran HT filament yarn, 127
- Vectran UM, properties of, 125
- vehicle configurator, 414
- vehicle life, strong turbulence and, 47
- velocities, incident on the blade section, 91
- velocity discontinuity, avoiding, 100
- velocity potential, for any circular section, 40
- vent valves, 162
- vertical acceleration, power spectrum of, 560
- vertical displacement, needing to be large, 185
- vertical forces, resolution of, 269
- vertical instability, atmospheric, 330
- vertical landing
 - described, 378
 - the lost technique, 282
- vertical mooring method
 - acceptance of, 284
 - for large airships in the future, 282
- vertical profiles, fast measurements of, 558
- vertical railway, lowering airship to the ground, 319
- vertical surface, synchronised to operate like a conventional rudder, 65
- vertical tailfins, deviation is resisted by fixed, 18
- vertical takeoff and landing (VTOL) capability, 463
 - advantages of, 642
 - maintaining at penalty costs in cruise efficiency and fuel requirements, 472
 - of Zeppelin NT, 566, 569
- vertical takeoff and landing (VTOL) 'rotastat' hybrid, 463
- vertical thrust, applied as required during transfer, 656
- vertical tunnels (trunks), allowing personnel to reach top of the envelope, 253
- vertical velocity from turbulence, changing sign at the centre of the hull, 46
- very high endurance attribute, 436
- Very Large Airships (VLAs)
 - automated alignment of, 320
 - GH, evolutionary process of, 285
 - most successful ground handling system for, 322
 - no totally successful all-weather mooring system for, 322
 - planned new generation of, 280
 - situation different than for the blimps, 318
 - very few attempts at operational hardening of, 319
- Very Large Crude Carriers (VLCCs), pushing sideways by tug boats, 286
- V-form twin burner, 604
- VHF radio to Air Traffic Control (ATC), 598

- violent updrafts and downdrafts, encountered in line squalls, 693
- virtual inertia
 - of an airship, 184
 - effect, 82
- virtual mass and inertia, 63
- virtual reality, models and simulations, 280
- viscosity
 - of air, 24
 - of water, 24
- viscous effects, making allowance for, 41
- visual facilities, adding smoke trails to airflow, 635
- VLAs. *See* Very Large Airships (VLAs)
- volume
 - of an airship, 416
 - crossplotting against weight available for fuel, 386
 - of the envelope, 169
- volume adjustments, accommodating internally, 239
- volume change rates, equation for, 240
- volume flow
 - conservation of, 88
 - required in a fast descend, 677
- von Gablenz, Carl, 513
- vortex, size exceeding dimensions of the airship, 330
- vortex circulation, conserved, 49
- vortex elements, forming line vortices along the length of the body, 42
- vortex lattice panel, geometry of, 51
- vortex panels, continuing across the hull
 - representing lift carry-over, 50
- vortex rings, strength of, 100
- vortex roll-up, behind a propeller blade, 96
- vortex sheets, spacing between, 94
- vortex wake, 95, 96
- vortices
 - concentrated trailing behind and below the propeller, 95
 - extending downstream to infinity, 50
- V/STOL aeronautical spectrum, 463
- V/STOL aircraft, lessons learned from, 425
- V/STOL Spectrum, 465
- VTOL capability. *See* vertical takeoff and landing (VTOL) capability
- wake
 - contraction, 95
 - forming, 24
- wake diameter
 - immediately behind the tail, 403
 - smaller, 405
- wake radius, 400
- Walden, Michael, 483
- walking out, of sheds, 264
- Wallis, Barnes, 319
- Wallis, Barnes Neville, 284
- WALRUS project, 690
- warm front, cloud band ahead of, 344
- warp and weft, pattern of interlacing in a woven fabric, 114
- warp and weft yarns, interlaced, 116
- warp knitting, creating fairly open weave structures, 116
- Warwick Mills, providing hull fabric, 472
- washing line method, preferred initially, 311
- waste heat, available from propulsion system, 396
- water
 - collecting from the envelope, 231
 - as most common ballast material, 248
 - needing to be disposed at pickup site and similar quantity supplied, 654
 - operation from less likely to cause severe up and down gusts, 267
 - over the envelope and tail surface area adding to the mass, 363
 - picking up from surface, 231
 - produced as a by-product of combustion, 248
- water ballast
 - capacity on *SkyCat 20*, 471
 - getting rid of as quickly as possible, 657
 - hoses for transfer of, 652
 - protecting against freezing, 248
 - tank on Zeppelin NT, 565
- water recovery system
 - alternative to, 380
 - condensing moisture suspended in engine exhaust, 231
 - fitting, 231
 - incorporating, 380
 - involving cooling engine exhaust gases, 248
 - occupying considerable amount of space, 232
 - sensitive to maintenance problems, 249
 - techniques, 598
- water tanks, for water ballast, 231
- watertight buoyancy chambers, of the gondola, 155
- Watson, Bill, 620
- WDL Luftschiffgesellschaft mbH, German airships built by, 241
- WDL-1 airship JA1005, on takeoff, 361
- weapons, Mother ships carrying, 585
- weather
 - aspects of, 363–365
 - avoiding bad, 328
 - favorable for airship operations, 333–337
 - as a generic physical GH problem, 287–288
 - optimising use of local, 347–348
- weather conditions
 - operating in bad, 693
 - vagaries of, 259
- weather effects, 197
 - as heaviness, 360
 - variables related to, 197
- weather forecast, requirement for airship operations, 338
- weather hazards, effects of, 4
- weather processes, airship pilots needing to develop own understanding of, 337

- weather radar, avoiding hazards, 693
- weather satellite pictures
 - interpreting on a daily basis, 339
 - skills to interpret, 338
- weather window, of opportunity for an airship, 344
- weather zone, of the atmosphere, 336
- weathercocking
 - around the mast, 19
 - into the wind direction, 272
- weathering component, of laminate materials, 128–130
- weather-sensitivity, of airships, 328–329
- weave, affecting sleaziness of fabric, 136
- weave design patterns, 114–117
- weave patterns, 115
- weigh-off, steps in, 235–236
- weight
 - of a collector grid network, 538
 - as critical aspect of structural design, 496
 - design considerations for, 212–214
 - as design driver, 588
 - percentage of empty to gross, 496
 - predesign considerations, 212
 - progressive loss as fuel is consumed in flight, 16
 - of the propulsion system plus required fuel for typical mission, 224
- Weight & Balance document, weight from, 235
- weight and balance handbook, 237
- weight aspects
 - of airship design, 677–678
 - of airship operations, 236–238
- weight configurations, definitions of various, 209–211
- weight considerations, for solar-powered airships, 543–544
- weight data, selecting, 384
- weight determination, statistical approach to, 417
- weight empty trend, 418
- weight estimates and control, during all phases of airship design, 2, 209
- weight estimation, 214–234
- weight limitations, difficult to achieve, 155
- weight monitoring and control, 234
- weight penalty
 - of a competently executed vectoring system, 434
 - for increased envelope strength, 391
- weight reduction
 - attributable to improvements made in envelope materials, 426
 - due to advanced technology, 426
- weight trend, 426
 - typical for 1970s, 426
- ‘Weightlifter’ airship, in the 1970s, 689
- weights, estimated for major elements of configuration, 428
- weights discipline, differing from other design disciplines, 417
- weights engineer, ensuring that knock-on effects concerning weights are raised, 223
- weights group, working in absolute terms, 417
- Wellman telescoping mast, 316
- Westinghouse, Sentinel 1000 taken over by, 453
- Westinghouse airships
 - diameters of valves used in, 244
 - driving propellers through long shafts, 256
 - improved design for ballonet shape, 245
 - internal engine installations, 253
 - knife-edged cutter used, 254
 - propulsive units vectored vertically, 256
- Westinghouse Sentinel 1000, fans providing descent rate, 240
- wet snow
 - encountering, 364
 - tending to freeze on contact and adding tonnes of weight, 331
- wetted (surface) area, corresponding plot of, 415
- wetware, 279
- wheeled dolly rail-mounted, 292, 295
- wheeled undercarriage, need for, 183
- White Dwarf (1985), 620, 621
 - design data, 624
 - human-powered airship, 492
 - one man airship, 440
 - propeller design critical to, 637
- whole design, minimisation of the drag, 31
- winches. *See also* anchor winches
 - constant tension, 653
 - equipping with approximately 1000 feet of cable, 257
- wind
 - adding to difficulties, 291
 - counteracting or negating effects of, 311
 - designing airship to align itself freely with, 151
 - effects of, 361–362, 387–388
 - landing in light or calm, 374–375, 376
 - landing in light unsteady, 376–377
 - landing in moderate, 375, 377–378
 - landing in strong, 375, 378
- wind conditions, great concentration required in turbulent or gusty by the pilot, 369
- wind direction, change of with altitude, 362
- wind effects, 269
- wind screen, for envelope during inflation, 312
- wind shear, at operating altitudes, 332
- wind speed
 - impact on thruster effectiveness, 666
 - stronger than cruise speed, 329
 - for takeoff and landing, 362
- wind strength, ground handling with increased, 368
- wind tunnel
 - experiments at Aachen Technical University Departments, 614
 - forward speed tests, 96
 - simplest using air at atmospheric pressure and temperature, 53
 - sophisticated, 54
 - testing, 53–55
 - testing envelope shape, 635

- wind variations, 262, 263
- windows, weight of, 222
- wing, lift of an aircraft produced almost entirely by, 26
- winged and lifting body concepts, 20
- winged and lifting body projects, 21
- winged-hull dynastats, 467
- winter anticyclonic situations, 363
- winter weather, problem for airships on the ground, 255
- Wood, David, 620
- wood-based NanoCrystalline Cellulose, typical properties of, 141
- Woodward criterion, 676
- work done per unit time, by force T, 90
- World War I
 - 200 airships accepted into service, 448
 - methods measuring strength developed during, 135
 - Zeppelins, 322
- World War II, 200 airships accepted into service, 448
- wounded burst test, controlling crimp balance, 136
- wounded tensile strength, increasing, 136
- woven fabric, coated and laminated, 117
- woven glass fibres, fabrics made from, 126
- wrinkles, avoiding for the envelope under all conditions, 675
- wrinkling, resisting, 498
- yarn lubricity, promoting thread slippage and distribution of loads, 136
- yarn smoothness (or roughness), affecting loads carried by threads, 135
- yarn twist, secondary effect, 136
- yarn-on-yarn abrasion resistance (AR), comparative testing of, 127
- yarns, schematic diagrams of cowoven/comingled, 115
- yaw control, Zeppelin NT, 567, 568
- yaw perturbations, in ground phases, 433
- yaw rate response
 - dominated by yaw subsidence mode, 81
 - to rudder transfer function, 74, 80
- yaw rates, decreasing airspeed owing to increased drag, 359
- yaw subsidence mode, 76, 81
- yaw-guy booms
 - mooring mast complete with, 319
 - potential for, 319
- yawing moment, equations for, 64
- YEZ-2A
 - 1:75 scale models of, 54
 - 1/200th scale model, 56
- YEZ-2A airship programme, for Airship Industries Ltd., 84
- YEZ-2A maritime patrol airship
 - choice of CODAG installation for long endurance missions intended for, 106
 - CODAG (COmbined Diesel And Gas turbine) power-plant installation, 106
 - stern turbo-prop unit only used for specific phases of flight, 106
 - for U.S. Navy, 661
- YEZ-2A model, spraying polyurethane hull with a grey paint, 55
- YEZ-2A of Westinghouse Airships Inc., exhaust water condensation proposed for, 17
- YEZ-2A test programme, 55
- Young's work, theoretical compared to Hoerner experimental evidence, 29
- Zeppelin, Count, 263, 264, 314, 315, 439, 452
- Zeppelin [LZ3 (Army Z1)], successful landing on the ground instead of on water, 307
- Zeppelin airships, new generation of, 547
- Zeppelin captains, encountering strong turbulence, 48
- 'Zeppelin Luftschiffbau' (LZ), 547
- Zeppelin Luftschifftechnik GmbH & Co KG, 547
 - certified as maintenance shop, 547
 - patented technology, 559
- Zeppelin LZ 07, one gas cell filled with helium, 562
- Zeppelin LZ N 07, as research platform, 557
- Zeppelin LZ1, volume of 400,000 cubic feet, 435
- Zeppelin New Technology (Zeppelin NT), 547
 - structure, 503
- Zeppelin NT
 - aft and forward landing gears, 566
 - aft propulsion unit, 568
 - applications suited to, 557–558
 - ballonets, 562–563
 - basic structure, 559–562
 - cabin, 556, 564–565
 - characteristics of, 551
 - cockpit, 564
 - combining design principles of a blimp and a rigid airship, 5
 - comparison with helicopter or airplane, 556, 557
 - design principles of, 550
 - dimensions of, 550
 - electrical systems, 573–574
 - electronic flight instrument system (EFIS), 571–572
 - engines, 568
 - envelope, 121, 562–563
 - equipped with three propulsion units, 549
 - flight control, 569–570, 571
 - in flight over Germany, 548
 - flight performance data, 550–555
 - fuel system, 568–569, 570
 - fuel tank on, 569
 - fuselage, 559–563
 - general description, 548–550
 - general features, 555–556
 - gondola, 564

- ground operation of, 574–575
- hydraulic systems, 572–573
- instrument panel, 572
- interior structure of, 500
- landing gear, 565–566
- lateral and aft power plants on, 567
- longeron/frame connection points, 503
- longerons, 561
- mechanical support features, 556
- mooring position, 575
- passenger cabin layout, 565
- produced between 1997 and 2007, 547
- projected, 110
- propeller, 567
- propulsion system, 566–569
- rigid frame of, 560
- rigid internal structure of, 561
- side-mounted propulsion units, 567
- simpler framework in, 498
- skeletal structure in, 499
- system support features, 556
- vectored thrust propeller on, 567
- Zeppelin NT 07
 - mission platform in EC programme SMART (Space and Airborne Mine Area Reduction Tool), 556
 - passengers in, 555
- Zeppelin NT-07, with dynamic multi-axis control, 334
- Zeppelin operations, in the 1930s, 328
- ‘Zeppelin Reederei,’ certified as an airship operator, 547
- Zeppelin structures
 - comparison of historical and current, 548
 - reduced concerning number of elements and parts, 548
- Zeppy 1 (1985), 622, 624
- Zeppy 2 (1992), 622
- Zeppy I* (France), human-powered airship, 492
- Zeppy II* (France)
 - human-powered airship, 492, 493
- zero pressure disposable lift, lift reduction as a proportion of, 391
- ZMC-2, built in 1929 by Metalclad Airship Corporation, 501
- ‘ZMC-2’ metalclad airship, 14
- Zobel, Chris, 688
- ZPG2, carrying very large antennae, 437
- ZPG-2/2W series, 253
- ZPG3, carrying very large antennae, 437
- ZPG-3W
 - 40 ton lifting capacity, 641
 - carrying a 40 ft. span antenna, 437
 - envelope, 119
 - gondola partially inserted into lower envelope, 173, 177
 - helium valves located in the car, 244
 - largest nonrigid airship ever built, 124
 - largest nonrigid airships flown, 498, 512
- ZR1 (Shenandoah)
 - 19 day circuit of USA, 319
 - recorded flights for, 317
- ZR5 (Macon), recorded flights for, 317
- ZRS-1, tower-top connection system for use with, 319
- ZRS4, experiences on sea-borne mooring system, 319
- ZRS-4, flying aircraft carrier, 321
- ZRS4
 - Lakehurst home base, 320
 - moored to expeditionary masts at Camp Kearney and on board *Patoka*, 319
- ZRS-5, flying aircraft carrier, 321
- ZRS5, Sunnyvale home base, 320
- Zylon, 126, 142
- Zylon AS, properties of, 125
- Zylon HM
 - properties of, 125