

Index

Note: “t” after page number denotes a table; “f” after page number denotes a figure

- Δ wing, 375
- α -floor protection, **54**, 57, 234
- λ -shock, 219
- g-load, 362, 374
- 331-600 APU, 148

- Accelerate-go, 240
- Accelerate-stop, 227
- Acoustic power, 486
- Acronyms, xxv–xxviii
- Admittance, 538, 539
- Advance ratio, 154
- Aerodynamic derivatives, 114, 191
- Aerodynamic heating, 294
- After-burning, 127, 143
- Agility, 360
- Aileron, 376, 379
 - authority, 376
 - effectiveness, 377
 - yaw control, 187, 190
- Air conditioning, 147, 211
- Air traffic control, *see* ATC, 332
- Airbus, 263, 303, 316, 322f
 - A300, 25f, 134, 303, 349t, 440
 - Beluga*, 47t
 - CG asymmetry, 186
 - cross-sectional area, 31f
 - deterioration drag, 102
 - fly-over, 512
 - fuel temperature, 401f
 - ground effect, 82f
 - tyre temperature, 417
 - wetted area, 33t, 38t
 - wing lift, 80f
 - A319
 - fuel tanks, 62t
 - go-around, 323
 - mass properties, 73t
 - A320, 27, 52–53, 349t
 - cabin floor, 71f
 - climb, 279f
 - CO₂ emissions, 604, 605f
 - continuous descent, 308t
 - descent, 308f
 - elevator deflection, 185f
 - flap angles, 305t
 - flight envelope, 213f
 - flight in downburst, 386
 - fuel tanks, 62t
 - heat release, 599
 - holding, 315
 - L-gear noise, 516f
 - landing, 320f
 - LTO emissions, 603t
 - MAC, 35t, 36f
 - mass components, 73t
 - mass properties, 73t
 - noise guarantee, 465
 - noise stacks, 582
 - noise trajectory, 568f, 573–575f
 - perfect flight, 607–608
 - tankering, 445f, 447f
 - trim drag, 185f
 - weight versions, 52
- A330, 349t
 - fuel tanks, 62t
 - gliding range, 312
- A340, 349t, 460
 - CG limits, 58f, 59f
 - CG position, 56f
 - contrail experiment, 597
 - fuel tanks, 62f, 62t
 - mass properties, 73t
- A380, 7, 67, 425
 - altitude flexibility, 594
 - APU, 148
 - downwash, 117
 - drag, 104
 - drag sensitivity, 105t
 - ground effect, 82f

- Airbus (*cont.*)
 ground manoeuvre, 262f
 jet blast, 418
 mass properties, 73t
 span constraint, 47
 taxi-out fuel, 261t
 water load, 51
 wetted area, 33t, 38t
 wing-body, 28f
 winglet, 29
 A400, 47t
 propellers, 157t
 payload-range, 427f
 Aircraft accidents
 Airbus A330, 3
 B777 Heathrow, 400
 bird strike, 262
 tyre explosion, 409
 volcanic ash, 138
 Aircraft size, 33, 45
 Aircraft state, 564
 Airfoils
 icing, 395f
 NACA 0012, 108
 NACA 00XX, 79
 NACA 23012, 93
 NACA 6 series, 93, 107
 perimeter, 23, 23t
 SC-1095, 107
 Airlines, 2, 423, 425, 449, 594, 608
 Airport, 419, 555, 601
 Gatwick, 554
 Heathrow, *see* Heathrow
 London City, 561
 New York JFK, 448
 noise restriction, 554f
 Schwerin-Parchim, 575
 Airworthiness, 4
 Airy-Fock functions, 545
 Alenia C-27J, 156
 Altitude
 flexibility, 593, 598
 Altitude effects
 on atmosphere, 198f
 on SAR, 337f, 337
 ANSI
 noise absorption, 535–537
 noise metrics, 472t
 Antonov AN-225, 47t
 Appleman-Schmidt criterion, 595
 APU, 71, 147–149, 434, 562, 567
 emissions, 148t
 fuel flow, 148f
 in fuel planning, 435
 mass, 71
 noise, 475, 508
 Aquaplaning, 101, 249f, 321
 Area
 cross-section, 23, 30
 reference, 20
 wetted, 24–29
 Argon, 487t
 Armstrong's line, 211
 ATC, 315, 329, 332, 584, 598, 606, 609
 ATR72, 173f, 338
 drag polar, 104
 icing, 393
 mass properties, 73t
 noise footprint, 579f
 noise trajectories, 571f, 570–572
 payload-range, 430, 431f
 SAR charts, 338f
 take-off, 244
 Available-seat-km (ASK), **451**
 Aviation fuel, 397
 Aviation records
 Ily'a Murometz (1914), 45
 Axial momentum theory, 157
 BAE RJ 146, 311, 561
 Bank angle
 turn, 361
 with thrust asymmetry, 186
 Banked level turn, 361
 Barred owl, 584
 Bernoulli equation, 157
 Bessel functions, 505, 519, 546
 Bird strike, 262–263
 Black box, *see* FDR
 Block fuel, 329, 340
 Block time, 425
 Blumer-van Driest theory, 91
 Boeing, 399
 B727, 147, 554
 tyre temperature, 416
 B737, 554
 cabin pressure, 211
 L-gear noise, 516f
 landing gear, 516
 mass properties, 73t
 stabiliser, 22f
 wing, 20
 wing-body, 28f
 B737-900
 winglet, 29
 B747, 6
 -100 stability derivatives, 190
 control speed, 191f
 cross-sectional area, 32f
 drag, 103f
 equal-time point, 448
 forebody, 26
 jet blast, 418
 lateral control, 191f
 mass properties, 73t
 mission fuel, 439f
 payload-range, 427f
 range, 428f
 taxi-out fuel, 261
 ULD, 47
 vortex wake, 595

- WAT charts, 320f
 - wetted area, 33t, 38t
- B747, ramp weight, 49
- B777, 453, 507, 563
 - 200-IGW, 50
 - CO₂ emissions, 604f
 - flight levels, 348
 - fuel tanks, 33
 - fuel temperature, 408f
 - ground effect, 82f
 - mass properties, 73t
 - mission sensitivity, 604
 - SAR effects, 353
 - tyre temperature, 416
 - wetted area, 33t, 38t
- C-17 Globemaster, 47t
- MD-90, 507
- Boeing projects, 46
- Bombardier Dash8-Q400, 73t, 156, 171
- Brakes, 66, 73t, 249
- Braking, 248, 321
- Breguet range equation, 346
- Broadband noise, 480, 485, 515, 521
- Buffet
 - boundaries, 113
 - speed, 113
- Busemann biplane, 116
- Buzz-saw, 483

- Cabin pressure, 210, 211, 214
- CAD formats, 17f, 17, 254
- Calibrated Air Speed, 205
- Caravelle, 409
- Carbon-dioxide, CO₂, 487t
- Carbon-monoxide, CO, 601
- Cargo load, 52
- Cargo performance index, 47
- Case study
 - AEO take-off, 234
 - aircraft drag, 103
 - ATR72 payload-range, 430
 - ATR72, SAR, 338
 - CG effects on SAR, 353
 - Climb to specified Mach, 293
 - CO₂ emissions, 604
 - drag of Airbus A380-861, 104
 - drag of ATR72-500, 104
 - F4 wind-tunnel model, 102
 - F568 propeller, 165
 - flight envelopes, 215
 - fuel planning, 455
 - General Electric CF6-80C2, 134
 - go-around, A319, 323
 - Gulfstream G550, SAR, 335
 - heat released in atmosphere, 599
 - Honeywell RE-220 APU, 149
 - moments of inertia, 73
 - noise trajectories, A320, 568
 - noise trajectories, ATR72, 570
 - payload-range, float-plane, 460
 - range sensitivity, 429
 - spherically blunted ogive drag, 112
 - Turboprop PW127M, 143
 - wetted areas, 36
- Case study: Do aircraft float?, 32
- CASK, **453**
- Ceiling
 - absolute, 208, 210
 - operational, 213
 - service, 211
- Centre of gravity, 51, 68, 189
 - envelope, 53
 - in flight, 55
 - percent of MAC, **35**
 - range, 352
 - travel, 54
- Certificate
 - airworthiness, 4
 - noise, 553
 - safety, 381
- Cessna 180, 259
- CF6-80C2, 138, 139f
 - engine data, 135t
- CFM56, 134f, 137, 323, 607
 - emission indexes, 602f
- Chapman-Rubens factor, 88
- Cirrus clouds, 591
- Climb
 - continuous, 607
 - en-route, 169
 - ICAO A profile, 273
 - ICAO B profile, 274
 - ICAO Standard profile, 273
 - minimum-fuel, 296
 - minimum-time, 296
 - polar diagram, 292
 - supersonic, 294
- Climb angle, 278
- Clouds, 138, 200, 380, 591
- Cockpit, 4
- Cold soak, 396
- Combination tone noise, 481
- Combustor temperature, 138
- Computer models
 - configuration change at climb, 276
 - accelerate-stop, 240
 - equal-time point, 448
 - fuel tankering, 446
 - laminar skin-friction drag, 89
 - landing-gear drag, 99
 - propeller integration, 168–170
 - propeller trim at take-off, 242
 - stochastic area, 22
 - turbulent skin-friction drag, 91
- Concorde, 127, 218, 554
- Contamination, 250, 321
- Contrail, 589–591
 - factor, 595
- Control points, 17, 621
- Coriolis acceleration, 37
- Corner velocity, 366

- Cost index, 351–352
- Crab landing, 320, 321
- Cruise
 - climb, 343
 - in fuel planning, 435, 436
 - propeller aircraft, 346–347
 - subsonic, 341–346
 - supersonic, 353–355
- Cruise-climb, 607
- CTOL, 224
- Data handling
 - engine, 140
 - noise, 565
- Decelerate-stop, 239
- decibel, **471**
- Density altitude, 197
- Derating, 129, 248
- Descent
 - continuous, 307–308, 607
 - en-route, 170
 - steep, 308–311
 - unpowered, 311
- Dihedral, 21, 25, 95, 322
- Dihedral effect, 186
- Direct Operating Costs, 353
- Directivity, 480, 481f, 481, 483, 485t, 488f, 488, 497, 498, 510, 514, 515, 517f, 521, 522
- Discrete-tone noise, 480
- Displacement thickness, 522
- Distrails, 592
- Diversion distance, 440
- DOC, 448–453
- Doppler effect, 483, 484, 488, 520, 565
- Douglas DC-10, 87
- Douglas DC9-80, 113, 114
- Douhet, Giulio, 7
- Downwash, 116, 181, 185, 383, 584
- Dowty propeller, 156, 157t
 - R381, 157t
 - R391, 157t
 - R408, 157t
- Drag, 85
 - body of revolution, 110
 - cavity bays, 98
 - contamination, 100, 251
 - displacement, 100
 - fuselage, 92
 - fuselage upsweep, 93
 - hull, 115
 - idle engine, 190
 - impingement, 253
 - interference, 94
 - landing gear, 96
 - landing-gear struts, 98
 - lift-induced, 85
 - profile, 87, 99
 - sensitivity analysis, 104
 - spoilers, 95
 - spray, 101, 254
 - trim, 183
 - wave, 93–95, 116
 - wheels, 97
 - wing, 88
- EASA, 508
- Eckert reference temperature, 88
- Efficiency, 153
 - propeller, 153
 - propulsive, 596
- Elevator, 73t, 182, 183
- Emission angle, 477–478
- Emissions, 615
 - CO₂, 604
 - LTO, 600–604
- Emissions Trading, 608
- En-route stop, 443
- Endurance, 329, 341
- Energy
 - acoustic, 471
 - impact on landing, 263, 317
 - method, 285–288
 - potential, 287
- Energy height, **287**
- Engine
 - contamination, 138
 - design point, 133, 134f
 - failure, 186
 - installation effects, 137
 - rubber, 137
 - spool-up, 306
 - state, 140
 - strike, 321
 - surge, 220
 - wash cycle, 140
- Engine strike, 321
- EPNL, **472**, 472t
- Equivalent Air Speed, EAS, 205
- Equivalent all-out range, 440
- Equivalent continuous sound level, 561
- Equivalent Noise Level, **475**
- Equivalent Source Method, 533
- Estimated time of arrival, 447
- ETOPS, 147, 439, 463
- Exhaust-gas temperature, 127, 129, 135t, 508, 509
- F4 wing-body, 35, 37t
- F568 propeller, 157t
 - altitude effects, 167f
 - disk loads, 164f
 - geometry, 165f
 - shaft power, 167f
 - taxi conditions, 169f
- Faddeeva function, 540
- FADEC, 127, 135, 171, 617
- Fastest climb, 291
- FCOM, 3, 50, 214, 235, 236, 319, 335, 418, 464, 561
- FDR, 2–3, 400, 407, 408f, 408, 564
- Figure of merit, 331, 337
- Fineness, 94, 112

- Flaps, 73t, 81, 83
 - Fowler, 617
 - Kruger, 30
 - racks, 30
- Flare, 257, 321
- Fleet, 52
- FLIGHT code, xxiv, xxix, 73, 166, 227, 335, 369, 371, 386, 444, 446, 448, 572, 575, 582
- Flight Data Recorder, *see* FDR
- Flight envelope, 211–215
 - supersonic jet, 218
- Flight levels, 332, **332**, 347, 348f, 348
- Flight management system, *see* FMS
- FLIGHT program, 624–625
- Flight stacks, 315
- Flight testing, 2
- Float-plane, 115, 259
 - payload-range, 460
- Flowchart
 - aerodynamic drag, 86f
 - aircraft systems, 18f
 - CG calculation, 64f
 - engine model, 131f
 - environmental challenges, 610f
 - FLIGHT code, 11f, 14f
 - mass distribution, 64f
 - mission fuel, 432f
 - noise sources, 476f
 - propeller code, 12f
 - propeller simulation, 155f
 - turbofan engine noise, 479f
- FMS, 302, 305, 352
- Focke Fw-190 (Wulf Condor), 6, 379
- Fokker
 - Anton, 8
 - F-100, 259
 - F-50, 259
 - F27, 157t
 - F50, 157t
- Fuel, 397
 - contingency, 440
 - cost, 4, 433
 - density, 399
 - diversion distance, 440
 - heat capacity, 399
 - jettisoned, 50
 - loiter, 440
 - mission, 444
 - planning, 426
 - price, 328
 - temperature, 398
 - temperature in flight, 400
 - undrainable, 51
 - unusable, 440
 - vector, 54
- Fuel tanks, 33, 61, 72
 - use, 63t, 353
- Furnishings, 67
 - mass, 67, 71
- Fuselage
 - cross-section, 30–31
 - forebody, 25
 - inertia, 69
 - mass, 65
 - tail, 26
 - wetted area, 25
- Gas turbine, 126
- Gavotti, Giulio, 7
- Gearbox, 143, 165, 171, 175
- Global Forecast System, 201
- Go-around, 323
 - thrust recovery, 131f
- GP-7000 engine, 127, 443
- GPS coordinates, 564
- Grashof number, 404
- Gravity suit, 374
- Green dot speed, 277, **303**, 304, 315
- Green function, 519
- Ground effect, 84, 256
- Ground operations, 260
- Ground reflection, 538
- Grumman F-104, 189
- Gulfstream G550, 215, 617–621
 - APU, 149
 - cabin pressure, 211
 - cockpit, 4
 - figure of merit, 337
 - flight envelope, 215f, 620f
 - ground effect, 82f
 - landing gear, 618
 - mass properties, 73t
 - operational limits, 619t
 - payload-range, 428–429
- Hague Convention, 7
- Hamilton-Sundstrand, 143, 165, 166f, 167f
- Hankel functions, 505
- Hartzell propellers, 157t
- Heathrow airport, 1, 315, 448, 554, 555, 557t, 606
- High-lift devices, 30
- History
 - aircraft icing, 392
 - military aircraft, 7–8
- Holding, 439, 440
- Humidity, 196t, 426, 557, 595, 597
- Hydrocarbons, HC, 601
- Hydrogen propulsion, 591
- Hydroplaning, *see* Aquaplaning
- Hysteresis, 412
- IATA, 328
- ICAO, 196, 316, 439
 - atmosphere, 197
 - climb profiles, 273–274
 - databank, 601, 602f
 - environment, 594
 - ISA, 200f
 - LTO emissions, 600, 601
 - LTO flight modes, 602t

- ICAO (*cont.*)
 noise, 510, 572
 noise certification, 555, 556f, 558
 pavement, 50
 unit of risk, 463
 wake separation, 118t, 584
- Iceland volcanic eruption, 138
- Icing, 392, 394
 propeller, 165
- Ideal gas equation, 196, 203
- Ily'a Murometz, S-27, 45
- Immelmann, Max, 8
- Impact pressure, 204
- Impedance, 535, 538, 539, 541
- Indicated Air Speed, 205
- Inertial coupling, 374
- Inertial particle separator, 143
- Initial value problem, 278
- Inlet, 126, 132, 480, 482, 486, 487, 508
- INM program, 564
- Installation effects, 137
- Intake, *see* Inlet
- Intake buzz, 218
- Interrupter gear, 8
- Italian Air Force, 7
- Jet
 co-axial, 491
 Fisher model, 491–494
 fully mixed, 492
 plug, 496
 Stone model, 494–500
- Jet blast, 418
- Jet shielding, 501–507
- Jet stream, 200, 338
- Jet-A fuels, 398, 398t, 399, 400, 404, 408
- KLOC, xxiv
- Landing
 flare, 321
 instrument, 300, 303
- Landing gear, 96–100
 Gulfstream G550, 620t
 installation, 99
 mass, 66
 noise, 512
- Lift, 78
 augmentation, 81
 curve slope, 83, 106, 107, 108
 ground effect, 79
 spoilers, 95
 wing, 79
- Lockheed, 45
 382J, 156
 C-130, 6
 C-130J, 47t
 C-130J with floats, 461f
 C-5A, 189
 C-5B, 47t
- Constellation, 210
 SR-71, 210
- Loiter, 315, 440
- MAC, *see* mean aerodynamic chord
- Mach number
 design dive, 65, 207
 economic, 350–352
 long range, **334**
 maximum range, **334**
 structural design, 206
 tip, 152
- McDonnell-Douglas
 F-15, 270
 F-15E, 218
 F-4, 270, 296, 329
- Mean aerodynamic chord, **34**, 180
- Messerschmidt Me-262, 285
- Methane, 600
- Microburst, 380
- Military Standards, 199
- Mission
 failure, 4
 planning, 424
 reserve fuel, 438
- Molecular mass, 487t
- Moments of inertia, 68–72
- MTOW, 3, **48**
 versus payload, 47
 versus wing-span, 46
- Nacelles, 28–29
- NADP, 274
- Nitrogen oxides, NO_x, 601
- Nitrogen, N₂, 487t
- Noise
 absorption, 535
 certification, 553, 555
 certified levels, 622t, 623t
 data handling, 565
 footprint, 578, 580
 ground reflection, 538
 microphones, 557
 night curfew, 556
 shielding, 533
 tax, 559
- Noise directivity, *see* Directivity
- Normal load factor, **271**, 276, 293, 361, 372
 1g flight, 362
 turning, 369
- Noy, **473**
- Nozzle, 126, 127, 135, 142, 190, 501, 503, 504
 APU, 147, 509
 fuel, 143, 144
- NTSB, 409
- Nuclear power, 45
- Nusselt number, 404, 413, 414
- Ogive, 110–112
- Optical thickness, **590**

- Optimisation, 4, 278, 347
 Owl technology, 584
 Oxygen, 487t
- Passengers, 45, 52, 54, 57, 61, 67, 72, 431
 Payload-range, 426–429
 calculation, 430
 float-plane, 460–463
 Peng-Robinson equation, 404
 Perfect flight, 606–608
 Phugoid, 313
 Piaggio Avanti, 157t, 174
 Pitching moment, 60, 181, 229, 234
 Pitot probe, 203
 Point performance, 330
 Polar diagram, 292
 Power, 130, 137
 APU, 147
 coefficient, **154**
 ratings, 128–129
 Predictor-corrector, 437
 Pressure
 acoustic, 471
 impact, 204
 stagnation, 203
 standard atmosphere, 196t
 Pressure altitude, **202**
 Profile drag, *see* Drag
 Propeller
 247F, 157t
 advance ratio, 153, 154
 coefficients, 154
 Dowty R391, 156
 efficiency, 153
 electronic control, 156, 165
 F568, 165–168
 failure, 244
 installation effects, 173
 intake, 173
 mass, 71
 pitch, 152, 165
 wing interference, 173
 Pull-out, 293
 Pull-up, 293
 PW F-100, 143, 146f
 PW127M, 60, 143, 244
 residual thrust, 171f
 PW980A APU, 148
 Pylons, 28–29
- Radar, 263
 Radiative forcing, 599–600
 Radiosonde, 199
 RAF, 7
 Raleigh equation, 205
 Ram compression, 127
 Range equation, 339
 Ray tracing, 534
 Rayleigh number, 404
 RE-220 APU, 149
- Redispatch, 441
 Reference system, 18, 37
 noise trajectory, 564
 Reflection-only method, 534
 Republic R-4, 379f
 Riemann integral, 116
 Risk analysis, 463–465
 Roll, 374–379
 Roll rates, 379
 Rolling
 coefficient, 255, 255t
 damping, 377
 moment, 186, 375
 Rolls-Royce
 AE-2100DE engine, 6
 BR710 engine, 617, 619t
 Olympus-593, 127
 Rubber engine, 137
 Rudder, 73t, 187–191
 Runge-Kutta methods, 257, 407
 Runway, 50, 101, 261, 317, 321
 conditions, 250, 321t
 temperature, 414
- Saab-2000, 157t
 Safety, 277, 320, 456, 463
 SAR, **330**
 ATR72-500, 338
 Gulfstream G550, 335–337
 numerical solution, 332–334
 risk analysis, 464
 SAT, *see* static air temperature
 Scale effects, 46
 Scheduling, 424, 425
 Sears-Haack body, 26f, 26, 111
 SEL, *see* sound exposure level
 Sensitivity analysis
 drag, 104
 mission parameters, 604
 noise, 567
 noise components, 501
 range, 429
 Shimmy dampers, 238
 Shock absorbers, 236
 Side-slip, 40, 186, 375
 Sikorsky, Igor, 45
 Skin friction, 88, 91
 coefficient, 88, 90, 92
 laminar, 88
 turbulent, 90
 Slats, 73t, 83, 102, 276
 retraction, 283
 setting, 276
 Slush, 100, 232, 250, 253
 Software, xxiii, 4, 127, 171
 Solidity, 153
 Sound
 hearing threshold, 471
 intensity, 471
 loudness, 471

- Sound exposure level, **475**
 Sound pressure level, 471
 Specific excess power, **270**, 287
 charts, 288
 differential, 290
 load-factor effect, 364
 Specific excess thrust, **270**
 Specific range
 jet aircraft, 330
 supersonic, 330
 Speed
 dash, 216
 design dive, 207
 design flap, 208
 design manoeuvre, 207
 ground, 40, 203
 maximum gust intensity, 207
 minimum control, 189
 minimum drag, 209
 minimum power, 208
 never-to-exceed, 207
 sinking, 311
 stall, 213
 Spitfire, 379
 Spoilers, 73t, 95, 249, 311
 Spray, 101, 252f
 Square-cube law, 46
 Stability derivatives, 189
 Stall, 379, 380
 line, 213
 warning, 256
 Stall speed, 255, 290, 294, 364
 Standard day, **195**
 Static air temperature, **401**
 Statistics, 20, 423, 426, 451, 464–465
 Steep descent, 308–311, 561, 572
 Steepest climb, 272
 Stochastic analysis, 21
 Stratosphere, 196
 Strouhal number, 491, 493, 496, 498, **510**, 513, 514
 Supercooling, 394
 Supersonic acceleration, 217–218
 Sutherland's law, 198
 Synchronphasing, 165

 Tail strike, 57, 257, 258f
 Take-off
 CG effects, 236
 risk analysis, 465
 shock absorbers, 236–238
 time, 256
 Tank, Kurt, 6
 Tankering, 444–446
 Tanks, *see* Fuel tanks
 TAT, *see* total air temperature
 Taxiing, 168, 261–262
 fuel, 261t
 Temperature inversion, 198, 396
 Thermal conductivity, 399, 405, 414
 Thrust
 asymmetry, 186
 coefficient, **154**
 cut-back, 555
 reversal, 318
 reversers, 250
 Time
 equal-time point, 446
 no return, 447
 noise stacks, 582
 Time delay
 noise, 566
 take-off, 239
 Time-on-station, 424
 Time-zone effect, 424
 Tip
 losses, 162
 Mach number, 154
 speed, 154
 vortex, 116
 TOGA, **277**
 Torque, 154, 155
 coefficient, **154**
 Total air temperature, **401**
 Trajectory, 309
 continuous descent, 307
 curvature, 380
 final approach, 303
 NADP, 560, 561
 optimal, 607
 perfect flight, 606
 steep descent, 308
 Transition altitude, 332
 Transonics, 105, 108
 Trim
 drag, 183
 longitudinal, 179
 propeller, 168
 stick-fixed, 183
 stick-free, 184
 tank, 352
 with landing gear, 182
 Trimmable H-stabiliser, 57, 66, 184, 185, 618
 Tropopause, 213, 288
 Troposphere, 196
 Turbofan, 127
 Turbojet, 126, 143
 Turboprop, 127, 141
 Turbulence, 117, 254, 510, 541, 542, 576, 584
 Turn radius, 362
 Turn rate, 365
 Turn-around time, 424
 Type certificate, 5, 128, 130, 134, 137, 428, 509
 APU, 508
 propeller, 156
 Tyre, 101
 cornering force, 246
 dimensions, 410
 explosion, 409
 heating, 409–416
 hysteresis, 412

- inflation gas, 410
- load-speed charts, 410
- material composition, 415
- slip ratio, 249, 415
- standing wave, 412

- U-turn, 139, 367, 448, 607
- Under-relaxation, 162, 437
- Unit load device (ULD), 50

- V-n diagram, 372–373
- Vectored thrust, 278
- Velocity potential, 506, 538
- Vincenty inverse distance, 565
- VMCA, **189**
- VMCG, **245**, 248
- Volcanic ash, 138, 590
- Volume, 31
 - cargo, 31
 - fuel tanks, 33–34
 - scaling, 33
- von Kármán ogive, 111
- von Kármán, Theodore, 7
- Vought F8, 211, 218

- Wakes, 116–118
- WAT charts, 235
- Water vapour, 198, 394, 487t, 600
- Wave drag
 - airfoil, 105–108
 - forebody, 94
 - ogive, 110
 - wing, 93
- Weather, 199
 - global circulation, 200
 - icing, 199
 - turbulence, 199
- Weight
 - limits, 45
 - management, 51–52
 - passenger, 52
- Weight effects
 - on control speed, 191f
- Weighting, 51
- Weights
 - all up —, 50
 - manufacturer's empty —, 48
 - maximum brake-release —, 49
 - maximum landing —, 49
 - maximum ramp —, 49
 - maximum structural payload —, 49
 - maximum take-off —, 48
 - maximum taxi —, 49
 - maximum zero-fuel, 48
 - operating empty —, 48
 - useful load, 49
- Wells, H.G., 7
- Wetted area, 24, 88, 460
 - breakdown, 33t
 - fuselage, 25
 - nacelles, 28
 - pylons, 28
 - shell, 65
 - wing, 24
- Wheel lock, 249
- Wind, 203, 321
 - at landing, 321t
 - downburst, 380
 - effect on noise, 543, 573–574
 - effect on propeller, 156t
 - effects on payload-range, 428
 - effects on SAR, 338
- Wind shear, 199, 380
- Wind tunnel, 106, 107, 108
- Wing, 20, 88
 - area, **20**
 - buffet, 113
 - dropping, 379
 - flutter, 220
 - fuel tanks, 33, 401
 - geometry, 20–21
 - loading, 46
 - sections, 23
 - span, 20, **20**
 - stall, 375
 - strike, 322
 - tanks, 61
- Winglets, 29, 117
- Wright Brothers, 263

- Yaw, 40
 - adverse, 374
 - angle, 39
 - attitude, 39
 - in roll, 186
 - propeller, 163
- Zeppelin airships, 7
- Zoom climb, 210, 270
- Zoom dive, 217, 290, 292, 294, 295, 314