Cambridge University Press & Assessment 978-1-107-03006-0 — The Physics of Rock Failure and Earthquakes Mitiyasu Ohnaka Index More Information

Index

1923 Kanto earthquake, 209, 210, 220, 221 1945 Mikawa earthquake, 226, 227 1966 Tashkent earthquake, 241 1973 Nemuro-Hanto-Oki earthquake, 235 1978 Izu Oshima Kinkai earthquake, 228, 229 1986 Chalfant earthquake, 230 1986 Mount Lewis earthquake, 230 1986 Stone Canyon earthquake, 231 1989 Loma Prieta earthquake, 214, 224, 238 1990 Upland earthquake, 231 1992 Joshua Tree earthquake, 231 1992 Landers earthquake, 231 1995 Kobe earthquake, 98, 152, 185, 196 2000 Tottori earthquake, 185 2009 L'Aquila earthquake, 247 activated seismicity during the process leading up to a great or major earthquake, 212 activation of seismicity, 145, 208 adhesion, 11 aftershock activity, 208 apparent area of contact, 11 apparent shear rupture energy, 179, 196 asperities, 2, 3, 11, 13, 33, 72, 91, 99, 100, 106, 143, 144, 147, 156, 175, 183, 184, 185, 198, 206 asperity area, 185 average recurrence time interval for large earthquakes on a fault, 201 background seismicity, 145 barriers, 2, 3, 72, 91, 106, 107, 143, 144, 251 Benioff strain release, 214, 237, 238 biaxial testing apparatus, 39 breakdown displacement, 24, 36, 52, 57, 59, 69, 88, 92, 100, 142, 148, 151, 153, 161, 165, 181, 183, 198 breakdown (or slip-weakening) phase, 50 breakdown process, 19, 161 breakdown stress drop, 3, 26, 36, 52, 83, 84, 85, 87, 148, 153, 161 breakdown time, 168, 170 breakdown zone, 19, 20, 22, 39, 69, 161, 174 breakdown zone length (or size), 69, 70, 142, 170 breakdown zone model, 20, 24 brittle fracture, 9

brittle regime, 72 brittle-plastic transition regime (or semi-brittle regime), 72, 79 b-value, 180, 198, 247 cataclasis, 7 causal factors for recurrence time interval fluctuation, 202 change in Coulomb failure stress, 239 characteristic length, 37, 44, 62 representing fault surface irregularity, 123, 139, 140, 182, 185, 193 representing the geometric irregularity of shear-fractured (or shear-rupture) surfaces, 36, 50.88 chemical effect of (pore) water (molecules), 73, 81 cohesive force, 19 cohesive strength, 9, 10, 11 cohesive zone, 18, 19 cohesive zone model, 19 concept of effective stress, 73 constitutive equation, 8 constitutive law, 6 for earthquake ruptures, 1, 3, 19 for plastic flow, 8 for (real) earthquake ruptures, 4, 91, 103 for shear failure, 32 for shear failure (or fracture) of intact rock, 28 for shear failure (or fracture or rupture), 33, 34 for shear rupture, 4 constitutive law displacement parameters, 112 constitutive law formulation for earthquake ruptures, 93 constitutive law parameters, 46, 56, 71, 104 constitutive properties of the shear failure of intact rock, 72 constitutive relation, 6, 8, 19, 67, 68 for bond breaking process, 9 for fracture, 9 for frictional slip failure, 9, 50 for rock fracture, 9 for the shear failure of intact rock, 35, 50, 72 constitutive relation parameters, 26 constitutive scaling law, 4, 63, 185 constitutive scaling relation, 184 crack driving force (or crack extension force), 16

267

CAMBRIDGE

268

Cambridge University Press & Assessment 978-1-107-03006-0 – The Physics of Rock Failure and Earthquakes Mitiyasu Ohnaka Index

More Information

critical length (or size) L_c (of nucleation zone), 141,	elastic brittle fracture, 17
142, 180	elastic constants
critical length (or size) <i>L</i> _{sc} (of nucleation zone), 131, 134, 140	Lame's constants, Young's modulus, Poisson's ratio, modulus of rigidity, bulk modulus of
critical size of seismic nucleation zone, 146	elasticity, 6
cumulative Benioff strain release, 214, 238	elastic crack model, 18
cutoff frequency f_{max} , 167	elastic deformation of rock, 34
cutoff frequency $f_{\text{max}}^{\text{s}}$ (at seismic source), 168, 169,	elastic rebound model, 149
174	elastic strain energy, 72, 143, 144, 145, 148, 201, 207,
cycle process for a typical, large earthquake, 206	234 anarry relaced rate 16, 23
deformation 6	chergy release rate, 10, 25
ductile 7.8	fault zone 33 231
elastic 6	fault zone heterogeneity 231
non-elastic 7	fault zone thickness 34
non-clastic, 7	effective 33, 180
plastic 7	Fichtelbirge granite 86
delayed fracture 217	forecast scientific scenario (or predictive model) 233
denth profiles of constitutive law parameters	241
106	fracture energy 16–19
displacement-hardening (or slin-strengthening) 59	of inhomogeneous (or heterogeneous) materials 17
displacement-related constitutive law parameters	fracture modes 9
62	fracture strength 11
ductile fracture 9	fracture surface
duration (time) 189	of a heterogeneous body 16
of shear runture nucleation 179 190 193	frequency characteristics (of strain gauge sensor) 41
dynamic high-speed runture (or earthquake) 145	frictional coefficient 12
dynamic rupture growth at accelerating speeds 135	frictional sliding 14
dynamically propagating stick-slip rupture 51, 53	frictional slip failure 4
54	frictional slip failure energy, 65
	frictional slip failure (or frictional stick-slip failure)
earthquake nucleation process, 242	39
earthquake rupture, 121, 145, 146, 223	frictional stick-slip failure, 14, 39
process. 4	frictional strength, 13, 72
earthquake (rupture) nucleation, 224	frictional strength (or resistance), 12, 14
process, 122	
effect of (effective) normal stress	Gamma function, 201
on shear failure strength, 74, 75	generation of short-period strong motion (at the
effect of effective normal stress	source), 175
on the shear failure strength of wet Tsukuba	geometric irregularities, 2
granite, 77	geometric irregularity, 2
effect of normal stress	of a nonplanar fracture surface, 16
on the shear failure strength of dry Westerly	of fault surfaces, 123, 136, 138, 182
granite, 75	of shear-fracturing surfaces, 19
effect of strain rate	of shear rupturing surfaces, 36
on shear failure strength, 74, 81	of shear-rupturing (or shear-fractured) surfaces, 88,
effect of temperature	123
on shear failure strength, 74	with band-limited self-similarity, 2
on the shear failure strength of dry Westerly	geometric property of rupture surfaces, 62
granite, 76	Gutenberg-Richter frequency-magnitude relation,
on the shear failure strength of wet Tsukuba	197, 198

Hawking, Stephen, 92

of seismogenic layer and preexisting faults therein,

heterogeneities

2

Index

granite, 79

effective normal stress, 73 effective stress law, 73

on the shear failure strength of wet Tsukuba

effective breakdown displacement, 103

effective breakdown stress drop, 103

More Information

269		
	heterogeneity, 2	prerequisites for rational constitutive formulation
	high-pressure testing apparatus, 28	for real earthquake ruptures, 92
	HOOKE'S law, 6	minimum) 28
	immediate foreshocks 157 160 223 225 226 227	probabilistic forecast 236
	229. 231	probability density function, 200
	inhomogeneous (or heterogeneous) fault, 3, 4, 72, 91, 121, 122, 142	probability (of a future earthquake occurrence), 2 201, 236
	interlocking asperities, 3	pulse width of slip acceleration, 168
	intermediate-term forecasting models, 237	
	interstitial pore water, 73	quantification of seismic activity (or seismicity
	interstitial pore water pressure, 73	quantification), 237 quantitative effects of effective normal stress and
	J integral, 22, 23	temperature on the shear failure strength of wet Tsukuba
	laboratory-derived constitutive relation for shear	granite, 80
	tailure, 20, 34, 63	quantitative effects of normal stress and temperat
	laboratory-derived rupture nucleation model, 145 law of effective stress, 73	granite, 77
	linear slip-weakening model, 101	quiescent period of seismicity, 207
	model, 238, 239	quiescent seismicity (or background seismicity),
	macroscopic (shear) fracture surfaces 7 33 34	
	mainshock nucleation zone size, 229, 231	rate- and state-dependent constitutive law, 94, 96
	mainshock rupture, 208	rate- and state-dependent constitutive law parame
	master fault, 144, 145, 206, 208, 240	96, 97
	mechanical effect of pore water pressure, 73	real area of contact, 11, 14
	modal analysis and physical parameters for Tsukuba	real area of fracture surface, 16
	granite, 30	recurrence time interval, 201, 236
	model of the cycle process for a typical, large	recurrence time interval fluctuation, 203
	earthquake, 209	release of elastic strain energy, 68, 69
	and the first of the state of the second sec	residual friction stress, 36, 84, 100
	non-elastic (or ductile) deformation, 54	resistance to rupture growth, $2, 5, 10, 25, 27, 05, 02, 121, 127, 134, 141, 143, 145, 148, 151$
	earthquake 4	92, 121, 127, 134, 141, 143, 143, 146, 131, 183, 195, 197, 208, 225, 226, 228, 229
	earthquake, 4	resistance to (shear) runture growth 179
	nucleation process, 92, 127, 128, 136, 145, 189, 192.	resolved normal stress across fault plane. 32, 82
	208, 209, 225, 226, 243, 244	resolved shear stress along fault plane, 32, 82
	nucleation phase (shear rupture), 127, 128, 129	roughness of sliding surfaces, 14
	nucleation process of frictional stick-slip failure, 46	rupture growth length, 131, 139, 146, 147, 189, 1
	nucleation zone, 46, 136, 226, 229, 242	193, 244
	nucleation zone length (or size), 142, 147, 242	rupture growth rate (or rupture velocity), 129, 13 136, 139, 189
	peak shear strength, 34, 36, 83, 100, 127	Car Managashi 26
	peak slip acceleration, 52, 54, 163, 164, 165, 174	San Marcos gabbro, 86
	peak sup velocity, 52, 54, 105, 104, 105, 1/4 physical model of shear runture publication process	scale_dependent earthquake runtura 1 4
	141 physical model of the nucleation process for trained	scale-dependent earthquake rupture generation
	earthquakes, 223	scale-dependent physical quantities, 3, 92, 100, 1
	plastic now law parameters, 8	180, 181
	plasue regime, 72 plate-boundary subduction zone, 214, 210	scale-dependent shear rupture generation process
	precursory phenomena 221 233 241 247	scale-dependent shear runture process
	produsory phonomena, 221, 253, 241, 247	sourc-acpendent shear rupture process

CAMBRIDGE

Cambridge University Press & Assessment 978-1-107-03006-0 — The Physics of Rock Failure and Earthquakes Mitiyasu Ohnaka Index

scaling parameter

More Information

270	Index

for the physical scaling of scale-dependent physical quantities, 181 scaling property inherent in shear-rupture breakdown, 3, 4 scaling relation between breakdown displacement and breakdown zone size, 179, 188 between breakdown displacement and nucleation zone size, 179, 188 between critical region size and final event magnitude, 240 between seismic moment and breakdown displacement, 151, 153 between seismic moment and nucleation zone size, 154 between the duration time of shear rupture nucleation and characteristic length, 190 seismic activity, 208, 209, 210, 217 model, 207, 215, 222 seismic gap, 207, 235 seismic moment, 149, 150, 151, 153, 244 seismic nucleation phase, 146 seismic nucleation zone, 141 seismogenic fault zone properties, 1 seismogenic layer, 1, 70, 71, 224, 225, 226, 227, 228, 229 Senatorski's fault model, 203 shallow earthquake source, 91 shallow focus earthquakes, 1, 121 shear failure (or fracture) strength, 72, 73 shear failure (or rupture), 1 shear fracture, 4, 9 shear fracture energy, 25, 36, 65 shear fracture strength of intact rock, 3 shear rupture nucleation (process), 121, 122, 131, 135, 141, 145, 146, 148, 208, 242 short-term forecasting model, 243, 244 single-degree-of-freedom rigid-block spring model, 67 sliding mode or in-plane shear mode (mode II), 9 slip acceleration, 50, 161, 181 slip failure, 46 slip rupture nucleation, 129 slip velocity, 50, 128, 136, 161 slip-dependent constitutive formulation, 56, 100, 101 slip-dependent constitutive law, 55, 56, 99, 100, 101, 102.106 slip-dependent constitutive relation, 101 for shear failure of intact granite, 34 slip-rate effects on friction, 95 slip-strengthening, 46 slip-strengthening mechanism for frictional slip failure, 46 slip-strengthening phase, 46, 101

slip-weakening, 59, 128 slip-weakening displacement, 36 slip-weakening mechanism for frictional slip failure, 46 slip-weakening phase, 101 slip-weakening process, 46 slow and quasi-static rupture growth, 135 spherical triaxial pressure cell, 28 stability or instability of shear failure process, 32 stability/instability of slip failure (or shear rupture) process, 69 steady-state creep flow, 8 stepover zones, 2 stick-slip, 14 stick-slip (shear) rupture nucleation, 127, 131, 138, 141 stick-slip rupture, 50 stiffness of loading system (elastic), 14, 39, 67 stress corrosion (or stress-aided corrosion), 73, 82, 217, 219 stress drop, 149 stress transfer, 203 strong areas highly resistant to rupture growth on a fault, 3, 71, 72, 144 strong areas of high resistance to rupture growth, 3 strong (local) areas highly resistant to rupture growth on a fault, 2 strong motion, 4 seismic waves, 3 strong motion seismic waves, 160, 161 structural heterogeneities, 2 tearing mode or anti-plane shear mode (mode III), 9 tensile fracture (mode I), 9 theoretical strength, 11 time-dependence of static frictional coefficient, 13, 14 time-to-failure function model, 213, 237 transition process from the phase of stable, slow rupture growth to the subsequent accelerating phase of rupture growth, 135 Tsukuba granite, 30, 39, 73, 80, 85, 87, 122 underlying physical fault model of earthquake sources, 168 unification of constitutive relations for the shear failure of intact rock and for frictional slip failure, 56 unified comprehension of shear fracture and frictional stick-slip failure, 59 unifying (constitutive) law, 4, 32, 100 Weibull distribution, 200 Westerly granite, 73, 75, 76, 77, 80, 258, 264, 265 zone of dynamic rupture propagation, 46