

Index

- d_{31} -effect, 425
 d_{33} -effect, 425, 428
- Abbe number, *see* dispersion
- aberrations, 38, 76, 84–86, 176, 189, 194, 195, 268, 270, 271, 281, 286, 287, 387, 402
- astigmatism, 17, 177, 192
 - chromatic, 11, 12, 38, 186–189, 267, 364, 399
 - coma, 76, 364
 - defocus, 192
 - field curvature, 364
 - monochromatic, 187
 - optical, 74, 76
 - Seidel, 76
 - spherical, 12, 18, 51, 83, 186, 187, 192, 270, 364
 - tetrafoil, 177, 192, 194
 - tilt, 76, 84
 - tunable, 16, 191–194
 - wavefront error, 243, 258, 259
- accommodation, 41, 45, 46, 48, 60, 402
- chameleon eye, 54–55
 - fish eye, 50–54
 - human eye, 46–50
 - sea bird eye, 55–60
 - states, 60
 - vertebrates, 45
- achromatic doublet, 183, 186–188
- achromaticity, 92, 186
- achromatization, 402
- acousto-optical, 397
- actuation, 77, 78, 242, 244, 420
- external, 242
 - integrated, 159, 242, 243
 - principles, 241, 242
 - thermo-mechanical, 399
- actuator beam, 426, 428
- actuator design, 425
- actuator frame, 426–428
- actuator platform, 428
- actuators, 13–18, 183–186, 421, 423–426, 428
- dielectric elastomers, 347
 - electro-thermal, 378
 - electrofluidic, 159
 - electromagnetic, 85
 - electrostatic, 400
 - iris actuator, 184
 - liquid crystal elastomers, 347–353
 - LTCC-based, 424
 - micro servo motor, 185
 - muscle-like, 347
 - piezo-electric, 384, 406
 - pneumatic, 10, 94, 108, 109
 - prism, 378
 - radial symmetric, 183, 184
 - servo motor, 184
 - shape memory alloy, 347
 - silicon anchors, 182, 184
 - vectored, 177, 184–185, 191–194, 358, 360
- acute vision, 47
- adhesion promoter, 250
- agriculture, 396
- Airy disc, 58
- diameter, 58
 - radius, 47, 51, 59
- Al_2O_3 , *see* alumina
- Al_2O_3 -based bending actuator, 428
- AlN, *see* aluminum nitride
- alumina, 424
- aluminum nitride, 81
- mechanical properties, 224–227
 - membrane, 399
 - optical properties, 227–228
 - piezo-electric properties, 223
 - thermal properties, 228–229
- amorphous silicon, 26
- amphibian, 45
- anti-adhesive coating, 250, 251
- aperture, 78, 157, 242, 243, 245, 246, 253, 257–259, 419, 420, 430
- slit, 401
- apodization, 375
- aquatic invertebrates, 53
- arrays
- microcone, 68
 - microiris, 429
 - microlens, 68, 429–431

- arrays (*cont.*)
 microprism, 68
 uniformity, 279
- artificial muscles, *see* liquid crystal elastomers
- aspheres, 60, 402
- aspherical surfaces, 58, 402
- assembly
 optical, 364
- AST, *see* astigmatism
- astrophysics, 396
- attenuators, 19–21, 68, 78, 156
- axicon, 214
- backlighting, 69
 unit, 88
- band gap, 295
- barcode reading, 86
- beam
 deflection, 68, 372–374
 deflector, 78
- bending actuator, 424, 428
- bi- and multifocal, 49
- binocular vision, 41
- biochemistry, 396
- biomedical imaging, 87
- biosensor, 308
- birefringence, 182
 stress, 80, 87
- blocking force, 424
- BLU, *see* backlighting unit
- Bragg reflection, 86, 87
- bulge test, 224
- calotte
 iris/diaphragm, 431
 silicone, 431
 spacer, 431
- camera
 plenoptic, 429, 431
- capillary
 forces, 74, 158
 length, 70
- cataracts, 47
- cephalopods, 53
 vision, 52–54
- chameleons, 54
 vision, 54–55
- charge-carrier effect, 308
- chemical
 sensing, 298
 sensor, 298
- chromatic aberrations, 38
- chromatic imaging, 50
- ciliary muscles, 46, 47, 177
- closed-loop control, 245, 256, 259
- coefficient of thermal expansion, 228
- coercive field strength, 250, 425
- coherence, 87, 320
- Colladon Daniel, 67
- colloid, 67
- color, 395
 correction, 49
 detection, 395
 receptors, 395
- components, 39
- composite, 68, 69
- computed tomography, 397
- COMSOL, *see* finite element method
- concave shaped lens, 54
- concentrated photovoltaics, 68
- cones, 44
- contact angle, 4, 71, 159
 apparent, 72
- contrast, 243, 256
 analysis, 256
- convergence, 41, 42, 54
- convergence angle, 41
- convexiciliated fovea, 43, 54
- cornea, 46, 51, 54, 59, 402
 birds, 56
 curved, 60
 deformable, 55, 56
 fish, 50
 flat, 52, 59, 60
 radius of, 45
 refractive indices of, 51
 seabird, 58
 surface, 39, 46
- coupled oscillator, 328
- crabs
 eye movement, 40
- creep, 80, 245, 256
- crocodiles, 59
- crystalline lens, 39, 46, 47, 50, 54, 56, 58, 402
- CTE, *see* coefficient of thermal expansion
- cuttlefish, 53
- CYTOP, 20, 169, 359, 407
- data cube, 396
- data storage, 87
- DBR, *see* distributed Bragg reflector
- deep reactive ion etching, 325
- deflection, 222, 427
- deformable
 cornea, 55, 56
 crystalline lens, 56
 gratings, 27–29, 113–115
 lenses, 16–18, 101–108
- density, 69
 matching, 76, 169
- deoxyribonucleic acid, 69
- depth map, 419

- depth of field, 171, 172, 419–421, 423
 depth of focus, 363, 365, 374
 diaphragm
 array, 420
 optical, 430
 DIC, *see* differential interference contrast
 die
 bonding, 68
 transfer, 69
 dielectric, 72
 constant, 293
 crystal, 67
 elastomers, 15, 18, 27, 347
 forces, 78
 linear, 72
 stack, 299
 dielectrophoresis, 8, 23
 differential interference contrast, 214
 diffraction, 401
 limiting, 47
 diffraction-limited, 266, 272, 274, 286, 288, 420
 diffractive, 402
 hybrid, 402
 optics, 27–29
 power, 48
 diffractive optical element, 211
 diffractive-refractive element, 211
 diffusion, 81, 248, 258
 dispersion, 178, 186, 402
 relation, 296
 dispersive elements, 398
 tunable, 398
 display, 68, 69, 78, 86, 87, 156
 distributed Bragg reflector, 295, 299
 diving seabirds, 56
 DNA, *see* deoxyribonucleic acid
 DOE, *see* diffractive optical element, 214
 DOF, *see* depth of field
 drive stage, piezoelectric, 432
 droplet-based microfluidics, 73
 droplets
 sessile, 70, 159

 EAP, *see* electroactive polymers
 EASLM, 197
 elasticity, 67, 68, 80, 81
 elastic media, isotropic, 80
 tensor, 80
 elastomer, 68
 stamp, 69
 elastomeric lenses, 16–18
 electric
 field, 68, 71, 425, 428
 forces, 71, 159
 electro-optic
 effect, 293
 tuning, 307
 electroactive polymers, 15, 18, 27
 electrochemical cell, 380
 electrochromic, 380
 electrochromism, 380
 electrostriction, 81
 electrothermal, 335
 electrowetting-on-dielectrics, 4–8, 23–24, 71, 72, 77, 87, 159, 167, 398, 400, 406, 430, 432–434
 endoscope, 86, 319, 334
 energy level, 68
 engineered eyeball, 363–365
 environmental monitoring, 396
 epoxy resin, 250, 251
 evaporation, 249
 EWOD, *see* electrowetting-on-dielectrics
 extended modes, 296
 extrusion, 68
 eye, *see* vision
 aquatic, 50
 compound eyes, 395
 engineered, 363–365
 eye-ball, 40
 human, 46, 177, 183, 401
 movements, 42
 retina, 41
 surgery, 48, 87
 tubular, 39
 types, 53

 f-number, 402, 420
 fabrication, 424
 achromatic doublet, 183
 diamond milling, 179
 hot embossing, 179
 isotropic etching, 301
 master lenses, 179, 182, 183
 piezo-lens, 385
 precursor, 182, 183
 reaction injection molding, 178–183, 195
 reactive ion etching, 169, 304
 Fabry-Pérot
 resonator, 24–27, 311–313
 sensor, 312
 Fano resonance, 297
 far to near vision, 55
 fatigue, 87
 feed-back mechanisms, 41
 FEM, *see* finite element method
 ferroelectric, 424
 ferrofluids, 9
 fibers
 optical, 19
 field of view, 364, 421, 422
 filters, 24–27, 397
 finite element method, 16

- fish
 - vision, 50–54
- fixation period, 45
- flat curvature, 51
- fluid, 241–243, 246, 248–252, 254, 255, 258, 259
 - opaque, 406
- fluidic lenses, *see* liquid lenses
- focal length, 50, 51, 55, 57, 78, 188–191, 241, 243–245, 250, 256–258, 265–267, 272, 276, 278, 279, 283–286, 419, 421, 422
 - chameleon eye, 54–55
 - fish eye, 50–54
 - human eye, 46–50
 - sea bird eye, 55–60
 - tuning, 84, 377
- focal number, 266
- focal plane, 422
- focused ion beam, 304
- food industry, 396
- four-fold exposure sequence, 431
- Fourier-domain OCT, 321
- Fourier-optics, 430
- fovea, 43–44
 - concavociliated, 43
 - convexiciliated, 43, 54, 55
 - falcon, 55
- foveal to peripheral vision, 44
- frame rate, 319
- free energy, 69, 158
- freeform-surfaces, 60
- frequency, spatial, 430
- Fresnel
 - lenses, 29
 - zone plate, 29
- fringe field, 72
- frontal visual field, 54
- fundamental equation of capillary hydrostatics, 71, 74, 75
- fundoscopy, 319

- gas, 67
 - permeability, 84
- gaze, 41, 42, 44
 - stabilization, 40
- geometric efficiency, 425
- glare reduction, 68
- GOPHER process, 311
- graded refractive index, 53
- gradient index, 51, 52, 54, 56, 60
 - structure, 51, 52, 58
- gradient refractive index
 - profile, 54
- Grating Light Valve, 399
- gratings, 27–29, 81
 - binary, 409
 - blazed transmission, 409
 - effective constant, 399
 - efficiency, 399
- gravity, 71, 76
- GRIN, *see* gradient index
- group velocity, 298
- guided modes, 296
- guided-assembly, 305

- headlight
 - automobile, 69, 85, 87
- Helmholtz, Hermann von, 38
- hemoglobin, 322
- high resolution, 42
- high visual acuity, 54
- high-resolution, 38
- Hooke's law, 80
- hot embossing, 68, 250
- human eye, 402
- hybrid
 - optical element, 211
- hybrid-asphere, 402
- hybrid-diffractive–refractive, 402
- hydraulic
 - actuation, 10
 - irises, 23
 - lenses, 10–15
- hydrodynamic lenses, 15
- hydrogel, 9, 81
- hydrogen annealing, 301
- hydrophobic, 407
- hyperelasticity, 80
- hyperspectral, 395
- hysteresis, 245, 253, 254, 256, 259

- III–V semiconductors, 24–25, 223
- IDE, *see* interdigitated electrodes
- illuminance, 87
- illumination, 67, 84, 86, 87
 - plane wavefront, 279, 284
 - spherical wavefront, 280, 286
- image
 - intermediate, 401
 - plane, 418
 - stabilization, 73, 77, 80, 86
- imaging, 51, 396
 - hyperspectral, 395
 - lateral, 395, 398
 - optics, 86, 87
- in-plane excitation, 425, 428
- index guiding, 295
- index tuning
 - in photonic crystals, 308–309
- indium tin oxide, 5, 20, 169, 407, 432
- inflection point, 83
- InGaAs/InP, 25
- inorganic solid, 67

- integral photography, 417
 intensity distribution, 84, 87
 interdigitated electrodes, 425, 428
 interfaces
 energy, 71, 158
 thermodynamics of, 69
 interferometer
 Mach-Zehnder, 276, 278, 332
 intra-ocular
 lens, 48, 87
 muscles, 45
 intra-ocular lenses, 48
 bifocal, 48
 multifocal, 48
 inverse diamond, 304
 IOL, *see* intra-ocular lenses
 iris, 379
 optical, 430
 iris/diaphragm calotte, 431
 irises, 19, 21–24, 167
 iris stop, 68, 70, 78, 167
 liquid crystal elastomer, 353–356, 363
 optofluidic, 364
 ITO, *see* indium tin oxide
- Kerr effect, 307
- lamination, 68
 Laplace pressure, 70, 78
 laser, 87
 machining, 250
 structuring, 250, 259
 tuning, 299
 lateral, 395
 lateral field, 54
 LC, *see* liquid crystal
 LCA, *see* aberrations, longitudinal chromatic
 LCD, 197
 LCE, *see* liquid crystal elastomers
 leakage, 243
 LED, *see* light emitting diode
 lenses, 50
 achromatic doublet, 183
 adaptive, 176–196, 241–243, 245, 255, 256
 array, 420
 arrays, 8
 aspheric, 401
 chamber, 243, 244, 248, 250–252, 254, 258, 259
 characteristics, 265–266, 276
 converging, 243, 244
 cylindrical, 222, 227, 373
 deformable, 16–18, 56, 176–196
 deformation, 41, 47, 60
 deformed, 58
 design, 243–245, 258
 diameter, 58
 displacement, 51
 diverging, 243, 244
 elastomer bulk, 84, 356–363
 elastomeric, 16–18, 68, 176–196, 363, 364
 achromatic doublet, 186–188
 equiconvex, 188, 192
 membrane, 81–84
 fluid–fluid, 241
 fluid–gas, 242
 fluid–membrane, 241–243
 focus-variable, 68, 81, 84, 86, 87
 liquid, 73, 78
 reflective, *see* lenses, reflective
 Fresnel, 29, 68
 glass, 363
 achromatic doublet, 188, 192
 equiconvex, 192
 singlet, 192
 human eye, 46
 hydraulic, 10–15
 hydrodynamic, 15
 hyperchromatic, 399
 intra-ocular, 48
 liquid, 4–9, 68, 73–77
 aspherical, 78
 conical, 78
 performance nomogram of, 77
 stable centering of, 73
 liquid crystal, 8, 18–19
 liquid crystal elastomer, 356–363
 membrane, 84, 87, 376–377
 reflective, *see* lenses, reflective
 microlens array, 418, 420–423, 425–431
 microlenses, 271, 276, 278, 280, 429
 non-spherical, 222–223
 plano-concave, 244, 255
 plano-convex, 242, 244
 plastic, 68
 primary, 68, 87
 radius, 50
 reflective
 focus-variable, 101–108
 tunable aspheric, 103–105
 solid immersion, 68, 84
 spherical, 221
 lensmaker’s formula, 50, 241
 lifetime
 photon, 297
 light-matter interaction, 298
 cone, 296
 confinement, 295
 guide, 67
 line, 296
 shaping, 68
 trapping, 298

- light emitting diode, 68, 69, 87, 303
 light field capturing, 417–420
 lightguide, 69
 lines of gaze, 41
 liquid, 67, 68
 optical, 73
 liquid crystal, 68, 88, 293, 308, 348, 397
 in photonic crystals, 308
 laser, 309
 lenses, 18–19
 liquid crystal elastomers, 18, 185–186,
 346–366
 characteristics, 351–353
 description, 347–353
 for tunable iris, 353–356
 for tunable lens, 356–363
 orientation, 349
 structure, 348
 thermal actuation, 350–351
 liquid lenses, 4–9
 lithium niobate, 307
 local curvature, 74
 long focal length, 54
 long-term performance, 426, 428
 long-term stability, 254, 258
 longitudinal charge constant, 250
 low temperature cofired ceramics, 424
 low-profile, 424
 LTCC, *see* low temperature cofired ceramics
 luminaire, 68
 luminous flux, 88
- machine vision, 86
 magnification, 420
 magnitude, 39
 mantis shrimp, 395
 Maréchal criterion, 273, 274
 materials
 aluminum nitride, 223–229
 amorphous silicon, 26
 azobenzene, 199
 ceramics, 67
 CYTOP, 20, 169, 359
 dielectric elastomers, 15, 18, 27
 elastomer, 178–183
 crown, 183, 187
 flint, 183, 187
 mechanical properties, 179
 optical properties, 178
 elastomers, 16–18, 27–28
 electroactive polymers, 15, 18, 27
 electrochromic, 22, 24
 ferrofluids, 9
 glass
 optical properties, 178
 hydrogel, 9
 indium tin oxide, 5, 20, 169, 380
 InGaAs/InP, 25
 liquid crystal elastomers, 18, 185–186, 346–366
 liquid crystals, 8, 18–19
 metal, 67
 nanocrystalline diamond, 229
 optical liquids, 5, 13, 21, 23–24
 optical plastics, 178
 parylene, 6, 28, 166
 piezoelectrics, 20, 23
 PMMA, 214
 poly-3,4-ethylenedioxythiophene, 380, 382
 polyacrylate, 14
 polydimethylsiloxane, 10, 11, 16, 176–183, 187,
 196, 350
 polyetheretherketone, 182
 polyimide, 350
 polymethylmethacrylate, 27, 179, 183
 polystyrene, 10, 27
 PZT, 20
 semiconductor, 67
 shape-memory alloy, 16
 silicon, 6, 15, 19–20, 22, 25–26, 28
 silicone, 16–18, 27–28
 SU-8, 6, 107
 Maxwell's equations, 295
 mean curvature, 70
 membrane, 242–250, 253–256, 258, 259
 clamped, 82, 84
 deflection, 247, 248, 253, 254
 diameter, 243, 245–248, 252–259
 elastic, 68, 81, 242
 homogeneous, 243
 inhomogeneous, 243
 plano-convex, 243
 shape, 243
 thickness, 245–248, 250, 253–259
 MEMS, *see* micro-electro-mechanical systems
 MEMS tuning
 in photonic crystals, 310–314
 meniscus-driven evaporation, 305
 mesogens, 348
 metamaterial, *see* optical metamaterial
 micro-electro-mechanical systems, 17, 19
 micro-iris, *see* irises
 micro-saccades, 45
 microelectromechanical system, 310
 microfluidics, 69, 431, 432
 microlenses, *see* lenses
 microscope objective, 212
 microscopy, 69, 84
 miniaturization, 294
 minimal surfaces, 158
 minimalist
 design, 243, 258, 259
 lens, 244

- mirrors, 19
 3D, 105
 aberration correcting, 103, 109–112
 Bragg, 24–27
 broad-band, 297
 focus control, 100–108
 piston, 68
 tilting, 68
 tip-tilt, 68, 94–99
 tip-tilt-focus, 105
- MIT Photonic Bands, 296
- MLA, *see* microlens array
- mobile phone camera, 86
- modes, 293
 in photonic crystals, 295–299
- modular, 411
- modulation transfer function, 11, 86, 422
- molding
 compression, 68
 injection, 68
 replica, 85
 transfer, 68
- monocular accommodation, 54
- monolithic actuator platform, 428
- Mott model, 235
- MTF, *see* modulation transfer function
- multifocal
 elements, 60
 lenses, 49
- multilayer technology, 424
- multiplicity, 421
- nanochemistry, 68
- nanocrystalline diamond
 electrical properties, 233–235
 fabrication, 230–232
 mechanical properties, 232–233
 optical properties, 235–237
- nanoparticles, 69
- NCD, *see* nanocrystalline diamond
- near focus distance, 51
- near-field coupling
 in photonic crystals, 294
- near-field tuning, 310
- negative lens, 55
- negative optical power, 54, 56
- neural signals, 46
- non-linear optics, 307
- nonimaging optics, 86, 87
- numerical aperture, 84, 279, 402
- OASLM, 197
- objective, 419
- OCT, *see* optical coherence tomography
- OLED, *see* organic light emitting diode
- optical
 axis, 73, 74
 filter, 299
 liquids, 5, 13, 23–24, 156
 metamaterial, 294
 mode, 293
 resonance, 293
- optical addressing system, 212
- optical coherence tomography, 43, 46, 47, 87, 319, 336
- optical diaphragm, 430
- optical fibers, *see* fibers
- optical iris, 430
- opto-electrowetting, 73
- optofluidics, 21, 23–24, 69, 156, 167
- Ordyl, 359, 407
- organic light emitting diode, 68
- osculating sphere, 74
- oxidation state, 86
- PAC, *see* photo-addressable cell
- parallax, 417
- paraxial approximation, 76, 83
- partial pressure, 86
- parylene, 6, 28, 166, 407
- passive motion, 78
- PC, *see* polycarbonate, 68
- PCB, *see* printed circuit board
- PDMS, *see* polydimethylsiloxane
- PEEK, *see* polyetheretherketone
- penguins, 59
- perception, 38
- phase
 contrast, 214
 diagram, 68
 distortion, 432
 guiding structures, 70, 78
 transition, 68
- photo-addressable cell, 199
- photo-alignment, 204
- photo-orientation, 203
- photoconductor, 73
- photon, 293
 lifetime, 297
 -matter interaction, 293
 tunneling, 313
- photonic crystal devices
 biochemical sensor, 298, 308
 liquid crystal laser, 308
 MEMS scanners, 311
 microscanner, 299
 mirrors, 299
 nanocavity laser, 299, 309
 optical filter, 299
 scanners, 311
- photonic crystal tuning
 in a Fabry-Pérot resonator, 311–313

- photonic crystal tuning (*cont.*)
 via changing boundary conditions, 314
 via electro-optic effect, 307
 via liquid crystal, 308
 via MEMS tuning, 310–314
 via photon tunneling, 313
 via plasma effect, 307–308
 via refractive index, 308–309
 via symmetry breaking, 313–314
 via thermal effects, 309–310
 via thermo-optic effect, 309
- photonic crystals, 29, 293–315
 1D, 295, 299–300
 2D, 296, 300–303
 3D, 303–305
 analogy to semiconductors, 295
 band structure, 295
 boundary conditions, 294
 broad-band applications, 299
 coupled, 294
 defects, 295, 302
 definition, 295
 even modes, 296
 fabrication, 299–305
 functionalization, 308
 GOPHER process, 301
 guided assembly, 305
 hole slab, 300
 ideal, 294
 inverse opal, 305
 mechanical tuning, 294
 modes, 295–299
 nanobeam, 299–300
 nanocavity LED, 303
 nanorods, 296
 odd modes, 296
 opal structure, 305
 point defect, 301
 Q factor in cavities, 299
 resonant cavity, 298
 rod slab, 301
 scale invariance, 295
 sensitivity, 298
 simulation, 295
 slab, 296–298, 300–303
 slab modes, 297
 theory, 294–299
 transverse electric modes, 296
 transverse magnetic modes, 296
 tuning, 156, 293, 305–314
 tuning of, *see* photonic crystal tuning
 woodpile, 304–305
- photonics, 293
 photonics instrumentation, 265, 276
 photoreceptor, 53
 photoreceptor cells, 54
- pick-and-place, 69, 424
 piezo, *see* piezoelectric
 piezoceramic
 thick film, 428
 thick film actuator, 422, 425
 thick film technology, 424
 piezoelectric, 81, 241–245, 247, 248, 250, 253, 258, 259, 432
 actuation, 243, 244
 actuator, 244, 245, 247, 251–254, 259, 421
 bending actuator, 243, 247, 250
 bimorph bending actuator, 244, 249, 250
 buzzer, 249
 diameter, 248
 drive stage, 432
 foil, 249, 250
 material, 245
 monomorph bending actuator, 243
 radius, 245, 247, 248, 253
- pixel size, 400
 planar electrodes, 425, 428
 plane wave modes, 297
 plane waves, 411
 plasma, 67, 71
 effect, 293, 298, 308
 plasma effect tuning, 307–308
- plasmonics, 315
 plenoptic camera, 417–420, 422, 423, 429, 431
 PMMA, *see* polymethylmethacrylate
 pneumatic
 actuation, 10, 94, 108, 109
 irises, 23
- Pockels effect, 307
 Poisson's number, 80
 polarization, 78, 80, 87, 198, 395, 425
 polyacrylate, 14
 polycarbonate, 68
 polydimethylsiloxane, 10, 11, 16, 28, 176–196, 350
 polyetheretherketone, 182
 polyimide, 350
 polymer, 67
 cast, 69
 crosslinked, 81, 178–183
 -embedded colloidal crystal, 69, 86, 87
 ferrocen based, 86
- polymethylmethacrylate, 27, 68, 81, 179, 183
 polystyrene, 10, 27
 presbyopia, 47
 pressure, 242–245, 250, 253, 255–257, 259
 hydrostatic, 71
 sensor, 245, 250–256, 259
- priming, 251, 252, 259
 prism, 78, 241, 398, 399
 deflection, 372–373
 tunable, 398
- PS, *see* polystyrene

- pyrex, 407
 PZT, 20, 424, 425
- Q factor, 299
 definition, 299
 of a photonic crystal cavity, 299
 quality factor, *see* Q factor
- radius of curvature, 47, 48, 50, 55, 57, 58, 60, 70,
 73, 241, 242, 247
- rainstorms, 4
- rapid prototyping
 3D printing, 364
- Rayleigh criterion, 95, 100, 272, 273, 420
- reactive ion etching, 169
- refocusing, 421, 423
- refraction loss, 58
- refractive index, 46, 48, 50, 51, 54–56, 59, 178–179,
 241, 246, 249
 cephalopod eye, 53
 corneal tissue, 56
 fish eye, 50, 51
 human eye, 46
- refractive lenses, 48
- refractive power, 48, 56, 58, 83, 242, 243, 245–248,
 253–256, 259
- remanent polarisation, 425
- resolution, 46, 58, 84, 87, 243, 253, 257, 259, 419,
 420
 chart image, 288
 spectral, 401
- resonance
 optical, 293
- restoring force, 74
- retina, 41–43, 45, 46, 50, 51, 53–55, 58
 detector, 41
 image on, 47
 images on, 54
 movement, 39
 specialization, 42
- rms-radius, 51
- router, 68
 optical, 78
- S-bend actuator, 428
- SA, *see* aberrations, spherical
- saccades, 44, 45, 401, 402
 eye movement, 44, 54, 402
- safety, 396
- SAM, *see* self-assembled monolayers
- scalability, 245, 247, 248, 259
- scanner
 MEMS, 94–99, 311
 using photonic crystals, 311
- scanning
 cylindrical lens, 373–374
 motions, 39
 prism, 372–373
- Schrödinger's Equation, 295
- screen printing, 424, 428
 piezoelectric actuator, 424
- seabirds
 vision, 55–60
- self-assembled monolayers, 203
- self-assembly, 68, 305
- Shack-Hartmann sensor, *see* wavefront sensor
- shape-memory alloy, 16, 347
- sheet
 micro-optical, 68
 polarizer, 68
 reflector, 68
- shop lighting, 87
- Shore hardness, 179
- SHS, *see* wavefront sensor
- shutters, 19, 160, 164
- silicon, 6, 15, 19–20, 22, 25–26, 28
- silicone, 16–18, 27–28, 68, 87, 241, 243, 244, 248,
 249, 251, 259
 casting, 250, 259
 elastomer, 81, 84, 85
 -on-glass, 68
- silicone calotte, 431
- simulation
 finite element, 189
- slide focus device, 243
- slit apertures, 398
- slow light, 298, 307
- SMA, *see* shape-memory alloy
- SMD, *see* surface-mounted device
- socket, 40, 45
- soft condensed matter, 67
- soft-matter micro-optics, 71
- spacer calotte, 431
- spatial frequency, 430
- spatial light modulators, 197, 399
- spatial movable detectors, 39
- speckle, 87
- speckle reducer, 81
- spectral, 398
 imaging, 396
 range, 49
- spectroscopy, 395
- spectrum, 396
- spherical
 aberrations, 51
 cap, 70, 73
 gradient index lens, 52
 lens, 53
 shape, 74, 76
- spot diagrams, 46, 51, 52, 58

- spotlight, 84, 87
 squids, 53
 Stöber process, 305
 step response, 166, 257
 stereoscopy, 417
 stiction, 330
 pad, 331
 strain, 80, 183–186, 189, 190
 Strehl ratio, 274
 stress, 80
 -strain relation, 80
 optical parameters, 80
 stretching, 68
 SU-8, 6, 107
 surface
 forces, 68, 69
 profile, 74
 tension, 69, 71, 158
 surface-mounted device, 424
 swelling, 78, 81, 85, 87, 243, 248, 249, 258
 swept-source OCT, 321
 switch, 68
 optical, 78
 symmetric bi-concave lens, 55
 symmetry breaking
 in photonic crystal tuning, 313–314
- TCO, *see* transparent conductive oxide
 TD-OCT, *see* time domain OCT
 TE modes, *see* transverse electric modes
 telecommunications, 87
 television, 68
 tendon, 40
 TF, *see* tetrafoil
 thermal expansion, 253, 254
 coefficient of, 249
 of liquid crystal elastomers, 348
 thermal tuning
 in photonic crystals, 309–310
 thermo-optic
 effect, 293, 309
 tuning
 in photonic crystals, 309
 thermo-pneumatics, 81
 thermodynamic equilibrium, 86
 thermoplastic, 68
 thick film technology, *see* piezoceramic thick film
 technology
 through-thickness excitation, 425, 428
 time domain OCT, 320
 TM modes, *see* transverse magnetic modes
 transfer functions, 275
 transmission, *see* UV-VIS spectroscopy
 transmission spectrum, 288
 transmittivity, 80
 transparent conductive oxide, 433
 transverse electric modes, 296, 298
 in photonic crystals, 296
 tunable
 aberrations, 16, 109–112
 AIN membrane lens, 376–377
 apertures, 157, 160, 241, 374, 379–384
 attenuators, 19–21, 160
 Bragg mirrors, 26–27
 diffractive optics, 27–29, 113–115
 Fabry-Pérot resonators, 24–27
 filters, 24–27, 397
 focal length, 241
 Fresnel lenses, 29
 gratings, 27–29
 irises, 19, 21–24, 39, 160, 167, 353–356
 lenses, 3–19, 356–363
 photonic crystals, 29
 piezo lens, 384–387
 prism, 222, 378–379
 radius of curvature, 241
 slit apertures, 398
 transmission, 383
 zoom system, 371–372
 two-beam interference, 276
- uniform refractive index, 54
 USAF 1951, 255, 256
 UV-laser, 250, 251
 UV-VIS spectroscopy, 178
- variable fluidic membrane lens, 402
 variable optical attenuators, *see* attenuators
 VCSEL, *see* vertical-cavity surface-emitting lasers
 VCSEL driver, 214
 vectored actuator, 184–185, 191–194, 357–360
 vertebrates, 43, 45, 54
 binocular vision, 41
 eye movement, 40
 eyes, 46
 imperfect vision, 42
 optical accommodation, 45
 vertical-cavity surface-emitting lasers, 207, 213,
 299
 viewing aid, 84, 87
 vision
 3D, 39
 apposition, 395
 aquatic, 46
 binocular, 41
 cephalopods, 52–54
 chameleons, 54–55
 fish, 50–54
 human, 46, 50
 sea birds, 55–60
 visual
 acuity, 40, 58

- perception, 402
properties, 47
system, 54
vitreous humor, 46, 51
VOA, *see* attenuators
voice coil, 81
voltage tunable lens, 282
volume forces, 71
- wafer-level optics, 418
wavefront error, *see* aberrations
wavefront sensor, 176, 187
wavelength division multiplexing, 338
wavelength resolved measurement, 395
- wetting, 67, 68, 71
wetting angle, 398
woodpile, 304–305
- Yablonovite, 303–304
Young's equation, 71
Young's modulus, 80, 179, 424
Young-Lippmann equation, 72, 159
- ZEMAX, 363
Zernike polynomials, 17, 177, 193
zonula fibres, 177, 183
zoom, 86