

Index

- access threshold, 157
- ad hoc, 184
 - random network topology, 164
- adaptive power allocation, 58, 66
 - greedy power allocation, 78
 - water-filling, 77
- adaptive system, 335
- Aloha
 - channel aware, 155
 - pure, 45
 - slotted, 46
 - energy efficiency, 304
- average data rate, 263
- average power, 264
- average power consumption
 - slotted Aloha, 307
- best response, 314
- BS density, 328, 329
- BS sleeping, 332
- BSAA, 260
- CAD-MAC, 182, 197
 - robustness, 198
- CCI, 203
- cell breathing, 333
- cell size adaptation, 333
- centralized scheduling
 - opportunistic
 - fair, 186
- channel, 15
 - fast-fading, 19
 - flat
 - slow, 21
 - flat-fading, 19
 - frequency selective, 20
 - estimation, 22
 - path loss, 15
 - shadowing, 17
 - slow-fading, 19
 - small-scale fading, 18
- channel aware, 149
- channel estimation, 20
 - fast fading, 23
- channel inversion, 159
- CoMP, 333
- complete contention resolution, 149
- computation energy, 337
- contention
 - type I, 186
 - type II, 187
- contention probability, 159, 171, 191, 193, 207
- contention resolution slot, 196, 197
- coverage, 333
- cross layer, 6, 152
- CSMA, 46
 - I persistent, 47
 - collision avoidance, 49
 - collision detection, 48
 - detection delay, 47
 - non-persistent, 47
 - p persistent, 47
- CSMA/CA
 - contention window, 51
- data rate region, 69
 - long-term, 85
- delay analysis, 139
- delay transmit diversity, 111
- deployment efficiency, 327
- distributed, 43
- distributed MAC
 - efficiency, 196
 - optimal, 149, 197
 - channel aware, 182
- dynamic subcarrier assignment, 58, 63
 - sorting-search algorithm, 75
- efficiency, 197
- EMMPA, 271
- energy consumption, 245
 - circuit power, 246
 - lower bound, 245
 - time, 247
 - traffic load, 304

- energy efficiency, 25, 240, 322
 - antenna switching, 272
 - average, 264
 - capacity, 244
 - link, 29
 - methodology, 241
 - MIMO, 253
 - antenna switching, 273
 - MU-MIMO, 270
 - network, 29
 - convex, 325
 - OFDM, 253
 - MIMO, 252
 - PF, 30
 - power adaptation, 244
 - power allocation, 273
 - quasi concave, 254, 315
- energy efficiency and spectral efficiency tradeoff
 - interference, 326
- energy efficiency capacity, 245, 247, 273
 - circuit power
 - MU-MIMO, 271
 - frequency selective, 255
- energy efficient
 - conservative nature, 317
- energy-efficient cellular network, 321
- energy-efficient deployment, 330, 331
- energy-efficient design, 337
- energy-efficient handover, 333
- energy-efficient OFDMA
 - flat-fading, 285
- energy-efficient resource allocation
 - no fairness, 287
- energy efficient resource management
 - circuit management, 283
 - frequency domain, 284
 - space, 284
 - time domain, 283
- energy-efficient scheduling
 - closed form, 293
- energy efficient transmission
 - algorithm
 - superlinear, 262
 - circuit power
 - upper bound, 248
 - downlink, 257
 - link adaptation
 - closed form, 265
 - OFDMA, 257
 - power
 - closed-form, 265
 - QoS, 256
 - resource constraint, 257
- energy efficient transmission
 - frequency selective
 - optimal, 255
- energy efficiency
 - rate adaptation, 244
- equilibrium, 224, 315
 - frequency selective
 - unique, 317
 - frequency selective channel
 - multiple, 317
 - interference, 231
 - multi channel, 228
 - unique, 230
 - necessary and sufficient, 315
 - uniqueness
 - flat-fading, 316
- ESPA, 274
 - convergence, 275
- exposed terminal problem, 49
- extreme value theory, 126, 132
- fading
 - Nakagami, 134
 - Rayleigh, 130
- fairness, 84
 - max–min, 84
 - proportional, 84
- Fatou’s lemma, 106, 108
- feasible power, 219
- feeder loss, 334
- FFR, 214
- Foster–Lyapunov method, 106
- GABS, 259
 - convergence, 261
- heterogeneous channel, 185
- heterogeneous networks, 331
- hidden terminal problem, 49
- ICR, 204, 210
- Improved EMMPA
 - complexity, 277
- improved EMMPA, 277
- infrastructure, 2
- interference avoidance, 205
- interference detection, 211
- interferer recognition, 208
- trigger, 204
- Iterative EMMPA, 275
 - complexity, 275
- layer, 4
 - link, 4
 - MAC, 8
 - network, 5
 - PHY, 4, 7
- lighting
 - development
 - energy efficiency, 239
 - efficiency, 239
- LS estimator, 21, 22

- M-QAM, 27
 - BER, 249
- MAC
 - distributed
 - design rule, 44
 - energy efficient, 303
 - energy efficient, 301
 - robustness, 195
 - scheduling
 - sleeping, 304
 - throughput, 167
- maximum stability region, 102
- MIMO
 - antenna switching, 271
- minimum network power, 329
- minimum power consumption, 330
- MU-MIMO, 266, 268
 - energy efficiency capacity, 270
 - energy efficient
 - power allocation, 270
- multi-user diversity
 - distributed, 150
- network coupling factor, 317
- network energy efficiency
 - no fairness, 293
- network energy efficiency, 308, 328, 329
 - PF, 293
 - tradeoff
 - bandwidth, 286
 - multi user, 304
 - upperbound, 325
- network spectral efficiency, 324
- network throughput, 159, 190, 191
- OFDM, 56
- opportunistic random access
 - distributed scheduling
 - channel aware, 154
- optimal BS density, 330
- optimal rate allocation, 71
- PF
 - energy efficiency, 288
- power allocation
 - average power
 - peak power, 174
 - capability-limited, 176
 - water-filling, 265
 - energy efficient, 255
- power amplifier, 334
- power and rate relationship
 - network, 324
- power constraint
 - average, 158
 - peak, 158
- power consumption
 - BS, 237
 - communication
 - transmission power, 241
 - computation
 - circuit power, 242
- MIMO, 253
 - mode, 302
 - network, 328
- OFDM, 253
- power control, 217
 - circuit power dominance, 309
 - distributed, 221
 - elastic traffic, 222
 - energy efficient, 314
 - conservative, 326
 - interference dominance, 310
 - multi channel, 314
 - noise dominance, 310
 - non-concave, 222
 - pricing, 231
- QoS, 33
- rate adaptation, 58
- rate and power relationship, 323
 - network, 324
- rate-power relationship, 258
- Rayleigh fading, 155
- renewable energy, 334
- resource allocation
 - tradeoff, 322
- response function, 226
 - standard, 225
- RF amplifier, 334
- RTS/CTS, 51
 - fairness, 202
- scheduler
 - centralized
 - channel aware, 160
- scheduling, 167
 - α fair, 40
 - distributed
 - DOMRA, 166
 - energy efficiency
 - frequency selective, 291
 - PF metric, 297
 - energy efficiency metric, 295
 - joint channel- and queue-aware, 94
 - max throughput, 36
 - max-min, 38
 - normalized-SNR-based, 136
- OFDMA, 95
 - EXP rule, 96
 - generalized QoS, 117
 - M-LWDF rule, 96

- scheduling (cont.)
 - max-sum-capacity, 95
 - MDU, 97, 118, 119
 - proportional fair, 96
- opportunistic
 - splitting, 160
- PF, 37
- RR, 35
- self-max-SNR, 186
- utility, 39
- spectral efficiency
 - link, 26
 - network, 27
 - upper bound, 326
- stability, 100
- standard interference function
 - energy efficient, 315
- standard response function
 - convergence, 226
- system architecture, 336
- threshold, 162, 167, 172, 187, 192, 193, 207
- tradeoff
 - network spectral and energy efficiency
 - no circuit power, 324
 - spectral and energy, 322
 - single user, 323
 - spectral efficiency and energy efficiency, 326
- transmission power
 - M-QAM, 249
 - rate, 246
- transmit power dominance
 - power control, 309
- trigger, 210
- utility function, 61
 - average data rate, 81
 - delay-based, 97
 - non-concave, 81
 - rate-based, 61
- water-filling, 66