

Index

- four-third earth radius approximation, 22, 217–18
 airborne Doppler radar, 67, 180–2
 aliasing of Doppler velocities, 88–9
 altitude calculations, 217–18
 amplitude of signal, 27–8
 anomalous propagation, 22
 antenna, 15–16, 202–4
 artifacts: chaff echoes, 60–1; clutter, 43, 60–1; dual-polarization, 106–110; noise, 106–108, 205–7; sun emissions, 60, 107
 ash, 59–60
 attenuation, 23–4, 153–4, 188, 205
 atmospheric refraction, 20–2
 atmospheric windows, 10
 autocorrelation, 230–1
 aviation needs, 134–5
- backscattering cross section σ_b : of optical and Rayleigh targets, 13; of clear air, 15
 bands, radar, 19
 bandwidth of receiver, 205–7
 baroclinic instability, 44
 beam filling, 204, 211–3
 beam width of antenna, 15–16, 202–4
 bird echoes, 58–9, 106, 108
 bistatic Doppler radar, 181–2
 boundary layer, 76–7, 92, 124–5
 bow echoes, 124, 128
 Bragg scattering, 13–15, 187
 bright band, 50–2, 103, 155–6
- CAPE, 116
 CAPPI, 38–9
 capping inversion, 118: breaking, 124–5
 chaff, echoes from, 60–1
 CIN, 117
 circulator, 202
 clear air echoes, 13–15, 187
 climatology: cloud occurrence, 200; convection in the US, 118; lightning and thunderstorms, 117; precipitation in tropics, 198–9
 cloud radars, 18–19, 189–95, 200
 clouds, 56, 71
- clustering of drops, 209–10
 clutter, 43, 60–1
 complex numbers, 234–6
 concept map, 6
 cone of silence, 30–1
 convective instability, 44
 copolar signals, 94
 copolar correlation coefficient, 99–101, 106–9, 213, 241
 correlation between two data sets, 227–34, 238–9
 cross-polar signals, 94
- data assimilation, 174–9, 185, 219–21, 228
 data format, 218–19
 dBZ, 34, 221–3
 dielectric constant $|K|^2$, 33–4
 differential attenuation, 108–10
 differential backscattering phase delay δ_{co} , 98
 differential phase shift Ψ_{dp} , 97–9, 241
 differential propagation phase Φ_{dp} , 98–9: specific differential propagation phase delay K_{dp} , 99, 213
 differential reflectivity Z_{dr} , 94–6, 241: Z_{dr} columns, 105
 distance determination, 25–7. *See also* range
 divergence Doppler pattern, 81–3
 Doppler spectrum, 66, 69, 192–5, 243
 Doppler velocity, 65–6: calculation, 239–40; divergence, 81–3; large-scale patterns, 76–80; multiple measurements of, 180–3; Nyquist, 88–9; rotation, 80–1; small-scale patterns, 80–3
 downbursts, 83–4
 drizzle, 45–6
 drop-size distributions, 158–61: measurements at W-band, 193–4
 dual-Doppler: winds, 180–3; retrievals, 183–5
- echo fluctuation, 28
 echo structure: ash, 59–60; birds, 58–9, 106, 108; beam smearing of, 210–12; bow echoes, 128; bright band, 50–2; chaff, 60–1; convection, 45, 127–8; clouds, 56; drizzle, 45–6; graupel, 105; hail, 54–5, 97; horizontal speed, 49–50, 229; ice pellets, 54; identification: 62–4, 112–4; insects, 58, 107;

- overhang, 123; rain, 44–7, 102–4; refractive index gradients, 56–7; rimed snow, 70; severe thunderstorms, 127–9; snow, 52–3, 103; stalactites, 53; sun emissions, 60, 107; supercell storms, 121–3, 128; tracking, 168–9, 229; trails of precipitation, 48–50; tropical cyclone, 145–7; weak echo region, 123
- elevation calculations, 217–18
- emission and noise, 188, 205–7. *See also* absorption
- equivalent radar reflectivity factor Z_e , 34
- error, unit transformation of, 228
- extrapolation, 168–9, 229
- feed of antenna, 203
- fire, echoes from, 59–60
- fluctuating radar signal, 29, 208–9
- forecasting: convection, 115–16, 126–32; data assimilation, 174–9; ensemble, 170; midlatitude cyclones, 136–40, 142–6; precipitation nowcasting, 169–71; severe weather nowcasting, 171–4; storm initiation, 173–4; tropical cyclones, 137–9, 146–7; widespread events, 134–6
- Fourier spectrum, 231, 241–3. *See also* Doppler spectrum
- freezing rain/drizzle, 48, 136–7, 139–41
- fuzzy logic, 113
- gain of antenna, 204–5
- gauge adjustments, 164–5
- generating cells, 48–9
- geometry of measurements, 215–21
- graupel, 105. *See also* rimed snow
- ground echoes, 60–2: and CAPPIS, 39; anomalous propagation (AP), 23
- hail, 54–5, 84: detection, 127; dual-polarization signature, 94–7; spike, 54–5
- HTI (height-time indicator), 29–30
- hurricane, 140, 145–7
- ice pellets (sleet), 54, 136–7
- icing, 134, 139–41
- in-phase signal I and in-quadrature signal Q , 27, 207–8, 236–7
- insects: and updrafts, 58, 71–72; dual-polarization signature, 106–7
- instabilities (atmospheric), 44
- interference echoes, 60, 62
- intermediate frequency (IF), 205, 234
- klystron, 201–2
- latitude-longitude calculations, 216–17
- Lemon severe storm criteria, 127–9
- level 1–3 data, 207
- lidar, 10, 193–4
- linear depolarization ratio (LDR), 96, 98, 101–2
- lifetime: convective cells, 44; of weather as a function of scale, 134
- local oscillator (LO), 205
- magnetron, 201–2
- melting layer, 50–2, 103
- mesocyclon, 81–2, 129
- mesoscale, original definition, 2
- microwave radiometer, 193–4
- Mie scattering, 12–13, 190–2, 194–5
- mirror image technique, 197
- mixing (receiver), 205
- multicell thunderstorms, 120–1
- multiple-Doppler: winds, 180–3; retrievals, 183–5, 214
- multiple frequency measurements, 186–7, 191–4
- MST radars, 17
- networks of radars, 4–5
- noise, 106–108, 188, 205–7
- nowcasting, 166
- nugget of autocorrelation, 230–1
- Nyquist velocity v_{max} , 88–9
- observation operators, 177, 215–21
- optical scattering, 12–13
- overhang echo, 123, 128
- phase: of the target or of the radar return φ , 27, 65, 236–7; snow-rain transitions, 50–2, 103–4. *See also all entries on* differential phase
- power spectrum, 66, 69, 192–5, 241–3
- PPI (plan position indicator), 29–30
- products, 32, 38: CAPPI, 38–9; Doppler PPI, 80; echo-top, 61; PPI of reflectivity, 29–30; precipitation nowcasting, 169–71; range-height indicator (RHI), 97; rainfall accumulation, 41; severe weather detection, 129; severe weather nowcasting, 171–4; target identification: 112–4; velocity-azimuth display (VAD), 85–7; vertical cross-sections, 39–40, 85, 138; VIL, 39–41, 127
- pulse duration τ , 26
- pulse repetition frequency (PRF) f_r , 26, 88–9
- pulse thunderstorm, 119
- radar bands, 19
- radar equation, 33, 206
- radar model: CPS-9, 2; MU, 17; S-Pol, 18; WSR-88D, 18
- radar networks, 4–5
- radar products, 32, 38. *See also* products
- radar reflectivity factor Z , 32. *See also* reflectivity factor
- radial, 218
- radial velocity, 76–9. *See also* Doppler velocity

- radome, 18, 24, 204
 RASS (radio acoustic sounding system), 17, 73–5
 rain: accuracy needs, 148–9; cold, 44–5, 102–4, 155–7;
 drop shape, 93–4; dual-polarization profiles, 102–3;
 echo, 44–7; estimation, 35–38, 110–12, 150–65;
 flash-flood warning, 127, 129; transition to snow,
 103–4; tropical climatology, 198–9; warm, 44–5,
 156, 158–9
 range: determination, 25–6; folding, 90; maximum
 unambiguous r_{\max} , 26
 RHI (range-height indicator), 29–30
 Rayleigh scattering, 12–13
 receiver, 205–7
 reflectivity factor Z , 32: differential (Z_{dr}), 94–6;
 equivalent radar reflectivity factor Z_e , 33–4; typical
 values, 36; units, 32, 34–5; Z - R relationships, 35–38.
See also structure of echoes
 refraction in the atmosphere, 20–2: anomalous
 propagation, 22
 refractive index: echoes from gradients, 56–7;
 measurements, 185–7; of air, 14; of targets, 11;
 structure parameter C_n^2 , 15
 refractivity N , 20, 185–7
 regressions, 223–7
 representativeness error, 210–4
 retrievals, 183–5
 rimed snow, 70, 140. *See also* graupel
- satellite imagers, comparing with, 3–5
 scanning strategy, 31, 218–9
 scatterers, 11–15: Bragg, 13–15, 187; Mie, 12–13, 192,
 194–5; optical, 12–13; Rayleigh, 12–13
 scattering efficiency factor ξ_s , 11–12
 sea clutter, 62
 shape of targets (obtained from dual-polarization): axis
 ratio, 94–6; non-symmetry, 96, 101–2; shape
 diversity, 99–101. *See also* echo structure
 signal processing, 207, 234–43
 signal quality index, 240
 signatures of severe storms, 127–30
 simulation of radar observations, 177, 215–21
 size parameter γ , 12
 Snell law, 20–1
 snow: echoes, 52–3; estimation, 110–11, 156, 162–3;
 forecasting, 136–7
 sound, speed of, 74
 spaceborne radars, 195–200
 spectrum width σ_v , 28, 65–6, 68, 240
 stratiform precipitation, 44
- sub-refraction, 22
 super-refraction, 22–3
 supercell thunderstorms, 121–3, 128
 surface reference technique, 197
 sweep, 218
 synoptic scale, 1
- target: definition, 8; identification: 112–4; shapes,
 94–101; types, 43. *See also* echo structure
 TBS (three-body scattering) and hail, 55
 temperature profiling by RASS, 73–5
 threats from storms: anticipation, 115–16, 126, 130–2;
 hail, 126; thresholds, 135; thunderstorms, 126;
 tropical cyclones, 146; widespread events, 134–5;
 winds, 127–9
 thunderstorms: bow echoes or derecho, 124; lifecycle,
 118–23; multicell, 120–1; signatures of severe,
 127–30; supercell, 121–3, 128
 time to independence of echo
 fluctuations, 28
 tornado: debris, 105–6, 130; vortex signature (TVS):
 81–2, 129
 tracking of echoes, 168–9, 229
 trails of precipitation, 48–50, 154, 156–7
 transmit-receive (T-R) cell, 202
 transmissivity of atmosphere, 10
 transmitter, 201–2
 trapping of radar waves, 22–3
 tropical cyclone, 140, 145–7
 turbulence, 72, 139, 141
 types of weather radars: cloud radars: 19, 190;
 spaceborne radars, 195; weather surveillance radars,
 17–18; wind profilers, 16–17
- velocity aliasing, 88–9
 vertically-integrated liquid (VIL), 39–41, 127
 volume scan, 30, 218–9
 volume scattering coefficient β , 11–12
- waveguide, 202
 waves: electromagnetic: 8–10; gravity and Kelvin-
 Helmholtz, 72, 139, 141; polarized, 92–3
 weak echo region (WER), 123, 128
 wet snow, 103–4. *See also* bright band
 wind profile determination from Doppler patterns,
 78–9
 wind profilers, 16–17, 71–4
- Z - R relationships, 35–38, 110, 157–62, 223–7