

Index

- 18650 cell, 134
- 3D cell design, 13
- A_2B_7 , 56
- AB_2 , 56
- AB_5 , 56
- absorbed glass mat battery, 52
- activated carbon, 65
- activation polarisation, 33
 - fuel cell, 75
- active battery balancing, 186
- active cooling, 164
- active electrode area, 63
- active material, 8, 230
- additive, 230
- additives, 115, 118
 - film-forming, 120
 - flame-retardant, 120
 - gas-forming, 120
 - redox-shuttle, 119
 - SEI forming, 119
 - shut-down, 120
- ageing, 230
- ageing rate, 189
- AGM, 52
- air-cooling, 164
- Al current collector, 128
- all-electric vehicle, 144
- alloy
 - negative electrode, 96
- amorphous carbon, 91, 95, 127
- ampere, 230
- ampere hour, 230
- anode, 7, 230
- anodic current, 22
- assembly process, 138
- asymmetrical capacitor, 65
- available capacity, 230
- β - Al_2O_3 , 67
- band structure, 31
- battery, 14, 230
- battery balancing, 185
- battery degradation, 194
 - accelerating factors, 201
 - active materials and electrolytes, 212
 - analysis methods, 221
 - changes in bulk material, 210
 - current, 206
 - electrolytes, 219
 - layered oxides, 217
 - $LiFePO_4$, 219
 - $LiMn_2O_4$, 218
 - mechanisms, 195
 - negative electrode, 212
 - positive electrode, 215
 - SEI, 213
 - separators, 220
 - temperature, 202
 - voltage, 206
- battery design, 152
- battery durability, 194
- battery electric vehicle, 144
- battery life, 155, 189
- battery management system, 168
- battery models, 183
 - cycle counting, 191
 - empirical, 191
 - energy throughput counting, 191
 - equivalent circuit, 191
 - physical, 191
- battery monitoring, 178
- beginning-of-life, 155
- BEV, 144
- binder, 127
- bipolar cell, 12
- bipolar electrode, 230
- bipolar plate, 76
- blocking electrode, 9
- BMS, 168
- BOL, 155
- Butler–Volmer equation, 22
- calendar ageing, 195
- calendar life, 155, 189, 195, 230
- calendering, 138

- capacitance, 63, 230
 capacitor, 62, 230
 capacity, 36, 230
 theoretical, 37
 capacity fade, 195
 capacity retention, 230
 carbon black, 93, 127
 cathode, 7, 230
 cathodic current, 22
 cell, 230
 cell balancing, 130
 cell casing, 11
 cell design, 126, 134
 cell format, 134
 cell formation, 139
 cell production, 137
 cell selection, 156
 cell voltage, 17
 cell-to-cell variations, 157
 centralised BMS, 171
 charge, 230
 charge carrier, 230
 charge current, 230
 charge current limit, 230
 charge separation distance, 63
 charge transfer, 22
 charge-depleting, 150
 charge-sustaining, 150
 charge-transfer resistance, 44
 charging methods, 171
 constant current, 172
 constant current–constant voltage, 173
 constant voltage, 173
 temperature control, 172
 voltage control, 172
 chemical potential, 16
 Chevrel phases, 72
 CID, 137
 composite electrode, 28, 126, 129
 concentration polarisation, 25, 33
 fuel cell, 75
 constant current charging, 231
 constant power discharge rate, 36
 constant voltage charging, 231
 constant voltage charging method, 173
 contaminations, 211
 conversion material, 30
 conversion oxides, 98
 conversion reaction, 30
 cooling media, 164
 cooling system, 163
 core-shell model, 110
 co-solvent, 116, 125
 coulomb, 231
 coulombic efficiency, 40, 231
 counter electrode, 46
 C-rate, 35, 230
 crossover, 78
 Cu current collector, 128
 current, 22, 231
 current collector, 10, 126
 corrosion, 214
 current counting, 182
 current density
 fuel cell, 75
 current distribution, 128
 current interrupt device, 137
 cut-off voltage, 21, 35, 231
 cycle life, 155, 189, 231
 cycling stability, 231
 cylindrical cells, 134
 degradation mechanisms
 chemical, 195
 Li-ion cell, 208
 mechanical, 195
 side reactions, 210
 surface film formation, 210
 degrees of electrification, 144
 dendrites, 90
 depth of discharge, 181, 231
 desulphation, 50
 dielectric constant, 63
 differential voltage analysis, 226
 diffusion coefficient, 25
 diffusion pathway, 29
 dimethyl carbonate, 116
 discharge current limit, 231
 discharge profile, 17
 DMC, 116
 DOD, 181, 231
 double-layer capacitance, 24, 44, 63
 double-layer capacitor, 65
 drying process, 138
 duty cycle, 147
 EC, 116
 EDLC, 65
 efficiency, 231
 electric charge, 231
 electrical equivalent model, 231
 electrical impedance, 44
 electrical potential, 16
 electrochemical cell, 7–8, 231
 electrochemical double-layer, 24
 electrochemical double-layer capacitor, 62
 electrochemical equilibrium, 16
 electrochemical force, 15
 electrochemical impedance spectroscopy, 44, 223
 electrochemical potential, 16, 231
 electrochemical stability window, 32
 electrode, 7, 9, 77, 231

- electrode fabrication, 137
 electrode kinetics, 22
 electrode potential, 231
 electrolyte, 7, 9, 231
 concentration, 25
 gel polymer, 123
 ionic liquids, 124
 Li-ion battery, 114
 liquid, 115
 polymer, 123
 resistance, 44
 viscosity, 26
 electrolytic cell, 7
 electronic protection devices, 165
 electronic structure, 30
 electrostatic field, 62
 electrostatic potential, 16
 end-of-life, 155
 energy, 38
 of capacitor, 62
 energy density, 38, 231
 energy efficiency, 41
 energy management, 152
 energy optimised cell, 130
 energy optimised electrode, 129
 energy throughput, 147
 entropy heat, 21
 EOL, 155
 ethylene carbonate, 116
 EV, 144
 exchange current, 22
 exfoliation, 95, 214

 farad, 231
 Faraday's law, 37
 fast-charging, 155
 fault detection, 170
 Fermi level, 30
 Fick's first law, 25
 Fick's second law, 26
 film-forming additives, 120
 flame-retardant additives, 120
 fluorophosphates, 112
 fluorosulphates, 112
 forced air-cooling, 164
 formation reaction, 30
 fuel cell, 74, 232
 full cell, 12

 Galvani potential difference, 16
 galvanic cell, 7, 232
 galvanostatic cycling, 41, 222
 gas diffusion layer, 77
 gas formation additives, 120
 gas-shift reaction, 79
 gel battery, 52

 gel polymer electrolyte, 123–4
 Gibbs free energy, 15–16, 21
 Gibbs phase rule, 17
 graphite, 91

 half-cell, 11, 227, 232
 hard carbons, 96
 heating media, 164
 heating system, 163
 Helmholtz plane, 24
 HEV, 145
 high-temperature battery, 66
 HOMO, 31
 hot-spots, 177
 hourly rate, 36
 Hunter's disproportional reaction, 108
 hybrid capacitor, 65
 hybrid electric vehicle, 145
 hydrogen, 74

 impedance, 232
 incremental capacity analysis, 225
 inner Helmholtz plane, 24
 inorganic composite membrane separator, 122
 insertion
 negative electrode, 98
 insertion electrode, 9
 insertion material, 29
 intercalation, 29
 intermetallic alloy, 55
 intermetallic materials
 negative electrode, 97
 internal resistance, 33, 232
 fuel cell, 75
 internal short circuit, 176, 232
 ion conductivity, 26–7
 ion mobility, 26
 ion pairing, 27
 ionic liquids, 66, 124
 IR drop, 33, 232
 irreversible heat generation, 21

 Jahn–Teller distortion, 107, 218
 Joule heating, 21

 KOH, 56

 layered oxides, 102
 lead dioxide, 48
 lead–acid battery, 48
 LFP, 109
 Li (metal) polymer battery, 83
 Li metal battery, 83
 $\text{Li}_2\text{FeSiO}_4$, 112
 $\text{Li}_2\text{Mn}_2\text{O}_4$, 107
 Li_2MnO_3 , 105

- Li₂MSiO₄, 112
- Li₄Ti₅O₁₂, 98
- Li-air battery, 59
- LiAsF₆, 117
- LiBF₄, 117
- LiCF₃SO₃, 117
- LiClO₄, 117
- LiCoO₂, 102
- LiCoPO₄, 111
- Li-dendrites, 205
- LiFePO₄, 109
- Li-ion battery, 59, 83
- Li-ion capacitor, 65
- Li-ion polymer battery, 59, 83
- LiMn₂O₄, 105
- LiMnPO₄, 111
- LiMPO₄F, 112
- LiMSO₄F, 112
- LiN(SO₂CF₃)₂, 117
- LiNi_{0.8}Co_{0.15}Al_{0.05}O₂, 104
- LiNi_{1/3}Mn_{1/3}Co_{1/3}O₂, 104
- LiNiO₂, 103
- Li-oxygen battery, 59
- LiPF₆, 117, 220
- Li-plating, 93, 205, 211
- liquid cooling, 164
- liquid electrolyte, 115
- Li-rich NMC
 - Li-rich, 105
- Li-Si alloys, 97
- Li-sulphur battery, 60
- LiTFSI, 117
- lithium, 57
- lithium batteries, 57
- lithium metal battery, 58
- lithium-ion battery, 83
- Li-triflate, 117
- LiVPO₄F, 113
- Li_xM₂(XO₄)₃, 111
- LTO, 98
- LUMO, 31

- many-particle model, 110
- mass transport, 24, 28
- master-slave BMS, 171
- MEA, 77
- mechanical stability, 154
- Me-ion battery, 70
- membrane
 - fuel cell, 74
- membrane electrode assembly, 77
- memory effect, 57
- metallic lithium
 - negative electrode, 89
- Mg battery, 72
- micro-HEV, 145
- microporous polymeric membrane separator, 122

- mild HEV, 145
- modular BMS, 171
- molten salts, 67
- monopolar cell, 12
- multi-layered separator, 122

- N/P ratio, 55, 132
- Na-ion battery, 70
- Na-NiCl₂ battery, 67
- natural gas, 74
- NCA, 104
- negative electrode, 7, 232
 - Li-ion battery, 86
- Nernst equation, 17, 49
- nickel metal-hydride battery, 52
- nickel oxyhydroxide, 53
- NiMH, 52
- NiOOH, 53, 56
- NiZn battery, 68
- NMC, 104
- nominal voltage, 17, 232
- non-active material, 8
- non-aqueous solvents, 115
- non-blocking electrode, 26
- non-woven fabric mat separator, 122
- Nyquist plot, 44

- OCV, 17, 33, 232
- ohmic polarisation, 33
- ohmic resistance
 - fuel cell, 75
- open circuit, 44
- open circuit voltage, 17, 232
- operating temperature range, 202
- outer Helmholtz plane, 24
- overcharge, 35, 232
- overdischarge, 35, 232
- overpotential, 22, 232
- oxidant, 7, 232
- oxidation, 7, 232
- oxides
 - negative electrode, 98
- oxygen recombination reaction, 54

- P/E ratio, 148
- parallel connected capacitors, 64
- passive battery balancing, 186
- passive cooling, 164
- Pb-acid*, 48
- PbO₂, 48
- PC, 116
- PEM, 77
- PEMFC, 75
- PEO, 123
- Peukert law, 37
- Peukert plot
 - modified, 37

- PEV, 144
 PHEV, 146
 planar electrode, 28
 plasticiser, 123
 plug-in hybrid electric vehicle, 146
 polarisation, 232
 polarisation profile, 75
 polarity reversal, 55, 232
 poly(ethylene oxide), 123
 poly(propylene oxide), 123
 polyanionic materials, 111
 polymer electrolyte, 123
 polymer electrolyte membrane, 77
 polymer electrolyte membrane fuel cell, 75
 polysulphides, 61
 porous electrode, 28
 positive electrode, 7, 232
 Li-ion battery, 100
 mixed materials, 113
 positive temperature coefficient, 137
 post-mortem analysis, 228
 potassium hydroxide, 56
 potential, 232
 potential difference, 15
 potentiostatic cycling, 41
 pouch cells, 135
 power, 39, 232
 power capability, 22
 power density, 232
 power fade, 195
 power optimised cell, 130
 power optimised electrode, 129
 power-to-energy ratio, 148
 PPO, 123
 primary cell, 7, 232
 prismatic cells, 135
 propylene carbonate, 116
 pseudo-capacitance, 64
 pseudo-capacitor, 65
 PTC, 137
 pure electric vehicle, 144
- Ragone plot, 39, 132
 rate capability, 232
 rated cell capacity, 35
 redox flow battery, 72
 redox reaction, 7, 232
 redox-shuttle additives, 119
 reductant, 7, 232
 reduction, 7, 232
 reference electrode, 12, 46, 233
 reference potential, 17
- salt, 233
 Li-ion battery, 117
 salt concentration, 27, 118
 secondary cell, 7, 233
- SEI, 87
 SEI forming additives, 119
 self-discharge, 155, 198, 233
 Pb-acid, 50
 separator, 10, 120
 inorganic composite membrane, 122
 microporous polymeric membrane, 122
 multi-layered, 122
 non-woven fabric mat, 122
 permeability, 121
 pore size, 121
 shut-down, 121
 series connected capacitors, 64
 shedding, 51
 shelf-life, 155, 233
 shut-down additives, 120
 Si-based electrode, 96
 silicon, 96
 single-phase insertion reaction, 30
 SLI, 51
 SOC, 180, 233
 SOC estimation
 capacitors, 187
 SOF, 192
 SOFC, 79
 SOH, 189, 233
 solid electrolyte interphase, 87
 solid oxide fuel cell, 79
 solid polymer electrolyte, 123
 solvation shell, 95
 solvent co-insertion, 214
 solvents, 115
 SOP, 192
 specific capacity, 37
 specific energy, 38, 233
 specific power, 232
 spinel, 105
 high-voltage, 108
 standard hydrogen electrode, 17
 standard potential, 15, 17
 starting, lighting and ignition battery, 51
 state functions, 179
 state of charge, 180, 233
 state of function, 192
 state of health, 189, 233
 state of power, 192
 Stokes–Einstein equation, 26
 stratification, 50
 strong HEV, 145
 sulphation, 50
 sulphuric acid, 48
 super capacitor, 62
 surface protective layer, 101
- tab, 136
 tap density, 137
 technology selection, 157

- temperature, 20
- temperature control charging method, 172
- thermal control, 174
- thermal cycling, 205
- thermal management, 174
- thermal runaway, 175
- thermal system, 163
- transfer coefficient, 22
- transference number, 26
- turbostratic disordered graphite, 93
- two-phase insertion reaction, 30

- ultra capacitor, 62
- undercharge, 233
- usage condition, 146

- valve regulated battery, 52
- vanadium redox flow battery, 73
- VC, 119

- vinylene carbonate, 119
- Volt, 233
- voltage, 15, 233
- voltage control charging method, 172
- voltage depression, 57
- voltage hysteresis, 34
- voltage look-up table, 183
- voltage profile, 17
- voltammogram, 42
- volumetric capacity, 37
- VRLA, 52

- Warburg impedance, 45
- working electrode, 46
- working voltage, 233

- ZEBRA battery, 67
- Zinc-air battery, 69