

Index

- “ π ” model, 63, 80, 101
- “T” model, 80

- Abbe limit, *see* diffraction limit
- ABCD matrices, 78, 80, 86
- acoustic waves, 226
- actin, 303
- adapter, 47
- adaptive weight smoothing, 301
- admittance, 11, 22, 62, 63, 95, 97, 98, 99, 101, 137, 143, 174, 175, 180, 195, 196, 198, 301, 303
 - matrices, 78, 197
- ambient conditions, 150, 206, 207
- angular frequency, 83
- anisotropic dielectrics, 126
- anisotropic magnetoresistance, 263
- ANSYS Designer, 71
- antenna, 5, 67, 123, 129, 145, 173, 227, 228, 233, 241, 246, 271, 283, 284, 285
 - free space resistance, 130
 - nanoscale, 68
 - near-field, 163
- approach curve, 137
- atomic force microscope, 5, 6, 33, 107
 - conductive, 218
 - contact mode, 107, 110, 131, 135, 153, 166, 293
 - non-contact mode, 107, 247
- attenuator, 54, 139, 140
- AWR Microwave Office, 71

- band gap, 177, 179, 188
- Bardeen formalism, 109
- beam-bounce feedback, 107
- Beatty standard, *see* mismatch standard
- Bessel function, 225
- Bethe, 111, 225
- bias tee, 113, 119
- bilinear transform, 59
- biological systems, 279
- biological tissue, 291
- Boltzmann constant, 165, 206, 265, 283
- Born approximation, 228
- boundary conditions, 12, 16, 17, 20, 72, 77, 129, 152, 161, 227, 238, 254, 255, 288

- bridge-based impedance detector, 105
- Buckminsterfullerenes, 1

- calibration, 4, 6, 27, 28, 37, 45, 62, 68, 77, 85, 104, 138, 204, 211, 214, 218, 226
 - admittance, 143
 - coefficients, 45
 - constant, 134, 165, 173, 216
 - FMR, 143
 - lines, 30
 - magnetic field, 143
 - multimode, 31–33
 - NSMM, 33–34, 124, 130
 - one-port, 11, 49, 50, 135, 136, 139, 214, 303
 - on-wafer, 31, 53, 62, 93, 94, 188, 191
 - quality factor, 114
 - reference samples, 118, 164, 166
 - standards, 29, 34, 43, 45, 49, 50, 57, 60, 62, 124, 131, 136, 192, 244
 - test structures, 6, 56, 57, 68, 71, 93, 194, 245
 - underlying assumptions, 70
 - validation, 70
- canonical momentum, 151
- cantilevers, 119, 123, 125, 256, 273
 - bimaterial, 258
 - parasitic effects, 123
- capacitance, 7, 8
 - depletion layer, 170
 - oxide, 215
 - topography-dependent, 297
- capacitance per unit length, 19, 69, 101
- capacitance-voltage curve, 207, 208, 211, 213, 216
 - measurement, 207
- carbon nanotube bundles, 84, 85
- carbon nanotubes, 1, 2, 5, 52, 53, 57, 58, 60, 61, 63, 64, 67, 69, 75, 83, 84, 85, 100, 101, 187, 188, 203, 247
 - ballistic transport, 2, 67
 - characteristic impedance, 69
 - electromagnetic characterization, 90
 - impedance, 60, 84
 - interconnects, 3
 - metallic, 64
 - quantum mechanical properties, 85
 - semiconducting, 64

- carbon nanotubes (*cont.*)
 - separation, 64
 - single-walled, 69, 83, 187
 - surface impedance, 83
 - transistor, 64, 187
 - transport properties, 90
- carbon-based nanomaterials, 1
- carriers, 69, 108, 180, 181, 207, 209
 - concentration, 155, 178, 218, 219
 - mobility, 171
- charge density, 12
 - magnetic, 225
 - time-dependent, 149
- circuit models, 52, 68, 71, 74, 75, 77, 84, 85, 86, 101, 124, 154, 188, 189, 190, 191, 192, 201, 241
 - circuit libraries, 75
 - critically coupled resonator, 138
 - limitations, 74–75
 - parameter extraction, 70, 100
 - resonant circuit, 158
- circulator, 116
- clock frequencies, *see* operating frequencies
- CMOS, 3, 53, 245
- coaxial cable, 17, 271, 284, 289
- cold bias conditions, 192
- Cole-Cole diagrams, 174
- collision frequency, 155
- COMSOL, 71
- conductance per unit length, 19, 101
- conduction channel, 69, 194
- conductivity, 12, 204
- conformal mapping, 175
- connectors, 27, 55
 - precision, 55
- constitutive relations, 149, 150
- contacts, 4, 27, 53, 56, 61, 62, 65, 68, 84, 90, 192, 195, 196, 214
 - capacitive, 81
 - host structure, 93
 - impedance, 5, 6, 67, 80, 92, 102
 - ohmic, 93, 100
 - positioning, 67
 - reactance, 81
 - resistance, 101
- coordinate system, 19, 129, 174
- coplanar waveguide, 31, 52, 55, 56, 62, 63, 64, 71, 76, 81, 91, 92, 93, 97, 143, 164, 192, 194, 274
- copper nanowires, 2
- cost function, 46, 86, 235, 301
- Coulomb forces, 291
- coupling capacitance, 125, 126, 127, 128, 129, 143, 153, 154, 162, 165, 166, 175
 - conical tip model, 127–128, 205
 - parallel plate model, 125–126, 204–205
 - spherical tip model, 126–127
- CST Microwave Studio, 71
- current density, 12
 - magnetic, 226
 - time-dependent, 149
- cutoff frequency, 52, 55, 63, 188
- de Broglie wavelength, 36, 69
- Debye screening length, 291
- de-embedding, 5, 8, 11, 27–28, 32, 41, 53, 55, 75, 85, 90, 93, 97, 137, 138, 143, 187, 192
- defects, 6, 8, 165, 181, 182, 187, 203, 218, 243, 248, 255
 - subsurface, 144, 222
- demagnetization, 152
- demagnetizing factor, 253
- de-noising of images, 141, 298
- density of states, 69, 109, 177, 219
- depletion region, 208
- depletion width, 206
- depolarization, 152
 - surface, 152
- destructive interference, 45, 46, 49
- devices
 - active, 187, 191
 - carbon nanotube, 83, 84
 - CMOS, 53
 - empty reference, 53, 62, 63, 74, 93, 99, 194, 199
 - extreme impedance, 52, 82, 91
 - GaN nanowire, 101, 102
 - massively parallel, 64
 - microelectronic, 3
 - microfluidic, 296
 - microwave, 37
 - nanoelectronic, 52, 84
 - nanotransistor, 8, 199
 - nanowire, 63, 79, 80, 81, 84, 95
 - nonlinear, 85
 - one-dimensional, 177
 - on-wafer, 53
 - silicon-based, 207
 - symmetric, 80
 - Wheatstone bridge, 59
- dielectric constant, 176
- dielectric films, 81, 173–174
- dielectric substrate, 173
- dielectrophoresis, 4, 64, 92, 93, 192
- differential measurement, 60, 61, 134
- diffraction limit, 104, 279
- diode detector, 113
- dipole fluctuations, 292
- directional coupler, 58, 60, 113, 119
- dissipation volume, 161
- distributed circuits, 18
 - of low-dimensional systems, 70, 174
- dopant concentration, 7, 167, 170, 213
- dopant profiling, 8, 166–167, 168, 203, 204, 207
 - calibrated, 167, 211
 - scanning-probe-based, 203, 210
 - two-dimensional, 210
- dynamic microscopy modes, 293

- effective mass, 155
 Einstein, 105
 Einstein de Haas effect, 256–258
 electric displacement, 12, 150
 electric field, 12, 36, 73, 149, 150, 152
 electric susceptibility, 152
 electromagnetic materials equations, 12
 electrostatic capacitance measurement, 136
 electrostatic force microscopy, 137, 293–296
 electrostatic limit, 80
 electrostatics, 126
 elementary dipole, 129, 224, 226, 236
 empty device approach, 61–64, 102
 environmental cells, 304
 environmental control, 119
 equation of motion, 152, 252, 254
 equilibrium, 152, 206, 209, 243
 error box, 30, 31, 32, 85, 94, 140
 error models, 25, 27
 one-port, 139
 three-term, 60
 error terms
 directivity, 34, 49, 59, 136
 port match, 34, 49, 59, 136
 tracking, 34, 49, 59, 136
 evanescent modes, 32, 284
 evanescent waves, 105, 165, 236
 exchange energy, 150

 fabrication, 4, 6, 50, 53, 57, 61, 63, 94, 99, 187, 188, 192, 199
 far field, 129, 141
 Fermi energy, 109
 Fermi level, 69, 170, 181, 204, 209
 Fermi velocity, 69, 83, 178
 ferroelectric, 85, 171, 173
 ferromagnetic resonance, 143, 144, 251, 255, 258, 260, 261, 264, 266, 268, 270
 scanning thermal microscopy, 270
 thermally excited, 265
 ferromagnetic-ferroelectric composites, 149
 ferromagnets, 85, 251, 252, 264, 271
 multilayer structures, 262, 265, 268
 Fert, Albert, 264
 field effect transistors, 68, 187
 filter, 141
 finite element electromagnetic solvers, 72, 128
 memory requirements, 74, 80
 flexible substrates, 68
 fluorescence imaging, 279
 fluorographene, 188
 focused ion beam, 81, 92, 105, 203
 deposition, 92
 force-distance curve, 110
 forward problems, 226
 solution, 230
 Fourier transform, 229

 Fredholm integral equation, 229
 frequency shift, 114, 159, 161, 162, 165, 173, 226, 232, 233, 246, 291
 image, 114
 measurement, 161
 frequency-following feedback, 113
 fringe capacitance, 126, 132, 135, 284

 GaN nanowire, 84, 85, 86, 90, 92, 188, 192, 194, 198, 199, 297, 299
 device fabrication, 91–93
 device measurement, 93–97
 Geim, 174
 generalized reverse cascade matrix, 32
 genetic algorithm, 84, 85
 Gilbert damping parameter, 253
 grain size, 173
 graphene, 1, 2, 4, 36, 52, 69, 100, 173, 174, 175, 188, 203
 nanoribbons, 90, 188
 NSMM measurements, 174–179
 permittivity, 176
 resistive model, 175
 sheet resistance, 176
 spreading resistance, 175
 transistors, 188
 graphene-boron nitride, 188
 Green's function, 161
 ground penetrating radars, 222
 Gruenberg, Peter, 264
 guided waves, 11, 15
 backward-propagating wave, 19
 fields, 16
 forward-propagating wave, 19
 power, 18
 wavelength, 16
 guided-wave measurements, 5, 53, 55, 173
 gyromagnetic ratio, 151, 252, 257

 half space, 129, 157, 229
 half-wavelength resonator, 116
 Hankel function, 225
 harmonic time dependence, 17, 19, 21, 253
 Heaviside, 18
 height-dependent measurement, 114
 Hertz vector potentials, 14–15, 129
 hexagonal boron nitride, 179
 HFSS, 71
 high-resolution optical microscopy, 279–282
 high-speed imaging, 119
 h-matrix representation, 23
 host structures, 27, 53, 61, 62, 63, 64, 70, 71, 74, 81, 82, 91, 97, 190, 192, 196
 hybrid coupler, 40, 42, 44, 48, 49, 57, 139

 I/Q mixer, 49
 image charge method, 162
 image processing, 297–301

- impedance, 17, 22, 53, 64, 75, 137, 227
 antenna, 67, 129, 163, 283, 285
 bulk samples, 155
 characteristic, 17, 18, 19, 24, 30, 37, 39, 77, 79, 101, 128, 286
 contact, 64, 70, 83, 91, 190
 coupling, 125
 electric dipole, 130
 extreme, 6, 38, 39, 40, 43, 45, 46, 48, 53, 70, 71, 100
 graphene, 176
 images, 301
 layered material, 157
 load, 19, 21, 37, 38, 40, 117, 143
 local, 106, 135
 matched, 21, 131, 188
 matrix, 11, 23, 97, 195, 196
 measurements, 5, 7, 42, 49, 58, 131, 232, 241, 242, 272
 MOS, 178
 reference, 24, 50, 58, 96, 136, 140, 246
 resonator, 162
 sample, 125, 138, 158, 162
 semiconductor sample, 155
 source, 118
 surface, 83, 155, 157, 271
 tip-sample, 114, 128, 153, 155, 245, 287
 tunneling, 156
- impedance matching network, 40–42
- impedance mismatch, 6, 36, 37, 40, 53, 55, 57, 58, 67, 69, 70, 91, 192
 in nanoelectronics, 36
- impedance transformer, 59
- impulse measurement techniques, 142
- inductance, 155
- inductance per unit length, 19, 69, 101
- interconnects, 67, 83, 85, 90, 245
 carbon-nanotube-based, 2, 3, 5, 63, 84
 nanowire-based, 68
- interfaces, 6, 8, 55, 117, 165, 182, 187, 206, 210, 243, 248
 subsurface, 144, 222
- interfacial spin transport, 261
- interferometer, 42–45, 48, 139
 active signal injection, 48–50
- interferometer transition coefficients, 140
- interferometric scanning microwave microscope, 139, 140
- intrinsic linewidth, 143
- intrinsic properties, 6, 53, 62, 68, 188, 191
- inverse problems, 8, 85, 124, 223, 225, 226, 230, 231, 233, 235, 236, 242
 solution, 230–231
- isotropic media, 12
- JCMSuite, 71
- kinetic inductance, 64, 69, 75, 85, 90, 100, 176, 188
- Kirchoff's laws, 19
- Kittel resonance condition, 254
- Landau-Lifshitz equation, 150, 252
- Landé g factor, 150, 151, 252
- Laplace equation, 17, 288
- Lennard-Jones potential, 110
- line-reflect-match calibration, 29, 191
- Liouville's equations, 151
- lithography, 53, 58, 64, 71, 76, 192
- local density of states, 109
- local interactions, 150
- local regression, 301
- lock-in amplifier, 108, 112, 114, 116, 166, 172, 178, 180, 263
- Lorentz force law, 251
- Lorentz gauge, 13, 14
- Lorentzian, 117
- loss tangent, 114, 155
- low-dimensional systems, 67, 69, 173, 251
 quantum effects, 67
- lumped-element circuits, 18, 81, 100, 117, 153, 159, 174, 205, 215, 271
- macroscopic dipole density, 151
- magnetic dipole, 129, 143
- magnetic field, 12, 13, 15, 36, 110, 143, 149, 150, 152, 228, 229, 251, 252, 255, 257, 261, 262, 274, 293
- magnetic induction, 12, 150
- magnetic resonance force microscope, 269
- magnetic susceptibility, 152
 tensor, 253, 256
- magnetization, 12, 13, 143, 149, 150, 151, 152, 252, 253, 265, 266, 271, 272
 elliptical motion, 259
 motion, 263, 273
 non-uniform motion, 255
 precession, 252, 268
 uniform precession, 253
- magnetization dynamics, 144, 251–255, 264, 272, 274
 all-electrical measurements, 262–264
 inductive measurements, 266
 multilayer structures, 265
 NSMM, 270
- magneto-electric materials, 150
- matched load, 54
- material parameters
 extraction, 68, 70, 125, 208, 218, 242
 microscopic, 13
 modeling, 83, 190, 296
- materials characterization, 8
 fundamentals, 149–152
 local, 149
 local spectroscopy, 173
- Maxwell's equations, 11–12, 124, 150
 in cylindrical coordinates, 129
 magnetostatic limit, 255
- Maxwell-Garnett mixing formula, 291
- Maxwell-Lorentz microscopic equations, 149
- mean free path, 67, 69
- measurement science, 4, 5

- measurement uncertainties, *see* uncertainties
- mechanical break junctions, 4
- metal oxide semiconductor, 166, 167, 178, 204, 206, 207
capacitor, 167, 204, 209, 210
theory, 166, 170, 207–210
- metal-semiconductor junction, 206–207
- metamaterials, 149
- method of images, 116, 126
- method of least squares, 47
- microbridges, 68, 71, 81
- microcantilever, *see* cantilevers
- microcapacitors, 131–134, 215
- microscopic dipole density, 151
- microstripline, 31, 173, 262
- microwave network
one-port, 6, 27, 33, 37, 39, 45, 59, 60, 117, 123
three-port, 42, 46, 116
two-port, 24, 27, 29, 63, 76, 80, 86, 123, 303
- microwave signal path, 33, 106, 111, 112, 117
- microwave solvers, *see* finite element electromagnetic solvers
- microwave tomography, 222–223
image reconstruction, 227
- microwaves, 1, 145, 282, 296
- mid-gap states, 210
- millimeter-waves, 1
- mismatch standard, 54
- mixing resistance, 268
- modeling, 6, 41
finite-element, 69, 71, 74, 77, 124, 144, 180, 246, 266
lumped-element, 80–82, 124
nanoscale components, 70
NSMM, 117, 241
parasitic capacitance, 64
three-dimensional, 72
tip-sample interaction, 109, 125, 153
transistor, 189, 191
transmission line, 77–79, 124
- molecular beam epitaxy, 93
- molybdenum disulfide, 180
- Moore's law, 1
- multiferroic, 85
- multilayer media, 156–158
biological, 287–290
- multiline thru-reflect-line calibration, 28, 29–31, 32, 54, 62,
71, 72, 93, 95, 96, 191, 192, 194
- multimode calibration, 29, 31–33, 79, 145
- multiphysics simulation, 180
- multiport device, 22, 24, 42
- myosin, 303
- nanoelectronics, 1, 4, 68, 70, 90, 104, 187, 203
- nanoscale building blocks, 3, 4, 6
- nanowires, 53, 68, 69
conductivity, 77
contact resistance, 75, 77, 79, 81
cross section, 81
- impedance, 76
- metallic, 2, 68, 70, 76
resistivity, 75
semiconducting, 1, 52, 90
- near field, 105, 123, 124, 128, 129, 141, 153, 226
conditions, 154
- near-field scanning microwave microscope, 6, 7, 33, 123,
203, 251
AFM-based, 107, 119, 216
aperture-based, 111–112
biological applications, 296, 301–304
capacitance calibration, 130–135, 214–216
complex impedance calibration, 136
customized, 119
depth sensitivity, 238, 243, 296
designs, 104, 123, 272
de-trending images, 301
dopant profiling, 207, 213
electrostatic force calibration, 136–137
FMR, 251
high-speed, 119
history, 104–106
images, 132, 133, 135, 298, 299, 301
in liquid, 119
local and non-local interactions, 141
local spectroscopy, 181, 213
magnetic measurements, 144, 251, 270
measurement uncertainty, 165
modeling, 153, 180, 233, 241, 297
non-resonant, 117–118
operating frequency, 117, 128, 136, 167, 171, 299
reflection mode, 116
resonant, 114–117, 158, 159, 168, 171, 214
selection frequency, 170
sensitivity, 117
signal-to-noise ratio, 114, 139, 179
STM-based, 113, 141, 156
subsurface measurements, 138, 174, 223, 233, 242–248
time domain, 141–142
tip-based, 112–114
transmission mode, 144
two-port, 153
- near-field scanning optical microscopy, 282
- near-field scattering, 223
- neural networks, 85
- Newton-Kantorovich method, 235
- NISTcal, 30
- noise, 5, 79, 165, 191, 265, 298, 300
mechanical, 54, 119
thermal, 119
- noise power spectral density, 265
- nonlocal interactions, 150
- Novoselov, 174
- nuclear magnetic resonance, 143, 251
- ohmic contacts, 101
- on-wafer calibration, 28, 31, 70, 71

- on-wafer measurement, 5, 27, 52, 57, 61, 64, 90, 93, 98, 100, 187, 194
 - best practices, 53–57
 - simulation, 72
 - standards, 57, 94
 - test platform and instrumentation, 54
- on-wafer measurements, 143
- open circuit, 21, 22, 29, 38, 60, 61
- operating frequencies, 1, 68, 69, 113, 117, 137, 139, 168, 243, 244, 294
- optimization, 45, 47, 71, 137, 140, 197, 201
 - of devices, 4, 61, 91, 93, 188
 - iterative, 85
- optoelectronics, 3, 8
- packaging, 68
- parameter extraction, 52, 76, 85, 90, 124, 137, 153, 167
- parametric curve, 21
- parasitic capacitance, 5, 63, 64, 75, 101, 109, 125, 134, 138, 154, 194, 195
- parasitic coupling, 53, 62, 64, 75, 91, 125
- parasitic impedance, 125
- parasitic reactance, 6, 62, 64, 188, 213
- parity transformation, 150
- Pauli repulsion, 109
- permeability, 7, 85, 154, 160, 224, 227, 234, 271, 272, 283, 285, 287
 - of free space, 13, 36, 151, 253
 - tensors, 12, 228
- permittivity, 7, 85, 105, 112, 114, 127, 130, 134, 154, 155, 160, 162, 164, 165, 173, 204, 206, 208, 214, 216, 224, 227, 229, 233, 234, 235, 237, 238, 240, 246, 248, 283, 284, 287, 291, 296, 297, 301
 - of free space, 13, 36, 151, 205, 291, 295
 - Lorentz-Drude, 155
 - profile, 285
 - subsurface, 241
 - tensors, 12, 172, 228
- perturbation theory, 159, 228
- phase shifter, 117, 168
- phosphorene, 179
- photoacoustic effect, 270
- photoactivated localization microscopy, 281
- photolithography, *see* lithography
- photonic bandgap crystals, 149
- piezoelectric transducers, 111
- Planck's constant, 36, 69, 83, 109
- plane wave decomposition, 236
- plasma frequency, 155
- Poisson's equation, 211, 216
- polarization, 12, 13, 149, 150, 151, 152, 171, 172
 - dielectric, 150
- post processing, 141
- power, 3, 5, 17, 18, 21, 37, 41, 153, 260
- power divider, *see* power splitter
- power spectral density, 267
- power splitter, 40, 42, 43, 44, 46, 47, 48, 49, 57
- power waves, 23, 24, 32
- Poynting's vector, 18, 154
- probes, 7, 27, 31, 33, 245, 270, 297
 - antenna, 283
 - coaxial, 105, 284
 - electric dipole, 143, 157
 - geometry, 123
 - ground-signal-ground, 55, 61, 91, 94, 99
 - high-impedance, 60
 - inductive loop, 155
 - loop, 272
 - magnetic, 256
 - nanowire, 105, 216
 - near-field, 104, 123, 125
 - needle, 112
 - non-resonant, 123
 - NSMM, 106
 - on-wafer, 53, 55, 94, 191
 - pitch, 55
 - planarization, 55
 - positioning, 55–56
 - resonant, 114, 123
 - scanned, 111
 - skate, 55
- probe-sample coupling, *see* tip-sample interaction
- propagation constant, 16, 19, 30, 31, 77, 79, 95, 96, 128, 156, 160, 194, 245, 286
 - of free space, 157
- Pt nanowire, 75, 76, 78, 81, 82, 86
- quadrupole density, 150
- quality factor, 105, 108, 114, 117, 123, 138, 159, 160, 161, 162, 163, 164, 165, 174, 175, 247, 258, 291
 - effective, 117
 - image, 114
 - measurement, 161–162
- quantum capacitance, 69, 75, 85, 90, 101, 177, 178, 181, 188
 - graphene, 176
 - one-dimensional, 178
- quantum Hall effect, 36
- quantum resistance, 36, 38, 58, 69, 85
- quarter-wavelength resonator, 115
- radio-frequency scanning tunneling microscope, 119
- reciprocity principle, 23
- redundant measurements, 45–47, 79, 81
- reference planes, 49, 80, 136, 145
 - coaxial, 27
 - definition of, 25
 - translation of, 25, 62, 70, 77, 96, 138, 194
- reference samples, 62, 137, 164, 168, 204, 211, 212, 214, 218, 287
- reference standards, 27, 46, 47, 139
- reflection coefficient, 21, 23, 26, 33, 37, 43, 45, 46, 49, 58, 117, 123, 134, 136, 137, 157, 158, 161, 167, 180, 213, 232, 233, 241, 242, 247, 272, 284, 285, 300, 301

- definition of, 21
- NSMM, 117, 128, 131, 153, 159, 166, 207, 214, 223
- signal-to-noise ratio, 246
- reflectometer, 40, 42, 43, 44, 45, 46, 48, 50
 - one-port, 42
 - reflection coefficient, 42
- relative permittivity, *see* permittivity
- resistance per unit length, 19, 101
- resonance frequency, 105, 108, 159
- resonant cavities, 123
 - equivalent circuit, 162
 - power dissipation, 161
- resonant circuit, 113, 158
- retarded potentials, 14
- Ricatti form, 158
- Rytov approximation, 231

- scanning capacitance microscope, 178, 203
 - dopant profiling, 210–212
- scanning electron microscope, 5, 76, 81, 83, 92, 189, 271, 304
- scanning Kelvin probe microscope, 203, 218
- scanning nonlinear dielectric microscope, 171–173
- scanning probe microscope, 4, 104, 107
 - depth profiling, 222
 - distance following techniques, 106–109
 - spatial resolution, 6
- scanning spreading resistance microscope, 203, 218
- scanning tunneling microscope, 5, 33, 107, 141, 218
 - constant current mode, 114
 - radio frequency, 107, 272
 - spatial resolution, 105
- scattering parameters, 5, 6, 22, 23, 27, 28, 49, 53, 54, 60, 62, 71, 72, 73, 78, 83, 84, 85, 86, 90, 94, 96, 98, 102, 140, 191, 192, 197, 198, 199, 200, 215
 - calibrated, 96
 - definition, 22–23
 - matrices, 11, 42, 44
 - reciprocal, 24
 - symmetric, 24
- scatterplot, 298
- semiconductor, 1, 3, 155, 165, 170, 204, 206, 209, 210, 216, 218
 - FET, 192
 - oxide layer, 166, 167
 - two-dimensional, 179
- sensors, 68
- sheet resistance, 7, 175
- short circuit, 21, 22, 29, 54, 60, 61, 94
- short-open-load-thru calibration, 29, 191
- signal flow graphs, 11, 25–27
 - Mason's rules, 26–27
 - signal loops, 26
 - Wheatstone bridge, 58
- silicene, 179
- simply-connected domain, 234
- simulations, 25, 85, 129, 131, 138, 143, 174, 181, 191, 201, 206, 210, 227, 245, 267
 - circuit model, 71
 - finite-element, 77, 83, 124
 - full wave, 71, 82
 - meshing, 80
 - molecular dynamics, 292
 - single-mode propagation, 31, 137, 145
 - six-port network analyzers, 29
 - six-port reflectometer, 5
 - skin depth, 7, 8, 170, 232, 243, 244
 - Smalley, Richard, 2
 - Smith chart, 21, 22, 29, 39, 40, 41, 42, 49
 - Sommerfeld, 129, 147
 - Sommerfeld identity, 225
 - Sommerfeld integral, 129
 - space charge density, 170
 - spatial resolution, 105, 107, 138, 143, 149, 203, 209, 243, 247, 270, 272, 279, 281, 294, 296, 301
 - spectral decomposition, 225
 - speed of light, 13
 - spin, 69, 150, 151, 251, 252, 254, 257, 262, 272
 - spin degeneration, 177
 - spin Hall effect, 268
 - spin pumping, 268
 - spin rectification effect, 263
 - spin torque, 266–268
 - spin valve, 265
 - spin wave, 144, 255, 268
 - spin-orbit coupling, 261
 - split post resonator, 164
 - spreading resistance, 174, 175
 - STATISTICAL, 30
 - statistical density operator, 151
 - stimulated emission depletion microscopy, 280
 - stray capacitance, *see* parasitic capacitance
 - stripline resonator, 116
 - subsurface imaging, 119
 - sub-wavelength aperture, 105, 111, 143
 - superlocalization, 281
 - super-resolution fluorescence microscopy, 280
 - surface band bending, 210
 - surface charge density, 170
 - surface current density, 12
 - surface resistance, 170
 - switch terms, 30
 - Syngé, 105

 - tagging methods, 279
 - Taylor series, 79
 - Telegrapher's equations, 19
 - terahertz, 69, 187
 - Tersoff-Hamann theory, 109, 110
 - test fixtures, 27, 28, 76
 - test platforms, 68, 214
 - thru, 29, 94
 - thru-reflect-line calibration, 29
 - Tikhonov's regularization, 230
 - time-domain measurements, 142

- time-resolved Kerr microscopy, 262
- tip geometry, 137, 154, 205
 effective tip radius, 126, 131, 134, 136, 163, 205, 209
 tip apex, 109, 126, 295, 296, 297
- tip-sample capacitance, 124, 172, 207, 246, 300
- tip-sample interaction, 8, 124, 125, 136, 153, 155, 156, 159, 163, 165, 174, 213, 214, 215
- tip-sample models, 124, 204, *see also* coupling capacitance
- topographic artifacts, 296–297
- topographic cross-talk, 297
- topographic images, 109
- torque wrench, 55
- total internal reflection fluorescent microscopy, 281
- trace operator, 151
- transistors
 carbon nanotube, 187
 cold state measurements, 190
 DC electrical measurements, 191
 graphene, 188
 modeling, 189–190
 nanowire, 93
 transconductance, 187, 198
 transit time, 198
- transition metal dichalcogenides, 3, 173, 179, 180, 181, 188
 measurement, 179–182
- transmission coefficient, 123, 144, 153, 164
- transmission electron microscope, 5
- transmission line, 15, 16, 18, 19, 21, 22, 23, 25, 30, 68, 69, 74, 77, 79, 80, 85, 86, 91, 101, 123, 143, 153, 156, 158, 160, 243, 245, 286
 calibration lines, 94
 impedance, 21
 modeling, 71, 77–79
 theory, 11, 18–22
- transverse electric (TE) wave, 15, 16, 36
- transverse electromagnetic (TEM) wave, 15, 16, 18, 33, 36, 70, 79, 287
- transverse magnetic (TM) wave, 15, 16, 36, 287
- tungsten diselenide, 179
- tuning fork feedback, 108
- tunneling current, 107
- tunneling resistance, 156
- two-dimensional electron gas, 36, 176, 251
- two-dimensional materials, 1, 3, 53, 176, 181, 188
- two-port device, 23, 25, 32, 53, 76, 195
- ultra-high vacuum, 107
- uncertainties, 5, 46, 57, 64, 98, 100, 198, 200, 284
 nanofiber devices, 97–100
 statistical, 79, 81, 140, 164, 165
 type A, 97, 199
 type B, 98
- uncertainty budget, 99
- uniqueness, 227
- validation, 6, 62, 70, 71, 75, 81, 85, 136, 191, 201
 of tip-sample models, 129
- valley parameter, 177
- van der Waals forces, 109
- van der Waals heterostructures, 174
- vector and scalar potentials, 12–14
- vector network analyzer, 24, 27, 28, 29, 31, 42, 43, 44, 45, 47, 48, 49, 54, 56, 95, 124, 131, 132, 136, 139, 140, 145, 168, 214, 266
- verification, *see* validation
- verification kit, 54
- vertical electrical dipole, 157, 273
- vertical vias, 84
- vortex, 264
- wave equations, 15, 72
- wave propagation, 11
- waveguide, 5, 18, 31, 36, 50, 54, 55, 74, 116, 123, 138, 143, 161, 173, 225, 270
- wavelength, 16, 18, 29, 73, 80, 100, 104, 112, 129, 131, 132, 153, 225, 226, 228, 231, 279, 281, 285
- weighting function, 141
- Wheatstone bridge, 53
 measurement of nanotubes, 57–61
- wireless communications, 1
- yttrium iron garnet, 143, 268