

Index

- 100-year loading condition, 322
 20-node solid elements, 61, 179, 193, 283, 292
 4-node elements with internal degrees of freedom, 279
 4-node shell elements, 283
 5-element strip gauge, 44
 8-node shell elements, 193, 283
 8-node solid elements, 283
- acceptable safety level, 364
 acceptance criteria for defects, 126
 accidental limit state, 13, 362, 466, 480
 accommodation platform, 6
 accumulated fatigue damage, 355, 368, 401, 474
 accumulated probability, 156, 478
 accumulation of damage, 164
 accumulation of load cycles, xviii, 355
 accurate tolerances, 398
 ACFM. *See* alternating current field measurements
 acoustic emission, 482
 actuator, 65
 adhesion, 391
 Ag/AgCl reference cell, 154
 air environment, 125, 414, 433
 aircraft, 2, 5
 aircraft industry, 3
 air-filled members, 466
 air-hammer, 346
 Airy wave theory, 405
 ALARP, 16
 Alexander L. Kielland, 6, 9, 203, 274, 416
 allowable stress ranges, 78, 120, 319, 320, 423
 ALS. *See* accidental limit state
 alternating current
 field measurement, 332, 337, 481
 potential drop, 337
 alternating flux, 336
 alternating loading, 437, 442, 445
 alternating magnetic flux, 336
- aluminum, 113, 334, 389, 390
 helideck structures, 390
 plate to steel plate, 390
 structures, 343
 American Petroleum Institute, 435
 amplitude, 4
 analysis program, 16
 analytical approach, 376, 447
 analytical equation, 183, 232
 angle deviation, 176, 227
 angles, 488
 angular deviation, 174
 angular misalignment, 33, 175, 176
 annual failure probability, 15, 156, 164, 167, 317
 anode attachment, 215
 API. *See* American Petroleum Institute
 arc spraying, 390
 area of ring stiffener, 242
 arithmetic average height parameter, R_a , 352
 artificial defects, 338
 As Low As Reasonably Practicable, 16
 as-built tolerances, 187
 as-welded condition, 343, 345
 atmospheric service, 389
 atomic spacing, 20
 attachment length, 50, 143, 148, 149, 432
 austenitic alloys, 384
 austenitic stainless steels, 384
 austenitic steel, 113, 131
 AUT, 335. *See* automated ultrasonic testing
 automated ultrasonic testing, 335
 automobile engines, 114
 automobile industry, 3
 axial force, 35, 175, 176, 248, 264, 404, 437
 axial load, 254
 axial misalignment, 188, 234
 axisymmetric finite element analysis, 211, 236, 251
 axisymmetric finite element model, 232, 234
- back gouging, 413
 backing bar, 329
 bainite, 138

- baking of bolts, 384, 390
- ballast condition, 55
- ballast water, 13
- Basquin, 2, 100
- Battelle approach, 280
- Bauschinger effect, 96
- Bayesian updating, 468
- beam on elastic springs, 438
- beam theory, 109, 239
- bearing surfaces, 389
- bearing type or shear connections, 380
- bearings with fillet-welded connections, 273
- bending moment, 438
- bending stress, 340
- bevel washer, 387
- bias, 264, 368
- biaxial stress, 28, 86
- bilinear S-N curve, 315
- bilinear stress distribution, 292
- bimetallic corrosion, 390
- blow counts, 401
- boat sample, 80
- bolt, 379
 - diagram, 395
 - diameter, 379
 - direct tensioning, 397
 - fitted bolts, 380, 382, 388
 - heavy-duty bolts, 396
 - high quality bolts, 396
 - pretension load, 397
 - stress area, 393
 - stud bolt, 379
 - threads, 382
 - torque method, 397
- bolted connections, 379
- bolted flanges, 381, 390
- bond strength, 271, 435, 436
- boundary conditions, 2, 162, 174, 178, 181, 228, 240, 282, 401, 411, 427, 432
- box, 398
- box test specimen, 458
- brace, 252, 273, 404
 - inclination angle, 254
 - outside diameter, 253
 - thickness, 254
- bracket toe, 23
- bridge, 13, 485
- bridge deck, 281
- brittle development, 409
- brittle material, 5
- buckling arrestor, 241
- buckling stiffener, 53
- built-up sections, 278
- bulb section, 24, 54, 59, 61, 277, 278, 283, 488
- bulging factor, 496
- bulkhead, 69, 178, 183, 219, 226, 227, 243, 300
- bushes, 390
- butt weld, 32, 125, 138, 140, 174, 177, 182, 184, 206, 210, 212, 231, 288, 307, 323, 330, 368, 371, 398, 408, 433
- caisson, 261
- calcareous deposit, 130, 154
- calculated
 - crack growth, 348
 - fatigue life, 433
 - values, xix
- calculation
 - errors, 16
 - reduced stress, 344
 - stress concentration, 344
- calibration, 16, 149, 280, 296, 376, 422, 427, 432, 434
- capacity curve for grouted connection, 462
- capillary action, 334
- carbon steel fasteners, 384
- cast joint, 150, 252, 253
- cast nodes. *See* cast joint
- catastrophic failure, 364
- cathode ray screen, 334
- cathodic protection, 154, 383
- centric neutral axis, 246
- certification, 11
- chains, 11, 431, 491
- characteristic, 13
 - capacity, 14, 157, 443
 - cube strength, 442
 - fatigue capacity, 369
 - friction coefficient, 447
 - load, 13
 - number of cycles to failure, xviii
 - S-N curve, 157, 160, 163
 - stress range, 369, 370
 - value, 152
- Charpy V-notch, 386
- Charpy V values, 408
- chemical requirements, 386, 396
- chord, 404
 - length parameter, 254
 - length to diameter ratio, 259
 - outside diameter, 253
 - radius to thickness ratio, 254
 - thickness, 253
- circumferential ring stiffener, 217
- circumferential weld, 33, 34, 150, 191, 206, 215, 218, 244, 248, 435. *See also* girth weld
- clad pipes, 131
- clamped connection, 380
- classical shell theory, 109, 205, 236, 454
- classical theory for spherical shells, 248
- classification standard, 7
- cleavage of grains, 410
- close visual inspection, 466, 467, 481
- closed form expressions, 312
- closure girth welds, 209, 266
- clustered pores, 139, 332
- C-Mn steel, 131
- CNG, 237. *See* compressed natural gas
- coalescence of voids, 410
- coarse threads, 389
- coating, 337, 343, 351, 389
- coefficient of friction, 380, 397

- coefficient of variation, 264, 357
 Coffin-Manson, 100, 306
 coil, 336
 cold forming, 118, 119
 cold rolling, 388
 cold working, 349
 collapse, 362
 collar plate, 53, 275
 collinearity, 227
 combined
 axial load and bending moment, 436
 effect of normal stress and shear stress, 85
 load and response process, 322
 loading, 62, 64, 72
 low-cycle and high-cycle fatigue, 106
 stress, 111, 198
 compact flanges, 190
 complementary incomplete gamma function, 312, 315
 complete elliptic integral, 494
 compressed natural gas, 16, 369
 compression of clamped plates, 393
 compressive residual stresses, 339, 349
 compressive stresses, 347, 350, 422
 compressive strut, 452
 computer software, 16
 concave profile, 342
 concrete structure, 462
 conductor frames, 482
 conductor material, 336
 conductors, 253
 cone, 222, 226, 394
 confidence, 159, 160, 161, 168, 337, 364
 confinement, 460
 conical connection, 215
 conical junction, 222
 conical transition, 222, 224
 connector, 168, 398
 connector in tethers, 398
 consequences, 367
 substantial, 367
 without substantial, 367
 consequences of failure, 140, 160, 329, 330, 359, 363, 466
 consistent calculated fatigue lives, 467
 constant amplitude loading, 3, 130, 158, 346, 441
 constant amplitude testing, 26, 56, 158, 347
 constant slope S-N curve, 127
 constant stress direction, 84
 contact pressure, 392
 contact stress, 438
 contact surfaces, 380
 contamination, 329
 contour around crack tip, 427
 contrast paint, 333
 conversion, 346
 cope hole, 60, 177, 178, 179, 181, 183, 184, 190
 copper, 334
 correlation, 348, 366, 370, 478
 corrosion, 465
 allowance, 465
 fatigue, 154, 155
 pits, 155
 protection, 351, 379, 389, 396, 399, 465
 protection of bolts, 390
 rate, 390
 resistant alloy, 384
 corrosive environment, 31
 counting method, 4
 coupled differential equations, 425
 CoV, 264, 357, 366, 368, 377. *See* coefficient of variation
 cover plate, 75, 301
 CRA. *See* corrosion resistant alloy
 crack, 141, 330, 332
 curvature, 415
 ends, 348
 shape, 411
 size through thickness, 137
 crack closure, 326, 349, 423, 431
 crack detection, 469
 crack driving force, 427
 crack driving stress range, 349, 471
 crack growth, 416, 433, 471
 analysis, 46
 curves, 427
 equation, 410
 parameters, 433
 crack initiation, 4, 56, 59, 101, 130, 141, 143, 155, 271, 306, 350, 389, 410, 416, 425, 427
 crack tip, 10, 80, 121, 145, 155, 335, 348, 410, 427
 crack tip opening displacement, 5, 408, 428, 482
 cracked specimen, 428
 cracking of grout, 440
 crack-like defects, 335
 crane pedestal, 226
 creep, 385, 397
 critical crack size, 427
 cross-type filament, 31
 crown point, 259
 cruciform joint, 103, 138, 143, 145, 288, 290, 305, 308, 309, 328, 330, 341, 344, 409, 413, 415
 crushing of grout, 442
 crystal lattices, 28
 CTOD. *See also* crack tip opening displacement
 CTOD design curve, 5
 CTOD testing, 5, 429
 cumulative distribution, 310, 316
 cups filled with grease, 389
 curing, 444
 current-carrying coils, 481
 cut threads, 388
 CVI. *See* close visual inspection
 cyclic
 slip, 19
 strain controlled test, 96
 strain hardening exponent, 97
 stress-strain curve, 96

- cylindrical shaped burr, 343
 cylindrical shell, 205, 241
- damage accumulation hypothesis, 4
 damage statistics, 275
 damping, 400
 dampness, 329
 danger of loss of human life, 367
 deck structure, 105, 316, 321, 401
 deepwater platform, 404
 defect distribution, 472
 defects, 19
 defects in welded connections, 138
 deflection range, 488
 deformed elements, 282
 degradation of structures, 465
 Department of Energy, 5, 184, 271, 273, 339, 435
 design fatigue factor, 21, 112, 319, 400, 415, 420, 465, 486. *See also* DFF
 design methodology, 372
 design criterion, 62
 design format, 369
 design premises, 15
 design standard, 126
 design S-N curve, 32, 134, 157, 160
 design values, 471
 capacity, 13
 chart, 319, 443
 load effect, 13, 370
 point, 378
 detectable size of crack, 473
 detecting surface-breaking flaws, 337
 detection event, 473
 deterministic crack growth
 analysis, 427, 475
 development, 469
 deterministic discrete fatigue analysis, 401, 402
 DFF, 156, 319, 357, 360, 366, 367, 378. *See also*
 design fatigue factor
 diameter ratio, 254, 257
 differential equation, 205, 228, 239, 425, 475
 dimensions, 396
 direct tensioning of bolts, 397
 direction of fluctuating stress, 123
 discipline checking, 16
 dislocation theory, 3
 displacement control, 46
 displacement transducer, 456
 dissimilar metals, 390
 distance between shear keys, 442
 distortion, 39, 174
 documentation, 379
 dog-bone-shaped test specimens, 33
 double-side welded joints, 267
 double-sided brackets, 52
 double-sided fillet welds, 221
 double-skin grouted joints, 271
 doubling plate, 74, 120, 280, 291, 317
 drag coefficients, 252
 driving energy, 401
- driving of piles, 400
 drum, 221, 231
 ductile fracture, 410
 ductile material, 100, 429
 ductility, 15
 ductility of individual members and joints, 365
 dull hammer tips and bits, 346
 duplex, 131
 dye penetrant, 134, 334
 dynamic actions from wave loading, 107
 dynamic amplification, 404
 dynamic amplification factor, 402
 dynamic loading, 150, 329, 343, 348, 350, 379, 444
 dynamic pressure, 13
- early age cycling, 442, 462
 EC, 336, 348, 483. *See* eddy current
 eccentricity, 61, 67, 175, 176, 177, 182, 183, 208, 209, 210, 225, 226, 227, 229, 231, 232, 237, 239, 240, 254, 384. *See also* misalignment
 economics, 363
 ECSC procedure, 305
 eddy current, 332, 336, 481
 effect of coating, 156
 effect of correlation, 373, 480
 effect of surface roughness on fatigue strength, 353
 effect of weld length, 370
 effective
 area, 394
 bolt stress area, 387
 crack length, 10
 hot spot stress, 285, 286, 288, 303, 404
 length, 261, 263, 276
 number of shear keys, 462
 section modulus, 488
 spring stiffness, 455
 stiffness, 394
 stress cycling, 116
 stress intensity factor, 431
 stress range, 88
 Efthymiou equations, 257
 elastic length, 205, 226, 237, 444, 454
 elastic limit, 2
 elastic section modulus, 175, 208, 221, 260, 276, 485
 elastic strain, 20
 elastic strain range, 99
 elastic stress concentration factor, 3, 101, 106, 173.
 See also stress concentration factor and SCF
 elastic stress field at crack tip region, 410
 electric current, 390
 electric grinder, 343
 electrical
 impedance of coil, 336
 isolation, 390
 resistance, 337
 electromagnetic induction, 336
 electromagnetic resonant test machines, 31
 electromagnetic technique, 337

- electroplating, 383
 elliptical, 494
 elliptical shaped transitions, 398
 elongation at fracture, 95, 386
 elongation capacity of steel material, 397
 elongation of bolt, 386, 393
 embrittlement, 382, 386
 end cap effect, 231
 endurance, 109, 154, 192
 energy release rate, 5, 428
 engagement in nut, 381
 engineering approach, 162
 engineering assessment, 478
 engineering judgment, 27, 162, 337, 479
 engineering shear stress, 65, 72, 112
 engineering strain, 95
 engineering stress, 95
 enhanced control, 238, 370, 371, 372, 374, 375
 environmental consequences, 363
 environmental criteria, 400
 environmental data, 468
 equivalent load effect, 355
 equivalent stress range, 27, 38, 72, 201, 313, 416, 492
 estimated reliability, 364
 event margin, 476
 expansion of hole, 349
 extended fatigue life, 348
 extensometer, 96
 external force, 395
 external load, 385
 extrusions, 19, 20
- fabrication, 360
 misalignment. *See also* misalignment and eccentricity
 quality, 83
 standard, 126
 fabrication tolerances, 33, 35, 126, 138, 162, 168, 173, 174, 184, 231, 236, 291, 330, 369, 370, 371, 372, 380, 381, 441, 447
 factor accounting for modeling error, 366
 FAD. *See* failure assessment diagram
 fail-safe, 2, 5, 14
 failure assessment diagram, 429, 489
 failure mechanism, 15, 363
 failure mode, 22, 23, 24, 25, 75, 128, 339, 382, 387, 437, 442
 failure path, 366
 fastener, 383. *See* bolt
 fatigue capacity, xviii, 3, 8, 116, 168, 173, 203, 266, 349, 352, 355, 379, 385, 389, 392, 440, 467, 480, 485
 curve, 442
 fatigue crack arrester steel, 138
 fatigue crack growth, 4, 5, 19, 59, 107, 140, 145, 202, 324, 410, 465, 493
 from a surface irregularity or notch, 25
 from weld root, 23
 from weld toe, 22
- fatigue damage, xviii, 322, 403
 accumulation, 355
 hypothesis, 4
 rate from several analyses, 478
 fatigue design of ship side plates, 486
 fatigue ductility
 coefficient, 100
 exponent, 100
 fatigue endurance, xviii
 fatigue limit, 4, 26, 112, 114, 127, 158, 167, 173, 486
 fatigue limit state, 13, 252, 327, 442, 456
 fatigue strength, xviii, 31, 43, 84, 95, 100, 106, 113, 128, 131, 134, 136, 137, 141, 142, 150, 151, 154, 155, 158, 214, 219, 237, 255, 306, 327, 328, 330, 331, 339, 342, 346, 347, 352, 353, 388, 391, 487
 coefficient, 100
 exponent, 100
 FCA. *See* fatigue crack arrester steel
 FCAW, 64. *See also* flux core arc welding
 FEA. *See* finite element analysis
 ferrite, 138
 ferromagnetic materials, 28, 329, 332, 337, 348, 389
 fibrous faces, 410
 fictitious crack, 149, 410
 fictitious notch radius, 103
 fillet welds, 111, 176, 291
 filling and emptying, 369
 final crack size, 412
 final fracture, 19, 136, 145, 382, 429, 431
 financial consequences, 367
 fine threads, 389
 finite element analysis, 25, 27, 32, 50, 55, 60, 101, 178, 210, 271, 272, 274, 275, 340, 349, 427, 431, 438
 finite element method, 3, 6, 11, 280, 308, 428
 finite-width correction function, 496
 first-order reliability, 163
 fitted bolts, 380, 382, 388
 fixed spreader-moored arrangements, 407
 flange connection, 242, 384
 flanges, 397
 flare tower, 13, 266, 322, 485
 flaws, 332
 flexibility, 393, 452
 floating production, storage and offloading vessels, 78, 274, 353, 407, 466
 flooded member detection, 466, 481
 FLS. *See* fatigue limit state
 fluctuating stress, 190
 fluorescent particles, 481
 flux core arc welding, 63
 FMD, 483. *See also* flooded member detection
 footprints, 11
 force range, 31, 485
 foundation design, 405
 foundation piles, 401
 FPSO, 177, 346, 407, 479, 483, 486, 488, 504. *See also* floating production, storage and offshore loading vessel

- FPSO Fatigue Capacity JIP, 51, 52, 61
 fracture mechanics, 5, 46, 125, 408, 410, 428, 469, 489, 492, 500
 fracture mechanics analysis, 432
 fracture toughness, 5, 136, 153, 327, 386, 412, 415, 428, 429, 430, 482, 489, 490, 493
 free spans, 13
 frequency domain analysis, 402, 403. *See also*
 stochastic fatigue analysis
 frequency of failure, 364
 fresh water, 154
 fretting, 113, 392
 friction coefficient, 392, 438, 447, 450, 485
 frictional resistance, 392
 full penetration weld, 23, 24, 87, 176, 191, 210, 272, 299, 305, 344, 413
 full-scale tests, 440
 fully reversed load cycling, 463
- galling, 387
 galvanizing, 382
 Gamma functions, 312, 475
 gamma rays, 336
 gap between braces, 254
 gap parameter, 254
 gas pores, 336
 gas turbine disks, 114
 Gaussian distribution, 158, 160
 Gaussian points, 194, 284, 305
 general visual inspection, 467
 geometric stress, 109
 geometrical arrangement, 123
 geometry function, 145, 410, 411, 413, 424, 425, 431, 432, 492, 496
 girth weld, 33, 150, 206, 249, 343, 398, 428. *See also*
 circumferential weld
 Glinka's rule, 101, 102
 global dynamics, 402
 gouging, 413
 grind repair of fatigue cracks, 349
 grinder tool, 343
 grinding, 345, 346, 359
 depth, 342
 flush, 343
 radius, 341
 weld root, 413
 grip length, 379
 grit blasting of surfaces, 353
 grit flapper disk, 343
 grit grinding, 343
 gross error, 15, 16, 18, 363, 465, 467
 ground connection, 342, 345
 ground weld toe, 104
 grout matrix shear failure, 443
 grout reinforced joint, 252
 grouted conical connection, 445
 grouted connection, 435
 growth of voids, 410
 guidance on Weibull shape parameter, 321
 guidelines for fatigue design of FPSOs, 407
- guidelines for fatigue design of semi-submersibles, 407
 gusset connection, 300
 gusset plates, 272
- hammer blow, 421
 hammer peening, 8, 267, 339, 345, 346, 347, 351, 359
 hammerhead, 345
 handheld probe, 335
 hardened washers, 387
 hardness, 384, 387
 measurement, 33, 34
 of bolt, 386
 of nut, 382, 386
 values, 82
 harsh environments, 6
 HAZ, 97, 138. *See also* heat affected zone
 HCF. *See* high cycle fatigue
 head bolts, 379
 Health and Safety Executive, 5, 424
 heat affected zone, 80, 97
 heat treatment, 388, 396
 heating mats, 431
 heavy stiffened tubular joints, 252, 253, 341
 heavy-duty bolts, 396
 height of shear key, 442
 helideck structures, 388
 hemispherical tip, 346
 HFMI, 8. *See* high frequency mechanical impact
 high-capacity bolt, 386
 high cycle fatigue, 20, 106, 279
 high cycle range, 346
 high-frequency mechanical impact, 8, 347
 high natural period, 404
 high-quality bolts, 396
 high-speed trains, 114
 high-strength grout, 449
 high-strength steel, 7, 127, 237
 high-temperature exposure, 383
 HISC. *See* hydrogen induced stress cracking
 hole-drilling method, 28, 36
 Hollande profile, 278
 homogenous part, 205
 hopper corner, 44, 48, 49, 286, 288, 292, 294
 hot galvanizing, 388
 hot spot, 254
 hot spot stress, 6, 38, 40, 44, 55, 91, 109, 110, 117, 174, 179, 253, 254, 259, 263, 265, 268, 270, 272, 274, 279, 280, 281, 285, 291, 294, 296, 297, 299, 300, 301, 302, 303, 305, 340, 341, 344, 358, 371, 402, 404, 424, 427, 432, 469, 477
 hot spot stress method, 109, 110, 282
 hot spot stress S-N curve, 49, 50, 58, 109, 125, 127, 279, 290, 291, 297
 hot-dip galvanizing, 382, 390
 HP, 54, 278. *See also* Hollande profile
 HSE. *See* Health and Safety Executive
 human life, 363
 human mistakes, 16
 human understanding, 16

- hydraulic actuator, 31, 460
 hydraulic axial tensioner device, 397
 hydrodynamic analysis, 407
 hydrodynamic behavior, 405
 hydrodynamic coefficients, 405
 hydrogen, 130
 cracking, 128, 329, 332, 384
 damage, 383
 embrittlement, 390
 induced stress cracking, 383
 resistant material, 384
 sources, 383
 hydrophone support, 6, 9, 203, 274, 409, 416
 hysteresis loops, 96
- IACS, 185. *See also* International Association of Classification Societies
 IIW, 49, 83, 114, 126, 306, 339, 350. *See also* International Institute of Welding
 image on film, 336
 impact strength, 386
 imperfections, 19, 80, 238, 328, 330, 433
 impressed current, 383
 improvement, 339, 363
 improvement by grinding, 351
 improvement factor, 267, 339, 345, 350
 impurity elements, 386
 in way of, 181, 183
 inclined piles, 437
 inclusions, 20, 336, 410
 Incoloy, 131
 incomplete gamma function, 312
 incomplete penetration, 330
 Inconel, 131
 increment in crack growth, 412
 independent analysis, 16
 independent testing, 335
 independent variables, 371
 inelastic strain, 3
 inflection point, 209, 239
 influence function, 259, 265
 initial crack
 depth, 425
 length, 425
 size, 412
 initial defect depth, 148, 492
 initiation of crack, 19
 inner bottom of bulk carriers, 107
 in-plane bending, 254, 264, 267, 268, 404
 in-plane loading, 380
 insert gusset plates, 299
 insert tubular, 202
 in-service inspection, 14, 116, 267, 268, 324, 337, 359, 364, 366, 367, 407, 427, 434, 467, 468
 in-service life, 14, 33, 43, 319, 331, 343, 348, 350, 368, 390, 397, 401, 421, 429, 489
 inspection
 intervals, 429
 planning, 473
 updating, 473
- installation of jacket structures, 442
 installed condition, 400
 instrumented test data, 185
 integrated complete pile model, 402
 interaction equation, 74, 89
 intercept of log N axis, 124
 intercrystalline fracture. *See* separation along grain boundaries
 internal
 crack, 410
 defect, 339, 413
 imperfections, 332
 voids, 20
 internal pressure, 237, 245
 internal ring stiffeners, 252, 270, 305
 International Association of Classification Societies. *See also* IACS
 International Institute of Welding, 126, 280. *See also* IIW
 intersection line, 90, 93, 194, 254, 285, 286, 297
 intrusions, 19, 20
 inverse negative slope, 27
 iron particles, 333
 iron-zinc alloys, 390
 irregular slag, 139
 ISO – International Standard Organization, 5
 isotropic hardening, 119
- jacket, 13, 205–227, 400, 435, 483, 485
 jack-up, 13, 128, 400, 440
 Japanese Ship Classification Society, 121
 J-integral, 427
 joint classification, 109, 256
 joint flexibility, 263
- K-joint, 252, 253, 257, 263, 270, 404
- lack of fusion, 138, 139, 141, 328, 330, 332
 lack of fusion between welding passes, 332
 lack of parallelism, 387
 lack of penetration, 138, 139, 210, 301, 328, 332, 413, 415, 420
 lamellar tearing, 140
 land-based structures, 392
 large diameter connections, 440
 large-scale test specimen, 75, 137
 large-scale tubular joints, 270
 lateral pressure, 276, 279, 288
 LCF. *See* low cycle fatigue
 leak-before-break, 399, 466
 leg length, 68, 75, 151, 283, 294, 297, 342, 344
 legs with insert piles, 272
 length effect, 374
 length of bolt, 385
 length of grouted connection, 444
 life extension, 83
 lighting, 333
 limit state, 14
 limit state function, 355, 376, 471
 linear cumulative damage, 114

- linear elastic finite element analysis, 101
- linear elastic stress, 101
- linear elastic theory, 3, 428
- linear extrapolation, 31, 77, 285, 304, 305
- linear stress distribution, 289
- linear variable transducers, 460
- linear wave theory, 405
- linearization of drag term, 402
- linearized stiffness matrix, 402
- load
 - cells, 30
 - coefficient, 13
 - control, 46
 - effect, 355, 365
 - on shear keys, 462
 - reversals, 99, 100, 380, 463
 - shedding during crack growth, 288
 - spectra, 115
- load-carrying
 - braces, 482
 - capacity, 365
 - welds, 145
- loaded condition, 55
- local approaches, 6
- local stress concentration factor, 101, 340
- local yielding, 38, 44, 117, 158, 347, 385
- locking devices, 397, 398
- log normal, 357, 358
- long-term durability, 391
- longitudinal, 288, 487
- longitudinal bulkhead, 107
- longitudinal stiffener, 275. *See also* longitudinal
- longitudinal welds, 237
- long-term loading, 2, 21, 137, 324, 367, 397, 433, 464, 467, 468, 472, 477, 480
- long-term pretension, 385
- long-term stress range distribution, 4, 84, 114, 138, 141, 310, 322, 323, 325, 339, 349, 377, 404, 416, 474, 479
- loose stud, 489
- loss of pretension force, 397
- low cycle fatigue, 2, 20, 95, 96, 106, 138, 279, 339
- low cycle fatigue data, 99
- low cycle range, 346
- low temperatures, 386
- lower-bound curve, 49
- lower stool connections, 107
- lower-bound characteristic S-N curve, 114
- lubricants, 397
- Lüder plateau, 430
- lug plate, 53, 57, 275

- machined components, 398
- machined surface, 142
- machined tolerances, 388
- macrograph section, 34
- macroscopic defect, 19
- macro-section, 34
- magnesium, 334
- magnetic flux leakage around flaw, 333

- magnetic method, 28
- magnetic particle inspection, 329, 332, 389, 481
 - under water, 481
- magnetic properties, 333
- magnetic yokes, 333
- magnetization, 28
- magnifying glass, 56, 333
- main frame structure, 401
- maintenance, 360
- manholes, 274
- manual welding, 33, 80, 199
- marine environment, 13, 386, 390
- marine structures, 13, 114, 359, 392
- material, 327
 - certificate, 118, 121
 - coefficient, 14, 392
 - ductility, 408
 - fracture toughness, 412, 415
 - grade, 396
 - parameters, 412
 - testing, 34
 - toughness, 408, 430
 - ultimate strength, 430
 - yield strength, 430
- maximum acceptable failure probability, 472
- maximum allowable crack size, 415
- maximum allowable stress range, 319, 488
- maximum nominal contact pressure, 449
- maximum recommended pretension, 385
- maximum stress, 25, 27, 29, 115, 136, 158, 229, 240, 415
- maximum stress intensity factor, 412
- maximum stress range, 310
- maximum surface stress, 308
- maximum temperature, 390
- mean crack growth parameter, 416
- mean fatigue test data, 186
- mean minus three standard deviations, 370, 373
- mean minus two standard deviations, 48, 59, 87, 153, 160, 370, 373, 414
- mean plus two standard deviations, 414, 423
- mean S-N data, 186
- mean stress, 116
 - effect factor, 7
 - level, 7, 43, 55, 116, 324
 - reduction factor, 118, 120
- mean tension, 133
- mean thickness, 223
- mean values of parameters, 422
- mean wave steepness curve, 403
- mean zero up-crossing period, 21, 203, 317
- measured crack size, 474
- measurement, 350
 - action effects, 472, 483
 - environment, 483
 - stress ranges, 468
 - surface roughness, 350
- mechanical properties, 379, 387, 396
- mechanical shear keys, 436
- membrane loading, 174

- membrane stress, 109, 217, 279, 340
 metallic coating, 389
 metallizing, 390
 metallographic section, 80
 method of fabrication, 123
 method of inspection, 123
 microcracks, 19, 139, 333
 microplastic properties, 20
 microscopy, 83
 microstructure, 138, 390
 mild steel, 97, 104
 mill scale, 390
 minima distributions, 373
 minimum distance between shear keys, 443
 minimum specified yield strength, 386. *See also* SMYS
 minimum stress, 158
 misalignment, 63, 64, 174, 176, 185, 234, 330. *See also* eccentricity
 modes I-III, 411
 module support frames, 273
 moment capacity, 447
 moment of inertia, 61, 228, 229, 239, 278, 485
 moment resistance
 contact pressure, 447
 horizontal friction force, 447
 shear keys, 450
 vertical friction force, 448
 monitoring, 362, 471
 monopiles, 120, 149, 441, 444
 monotonic loading, 96
 monotonic stress-strain curves, 96
 mooring chain, 11, 488
 Morison equation, 321, 404
 MPI, 333, 334, 344, 348, 389, 483. *See also* magnetic particle inspection
 mud line, 402
 multi-leg jacket structure, 365
 multiplanar, 253
 multiplanar stiffened tubular KK joints, 257

 narrow banded response, 406
 natural period, 402
 NDT, 23, 126, 134, 140, 141, 162, 210, 268, 300, 328, 329, 331, 332, 333, 342, 344, 346, 348, 471, 476, 481, 483. *See also* non-destructive testing
 negative inverse slope, 124
 Neuber's rule, 101, 102, 104, 117
 neutron diffraction method, 28
 Newman-Raju equations, 427
 nickel alloy, 383, 384
 noble metal, 390
 noise, 347
 nominal bolt diameter, 388
 nominal shear stress, 198
 nominal stress, 49, 109, 235, 288, 344, 415
 approach, 109, 308
 fillet weld, 111, 176
 nominal stress S-N curves, 5, 6, 25, 49, 123, 125, 217, 220, 281, 288, 299, 418

 non-conductive gaskets, 390
 non-destructive testing, 23, 126, 210, 268, 300, 327, 362, 467
 non-fluorescent light, 481
 nonlinear buckling analysis, 444
 nonlinear elastic strain, 101
 nonlinear finite element analysis, 95, 102, 227
 nonlinear stress, 280
 non-magnetic materials, 332
 non-magnetisable materials, 334
 non-proportional, 72, 84
 normal control, 238
 normal distribution, 79, 168, 357, 358, 377
 normalized standard deviation, 357, 377
 North Atlantic, 12, 56
 North Sea, 12, 13, 343, 346, 364, 379, 401, 404, 428, 435
 Norwegian Petroleum Directorate, 184, 364
 notch acuity, 106
 notch effect, 267
 notch sensitivity, 3, 106
 notch stress, 101, 109, 117, 131, 211, 233, 279, 280, 281, 292, 306, 424
 approach, 308
 concentration, 424
 intensity factor, 306
 method, 306
 notch stress S-N curve, 131, 307
 number of cycles, 4, 43, 72, 114, 123, 157, 168, 173, 203, 273, 311, 348, 369, 414, 416, 485, 492
 number of tests, 30
 nut, 379, 381, 386, 387, 389
 nylon, 390

 offshore industry, 4, 374
 opening mode, 411
 operational loads, 322
 operator, 347
 optimal inspection plan, 466
 organic coatings, 383
 outer diameter of pile, 442
 out-of-plane bending, 254, 264, 268, 404
 out-of-plane moments, 482
 out-of-roundness, 210, 238, 239, 240, 370, 371, 375
 outside ring stiffener, 291
 ovality, 231, 238, 369
 ovalization of cylinder, 446
 overlapping joints, 252
 overlapping weld, 330
 overload in compression, 345
 overmatch material, 408
 oversized conical mandrel, 349
 oxidation, 20, 391

 painting/coating of contact surfaces, 390
 Palmgren-Miner
 damage, 21
 rule, 4, 88, 114, 128, 314, 357, 376, 377, 404, 474, 477

- parallel shear stress, 64, 70, 72, 112, 203
 parametric equations, 254, 255, 263, 264, 268, 271
 Paris crack growth equation, 149, 412, 424
 partial penetration weld, 413, 418
 peak stress range, 306
 peening tip, 345
 penetrant testing, 332, 334
 phase angle, 404
 phased array, 483
 phosphatizing, 383
 photo-elasticity, 3
 photographic record, 335
 photography, 333
 physically correct values, 471
 pickling process, 383, 390
 pile clusters, 437
 pile driving, 32, 157, 322, 368, 401, 421
 pile driving history, 421
 pile grippers, 442
 pile-to-sleeve, 401, 436, 437
 pin, 398, 485
 pin groove, 399
 pin hole, 76, 79
 pipe-laying barge, 231
 pipeline, 13, 116, 125, 214, 231, 234, 237, 335, 428
 plain tubular members, 436
 planar
 defects, 138, 139, 141, 333, 335, 336
 imperfections, 332
 internal defects, 334
 plane strain, 101, 428
 plane stress, 101, 428
 planned lack of penetration, 139
 planning in-service inspection, 368
 planning of testing, 26
 plastic
 dissipation, 20
 expansion, 238
 gasket, 390
 plastic strain, 2, 20, 96
 plastic strain range, 99
 plasticity, 5, 107
 plasticity correction factor, 105
 plate lap fillet weld, 280
 plate thickness, 277
 plated structure, 125, 174, 177
 PoD. *See* probability of detection
 Poisson's ratio, 120, 133, 237, 255, 388
 polar coordinates, 410
 pollution, 367
 polynomial, 206, 284
 pore, 139, 332
 porosity, 330
 position of weld, 177
 post weld heat treatment, 38, 324, 347, 422
 post-weld improvement, 339
 precipitation hardening, 384
 pre-cracked, 428
 pre-load, 40
 pressure distribution, 447
 pressure range, 486
 pre-strained, 132, 134
 pretension, 379
 bolt force, 380
 level, 397
 load, 397
 pretensioned riser, 229
 principal stress, 20, 30, 36, 66, 84, 86, 109, 192, 254,
 286, 291, 302
 principal tensile stress, 438
 probabilistic analysis, 468, 469
 probabilistic crack growth analysis, 475
 probability density function, 310
 probability level, 487
 probability of being exceeded, 317, 357, 368
 probability of detection, 330, 332, 333, 337, 468,
 480, 482
 probability of failure, 15, 160, 163, 355, 377, 378,
 469, 473, 474
 accumulated, 356, 358, 359, 362, 363, 374, 375
 annual, 356, 360, 362, 366, 375
 calculated, 356, 357, 360, 363, 375, 471
 nominal, 360
 simplified methods, 365
 system collapse, 365
 system reliability, 366
 time-limited, 77, 356
 probability of survival, 4, 123, 157, 158, 160, 161,
 281, 370
 probe with measuring tip, 352
 production welds, 199
 progressive failure path, 363
 proof stress, 386
 propagation of crack, 19
 property class, 381, 384, 386
 proportional loading, 73, 84, 86
 prying action, 385
 pseudo-elastic stress, 102, 105, 107
 PT, 334. *See also* penetrant testing
 pushover analysis, 365
 PWHT, 38, 39, 43, 44, 45, 120, 431. *See also* post
 weld heat treatment
 QRA. *See* quantified risk analysis
 quadratic displacement function, 289
 quality assurance, 347, 396
 quantified risk analysis, 15
 quarter ellipse, 190
 radial cracks in meridian direction, 460
 radial displacement, 219, 449, 454
 radial stiffness, 206, 460
 radial stiffness parameter, 442
 radiation hazards, 336
 radioactive isotope, 336
 radiographic testing, 330, 332, 336, 482
 radius
 impacting tool, 347
 probe tip, 352
 sleeve, 442

- radius to thickness ratio of chord, 257
 rainflow counting, 4, 287
 Ramberg-Osgood, 97
 random variables, 377
 range of stress intensity factor, 419
 range-pair-range, 4
 raw fatigue test data, 68
 Rayleigh distribution, 314, 315, 475
 readout points, 33, 93, 284, 285, 297
 receiver, 481
 rectangular hollow sections, 272, 273, 299. *See also*
 RHS
 redistribution of stress, 57, 137, 348, 469
 reduced coordinate, 207, 209
 reduced integration, 283
 reduced shank, 385
 reduction factor, 268, 353
 reduction of area, 386
 redundancy, 10, 362, 364
 reeling of pipeline, 112, 231
 reference standards, 396
 reference thickness, 49, 69, 125, 143, 147, 148, 150,
 298, 341
 regression analysis, 36, 38, 126, 159
 reinforcement, 191, 275
 relative displacement, 440, 450
 relative sliding between steel and grout, 446
 reliability
 analysis, 376
 index, 163, 167, 377
 inspection method, 348
 methods, 357
 updating, 473
 remote operated vehicles, 8
 removal of coating, 336
 renewal of hot spot area, 348
 repair, 349
 repair welding, 140
 reserve strength ratio, 365
 residual, 362
 residual stresses, 27, 36, 45, 116, 126, 137, 157, 324,
 347, 388, 423, 431
 reversed loading, 441
 RHS, 273, 299, 301. *See also* rectangular hollow
 sections
 ring core method, 28
 ring-stiffened tubular joints, 366
 ring stiffener, 219, 221, 225, 241, 270
 double-sided, 194
 one-sided, 194
 shell, 218
 ripples at crack front, 20
 riser, 13, 125, 227
 risk analysis, 363
 risk matrix, 363
 risk of failure, 15, 397
 robustness, 364, 386, 465
 rolled threads, 388
 rolling direction, 97, 140
 rolling process, 388
 root area, 210, 231, 329, 387, 388, 413
 root mean square roughness, R_q , 352
 rosette, 28, 30, 36, 65
 rotary burr, 77, 342, 343, 345
 roughness, 343
 roughness parameters, 352
 rounded rectangular holes, 190
 ROV. *See* remote operated vehicle
 R-ratio ($R = \sigma_{\min} / \sigma_{\max}$), 29, 77
 RSR. *See* reserve strength ratio
 RT. *See* radiographic testing
 rubber gasket, 390
 rules for fixed offshore structures, 374
 run-out, 4, 36, 38, 39, 133, 158, 167
 sacrificial anodes, 383
 saddle, 264, 270, 304
 safe life, 5
 safety
 barrier, 14
 factor, 157, 414, 435
 format, 376
 index, 366
 sailing routes, 11
 scale parameter, 4, 310, 325, 344, 377, 475, 492
 scallop, 57, 190. *See also* cope hole
 scantlings, 7
 scatter-band, 69
 SCF, 208, 210, 221, 257, 275, 278. *See also* stress
 concentration factor
 sealing, 391
 sealing compound, 398
 seam welds, 327, 369
 seamless pipes, 151, 231
 seawater, 31, 386
 environment, 128
 with cathodic protection, 433
 secondary stresses, 430
 sectioning method, 28
 sector, 404
 semi-elliptic, 425, 494
 crack, 46, 489
 shape, 349
 surface defect, 141
 semi-major axis, 188
 semi-minor axis, 189
 semi-submersible platform, 13, 301
 SENB. *See* single edge notch bending
 sensitivity factors, 378
 SENT. *See* single edge notched tensile
 separation along grain boundaries, 410
 series system, 373
 service temperature, 415
 serviceability limit state, 13
 settlement, 441
 shakedown, 2, 32, 38, 116, 347, 423
 shank, 379, 381, 390
 shape parameter, 4, 21, 78, 310, 316, 317, 320, 325,
 344, 377, 378, 433, 475, 487, 491, 492
 shear area, 71

- shear force, 438
 shear keys, 435, 445
 shear plates, 438
 shell stiffness of pile, 454
 shell stiffness of transition piece, 454
 shell theory, 211, 222
 shift in neutral axis, 183, 232, 244
 ship
 chemical tankers, 21
 oil tankers, 21
 panamax bulk carriers, 21
 shuttle tanker, 488
 shuttle tankers, 21
 tanker structures, 178
 ship side, 346
 ship-shaped structures, 23, 39, 60
 side longitudinal, 7, 13, 52, 122, 346, 486. *See also* longitudinal
 similarity between S-N fatigue and fracture mechanics, 413
 simple tubular joints, 137, 252, 255, 288, 341, 469
 simplified analysis, 294, 415
 single edge notched bending, 428
 single edge notched tensile, 428, 482
 single element gauges, 44
 single fastening system, 392
 single-filament strain gauge, 31, 33
 single-side girth weld, 209, 420. *See also* girth weld and circumferential weld
 single-side welds, 232, 266, 268, 322
 single-skin grouted joints, 271
 singularity, 293
 sizing
 defects, 330, 335
 internal defects, 414
 of crack, 473
 surface-breaking flaws, 337
 skew bending, 276, 488
 skew loading, 278
 slag inclusions, 328, 330, 332
 slamming loads, 401
 sleeve lengths, 437
 slender jackets, 442
 slenderness of pile, 444
 sliding between grout and steel, 440
 sliding support, 485
 slip band, 3
 slip coefficient, 392
 slip planes, 19
 slip-resistant bolted connections, 380, 381, 388
 slip-resistant joint, 391
 slope angles, 223
 sloped interface, 387
 slots, 338
 SLS. *See* serviceability limit state
 small-scale test specimens, 27, 126, 136, 158, 371
 small-scale tests, 29, 33, 126, 442
 SMYS. *See also* minimum specified yield strength
 S-N classification, 328
 S-N curves
 air environment, 125
 aluminum structures, 134
 base steel material, 349
 chains, 135
 concrete structures, 136, 444
 copper, 134
 ground weld toes, 350
 high-strength steel, 127
 pile driving, 157
 seawater with cathodic protection, 128
 seawater without corrosive protection, 129, 155
 sour environment, 131
 stainless steel, 131
 titanium risers, 135
 umbilical tubes, 132
 wire ropes, 136
 S-N test data, 410
 soap solution, 56
 soft brackets, 84
 soil, 401
 solidification, 140
 sour environment, 31, 131
 spar platform, 13
 specified minimum tensile strength, 386
 specified service life, 5
 spectrum loading, 350
 spherical shell, 248
 splash zone, 156, 367, 390, 401
 split corrosion, 391
 spraying hot aluminum, 390
 spraying hot zinc, 390
 springback stress, 119
 spring stiffness, 394
 bolt, 393
 bolt and joined plates, 396
 joined plates, 394
 shear key per unit length, 451
 springback force, 238
 spurious indications, 337
 SSC. *See* sulfide-stress cracking
 St. Venant torsion, 283
 stainless steel, 131, 334, 383, 384, 389, 390, 486
 stainless steel bolts, 390
 standard deviation, 36, 38, 44, 45, 49, 59, 69, 74, 87, 151, 186, 357, 433
 “known”, 161
 “unknown”, 161
 stress response spectrum, 314, 475
 start-stop position, 200, 328
 static capacity, 428
 static strength, 382
 static system, 174
 stationary Gaussian process, 475
 steel grade, 381
 Steel in Marine Structures, 305
 steelmaking, 383
 steering groove, 345, 347
 stiffened plates, 177

- stiffened tubular joints, 305
 stiffener height, 277
 stiffener web thickness, 277
 stiffness of shell, 226
 stiffness ratio between bolt and contact surfaces, 385
 stochastic fatigue analysis, 314, 401, 404. *See also* frequency domain analysis
 stochastic variables, 355
 Stokes' 5th order theory, 403
 stop hole, 348
 storage tank, 249
 strain amplitude, 96
 strain gauge, 30, 35
 strain hardening, 20, 430
 strain-based approach, 20
 strain-life, 99
 strengthening, 363
 stress amplitude, 104, 347
 stress concentration factor, xix, 46, 125, 174, 231, 253, 420, 489
 butt welds, 174
 elliptical hole, 188
 fillet welds, 176
 hole, 188
 holes at crack ends, 348
 holes with reinforcement, 193
 rectangular hole, 190
 scallop or cope hole, 190
 tubular and shell structures, 205
 weld toes, 341
 stress evaluation points, 284
 stress gradient, 31, 45, 143, 145, 150, 305
 stress histogram, 114
 stress intensity factor, 348, 410, 424, 489, 490, 494
 stress magnification factor, 424
 stress modification factor, 168
 stress reduction factor, 344
 stress relief, 43, 45
 stress relief grooves, 382, 398
 striation, 20
 stringer, 487
 heels, 294
 transverse bulkheads, 107
 strip with strain gauges, 31
 stripping of threads, 385
 strong backs, 36
 structural integrity, 21, 139, 366, 472, 482, 483
 structural stress, 6, 279, 280
 analysis, 281
 method, 110
 stub, 209, 266
 stud bolt, 379, 382
 Student's t-distribution, 169, 170
 studless chain, 490
 submerged in water, 441
 subsea fasteners, 384
 subsea wellheads, 13
 subsiding platforms, 401
 substantial consequences, 345
 sulfide stress-cracking, 384
 super duplex, 131
 superposition, 264, 432
 superposition principle, 247, 302, 490
 support structures for wind turbines, 400
 surface
 defects, 25, 333
 finish, 381
 imperfections, 332
 irregularity, 441, 447
 roughness, 127, 307, 350, 351, 353, 389, 392, 441, 462
 surface stress
 methods, 280
 range, 142
 surface-breaking defects, 333
 suspension fluid, 333
 swell, 321, 322
 system effect, 373
 system reliability, 80, 363
 tack weld, 329
 tapering, 382
 target notch stress, 308, 309
 target safety level, 17, 360, 362, 366, 369, 376, 481
 T-bar profile, 178
 Teflon washer, 390
 temperature shrinkage, 9
 temporary repairs, 349
 temporary supports, 444
 ten-point height, R_z , 353
 tensile capacity of grout, 446
 tensile stresses, 452
 tension-type connections, 380, 392
 terminology, xviii, 379
 test frequency, 31
 test laboratory, 2, 44
 test matrix, 61
 testing, 379
 testing machine, 27, 31, 133
 tether connections, 95, 127, 190
 tethers of tension-leg platform, 469
 tetrahedral elements, 293
 thermal stress relieving, 347
 thickness
 chord, 272
 cylinder, 250
 effect, 69, 125, 131, 132, 340, 342
 end sphere, 250
 exponent, 49, 69, 125, 126, 131, 132, 156
 grout, 442
 insert pile, 272
 measurements, 335
 pile, 442
 ratio brace to chord, 257
 sleeve, 442
 transition, 174, 179, 182, 211, 215, 223, 225, 244, 246, 401, 420
 threaded fasteners, 388

- threads, 379, 398
 coarse, 389
 cut, 388
 fine, 389
 geometry, 390
 inch series, 388
 metric, 388
 pitch, 388
 rolled, 388
 root, 382
 run-out, 381, 382, 389
 stripping, 387
 tapering, 389
- three-dimensional
 defects, 139
 elements, 285
 finite element analyses, 51
- threshold value, 115, 130, 155, 412, 425, 433
- throat thickness, 62, 69, 75, 76, 198, 203, 291, 418
 actual, 63
 nominal, 63
- through-thickness
 center crack, 416
 crack, 410
 defects, 482
 stress method, 280
- TIG. *See* tungsten inert gas
- TIG dressing, 345, 346
- tight tolerances, 382
- time interval until next inspection, 360
- time-of-flight diffraction, 335, 483
- time to first inspection, 359
- time-dependent loading, 355
- time-domain simulation of load response, 464
- titanium, 334, 383
- T-joint, 128, 257, 259
- T-joint plate connection, 222, 290
- tolerance class for nut, 390
- tolerance limits, 160
- tolerance-bound theory, 163
- tolerances, 385, 389, 396
- topside stool, 321
- torque method, 397
- torque-tension relationship, 387
- torsional load, 61, 66
- transcrystalline cracking, 20
- transcrystalline fracture. *See* cleavage of grains
- transition in slope, 26, 178, 224
- transmission and detection of ultrasonic waves, 334
- transmitter, 481
- transportation, 368, 400
- transverse frame, 52, 59, 177, 178, 487
- triangular thread geometry, 382
- triaxiality in thread root, 388
- true fracture
 ductility, 96
 strength, 96, 100
- true strain, 96
- true stress, 95
- tubular joints, 104, 123, 125, 126, 135, 137, 143, 145, 147, 252, 304, 327, 331, 349, 368
- tubular KK joints for jack-up, 257
- tubular member, 206
- tubular penetrating plates, 84
- tubular segment, 227
- tungsten inert gas, 104, 345
- two slope S-N curve, 26
- two-dimensional
 elastic theory, 219
 strain effect, 254
 stress solution, 410
- U.L.S. *See* ultimate limit state
- ultimate limit state, 13, 21, 95, 252, 327, 437, 442, 456
- ultimate strength, 386
- ultrasonic method, 28
- ultrasonic peening, 75, 347
 impact treatment, 347
 needle peening, 347
 treatment, 347
- ultrasonic testing, 330, 332, 334, 414, 482. *See* UT
- ultraviolet light, 481
- umbilical tubes, 132
- UN. *See* Unified National Threads
- uncertainty, 376, 377, 414
 crack growth parameters, 471
 fatigue analysis, 401
 importance, 165
 inspection method, 471
 load effect, 401
- under water, 333, 337
- undercut, 19, 139, 140, 143, 149, 150, 328, 330, 333, 336, 341, 342
- undermatch weld material, 409
- underwater hammers, 437
- uniaxial strain measurements, 254
- Unified National Threads, 389
- Unified National Threads with controlled root, 389
- uniform safety level, 374
- uniform stress distribution, 382
- uniplanar joints, 253
- UNP. *See* ultrasonic needle peening
- UNR threads. *See* Unified National Threads with controlled root
- unstable fracture, 154, 333, 408, 415, 431, 488, 493
- un-symmetrical section, 276
- UP, 75. *See* ultrasonic peening
- up-crossing period. *See* zero up-crossing period
- updated failure probability, 472
- updated reliability, 348
- UPT. *See* ultrasonic peening treatment
- user-friendly, 347
- UT, 334. *See* ultrasonic testing
- utilization factor, 319
- variable amplitude loading, 3, 4, 114, 127, 130, 158, 346
- variable amplitude testing, 26

- variable buoyancy, 402
- variable long-term loading, 355
- variance, 377
- varying stress direction, 94
- VI, 333. *See* visual inspection
- vibration, 347
- vibration stress relieving, 347
- video recording, 333
- visual inspection, 332, 333, 467, 481
- voltage, 336
- volumetric
 - defects, 138, 335
 - flaws, 336
 - imperfections, 330, 332
- von Mises, 107, 119
- vortex-induced vibrations, 13, 400, 401

- wall thickness ratio, 254
- washer, 379, 387, 389
- washer material, 381
- water tightness, 15
- waterline area, 404
- wave action, 421
- wave height exceedance diagram, 403
- wear of burrs, 343
- wear of the grout, 442
- web of longitudinal, 61
- web-stiffened cruciform joints, 294
- Weibull distribution, 21, 310, 315, 317, 321, 325, 344, 463, 475, 491
- weld
 - cap, 231
 - convexity, 330
 - ends, 123
 - geometry, 109
 - groove, 329
 - inter-run positions, 343
 - made from both sides, 343
 - profiling, 339, 340, 341, 342
 - reinforcement, 148
 - repair, 150, 348
 - shape, 330, 331
- weld beads, 139, 157
- weld improvement, 74, 83, 215, 267, 268, 307, 331, 339, 346, 427, 478
- weld length effect, 150
- weld root, 10, 23, 57, 63, 75, 82, 116, 132, 136, 139, 157, 191, 192, 196, 201, 202, 214, 231, 232, 234, 267, 272, 291, 299, 307, 308, 309, 339, 343, 348, 415, 418, 420
- weld seam, 237
- weld toe, 19, 22, 31, 39, 55, 75, 116, 123, 136, 231, 339, 416
 - grinding, 342, 343, 478
 - profile, 148
 - radius, 341
- welded penetration, 191, 301
- welder qualifications, 158
- weld-improved areas, 350
- weld improvement, 84
- welding, 328
 - access, 328
 - consumables, 329
 - mechanical qualification testing, 328
 - method, 139, 158, 162, 331
 - position, 38
 - procedure, 33, 83
 - procedure qualification testing, 409
 - procedure specification, 328, 408
 - qualified procedure, 328
 - quality management system, 329
- well-known case, 360
- well-trained and qualified personnel, 335
- wind turbine structure, 13, 22, 224, 442, 444, 445
- Wöhler, 2, 3, 5
- workmanship, 168, 210, 342, 343, 345, 346, 350, 396
- worldwide trades, 11
- wormhole, 139
- WPS. *See* welding procedure specification

- X-joint, 257, 404
- X-ray diffraction method, 28
- X-ray tube, 336

- yield strain, 20
- yield strength, 43, 339, 347, 429, 489
- yield strength of weld material, 414
- Y-joint, 257, 404
- yoke plates, 438
- Young's modulus, 20, 135, 175, 254, 255, 430, 443
- Young's modulus of grout, 443

- Z quality steel, 140
- zero up-crossing period, 485
- zinc, 389
 - alloys, 390
 - bath, 390
 - coating, 390