

Index

- α_D definition, 28
- β_D definition, 28
- ϵ definition, 30
- beam constitutive law, 13
- beam governing equations, 15
- beam kinematics, 12
- bilayer
 - basic solution, 49
 - equal thickness, 55
 - four-point bending, 57
- bilayers
 - effect properties for multilayer, 80
- blister test, 43
- buckling
 - bilayer, 138
 - circular, 146
 - energy release rate, 140, 144
 - mode mix, 145
 - stress intensity factors, 144
 - telephone cord, 152
- bulge test, 43
- channeling cracks, 89
 - effect of delamination, 100
 - effect of substrate modulus, 93
 - effect of substrate plasticity, 95
 - interacting, 96
 - on semi-infinite substrate, 92
 - software, 247
- calcium-magnesium-alumino-silicate, CMAS, 245
- convective heat transfer, 19
- convergent cracks, 133
- corner cracks, 132
- crack face contact, 37
- crack tip fields
 - bimaterial, 30, 35, 269
 - center crack on an interface, 36
 - isotropic, 22
- cut test, 131
- delamination
 - phase factor, 51
 - software, 239
- temperature gradients, 164
- thin film, 54
- thin strip, 157
- Dundurs' parameters, 28
- environmental barrier coatings, EBCs, 202, 251
- edge cracks, 127
- energy release rate
 - bilayer with uniform temperature, 60
 - basic definition, 24
 - buckled film, 144
 - center crack on interface, 35
 - channeling, 89
 - corner cracks, 132
 - crack length effect, 128
 - crack spacing, 98
 - deflection at an interface, 122
 - delamination of bilayer, 50
 - four-point bending, 57
 - interface, Irwin's relation, 30
 - kinking from an interface, 113
 - multilayer calculation, 75, 78
 - numerical computation, 232
 - penetrating crack, 121
 - temperature gradient, 163, 167
 - thermal shock, 176
 - thermal transients, 182
 - thin film on thick substrate, 54
 - tunneling crack, 103
- four-point bending, 46, 57
- heat equation, 18
- heat flux, 19
- Hooke's law, 6
- hot spots, 178
- indentation, 46
- interface toughness
 - epoxy glass, 39
 - epoxy plexiglass, 32
 - in TBCs, 45

- interface toughness (*cont.*)
 - measurement overview, 41
 - mixed mode forms, 32
 - mixed mode, $\beta_D \neq 0$, 35
 - mixed mode, $\beta_D = 0$, 31
- kinking
 - criteria, interface, 108
 - criteria, isotropic, 26
 - effect of mismatch, 111
 - interface, 106
 - isotropic material, 24
 - role of flaw size, 114
 - role of residual stress, 114
- large deflections, 11, 143
- mesh considerations, 236, 241, 263
- mode mix
 - basic definition for an interface, 35
 - bilayers, 58
 - delamination with edge/moment loads, 54
 - effect for TBCs, 46
 - general multilayers, 78
 - isotropic material, 25
 - numerical computation, 233
- mudcracks, *see* channeling cracks
- multilayers
 - bilayer approximation, 79
 - delamination ERR, 74, 76
 - examples, 81
 - governing equations, 70
- phase angle, *see* mode mix
- phase factor
 - delamination, 51
 - thin layer, 87
- plate theory, 16
- software
 - chart, 4
 - FEA, 227
 - mode-mix, 227
 - steady-state, 188
 - transients, 208
- stiffness derivative, 232
- stress intensity factors
 - bilayer, 52
 - center crack on interface, 36
 - complex representation, 30
 - numerical computation, 233
- superlayer test, 81
- thermal barrier coatings, TBCs, 45, 84, 244, 245
- temperature gradient
 - bilayer, 164
 - isotropic material, 162
 - multilayers, 171
 - thin film on thick substrate, 168
 - transient, 174
- thermal shock, 174
- thermal transients
 - cold shock, 175
 - critical cooling rates, 185
 - hot spots, 178
 - multilayers, 183
 - single layer, 180
- trilayer, 81, 86
- tunneling cracks, 102