

Index

- ACK, 6
 admission control, 222, 238, 254, 309, 310, 314, 315, 316, 318, 327, 349, 337, 339, 340–342, 344–345, 349–372, 400
 alternating-direction method of multipliers (ADMM), 150–151, 156–157, 163, 165–170, 174–175, 303–305
 amplify-and-forward one-way relay network (AF-OWRN), 84
 analog-to-digital converter (ADC), 202, 204
 antenna array, 24, 25, 71, 117
 antenna selection, 117, 146, 279, 313
 antenna tilting, 25
 application program interface (API), 5, 6, 443, 445, 461
 application specific integrated circuit (ASIC), 5, 35
 average data rate (ADR), 17, 18, 19, 191
 average effective signal-to-noise ratio (AESNR), 84, 97, 98, 101, 102
 AWGN, 37, 42, 87, 92, 95, 259, 318, 416
- baseband unit (BBU), 3–10, 82–84, 86, 87, 92–95, 102–104, 106, 109, 114, 149, 156, 169, 179–182, 184–188, 190–196, 200–205, 216, 228, 229, 231, 251, 282–284, 286, 288–291, 297, 301, 311, 314, 316, 317, 347–349, 365–368, 372, 377, 378, 385, 386, 392, 397–402, 407–412, 416, 418, 419, 432, 451, 457, 462–468, 470
 basis expansion model (BEM), 84, 93, 95, 100, 101
 Bellman equation, 285, 289–291, 293, 294, 416
 bisection method, 149, 173, 386
 blanket transmission scheme (BTS), 117, 118
 block coordinate descent (BCD) method, 303
 block error rate (BLER), 200, 202, 206, 208, 210–221
 broadcast channel, 70, 71, 81, 177, 313
- capital expenditure (CAPEX), 3, 4, 24, 149, 201, 397, 410, 461
 carrier aggregation (CA), 12–22, 26, 147, 222, 281
 channel estimation error, 56, 62, 84
 channel state information (CSI), 27, 56, 76, 79, 82–85, 101, 102, 112–114, 117, 121, 124–127, 132, 136, 155, 175, 203, 205, 216, 243, 245–247, 282, 284, 285, 289, 291–293, 295–297, 299, 302, 304, 310, 311, 413, 416
 channel state information acquisition, 79, 83–85, 102, 112, 114, 155
 channel state information RS (CSI-RS), 27
 code block (CB), 37–39, 268, 270, 276, 288, 291, 292, 457, 459, 460, 470
 code block error rate (CBLER), 37, 39
 cognitive radio network (CRN), 232, 233
 cognitive radio resource management (CRRM), 233, 238, 243, 244, 251
 collaborative schedule (CS), 8, 457–460, 470
 commercial-off-the-shelf (COTS) platform, 5, 6, 461–465, 467–471
 common public radio interface (CPRI), 6–11, 179–185, 188, 197, 201, 222, 228, 375, 451–454, 456, 462, 470
 complex Gaussian random variable, 127, 203, 207
 component carrier (CC), 14–19, 262, 272
 compressed CPRI, 182–184
 compressive sensing, 73, 74
 compress-forward, 54, 61–63, 65, 67, 75, 79, 114
 compress-forward estimate (CFE) approach, 114
 computational diversity, 41, 45, 46
 computational gain, 41, 44–46
 computational outage, 38, 40, 41, 44–48, 50–53
 compute-forward, 61, 62, 70, 71
 cone projection, 167–169, 194
 conjugate gradient method, 167
 content delivery network (CDN), 6
 convex optimization, 69, 77, 92, 149–158, 160, 162, 164, 166, 168–172, 174–176, 178, 212, 213, 215, 223, 294, 303, 309, 312, 319, 321, 334, 345
 core network (CN), 432–434, 440, 445, 448
 cooperative beamforming, 54, 79, 283, 293, 305
 cooperative transmission, 70, 71, 293
 coordinated beamforming, 145, 150, 153–155, 158, 162, 173, 175, 176, 255, 288, 345
 coordinated multi-point (CoMP) algorithm, 4, 55, 118, 221, 233, 237–239, 241, 288, 290, 291, 327, 397, 398, 406–408, 413, 417, 428, 451, 456–459, 470

- covariance matrix, 63, 68, 72, 75–77, 90, 91, 105, 106, 188, 201, 416
- Cramér–Rao bound (CRB), 92, 93, 98, 111–113
- cumulative distribution function (CDF), 20, 22, 23, 29, 43, 44, 50, 51, 455
- curse of dimensionality, 286
- cyclic prefix (CP), 55–57, 60–66, 69–71, 74–76, 78, 79, 228, 453, 458
- data sharing, 54, 70–74, 76, 78–79, 81
- decode-forward, 61–62, 81
- deferred acceptance algorithm, 424
- degrees of freedom (DoFs), 118, 147
- delay sensitivity, 378, 381–382, 384
- device-to-device (D2D) communication, 233–238, 249
- difference-of-convex (DC) programming, 155
- digital signal processing (DSP), 5, 35, 470
- dirty paper coding, 73, 193
- discrete Fourier transform (DFT), 92, 100
- distributed antenna system (DAS), 80–81, 117–118, 146–147, 199, 229, 312–313, 315, 344
- distributed caching, 408, 411–412, 416, 418–419, 421, 423, 425, 427–428
- distributed quantization and compression, 180, 185–186, 188, 196
- distributed source coding, 185–186, 189, 191, 198, 201
- energy efficiency, 118, 127–132, 136–139, 142, 147, 227, 239, 240, 296, 313, 315, 344, 348, 379, 382, 389–392, 410
- enhanced inter-cell interference coordination (eICIC), 13, 31
- ergodic rate, 127, 136, 139
- estimate compress-forward (ECF) approach, 114
- estimation accuracy, 83–85, 101–102, 106, 110, 112–114
- exhaustive search, 67, 132, 218–220, 334, 338
- factorization caching, 166–167
- fast fading, 103, 117, 120, 125
- filtering, 180, 182, 409
- Fluid Net, 229, 231, 252, 375, 393
- Fog-RAN, 149, 152, 179
- forward error correction (FEC), 36–37
- fractional frequency reuse (FFR), 229, 280
- frequency-flat fading, 95
- fronthaul, 4, 6–7, 10–11, 36, 41, 54–56, 58, 60–64, 67–86, 95, 103, 113–115, 149, 154, 179–180
- fronthaul compression, 80–81, 179, 180, 182, 184, 186, 188, 190, 192–194, 196, 198, 280
- full dimension (FD)-MIMO, 25–26, 31
- greedy algorithm, 134, 139
- general purpose platform (GPP), 347
- H-CRAN, 228, 231–233, 239, 240, 243–246, 248–252
- handover management, 398–403, 405, 406
- Hermitian nonnegative definite matrix, 343
- heterogeneous network, 13, 14, 17, 31, 47, 117, 231, 398, 400
- home agent, 440
- home location register (HLR), 441
- homogeneous self-dual embedding (HSD), 157
- human-to-machine (H2M) communication, 227
- hybrid automatic repeat request (HARQ), 19, 180, 232, 239, 241, 243, 458, 465, 466
- hypervisor virtual machine, 464
- implicit differentiation, 331
- independent compression, 62, 68, 69, 76, 77
- in-network processing, 181, 194–196
- in-phase/quadrature-phase (I/Q), 201, 8, 200, 203, 375
- inter-cell interference, 13, 15, 28, 31, 43, 54, 123–125, 129, 139, 189, 201, 229, 345, 413, 416, 456
- interference cancellation, 55, 61–63, 65, 81, 117, 125, 178, 198, 344
- interference-rejection combining (IRC) receiver, 28, 466
- interior-point method, 150
- internet of things (IoT), 175, 227, 240, 247, 392, 393, 411
- joint decoding reception scheme (JDERS), 118, 121, 123–132, 134, 136–142, 144–145
- joint decompression, 185–186, 188, 191, 198, 200, 202, 203, 205, 222
- joint decompression and detection (JDD), 200, 202–203, 205–206, 208
- joint likelihood function, 112
- joint reception (JR), 8, 54, 470
- joint transmission (JT), 4, 8, 11, 35, 54, 78, 398, 406, 412, 457
- Kalman filter, 84–85, 104–105
- Karush–Kuhn–Tucker (KKT) point, 155
- lattice codebook, 62, 71, 196
- line-of-sight (LOS) condition, 18, 19, 28, 120, 124
- Lipschitz condition, 326
- Little’s law, 368
- load balancing, 14, 15, 17, 21, 22, 200, 376, 410, 442–444, 447, 448, 461, 465, 468, 470
- log-normal random variable, 120
- long-term evolution (LTE) network, 3–9, 11–15, 17, 22–24, 26, 27, 30, 31, 37, 44, 46, 50, 179, 181–184, 188, 190, 193, 222, 227, 229, 230–233, 238, 239, 343, 348, 367, 398, 400, 406, 451–453, 456, 457, 462, 463, 465–469
- lossless compression, 180, 183, 198, 201, 222

- Lyapunov drift-minus-utility, 287, 288
 Lyapunov function, 286–288, 299, 303, 308
 Lyapunov optimization, 283, 286–288, 299, 303, 308, 311
- machine-to-machine (M2M) communication, 227, 347
 machine-type communication (MTC), 243
 media access control (MAC), 7
 majorize-minimization (MM) method, 77
 many-to-many matching, 422–424
 Markov chain, 285
 Markov decision process (MDP), 283, 311, 391–392
 massive MIMO, 114, 116–117, 132, 146–147, 315–316
 matching game, 418, 422–424
 max–min SINR, 326, 334, 339, 342
 maximum *a posteriori* probability (MAP), 84, 93
 maximum likelihood (ML), 83, 112
 maximum ratio transmission (MRT), 173
 max-rate scheduling (MRS), 52
 mean field game, 418
 minimum-mean-squared-error (MMSE)
 beamforming, 65
 mobile cloud networking (MCN), 10
 mobile switching center (MSC), 441
 modulation and coding scheme (MCS), 241, 367
 multi-cell processing (MCP), 55, 201, 222
 multiple-input multiple-output (MIMO), 9, 55, 84, 117, 201, 315
 multivariate compression, 76–77, 191–193, 315
- NACK, 6
 nearest selection (NS), 134, 140
 network allocation vector (NAV), 236
 network-aware fronthaul processing, 180–181, 184, 191, 194
 next generation fronthaul interface (NGFI), 7–11
 non-line-of-sight (NLOS) condition, 18, 19, 28
 noise shaping, 183
 noisy network coding, 62, 80
 non-training-based channel estimation, 82–84, 112
 non-uniform memory access (NUMA), 464, 465
- open base station architecture initiative (OBSAI), 6
 Open Radio Interface (ORI), 10
 operating expense (OPEX), 3, 4, 24, 149, 201, 396, 397, 408, 410, 461
 operating system (OS), 6, 37, 433, 442, 461, 463, 464, 468
 optical transport network (OTN), 6
 optimal operating point selection (OOPS) algorithm, 385, 386
 optimized non-uniform quantization, 183
 orthogonal frequency division multiplex (OFDM), 60, 84, 94, 115, 116, 122, 130, 183, 238, 244, 406
- packet data convergence protocol (PDCP), 7
 packet transport network (PTN), 9
 pairwise error probability, 200, 202, 221
 pairwise stability, 425
 peak-to-average power ratio (PAPR), 183
 per-block scaling, 183
 physical layer (PHY), 7
 pilot contamination, 117, 122, 124–125, 128, 129, 131–132
 point-to-point fronthaul processing, 180–181, 183
 power amplifier (PA) efficiency, 367
 power-scaling law, 127–128
 primary serving cell (PCell), 15
 probability mass function (PMF), 39
 proof-of-concept (PoC), 451
 proportional fairness (PF), 17, 190–191, 312
- quantization noise, 54, 61–71, 74–79, 183–184, 190, 192, 195, 201–202, 205–206, 210, 216–217, 257, 268, 315
 quasi-Newton method, 112, 113
 queue stability, 286–288, 302, 437
 queue state information (QSI), 282, 295–296, 299, 302–304, 413–414
- radio access link (ACL), 83, 86, 95, 101–104
 radio access point (RAP), 35–37, 40–41, 44–45
 radio access technology (RAT), 5–6, 461–462, 471
 radio aggregation unit (RAU), 9, 117–122, 124–143, 145
 radio cloud center (RCC), 7, 9
 radio frequency (RF), 9, 154, 228, 231–232, 302, 366–369, 371, 397, 409
 Radio over Ethernet (RoE), 10,
 radio resource connection (RRC), 14–15, 31
 real-time (RT) signal processing, 464–465, 469, 470
 reference signal received power (RSRP), 26, 28–29, 456–457
 reference signal received quality (RSRQ), 26, 28–29, 235
 regularization factor, 117
 remote radio systems (RRS), 7, 9
 remote radio unit (RRU), 3–5, 7, 8, 10, 94, 368, 451, 462
 residual pooling gain, 358, 359
 resource block (RB), 17, 18, 44, 184, 229, 233, 234, 237–239, 244, 255–258, 267–269, 283, 284, 306, 307, 309, 310, 367, 456
 reverse compute-forward, 70, 71
 round robin, 140, 360, 381, 383, 384, 389–391
 RRH activation, 301, 302, 304
- scalar quantization, 181
 scheduling with complexity cut-off (SCC), 48, 50–52
 scheduling with water filling (SWF), 48
 secondary serving cell (SCell), 15

- second-order cone programming (SOCP), 149
 segment training, 84–85, 93, 95, 101–103, 114
 selection reception scheme (SRS), 118, 142
 selection transmission scheme (STS), 117
 self-organizing network (SON), 434
 semi-blind channel estimation, 84–85, 112–113, 115
 semidefinite programming (SDP), 150, 157, 168, 294–295
 sequential minimum-mean-square-error (SMMSE) estimation, 84–85
 session arrival, 349–350, 352
 side information, 61–62, 64, 66–67, 186–188, 198, 201
 single-carrier frequency-division multiple access (SC-FDMA), 44
 single fiber bidirection (SFBD), 452
 small-scale fading, 127, 170–171
 SoftRAN, 229–230, 251
 sparse beamforming, 81, 150, 154, 175, 177, 280, 312, 344
 spectral efficiency, 82–83, 110, 113, 115, 117–118, 128, 136, 146–147, 190–191, 193, 243, 312, 315, 344, 407, 410
 spectrum sharing, 377–378, 380–383, 385–387, 391–393, 450
 stationary distribution, 352, 354
 statistical multiplexing gain, 8, 347–349, 357–358, 364, 373
 Stieltjes transform, 330, 343
 symbolic subspace, 169
 symmetric quasidefinite matrix, 166
 substitutability, 424–426
 successive convex approximation (SCA), 68
 successive interference cancellation (SIC), 62, 66, 81, 198, 344
 superimposed training, 83–85, 93, 95, 101, 114–116
 training-based channel estimation, 82–85, 93, 112, 114–115, 155
 translation lookaside buffer (TLB), 464
 transmission diversity, 9, 236
 transmission time interval (TTI), 46–47, 49
 user-centric cluster, 60
 user-level resource scheduling (US), 436, 437
 virtual base stations (VBSs), 347–374
 virtual machines (VMs), 5–6, 433, 443–447, 449, 463–467
 visiting location register (VLR), 441
 wavelength division multiplexing (WDM), 6–8, 348, 351, 451–456, 470
 zero-forcing beamforming (ZFBF), 173–174, 176, 346