

Index

- 3rd Generation Partnership Project, 2
- 5G network, 2, 7–13, 61–63, 71, 72, 82, 97, 103, 112, 146, 184, 208, 241
- battery life, 3, 143, 156, 267–270
- cloud radio access network (C-RAN), 6–14, 61, 71–90, 99–117, 120, 129, 132, 136, 183–185, 197, 236, 242–243, 252, 261–266
- baseband unit (BBU), 6, 8, 12, 66, 71–78, 253, 261–266, 274, 277
 - CU-DU architecture, 74–76, 102
 - DU scheduling, 77
 - intra-CU switch, 81
- management and orchestration (MANO), 73, 96, 100, 104–105
- next-generation fronthaul interface (NGFI), 8, 12, 73–76
 - optical transport networks (OTN), 75
 - packet data convergence protocol (PDCP), 76, 79, 85–88, 99, 105, 112–114, 128, 185
- radio access network (RAN), 2–12, 61–90
 - radio link control (RLC) layer, 65, 68, 76, 79, 83, 85, 88, 99, 105, 109, 112–114, 128, 185
 - wavelength division multiplexing (WDM), 75, 76, 262–265
- total cost of ownership (TCO), 71, 75, 261
- connection-oriented network, 2
- content convergence, 2, 61
- core network (CN) convergence, 61
- cross-layer TCP optimization, 61, 136
- end-to-end (E2E) network architecture, 61, 62
 - flexible and smart RAN, 62
 - high layer split, 65–66, 70
 - non-real-time processing of RAN protocol stack, 65
 - open interface, 64
 - radio resource management (RRM), 65, 85, 88, 90, 100, 104, 106, 120, 195, 241
- flow-based QoS, 62, 69, 70
 - E2E bearer establishment, 69
- mobile edge computing (MEC), 69, 70, 73–74, 100, 110, 112
- multilevel centralized and distributed network
 - MCD protocol stack, 83–87
 - semi-static link, 84, 85
 - real-time channel mapping, 85
 - user-centric network (UCN), 82
- network slicing, 62, 64–68, 70, 103, 116
 - access control, 10, 69, 100, 119
 - E2E network slicing, 62, 65, 67, 184
 - RT (real-time) scheduling, 69
 - spectrum planning, 68
- service-based and componentized core network, 62
- service oriented architecture (SOA), 63
- transport network conditions, 65
- energy-efficient signaling design, 142–179
 - cell zooming, 13, 143–146
 - BS relaying, 144
 - device-to-device (D2D) communication, 110, 144, 189–191, 217
- multi-RAT HetNet, 142, 166–167, 175, 177–178
- single-RAT HetNet, 142, 166
- sleeping strategy, 143–146
 - base station (BS) sleeping, 143, 145–146, 166
- energy-saving solution
 - energy-saving in GSM, 253
 - multi-carrier power amplification, 252
 - single-carrier power amplifier, 252
 - energy-saving in LTE, 253–255
 - channel shutdown, 253, 260
 - multicast broadcast single frequency network (MBSFN), 255
 - small base station turnoff, 254
- multi-RAT cooperation energy-saving, 14, 109, 255–260
 - AP device shutdown, 260
 - AP RF channel shutdown, 260
- invisible base station (BS), 272–284
 - common public radio interface (CPRI), 11–12, 75–76, 261, 272, 274
 - smarTile, 11, 272–283
 - over-the-air calibration, 279, 280

- information and communication technology (ICT), 2, 8
- internet of things (IoT), 1, 70, 94, 116, 119, 182, 188, 214, 221
- network function virtualization (NFV), 6, 9, 12–13, 62–64, 71–74
- no more cells (NMC), 9, 81–82
- operating expenditure (OPEX), 3, 9, 71–72, 108, 129, 272
- peak data rate, 2, 182, 216
- quality of experience (QoE), 10, 33, 99–101, 106–107, 112, 118, 124, 184
- quality of service (QoS), 3, 34, 62–70, 87, 99–100, 103–104, 111–112, 118, 120, 124, 145, 200, 235, 256–257, 259
- radio access technology (RAT), 2, 9, 14, 61, 74, 118, 142, 166, 168–169, 185
- simultaneous wireless information and power transfer (SWIPT), 3
- software-defined air interface (SDAI), 6, 11, 13, 124, 182–246
- channel modeling, 96, 100–101, 186–188, 191
- birth and death of multipath components, 189
- channel hardening, 188, 198
- channel impulse response, 187
- correlation-based stochastic models, 187
- frequency dispersion, 186
- ray-tracing, 186, 191
- time-selective fading, 186
- flexible MIMO, 185, 198–207
- analog beamforming, 185, 198
- beam sweeping, 128, 133–136, 205–206
- digital beamforming, 133, 183, 185, 198–201, 205–207
- EE-SE green points, 202–203
- full-array structure, 199
- hybrid beamforming, 8, 11, 82, 198–207
- sub-array structure, 199, 202, 207
- TRP/UE analog beam(s) selection, 206
- flexible multiple access, 221–232
- cell-specific/user-specific interleaver design, 230
- constellation-constrained capacity, 228
- message-passing algorithm, 224
- multi-user shared access, 225
- non-orthogonal multiple access (NOMA), 185, 221–232
- orthogonal multiple access, 221, 229
- pattern division multiple access (PDMA), 185, 226–231
- posteriori probability detection, 224
- sparse code multiple access, 185
- successive interference cancellation (SIC), 222, 225
- super position coding (spc), 221–222
- frame structure design, 234, 237
- bidirectional subframe, 194–195
- flexible frame structure, 124, 128, 185, 191–195, 234, 252
- long and short scheduling frames, 194
- reference signal, 130, 183, 192, 195, 201, 207, 255, 280, 282
- scheduling unit, 192, 195, 197
- slot format, 197
- full duplex, 11, 16, 82, 182, 185, 192, 197, 232–241
- interference management, 99–100, 105, 192, 233
- joint interference mitigation, 236
- opportunistic DL/UL data, 239
- self-interference cancellation, 233
- self-interference mitigation, 235
- new waveform, 207–220, 274
- cubic metric, 217–218
- delay-Doppler domain, 211–212
- filter bank multi-carrier (FBMC), 183, 185, 207, 209–211, 214
- filtered-OFDM (f-OFDM), 185, 207–209, 214, 216
- generalized frequency division multiplexing (GFDM), 185, 207, 211–212, 214–215
- guard interval, 209
- orthogonal Time Frequency Space (OTFS), 185, 207, 211–215
- power back-off, 218–219
- raised-cosine edge, 208
- spectrum mask, 216
- unified framework of waveform, 208, 215
- universal filter multi-carrier (UFMC), 183, 185, 207, 209, 214, 216
- windowed OFDM (w-OFDM), 207–209, 216
- SCP function component, 241–246
- context-aware service delivery, 244–245
- service-oriented new UE state, 242
- SDAI slice, 242
- software-defined networking (SDN), 2, 6, 9–10, 13, 63–64, 66, 71, 73, 146
- multi-stream aggregation, 156
- software-defined radio (SDR), 5
- theoretical green strategies, 16–58
- access level energy saving, 18
- area energy efficiency, 19
- Pareto-optimal EE, 44, 46, 49–51, 169–191, 194, 179
- utopia EE, 44–46, 167, 169–171, 177, 179
- weighted minimum energy efficiency, 18
- weighted Tchebycheff method, 44, 46–47, 57–57, 167, 170

- EE-SE trade-off, 13, 20–21, 23–32
- network level energy saving, 18, 256, 258
- cellular network power consumption, 4
- heterogeneous networks (HetNets), 4, 9, 142, 166–167
- mobile VCE Green Radio Project, 4
- user experienced data rate, 2
- wireless big data, 94–96, 126–127, 191
 - background of big data, 90
 - data visualization, 93–94
 - distributed data mining, 93
 - distributed data storage and computing, 93
- wireless data source
 - IT+CT, 12, 96
 - IT+CT+DT, 12, 96
- wireless big-data-assisted network design
 - core network gateway, 101
 - central unit data analytics (CUDA), 105
 - distributed data analytics (DUDA), 105
- data driven intelligent RAN architecture, 104–105
- flexible content distribution, 103
- intelligent NMS/MANO, 100
- network data analytics (NWDA), 99, 104
- on-demand resource orchestration, 103
- wireless big-data-assisted network management
 - big-data-assisted protocol stack, 112
 - big-data-enabled efficient mobility management, 128
- coverage hole discovery, 100–101, 104, 106
- MAC Hybrid ARQ, 114
- proactive caching, 100–101, 110
- QoE issue debugging, 101, 106
- reconfigurable compression and encryption in PDCP, 113
- transform-domain signal processing, 123
- virtual-grid-enabled network performance optimization, 120
- wireless traffic, 1