

Index

Entries in bold are primary references, usually a definition.

- Absorption, 112, 298
 - coefficient, 113
 - cross section, **112**, 316
 - infrared, 113
 - internal, 316
 - ultraviolet, 113
- Adaptive bit loading, 712
- Adaptive estimation, 599
- Add-compare-select, 540
- Additive-noise-limited channel, **19**, 688
- Additivity property of entropy, 279, **674**, 862
 - product state, 786
- Algebraic block code, 611, **612**
 - binary, **617**, 640
 - critical rate, 611, **635**
 - generator matrix, 614
 - irregular, 647
 - matrix description, 613
 - performance, 623
 - properties, 613
 - Reed–Solomon, *see* Reed–Solomon code
 - regular, 647
 - weight profile, **628**, 635
- Algorithm
 - back-propagation, **564**, 724
 - Bahl, 644
 - split-step Fourier method, 229
 - Viterbi, **540**, 565, 626
- Aliasing, **46**, 399
- Alphabet, **1**, 609
 - q -ary, 609
 - binary, 609
- Amplified spontaneous emission, **334**, 337
- Amplifier, *see* Lightwave amplifier
- Amplify-and-forward, 5
- Amplitude
 - peak, xxv
 - root-mean-squared, xxv, **39**, 324
- Amplitude modulation, 12
- Amplitude-shift keying, **415**, 467
- Analytic signal, **32**, 101
- Ancilla embedding, 103, **810**
- Ancilla state, **789**, 810
 - image mode, 795
 - unoccupied, 792
- Angular frequency, **8**, 30, 235, 518, 570
- Anharmonic oscillator, 202
- Anisotropic material, **81**, 96
- Annihilation operator, 770
- Anomalous dispersion, 161
- Antenna, **18**, 298
- Anti-Stokes scattering, 205
- Antipodal modulation, 414, **466**, 477
 - error rate, 423, **476**
 - quantum optics, **775**, 831
- Approximation
 - gaussian, 453, **506**
 - paraxial, **92**, 120
- Arrival process
 - photodetection, 309
 - photoelectron, **258**, 285, 294
 - photon, 237, **257**, 311
- Arrival rate
 - constant, 259, 286, 428, 441
 - photoelectron, xxvi, **258**, 270, 312, 692
 - constant, 331, 519
 - photon, 9, 122, **257**, 265, 309, 311
 - time-varying, 257
- Associative property, 29
- Asymptotic
 - coding gain, **625**, 659
 - energy efficiency, **474**, 492, 689
- Attenuation, 155
 - coefficient, 114
 - material absorption, 112
 - optical fiber, 112
- Autocorrelation function, **68**, 72, 106, 294
 - additive white gaussian noise, 344
 - circularly symmetric gaussian noise, 267
 - complex-baseband noise, 76
 - electrical, **98**, 109
 - fourth-order, 267
 - frequency, 199
 - laser, 345
 - lightwave noise power, 267
 - lightwave power, 98

- noise, **74**, 279
- optical, 109
- width, 70
- Autocovariance function, *see* Covariance function
- Avalanche photodiode, 290, **306**, 515
 - absorption region, 306
 - characteristic function, 333
 - current loop, 307
 - gain, 306
 - multiplication region, 306
 - probability mass function, 332
- Axial field component, **88**, 124, 139
- Axis
 - fast optic, **97**, 183
 - optic, 97
 - polarization, 96
 - principal, 81
 - slow optic, **97**, 183
- Back propagation, **564**, 724
- Bahl algorithm, 644
- Balanced modulator, 330
- Balanced photodetection, 9, 19, **308**, 378, 494, 574
- Bandgap, **303**, 319
- Bandlimited
 - channel, **18**, 21, 238, 271, 398, 522, 659
 - gaussian noise, **271**, 274
 - gaussian random process, *see* Random process, gaussian, bandlimited
 - information channel, **676**, 706, 710
 - lightwave signal, **277**, 294
 - lightwave source, 325
 - noise, 75
 - random process, *see* Random process, bandlimited
 - signal, 12, 24, **34**
 - system, **26**, 74
 - waveform, **45**, 109, 723
 - wavelength-multiplex channel, 726
- Bandwidth, 12, **34**
 - 3-dB, **34**, 355
 - effective, 70
 - half-power, **34**, 74
 - ideal, 34
 - maximum, **45**, 281
 - noise
 - circularly symmetric gaussian, 271
 - noise-equivalent
 - baseband, **74**
 - complex-baseband, **77**, 280
 - passband, **74**, 77
 - root-mean-squared, **34**, 100
- Baseband
 - noise-equivalent bandwidth, 74
 - signal, **3**, 12, 24
 - power, 11
 - waveform, **3**, 45, 398
- Basis, **41**
 - change of, **48**, 102, 745
 - countable, **39**, 751
 - finite field, 613
 - Fourier, 45
 - gaussian distribution, 59
 - mode, 88
 - Nyquist, 45
 - orthonormal, **41**, 50, 88, 100, 277
 - polarization mode, 96
 - principal polarization state, 370
 - spatial modes, 147
 - square-root, 840
 - uncountable, 751
- Bayes' rule, **55**, 413, 545, 640, 651
- Beamsplitter, **301**, 789
- Beer–Lambert law, 113
- Belief propagation, 665
- Bending loss, 151
- Berrou code, **642**
 - consensus, 644
 - constituent decoder, 644
 - prior, 644
 - error rate floor, 646
 - minimum Hamming distance, **646**, 655
 - parallel concatenation, 646
- Bessel differential equation, 134, **151**
- Bessel function
 - expansion
 - large-argument, 168
 - small-argument, 153
 - first kind, **132**, 134, 406
 - identity, 141
 - modified, **62**, 104, 518, 638
 - recursion relations, 136
- Bias, **15**, 513
 - current, **324**, 327
 - forward voltage, 304
 - reverse voltage, **304**, 305, 352
- Binary asymmetric channel, **436**, 439, 441
 - quantum, **831**, 868
- Binary block code, **617**, 640
- Binary entropy function, **636**, 675, 701, 865
- Binary phase-shift keying, **466**, 475, 625
 - error rate, 476
 - error rate floor, 485
 - with phase noise, 484
- Binary symmetric channel, **434**, 439, 456, 701
 - capacity, 705
 - crossover probability, 434
 - quantum, 831
- Binomial
 - coefficient, **590**, 624
 - probability mass function, 260
- Biorthogonal modulation, 499

- Birefringence, **81**, 370
 circular, **97**, 183
 fiber, 370
 linear, 97
 optical fiber, 183
 intensity-dependent, 218
 linear, 185
- Bit, 1, 240
 energy, 22, **423**, 466
 error, **6**, 431
 error rate, **6**, 15, 25, 477
- Bivariate
 gaussian random variable, 106
 probability density function, **54**
 gaussian, **58**, 104, 251, 253
 maximum-entropy, 252
- Block
 code, *see* Algebraic block code
 detection, 401, **495**, 573, 849
 quantum-lightwave, 869
 signal, 255, **373**, 491, 554, 724, 732
 synchronization, 573
 transfer function, 373
- Block-symbol state, 742, 778, 815, 819, **846**, 848
 construction, 850
 detection, 849, **851**, 852
 detection operator, 816
 entangled state, 781, **819**, 861
 partial trace, 858
 product state, 781, **819**
- Blocklength, 614
- Blue-shift, **213**, 404
- Boltzmann
 constant, 240
 entropy, 673
 factor, 206, **245**
 probability density function, **250**, 293
- Bose–Einstein probability mass function, **244**, 293
- Bound
 Shannon
 bandlimited channel, 21, **711**
 single-letter capacity, **697**, 699
 spectral rate efficiency, 22, **719**
 union, **479**, 541, 840, 842
 von Neumann entropy, 868
- Boundary
 cladding/casing, 137
 core/cladding, **127**, 133, 138
 planar, 115
- Boundary conditions, **80**, 88, 115, 121, 127, 151
 step-index fiber, 138
- Bounded-distance decoder, 622
- Bra, 48, **751**
- Bra–ket notation, 750
- Bragg diffraction grating, 207
- Branch (mode)
 characteristic equation, **130**, 142
- Branch (trellis), **537**, 538, 626
 metric, **539**, 632
 state-dependent, 560
 label, 538, 656
 trellis-coded modulation, 658
- Brillouin scattering, 206
 stimulated, 313
- Burst error, 608
- Campbell’s theorem, 286, **289**, 296, 428, 458, 569
 derivation, 290
 modified form, 290
- Campbell–Baker–Hausdorff identity, 772
- Canonical commutation relationship, **764**, 766
- Canonical quantization, **751**, 761
- Capacity, *see* Channel capacity
- Carrier, **12**
 coherent, **6**, 13, 214, 560
 frequency, **12**, 31
 noncoherent, **6**, 13, 25, 172, **387**, 392, 393, 467,
 556, 566
 wavelength autocorrelation function, 179
 partially coherent, 471, 507, **510**, 569
- Causal impulse response, 73
- Causality, 29
- Central chi probability density function, **65**
 one degree of freedom, 65
- Central chi random variable, 65
- Central chi-square probability density function, **63**,
 372, 376
N degrees of freedom, 64, 274
- Central chi-square random variable, 63
- Central limit theorem, **66**, 216, 256, 279, 286, 371,
 553, 726
- Centroid, 34
- Centrosymmetric material, 203
- Chain rule
 entropy, **674**, 731
- Channel, 1, **17**
 additive white gaussian noise, **271**, 281, 425, 530
 discrete-time, 400
 additive-noise-limited, **19**, 688
 bandlimited, **18**, 21, 238, 271, 398, 522, 659, 671,
 676, 710
 binary asymmetric, **436**, 439, 441
 quantum, **831**, 868
 binary symmetric, **434**, 439, 456, 701
 “black box”, **672**, 691, 843
 capacity, *see* Channel capacity
 classical
 ideal, **854**, 856
 code, *see* Code, channel
 coherence timewidth, 590
 continuous-time
 memoryless, 374

- discrete-time, 17, 18, **398**, 411, 494, 671, 698
 - additive bandlimited gaussian noise channel, 634
 - additive white gaussian noise, 412
 - electrical, **397**, 411
 - matrix, 602
- electrical, *see* Electrical channel
- gain, 709
 - noise, 872
 - signal, 872
- “gray box”, **691**, 843
- impulse-response matrix, 373
- information, *see* Information channel
- interference-limited, 552
- lightwave, *see* Lightwave channel
- memoryless, **672**
 - Kerr, 729
 - continuous-time, 374
 - discrete-time mimo, 707
 - photon-noise-limited, 446
 - space-time separable, 495
- multi-input multi-output, 15, **372**, 602
 - continuous-time, 374
 - mode-multiplex, 372
- multiplex, *see* Multiplex channel
- noiseless product-state, 858
- noisy product-state, 860
- nonlinear, 23, 559, **722**
 - interference-limited, 726
 - Kerr, 722
- phase-insensitive, **253**, 799, 871
- photon-noise-limited, **265**, 402
- photon-optics, *see* Photon optics
- physical, 4, **17**, 361
- Poisson, 265, 311, **401**, 692
- product, **706**
- quantum-lightwave
 - gaussian, 871
- reverse, 529
- signal-dependent-noise, 20
- space-multiplex, 15, **369**
- space-time separable, **376**, 494
- state, 536
- state estimation, 590
- state vector, 536
- transfer-function matrix, 370, 373
- transition matrix, **636**, 672
- transition probability matrix, **636**, 672, 679, 817
- wave-optics, *see* Wave optics, channel
- waveform, **17**, 397
 - bandlimited, 18
 - electrical, **17**, 398
 - lightwave, 17
- Z, 693
- Channel capacity, 20, 237, 363, **669**
 - additive-noise-limited channel, **688**, 697
 - classical limit, 695
 - large-signal limit, 695
- bandlimited, 21
 - discrete-time memoryless channel, 679
 - equal-energy signaling, 711
 - photon-optics, 21, **713**
 - wave-optics, 21, 676, **710**
- binary-symmetric channel, **636**, 705
- classical, 859
- continuous information channel, **710**
- dispersionless nonlinear lightwave channel, 724
- ideal classical channel, 854
- ideal photon-optics channel, 685
 - homodyne demodulation, 694
 - large-signal limit, 686
 - small-signal limit, 687
 - small-signal limit per photon, 687
- information-theoretic, 21, **670**
- intensity modulation, 701
- multi-user detection, 728
- noiseless product-state channel, 858
- noisy product-state channel, 860
- nonlinear interference-limited channel, 726
- phase modulation, 638, **703**
- Poisson channel, **692**, 731, 867
- product channel, 706
- quantum-lightwave channel
 - additive-noise, 871, **876**
 - block-symbol state, 869
 - classical, 843
 - component-symbol state, 867
 - phase-insensitive, 876
 - thermal-noise, 876
- single-carrier nonlinear lightwave channel, 723
- single-letter, **20**, 676
 - photon-optics, 244, **680**
 - wave-optics, 684, **696**
- Channel matrix, **373**, 401, 707, 871
 - frequency domain, 373
 - nonhermitian, 189
 - normal, **495**, 554
 - polarization, 370
 - time domain, 373
- Characteristic equation, **128**, 158
 - hybrid mode, 141
 - linearly polarized mode, 153
 - TE mode, 128
 - TM mode, 129
- Characteristic function, **56**, 275
 - conditional, 288
 - exponential probability density function, 282
 - noncentral chi-square probability density function, **64**, 275
 - Poisson probability distribution, **260**, 264
 - Poisson transform, 263
 - probability mass function, 56

- quantum, 799
- Check equations, **614**, 649
 - Gallager code, 649
 - Tanner graph, 647
- Check matrix, 614
 - regular, **617**, 646
 - systematic, 616
- Checkword, 642
- Chi probability density function
 - central, 65
 - noncentral, 65
- Chi-square probability density function
 - central, **63**, 372, 376, 731
 - N degrees of freedom, 64, 274
 - two degrees of freedom, 64, 273
 - noncentral, 105, 347, 360, 805
 - N degrees of freedom, 64, 274, 284
 - two degrees of freedom, **63**, 255, 273, 340, 561
- Chirp, **213**, 404
- Chromatic dispersion, 161
- Circular polarization, 94
- Circularly symmetric
 - complex gaussian random variable, 60
 - complex gaussian random vector, 60
 - gaussian noise, **256**, 271, 334, 390, 481, 573, 575, 724, 748, 872
 - gaussian prior, **697**, 699, 877
 - gaussian probability density function, **58**, 78, 254, 872
 - multivariate, **60**, 707
 - gaussian random process, **255**, 343, 574
 - bandlimited, **277**, 283
 - gaussian random variable, **58**, 78, 251, 254, 281, 483, 518, 553, 602, 696
 - with a bias, 255
 - gaussian random vector, 106
 - gaussian signal state, 748, **806**, 873
 - gaussian smoothing function, 802
- Classical
 - information, **679**, 736, 815
 - optics, 6
 - signal state, 741
- Clock phase, 473
 - estimation, 587
 - synchronization, **573**, 586
- Closure property, 774
- Coaxial cable, 124
- Code
 - algebraic, *see* Algebraic block code
 - Berrou, *see* Berrou code
 - binary block, **617**, 640
 - channel, 2, 15, 534, 535, **608**
 - check matrix, 614
 - composite, *see* Composite code
 - constrained, 660
 - convolutional, *see* Convolutional code
 - critical rate, 611, **635**
 - cutoff rate, 611, **635**
 - cyclic, **613**, 620
 - data modulation, 609
 - data transmission, 608
 - DC-balanced, 663
 - DC-free, 663
 - dicode, 663
 - dual, 614
 - duobinary, 663
 - modified, 663
 - error control, 608
 - Gallager, *see* Gallager code
 - graphical description, 625
 - Gray, **451**, 477, 515
 - Hamming, 615
 - heft, **616**, 647
 - inner, 609
 - LDPC, *see* Gallager code
 - linear, 613
 - low-density parity-check, *see* Gallager code
 - maximum-distance, **613**, 620
 - modulation, 659
 - Morse, 15
 - outer, **609**, 612, 655
 - partial-response, 534, **663**
 - precode, **534**
 - punctured, 643
 - rate, **2**, 534, 609
 - Reed–Solomon, *see* Reed–Solomon code
 - repetition, **615**, 666
 - runlength-limited, 660
 - source, **15**
 - spectral-notched, 663
 - stream, 628, **662**
 - turbo, *see* Berrou code
 - Ungerboeck, 656
- Codebit, **609**, 617
 - convolutional code, 631
 - energy, **623**, 646
 - Gallager code, 652
- Codebook, **609**, 780, 847
 - quantum, 847
- Coded-modulation, xx, 3, 15, 22, 238, **413**, 464, 534, 685, 741
- Codeframe, 630
- Codeword, 2, 5, 15, 413, **609**
 - block error rate
 - hard-decision, 624
 - soft-decision, 625
 - error rate, 475, **610**
 - sensed, 610
- Coding gain, 475, 610, **659**
 - asymptotic, **625**, 659
- Coherence, **6**
 - function, **97**, 105

- temporal, 68
- interval, **70**
- partial, 13, 388, 470, **556**, 569
- quantum, 7, **782**, 784, 805
- region, **98**, 374, 376
- spatial, **98**, 374
- temporal, 97
- time, 78
- timewidth, **70**, 98, 293, 294
- Coherent carrier, **6**, 12, 13, 214, 560
- Coherent state, 737, **739**, 761, 762, 772
 - P distribution, 797
 - binary detection, 831
 - binary error rate, 831
 - density matrix for a pure signal state, 802
 - displacement operator, **772**, 836
 - in-phase component operator, 761
 - minimum-uncertainty, 749, **767**, 802
 - nonorthogonality, **774**, 775, 848, 867
 - operator, **762**, 789
 - photon-number-state representation, 741, **773**
 - quadrature component operator, 761
 - state detection, 789
 - symmetric, 840
- Colored noise, 74
- Commutation relationship, 810
- Commutative property, 29
- Commutator, **51**, 102, 763
- Commuting operator, 792
- Complementary error function, **57**, 437, 456
- Complex-conjugate transpose, **42**, 60, 107, 351, 751
 - coherent-state operator, 762
 - dispersion relationship, 165
 - gradient, **596**, 606
 - random variable, **53**
- Complex-baseband
 - impulse response, 40, 364
 - noise
 - autocorrelation function, 76
 - bandwidth, 271
 - equivalent bandwidth, 77
 - power density spectrum, 76
 - probability density function, 250
 - random process, 75
 - signal, 12, **39**, 53, 77, 101, 307, 362, 383
 - energy, 44
 - transfer function, 40
 - waveform, 399
- Complex envelope
 - field, **88**, 144, 387
 - power density spectrum, **179**, 198
 - signal, 39, **144**, 162, 361, 389, 724
 - spectrum, 364
 - vector form, 218
- Component
 - in-phase, **39**, 313
 - quadrature, **39**, 313
- Component maximum posterior, 544
- Component-symbol state, 742, **759**, 776, 778, 780, 815, 819, 844, 846, 869
 - marginalization to, 858
- Componentwise maximum posterior, 544
- Componentwise maximum-posterior decoding, 639
- Composite code, **611**, 639, 641
 - Berrou, 642
 - Gallager, 641
 - low-density parity-check, *see* Gallager code
 - turbo, *see* Berrou code
- Composite signal
 - space, 742, **759**
 - state, **742**, 813
- Concave function, 719
- Conditional
 - entropy, **673**, 854
 - probability, **54**, 291, 545
 - density function, **54**, 431
 - of a detection error, **437**, 507
- Conjugate symmetric signal, 32, **269**
- Conjugate variables, **767**
- Consensus, 644
- Constant
 - Boltzmann, 240
 - Euler, 153, 731
 - free-space permeability, 80
 - free-space permittivity, 80
 - Planck's, 8
 - reduced Planck's, **8**
- Constant-modulus objective function, 598
- Constellation, *see* Signal constellation
- Constitutive relationships, **81**, 83, 150
- Constrained code, 660
- Constraint length, **536**, 543, 551
 - of a constituent code, 642
 - of a convolutional code, 629
 - of intersymbol interference, 536
- Continuous information channel, **18**, 634
 - gaussian, 698
 - memoryless, 634
- Continuous-time
 - channel
 - memoryless, 374
 - multi-input multi-output channel, 374
 - system, 28
 - waveform, 17, 398, **414**
- Controlled local oscillator, 576
- Convolution, **28**
 - associative property, 29
 - commutative property, 29
 - distributive property, 29
 - Fourier transform of, 31
- Convolutional code, 611, **628**
 - binary, 629

- codebit, 631
- codeframe, 630
- constraint length, 629
- dataframe, 630
- decoding
 - sequential, 633
 - Viterbi, 629
- encoder, **629**, 630
- generator polynomial, 630
- performance, 634
- trellis, 632
- weight profile, 635
- Correlation, 55
 - coefficient
 - random variable, 58
 - signal, 466
 - pseudocovariance
 - function, 268
 - matrix, 107
- Correspondence principle, **762**, 771, 792
- Costas loop, 582
- Counting soldiers, 667
- Coupled-mode theory, **146**, 299, 371
- Coupler
 - 180-degree hybrid, 300
 - 3-dB, **301**, 351
 - 90-degree hybrid, 301
 - directional, 300
 - symmetric, 300
 - lightwave, 298
 - multimode interference, 301
- Coupling
 - amplitude–phase, 405
 - coefficient, 147
 - efficiency, **117**, 150
 - fiber, **150**
 - matrix, 299
 - mode, *see* Mode coupling
- Covariance, **56**, 58
 - function, **68**, 346
 - matrix, **59**, 749
 - gaussian state, 806
 - noise, **255**, 495
 - real, **57**, 252, 593
 - signal, **707**, 733
 - spatiotemporal, 375
- Cramér-Rao bound, 593
- Creation operator, 770
- Critical
 - angle, **116**, 130
 - rate, 611, **635**, 636
- Cross
 - coherence function, 98
 - phase modulation, **224**, 227, 553
 - interference, 226
 - polarization
 - modulation, 218
 - power density, 89
- Cross section, 315
 - absorption, **112**, 316
 - scattering, 114
 - stimulated emission, 355
- Crossover probability, 434
- Crosstalk, 16, **368**, 371, 373
- Cumulative probability distribution function, 53
- Curl, **79**, 83
- Cutoff condition, **130**, 153, 158
 - hybrid mode, 143
 - linearly polarized mode, 137
- Cutoff rate, 611, **635**
 - figure, 636
 - phase-shift keying, 638
- Cyclic code, **613**, 620
- Dark current, 306, **312**, 358
 - noise, 331
- Dataframe, **572**, 630
- Dataword, **2**, 15, 609, 617
- dBm, 25
- Decision region, **430**, 477, 478, 817
 - complex gaussian noise, 480
 - real gaussian noise, 436
- Decision subspace region
 - classical, **497**, 818
 - quantum-optics, **820**, 839
- Decision-feedback demodulation, 419, **533**
 - combined with a linear equalizer, 533
 - error propagation, 533
- Decoder, 5, **18**, 361, 410
 - bounded-distance, 622
 - data modulation, 609
 - data transmission, 609
 - hard-decision, 545, **610**
 - incomplete, 622
 - iterative, 611
 - message passing, 648
 - sequential, 611
 - soft-decision, 545, **610**, 625
 - spherical, 611
 - Viterbi, 633
- Decoding, 5, 523, **610**, 691
 - error, **622**, 622, 624
 - failure, 622
 - hard-decision, 698
 - maximum-likelihood, **629**, 639
 - sequential, 629, **633**, 637
 - sphere, 628
 - spherical, 621
 - trellis-based, 632
 - turbo, 643
- Decoherence, 783
- Delay

- group, *see* Group delay
- ray, 156
- Delay spread, **176**
 - control, 180
 - distribution, 177
 - maximum, 178
 - minimum, 177
 - ray optics, **156**, 191
 - root-mean-squared value, 182
 - step-index fiber
 - maximum, **156**, 179
 - wavelength-dependent, **181**, 214
- Delay-line interferometer, 301
- Delay-locked loop, **587**, 606
- Demodulation, **4**
 - decision-feedback, 533
 - combined with a linear equalizer, 533
 - error propagation, 533
 - direct photodetection, **20**
 - energy, 500, **509**
 - envelope, **14**, 24, 388
 - hard-decision, **5**, 18
 - heterodyne, 13, **379**, 381
 - quantum-lightwave, 792
 - homodyne, 13, **380**, 383, 694
 - quantum-lightwave, 790
 - to a complex-baseband waveform, **380**, 574
 - to a real-baseband waveform, 380
 - to quantum complex-baseband, 795
 - noncoherent, **500**, 512
 - noncoherent binary, 518
 - partial-response decision-feedback, 419
 - partial-response maximum-likelihood, 664
 - phase-asynchronous, 14, 362, **388**, 463, 500
 - phase-sensitive, 790
 - phase-synchronous, **13**, 524
 - quantum-lightwave, 747
 - soft-decision, **5**, 18
- Demodulator, **307**, 361
 - complex-baseband, 379
 - direct-photodetection, *see* Direct photodetection
 - dual-polarization, 493
 - heterodyne, **307**, 381
 - homodyne, 309
 - phase-asynchronous, 14, **500**, 502
 - phase-synchronous, **379**, 476
 - quantum heterodyne, 792
- Density function, *see* Probability density function
- Density matrix, 679, 680, 746, **777**
 - average, **780**, 847
 - block-symbol state, **780**, 858
 - component-symbol state, **780**, 858
 - basis, 781
 - coherent ensemble, 783
 - marginalized, **779**, 859
 - mixed signal state, *see* Mixed signal state
 - noncoherent state, 783
 - photon-number-state representation
 - additive noise, 803
 - bias plus noise, 804
 - thermal noise, 872
 - product state, **779**, 786, 857
 - pure signal state, *see* Pure signal state
 - signal constellation, **780**, 780
 - signal plus noise, 838
 - statistical ensemble, 783
 - vacuum state, 872
- Density operator, 746
- Depletion region, 305
- Detection, **5**, **8**
 - hard-decision, 5, 18, 418, **610**, 698, 700
 - photon-optics signal model, 692
 - maximum-likelihood, 433
 - maximum-posterior, 433
 - maximum-posterior sequence, 544
 - multi-user, **373**, 728
 - optimal, 477
 - quantum, 747, **816**, 846
 - coherent states, 831
 - sequence, 542
 - signal state, *see* Signal state, detection
 - single-user, **373**, 726
 - soft-decision, 5, 18, 418, **610**, 698
 - symbol-by-symbol, **5**, 528, 545
- Detection filter, 5, 390, **423**
 - additive noise, 426
 - integrating, 425, 458
 - intersymbol interference, 556
 - linear, 424
 - matched, *see* Matched filter
 - minimum error, 529
- Detection operator, 816, **820**
 - antipodal coherent state modulation, 831
 - block-symbol state, **816**, 849
 - component-symbol state, **816**, 849, 867
 - displacement receiver, 835, 880
 - homodyne demodulation, **791**, 835, 880
 - optimal, 832
 - relationship to matched filter, 834
 - orthogonal pure signal state, 829
 - quantum on-off keying, **834**, 880
 - suboptimal, 835
 - table of, 832
- Detection statistic, 395, 412, **419**, 424, 525
 - complex sample, 477
 - photon-counting, 692
 - sufficient, **399**, 412, 419, 420, 622
- Detection threshold, **5**, **433**
 - binary symmetric channel, **439**
 - dependence on prior probability, 439
 - direct-photodetection, 433
 - optimal, 436

- photon counting, 402
 - ideal, 441
 - nonideal, 442
- Determinant, 48
- Dielectric
 - material, **80**, 84, 110, 151, 166, 202
 - waveguide, 87, **124**
 - cylindrical, 132
- Differential
 - delay, 191
 - group delay, 214
 - per unit length, 185
 - polarization-dependent, **185**, 196
 - phase shift, 184
 - transit time, 156
- Differential entropy, **240**, 673, 696
 - conditional, 724
- Differential equation
 - Bessel, 151
 - Helmholtz, 84
 - lightwave amplification, 316
 - nonlinear pulse propagation, 217
 - nonlinear Schrödinger, 202
 - phase-locked loop, 578
- Differential-phase modulation, 469
 - binary, 469
 - bit error rate, 503
 - multilevel, 504
- Differential-phase-shift keying (DPSK), *see* Differential-phase modulation
- Diffraction, 298
 - grating, 207
- Digitize, 1
- Dipole, 80
- Dirac
 - impulse, **28**, 89, 345
 - signal-state representation, 752
- Direct photodetection, xxv, 9, 14, **310**, 519
 - demodulation, **20**
 - with intensity modulation, *see* Intensity modulation
- Directional coupler, 300
 - symmetric, 300
- Discrete information channel, **18**, 610, 672, 679, 691
 - memoryless, **634**, 679
- Discrete-time
 - additive white gaussian noise channel, **400**, 412
 - channel, 17, 18, **398**, 411, 494, 671, 698
 - channel matrix, 602
 - direct-photodetection channel, **401**, 412
 - electrical channel, **397**, 411
 - Poisson channel, **401**, 412
 - sequence, **398**
- Discriminator, 311
- Dispersion, 4, **126**
 - anomalous, 161
 - chromatic, 161
 - controlled optical fiber, 229
 - group-velocity, **161**, 167
 - intermodal, **155**, 163, 169, 176, 194
 - intramodal, **155**, 169, 173, 194
 - length, **213**, 216, 226, 235, 404, 563
 - linear, 4, **126**, 155, 175
 - material, 82, **155**, 163
 - coefficient, **164**, 175, 180
 - zero wavelength, **164**, 180
 - multiple sources, 181
 - narrowband, 159
 - nonlinear, 155
 - normal, 161
 - polarization-mode, 94, 97, 155, **182**
 - ray optics, 156
 - shifted optical fiber, 181
 - slab waveguide, 157
 - slope, 194
 - transit time, **156**
 - waveguide, 194
 - coefficient, **174**, 180
- Dispersion relationship, 6, **86**, 159, 167, 191, 364
 - complex, 165
 - graded-index optical fiber, 169
 - normalized, **158**, 159
 - plane-wave, 86
 - power series approximation, 160
 - waveguide mode, 157
- Dispersive material, 82
- Displacement operator, **772**, 836
- Displacement receiver, **445**, 488
 - binary error rate, 446
 - detection operator, **835**, 880
- Distance
 - euclidean, **44**, 478, 539
 - maximum, 850
 - minimum, 414
 - squared, **44**, 478, 774, 840
 - Hamming, 613
 - minimum, 613, **616**
 - metric, 478
- Distortion, 4, **155**
 - intensity-dependent, 16
 - linear, 4
 - mode-dependent group delay, 175
 - multiple sources, 181
 - polarization-dependent delay, 187
 - polarization-dependent loss, 189
 - wavelength-dependent group delay, 179
 - nonlinear, 4, **216**
 - single pulse, 219
- Distributive property, 29
- Divergence, 79
- Diversity, 608
 - polarization, 491

- Doping, 303
 Doppler shift, 207
 Down-conversion, **304**, 379
 Dual
 code, 614
 space, 614
 Dual-polarization keying, 491, **493**
 Dyadic product, 43
- Effective
 area, **211**, 232
 length, **213**, 229, 234, 235, 563
 power, **223**, 233
 Effective timewidth, 34
 Eigenbasis, **49**, 51, 741, 753, 758, 831
 countable, 753
 uncountable, 753
 Eigenfunction, **33**, 86, 88, 278
 Eigenmode, 33, 86, **88**, 121
 Eigenstate, **742**, 752, 754, 755
 common set for observables, 748
 homodyne demodulation, 835
 of coherent-state operator, 768
 photon-number operator, 754
 polarization measurement, 756
 sampling, **821**, 836, 879
 sampling operator, 823, 828, 834
 Eigenvalue, **33**, 47, 50, 86, 278
 Eigenvector, **47**
 of a covariance matrix, 59
 orthogonal, 185
 Eikonal equation, **92**, 105, 119
 Elastic scattering, 114
 Electric field, 79
 complex representation, 84
 cylindrical coordinates, 138
 Electric flux density, 79
 Electrical
 bit energy, **423**, 466
 channel, **17**, 361
 discrete-time, **397**, 411
 intermodal-dispersion-limited, 392
 intramodal-dispersion-limited, 393
 nonlinear, 556
 relationship to lightwave channel, 362
 optical conversion, **9**, 362
 pulse, xxvii, **100**, 391
 energy, 365, **382**, 423, 426, 466
 signal-to-noise ratio (SNR), **75**, 108, 268, 343
 relationship to OSNR, 268
 waveform, xxvii, 108
 classification, 377
 direct photodetection, 296
 noiseless, 416
 noisy, 430
 phase-synchronous demodulation, 307
- Electro-optic effect, 329
 Electromagnetic
 field, 79
 complex-baseband, 87
 wave, 83
 Electron–hole pair, 303
 Electrostrictive force, 207
 Encoder, 2, **18**, 241, 242, 361, 410
 Berrou code, 642
 classical, 844
 convolutional code, **629**, 630
 inner, 612
 optimal, 670
 outer, 612
 state, 658
 systematic, 617
 trellis description, 632
 Energy
 codebit, **623**, 646
 complex-baseband signal, 44
 direct-photodetected lightwave, 336
 electrical bit, 22, **423**, 427, 466
 electrical pulse, 365, **382**, 423, 426, 466
 level, 244
 passband signal, 12, 25, **44**
 photon, 8
 quanta, 203
 redistribution, **4**, 146
 between subchannels, 373
 linear, 155, **202**, 395
 multimode fiber, 155
 nonlinear, **216**, 221
 thermal, 112, 206, **243**
 vacuum-state, **246**, 770, 771
 zero-point, **246**, 771
 Energy demodulation, 500, **509**
 Energy efficiency, **474**
 intensity modulation, 505
 PSK, 474
 QAM, 474
 Ensemble, 68
 Entangled state, *see* Signal state, entangled
 Entropy, **239**, 673
 additivity property, 279, **674**, 862
 Boltzmann, 673
 chain rule, **674**, 731
 classical, 673
 conditional, **673**, 854
 differential, **240**, 673, 696
 conditional, 724
 Gordon distribution, 685
 joint, 673
 noise, **682**, 698, 731
 Poisson distribution, **687**, 692, 732
 product distribution, 674
 Shannon, 673, **785**

- table of common distributions, 240
- units, **240**, 696
- von Neumann, *see* von Neumann entropy, 880
- Envelope, **12**, 14
 - complex field, **88**, 144, 387
 - complex signal, 12, 39, **144**, 162, 361
 - vector, 218
 - demodulation, **14**, 24, 388
 - passband signal, 162
 - root-mean-squared amplitude, 364
- Envelope method, **700**, 729
- Equalization, **522**, 527
 - linear, 527
 - with additive noise, 530
 - matched filter, 528
 - nonlinear, 559
 - optical fiber dispersion, 181
 - zero-forcing, 528
- Equalizer
 - constant modulus, 598
 - minimum mean-squared error, 529
 - nonlinear minimum-error, 541
 - zero-forcing, **528**, 533
 - multi-input multi-output channel, 554
- Equivalence class, 496
- Erbium, 313
 - doped lightwave amplifier, *see* Lightwave amplifier
- Ergodic process, 69
- Error
 - bit, **6**, 431
 - block, 6
 - burst, 608
 - codeword, 6
 - decoding, 622
 - frame, 6
 - function, **57**, 63, 347
 - complementary, **57**, 437, 456
 - message, **6**, 676
 - propagation, 533
 - random, 608
 - symbol, **5**, 21, 451, 456
- Error rate
 - antipodal modulation, 476
 - based on the union bound, 481
 - binary coherent state, 831
 - binary orthogonal modulation, 476
 - binary phase-shift keying, 476
 - with phase noise, 485
 - binary pure signal state, 830
 - bit, **6**, 15, 25, 477
 - bit error vs. symbol error, 451
 - block, 6
 - codeword, 6, 15, **610**
 - differential-phase-shift keying (DPSK), 503
 - equal-energy phase-asynchronous modulation, 503
 - floor, 485
 - frame, 6, **589**
 - gaussian approximation, 506
 - heterodyne binary phase-shift keying, 487
 - homodyne binary phase-shift keying, 487
 - shot-noise limit, **487**, 832
 - with matched local oscillator, 832
 - message, **6**, 15, 676
 - multilevel modulation, 447
 - on–off keying, 438
 - quantum, 834
 - shot-noise limit, 506
 - with additive white gaussian lightwave noise, 453, 504
 - phase-shift keying, **483**, 504
 - photon counting, **441**, 832
 - binary keying, 441
 - multilevel keying, 451
 - with a matched local oscillator, 832
 - with noise photons, 441
 - quadrature amplitude modulation (QAM), 482
 - quantum antipodal modulation, 832
 - quantum on–off keying, 832
 - sequence detection, 540
 - shot-noise-limited, 487
 - symbol, 451
- Estimation
 - adaptive, 599
 - carrier phase, 13, **574**
 - decision-directed, 581
 - error, 577
 - maximum-likelihood, 574
 - channel matrix, 602
 - channel state, 590
 - clock phase, 587
 - detection filter, 595
 - impulse response, 591
 - joint carrier and clock phase, 588
 - nonlinear phase, **463**
 - polarization-state, 553, **600**, 606
 - spatial mode, 601
 - stochastic gradient decent, **600**, 603
- Étendue, 117
- Euclidean distance, **44**, 478, 539
 - maximum, 850
 - minimum, 414
 - squared, **44**, 478, 774, 840
- Euler’s constant, **153**, 731
- Evanescence
 - field, 131
 - mode, **131**, 148
- Evidence
 - extrinsic, **547**, 641, 649
 - intrinsic, 545, **547**, 641, 649, 655

- Evolution equation for pulse timewidth, **222**, 232
 Excess noise factor, **332**, 515
 Expectation, **53**, 270
 quantum, **754**, 777
 Expected number
 of noise photons, **241**, 490, 684, 695, 803, 838
 of photons, 241
 of signal photons, **241**, 739, 805
 Expected value, 53
 Exponential
 probability density function, **65**, 103, 250, 273,
 376, 702
 random variable, **65**
 Extinction ratio, **327**, 516
 Extrinsic evidence, 545, **547**, 641, 649
 Berrou code, 645
 Gallager code, 651
 Eye diagram, **525**
- Fabry–Pérot resonator, 357
 Fano inequality, 675
 Fast optic axis, **97**, 183
 Fermat's principle, 92
 Few-mode fiber, 369, **372**, 601
 Fiber, *see* Optical fiber
 Field
 electric, 79
 electromagnetic, 79
 finite, *see* Finite field
 magnetic, 79
 monochromatic, **80**, 83, 125, 151
 complex, 125
 narrowband, 87
 plane-wave, 85
 Filter
 all-pass, 364
 causal, 29
 detection, 390, *see* Detection filter
 estimation, 595
 image-rejecting, 578
 linear shift-invariant, 29
 loop, **577**, 580, 604
 lorentzian, 295
 noise-suppressing, **271**, 293, 354, 381, 382, 396,
 559
 transversal, **531**, 559
 Wiener, **591**, 598
 Finite field, **612**, 618
 basis, 613
 characteristic-two, 613
 orthogonal vectors, 613
 First moment, 53
 Fluctuation–dissipation theorem, 335
 Flux density, 79
 Fock state, *see* Photon-number state
 Forward error correction, 619
 Forward–backward algorithm, *see* Bahl algorithm
 Four-dimensional signal constellation, 491
 Four-wave mixing, 205, 225, **228**, 234
 interference, 228
 interchannel, **228**, 553
 intersymbol, 229
 intrachannel, 229
 Fourier series, **45**, 355, 406, 516
 cosine, 104
 Fourier transform, **30**, 38
 convolution property, 31
 differentiation property, 31
 inverse, **30**, 217, 261, 284, 570
 modulation property, 31
 properties, **30**, 99
 scaling property, 30
 sign convention, xxv
 spatial, 30
 temporal, **30**, 125, 162
 Frame (data), 5
 error rate, 6
 synchronization, 573, **588**, 590
 Frame (trellis), **537**, 634
 Fraunhofer diffraction, 402
 Free-space
 impedance, **108**, 140
 permeability, 80
 permittivity, 80
 phase velocity, 86
 wavelength, 84
 wavenumber, **80**, 84, 121, 165, 209
 Frequency, 8
 angular, **8**, 30, 235, 518, 570
 carrier, **12**, 31
 instantaneous, 212
 mixer, **307**, 578
 modulation, 463
 noise, 579
 normalized, **128**, 151, 157
 spatial, **30**, 120
 translation, **3**, 12
 Frequency-shift keying, **468**
 coherent, 469
 noncoherent, 469
 orthogonality condition, 469
 phase noise floor, 520
 Full-rank matrix, **48**, 189, 614
 Function
 Bessel
 first kind, **132**, 134, 406
 identity, 141
 modified, 134
 coherence, **97**
 complementary error, **57**, 437, 456
 concave, 719
 error, **57**, 63, 347

- gamma, **64**, 66, 233, 274
- generalized, 28
- Gordon, *see* Gordon function
- Hermite polynomial, 145, **154**
- Laguerre polynomial, 66
- log-likelihood, **477**, 542, 583
- lorentzian, **345**, 356
- modified Bessel, **62**, 104, 518, 638
- objective, **241**, 530
- pseudocovariance, 268
- radial prolate spheroidal, 280
- rect, 36
- signum, 29
- sinc, 37
- smoothing, 801
- triangular, 72
- unit-step, 29

- Gain
 - homogeneous, 320
 - inhomogeneous, 320
 - internal photodetector, *see* Photodetector, internal gain
 - lightwave amplifier, *see* Lightwave amplifier, gain
 - modulation, 320
 - noise, 307
 - per unit length, 315
 - saturation, 316
 - small-signal per unit length, 316
- Gallager code, 641, **646**
 - check equations, 649
 - codebit, 652
 - irregular, 647
 - posterior probability ratio, 649
 - regular, 647
- Gallager induction, 668
- Galois field, 612, **618**
- Gamma
 - function, **64**, 66, 233, 274
 - probability density function, **65**, 405
 - random variable, 65
- Gaussian
 - noise model, 727
 - probability density function, *see* Probability density function, gaussian
 - pulse, 37
 - generalized, 233
 - quantum-lightwave channel, 871
 - random process, *see* Random process, gaussian
 - random variable, *see* Random variable, gaussian
 - signal state, *see* Signal state, gaussian
- Generalized
 - angle, 826
 - function, 28
 - likelihood function, 583
 - likelihood principle, 583
 - measurement, **787**, 792
 - rotation, **48**, 753, 755, 823
- Generator
 - matrix, **614**, 630
 - systematic, 617
 - polynomial, 630
- Geometric probability mass function, 242
- Geometrical
 - optics, 6, **91**, 119
 - wavefront, 92
- Germanium, 111
- Girth, **627**, 647, 655
- Glauber
 - number, 739, **762**, 768, 791, 802
 - state, **739**, 761
- Gordon distribution, 242, **266**, 292, 681, 697, 803, 804, 838, 873
 - entropy function, **242**
 - variance, 266
- Gordon formula, 22, **714**
- Gordon function, **242**, 683, 696, 716, 863, 873, 877
- Graded-index optical fiber, **110**, 169
 - cladding, 121
 - maximum launch angle, **120**, 150
 - mode, 144
 - mode-dependent group delay, 169
 - numerical aperture, 120
 - ray propagation, 119
 - ray trajectories, 120
- Gradient
 - complex, **596**, 606
 - spatial, 305
- Gradient descent method
 - stochastic, **600**, 603
- Gram matrix, **49**, 825
- Gram–Schmidt procedure, 100
- Graph
 - edge, 627
 - Tanner, **625**, 647
 - trellis, 625
- Gray code, **451**, 477, 515
- Grazing angle, 116
- Group delay
 - figure, 174
 - mode-dependent, **155**, 157, 161, 167, 171, 172, 349, 364, 366, 367
 - mode-group, **168**, 170, 177
 - optimal index profile, 178
 - polarization-dependent, **184**, 185, 368
 - relationship to group-velocity dispersion, 173
 - spread, 167
 - subcarrier, 224
 - wavelength-dependent, 155, 170, **173**, 179, 199, 366, 367
 - weighted average, 176
- Group index, **163**, 170, 192, 195

- Group velocity, **161**, 162
 dispersion coefficient, **161**, 173, 235, 364, 534, 569
 total, **174**, 180
 dispersion compensation, 181
 polarization-dependent, 183
- Guard
 band, 409
 interval, **537**, 591
- Guided mode, *see* Mode, guided
- Hadamard's inequality, 48
- Half-power bandwidth, 74
- Hamiltonian, **762**, 771
- Hamming
 code, 615
 distance, **613**
 minimum, 613, **616**
 sphere, 621
 weight, **613**, 622
- Hard-decision
 decoder, **610**
 decoding, 698
 detection, 18, 608, **610**, 698, 700
- Hardlimiter, 582
- Harmonic oscillator, 202
 classical, 82
 quantum, 761
- Hartley–Shannon theorem, 21
- Heft, **616**, 647
- Heisenberg
 representation, **752**, 792
 uncertainty relationship, 36, **767**
- Helmholtz equation, 80, 84
 cylindrical coordinates, 139
 scalar, **84**, 105, 126, 133
 boundary conditions, 127
 vector, 80, **84**, 121, 126, 138
 boundary conditions, 121
- Hermite polynomial, 145, **154**, 809
- Hermite-gaussian mode, 145
- Hermitian matrix, 47, **49**, 185, 752
- Heterodyne demodulation, 13, 307, **379**, 381
 operator, 793
 including an image mode, 794
 quantum-lightwave, 792
 shot-noise-limited, **385**, 795, 796
- Hilbert
 space, **43**, 752
 transform, **32**, 101
- Hole, 303
- Holevo information, **857**, 862, 881
- Homodyne demodulation, 13, 307, **380**, 383
 detection operator, **791**, 835, 880
 quantum optics
 to complex-baseband, 795
 quantum-lightwave, 790
 shot-noise-limited, 487, 796, 831, 842, 866
 to a complex-baseband waveform, **380**, 574
 to a real-baseband waveform, 380
- Homogeneity, 27
- Homogeneous
 material, 81
 system, 28
- Husimi distribution, 801
- Hybrid mode, **124**, 138, 142
 characteristic equation, 141
 cutoff conditions, 143
- Hypersphere, 491
- Hypothesis testing, 418, **430**
 quantum-optics, 820
 sequential, 633
- Identity
 matrix, 48
 operator, 774
- Image
 frequency, 386
 mode, **308**, 386, 487
 quantum-optics, 794
 vacuum-state operator, 794
- Image rejecting filter, 578
- Impact ionization, 306, 332
- Impairment, **4**, 155
 absorption, 112
 attenuation, 112
 cross-phase modulation, **205**, 226
 interchannel interference, 553
 four-wave mixing, **205**, 228
 interchannel interference, **228**, 553
 intersymbol interference, 229
 group-velocity dispersion, **161**, 235, 569
 interchannel interference, *see* Interference,
 interchannel
 interference, *see* Interference
 nonlinear, 202
 polarization-dependent loss, **189**, 371, 553
 polarization-mode dispersion, 182
 scattering, *see* Scattering
 self-phase modulation, **204**
- Impedance, 85
 free-space, **108**, 140
 material, 210
- Impulse
 Dirac, **28**, 89, 345
 Kronecker, **28**, 41, 89, 278, 498, 777
 sifting property, 28
- Impulse response, 27, **28**, 101
 causal, 73, 74
 channel matrix, 373
 complex-baseband, 40, 364
 estimation, 591

- noncoherent lightwave channel, 393
- passband, 40
- ray optics, 191
- right-sided, 29
- shift-invariant, 28
- symmetric, 561
- time-varying, 28
- In-phase
 - component operator, **761**, 797
 - noise component, 75
 - signal component, **39**, 313
 - signal representation, 761
- Incomplete decoder, 622
- Independent
 - increment, 257
 - random matrix, 375
 - random variable, **55**, 388
 - random vector, 67
- Index of refraction, 80, **83**, 86, 170, 195
 - angularly dependent, 81
 - complex, 165
 - fiber core, 151
 - graded-index fiber, 110
 - group, 163
 - inhomogeneous medium, 91
 - power-law profile, *see* Power-law index profile
 - profile, parabolic, **119**, 145, 153
 - silica glass, 192
 - step-index fiber, 110
 - time-varying, 328
- Inelastic scattering, **114**, 205
- Inequality
 - Hadamard's, 48
 - Schwarz, **43**, 426
 - timewidth–bandwidth, **36**, 767
- Information, 1
 - classical, 679
 - Holevo, **857**, 862, 881
 - mutual, **674**, 690
 - rate, *see* Information rate
 - relationship to entropy, 673
 - side, 726
- Information channel, 18, 361, 363, **410**, 411
 - additive-noise-limited, 688
 - bandlimited, **706**, 710
 - photon-optics, 688
 - binary asymmetric, **436**, 439
 - quantum, **831**, 868
 - binary symmetric, **434**, 439, 456, 701
 - quantum, 831
 - classical, **679**, 707
 - continuous, **18**, 634, 672, 676
 - capacity, 710
 - gaussian, 698
 - memoryless, 634
 - discrete, **18**, 610, 672, 679, 691
 - memoryless, 634, **671**, 679, 848
 - gray box, 691
 - hard-decision, **672**, 698
 - ideal photon, 685
 - bandlimited, 21, **713**
 - Laguerre, 690
 - memoryless, **411**, 610
 - multi-input multi-output, 707
 - probability model, 411
 - quantum-lightwave, **679**
 - additive-noise-limited, **871**, 876
 - block detection, 869
 - ideal, 862
 - phase-insensitive, 876
 - thermal-noise, 876
 - soft-decision, **672**, 698
 - spectral rate efficiency, 718
 - waveform, 18, **672**, 676, 679, 710
 - bandlimited, **676**, 710
 - nonlinear, 671
- Information rate, 2, **11**, 474, 534, 573, 611, 710
 - bandlimited channel, 711
 - function of signal power, 734
 - maximum, **21**, 433, 669
 - relationship to arrival rate, 714
 - relationship to bandwidth, **22**, 715
 - relationship to channel capacity, 669
 - relationship to codeword error rate, 678
 - saturation with bandwidth, 716
 - using photon counting, 693
- Information theory, **18**, 240
 - quantum, 878
- Inhomogeneous material, 81
- Injection current, 323
- Inner code, 609
- Inner product, **42**, 49, 100, 102, 147, 466, 595, 708
 - coherent state, 850
 - pure signal state, 781, **830**, 863
 - signal state, **753**, 830
- Intensity, 9, **87**
 - autocoherence function, 98
 - modulation, 15, **467**
 - approximate forms using \mathcal{Q} , 453
 - binary modulation error rate, 438
 - channel capacity, 701
 - error rate, 453
 - error rate with additive lightwave noise, 504
 - gaussian approximation, 506
 - intersymbol interference, 523
 - multilevel, **447**, 451, 515
 - multiple fiber segments, 321
 - on–off keying, 467
 - shot-noise-limited error rate, 506
 - threshold, 433
 - noise, 346
 - probability density function, **347**, 359

- Interchannel interference, *see* Interference,
 interchannel
- Interference, **4**, 155
 interchannel, **4**, 16, 368, 373, **522**, 556, 568
 cross-phase modulation, 553
 estimation, 555
 four-wave mixing, **228**, 553
 gain modulation, 320
 nonlinear, 16, **205**
 intermodal, 556
 intersymbol, 395, **523**, 569
 equalization, 522
 four-wave mixing, 229
 nonlinear, 229
 postdetection, 531, 533
 power penalty, 515
 predetection, 531
 modal, **392**
 multipath, 302
 nonlinear, 181, 202, **223**, 559, 726
 equalization, 559
- Interferometer
 delay-line, 301
 Mach–Zehnder, 329
- Intermediate frequency, **13**, 308, 379, 577
- Intermodal dispersion, **155**, 163, 169, 176
 electrical channel, 392
 lightwave channel, 366
- Internal gain noise, 331
- Interpolation, 46, **399**
- Interstitial region, **622**, 628
- Intersymbol interference, *see* Interference,
 intersymbol
- Intramodal dispersion, **155**, 169, 173, 194
 electrical channel, 393
 lightwave channel, 367
- Intrinsic
 evidence, 545, **547**, 641, 649, 655
 Berrou code, 645
 Gallager code, 651
 linewidth, **179**, 326, 345
 region, 305
- Inverse
 Fourier transform, **30**, 217, 261, 284, 570
 Poisson transform, **262**, 698
- Ionization
 coefficient, 306
 impact, 306
 ratio, **332**, 359
- Irregular algebraic block code, 647
- Isotropic material, **81**, 91, 203
- Isserlis theorem, 54, 267, **297**
- Jacobian matrix, 103
- Jitter, **349**
- Joint
 detection
 classical, 495
 quantum-lightwave, 846
 estimation, 588
 probability, 413
 probability density function, 54
 signal space, 742
 Jointly orthogonal modulation, **474**, 492
- Jones
 representation of polarization, **94**, 183
 vector, **94**, 108, 186
- Kerr
 nonlinear fiber coefficient, **210**, 235
 nonlinear lightwave channel, **722**
 mimo, 728
 multiplex, 726
 single-carrier, 723
 nonlinearity, **204**, 229, 553
 glass, 208
 optical fiber, 208
- Ket, 48, **751**
- Keying
 antipodal, 466
 quantum coherent-state, 775
 ASK, 467
 BPSK, **466**, 625, 832
 DPSK, 469
 dual-polarization, 491
 FSK, 468
 MSK, 473
 on–off, 467
 OQPSK, 473
 polarization-switched, 492
 PSK, 472
 pulse-position, 689
 QAM, 472
 QPSK, **472**, 483
 offset, 473
 quantum-lightwave
 antipodal, 831
 on–off, 832
 phase shift, 831
- Kramers–Kronig transform, **32**, 83, 102, 165
- Kronecker
 impulse, **28**, 41, 89, 278, 498, 777, 809
 product, **51**, 779, 813
- Lagrange multiplier, 241
- Laguerre
 information channel, 690
 polynomial, **66**, 805
 generalized, 66
 probability mass function, **66**, 277, 444, 690, 805
 random variable, **66**, 276
- Laplace recursion formula, 48

- Laser diode, **326**, 356, 357
 extinction ratio, 327
 Fabry–Pérot resonator, 357
 free spectral range, 357
 intensity noise, **346**, 358, 397
 linewidth
 intrinsic, **326**, 345
 modulated, 569
 modulation response, 327
 phase noise
 power density spectrum, 347
 probability density function, 511
 relaxation oscillation frequency, 328
 spectral width, *see* Intrinsic linewidth
 threshold current, **326**, 356
- Length
 dispersion, **213**, 216, 226, 235, 404, 563
 effective, **213**, 229, 234, 235, 563
 nonlinear, **213**, 230, 235, 563
 walk-off, **213**, **214**, 216, 234
- Letter, **1**, 411
- Lifetime
 charge carrier, 325
 upper-state, **246**, 314, 318
- Light-emitting diode (LED), **323**
 modulation response, 325
 noise statistics, 355
 spectrum, 323
- Lightwave
 coupler, 298
 envelope, 143
 ergodic, 98
 monochromatic, 94, **123**, 143, 739
 noise, *see* Noise
 partially polarized, 94
 power, *see* Power, lightwave
 unpolarized, 94
- Lightwave amplifier, **312**
 Brillouin, 313
 distributed, 322
 doped-fiber, 313, **317**, 325, 396
 gain, 312, **315**
 internal, 316
 saturation, 316
 small-signal, 316
 gain site, 312
 noise, 337
 noise figure, 338
 parametric, 313
 phase-insensitive, **313**, 388, 796, 813
 quantum-noise limit, **336**, 339, 796
 phase-sensitive, 313
 pump, 313
 Raman, 313
 semiconductor, 318
- Lightwave channel, xix, 4, 17, **361**, 361
 impulse response, 393
 intermodal dispersion, 366
 intramodal dispersion, 367
 linear, **110**, 363
 mode-multiplex, 372
 nonlinear, 201
 polarization-multiplex, 370
 quantum, 862
 relationship to electrical channel, 362
 single-input single-output, 363
 space-multiplex, 369
 table of models, 393
 transfer function, 364
- Lightwave field, 143
 complex, 98
 complex envelope, **88**, 144
 random, 68, **97**
 spatially random, **98**, 374
 temporally random, 97
 vacuum state, 249
- Lightwave signal, 8, **364**
 bandlimited, **277**, 294
 direct-photodetected energy, xxv
 expected number of photons, **241**, 348
 mean number of signal photons, 259
 narrowband, 159
 power, 4, 25, **87**, 105
 spectrum, 159
- Lightwave source, **10**, 323, 355
 bandlimited, 325
 coherence properties, 13
 coupling efficiency, 118
 étendue, 117
 for a multimode fiber, 176
 laser diode, *see* Laser diode
 light-emitting diode, *see* Light-emitting diode
 numerical aperture, **118**, 151
 spontaneous emission, 256
- Likelihood
 function, **432**
 generalized, 583
 log, **477**, 542, 583
 ratio, **433**, 461
 log, **433**, 652
- Linear
 causal media, 82
 polarization, *see* Polarization, linear
 polarizer, 301
 shift-invariant filter, 29
 time-invariant system, **33**, 84, 363
- Linearity, 28
- Linearly independent set, **41**, 613, 647
- Linearly polarized mode, **133**
 cutoff condition, 137
 dispersion relationship, 159
- Linewidth, **179**, 569

- intrinsic, **326**, 345
- Local oscillator, 13, 19, 308, **379**, 384, 408, 446, 577
 - controlled, 576
- Log-likelihood
 - function, **477**, 542, 583
 - ratio, **433**, 652
- Loop filter, **577**, 580, 604
- Lorentzian
 - filter, 295
 - function, **345**, 356
 - pulse, **38**, 101
- Low-density parity-check code, *see* Gallager code
- Lowering operator, 771

- Mach–Zehnder interferometer, 329
- Magnetic
 - field, 79
 - complex representation, 84
 - flux density, 79
- Manakov equation, 218
- Manakov–PMD equation, 218
- Marginal probability density function, 54
- Marginalization, 54, 104, **544**, 639, 677, 779
 - block, 546
 - quantum-lightwave product state, 858
- Mark, 1
- Marker detection, 589
- Matched filter, 390, 408, 423, 424, **426**, 854
 - bank, 390, **498**, 542
 - coherent state, 834
 - optical, 421
 - whitened, **427**, 458
- Material
 - anisotropic, **81**, 96
 - centrosymmetric, **203**, 208
 - circular birefringent, **97**, 183
 - crystalline, 114
 - dielectric, **80**, 84, 110, 151, 166, 202
 - dispersion, **155**, 163
 - zero-wavelength, **164**, 180
 - dispersion coefficient, **164**, 175, 180
 - silica glass, 192
 - dispersive, 82
 - homogeneous, 81
 - impedance, 107, 210
 - inhomogeneous, 81
 - isotropic, **81**, 91
 - linear-birefringent, 97
 - noncrystalline, **112**, 114
 - nondispersive, 82
 - polarization, **80**, 148
- Matrix
 - channel, 401, 707, 871
 - commuting, 47, **51**
 - conjugate, 46
 - conjugate transpose, 46
 - covariance, *see* Covariance matrix, 252
 - density, 746, **777**
 - exponentiation, **49**, 102, 772
 - full-rank, **48**, 189, 614
 - Gram, **49**, 825
 - hermitian, 47, **49**, 60, 185, 752, 825
 - identity, 48
 - logarithm, 102
 - nonhermitian, 49
 - nonnegative-definite, **47**, 189, 371, 776, 819, 825
 - normal, **51**, 190
 - outer product, 51
 - polarization-dependent loss, **189**, 371, 553
 - positive-definite, 47, 819
 - product, 47
 - projection, **50**, 753, 783
 - pseudocovariance, **60**, 107
 - rank, 48
 - rank-one, **747**, 782
 - singular-value decomposition, **49**, 190, 554
 - square, 46
 - symmetric, 47, 59
 - trace, *see* Trace
 - transformation, **42**, 50
 - transpose, 46
 - unitary, **48**, 185, 196, 370
- Maximum-distance code, **613**, 620
- Maximum-entropy distribution, **241**, 803
 - continuous energy, 250
 - discrete energy, 242
 - photon-optics, **242**, 684
 - thermal equilibrium, 244
 - wave-optics, 697
 - with a mean constraint, 242
 - without a mean constraint, 292
- Maximum-entropy principle, 240
- Maximum-likelihood
 - decoding, **629**, 639
 - detection, 433
 - sequence detection, 535, 536, **542**
- Maximum-posterior
 - decision rule, 431
 - detection, 433
 - sequence, 544
 - sequence detection, 522, 535, **544**
- Maxwell's equations, 6, **79**
 - complex representation, 84
- Maxwellian
 - probability density function, 188
 - random variable, 65
- Mean, 53
- Mean-squared value
 - frequency, 34
 - timewidth, **34**, 222
- Measurement operator, **742**, 778
- Memoryless

- additive white gaussian noise, 583
- channel, 748
- continuous-time channel, 374
- discrete-time mimo channel, 707
- Kerr channel, 729
- photon-noise-limited channel, 446
- space-time separable channel, 495
- system, 30
- Meridional ray, 116
- Message
 - error rate, **6**, 15, 676
 - passing decoder, 648
- Mimo channel, *see* Multi-input multi-output channel
- Minimal trellis, 631
- Minimum distance, **414**, 435
 - between sequences, 540
 - classical signal vs. quantum-lightwave signal, 842
 - codeword segment, 634
 - for a code, 611
 - for trellis-coded modulation, 658
 - quantum-lightwave coherent state, 842
 - sequence, 541
 - signal constellation, 464
 - four-dimensional, 492
- Minimum Hamming
 - distance, 613, **616**
 - relationship to euclidean distance, 625
 - weight, **613**, 634
- Minimum mean-squared error, 529
 - orthogonality condition, 597
- Minimum phase, 165
- minimum separation, **524**, 567
- Minimum-distance sequence detection, 538
- Minimum-shift keying, 473
- Mixed signal state, 746, **778**, 808, 821, 837, 872
 - representation, 782
- Mixer, *see* Frequency mixer, 576
- Mixing, **313**
 - efficiency, 408
 - four-wave, *see* Four-wave mixing
 - gain, **379**, 382, 385, 578
 - mathematical identity, 307
 - noise–noise, 396
 - signal–carrier, 12
 - signal–local oscillator, 576
 - signal–noise, 337, 362, 396, 403, 435, 453, 460, **507**
 - signal–signal, 201
 - square-law photodetection, 19
 - subchannel–subchannel, 726
- Mobility, 352
- Modal noise, *see* Noise, modal
- Mode, 3, 4, 6, 88, 117, **121**
 - azimuthally symmetric, 141
 - basis, 88
 - confinement factor, 153
 - coupling, **146**, 176, 298
 - random, 375
 - cutoff condition, **130**, 137, 153, 158
 - decay rate in the cladding, **128**, 129, 158
 - delay for a mode-group, **168**, 170, 177
 - dependent group delay, **155**, 157, 167, 171, 172, 349, 366, 367
 - estimation of, 601
 - evanescent, 148
 - even-transverse electric, 128
 - graded-index optical fiber, 144
 - group delay, **161**
 - guided, 88, 111, 121, **123**
 - relationship to ray theory, 130
 - hermite-gaussian, 145
 - hybrid, **124**, 138, 142
 - image, **308**, 386, 487
 - linearly polarized, 133
 - multiplex channel, 16, 369, **372**, 555
 - odd-transverse electric, 128
 - of a linear system, 33
 - orthogonal, 88, **132**, 137, 146, 152
 - orthogonality condition, **89**, 90, 131, 148
 - partition noise, 348
 - power, 180
 - propagation constant, 127
 - radiation, **89**, 131, 146
 - spatial frequency within the core, **128**, 158
 - spatiotemporal, **239**, 244, 250, 739, 761, 769
 - step-index fiber, 132
 - suppression ratio, 348
 - transverse electric (TE), **124**, 151, 189
 - transverse electromagnetic (TEM), **85**, 124
 - transverse magnetic (TM), **124**, 151, 189
 - unguided, 88, **121**, 143, 146, 162
 - well-guided, **130**, 161, 211
- Mode-group, **168**, 173, 369
 - delay, **168**, 170, 177
 - density, 192
 - graded-index fiber, 169
 - index, **168**, 192
 - maximum value, 169
 - uniform distribution, 177
- Modem, **5**, 15, 361, 815
 - quantum, **742**, 815, 848
- Modified Bessel function, **62**, 104, 134, 518, 638
- Modified duobinary code, 663
- Modulation, **3**, 12
 - amplitude, 12
 - antipodal, **466**, 477
 - binary, 463
 - biorthogonal, 499
 - code, **609**, 659
 - coded, xx, 3, 22, 238, **413**, 464, 534, 685, 741
 - direct current, 324
 - frequency, 463, **468**

- index, **198**, 406
- intensity, *see* Intensity modulation
- jointly orthogonal, **474**, 492
- layer, 1
- multisymbol, 463
- on-off, 414
- orthogonal, 466
- phase-synchronous, 12
- quadrature amplitude, 472
- quantum antipodal, **775**, 831
- symmetric, 703
- trellis-coded, 656
- unequal energy, 467
- Modulator, **8**, 361
 - amplitude/phase, 330
 - balanced, 330
 - complex-baseband, **330**, 378
 - dual-polarization, 493
 - electro-absorption, 329
 - electro-optic, 329
 - lightwave-power response, 331
 - phase-asynchronous, 327
 - phase-synchronous, 378
- Modulus, 32
- Moment
 - n th, 53
 - first, 53
- Momentum
 - operator, **765**, 766
 - representation, 765
- Monochromatic
 - field, **80**, 83, 125, 151
 - complex, 125
 - lightwave, 94, **123**, 143, 739
 - plane wave, 93
- Morse code, 15
- Multi-input multi-output channel, 15, **368**, 372, 602
 - capacity, 707
 - continuous-time, 374
 - equalization
 - polarization modes, 553, **600**
 - spatial modes, 601
 - zero-forcing, 554
 - frequency response, 373
 - impulse response, 373
 - mode-multiplex, 372
 - transfer function, 373
- Multi-user detection, **373**, 728
- Multilevel modulation
 - error rate, 447
 - phase, 472
 - quadrature amplitude, 472
- Multimode interference coupler, 301
- Multipath interference, 302
- Multiplex channel, **368**
 - mode-division, **372**, 555
 - polarization-division, 370
 - space-division, **371**, 555
- Multiplexing, 15
 - frequency-division, 16
 - mode-division, 16, 369
 - polarization-division, 16
 - space-division, 15, **369**
 - time-division, 16, **368**
 - wavelength-division, 16, **368**, 568
- Multivariate gaussian probability density function, **57**, 707
- Mutual coherence function, 98
- Mutual information, **674**, 690
 - binary symmetric channel, 731
 - classical channel, 845, 856
 - function of the prior, 693
 - quantum channel, 857
 - Z channel, 693
- Narrowband
 - dispersion, 159
 - field, 87
 - signal, **12**, 44
- Nat, 240
- Nearest neighbor, **414**, 520, 541, 658
- Negative binomial probability mass function, **276**, 295, 325, 444
- Node, **537**, 552, 627
- Noise, 155
 - additive, **19**, 457
 - additive white gaussian, 21, 26, **73**, 279, 287, 385
 - autocorrelation function, 74
 - bandlimited, 75
 - circularly symmetric gaussian, **254**, 334, 481, 573, 748, 872
 - autocorrelation function, 267
 - bandwidth, 271
 - colored, 74
 - complex-baseband
 - autocorrelation function, 76
 - equivalent bandwidth, 77
 - correlated, 105
 - electrical power density spectrum
 - phase-synchronous demodulation, 381
 - energy per mode, 247
 - entropy, **682**, 698, 731
 - equivalent bandwidth, **74**, 461
 - figure, **78**, 461
 - lightwave amplifier, 338
 - segment of an optical fiber, 354
 - gaussian
 - bandlimited, **271**, 274
 - in-phase component, 75
 - lightwave power, 267, **346**
 - power density spectrum, 267
 - probability density function, **347**, 359

- modal, **376**, 402
- mode-partition, 348
- nongaussian, **478**, 530, 723
- nonlinear phase, *see* Nonlinear phase noise
- optical thermal, 256
- passband, *see* Passband, noise
- phase, *see* Phase noise
- phase-insensitive, 253
- photon, 7, 122, **257**
 - power density spectrum, 269
 - probability mass function, 260
- power, 73
 - passband, 77
- power density spectrum, 22
- pseudo-thermal, 256, 334
- quadrature component, 76
- quantum, **248**, 334, 490, 794, 803, 838, 839
- relative intensity, 346
- shot, 9, **239**, 305, 457
 - counting, 386, 486, **758**
- signal-dependent, **4**, 20, 261, 429, 454, 458, 505
- signal-independent, **4**, 19, 448, 457, 458
- signal-spontaneous emission, **337**, 461
- spontaneous emission, **256**, 337
- suppressing filter, **271**, 293, 354, 381, 396, 559
- thermal, 78, **248**, 360, 396, 403, 461
- white, 73, **249**, 271, 424, 528
- Noisy channel coding theorem, **677**
 - quantum optics, 860
- Noncentral chi
 - probability density function, 65
 - random variable, 65
- Noncentral chi-square
 - probability density function
 - N degrees of freedom, **64**, 274, 284
 - characteristic function, 64
 - two degrees of freedom, 340, **347**, 561
 - random variable, 63
- Nonclassical signal state, **741**, 749, 782
- Noncoherent
 - carrier, 6, 12, 25, 172, **387**, 392, 393, 467, 556, 566
 - direct photodetection, 387
 - wavelength autocorrelation function, 179
 - signal state, 783
- Noncoherent demodulation, **500**, 512
- Noncrystalline material, 112
- Nondispersive material, 82
- Nongaussian
 - noise, **478**, 530, 723
 - random process, 279
- Nonlinear
 - channel, *see* Channel, nonlinear
 - distortion, 4, 202, **216**, 226
 - fiber coefficient, 340
 - index coefficient, 210
 - interference, 16, 181, 202, **223**, 559
 - interchannel, 205
 - interchannel cross-phase modulation, 553
 - interchannel four-wave mixing, **228**, 553
 - intersymbol, 229
 - length, **213**, 230, 235, 563
 - lightwave propagation, 210
 - governing equation, 217
 - nondispersive channel, 219
 - numerical methods, 229
 - vector channel, 218
 - weakly dispersive channel, 222
 - phase estimation, 463
 - phase modulation
 - cross, 205, 553
 - self, 204
 - phase noise, 222, **339**, 341, 723
 - probability density function, 340
 - variance, 341
 - phase shift, **212**, 220, 234
- Nonlinear Schrödinger equation, **217**, 553, 723
 - multichannel, 223
 - numerical solution, **229**, 727
 - traveling timeframe, 218
 - vector channel, 218
- Nonlinearity
 - Brillouin scattering, 206
 - stimulated, **207**, 313
 - Kerr, **204**, 229, 553
 - glass, 208
 - optical fiber, 208
 - Raman scattering, 205
 - stimulated, **206**, 313
- Nonnegative-definite matrix, *see* Matrix, nonnegative-definite
- Nonorthogonal
 - signal, **499**, 818
 - signal state, **774**, 778, 786, 824, 840
 - waveform, 391
- Normal dispersion regime, 161
- Normal matrix, **51**, 190
- Normal ordering, 763
- Normalized
 - dispersion relationship, 158, 159
 - frequency, **128**, 151, 152, 157
 - index difference, **117**, 121, 129, 132
 - mode-group index, **170**, 176, 181
 - propagation constant, 157
- Nuemark extension, 789
- Numerical aperture, **116**, 129, 150, 376
 - graded-index optical fiber, **117**, 120
 - step-index fiber, 117
- Nyquist
 - pulse, 229, 388, **399**, 416, 455, 465, 526, 566, 585
 - joint, 466, **469**
 - joint property, 474

- rate, 46
- Nyquist–Shannon sampling theorem, **45**, 399, 672
- Objective function, **241**, 530
 - augmented, 241
 - constant-modulus, 598
 - mean-squared error, 596
- Observable
 - operator, 742, **752**, 755, 762, 782
 - matrix representation, 751
 - property, 754
- Offset QPSK (OQPSK), 473
- Operator, 751
 - annihilation, 770
 - coherent-state, **762**, 789
 - commuting, **758**, 792
 - convolution, 56
 - creation, 770
 - density, 746
 - detection, 816, *see* Detection operator
 - determinant, 48
 - differential, self-adjoint, 88
 - displacement, **772**, 836
 - generalized measurement, 787
 - Hamiltonian, **762**, 771
 - heterodyne demodulation, 793
 - including an image mode, 794
 - identity, 774
 - image mode vacuum-state, 794
 - in-phase component, **761**, 797
 - lowering, 771
 - measurement, **742**, 778
 - momentum, **765**, 766
 - noncommuting, 792
 - observable, 742, **752**, 755, 762, 782
 - matrix representation, 751
 - photon-number state, 754, 762, **764**, 790
 - position, **765**, 766
 - projection, **753**, 777, 778, 789
 - quadrature component, **761**, 797
 - raising, **770**, 772
 - self-adjoint, **752**, 768
 - trace, **47**, 777, 829
- Optic axis, **97**
 - fast, **97**, 183
 - slow, **97**, 183, 187
- Optical
 - cavity, 323
 - coupler, 313
 - electrical conversion, **8**, 310, 362
 - filter, 302
 - isolator, 302
 - pump, 256, **313**
 - signal-to-interference ratio (OSIR), **552**, 727
 - signal-to-noise ratio (OSNR), **75**, 108, 268, 341, 343
 - relationship to SNR, 268
 - signal-to-noise-plus-interference ratio (OSNIR), **552**, 553, 571
 - thermal noise, *see* Noise, optical thermal
- Optical fiber, **110**
 - absorption, 112
 - attenuation, **112**, 114
 - birefringence, **183**, 185
 - intensity-dependent, 218
 - characteristic equation
 - hybrid mode, 141
 - cladding, **110**
 - core, 110
 - cutoff condition
 - hybrid mode, 143
 - linearly polarized mode, 137
 - dispersion-controlled, **180**, 229
 - dispersion relationship, 170
 - effective area, 211
 - effective length, 213
 - equalization, 181
 - few-mode, 369, **372**, 601
 - graded-index, *see* Graded-index optical fiber
 - intermodal dispersion, 366
 - intramodal dispersion, 366
 - mode, power, 180
 - mode-confinement factor, 153
 - mode-group, **168**, 173
 - density, 192
 - mode-group index, **168**, 192
 - multimode, **111**, 119, 155, 169, 194, 365
 - impulse response per mode, 365
 - mode-dependent group delay, 175
 - nonlinear propagation
 - governing equation, 217
 - nondispersive channel, 219
 - numerical methods, 229
 - vector channel, 218
 - weakly dispersive channel, 222
 - parabolic index of refraction, 119
 - segment, **4**, 321
 - single-mode, **111**, 137, 151
 - attenuation, 11
 - complex-baseband transfer function, 364
 - dispersion, **173**, 194
 - impulse response, 364
 - nonlinear coefficient, 210
 - span, **4**
 - step-index, *see* Step-index optical fiber
 - transfer function
 - complex-baseband, 406
 - weakly guiding, 133
- Optical-matched filter, 421
- Orthogonal
 - quantum signal states, 745, **747**, 777, 823, 860, 879

- signals, 44, 390, 391, 425, **469**, 498, 879
 - classical vs. quantum-optics, 774
 - equal-energy, 501
 - error rate, 476
 - noncoherent, 501
 - waveforms, 469
- Orthogonality condition
 - frequency-shift keying, 469
 - minimum mean-squared error, 597
 - mode, **89**, 90, 131, 148
- Orthonormal
 - basis, **41**, 50, 88, 100, 277
 - basis states, 759
- OSNR, *see* Optical signal-to-noise ratio
- Outer code, **609**, 612
- Outer product, **43**, 47, 759, 777
 - basis functions, 759
 - matrix, 51
 - orthonormal basis vector, 50
- P* distribution, **797**, 802
 - classical signal in noise, 798
- Parabolic index profile, **119**, 153
- Parallel concatenation, 642
- Parametric amplification, 313
- Paraxial approximation, **92**, 120
- Pareto
 - index, 54
 - probability density function, 106, 634
 - random variable, *see* Random variable, Pareto
- Parseval's relationship, **31**, 44, 70, 73
- Partial-fraction expansion, 296
- Partial-response
 - code, 534, **663**
 - decision-feedback demodulation, 419
 - dicode, **419**, 663
 - duobinary, **418**, 663
 - maximum-likelihood demodulation, 664
 - maximum-likelihood detection, 419
 - pulse, 418
- Partial trace, **779**, 812, 858
- Partially coherent carrier, 13, 388, 470, **556**, 569
- Passband
 - impulse response, 40
 - noise, 75
 - bandwidth, 271
 - power density spectrum, 76
 - probability density function, 250
 - noise-equivalent bandwidth, 74, 77
 - noise process, 75
 - signal, 3, 12, **39**
 - energy, 44
 - envelope, 162
 - waveform, **3**, 710
- Path metric, **539**, 542
 - summed, 540
- Permeability, 80
- Permittivity, **80**, 82
- Phase
 - ambiguity, 583
 - asynchronous demodulation, 14, **500**
 - comparator, 576
 - estimation, *see* Estimation, phase
 - insensitive
 - channel, **253**, 799, 871
 - lightwave amplifier, **313**, 388
 - noise, 253
 - matching, **149**, 203, 233
 - mismatch, 228
 - modulation, *see* Modulation, phase
 - probability density function, 104
 - reference, 13
 - synchronous demodulation, 379
 - heterodyne, 381
 - velocity, **86**, 92, 161, 162
 - polarization-dependent, 184
- Phase-locked loop, **576**
 - acquisition step, 577
 - Costas, 582
 - damping coefficient, 580
 - first-order, 578, **580**
 - loop filter, **577**, 580, 604
 - natural frequency, 580
 - nonlinear analysis, 605
 - second-order, **580**, 604
 - tracking step, 577
 - transfer function, 579
 - first-order, 604
 - second-order, 604
 - transfer function for phase error, 604
- Phase noise, 14, **484**, 574
 - laser diode probability density function, 511
 - nonlinear, **339**, 502
 - nonlinear probability density function, 340
 - probability density function, 63
- Phase-shift keying, **472**
 - binary, 466
 - error rate
 - heterodyne BPSK, 487
 - homodyne binary phase-shift keying, 487
 - multilevel, 472
 - QPSK, 483
 - offset, 473
- Phase space, 739, 774
- Photocharge, xxvi, **259**, 382
- Photocurrent, xxvi, **9**, 259, 352
- Photodetected
 - lightwave energy, xxv
 - lightwave power, xxvi
- Photodetection, **8**, 238
 - balanced, *see* Balanced photodetection
 - direct, *see* Direct photodetection

- event, **257**, 305
- square-law, *see* Square-law photodetection
- Photodetector, **8**
 - avalanche photodiode, 306
 - dark current, **312**, 331
 - internal gain, 290, 306, 331
 - expected value, 359
 - PIN photodiode, 305
 - polarization-insensitive, 396
 - responsivity, 9
 - square-law, **100**, 108, 249
- Photodiode, 304
 - avalanche, 304
 - PIN, **305**, 352
- Photoelectron, xxvi, **257**
 - arrival process, **258**, 285, 294
 - arrival rate, xxvi, **258**, 270, 692
 - constant, 331, 519
 - counting process, **258**, 312
 - mean number, **259**
 - primary, **257**, 288, 311, 331
 - secondary, **257**, 288, 291
- Photon, **7**, 205
 - arrival process, 237, **257**, 311
 - arrival rate, 9, 122, **257**, 309, 311, 401, 421, 440, 685
 - time-varying, 257
 - counting process, 312
 - mean number, **241**, 348
 - in a coherence interval, 352
 - per bit, **503**, 514, 690, 775, 831
 - per pulse, 440, 451
 - noise-limited channel, **265**, 402
 - number, **239**, 311, 737
 - probability mass function, 338
 - energy, xxv, **8**
 - lifetime, 326
 - momentum, 8
 - noise, *see* Noise, photon
- Photon counting, **257**, 402, 456, 689
 - binary, 440
 - classical, 832
 - conventional, **831**, 836
 - multilevel, 451
 - random process, 257
 - threshold, 402
 - with a matched local oscillator, 832
 - with noise photons, 441
- Photon optics, **6**
 - bandlimited capacity, 21, **713**
 - narrowband, 714
 - description of shot noise, 309
 - detection, **422**, 428
 - discrete-energy property, 422
 - discrete-time channel, 401
 - memoryless, **682**, 692
 - photon noise, 237, **257**
 - relationship to quantum optics, 736, **773**
 - relationship to wave optics, **250**, 259
 - signal model, **7**, 237, 246, 737
 - signal propagation, 122
 - single-letter capacity, 244, **680**
 - spectral-rate efficiency, 719
 - treatment of photodetection, 238
- Photon-number state, **741**
 - basis, 764
 - operator, 754, 762, **764**, 790
 - representation, **741**, 838
 - of a classical state, 802
 - of a coherent state, 741, **773**
 - of additive noise, 803
 - with zero photons, 771
- Physical
 - channel, 4, **17**, 361
 - layer, **1**, 15
- Pilot signal, 574
- PIN photodiode, **305**, 352
- Planck's constant, 8
 - reduced, 8
- Plane wave, **85**, 107
 - in slab waveguide, **130**, 196
 - monochromatic, 93
- Poincaré sphere, **95**, 186, 188, 370, 601
 - latitude, 95
 - longitude, 95
 - transition along, **96**, 601
- Point process, 122, 331, **439**, 740
 - maximum entropy, 439
- Poisson
 - channel, 265, 311, **401**, 692
 - counting process, 9, **257**, 260, 312
 - probability mass function, **260**, 773
 - mixed, 262
 - summation formula, 37
 - transform, 239, **262**, 684, 737, 799
 - Dirac impulse, 265
 - exponential probability density function, 265
 - gamma probability density function, 275
 - inverse, **262**, 698
 - noncentral chi-square probability density function, 690
 - relationship to Gordon distribution, 266
- Polarization (field), 3, 80, **93**, 368
 - alignment, 495, 553, **600**
 - axes, 190
 - beam splitter, **301**, 493, 744
 - circular, 94
 - combiner, 301
 - cross modulation, 218
 - decorrelation length, **187**, 218
 - dependent group delay, **184**, 368
 - dependent group velocity, 183

- dependent loss, **189**, 199, 371, 553
- ellipse, 108
- elliptical, 93
- Jones representation, **94**, 183
- linear, **94**, 183
- mode dispersion, 94, 97, 155, **182**
 - first-order, 199
 - governing equation, 184
 - Jones representation, 183
 - linear-birefringent material, 185
 - second-order, 183
 - Stokes representation, 186
 - vector, **186**, 196
- modulation, 493
- multiplex channel, 16, 370, **491**
- optic axis
 - fast, **97**, 183
 - slow, **97**, 183, 187
- orthogonal, 96
- principal axes, 97, **183**, 185, 190
- principal states, **183**, 188
 - basis, 370
 - interference, 190
- sign convention, xxv
- slab waveguide, 130
- state estimation, 553, **600**, 606
- Stokes representation, **94**, 186
- Polarization (material), 80
 - nonlinear, 203, **208**
- Polarizer, linear, 301
- Position
 - operator, **765**, 766
 - representation, 765
 - vector, 85
- Positive-operator-valued measure, 788
- Posterior probability, 55, **412**, 544, 547
 - component maximum, 544
 - componentwise maximum, 544
 - density function, 432
 - marginal, 545
 - ratio, **432**, 461, 547, 643
 - Gallager code, 649
 - senseword, 649
 - sequence maximum, 544
- Potential, 304
- Power
 - baseband signal, 11
 - effective bandwidth, **70**, 293
 - lightwave, 4, 25, **87**, 105
 - autocorrelation function, 98
 - photodetected, xxvi, **4**
 - penalty, 607
 - discrete lightwave amplifier, 322
 - intersymbol interference, 515
 - reactive, 131
 - splitter, **301**, 386
- Power density spectrum, **69**, 105, 267, 269
 - arrival rate, 269
 - complex-baseband noise, 76
 - constant signal plus noise, 268
 - direct-photodetected electrical signal, **271**, 395
 - electrical
 - per unit resistance, xxvi, 73
 - phase-synchronous demodulation, 381
 - relative intensity noise, 346
 - shot noise, 385
 - filtered electrical signal, 287
 - filtered shot noise, 287
 - lightwave noise power, 267
 - lightwave signal, 70
 - noise, 22, **247**
 - one-sided, 69
 - passband noise, 76
 - quantum noise, 248
 - random binary waveform, 72
 - spontaneous emission, 257, **336**
 - direct-photodetected, **xxvi**, 561
 - lightwave power, 267
 - thermal noise, 250
 - two-sided, **69**, 279, 293
 - noise, 73
 - wavelength, 70
- Power-law index profile, **145**, 169, 171, 192
 - parameter, **145**, 169, 176, 182
 - optimal, **177**, 182, 196
- Poynting vector, 86
 - complex, 87
- Pre-equalization, **525**, 534
- Prefilter, 534
- Primary photoelectron, **257**, 288, 311, 331
- Primitive element, 620
- Principal
 - axis, 81
 - polarization axes, 97, **183**, 185, 190
 - polarization states, **183**, 188
 - basis, 370
 - interference, 190
- Principle of stationary phase, 367
- Prior probability, 18, 237, **412**, 436, 672, 681
 - Berrou decoder, 644
 - capacity-achieving, 673
 - equiprobable, **433**, 699
 - ratio, 548
 - unequal, 461
- Probability density function, **53**
 - bivariate, **54**, 295
 - gaussian, **58**, 104, 251, 253
 - maximum-entropy, 252
 - Boltzmann, **250**, 293
 - central chi, **65**
 - central chi-square, **63**, 372, 376, 731
 - two degrees of freedom, 273

- complex gaussian, 60
 - circularly symmetric, 60
- complex-baseband noise, 250
- conditional, **54**, 413, 431
- exponential, 64, **65**, 103, 250, 273, 376, 702
- first-order, 68
- gamma, **65**, 376, 405
- gaussian, **57**
 - bivariate, 253
 - circularly symmetric, **58**, 78, 254, 872
 - multivariate, 57, **60**, 707
 - spherically symmetric, 188
- inverse gaussian, 360
- joint, 54
- marginal, 54
- maxwellian, **65**, 188, 200
- noncentral chi, 65
- noncentral chi-square, **63**, 105, 340, 347, 360, 561, 805
 - two degrees of freedom, **63**, 255, 273
- Pareto, **54**, 106, 634, 636
- passband noise, 250
- phase, 63, 104
- posterior, **432**
 - ratio, 461
- prior, *see* Prior probability
- Rayleigh, **61**, 62, 65, 103, 254, 273
- ricean, **61**, 62, 103, 273, 502, 507, 509, 724
- second-order, 68
- table of, for noise processes, 283
- Probability distribution function, 53
 - posterior, 412
 - prior, 412
 - table for wave-optics and photon optics, 284
- Probability mass function, **53**
 - binomial, 260
 - Bose–Einstein, **244**, 293
 - geometric, 242
 - Gordon, *see* Gordon distribution
 - inverse gaussian, 332
 - Laguerre, **66**, 277, 444, 690, 805
 - maximum entropy, 241
 - negative binomial, 295
 - Poisson, **260**, 325, 773
- Product
 - channel, **706**
 - capacity, 706
 - mimo, 707
 - distribution, **55**, 253, 254, 554, 682, 742, 848
 - bandlimited gaussian random process, **278**, 706
 - gaussian, **59**, 253
 - mimo channel, 707
 - output posterior, 643
 - subblock, 678
 - state, 742, **760**
 - density matrix, **779**, 786, 857
 - expectation, 791
 - generation with a coupler, 790
- Projection, **43**, 100
 - matrix, **50**, 753, 783
 - operator, **753**, 777, 789
- Propagation
 - constant, **85**, 124, 157
 - along optic axes, 184
 - frequency-dependent, 157
 - mode, 127
 - mode-dependent, 157
 - normalized, 157
 - vector, **85**
- Pseudocovariance
 - function, 268
 - matrix, **60**, 107
- Pseudorandom sequence, **516**, 594
- Pseudothermal noise, 256
- Pulse, **3**
 - amplitude modulation, **463**, 517
 - multilevel, 464, **471**
 - multilevel error rate, 477
 - chirp, 38
 - electrical, xxvii
 - gaussian, 37, 100
 - generalized, 233
 - lorentzian, **38**, 101
 - non-return-to-zero, 467
 - inverse, 468
 - Nyquist, 229, 388, **399**, 416, 455, 465, 526, 566, 585
 - joint, 469
 - joint property, 474
 - partial-response, 418
 - position modulation, 689
 - quadratic phase, 38
 - raised-cosine, 468
 - rectangular, 36
 - sinc, 37
 - symmetric, 532
 - target, xxvii, **416**, 465, 525
 - transmit, 415
 - triangular, 101
- Puncturing, 643
- Pure signal state, **746**, 760, 776, 778
 - binary modulation error rate, 830
 - coherent
 - density matrix, 802
 - density matrix, 811
 - representation, 782
 - von Neumann entropy, 785
- Q, **438**
 - for an avalanche photodiode, 515
 - for intensity modulation, 453
 - for multiple fiber amplifiers, 462

- Quadratic-phase function, 367
- Quadrature
- component operator, **761**, 797
 - noise component, 76
 - signal component, **39**, 313
 - signal representation, 761, 762
- Quadrature phase-shift keying, **472**, 483
- offset, 473
- Quadrature-amplitude modulation, **464**, 472
- Quanta, 203
- Quantization, 1
- Quantum
- coherence, 7, **782**, 784, 805
 - correlation, 7
 - decoherence, 783
 - efficiency, xxvi, 258, **305**, 338
 - entropy, *see* von Neumann entropy
 - expectation, **754**, 777
 - information theory, 878
 - noise, *see* Noise, quantum, 249
 - noise regime, 249
 - phase, **782**, 805
 - state, 750
 - uncertainty, 7, 262, 683, 685, **743**, 776, 820, 824
- Quantum optics, **6**
- channel capacity, 843
 - heterodyne demodulation, 792
 - homodyne demodulation, 790
 - information channel, 843
 - modulation
 - antipodal, **775**, 831, 832
 - on-off keying, 832
 - using coherent states, 831
 - signal model, **6**, 7, 246, 446, 736
 - statistical, 743, **776**
- Quantum wave function, 738, 745, **753**, 765
- continuous, 755
 - in-phase component, 761
 - in-phase representation, 765
 - momentum representation, 765
 - position representation, 765
 - quadrature component representation, 762
 - quadrature representation, 765
- Quarter-square multiplier, 308
- Quasi-linear approximation, 723
- Quasi-probability distribution, 773, **797**
- P distribution, **797**, 802
 - Husimi, 801
 - Wigner, **799**, 802, 805
 - gaussian state, 806
- Radial prolate spheroidal function, 280
- Radiation mode, **89**, 131, 146
- Radiative-recombination lifetime, **319**, 325
- Raised-cosine pulse, 468
- Raising operator, **770**, 772
- Raman scattering, 205
- stimulated, 313
- Random process, 52, **67**
- bandlimited, 251
 - circularly symmetric gaussian, **78**, 254, 343, 574
 - bandlimited, **277**, 283
 - complex-baseband noise, 75
 - ergodic, 69
 - gaussian, **68**
 - bandlimited, **239**, 273, 280, 284
 - circularly symmetric, **255**
 - decorrelated, 278
 - product distribution, **278**, 706
 - independent increment property, 257
 - nongaussian, 279
 - notation, xxv
 - passband, 252
 - photon counting, 9, **257**, 260, 312
 - spatiotemporal, 284
 - stationary
 - strict sense, 68
 - wide sense, 68
 - Wiener, 343
- Random telegraph signal, 70
- Random variable, **52**
- n th moment, 53
 - additivity property, **253**, 261
 - bivariate gaussian, **58**, 255
 - central chi, 65
 - central chi-square, 63
 - complex, 53
 - complex gaussian, 60
 - correlation, 55
 - expectation, 53
 - exponential, 65
 - first moment, 53
 - gamma, 65
 - gaussian, 57
 - bivariate, **58**, 251, 255
 - circularly symmetric, **58**, 78, 281
 - multivariate, **57**, 284
 - spherically symmetric, 188
 - uncorrelated, 59
 - independent, 55
 - Laguerre, **66**, 276
 - maxwellian, 65
 - mean, 53
 - noncentral chi, 65
 - noncentral chi-square, 63
 - notation, xxv
 - Pareto, 666
 - phase, 511
 - Poisson, 260
 - Rayleigh, **62**, 391, 507
 - realization, **53**, 239
 - ricean, **62**, 391, 507

- root-mean-squared value, 54
 - uncorrelated, 56
 - uniform, 70
 - variance, 54
- Random vector
 - complex gaussian, 60
- Random walk, 343
- Rate
 - code, *see* Code, rate
 - information, *see* Information rate
- Rate equations, **317**, 328
- Ray, **92**
 - meridional, **116**, 120
 - skew, 116
 - tracing, 91
 - trajectory, **92**, 120, 150
 - transit time, **156**
 - impulse response, 191
 - unguided, 117
- Ray optics, **6**, 110
 - dispersion, 156
 - governing equation, **92**, 105
- Rayleigh
 - probability density function, **61**, 62, 103, 254, 273
 - random variable, **62**, 391, 507
 - scattering, **114**, 166, 193, 205
- Reach, **4**, 21
- Reactive power, 131
- Real-baseband
 - signal, **11**, 77, 307, 362, 383, 386, 489, 694
 - waveform, **310**, 380, 411, 581
- Realization
 - channel, 709
 - random variable, **53**, 239
 - sample function, 52
- Receiver
 - displacement, 835, 880
 - frequency response, 287
 - impulse response, 292
 - lightwave, 304
 - phase-asynchronous, **14**, 463, 500
 - phase-sensitive, 790
 - phase-synchronous, **13**, 524
 - photon-counting, **311**, 440, 456
 - multilevel, 451
 - polarization-sensitive, 368
 - quantum-lightwave, 837
 - sensitivity, 11, 25
 - suboptimal, 561
- Recode-and-forward, 5
- Reconfigurable add-drop multiplexer, 552
- Rectangular pulse, 36
- Rectifier, 14
- Red-shift, **213**, 404
- Reduced Planck's constant, 8
- Reed-Solomon code, 619
 - primitive, 620
 - primitive element, 620
- Reflection, 115
 - law of, 115
- Refraction, 115
 - law of, 115
- Regeneration, 5
- Regular
 - algebraic block code, 647
 - check matrix, **617**, 646
- Relative intensity noise (RIN), **346**, 358, 397
 - shot-noise limit, **346**, 359
- Relative permittivity, 82
- Relaxation oscillation frequency, **328**, 359, 397
- Remodulate-and-forward, 5
- Representation
 - Dirac, 752
 - Heisenberg, **752**, 792
 - in-phase component, 765
 - in-phase signal component representation, 761
 - interaction, 752
 - momentum, 765
 - position, 765
 - quadrature component, 765
 - quadrature signal component, 761, 762
 - Schrödinger, 752
- Resonator, 323
 - Fabry-Pérot, 357
 - free spectral range, 357
 - laser diode, 326
 - mode structure, 327
 - photon lifetime, 326
- Responsivity, xxvi, **9**, 259, 305
- Reverse channel, 529
- Ricean probability density function, **61**, 62, 103, 273, 502, 507, 509, 724
- Ricean random variable, **62**, 391, 507
- RIN, *see* Relative intensity noise
- ROADM, *see* Reconfigurable add-drop multiplexer
- Robust, **427**, 519, 609
- Root-mean-squared
 - bandwidth, **34**, 100
 - position, 767
 - timewidth, **34**, 100
- Root-mean-squared amplitude, xxv, **39**, 54, 324
- Rotation
 - generalized, **48**, 753, 755
 - joint probability distribution, 107
 - polarization axes, **187**, 369
 - signal constellation, 576
- Runlength-limited code, 660
- Sample, 1, **45**, 399
 - complex, 390
 - function, **52**, 68
 - instantaneous, 420

- Sampling, 1
 basis, symmetric, 830
 eigenstate, **821**, 836, 879
 rate, **46**, 235, 281, 692
 theorem, 18, 44, **45**, 281, 399, 672
- Saturation power, 317
- Scalar, 28
- Scalar Helmholtz equation, **84**, 126
 boundary conditions, 127
- Scattering, 113
 anti-Stokes, 205
 Brillouin, **206**
 stimulated, **207**, 663
 cross section, 114
 direction-dependence, 114
 elastic, 114
 inelastic, **114**, 205
 linear, 113
 Raman, **205**
 stimulated, 206
 Rayleigh, **114**, 166, 205
 Stokes, 205
- Schrödinger representation, 752
- Schur–Horn theorem, 785
- Schwarz inequality, **43**, 426
- Second law of thermodynamics, 243
- Self-adjoint
 differential operator, 88
 operator, **752**, 768
 transformation, **49**, 742, 752
- Self-phase modulation, **204**, 219, 223, 224
- Sellmeier formula, 192
- Semiclassical signal model, **7**, 680, 748, 815
- Semiconductor, 304
 bandgap, **303**, 319
 conduction band, **303**, 315
 diode, 323
 electron–hole recombination, 313
 intrinsic, 305
 -laser diode, *see* Laser diode
 lightwave amplifier, *see* Lightwave amplifier
 radiative recombination time, 319
 valence band, **303**, 315
- Sensebit, 649
- Senseword, 5, **610**, 626
 corrupted, 621
 hard-valued, 5, **610**
 memoryless, 418
 pictorial representation, 621
 soft-valued, 5, **610**
 symbol, 412
 uncorrectable, 622
- Separation of variables, **126**, 133, 139, 145, 151
- Sequence detection, 522, **535**
 constraint length, 537
 error rate, 540
 maximum-likelihood, 535, **542**
 maximum-posterior, 522, **544**
 minimum-distance, 538
 trellis, 537
- Sequential
 decoding, 629, **633**
 complexity, 639
 hypothesis testing, 633
- Shannon
 bound
 bandlimited channel, 21, **711**
 single-letter capacity, **697**, 699
 spectral rate efficiency, 22, **719**
 entropy, 673, **785**
 first coding theorem, 676
 second coding theorem, 677
- Shaping, gain, **472**, 699
- Shift-invariant system, 28
- Shot noise, *see* Noise, shot
- Shot-noise-limited
 error rate, 487
 heterodyne demodulation, **385**, 795, 796
 homodyne demodulation, 487, 796, 831, 842, 866
 relative intensity noise, 346, 359
 system, **286**, 346, 359, 429, 455, 457, 559, 767
- Side information, 726
- Sideband, 205
- Sifting property of an impulse, **28**, 345
- Signal, 27, **41**
 analytic, **32**, 101
 bandlimited, 12, 24, **34**
 baseband, **3**, 12, 24
 complex envelope, 39, **144**, 162, 361
 spectrum, 364
 vector, 218
 complex-baseband, 12, **39**, 53, 77, 101, 307, 362,
 383
 conjugate symmetric, 32, **269**
 dual-polarization, 493
 envelope, **12**, 14
 passband, 162
 impairment, *see* Impairment
 lightwave, *see* Lightwave signal
 narrowband, **12**, 44
 noise, *see* Noise
 nonorthogonal, *see* Nonorthogonal signal
 orthogonal, *see* Orthogonal signal
 passband, 3, 12, **39**
 periodic, 12
 polarization-multiplex, 491
 quantum-lightwave, 7
 real-baseband, **11**, 77, 307, 362, 383, 386, 489,
 694
 rectified, 14
 regeneration, 5
 right-sided, 29

- spectrum, 30
- square-integrable, 30
- timewidth-limited, 34
- vector, **42**, 788, 881
 - basis, 100
 - euclidean distance, 44
 - waveform, 3
- Signal constellation, **414**, 480
 - antipodal, **414**, 466
 - complex, 464
 - four-dimensional, 491
 - matrix, **497**, 818, 851
 - quantum, **825**, 832
 - on-off intensity modulation, **414**, 467
 - phase-shift modulation
 - binary, 466
 - eight-level, 472
 - multilevel, 472
 - pulse-amplitude modulation, 471
 - quadrature-amplitude modulation, **464**, 497
 - nonsquare, 472
 - quantum-lightwave, **780**
 - average state, **780**, 788, 847
 - coherent-state components, 819
 - nonorthogonal components, 815
 - pure-state components, **826**, 844
 - symmetric, 840
 - real, 414
 - signal space, 496
- Signal model, **6**
 - geometrical-optics, **6**, 119
 - photon-optics, **7**, 11, 237, 246, 737
 - relationship to quantum optics, 736
 - quantum-optics, xxv, **6**, 7, 246, 446, 736
 - ray-optics, **6**, 110
 - semiclassical, **7**, 680, 748, 815
 - wave-optics, xxv, **6**, 20, 83, 115, 122, 239, 361, 737
 - relationship to quantum optics, 741
- Signal space, **41**
 - basis, **41**, 759
 - composite, 742, **759**
 - definition of distance, 44
 - for a classical signal constellation, 496
 - for a quantum-lightwave signal constellation, 742
 - generalized measurement, 789
 - higher-dimensional, 536
 - Hilbert, 752
 - infinite-dimensional, 736
- Signal state, 736, **738**, 750
 - block-symbol, 742, 778, 815, 819, **846**, 848
 - entangled state, 781
 - product state, 781, 819
 - cat, 833
 - classical, 741, 800
 - coherent, *see* Coherent state, 762
 - component-symbol, 742, **759**, 776, 778, 780, 815, 819, 844, 846, 869
 - marginalization to, 858
 - composite, **742**, 813
 - detection, 738, 739, **747**, 815, 816, 818, 820, 843
 - block-symbol, 846
 - coherent-state, 789
 - component-symbol state, 845
 - entangled, **760**, 811, 819, 861
 - Fock, *see* Photon-number state
 - gaussian, 748, 800, **806**
 - circularly symmetric, 748, 749, **806**, 807, 873
 - Glauber, **739**, 761
 - image quantum-optics, 794
 - measurement, **742**, 776
 - mixed, *see* Mixed signal state, **778**, 837
 - nonclassical, **741**, 749, 782
 - noncoherent, 783
 - nongaussian, **749**, 800
 - nonorthogonal, 774, 778, 786, 824, 840
 - orthogonal, 745, **747**, 777, 823, 860, 879
 - photon-number, *see* Photon-number state
 - preparation, 738, **741**, 815, 843
 - product, *see* Product state
 - pure, *see* Pure signal state, 760, 776, 778
 - sampling, 823, 834
 - symmetric, 840
 - vacuum, *see* Vacuum state
- Signal state, detection, 738
- Signal-spontaneous emission noise, **337**, 461
- Signal-to-noise ratio, 21, 22, 26, **75**, 108
 - electrical (SNR), **75**, 108, 343
 - optical (OSNR), **75**, 108, 268, 341, 343
 - relationship between SNR and OSNR, 339
- sample, 420, 424, **426**, 435
 - effective, 424, **438**
 - matched filter, **426**, 435
- Sigum function, 29
- Silica glass, 83, **111**, 112, 166, 203, 210
 - material dispersion curve, 164
- Sinc pulse, 37
- Single
 - input single-output channel, 363
 - letter channel capacity, *see* Channel capacity, single-letter
 - mode optical fiber, *see* Optical fiber
 - user detection, **373**, 726
- Singular value, **49**, 554, 555
- Singular-value decomposition, **49**, 190, 554
- Skew ray, 116
- Slab waveguide, 125
 - dispersion, 157
 - power density, 130
 - TE characteristic equation, 128
 - TE mode pattern, 131
 - TM characteristic equation, 129

- Slow optic axis, **97**, 183
 Smoothing function, 801
 Snell's law, 115
 SNR, *see* Signal-to-noise ratio
 Soft-decision
 decoder, **610**
 decoding, 625
 detection, 18, 418, 608, **610**, 698
 Solid angle, 117
 Space
 -invariant system, 28
 -multiplex channel, 15, **369**, 371, 555
 Space-time separable channel, **376**, 494
 Span, 41
 Spatial
 Fourier transform, 30
 coherence
 function, 98
 region, 374
 frequency, **30**, 120, 127
 Spatiotemporal covariance matrix, 375
 Spatiotemporal mode, **239**, 244, 250, 739, 761, 769
 Speckle, 374
 Spectral
 -notched codes, 663
 shaping, 664
 susceptibility, **83**, 165
 width, *see* Linewidth
 Spectral rate efficiency, 156, 474, 475, **718**
 arbitrary modulation, 718
 for several modulation formats, 720
 maximum, 22
 phase modulation, 720
 photon-optics, 719
 wave-optics, 718
 wideband regime, 719
 Spectrum, 30
 Speed of light
 material, 83
 vacuum, 83
 Spherical decoding, 621
 Split-step Fourier method, **229**, 564
 Spontaneous emission, 246, **256**
 amplified, **334**, 337
 noise factor, 335
 nonlinear mixing with signal, 339
 power density spectrum, 257, **336**
 phase-synchronous demodulation, 381
 Spontaneous-spontaneous emission noise, 337
 Square-integrable signal, 30
 Square-law photodetection, 19
 Square matrix, 46
 Square-root detection basis, **840**, 851
 Standard deviation, 54
 State, *see* Signal state
 State preparation, *see* Signal state, preparation
 Statebook, 780, **847**, 875
 Stationarity
 strict sense, 68
 wide sense, 68
 Stationary
 point, 530
 random process, 68
 Statistic, 52
 sufficient detection, **399**, 419, 420, 622
 Statistical
 quantum optics, 743, **776**
 uncertainty, 7, 262, 683, **743**, 776, 820
 Step-index optical fiber, **110**, 132, 133, 179
 multiple-layer, 180
 Stimulated
 Brillouin scattering, **207**, 313, 663
 Raman scattering, **206**, 313
 emission, **246**, 312
 cross section, **315**, 355
 laser diode, 326
 Stochastic
 differential equation, 347
 gradient descent method, **600**, 603
 process, 52
 Stokes
 parameters, 94
 representation of polarization, **94**, 186
 scattering, 205
 vector, 108
 Subcarrier, 16, **201**, 225, 368
 interchannel interference, 551
 nonlinear interference, 224
 walk-off length, 215
 Subchannel, **15**, 551
 channel capacity, 706
 degrees of freedom, 368
 energy redistribution, 373
 independent, **285**, 706
 multimode fiber, 369
 polarization, 368
 time, 368
 uncorrelated, 709
 wavelength, **368**, 553
 Subcode, 640
 Submatrix, **48**, 615
 Sufficient detection statistic, **399**, 412, 419, 420, 622
 Sum-product algorithm, *see* Bahl algorithm
 Superposition, 27
 integral, 28
 Surviving path, 540
 Susceptibility, **81**
 nonlinear coefficient, 203
 spectral, **83**, 165
 temporal, 82, 165
 tensor, 81
 Symbol, 1

- clock, 586
 energy, 365, **382**, 423, 426, 466, 471, 514
 error, 5, 21, 451, 456
 mapping, 451
 pulse, 3
 state, 451
 Symbol state
 block-symbol, *see* Signal state, block-symbol
 component-symbol, *see* Signal state,
 component-symbol
 Symbol-by-symbol detection, *see* Detection,
 symbol-by-symbol
 Symmetric matrix, 47
 Symptom, 648
 Synchronization
 carrier phase, 574
 block, 573
 clock phase, **573**, 586
 frame (data), **573**, 588, 590
 marker, 588
 detection, 589
 preamble, 588
 Syncword, 588
 Syndrome, **622**, 648
 System, 1, 27
 additive, 28
 bandlimited, **26**, 74
 causal, 29
 continuous time, 28
 homogeneous, 28
 linear, 27, **28**, 560
 linear time-invariant, **33**, 84, 363
 memoryless, 30
 shift-invariant, 28
 shot-noise-limited, **286**, 429, 455, 457, 559, 767
 space-invariant, 28
 spatially local, 30
 time-invariant, 28

 Tangential field component, 139
 Tanner graph, **625**, 647
 girth, 627
 Target pulse, xxvii, **416**, 465, 525
 Temporal
 coherence, 97
 coherence function, 98
 defocusing, 367
 Fourier transform, **30**, 125, 162
 susceptibility, 165
 Tensor product, **43**, 759
 Theorem
 Campbell's, *see* Campbell's theorem
 central limit, *see* Central limit theorem
 fluctuation–dissipation, 335
 Hartley–Shannon, 21
 Isserlis, 54, 267, **297**
 noisy channel coding, 677
 quantum optics, 860
 sampling, *see* Sampling theorem
 Wiener–Khinchine, 69
 Thermal
 energy, xx, 112, 206, **243**
 equilibrium, 206, **243**, 244
 maximum-entropy distribution, 250
 noise, 78, 237, **248**, 250, 358, 360, 396, 403, 461
 channel, 872
 floor, 249
 optical, 256
 power density spectrum, **249**, 250, 396
 noise regime, 248
 radiation, 113
 Thermodynamics, 243
 second law of, 243
 Three-dB coupler, 301
 Threshold
 detection, *see* Detection threshold
 lasing, *see* Laser diode, threshold current
 Time-division multiplexing, 16, **368**
 Time-invariant system, 28
 Timeframe, traveling, **167**, 218, 220, 224
 Timewidth, **34**, 82
 effective, 34
 -limited signal, 34
 root-mean-squared, **34**, 100
 Timewidth–bandwidth
 inequality, **36**, 767
 product, **35**, 688, 707, 711
 Total harmonic distortion, 355
 Total internal reflection, 116
 Trace, **47**, 776, 777, 829
 outer product, 102
 partial, **779**, 812, 858
 Training sequence, 372, 574, **590**
 Transfer function, **33**, 73
 baseband noise-equivalent bandwidth, 75
 block, 373
 channel matrix, 373
 complex-baseband, **40**, 364, 371, 406
 lightwave noise-suppressing filter, 293
 electrical, 395
 matrix, 370
 multi-input multi-output channel, 373
 passband, 40
 noise-equivalent bandwidth, 75
 phase-locked loop, 579
 first-order, 604
 second-order, 604
 polarization-dependent, 370
 receiver, 287
 Transform
 Fourier, *see* Fourier transform
 Hilbert, **32**, 101

- Kramers–Kronig, **32**, 83, 102, 165
 Poisson, **262**, 799
 Transformation
 matrix, **42**, 50
 self-adjoint, **49**, 742, 752
 unitary, **48**, 370
 Transit-time dispersion, **156**
 Transition probability, 636, **672**, 691, 700, 729, 848
 Transmittance, **114**, 321, 364
 Transparency region, 112
 Transversal filter, **531**, 559
 Transverse
 electric mode (TE), **124**, 151
 characteristic equation, **128**, 158
 even, 128
 mode pattern, 131
 odd, 128
 step-index fiber, 143
 electromagnetic mode (TEM), **85**, 124
 field component, 88
 magnetic mode (TM), **124**, 151
 characteristic equation, 129
 step-index fiber, 143
 Trellis, **537**
 branch, **537**, 538, 626
 code, 656
 -coded modulation, 656
 branch, 658
 for a convolution code, **632**
 graph, 625
 minimal, 631
 node, 537
 surviving path, 540
 Triangular pulse, 101
 Turbo code, *see* Berrou code
 Turning point, 809

 Uncertainty
 quantum, 7, 262, 685, **743**, 750, 820, 824
 statistical, 7, 262, 685, **743**, 820
 Ungerboeck code, 656
 Unguided mode, *see* Mode, unguided, 162
 Union bound, **479**, 541, 840, 842
 quantum, 842
 superfluous term, **479**, 541
 Unit-step function, 29
 Unitary
 matrix, **48**, 185, 196, 370
 transformation, **48**, 370, 753
 Up-conversion, 378
 Upper-state lifetime, **246**, 314, 318

 V parameter, **128**, 151, 157
 V_{π} , 329
 Vacuum state, **246**, 248, 771, 772, 794, 800
 energy, **246**, 764, 770, 771
 fluctuations, **249**, 487
 operator, image mode, 794
 Wigner distribution, 800
 Variance, 54
 Variational calculus, **241**, 252, 429, 530
 Vector
 field, **84**, 89, 126
 axial component, **88**, 124, 139
 normalized, 88
 tangential component, 139
 transverse component, 88
 Helmholtz equation, 126
 notation, xxv
 Vector space, 41
 Velocity
 group, *see* Group velocity
 phase, *see* Phase velocity
 Viterbi
 algorithm, **540**, 565, 626
 decoding, 629
 von Neumann entropy, **784**, 881
 antipodal coherent-state modulation, 865
 nonorthogonal signal states, 785, 864
 orthogonal signal states, 864
 pure signal state, 785
 Voronoi regions, **478**, 497

 Walk-off
 length, 213, **214**, 216, 234
 time, 215
 Water filling, **706**, 735
 spatial subchannel, 706
 Wave equation, **83**, 108, 114
 optical fiber, 132
 Wave optics, **6**, 115
 bandlimited capacity, 710
 relationship to photon optics, **250**, 259
 relationship to quantum optics, 741
 signal model, **6**, 20, 83, 122, 239, 361, 737
 signal rate, 735
 single-letter capacity, **696**, 698
 spectral-rate efficiency, 718
 Waveform, **3**
 bandlimited, **45**, 109, 723
 baseband, **3**, 45, 398
 channel, **17**, 397
 bandlimited, 18
 electrical, **17**, 398
 lightwave, 17
 complex-baseband, 399
 continuous-time, 398, **414**
 data-modulated, **214**, 573
 information channel, 18, 679
 bandlimited, **676**, 710
 nonlinear, 671
 modulated, 179

- noncoherent, 500
- nonorthogonal, 391
- passband, **3**, 39, 710
- power, 467
- pulse, 570
- random binary, 71
- real-baseband, **310**, 380, 411, 581
- Wavefront, geometrical, 92
- Waveguide, 6, 88, **121**
 - dielectric, 87, **124**
 - cylindrical, 132
 - dispersion, *see* Dispersion
 - dispersion coefficient, 180
 - optical fiber, *see* Optical fiber
 - slab, 110, **125**
- Wavelength, 7, **85**
 - dependent group delay, 155, 170, **173**, 179, 199,
 - see* group delay, wavelength-dependent
 - division multiplexing, 16, **368**, 568
 - bandlimited channel, 726
 - free-space, 84
- Wavenumber, **8**, 84, 86
 - free-space, **80**, 84, 91, 121, 165, 209
- Wavevector, 85
 - local, 92
- Weakly guiding fiber, 133
- Weight, Hamming, **613**, 622
 - minimum, **613**, 634
- Weight profile, **628**, 635
- Well-guided mode, **130**, 161, 211
- White noise, 73, **249**, 271, 424, 528
- Whitened matched filter, **427**, 458
- Wideband regime
 - photon-optics capacity, 715
 - wave-optics capacity, 719
- Wiener
 - filter, **591**, 598
 - process, **343**
- Wiener–Hopf equations, 598
- Wiener–Khinchine theorem, 69
- Wigner distribution, **799**, 802, 805
 - gaussian state, 806
 - relationship to other distributions, 802
 - vacuum state, 800
- Z channel, 693
 - mutual information, 693
- Zero-forcing
 - equalizer, **528**, 533
 - multi-input multi-output channel, 554
 - polarization alignment, 554
- Zero-material dispersion wavelength, 164
- Zero-point energy, **246**, 771