

Index

- activation energy
 - grain-boundary diffusion 34, 43
 - lattice diffusion 33, 41, 98
 - self diffusion 34
 - superplastic flow 48
- adiabatic heating 158
- aluminum alloys
 - Al–Ca 63
 - Al–Cu 61, 66
 - Al–Cu–X (2000) 63, 67
 - Al–Cu–Zr (SUPRAL) 63, 262
 - Al–Li (8090) 26, 65, 243, 263
 - Al–Mg–X (5000) 220, 262
 - Al–Mg–Zr (FORMALL, NEOPRAL) 63
 - Al–Si 25
 - Al–Zn–Mg (7475) 62, 65, 67, 243
- alumina
 - Al₂O₃–ZrO₂ 101, 103, 105, 115
 - diffusion bonding 251
 - dopants 99
 - monolithic 14, 99
- aluminides
 - iron (Fe₃Al and FeAl) 140, 122
 - nickel 126, 203, 222
 - titanium
 - Ti₃Al (α and α₂) 135
 - TiAl (γ) 136
- amorphous *see also* glassy phase
- anisotropy
 - composite 209
 - crystallographic 213
 - microstructural texture 1, 27
 - thermal expansion 211
- bicrystal
 - aluminum 26
 - boundary orientation 25
 - boundary sliding mobility 26, 27
 - copper 26
 - steel 26
- bismuth–tin 7
- cavitation
 - aluminum composites 178
 - ceramics 198
 - characteristics (shape of cavity) 178, 199
 - effect of back pressure 199
 - grain boundary 114, 133
- cavity growth
 - morphology and shape 114, 199
 - plasticity controlled 178
- cavity nucleation
 - hard particles 24, 179
 - interfaces 179
 - volume fraction 179, 182, 201
- ceramics
 - alumina 99
 - ductility 192

- hydroxyapatite 100
- mullite 103
- β -spodumene 100
- zirconia 93
- ceramic composites
 - iron carbide–iron 107
 - silicon carbide–silicon nitride 106
 - silicon carbide–zirconia 195
 - zirconia–alumina 105
- Class I solid solution alloy
 - Al–Mg 46, 141, 166, 219
 - Al–Mg–(Sc) 166
 - niobium alloys 220
 - solute drag mechanism 37, 223
 - tungsten–rhenium 220
- composites
 - aluminum based 145, 154
 - magnesium based 148, 154
 - zinc based 149
- copper alloys
 - brass 6, 24, 47, 151
 - bronze 5, 13
- creep
 - constitutive law 33
 - deformation map 51, 181
 - diffusional creep
 - Coble creep 34, 40, 165, 223
 - Nabarro–Herring creep 34, 40
 - dislocation climb 37
 - dislocation glide 37
 - Harper–Dorn creep 16, 36, 223
 - power-law creep 33
- diffusion
 - bonding (see diffusion bonding) 33
 - for creep 33
 - grain boundary 34, 51, 239
 - lattice diffusion 34, 51, 98
 - surface diffusion 239
- diffusion bonding
 - aluminium alloys 242
 - bond (shear) strength 243, 251
 - stainless steels 242
 - titanium alloys 240
 - UHCS 242
 - zirconia 251
 - zirconia–alumina 251
 - zirconia–metal 251
- dislocation
 - accommodation for grain-boundary sliding 40
 - climb 37
 - creep 36
 - glide 37
 - pile-ups 38, 42
- dispersoid (or precipitates)
 - Al₂Cu 63, 65
 - Al₃Sc 166
 - Al₃Zr 24, 62, 222
 - Fe₃C 24
 - oxides 62, 163
 - silicon carbide 145, 155
 - silicon nitride 161, 175
 - titanium carbide 24, 155
- elongation
 - effect of flow stress 19, 194
 - effect of grain size 95, 122, 197
 - effect of liquid 114, 175
 - effect of strain rate 85, 201
 - phase fraction 81
 - strain rate sensitivity 177, 190
- forging *see* thermomechanical process
- geology
 - earth mantle 117
 - olivine 117
- glassy phase
 - effect on plastic flow 100, 114
 - grain boundary 110, 109
 - thickness 114
 - volume fraction 114
- grain size
 - coarsening (see grain growth)
 - diffusion creep 34
 - effect of second phase shape *see* grain morphology
 - exponent 34, 109
 - grain-boundary sliding 33, 53
 - particle-stimulated nucleation 64
- grain boundary
 - adhesive strength 28
 - cavity nucleation 114
 - diffusion 34, 51, 239
 - glassy phase 100, 109
 - high angle 25, 66
 - low angle (subgrain) 25, 66
 - liquid phase 175
 - mobility 28
 - melting 176
 - pinning 24, 82
 - segregation 110

- grain boundary (*cont.*)
 - sliding 36
 - sliding mechanism
 - dislocation accommodated 40
 - diffusing accommodated 40
 - triple junction 112, 179
- grain growth
 - dynamic 70, 83, 94
 - static 94
- grain morphology 27

- hydroxyapatite 100

- impurity effect 97
- intergranular fracture 112, 195
- intermetallics
 - ductility 203
 - iron aluminide 140
 - nickel aluminide 131, 203
 - nickel silicide 126, 203
 - titanium aluminide 135
- internal stress
 - phase transformation 213, 215
 - temperature cycling 209
 - thermal expansion 211
- iron alloys
 - austenitic steels 77
 - ferritic steels 77
 - Hadfield manganese steels 77
 - laminates 79
 - low carbon steels 76
 - plain carbon steel 73
 - stainless steels 25, 77, 261
 - ultrahigh carbon steels 74, 233, 242, 259
 - white cast iron 25, 76, 232
- laminates
 - constitutive equation 150
 - Mg–Li 149
 - stainless steel 150
 - ultrahigh carbon steels 149, 242
- lead alloys 5, 6, 24, 45

- magnesium alloys
 - Mg–Al 70
 - Mg–Cd 71
 - Mg–Li 71, 107
 - Mg–Mn 71
 - Mg–Zn 69
 - composite 73
 - grain size effect 69
 - magnesium oxide 3, 13, 99
- mechanical alloying
 - Al–Mg–Li 163
 - IN 9021 613
 - IN 9052 164
 - MA 754 164
 - grain size effect 168
 - incipient melting point 175
- mechanical working *see* thermomechanical process

- nanocrystals
 - grain size effect 16, 226
 - sinterforging 236
 - strain rate 226
- Newtonian flow 28, 34, 38, 223, 225
- nickel alloys
 - aluminides *see* intermetallics
 - Gatorizing 231
 - IN 100 83, 234, 257
 - Inconel 718 84, 257
 - MA 754 83, 85, 128, 164
 - MA 6000 83, 164
 - MINIGRAIN 83
- phase transformation 11
- powder consolidation 2, 232
- powder metallurgy
 - aluminum 166
 - mechanical alloying 162
 - metal-matrix composites 154

- recrystallization
 - dynamic 67, 78, 84, 133
 - particle-stimulated nucleation 64
 - static 67
- rheology
 - mechanism 103, 196
 - rheocasting 171

- segregation
 - grain boundary 112, 174
 - interface 174
- silicon nitride 106, 161
- silicides
 - nickel silicide 126
- sinterforging
 - titanium 237
 - zirconia 236
- steels *see* iron alloys
- strain rate

Index

273

- constant rate testing 95, 128, 137
- constitutive laws 33, 109, 134
- effect of grain size 34, 169
- strain-rate-change test 96
- strain-rate-sensitivity
 - ceramics 193
 - effect on elongation 190, 192
 - impurity 97
 - metals 193
 - strain-rate-change test 96
- stress
 - biaxial stress 248
 - internal stress (or back stress) 208
 - on elongation 192
 - threshold stress 38, 157, 165
- stress exponent *see* strain-rate-sensitivity
- superplastic flow
 - activation energy 34
 - constitutive law 22, 23, 48, 109, 134
 - diffusional 48
 - grain-boundary sliding 34
 - grain size dependence 23, 34, 70, 80
 - mechanism 42
 - stress dependence 34
 - temperature dependence 34
- superplastic forming
 - alumina–zirconia 246
 - aluminum alloys 242
 - biaxial forming 151, 214, 246
 - bulk 259, 262
 - diaphragm forming 236
 - drape forming 236
 - extrusion 236
 - female forming 236
 - sheet 151, 248, 263
 - stainless steels 261
 - strain rate 29, 49
 - titanium alloys 240
 - zirconia 246
- testing
 - compression 92, 107
 - constant crosshead speed 95, 128
 - constant strain rate 95, 128
- strain rate change 96
- tension 92, 107
- texture
 - crystallography 211
 - grain anisotropy 3, 27
- thermomechanical process
 - extrusion 155, 236
- forging
 - sinterforging 235
 - superplastic forging 235
- isothermal rolling 65, 159
- thermal cycling
 - aluminum composites 147, 209
 - modeling 212
 - titanium alloys 216
 - zinc composites 209
- thermal expansion *see* internal stress
- titanium alloys
 - aluminides 135, 136
 - composites 216
 - phase fraction 81
 - phase transformation 215
 - superplastic forming 240
 - Ti–6Al–4V 79, 241, 251
 - Ti–6Al–@Sn–4Zr–2Mo 79
 - two-phase alloy 80
- titanium oxide 99, 237
- two-phase alloys
 - effect on grain size 82
 - effect on sliding 26
 - nickel aluminide 131
 - phase fraction 81
 - titanium alloys 137
- yttrium oxide 99
- zinc alloys
 - composite 209
 - Zn–Al 8, 42
- zirconia
 - Al₂O₃ composites 101, 115, 246, 251
 - monolithic 93, 246, 251