

Cambridge University Press

978-0-521-46280-8 - Interfacing the IBM-PC to Medical Equipment: The Art of Serial Communication

R. W. D. Nickalls and R. Ramasubramanian

Index

[More information](#)

Index

- 8250, 25
- 16450, 25
- 16C1450, 33
- 16550, 25
 - FIFO buffers, 26
- 16C1550, 33
- 82510, 26

- ACIA, 25
- ACK control character, 19, 20, 345
- analysis of pulse oximetry data, 102
- AND, 73, 75, 76, 78, 79
 - logic table, 76
- & prefix, 73
- &H prefix, 73
- ANSI Standards, 3
- applied parts, 89
- ARQ protocol, 19, 20
- ASC option, 48, 365
- ASCII, 12
 - ASC option, 48, 365
 - classification of control characters, 343
 - description of control characters, 344
 - table of control characters, 341
 - table of graphic characters, 342
- asynchronous transmission, 13
- autocorrelation, 99

- baud, 14
- baud rate divisor, 28, 31, 34
 - diagram of low & high registers, 40
 - high byte, 28, 31, 34
 - low byte, 28, 31, 34
 - table of, 28
- Baudot code, 12
- Baudot, Jean Maurice Emile, 14
- BEL control character, 345
- BIN option, 365
- binary notation, 373
- bit, 12
 - bit-encoded registers, 31
 - bit-mapped registers, 31
 - bit-mask, 74–76, 78, 79
 - bit-rate, 14
 - and ON COM statement, 46
 - break, 34, 42
 - and line control register, 34
 - and line status register, 36
 - break interrupt, 36
 - BS control character, 345
 - buffer
 - buffer overflow error, 69
 - emptying the receive buffer, 64
 - FIFO, 26
 - RB option, 48, 366
 - TB option, 48, 367
 - byte, 12

- cable length for RS-232, 11
- CAN control character, 346
- capacitance of RS-232 cable, 11
- Capnomac Ultima series, 176
- Cardiocard series, 176
- category AP equipment, 94
- category APG equipment, 94
- CD option, 47, 366
- character interface, 3
- character-frame, 13
 - diagram of, 14
- chassis ground, 7
- checksum, 21
 - 7-bit, 22, 72
 - 8-bit, 22, 71
 - CHECKSUMHEX\$ function, 71
 - cyclic redundancy check, 18, 21, 24
 - HEX\$, 71
 - hexadecimal, 71
 - modulo*128, 22, 72
 - modulo*256, 22, 71
 - Σ -checksum, 22, 71

Cambridge University Press

978-0-521-46280-8 - Interfacing the IBM-PC to Medical Equipment: The Art of Serial Communication

R. W. D. Nickalls and R. Ramasubramanian

Index

[More information](#)

396

Index

- Graseby 3400 pump, 220
- Nellcor N-200E, 138
- QuickBASIC programs for, 71
- TC-checksum, 22, 23, 72
 - Ohmeda 7800 ventilator, 304
 - Ohmeda 9000 pump, 249
- two's complement, 22, 23, 72, 249, 304
- TWOSCHECKSUM\$ function, 72
- CHECKSUMHEX\$ function, 71
- circuits
 - control, 7, 8
 - data, 7, 8
 - diagram of RS-232 circuits, 8
 - ground, 7, 8
 - input, 8
 - output, 8
- class I electrical equipment, 91
- class II electrical equipment, 91
- clear to send, *see* CTS
- clock
 - master clock, 28
 - receive clock, 16
 - reference clock, 28
 - resident clock, 17
 - table of baud rate divisors, 28
- code extension control characters, 343
- COLLECT.EXE, 177
- COM port, 25
- COMMANDER program, 112
- Compact II spirometer, 272
- compressed spectral array plot, 102, 105
- connectors, 9
 - pin-outs for 9-pin connectors, 6, 349
 - pin-outs for 25/26-pin connectors, 6, 348
- control characters
 - code extension characters, 343
 - device control characters, 343
 - format effectors, 343
 - information separators, 344
 - transmission control characters, 343
- control circuits, 7, 8
 - monitoring input control lines, 78
 - setting output control lines, 72
 - testing for line status, 80
- CR control character, 345
- CRC, *see* cyclic redundancy check
- CS option, 47, 50, 366
- CTS, 8, 9
 - and data output, 50
 - and device time-out error, 69
 - and modem status register, 35
 - CS option, 47, 50, 366
 - monitoring CTS status, 78
 - set HIGH to enable data output, 41
 - time-out parameter, 42
- cumulative distribution plot, 102, 104
- cumulative sum test (CUSUM), 99
- cyclic redundancy check (CRC), 18, 21, 24
- DART, 25
- data analysis, 98
- data bits, 13–15, 34
 - and line control register, 34
 - and ON COM statement, 46
- data carrier detect, *see* DCD
- data circuits, 7, 8
- data file
 - opening a data file, 56
 - SHOW.COM, 65
 - VIEW.EXE, 65
 - viewing a data file, 65
- data frame, 13
 - diagram of, 14
- data packet, 21
- data set request, *see* DSR
- data transmission, 12
 - asynchronous, 13
 - enchronous, 13
 - isochronous, 13
 - synchronous, 13
- data transmit ready, *see* DTR
- data visualisation, 99
- database packages, 100
- DATE\$, 57
- Datex anaesthesia monitors, 176
 - COLLECT.EXE, 177
- DC1 control character, 20, 345
- DC2 control character, 345
- DC3 control character, 20, 346
- DC4 control character, 346
- DCD, 8, 9
 - and device time-out error, 69
 - and modem status register, 35
 - CD option, 47, 366
 - monitoring DCD status, 78
- DEL control character, 347
- descriptive procedures, 98
- device control characters, 343
- DLAB, 27, 31, 34
 - and line control register, 34
- DLE control character, 345
- double insulation, 91, 92
- Dräger Evita ventilator, 313
- DS option, 47, 366
- DSR, 8, 9
 - and device time-out error, 69
 - and modem status register, 35
 - DS option, 47, 366
 - monitoring DSR status, 78
 - set HIGH to enable data input, 42
 - time-out parameter, 42
- DTR, 8, 77
 - and modem control register, 33, 72
 - control line subroutine SETDTR, 77

Cambridge University Press

978-0-521-46280-8 - Interfacing the IBM-PC to Medical Equipment: The Art of Serial Communication

R. W. D. Nickalls and R. Ramasubramanian

Index

[More information](#)

Index

397

- programming the DTR status, 72
- serial port on/off status, 41
- SETDTR subroutine, 77
- earthing, 91
- EBCDIC code, 12
- edge sensitive
 - Capnomac Ultima CTS, 181
 - modem status register bit-2 (RI), 35
- EIA, *see* Electronic Industries Association
- EIA Standards, 3
- ELAPSEDTIME\$ function, 66
- electrical safety, 88
 - and the PC, 88
 - applied parts
 - table of, 94
 - types, 93
 - category AP equipment, 94
 - category APG equipment, 94
 - caution with type B equipment, 96
 - class I equipment, 91
 - class II equipment, 91
 - definitions
 - applied parts, 89
 - medical electrical equipment, 89
 - patient circuit, 90
 - patient connection, 89
 - patient environment, 90
 - double insulation, 91, 92
 - F-type isolation, 92
 - general aspects, 90
 - general precautions, 95
 - guidelines for safe use of PCs, 97
 - isolating transformer, 88, 96
 - isolation circuits, 92
 - leakage current, 92, 95
 - single fault condition, 90
 - Standards, 88
 - table of applied part types, 94
 - type B equipment, 93, 96
 - type BF equipment, 93
 - type CF equipment, 93
- Electronic Industries Association, 3
- EM control character, 346
- EMPTYBUFFER subroutine, 65
- ENQ control character, 344
- EOR 77, *see also* XOR
- EOT control character, 344
- ERDEV, 68
- ERDEV\$, 68
- ERR, 68
- errors
 - and line status register, 36
 - buffer overflow error, 69
 - error messages, 69
 - error trapping, 68
 - framing error, 36, 69
 - overflow error, 36, 69
 - parity error, 36, 69
 - time-out error, 36, 42
- ESC control character, 346
- escape sequence, 19
- ETB control character, 346
- ETX control character, 19–21, 344
- Evans *et al.* oximetry program, 103
- Evita ventilator, 313
- exclusive OR, *see* XOR
- exit routine, 70
- exploratory data analysis, 98
- extended keys, 70
- F-type isolation, 92
- FCR, *see* FIFO control register
- FF control character, 345
- FIFO buffer, 26
- FIFO control register, 27, 39
- file viewing utilities, 65
- flow control, 18
- format effectors, 343
- frame, 13
 - diagram of, 14
- framing error, 17, 36
 - and device I/O error, 69
 - and line status register, 36
- frequency distribution plot, 102, 104
- FS control character, 347
- FULLCODE subroutine, 52, 57, 58, 280
- GETREPLY subroutine, 63, 64
- glossary, 375
- GND, 7, 8
- GNU PLOT, 369
- graphics packages, 101
- Graseby 3400 syringe pump, 211
 - Σ -checksum, 220
- ground
 - chassis ground, 7
 - circuits, 7
 - errors with differences in potential, 11
 - shield, 7
 - signal ground, 7, 8
- GS control character, 21, 347
- guidelines for safe use of PCs, 97
- H prefix, 73
- handshaking, 18
 - hardware, 18
 - software, 19
- hardware break, *see* break
- hardware handshaking, 18
- HEX\$, 71
- hexadecimal notation, 374
- HT control character, 345

Cambridge University Press

978-0-521-46280-8 - Interfacing the IBM-PC to Medical Equipment: The Art of Serial Communication

R. W. D. Nickalls and R. Ramasubramanian

Index

[More information](#)

398

Index

- I/O control by PC, 41
 - break signal, 42
 - role of DSR, 42
 - role of DTR, 41
 - role of RTS/CTS, 41
- IBMCOM forum, 29
- IER, *see* interrupt enable register
- IIR, *see* interrupt identification register
- inferential procedures, 98, 99
- information separators, 344
- INKEY\$, 70
- INP, 30, 73
- INPUT#, 56
- INPUT\$, 52
- INSTR, 55
- interrupt enable register, 38
- interrupt identification register, 37
- isolating transformer, 88, 96
- isolation circuits, 92

- Kalman filter, 99
- Kermit, 83
 - capture, 84
 - control codes, 86
 - initialisation file, 85
 - log session, 84
 - problems, 87
 - protocol, 84
 - terminal emulation, 85
- key
 - INKEY\$, 70
 - trapping extended keys, 70
 - trapping keys, 70
- key codes, 350
 - table of, 352

- LCR, *see* line control register
- leakage current, 92, 95
- least significant bit, 14
- LF option, 48, 366
- LF control character, 345
- line control register, 34
- line status register, 36
- LOC, 65
- LOF, 50
- long integer (&) notation, 73
- loopback, 33
 - and modem control register, 33
- LSB, *see* least significant bit
- LSR, *see* line status register
- LTRIM\$, 66

- mark/marking, 9
- master clock, 28
 - table of baud rate divisors, 28
- mathematical packages, 102
- MCR, *see* modem control register
 - memory address, 30
 - MID\$, 71
 - Minolta Pulsox-7 pulse oximeter, 160
 - MOD, 66, 71
 - modem control register, 8, 33, 72
 - modem status register, 9, 35, 78
 - modulo arithmetic, *see* checksum
 - most significant bit, 14
 - moving average, 99
 - MSB, *see* most significant bit
 - MSR, *see* modem status register
 - Murray code, 12

 - NAK control character, 20, 346
 - Nellcor N-200E pulse oximeter, 129
 - Σ -checksum, 138
 - NOT, 24, 73, 75
 - logic table, 76
 - one's complement, 24
 - two's complement, 24
 - Novamatrix
 - 500 pulse oximeter, 155
 - 505 pulse oximeter, 155
 - 515A pulse oximeter, 154
 - 520A pulse oximeter, 155
 - NUL control character, 344

 - O2SAT.COM program, 113
 - offset, 30
 - Ohmeda
 - 3700 pulse oximeter, 111
 - 3740 pulse oximeter, 111
 - 7800 ventilator, 295
 - 9000 syringe pump, 241
 - ON COM(n) GOSUB, 60
 - ON ERROR GOTO, 68
 - one's complement, 24
 - OP option, 47, 48, 366
 - OPEN, 56, 360
 - OPEN COM, 45, 364
 - bad file-name error, 69
 - execution of, 49
 - opening a data file, 56
 - opening the serial port, 45
 - OR, 73
 - logic table, 74
 - OR, 74, 75
 - OR, 74, 75
 - OS/2 and the serial port, 25
 - OUT, 30, 73
 - overrun error, 36
 - and device I/O error, 69
 - and line status register, 36
 - oximetry data, *see* pulse oximetry data

 - parity, 14, 15, 34
 - and line control register, 34

Cambridge University Press

978-0-521-46280-8 - Interfacing the IBM-PC to Medical Equipment: The Art of Serial Communication

R. W. D. Nickalls and R. Ramasubramanian

Index

[More information](#)

Index

399

- and ON COM statement, 46
- errors and line status register, 36
- parity error, 36, 69
- PE option, 48, 366
- table of parity options, 15
- Pasterkamp & Daien program, 103, 112
- patient circuit, 90
- patient connection, 89
- patient environment, 90
- PC
 - and electrical safety, 88
 - and electrical Standards, 88, 95
 - guidelines for safe use of PCs, 97
- PE option, 48, 366
- PEEK, 30
- Pettitt's non-parametric test, 99
- piecewise linear regression, 99
- pin-outs
 - table for 9-pin connectors, 6, 349
 - table for 25/26-pin connectors, 6, 348
- plotting the data, 369
 - see also* data analysis
- POKE, 30
- predictive procedures, 98, 99
- PRINT, 50
- PRINT#, 50
- problems with RS-232, 10
- programming, 29
- protocol, 16
 - ARQ protocol, 19, 20
 - parameters, 46
 - table of protocol options, 16
- protocol options, 29
- pulse oximeter
 - Minolta Pulsox-7, 160
 - Nellcor N-200E, 129
 - Novamatrix 500, 155
 - Novamatrix 505, 155
 - Novamatrix 515A, 154
 - Novamatrix 520A, 155
 - Ohmeda 3700, 111
 - Ohmeda 3740, 111
- pulse oximetry data
 - analysis, 102
 - COLLECT.EXE, 177
 - COMMANDER program, 112
 - compressed spectral array plot, 102, 105
 - cumulative distribution plot, 102, 104
 - desaturation index, 103
 - Evans *et al.* program, 103
 - frequency distribution plot, 102, 104
 - index of severity, 102
 - inferential procedures, 105
 - O2SAT.COM program, 113
 - Pasterkamp & Daien program, 103, 112
 - Taylor program, 103
 - time plot, 102, 103
- Pulsox-7 pulse oximeter, 160
- QBserial 2.0 program, 20
- QuickBASIC
 - adding date & time, 57
 - advantage over QBASIC, 44
 - AND, 75, 76
 - logic table, 76
 - &H prefix, 73
 - ASC option, 48, 365
 - BIN option, 365
 - CD option, 47, 366
 - checksum, 71
 - CHECKSUMHEX\$ function, 71
 - collecting reply codes, 63
 - controlling output control lines, 72
 - CS option, 47, 366
 - data-bits, 46
 - DATE\$, 57
 - DS option, 47, 366
 - ELAPSEDTIME\$ function, 66
 - EMPTYBUFFER subroutine, 65
 - EOR, *see* XOR
 - ERDEV, 68
 - ERDEV\$, 68
 - ERR, 68
 - error messages, 69
 - error trapping, 68
 - exclusive OR, *see* XOR
 - exit routine, 70
 - FULLCODE subroutine, 57
 - GETREPLY subroutine, 63, 64
 - GNU PLOT, 371
 - hexadecimal numbers, 73
 - INKEY\$, 70
 - INP, 73
 - input control line status, 80
 - INPUT#, 56
 - INPUT\$, 52
 - inputting data from the serial port, 51
 - LaTeX, 371
 - LF option, 48, 366
 - LOC, 65
 - LOF, 50
 - LTRIMS\$, 66
 - MID\$, 71
 - MOD, 71
 - monitoring input control lines, 78
 - NOT, 75
 - logic table, 76
 - ON COM(n) GOSUB, 60
 - ON ERROR GOTO, 68
 - OP option, 47, 366
 - OPEN, 56, 360
 - OPEN COM, 45, 364
 - opening a data file, 56
 - opening the serial port, 45

- optional OPEN COM parameters, 46, 364
- OR, 74, 75
 - logic table, 74
- OUT, 73
- outputting data, 50
- parity, 46
- PE option, 48, 366
- PRINT, 50
- PRINT#, 50
- protocol, 46
- protocol parameters, 46
- quit routine, 70
- RB option, 48, 366
- reading a register, 73
- receive buffer, 51
 - emptying the buffer, 64
- RESUME, 68
- RIGHT\$, 71
- RS option, 47, 367
- SEND subroutine, 63
- setting a bit HIGH, 74
- setting a bit LOW, 75
- SGN, 79
- SLEEP, 67
- stop-bits, 46
- STR\$, 66
- table of protocol parameters, 46
- TB option, 48, 367
- testing for a HIGH bit, 79
- testing for a LOW bit, 78
- TjX, 371
- text-based utilities, 371
- TIME\$, 57
- time delay, 67
- TIMER, 66, 67
- trapping keys, 70
- TWOCHECKSUM\$ function, 72
- WRITE#, 47
 - problems with WRITE#, 51
 - writing to a register, 73
- XON/XOFF not supported, 20
- XOR, 77
 - logic table, 77
- quit routine, 70
- RB option, 48, 366
- RDR, *see* received data register
- receive buffer
 - emptying the buffer, 64
 - RB option, 48, 366
- received data register, 32
- receiving data line, *see* RxD
- reference clock, 28
 - crystal frequencies, 29
 - table of baud rate divisors, 28
- references, 385
- register-select lines, 27
- registers, 26
 - baud rate divisor latch register, 40
 - bit-mapped registers, 31
 - FIFO control register, 39
 - interrupt enable register, 38
 - interrupt identification register, 37
 - line control register, 34
 - line status register, 36
 - modem control register, 33, 72
 - modem status register, 35, 78
 - numerical registers, 31
 - offset, 31
 - port address, 30
 - reading a register, 73
 - received data register, 32
 - register addresses, 30
 - setting a bit HIGH, 74
 - setting a bit LOW, 75
 - table giving offset, 31
 - table of, 26, 30
 - testing for a HIGH bit, 79
 - testing for a LOW bit, 78
 - transmitter holding register, 32
 - writing to a register, 73
- reinforced insulation, 91, 92
- reply codes, 63
- request to send, *see* RTS
- resident clock, 17
- RESUME, 68
- RI, 8, 9
 - and modem status register, 35
 - monitoring RI status, 78
- RIGHT\$, 66, 71
- ring indicator, *see* RI
- RS option, 47, 367
- RS control character, 347
- RS-232 interface, *see* serial interface
- RS-232 Standard, 3
- RS-422, 10
- RS-423, 10
- RS-485, 10
- RTS, 8, 41, 77
 - and modem control register, 33, 72
 - control line subroutine SETRTS, 77
 - programming the RTS status, 72
 - RS option, 47, 367
 - SETRTS subroutine, 77
- RxD, 7, 8, 12
- scan codes, 350
- SEND subroutine, 63
- serial interface, 3, 4
 - base address, 30, 31
 - circuits, 5, 8
 - circuits renamed, 5
 - compatibility with RS-423, 10
 - connectors, 9

Cambridge University Press

978-0-521-46280-8 - Interfacing the IBM-PC to Medical Equipment: The Art of Serial Communication

R. W. D. Nickalls and R. Ramasubramanian

Index

[More information](#)

Index

401

- control circuits, 7
- data circuits, 7
- diagram of circuits, 8
- distance limitations, 11
- DLAB, 31
- ground circuits, 7, 11
- input circuits, 8
- number of serial ports, 25
- opening the serial port, 45
- output circuits, 8
- problems with RS-232, 10
- table for 9-pin connectors, 6, 349
- table for 25/26-pin connectors, 6, 348
- timing of line sampling, 16
- voltages, 9
- serial port, *see* serial interface
- SETDTR subroutine, 77
- SETRTS subroutine, 77
- SGN, 79, 80
- shield, 7
- SHOW.COM, 65, 201, 284
- SI control character, 345
- SIA, 25
- signal ground, 7, 8
- simulator program, 358
- SLEEP, 67
- SO control character, 345
- software handshaking, 19
 - QBSerial 2.0 program, 20
- software tools, 100
- SOH control character, 344
- space/spacing, 9
- spectral array plot, 102, 105, 106
- spirometer
 - Vitalograph Compact II, 272
- spreadsheet packages, 100
- Standards for electrical safety, 88
- Standards for isolating transformers, 88
- Standards for PCs, 88, 95
- start-bit, 13, 15
- statistical tests for oximetry data
 - inferential procedures, 105
 - table of, 107
- statistics packages, 101
- stop-bit, 13, 15, 34
 - and line control register, 34
 - and DN COM statement, 46
- STR\$, 66
- STX control character, 20, 21, 344
- SUB control character, 346
- subroutine
 - CHECKSUMHEX\$, 71
 - ELAPSEDTIME\$, 66
 - EMPTYBUFFER, 65
 - FULLCODE, 57, 280
 - GETREPLY, 63, 64
 - SEND, 63
 - SETDTR, 77
 - SETRTS, 77
 - TWOSCHECKSUM\$, 72
- SYN control character, 346
- syringe pump
 - Graseby 3400, 211
 - Ohmeda 9000, 241
- Taylor oximetry program, 103
- TB option, 48, 367
- TC-checksum, *see* checksum
- THR, *see* transmitter holding register
- TIME\$, 57
- time
 - ELAPSEDTIME\$ function, 66
 - resident clock, 17
 - TIME\$, 57
 - TIMER, 66, 67
- time delays, 67
- time-out, 36, 46
 - and line status register, 36
 - CD option, 47, 366
 - CS option, 47, 366
 - CTS time-out, 42
 - DS option, 47, 366
 - DSR time-out, 42
 - DP option, 47, 366
 - using TIMER, 67
- time plot, 102, 103
- time series, 99
- TIMER, 66, 67
- tracking function, 99
- trailing edge, 35
- transmission control characters, 343
 - table of, 20
- transmit buffer
 - remaining space using LDF, 50
 - TB option, 48, 367
- transmitter holding register, 32
- transmitting data line, *see* TxD
- trapping keys, 70
- two's complement checksum, *see* checksum
- TWOSCHECKSUM\$ function, 72
- TxD, 7, 8, 12
- type B equipment, 93, 96
- type BF equipment, 93
- type CF equipment, 93
- UART, 25
 - 8250, 25
 - 16450, 25
 - 16C1450, 33
 - 16550, 25
 - 16C1550, 33
 - 82510, 26
 - bugs, 27
 - DART, 25

Cambridge University Press

978-0-521-46280-8 - Interfacing the IBM-PC to Medical Equipment: The Art of Serial Communication

R. W. D. Nickalls and R. Ramasubramanian

Index

[More information](#)

402

Index

- DLAB, 27
- FIFO buffers, 26
- FIFO control register, 27
- master clock, 28
- port address, 30
- protocol options, 29
- reference clock, 28
- register addresses, 30
- register-select lines, 27
- registers, 32
- SIA, 25
- table of baud rate divisors, 28
- table of COM port addresses, 31
- table of devices, 25
- table of register addresses, 31
- table of registers, 27
- USART, 25
- utilities for determining the UART, 29
- UCASE\$, 70
- Ultima series of monitors (Datex), 176
- US control character, 347
- ventilator
 - Dräger Evita, 313
 - Ohmeda 7800, 295
- VIEW.EXE, 65
- viewing a data file, 65
- Vitalograph Compact II spirometer, 272
- voltage transition, 16
- voltages, 9
- VT control character, 345
- WRITE#, 47
 - problems with WRITE#, 51
- XMODEM, 21
 - XMODEM-1K, 21
 - XMODEM/CRC, 21
- XOFF, 19, 20
 - and printers, 20
- XON, 19, 20
 - and printers, 20
- XOR, 77
 - logic table, 77
- ZMODEM, 21