

Index

- Baikonur launch complex, 1, 82, 106
- Baker diagram, 37–39, 68
- Blasius correlation, 47
- characteristic time of disturbance, 79–81, 104–5
- characteristic time of system, 78–80
- Claudius–Clapeyron equation, 63
- conservation equations: energy, 23–5; mass, 23–5, 29, 45, 88, 102, 109; momentum, 23–5, 29, 45, 88, 102, 109
- cryostabilization systems, 10–14; experimental studies of, 39–44, 121–8; mathematical modeling of, 44–9, 109–21
- Euler integration, 34, 48
- Euler number, 98–9
- external disturbances: change in flowrate, 77, 79–80, 83–5, 95–8; change in heat load, 77, 80, 107–10; change in system pressure, 77, 80–1; change in void fraction, 77; evaluation methods for, 78–80
- finite difference method, 93, 113
- flows: compressible, 30; equilibrium, 22, 29–35; incompressible, 30; non-equilibrium, 22, 35–6; steady state, 22, 39–56; transient, definition of, 22
- flow regimes, 16–18, 37–9: annular, 17; bubble, 17, 68; comparison of, 18; diagrams of, 18; droplet, 17, 68; effect on heat transfer, 68; importance of 17; influences on, 16, 20; irregular, 68; measurement of, 20; regular, 68; slug, 18, 59, 68; stratified, 18, 68–9, 109; wavy stratified, 18, 39, 41, 47, 68
- fluid transport systems, 14–15, 56–68
- gasification systems, 1–6: experimental studies of, 28–9, 82–6, 92–8; modeling transient flow in, 88–92, 100–5; practical design considerations for, 105–6; *see also* gasifiers
- gasifiers, 1, 6, 88–90; optimal flow regimes for, 25, 68, 105; steady state flow in, 25–37; with staggered fins (intensifiers), 6, 25–9, 68
- geysering, 14, 68; critical height for, 59–60, 67; critical time for, 59–60, 67; description of, 14, 56–60; experimental studies of, 59; mathematical model of, 60–7
- heterogeneous mixtures, 15
- ideal gas, 30, 110
- liquefied natural gas (LNG) systems, 7–9
- Lax–Wendroff method, 101–4
- Lockhart–Martinelli correction, 32, 56, 103
- magnet stabilization channels, *see* cryostabilization systems
- models: comparison of, 70–1; double (two) velocity, 44–5, 72; equilibrium, 69, 29–35, 102–4, 109–13; homogeneous, 18; requirements for, 18, 20,

- 69; single component (homogeneous), 18; two-component, 19; two-temperature, 74; two-velocity two-temperature, 75; three-velocity two-temperature, 76
- nondimensional analysis, 98–100, 104
- Nusselt number, 35, 49
- phase transition, 25, 110
- Prandtl number, 49
- quality, definition of, 15
- quenching 19, 44, 80, 107, 108, 117, 128
- Reynolds number 35, 47, 48, 98–9
- saturation properties, 31–2, 45, 63
- slip, definition, 16
- space simulation chambers, 10
- Strouhal number, 98–100, 105–6
- superconducting magnet systems, 10–14; HERA, 13, 37; LHC, 13, 37; Tevatron, 13, 37, 121–2; Tokamak, 12–13; UNK, 13–14, 37, 39–44, 48–55, 80, 107–9, 113–21, 128
- superheating, 39, 41, 48, 55, 108, 116–17
- time of disturbance propagation, 78–80
- transient behavior: high speed, 100–5; introduction to, 77–8; pressure, 86–7, 90; *see also* external disturbances, gasification systems, cryostabilization systems
- two-phase flows: design of practical systems using, 19; physical features, 15–18; *see also* flows
- vaporizers, *see* gasifiers
- void fraction, definition, 15; measurement, 15–16
- wall friction, 32–3, 47
- water hammer, 14, 56, 68