

Index

- accumulation of outer layer of billet in discard, 322
- adaptive remeshing, 223
- adhesion of lubricant to workpiece, 146
- advantage and disadvantage of backward extrusion, 24, 324
- allotropic behavior of steel, 118
- analogy, between stress and strain, 62, 66
- anisotropy
 - factor of, 442
 - measurement, 443
 - normal, 443
 - planar, 443
 - in sheet-metal, 442
 - in worked metals, 7
- area reduction, 77
- aspect ratio in
 - cylinder compression, 81
 - plain strain compression, 35
- asperity, 141
 - plastification, 142
- atoms, packing of, 3
- austenite, 118
- average
 - length strain, 78
 - pressure in frictionless compression, 81
- axi-symmetric FEM model, 225
- back-pull in wiredrawing, 398
- backward cup extrusion
 - effective strain rate distribution, 286
 - effective strain distribution, 288
 - FEA of process, 285–301
- balanced biaxial stretching, 438
- barreling of cylinder in compression, 108
- bearing in wiredrawing dies, 399
- bend allowance, 447
- bending, 28
 - of sheet-metal, 439
- biaxial stretching, 438
- billet, 22
 - removal without deformation, 350
- blank holder, 27, 444
- blanking, 30
 - conventional, 30
 - fine, 30
- blister defect, 323, 331
- bloom, 22
- bottleneck in forming, 12
- boundary
 - film lubrication, 146, 147–149
 - lubrication, 146
- boundary conditions in FEA, 224
- breakdown of material, 127
 - due to cracking, 134
- breakdown of
 - cast microstructure, 4
 - lubricant film, 13
- Bridgman’s
 - assumptions in necking analysis, 243
 - correction factor in tensile testing, 105
 - theoretical analysis of, 104
- buckling, 19
 - in deep-drawing, 444
- bulging in
 - cylinder compression, 108
 - wire drawing, 417, 418
- bulk metal forming, 9, 18
- burp cycle, 332
- calibration draw, 395
- capstan, 396
- casting
 - defect formation, 5
 - material loss, 5
- cast iron, 3
- cavity filling, 268
- cementite flakes 2, 3
- center bursts, 421
- center zone in plain strain compression, 41
- cermets, 398

- material model, 115
- chevron cracks, 421
 - growth in FEA, 423
- circle grid analysis, 435, 436
 - to determine strains, 68
- classification system
 - extrudability of Al-alloys, 335
 - extrusion processes, 10
 - metal forming, 9, 18
 - shapes of Al-profiles, 334
 - shapes of forgings, 271, 272
 - subdivision metal forming processes, 10
 - types of metal flow in extrusion, 326
- clay, deformation of, 1
 - deformation mechanism, 3
- clean cut in shearing, 30
- cleaning, of surfaces, 144
- closed die forging, 20–21
 - die filling in, 302
 - example of laboratory process, 302
 - FEA of, 302–316
 - optimized process, 279
- Cockroft-Latham failure criterion, 134
- coefficient of friction, 142
- cogging, 20
- coiling of wire, 396
- cold drawing of wire, 27
- cold forming
 - cold working by wiredrawing, 27
 - to gain high strength, 7
 - temperature range of, 118
 - vs. hot forming, 34
- complex strain path in sheet-metal forming, 437
- compression
 - axial, 87
 - homogeneous slab, 87
 - retarded stroke for constant strain rate, 108
- compression testing, advantages over tensile testing, 95
- compressive stress
 - on inside of bend, 439
 - in wiredrawing die, 398
- cone angle in wiredrawing, 400
- confinement of air in extrusion material, 332
- constancy of volume, 63
 - deviation from rule of, 64
- constitutive equation
 - definition, 115
 - in cold forming, 118
 - general expression, 117
 - in hot forming, 122
 - including microstructural mechanisms, 122
 - metals in general, 115–118
- contact angle in rolling, 370
- contact area
 - apparent area, 141
 - in compression, 107
 - real area, 141
- contact conditions between
 - billet and container, in extrusion, 351
 - roll and workpiece, in rolling, 365
- contact mechanisms, workpiece-die, 143
- contact pressure against die as process parameter, 14
- contact pressure against die in
 - cylinder compression, 230–233
 - deep drawing, 27
 - from the slab method, 373
 - light slab rolling, 380
 - normal slab rolling, 387
 - normal wiredrawing, 427
 - strip rolling, 391
 - wiredrawing, 400
- contact zone against
 - die in closed-die forging, 302–305
- contamination
 - as subsurface defect in extrusion, 330
 - of surfaces, 144
- continuous casting, 22
- continuum
 - mechanics, 2
 - medium, 2
- converging channel of wiredrawing die, 399
- conversion coating, 300
- cooling
 - effects, 159, 162
 - of plate against die, 163–164
- copper wiredrawing, 414
- Coulomb friction
 - model, 140–142
 - validity of model, 142
- cracking, 127
 - due to lamination, 8
 - in cylinder bulge, 134, 136
 - in shear, 136
 - transverse cracking in extrusion, 134
- critical blank size in deep-drawing, 444
- crystals, aggregate of, 3
- cup forming by deep drawing, 27
- curve fitting
 - applied for the flow stress, 118
 - determination of constants, 119
- cutting, 10
- cylinder compression
 - basic mechanics of test method, 106
 - compression velocity, 106
 - deformation in corner of bulge, 252
 - deformations in compression test, 253–254
 - dies applied in test, 106
 - experimental set-up, 106
 - FEA of test, 229
 - flow curve in test, 107
 - with friction, 108
 - friction effects, 199
 - friction measurement using pins, 153–154
 - frictionless compression, 1
 - homogeneous compression, 107, 251

- principal stress in frictionless case, 210
- reduced friction in test, 109
- strain rate field in frictionless case, 210
- as technological test, 93, 95
- velocity field in frictionless case, 209
- damage parameter in
 - light slab rolling pass, 381
 - normal slab rolling pass, 386
 - normal wiredrawing from FEA, 427
 - plain strain compression, 47
 - small reduction, large cone angle wiredrawing, 421
 - strip rolling pass, 392
 - wiredrawing, 421
- damage parameter, critical value, 134
- dead zone in
 - backward cup extrusion, 286
 - cylinder compression, 109
 - extrusion, 183, 322
 - plain strain compression, 41
 - strip rolling, 390
- deep drawing, 27
 - applied tooling, 27
 - fracture in, 28
 - of rectangular cup, 440
 - of round cup, 440
 - of sheet-metal, 439
 - wrinkling, 28
- defects
 - avoid defects because of economy, 14
 - blisters in extrusion, 323
 - of critical size, 130
 - in forging, 279
 - hot tearing in Al-extrusion, 159
- DEFORM[®]-code, 223
 - FEM-approach used, 224
- deformation
 - comparison of compression and tension, 59
 - over edge of plain strain compression die, 44
 - effect of varying clearance in shearing, 260–263
 - elastic, 1
 - energy, 160
 - fluctuations in wiredrawing, 417
 - homogeneity in cylinder compression, 108
 - homogeneity in extrusion seam, 238
 - of inhomogeneous nature, 2
 - macroscopic, 2
 - mapping of, 2
 - mechanism of, 4
 - microscopic, 3
 - multiplication of deformation crosses, 46
 - near punch in backward cup extrusion, 296
 - patterns in wiredrawing, 431
 - of permanent character, 116
 - plastic, 1
 - simple measure of total deformation, 77
- deformation analysis, 40–46
- deformation characteristics of extruded rod, 192
- deformation cross in
 - normal wiredrawing, 424
 - plain strain compression, 44
 - strip rolling, 390
 - cylinder compression, 253
- deformation from
 - deformed grid pattern, 182
 - effective strain distribution, 43
 - effective strain rate distribution, 43
 - grid pattern in backward extrusion, 290–292
 - strain rate distribution in wiredrawing, 425
 - velocity field, 85–87
- deformation in
 - backward cup extrusion, 286
 - deep-drawing, 440
 - extruded rod from grid pattern, 192–195
 - extruded rod, 361
 - extrusion, 24
 - extrusion billet from strain rate, 362
 - front end of extruded rod, 322
 - hot closed die forging, 310–314
 - light pass slab rolling, 377, 379
 - neck from circle pattern, 247
 - necking section, 243
 - neck in tensile test, 103
 - normal pass slab rolling, 383
 - plain strain compression test, 40–46
 - shearing, 30, 259
 - sheet-metal forming, 438
 - strip rolling, 389
 - wiredrawing, low reduction – large angle, 416
 - wiredrawing, normal drawing geometry, 425
- degree of reduction, 79
- deletion of FEM-mesh to model cracking, 422
- Δ -parameter, 81
 - in plain strain compression, 36
 - in rolling, 376
 - in strip rolling, 393
 - in wiredrawing, 403, 414
 - in Wistreich’s wiredrawing experiments, 414
- diamond in wiredrawing die, 398
- die bridge in extrusion, 333
- die cavity, 20
- die filling in closed-die forging, 277, 302
- die geometry, characteristic parameters, 400
- die-life, influenced by fatigue, 142
- die orifice, 23
- dies
 - in metal forming, 13
 - wear of, 13
- die splitting force in
 - strip drawing, 149
 - wiredrawing, 401, 414
- diffuse necking, 131
- dimensional stability in drawing, 395
- direct contact between surfaces, 144
- directionally oriented microstructure, 442

discard	equation to find friction in split die experiment, 401
in extrusion, 321, 323	Erichsen-test, 438
removal of, 324	Eulerian description, 222
dislocation, 3	eutectic phases, as contamination in extrusion, 324
density, 3	excessive stresses in sheet-metal forming, 441
movement, 3	experiments to validate FEM analysis, 35
dislocation networks in cold and hot forming, 122	explicit FEM-method, 222
displacement components, 86	exponent of strain hardening, 118
division processes, shearing, 30	extrudability of
draft in rolling, 383	Al, 25
drawing	Al-alloys, 335
as continuous process, 396	extrudate, 320
as discontinuous process, 396	extruded profiles, 23
of strip, 64	extrusion, 23–26, 320
unit in wiredrawing machine, 397	advantage of direct over indirect, 24
wheel, 396	backward process, 23
drawing cell in drawing machine, 398	billet, 23
drawing conditions in normal wiredrawing, 424	classification of processes, 10
ductility, 128	complex hollow profile extrusion, 25
increase through metal working, 7	container, 23
earring	of copper and brass, 24
factors influencing earing, 447	defect, 331
phenomenon in deep-drawing, 446	direct process, 23
ease of working, 128	division into subprocesses, 326, 347
economy in metal forming, 14	flow of outer layer of billet, 24
edges for cutting, 30	force, 337
effective strain distribution, plain strain	force against container wall, 338
compression, 43	forward process, 23
effective strain rate distribution, plain strain	friction force, 341
compression, 43	homogeneous deformation force, 341
elastic	hot extrusion of Al, 322
layer in bend, 440	hot lubricated, 25
zone, 191	indirect process, 23
elastic deformation	inhomogeneous deformation force, 342
of dies, 53	limitations in backward extrusion, 24
in tensile test, 102	of light metals, 24
elasticity theory, 53	load in backward extrusion, 325
elastic-plastic	metal flow in direct and indirect process, 24
materials, 116	in multi-hole dies, 24
emissivity, 164	peripheral billet layer, 24
emptying diagram	practice in forward extrusion, 323
in backward cup extrusion, 296	pressure, 337
concept, 195	pressure welding, 25
in extrusion made by FEA, 359	punch, 23
emptying line	ram, 23
longitudinal, 199	residue, 321, 323
transverse, 197	seam welds, 26
energy consumption	shell extrusion, 24
definition of, 69	of steel, 25
in extrusion, 325	tooling in porthole die extrusion, 25
friction energy, 406	total force, 337, 343
for homogeneous deformation, 405	welding, 26
for inhomogeneous deformation, 407–409	welding, FEM-model of, 233–238
total in wiredrawing, 405, 409	welding chamber, 25
energy dissipation, 69	failure
entrance into roll gap, 376	criteria, 134
	catastrophic, 130

Index

457

- FEA
 correction of flow curve, 245–246
 to determine thermal effects, 168–173
 in general, 220
 general importance in metal forming, 221
 graphical presentation of results, 229
 results as parameter distribution, 229
- FEM-codes
 development of, 221
 to model metal forming, 223
- FEM model, 2D
 backward Al-extrusion, 358–362
 backward cup extrusion, 285–301
 cylinder compression, 136, 200–201, 229–233, 250–253
 extrusion welding, 237–238, 333
 forward Al-extrusion, 352–357
 forward extrusion, subprocesses, 347–349
 plain strain compression, 225, 226
 shearing, deformations in sheared layer, 257–263
 shearing, to find K and n , 264–265
 slab rolling pass, 376–393
 tensile test, formability consideration, 130–131
 tensile testing, risk of cracking, 135–136
 tensile testing, stress conditions in neck, 243–246
 wiredrawing, 415–431
- FEM model, 3D
 closed-die forging, 302–316
 cylinder compression, 253
 extrusion welding, 233–237
 plain strain compression, 37–50
 tensile testing, necking, 247
- FEM-modeling, in general, 220
- FEM-solver, 224
- ferrite, 2, 118
- finished product, 13
- finishing die, 274
- finite difference method, 204
- finite element analysis (FEA), 34
 validation of, 35
- finite element method (FEM), 34
- finite elements, 221
- flash, 21
 formation of, 4
- flash gap, 277
 characteristic geometrical conditions, 281
 common designs, 281
 design rules in closed-die forging, 280
- flash less forging, 20
- flat rolling, 22
- flat-faced die, in extrusion, 322
- FLD-diagram, 130, 441
- flow criteria, the von Mises and Tresca criterion, 111
- flow criterion, correctness of, 38
- flow curve, 116
 determination in cold forming, 107
 determination curve in hot forming, 107
 from tensile test, 102
 true and nominal curve, 103
- flow direction of outer layer of billet in extrusion, 331
- flow formulation, 222
- flow patterns in extrusion, 326–328
- flow rule of Lévy-Mises, 73
- flow stress
 of Al-alloys in bending experiments, in cold, warm, and hot forming, 115, 116
 from compression test, 107
 of copper wire, 117, 416
 general function, 118
 to get right metal flow in Al-extrusion, 353
 mean value of in wiredrawing, 405
 parameter influence, 116
 as process parameter, 14
 from shearing test, 263–265
 temperature dependence, 117
 variation due to microstructure, 118
- flow types in extrusion, 190
- foil, 442
- folds, 279
- force
 on the roll, 367
 total force in wiredrawing, 399
- forgeability, 269
 of different metals, 270
- forging
 as a requirement, 7
 avoiding unsound grain flow, 8
 as nonstationary process, 85
 deformation in hot closed die forging, 310–314
 design of multistep series, 274–276
 design principles, 276
 design to avoid defects, 280
 to improve fatigue resistance, 8
 mass distribution principle in, 276
 optimum temperature, 269
 stock, 274
 typical multi-step forging sequence, 275
- forgings
 complexity of, 271
 shapes difficulty to forge, 272
- formability, 127
 to avoid defect formation, 14
 improvements in deep-drawing, 442
 limits, 441
 of metals in deep-drawing, 446
 parameter in deep-drawing, 445
 parameter in stretch forming, 445
- forming under
 compressive stress, 9, 18
 tensile stress, 9, 18

- fracture, 127
 - elongation, 94, 103
 - in forgings due to defects, 280
 - in shear, 138
 - strain, 94, 103
- free forming, 19
- friction
 - in backward cup extrusion, 300
 - Causing load increase in bending, 216
 - determination in plain strain compression, 37
 - dry friction, 144–145
 - effects in metal forming, 139
 - effects on flow curve from compression, 254
 - energy dissipation, 162
 - factor, 143
 - force, 141
 - force as process parameter, 14
 - heating, 161
 - hill, 208
 - influence on forming load, 139
 - measurement in forming, 149–155
 - measurement in wiredrawing, 400
 - measurement using pins, 152
 - shear stress, 142
 - shear stress in wiredrawing, 400
 - from surface ring pattern, 199
- friction coefficient, 142
 - value, boundary film lubrication, 148
 - value, hydrodynamic lubrication, 147
- frictionless compression, average pressure vs. Δ , 81
- friction models, 140
 - comparison of models, 143
 - implementation of in FEM-codes, 229
- full separation of contact surfaces, 144
- fusion welding, 26
- general extrusion, part of extrusion process, 349
- generic deformation modes in sheet-metal forming, 439
- Gleeble simulator, 96
 - testing, 35
 - working principle of simulator, 96
- grain
 - boundaries, 2
 - as crystals, 3
 - flow in forgings, 8
- graphical tools in FEM analysis, 224
- grid pattern analysis
 - in compression experiment, 249
 - deformation of grid elements, 41
 - in extrusion welding, 237
 - in FEA of compression, 250
 - in shearing experiment, 259
- grid pattern distortions in
 - backward Al-extrusion, 359
 - light slab rolling pass, 379
 - normal slab rolling pass, 385
 - normal wiredrawing, 426
 - strip rolling pass, 390
 - wiredrawing, small reduction, large cone angle, 418
- grid pattern technique, 2, 181
 - advantage of pattern from pins, 184
 - appearance of grid, 182
 - in backward extrusion of Al cup, 290–292, 357
 - contrast materials, 184
 - deformed pattern in extrudate, 183, 188
 - identification of grid elements, 186, 189
 - intrinsic pattern, 184
 - making pattern from contrast pins, 184, 185
 - notation to identify grid lines, 186
 - parting agent to avoid welding, 182
 - perfect deformed pattern in Al-extrusion, 187
 - in plain strain compression, 36
 - scratched patterns, 181
- hardness testing
 - contact pressure, 82
 - indenter, 93
 - test method, 93
- heat
 - capacity, 160
 - effects, 159
 - transfer coefficient, 163
- height strain, 80
- height-to-diameter-ratio, in cylinder compression, 80
- Hensel-Spittel constitutive equation, 118
- high-strain-rate zone in
 - normal wiredrawing, 424
 - plain strain compression, 45
 - rolling, 377
 - wiredrawing, 416
- hollow
 - extrusion dies, 25
 - profile extrusion, 333
- homogeneous deformation in cylinder compression, 109
- Hooke’s law, 73, 115
- hot forming
 - temperature range of, 118
 - vs. cold forming, 34
- hot tearing, 159
 - mechanism in Al-extrusion, 178
- hottest spot in Al-extrusion die, 178
- hydra-wedge for multistep compression, 98
- hydrostatic extrusion, 322
- ideal work method, 204
- impact extrusion, 21
 - backward method, 21
 - forward method, 21
- implicit FEM-method, 222
- inclusions, of MnS, 7
- incremental strain from velocity field, 85

- index notation for stress tensor, 55
- inferior properties due to lamination, 8
- ingot, 19
- inhomogeneous deformation in
 - cylinder compression, 109
 - light slab rolling pass, 379
 - normal slab rolling pass, 383
 - normal wiredrawing from FEA, 425
 - strip rolling pass, 390
- inserts, used in wiredrawing dies, 398
- instability, 18
 - causing necking, 131
 - criterion for start of necking, 104
 - in high slender cylinder compression, 95
 - in tensile testing, 103
- integrity of materials, 128
- interface between die and workpiece, 13
- intrinsic ductility, 128
- inverse modeling, 37
 - determine flow curve in tensile testing, 246
 - determine friction in backward cup extrusion, 299–301
- inverse parameter identification to
 - determine friction, 37
 - get right localized shear, 37
- inverse segregation in extrusion billet, 324
- inward compression, part of extrusion process, 349
- isothermal FEM model, 225
- isotropic materials, 63
- isotropy of sheet-metal, 442
- joining
 - of metal streams in extrusion, 25
 - processes, 9
- Lagrangian description, 222
- lamination, 8
 - in extrusion, 321
- laps, 279
- largest principal stress in normal wiredrawing, 427
- layered appearance, 8
- length
 - strain, transformed to reduction of area, 79
- Lévy-Mises flow rule, 73
- limiting draw ratio, LDR in deep-drawing, 444
- load-stroke curve
 - cylinder compression, 107
 - extrusion, 325
 - forging, 277
 - optimized curve in closed-die forging, 315
- localized necking, 94, 131
- logs of Al, 24
- loss of material, 4
- low-cycle fatigue of dies, 142
- lubricant, 13
 - thick lubricant film through wedge effect, 147
 - viscosity of, 147
- lubricated extrusion, 322
- lubrication
 - boundary film, 147
 - boundary films in, 148
 - in drawing, 397
 - in forging, 271
 - glass in extrusion, 25
 - hydrodynamic, 146–147
 - mechanisms, 144
- Ludvig’s law, 119
- machines, used in metal forming, 13
- machining
 - material removal, 6
- macro etching, 8
- malleability, 128, 269
- manufacturing
 - cheapest process, 7
 - classification system, 9
 - comparison of processes, 4
 - methods, 1
 - of rod and wire, 26
- mass production, 6
- material
 - failure in forming, 127
 - flow phenomena in wiredrawing, 431
 - inhomogeneity on micro-scale, 3
 - loss, 4
 - loss reduction in forging, 314
 - models implemented in FEA, 227
 - removal, 4
- matte surface, hydrodynamic lubrication, 146
- maximum principal stress to explain chevron cracking, 423
- mean through thickness strain rate in rolling, 370
- measurement techniques applied in Al-extrusion, 175
- mechanical properties
 - improved by forming, 4
 - of a material, 103
 - of finished product, 15
- mechanical working to gain high strength, 7
- mechanism of chevron crack formation, 422
- metal flow analysis, 181
- metal flow in
 - direct compared to indirect extrusion, 195
 - Al-extrusion from FEA, 354
 - extrusion, 326–328
 - in FEA, validated experimentally, 354
 - idealized 2D extrusion welding, 235
 - unlubricated direct extrusion, 189–191
- metal forming
 - characteristics of, 4
 - classification system, 9
 - definition of, 1
 - overview of processes, 10
 - requirements for sound process economy, 13
 - simulator, 93
 - stable process, requirement, 7, 13

- metal removal
 - processes, 9
 - by shearing, 30
- metallic bond formed in extrusion welding, 334
- mixed lubrication, 149
- modeling techniques
 - description of methods, 220
 - goal for performing engineering analysis, 219
- model material, 181
- Mohr's circle, 56
 - sign convention, 57
 - for strains, 62
- multistep
 - forming, 19, 98
 - wiredrawing, 398
- near net shaping, 20
- neck
 - average axial stress in, 105
 - as defect in sheet metal forming, 103
 - formation, 18
 - growth in tensile testing, 102
 - radius of curvature in, 105
 - tri-axial stress state in, 104
- necking
 - failure in sheet-metal forming, 130, 441
 - FEM model of, 130
 - instability in, 94
 - localized, 131
 - in tensile testing, 94, 102, 130
- neutral plane in
 - bending, 439
 - plane strain compression, 34
- neutral point in rolling, 367
- node in FEM-mesh, 221
- nominal strain from
 - circle grid analysis, 437
 - tensile test, 102
- nominal stress from tensile test, 101
- nonstationary processes, 84
- normal stress, definition of, 53
- Northon-Hoff constitutive equation, 118
- numerical modeling, 220
- open die forging, 19–20
- optimum die cone angle in wiredrawing, 411
- origin inside billet of surface layer of rod, 195
- outer billet layer, outflow of in extrusion, 329–331
- out of the plane stretching, 438
- overfolding, 279
 - in extrusion, 329
- overloading of tools, 53
- oxide layer, 144
 - oxide layer on
 - Al, 145
 - Al, oxide effect on emissivity, 165
 - Cu, 145
- particle paths, 85
 - in wiredrawing, 429
- pearlite, 2
- peripheral billet skin, flow of in extrusion, 328
- physical
 - in big WUMSI simulator, 98
 - metal forming simulation, 35
 - modeling, 37, 96–101
 - modeling techniques, 220
 - simulation, 92, 96
- pinching, part of extrusion process, 349
- pin measurement of friction, 149
- pipe, defect in extrusion, 181, 331
- plain strain compression
 - applied to sheet metals, 109
 - average contact pressure in, 111
 - effective strain in, 111
 - effective stress in, 111
 - inside channel-shaped die, 95
 - maintain ideal conditions 35, 109, 111
 - mechanics of ideal test, 110
 - relative contact pressure in, 82
 - technological test, 34, 93, 95
 - test to mimic rolling, 109
 - thermal effects in test, 227
 - thickness strain in, 111
 - with overhanging platens, 96
- plain strain
 - tensile test, 436
 - FEM model, 225
- plastic
 - constraint in plain strain compression, 110
 - straining, 4
 - yield, 70, 116
- plasticity theory, 53
- plastic zone, 12
 - geometrical shape of, 81
 - in backward cup extrusion, 286
 - in normal wiredrawing, 424
 - in wiredrawing, 400, 416
- plastification, 4, 53
 - of forming dies, 142
- plate material, 442
- pointing of wire or rod before drawing, 396
- point-tracking, in FEA to trace metal flow, 361
- polymers
 - deformation mechanism, 3
 - deformation of, 1
- porthole die extrusion, 25, 333
- postprocessing results in plain strain compression, 40–50
- postextrusion deformation, avoiding
 - phenomenon, 351

- postprocessing, 224
- power law
 - cold forming, 119
 - hot forming, 122
- power of deformation, 70
- Prandtl-Reuss equations, 222
- precision forging, 20
- predeformation of back end of billet, 193, 328
- preforming in forging, 274
- preform optimization in closed-die forging, 314
- preprocessing, 224
- prescribed circumference of extruded profile, 24
- pressure
 - through boundary interface, 141
 - distribution against die in wiredrawing, 420
- pad, 321
- peak in friction hill in wiredrawing, 420
- peak in friction hill in rolling, 380
- welding, 26
- welding in extrusion, 334
- welding onto the die, 13
- primary
 - dead zone in extrusion, 191, 356
 - deformation zone (extrusion), 190, 322, 356
 - shear zone in extrusion, 356
- principal strains from circle grid analysis, 437
- principal stress
 - definition of, 55
 - distribution of parameter in neck, 243
 - largest value in light slab rolling pass, 382
 - largest value in normal slab rolling pass, 386
 - in plain strain compression, 48
- problem areas, in forming, 12
- process parameters, 14
 - importance of, 14
 - in metal forming, 14
- product in forming, 13
- production processes
 - characteristics of, 6
 - select the best process, 6
- production in low numbers, 6
- productivity, high level of, 13
- profile drawing, 396
- projected length of arc of contact, 368, 372
- punch load, friction effects in backward cup extrusion, 296
- pure shear in torsion test, 111
- pyrometry, 159, 164
- radial compression, part of the extrusion process, 349
- radiation of heat, 159
- Ramberg-Osgoods equation, 119
- recovery, 122
- recrystallization, 7, 122
- redefined strain in compression, 80
- reduction ratio
 - definition of, 77
 - in extrusion, 79
- reduction in
 - percent, 79
 - wiredrawing, 399, 403
- remeshing, 223
 - to get good FEM mesh, 223
- removal of material, 4
- results of FEM-analysis, 224
- retention of peripheral layer of billet, 191, 327
- rigid-plastic materials, 116
- rigid zone, 42
- ring compression test, 149–152
 - measurement technique, 149
 - ring proportions, 151
- riser, in casting, 5
- rod, drawing of, 27, 395
- roll
 - force equation, 367
 - forging, 275
 - gap, 366
- rolling
 - force, 367
 - problem areas, 12
 - processes, 22–23
 - schedule, 23
- roughening rolling mill, 22
- sawing to make workpiece, 7
- scaling defect in extrusion, 330
- scalping operation in extrusion, 324
- scraping of ram against container, 193
- scraping
 - of ram head against container wall, 328
 - part of extrusion process, 349
- scratching
 - at rear end of container, 351
 - part of extrusion process, 349
- secondary
 - dead zone, 191
 - deformation zone, 190, 322
 - shear zone, in extrusion, 356
- section rolling, 22
- security components, 6, 302
- seizure of workpiece in rolling, 376
- selection of forward or backward extrusion method, 324
- semifinished products, 22
- shape change, permanent type, 53
- shaping methods, 1
- shear
 - band formation in plain strain compression, 42
 - cracking, 136
 - cross in cylinder compression, 136
 - flow stress, 71, 143
 - fracture in sheet-metal forming, 441

- shear (*cont.*)
 - layer of moderate shear, 42
 - localization, 138
 - strain in wiredrawing, 426
 - zone in Al-extrusion, 183, 191
- shearing, 10, 30
 - part of extrusion process, 348
 - as technological test, 257
 - FEM model of process, 257
 - to make workpiece, 7
- shear stress
 - at an interface, as process parameter, 14
 - definition of, 53
 - maximum value of, 56
 - positive or negative stress, 55
- sheet material, 442
- sheet metal forming, 9, 18, 27–29
- shiny surface appearance in thin-film lubrication, 146
- shut lap, 280
- Siebel’s drawing force equation, 403
- simulation, 224
- simulative tests in sheet-metal forming, 438
- slab, 22
- slab method, 205
 - applied in cylinder compression, 209–212
 - applied in extrusion, 338
 - applied in plain strain compression, 205
 - applied in rolling, 373
 - die pressure in cylinder compression, 212
 - die pressure in plane strain compression, 208
 - the force balance, 207
 - force in cylinder compression, 212
 - force in plane strain compression, 208
 - general assumptions, 206
- slab rolling, 376
 - description normal pass, 383
- sliding
 - contact zone at rear end of billet, 351
 - against die, plane strain compression, 161
 - friction, 145
- slip
 - in rolling, 367
 - of wire against capstan, 399
- slip line field method, 204
- slow flowing zone in extrusion, 329
- slug in backward cup extrusion, 285
- soft annealed condition, formability of material in, 131
- soft annealing, 27
 - in wiredrawing production, 397
 - of workpiece in backward cup extrusion, 285
- softening, strain-induced, 136
- solid formulation, 222
- spinning, 29
 - tooling in, 29
- split billet technique, 182
- split die principle, to measure friction, 400
- springback
 - because of elasticity, 440
 - compensation by coning of bend, 450
 - compensation by overbending, 449
 - compensation by stretch bending, 450
 - compensation methods, 449
 - phenomenon of, 447
 - prediction in FEA, 227
 - ratio, definition of, 448
 - ratio, experimental data for metals, 448
 - reduced by stretch forming, 29, 440
 - why difficult to predict, 449
- stable drawing as requirement, 399
- stagnant zone in
 - cylinder compression, 109
 - plain strain compression, 41, 45
 - in wiredrawing, 425
- static remeshing, 223
- stationary processes, 84
- steel
 - C-Mn-steels, 2
 - of high strength, 7
- sticking, 143
 - between billet and container, 351
 - friction, 145
- stock material in wiredrawing, 397
- straight line particle movement in wiredrawing, 429
- strain
 - additive nature of true strain, 59
 - conditions in rolling, 369
 - definition of, 58
 - deviatoric, 66
 - effective value of, 67
 - engineering shear strain, 61
 - finding direction of principal strain, 62
 - hydrostatic, 66
 - increment, 58
 - logarithmic, 58
 - maximum shear strain, 62
 - mean strain, 66
 - natural, 58
 - nominal, 58
 - normal strain definition, 61
 - plane strain state, 60
 - principal value of, 62
 - as process parameter, 14
 - shear strain definition, 61
 - transformation from true to nominal value, 59
 - true strain, 58
 - true strain in the neck, 105
 - volume strain, 63
- strain and strain rate from velocity field, 88
- strain hardening, 116
 - as parameter influencing necking, 131
 - exponent, 118

Index

463

- strain-induced softening, 136
- straining to improve mechanical properties, 4
- strain rate
 - conditions in rolling, 370
 - constant value in plain strain compression, 36
 - definition, 67
 - effective value in frictionless compression, 107
 - effective value of, 67
 - as process parameter, 14
 - as tensor, 67
 - sensitivity, 118
 - from velocity field, 86
- strength coefficient, 118
- stress
 - bi-axial, 56
 - components, 55
 - definition of, 53
 - deviator, 65
 - effective value of, 67
 - finding principal stress, 56
 - general state of, 55
 - homogeneous, 54
 - hydrostatic, 65
 - mean (normal) stress, 65
 - nominal, 54
 - plane, 56
 - positive or negative stress, 55
 - states in technological tests, 111
 - tensor, 55
 - transformation, 54
 - transformation by Mohr’s circle, 56
 - true, 54
- stress, strain, strain rate, compared by effective value, 67
- stretch forming, 28
- strip
 - drawing, 149
 - material, 442
 - rolling, 376
 - rolling as cold working process, 388
- subsurface
 - lamination, 321
 - layer of billet, flow of, 328
- subsurface sliding, 143
- surface appearance, speckled, 149
- surface expansion
 - in backward cup extrusion, 297–299
 - in closed-die forging, 316
- surface layer of billet, 24
- surface quality
 - in extrusion, 322
 - friction influence, 139
 - importance of, 13
- surface ring pattern
 - in backward cup extrusion, 299
 - in plain strain compression, 36
 - technique, 199–201
- surface
 - appearance, boundary film lubrication, 148
 - contamination of, 144
 - created in metal forming, 13
 - finish, 13
 - quality, 13
 - skin of billet, outflow of in extrusion, 329–331
- Swift’s equation, 119
- T4-condition, formability of material, 131
- taper, used in extrusion, 332
- technological tests, 92
 - description of test methods, 93
 - mechanics of tests, 92
 - in sheet-metal forming, 437
- temperature
 - conditions in extrusion, 175
 - determined indirectly by microstructure, 176
 - generation in metal forming, 160
 - at hot spot inside extrusion die, 173
 - in the die bearing in extrusion, 172
 - measurement, 164–167
 - as process parameter, 14
 - sensitivity, 118
 - at surface of Al-profile, 176
- tensile cracking, FEA study of tensile test, 134
- tensile strength, 103
- tensile stress cracking, 134
 - FEA of for compression test, 136
- tensile stress zone
 - in normal wiredrawing, 427
 - on outside of bend, 439
 - behind roll gap in normal slab rolling, 387
 - in strip rolling, 392
- tensile testing
 - to find flow curve, 94
 - mechanics of test method, 101
 - as technological test, 93, 94
- tensor
 - to describe strains, 62
 - notation, 55
- theoretical methods in metal forming, 204
- thermal
 - effects, 159–164
 - gradients in forging dies, 167
 - response of thermocouple, 165
- thermal conditions in
 - Al-extrusion, 171–176
 - light slab rolling pass, 380
 - normal slab rolling pass, 387
 - nonstationary forging, 167–169
 - stationary processes, 169–175
 - wire drawing, 170–171
- thermally coupled FEM models, 226

- thermocouple, 159, 165
 - with short thermal response time, 165
- thermomechanical treatment, 7
- thick-film lubrication, 146
- thin film lubrication, 148
- thinning
 - in sheet metal forming, 28
 - 3D-DEFORM[®], 224
 - of wire behind drawing die, 417, 418
- torsion testing
 - deformation without shape change, 96
 - to determine flow stress and ductility, 96
 - as technological test, 93, 96
- transformation of microstructure in steel, 118
- transient, thermal, 164
- Tresca friction model, 140
 - description of, 142–144
 - mathematical expression, 143
- Tresca yield criterion, 71
- trimming
 - of flash, 4, 21
 - by shearing, 30
- true strain from tensile test, 102
- true stress
 - best stress definition, 54
 - from tensile test, 101
- tube drawing, 396
 - using floating plug, 396
 - using internal mandrel, 396
- tube extrusion, 25
- turns of wire over capstan, 399
- 2D-DEFORM[®], 223
- types of metal flow in Al extrusion, 190
- uniform
 - deformation in tensile test, 102
 - energy method, 204
- unlubricated extrusion, 321
- upper bound method, 213
 - in cylinder compression, 216
 - friction sliding energy, 214
 - homogeneous deformation energy, 214
 - inhomogeneous deformation power, 214
 - power consumed in velocity discontinuity, 215
 - power consumption, 213, 342
 - in wiredrawing, 406
- upsetting
 - optimization of process, 331
 - of the extrusion billet, 323
- validation of
 - forging load in closed die forging, 309
 - friction in plain strain compression, 39
 - metal flow in plain strain compression, 39
- velocity
 - in backward cup extrusion, 292
 - components, 86
 - conditions in wiredrawing, 399
 - discontinuities in wiredrawing, 407
 - discontinuity in extrusion, 341
 - discontinuity lines, 214
 - field, 84
 - field in normal wiredrawing, 428
 - requirement to velocity field, 87
- velocity
 - of material particle through roll gap, 365
- visualization in FEA, 225
- Voce’s equations, 119
- volume constancy, 63
- von Mises yield criterion, 71
- Wanheim and Bay’s friction model, 140
- warm forming, temperature range of, 118
- weak
 - layers (z-direction lamination), 8
 - planes, 8
- wear of dies, 13
 - influence of friction, 139
- web of extrusion die, 333
- welding chamber in extrusion, 333
- weld joint of thermocouple, 165
- wire breaks, 26, 397
 - avoiding breaks in drawing, 399, 404
- wiredrawing, 26–27, 395
 - bearing channel, 26
 - as calibration process, 27
 - capstan used in, 26
 - as cold-forming process, 397
 - as continuous process, 26
 - converging die channel, 26
 - experiments of Wistreich, 414
 - force, 404
 - force from Siebel’s equation, 410
 - as industrial process, 397, 399
 - machines, 397
 - parameters in industrial process, 414
 - spooling of the wire, 27
 - tension on the wire, 410
- Wistreich’s experiments, drawing parameters used, 414
- workability, 127, 269
 - of Al-alloys in extrusion, 335
 - judged from tensile test, 94
- working
 - of metal, 19
 - of microstructure, 7
- working conditions, unfavorable in rolling, 383
- workpiece, 1
 - final stage, 13
 - initial stage, 12

Index	465
wrinkling, 19	
in deep-drawing, 444	
in sheet-metal forming, 441	
wrought products, 13	
WUMSI simulator, working principle, 98	
X-ray inspection, 130	
yield criterion, 70	
graphical representation of, 71	
shear stress criterion, 71	
Tresca or von Mises, 71	
yield stress, 103	
Zener-Hollomon constitutive equation, 122	