

Index

Individual exploration strategies are listed in *italics*.

2-D assumption, 22, 29

alcove test, 76

ambiguity elimination, 204

application, proposed

description, 27

impact on map quality, 17, 113

impact on map type, 28–30

ARNE

standard dialogue, 217–218

autonomous map-making, 4, 34

circle test, 73

confirmation threshold, tuning, 145

compliance, 201

confirmed features

number detected, 188–189

properties, 77, 205

updating, 78

contact line, 76

contact point, 75

correspondence problem, 72, 78

cumulative confidence, 42

danger area, shape of, 82

distance transform, 42, 88–93

distinctiveness measures, 18

emergence, 38

entropy, 41

environment model, *see* map

environment model, definition of, 14

environmental traps, 147–148

experimental strategy, 45, 122

exploration

cost, 122–123

reactive and map-based, 121

exploration strategies, 5, 9

mixed, 202

summary of results, 189–195

exploration utility, 42

feature clusters, 76

confirmation, 77

feature set, choice of, 72

free-space boundaries

avoiding multiple visits, 173

choice of step size, 174

experimental results, 176–183

impact of longest-line episodes, 184

implementation, 173–176

need for reactive movements, 175–176

free-space map, 79–83

cell types, 79

dangerous cells, 82

free cells, 80–82

occupied cells, 79

shape of free-space region, 80

unknown cells, 79

width of free-space sector, 81

genetic programming, 39

“go where it’s interesting”, 40–44

graphical user interface, 83

grids, regular, 29

hippocampus, modelling of, 25–26

human-guided exploration

experimental results, 160–161

procedure, 159–160

hybrid architectures, 4, 144, 200

internalized plans, 201

Kalman filter

- measurement model, 100–102
 - setting of parameters, 137
- normality assumptions, 139
- overview, 98
- plant model, 99–100
 - setting of parameters, 136

Kalman gain, 102

landmark disambiguation, 20

localisation, 9, 18, 97–103

- experimental results, 138–140
- orientation errors, 139

locus of interest, 41

longest lines of sight

- danger of traps, 171
- experimental results, 164–170
- implementation, 163–164

map

- area-based, 23–24
- biologically-inspired, 24–26
- closure, 109
- construction, 8
- feature-based, 22–23
- free-space, *see* free-space map
- full metric, 21–24
- metric topological, 20
- probabilistic grid, *see* probabilistic grid map
- quality, *see* quality metric
- strength hierarchy, 4, 17
- topological, 19–20

markers, as exploration aids, 20, 40

moths, navigation of, 16

navigation, model-based and sensor-based, 199–202

neural networks, 19, 22, 24, 41

observability, 41

omniscient observer, need for, 108

orthogonal regression, 77, 215–216

passive mapping, 37

path planning, 9, 87–94

path smoothing, 93–94

PGM, *see* probabilistic grid map

Polaroid ultrasonic sensor, 56–57

precision, premature loss of, 34

predictability continuum, 4, 15

and mapping errors, 200

probabilistic grid map, 30

data dependence, 33

probability

ambiguity of meaning, 30

premature use, 31

quadtrees, 23, 29, 42

quality metric, 9, 105–117

and shape of environment, 114–116

definition, 111–113

effect of hotspots, 142–144

evaluation, 114–117

false positives, 116–117

in previous research, 109

requirements, 105–108

selection of criteria, 113

RCDs

comparison with, 69

definition of, 59

re-examining known objects, 148

recognisable locations, 18–19

regions of constant depth, *see* RCDs

repeating fruitless actions, 148

robotics

behaviour-based, 3

definitions, 1

growth of research interest, 2

reactive, 13

robustness, 16

of map-based navigation, 199

seed-spreader, 44

self-organising maps, 19, 22

sensor orientation test, 75

sightseer, 43

significant turn actions, 19

simulation versus implementation, 6

sonar

echo analysis, 203

model, 8, 24

- multiple transducers, 202–203
- range overestimates, 60
- readings
 - and returns, 59
 - effective beam width, 60
 - numbers of grouped returns, 187–188
 - proportion explained, 188
- reason for use, 7
- testing of
 - experimental technique, 57
 - with convex edge, 61
 - with cylinder, 62
 - with rough corner, 63
 - with rough wall, 66
 - with smooth corner, 62
 - with smooth wall, 57
- variation in signal strength, 58
- state
 - external, 15
 - internal, 14
- statistical significance tests, 124–126
 - paired samples, 124
 - unpaired samples, 124, 125
- supervised wall-following*
 - avoiding fruitless examinations, 151–153
 - avoiding traps, 150–151
 - experimental results, 153–157
 - implementation, 150–153
 - interior and perimeter circuits, 150
 - skipping known objects, 151
- task flexibility, 17
- terrain acquisition*, 43–44
- test environments, 210–214
- test paths
 - evaluation of, 112–113
 - selection of, 111–112
- trace/replay mechanism, 6
- ultrasonic rangefinding, *see* sonar
- “umbilical cord”, 6
- validation gate, 102
 - choice of value, 137
- visibility angle
 - definition, 60
 - experimental results, 68
- wall-following*, 38–40
 - experimental results, 130–132, 140–144
 - implementation, 127–129
 - shortcomings, 147–149
- world model, *see* map