

1

The Wireless World

On Sunday, April 14, 1912, shortly before midnight, the *RMS Titanic* struck an iceberg off the coast of Newfoundland. The radio operator, John Phillips, repeatedly transmitted the distress call CQD in Morse Code. He also sent the newly established signal SOS. Fifty-eight miles away, the *Carpathia* received the messages, and steamed toward the sinking liner. The *Carpathia* pulled 705 survivors out of their lifeboats. Phillips continued transmitting until power failed. He and the other passengers could have been saved if more lifeboats had been available, or if the *California*, which was so close that it could be seen from the deck of the *Titanic*, had had a radio operator on duty. However, this dramatic rescue established the power of wireless communication. Always before, ships out of sight of land and each other were cut off from the rest of the world. Now the veil was lifted. Since the *Titanic* disaster, wireless communications have expanded beyond the dreams of radio pioneers. Billions of people around the world receive radio and television broadcasts every day. Millions use cellular telephones and pagers and receive television programs from satellites. Thousands of ships and airplanes communicate by radio over great distances and navigate by the radio-navigation systems LORAN and GPS.

The enormous increase of wireless communications is tied to the growth of electronics in general, and computers in particular. Often people distinguish between digital and analog electronics. By digital electronics, we mean the circuits that deal with binary levels of voltage, the ones and zeros that are the syllables of computers and calculators. In analog electronics, we deal with voltages and currents that vary continuously. Most systems today actually use a mixture of analog and digital electronics. It is analog electronics that is the focus of this book. We will study the design, construction, and testing of radio circuits and systems. The approach that we take is the progressive construction of a transceiver, the NorCal 40A.

The NorCal 40A transceiver was designed by Wayne Burdick. It is named after the Northern California QRP club. The club is a group of radio amateurs that develop new transceiver designs. QRP is a radio signal indicating a low-power station. Wayne originally designed the NorCal 40 transceiver as a club project, but it proved so popular that the club could not keep up with orders. An improved version, the NorCal 40A, is now available from the Wilderness Radio Company. The NorCal 40A operates in the frequency range from 7.00 MHz to 7.04 MHz, which is the 40-meter amateur band. The NorCal 40A is well suited

for learning electronics. It includes an exceptional variety of interesting analog circuits ranging from audio frequencies to radio frequencies and operates at power levels that vary from a picowatt, or 10^{-12} watts, at the receiver input, to two watts at the transmitter output. Because the transmitter was designed for Morse Code, it produces superb sine-wave signals that are extremely useful in receiver testing. In contrast to cellular telephone circuits, the frequencies are low enough that the signals can be conveniently observed on an oscilloscope, and the level of integration is low, so that the detailed behavior of the circuits can be probed. Because of its history as a club project, the circuits are bullet proof, the components are inexpensive, and the design is open.

1.1 Kirchhoff's Laws

The key quantities in electronics are voltage and current. We will study formulas for voltage and current at two levels. At the bottom, we have *components*, such as resistors, capacitors, and inductors, which have particular relationships between voltage and current. We will study these formulas in the next chapter. We connect components to form a *circuit*. In a circuit, two fundamental laws of physics – conservation of energy and charge – govern voltages and currents. Conservation of energy gives us *Kirchhoff's voltage law*, which applies to a loop of components. Conservation of charge gives *Kirchhoff's current law*, which applies to a junction between components. These laws are named for the German physicist Gustav Kirchhoff. Kirchhoff's laws, together with the current–voltage relations for individual components, allow us to predict what circuits will do.

We can define *voltage* by relating electric charge and potential energy. When a charge moves from one place to another, its potential energy changes. The potential-energy change comes from the force exerted by an electric field. We write the charge as Q and the potential-energy change as E . The units of charge are coulombs, with the abbreviation C, and the units of energy are joules, abbreviated J. See Table 1.1 for a list of units and prefixes that we will use in this book. We can write the voltage V as the ratio of the energy change and charge:

$$V = E/Q. \tag{1.1}$$

The units of voltage are volts, abbreviated as V. We can think of the voltage as the potential energy per unit charge. Often the voltage is called the potential, and that may help make the connection to potential energy clearer. In this connection, it is precise to speak of a voltage *difference*, because the voltage depends on the potential-energy difference between the beginning and ending points. Also, the sign of the voltage depends on the order of the points, and we will often add plus and minus signs to indicate the plus and minus terminals. However, it is typical to consider all the voltages relative to a single reference point, the *ground*, which in an electronic circuit is often the metal box. We will often talk about the voltage at some point in a circuit, and by this, we mean the voltage relative to the reference

Table 1.1. Units (a) and Prefixes (b), and Their Abbreviations.

Quantity	Symbol	Unit	Abbr.	Prefix	Multiplier	Abbr.
voltage	V	volt	V	atto	10^{-18}	a
charge	Q	coulomb	C	femto	10^{-15}	f
energy	E	joule	J	pico	10^{-12}	p
current	I	ampere	A	nano	10^{-9}	n
time	t	second	s	micro	10^{-6}	μ
resistance	R	ohm	Ω	milli	10^{-3}	m
conductance	G	siemen	S	kilo	10^3	k
power	P	watt	W	mega	10^6	M
capacitance	C	farad	F	giga	10^9	G
inductance	L	henry	H	tera	10^{12}	T
length	l	meter	m	peta	10^{15}	P
frequency	f	hertz	Hz	exa	10^{18}	E
absolute temperature	T	kelvin	K			
temperature, Celsius	T	degree	$^{\circ}\text{C}$			
pressure	P	pascal	Pa			

(a)

(b)

Note: We use the MKS (meter-kilogram-second) system, so that the expressions we derive will be combinations of these units. A few dimensions are also given in centimeters (cm). It is important to distinguish between upper and lower case. For example, one could mistake milli (m) for mega (M), or kilo (k) for kelvin (K). We use both the absolute temperature scale and the Celsius scale. The unit has the same size in each scale, but the zero is different. For absolute temperature, the zero is absolute zero. For the Celsius scale, the zero is the ice point of water, which is 273.15 kelvins on the absolute scale.

ground. We shall also speak of the voltage drop *across* a resistor or capacitor, and this is the voltage difference between the connecting wires.

We can apply our voltage definition to a circuit with components connected in *parallel* (Figure 1.1a). A parallel connection forces the voltage across each component to be the same because we calculate the voltage across each component at the same points:

$$V_1 = V_2. \quad (1.2)$$

It is more interesting to consider the voltages for components connected in a loop (Figure 1.1b). Consider a charge at point P . When we move the charge around the loop, the potential energy changes at each component. If we return to P , the potential energy returns to its initial value. We say that the potential energy is *path independent*. This is true as long as the magnetic-field changes inside the loop are not important. We will consider the effect of magnetic fields when we study inductors. This means that the sum of the voltages around the loop is zero:

$$0 = \sum_i V_i, \quad (1.3)$$

where i is an index for the components. This is *Kirchhoff's voltage law*, and it is a statement of the conservation of energy. You have to be careful about the




Figure 1.1. Parallel connection (a) and connecting components to form a loop (b). Kirchhoff's voltage law applies to a loop.

signs of voltages when you apply the formula. You might test yourself on your understanding of Kirchhoff's law by considering the parallel circuit in Figure 1.1a as a simple loop.

The *current* is the flow of charge past some point. The units are coulombs per second, or amperes (A). Often this is shortened to "amps." We will talk about the current *through* a wire or a component. Like the voltage, we will need to be careful about signs, and we will add arrows to indicate the positive direction. We can apply our current definition to a series connection (Figure 1.2a). If the current does not leak out along the way, the current in both components must be the same, and we write

$$I_1 = I_2, \quad (1.4)$$

where I is the traditional letter for current. For a junction between several components (Figure 1.2b), if charge does not pile up at the junction, positive current in




Figure 1.2. Series connection (a) and a junction between several components (b). Kirchhoff's current law applies to a junction between components.

some components must be offset by negative current in others, and we can write

$$0 = \sum_i I_i. \quad (1.5)$$

In words, the net current at a junction must be zero. This is *Kirchhoff's current law*, and it is a statement of conservation of charge. Test yourself on Kirchhoff's current law by considering the series circuit in Figure 1.2a as a simple junction.

Since the voltage is energy per charge, and the current is the rate of charge flow, we can find the power, which is the rate at which work is done, by multiplying voltage and current. We write the power P in watts (W) as

$$P = VI. \quad (1.6)$$

In a radio transmitter, power radiates into the air from an antenna as radio waves. In an audio system, power radiates from a speaker as sound. It may also go into heat, and we will have to watch carefully to see how hot our components get.

1.2 Frequency

In radio engineering, we commonly use voltages and currents that are cosine functions of time. For example, we might write a voltage $V(t)$ and a current $I(t)$ as

$$V(t) = V_p \cos(2\pi ft), \quad (1.7)$$

$$I(t) = I_p \cos(2\pi ft). \quad (1.8)$$

In these expressions f is the *frequency*. The units of frequency are hertz (Hz), after the German physicist Heinrich Hertz who first demonstrated radio waves. The frequency is the number of cycles of the cosine that are completed in one second. Often the zero of the time scale will not be important. In fact, if we shift the time scale by a quarter of a period, the cosine becomes a sine. This means that we could use sine functions if we wanted instead of cosine functions. In these formulas, V_p and I_p are called *peak amplitudes*. In the laboratory, we will often see cosine voltages on an oscilloscope, where the zero of the voltage scale may not be clear. For this reason, people usually measure the peak-to-peak voltage, V_{pp} , shown in Figure 1.3, rather than the peak voltage. The peak-to-peak voltage is twice the




Figure 1.3. Peak and peak-to-peak voltages.

peak voltage. It is important to keep track of whether one is talking about peak voltage, which is easier to use in mathematical formulas, or peak-to-peak voltage, which is easier to measure on an oscilloscope.

We can calculate power by multiplying voltage and current. We write

$$P(t) = V(t)I(t) = V_p I_p \cos^2(2\pi ft). \quad (1.9)$$

The power is not constant as it is for a steady voltage and current. We can separate the power into a steady part and a variable part by writing

$$P(t) = \frac{V_p I_p}{2} + \left(\frac{V_p I_p}{2} \right) \cos(4\pi ft). \quad (1.10)$$

The last term has zero average value, and so we can write the average power P_a as

$$P_a = \frac{V_p I_p}{2}. \quad (1.11)$$

The factor of 2 in the denominator takes into account the fact that the voltage and current vary over a cycle. This formula is for peak amplitudes. In terms of peak-to-peak amplitudes, the average power becomes

$$P_a = \frac{V_{pp} I_{pp}}{8}. \quad (1.12)$$

These formulas depend on the fact that the voltage and current are synchronized so that they are both cosines. This is the situation for a resistor or a properly adjusted antenna. However, for a capacitor or an inductor, one waveform is a cosine and the other is a sine. The power becomes

$$P(t) = V_p I_p \sin(2\pi ft) \cos(2\pi ft) = \left(\frac{V_p I_p}{2} \right) \sin(4\pi ft). \quad (1.13)$$

The average power is zero. This means that an inductor or capacitor does not consume power. However, we will see in the next chapter that they can store energy.

Radio waves travel at the speed of light, and this means that we can write a simple relation between the frequency f and the wavelength λ (the Greek letter *lambda*) as

$$f\lambda = c, \quad (1.14)$$

where c is the velocity of light, given exactly as

$$c = 299,792,458 \text{ m/s}. \quad (1.15)$$

For our purposes, 3.00×10^8 m/s is close enough. It is useful to be able to convert between wavelength and frequency quickly. To do this, divide the quantity that you know into 300:

$$f \text{ (MHz)} = 300/\lambda \text{ (m)} \quad \text{or} \quad \lambda \text{ (m)} = 300/f \text{ (MHz)}. \quad (1.16)$$

One reason that the wavelength is important is that it determines the antenna size. Transmitting antennas need to be at least an eighth wavelength long to be efficient. If the antenna is much shorter than this, most of the power will heat up the wire rather than radiate as radio waves. For example, consider an AM station

transmitting at 1 MHz, where the wavelength is 300 m. A large tower must be used for the transmitting antenna. This wavelength would not be suitable for portable telephones. In contrast, cellular phones use frequencies near 1 GHz, where the wavelength is 30 cm, and the antennas need only be a few centimeters long.

At any time, there are thousands of radio services in use around the world. Radios avoid interfering with each other by transmitting on different frequencies. Television stations do the same thing, but the different frequencies are called channels. In cellular phones the process is more complicated. In some systems, different frequencies are assigned. These frequencies may change as a car moves from the area covered by one antenna to another. In other cellular phone systems, the phones may share a range of frequencies with other users but transmit with different codes that allow them to be distinguished. The frequency bands that can be used for different applications are assigned by the Federal Communications Commission (FCC) in the United States and the corresponding communications authorities in other countries. Radio waves propagate long distances, and for this reason, the different communications authorities cooperate to help keep transmitters in different countries from interfering with each other. One factor in assigning frequencies is that waves at different frequencies travel different distances. For example, frequencies below 30 MHz can propagate around the world by reflecting off the ionosphere. Another factor is that some services like TV need large channel spacings. Each TV channel takes up 6.5 MHz. In contrast, AM stations are 10 kHz apart, and stations communicating by Morse Code may be only 500 Hz apart. Table 1.2 gives the names for the radio bands.

Fundamentally, radios are limited by unwanted signals that are at the same frequency as the signal we want. Sometimes these signals are produced by other

Table 1.2. Naming Radio Bands.

VLF (<i>very low frequency</i> , 3–30 kHz, or 100–10 km) – submarine communication (24 kHz)
<i>long wave</i> (30–300 kHz, or 10–1 km) – LORAN navigation system (100 kHz)
<i>medium wave</i> (300 kHz–3 MHz, or 1 km–100 m) – AM radio (500–1,600 kHz)
HF (<i>high frequency</i> or <i>short wave</i> , 3 MHz–30 MHz, or 100–10 m) – international broadcasting, air and ship communication, amateur communication
VHF (<i>very high frequency</i> , 30 MHz–300 MHz, or 10–1 m) – television (channels 2–6: 54–88 MHz), channels 7–13: 174–216 MHz) and FM radio (88–108 MHz)
UHF (<i>ultra high frequency</i> , 300 MHz–1 GHz, or 1 m–30 cm) – television (channels 14–69: 470–806 MHz), cellular telephone (824–894 MHz)
<i>microwaves</i> (1–30 GHz, or 30–1 cm) – GPS (1.575 GHz), PCS (personal communications services, 1.85–2.2 GHz), ovens (2.45 GHz), satellite TV (C-band: 3.7–4.2 GHz and Ku band: 10.7–12.75 GHz)
<i>millimeter waves</i> (30–300 GHz, or 10–1 mm) – This is the frontier and many applications are under development: car radar (76 GHz), computer networks inside buildings (60 GHz), aircraft landing in fog (94 GHz).
<i>submillimeter waves</i> (frequencies greater than 300 GHz, wavelengths less than 1 mm) – These frequencies are strongly absorbed by water vapor, and this limits them to scientific applications such as radio astronomy and fusion-plasma diagnostics.

Note: The frequency and wavelength ranges are identified, together with the prominent applications.

transmitters at the same frequency, and we call this *interference*. In addition, there are natural radio waves that are called *noise*. Noise appears at all frequencies, and the noise at the receiver frequency is treated just the same way as the signal we want. We hear the noise from a speaker as *hiss*. In a television receiver, noise makes speckles on the screen that we call *snow*. There are many sources of noise. For example, at the frequency used by the NorCal 40A, 7 MHz, the most important noise source is lightning in tropical thunderstorms. The transistors in a transceiver also produce noise, but typically the power is a thousand times less than the lightning noise. However, if the antenna is small, the lightning noise is not received well, and the transistor noise can dominate. At higher frequencies the noise may be quite different. For example, in the UHF TV channels between 400 and 800 MHz, radio waves from the center of the Milky Way dominate. At 12 GHz, which is used for satellite TV transmissions, the most important noise may be radio waves from the earth's surface.

In the simplest form, a radio communications system consists of a *transmitter*, with its antenna to launch the radio waves, and a *receiver*, with its antenna to receive them. In TV and radio broadcasting, that is all there is, but for two-way communications we need a transmitter and a receiver at each end. Typically these are combined in one box to make a *transceiver*. In the NorCal 40A transceiver, the transmitter and receiver share an oscillator circuit that determines the operating frequency, and they share the antenna.

1.3 Modulation

A cosine waveform by itself does not tell us much. Usually we would like to send a message, which might be an audio signal or a digital signal made up of 1s and 0s from a computer that might represent almost anything. We can include the message in our transmitted signal by varying the amplitude or frequency. This is called *modulation*. In *amplitude modulation*, or AM, we vary the amplitude. This is used in AM radio stations. For example, if we have an audio signal $a(t)$, we get an amplitude-modulated signal by using it as the amplitude:

$$V(t) = a(t) \cos(2\pi ft). \quad (1.17)$$

The signal $a(t)$ is called the *modulating waveform*. Usually the voltage is not transmitted in this form. We will see when we build an AM detector that it is easy to recover the audio voltage if a cosine is added:

$$V(t) = V_c \cos(2\pi ft) + a(t) \cos(2\pi ft). \quad (1.18)$$

Here $V_c \cos(2\pi ft)$ is the *carrier*. AM radio stations use this kind of signal. An AM modulated waveform is shown in Figure 1.4a.

We can also modulate by varying the frequency. This is *frequency modulation*, or FM. We can write an FM signal in the form

$$V(t) = V_c \cos(2\pi(f_c + a(t))t). \quad (1.19)$$




Figure 1.4. AM waveform (a) and FM waveform (b). In each case, the modulating signal is a cosine function. In AM, the amplitude changes, but the frequency stays the same. In FM, the frequency varies, but the amplitude is constant.

An FM waveform is shown in Figure 1.4b. FM signals usually require wider channels than AM signals, but FM systems are usually better at rejecting noise and interference. For this reason FM stations often program music, which is quite sensitive to noise. In contrast, AM stations often emphasize talk shows and news, which are less bothered by noise. Television uses both AM and FM – AM for the picture, and FM for the audio.

For digital signals, a variety of modulation types are used. The oldest is Morse Code, which may properly be considered digital modulation. In Morse Code, the letters are sent as a series of short and long pulses (*dits* and *dahs*), and different lengths of spaces are used to separate letters and words. This could be considered a form of AM. Morse Code is traditionally sent by hand and decoded by ear. A different approach that is better suited for machine reception is to use one frequency for a 1 and another frequency for a 0. We write

$$V(t) = \begin{cases} V_p \cos(2\pi f_1 t) & \text{for a 1,} \\ V_p \cos(2\pi f_0 t) & \text{for a 0.} \end{cases} \quad (1.20)$$

You will also hear these called *mark* and *space* frequencies. This approach is called *frequency-shift keying*, or FSK, and it is a form of frequency modulation. An FSK signal is shown in Figure 1.5a. Another approach is to keep the frequency the same, but to change the sign of the voltage. This is called *phase-shift keying* or




Figure 1.5. An FSK waveform (a) and a PSK waveform (b). The modulating signal in both cases is a series of alternating 1s and 0s.

PSK (Figure 1.5b):

$$V(t) = \begin{cases} +V_p \cos(2\pi ft) & \text{for a 1,} \\ -V_p \cos(2\pi ft) & \text{for a 0.} \end{cases} \quad (1.21)$$

Some of the most sophisticated modulation approaches are found in computer modems, where a combination of amplitude shifts and phase shifts are used.

1.4 Amplifiers

The radio signals that are received by an antenna are often weak, with typical power levels in the range of one picowatt. To make the level convenient for listening, a huge increase in the power is required, in the range of a factor of a billion. The device that does this is called an *amplifier*, and it is key to all electronic systems. Early amplifiers were made with vacuum tubes, but most amplifiers now are made with transistors, which are smaller and lighter. Vacuum tubes can handle much more power than transistors, however, so they are still found in high-power transmitters. We will study several different amplifiers in the NorCal 40A. An amplifier is characterized by the *gain*, which is the ratio of output power to input power. We write the gain G as

$$G = P/P_i, \quad (1.22)$$

where P is the output power and P_i is the input power. Figure 1.6a shows the symbol for an amplifier that is used in circuit diagrams. Amplifiers also appear in transmitters, because the signals are initially generated in low-power oscillators and therefore must be amplified.

1.5 Decibels

In radio systems, power varies by enormous factors. International broadcasters may transmit as much as a megawatt. Receivers work with signals that may be




Figure 1.6. (a) Symbol for an amplifier that appears in circuit diagrams. The symbol is a triangle that indicates the direction of power flow. (b) Operation of a mixer. The symbol for a mixer is a circle with a large \times inside it to indicate multiplication. The inputs and outputs are distinguished by arrows.