

Index

- 6LoWPAN, 172
- 802.11a, 140
- 802.11p, 134, 308
- access point, 124
- active scanning, 143
- adaptive frequency hopping, 40, 82, 90, 183
- address map, 170
- address tracking, 66
- advanced ad hoc on-demand distance-vector routing algorithm (AODV), 166
- advanced audio distribution profile, 110
- advanced encryption standard (AES), 78
- advertising channel, 184
- advertising packet, 185
- aggregate attributes
- alternate MAC/PHY, 87, 113, 206
- antenna detuning, *see* detuning
- antenna diversity, 252
- antenna gain, 30, 246
- application layer (APL), 157
- application-specific devices, 277
- application support layer (APS), 157
- assisted living, 304
- association, 125, 128, 227
- asynchronous links (ACL), 97
- attribute protocol, 196
- attributes, 197
- audio, 56, 110, 223
- authentication, 48, 67, 128
- authorisation, 66
- automated meter reading, 309
- base service set, 123
- baseband, 20
- BER, *see* bit error rate
- binary long object, 198
- bit error rate, 27
- bluejacking, 63
- bluetooth network encapsulation protocol, 108
- bonding, 102, 195, 227
- bridging, 125
- broadcast, 165, 199, 232
- broadcast transaction table (BTT), 165
- broadcaster role, 181
- cable replacement, 11, 43, 209
- cellular working group – RF, 277
- central role, 182
- ceramic antenna, 251
- characteristics, 200
- chipping rate, 34
- class, 30, 85
- cluster network, 46
- cluster tree, 155, 220
- codec, 110, 224
- coexistence, 36, 253
- colocation, 40, 255
- commissioning, 57, 227
- Continua Health Alliance, 109, 268, 301
- continuously variable slope delta modulation, 99, 224
- coordinator, 47, 153, 168
- data channel, 184
- dBm (definition), 30
- deauthentication, 128
- dedicated short range communications, 122, 306
- denial of service, 62
- detuning, 249
- direct sequence spread spectrum, 131, 150
- directionality, 246
- disassociation, 128
- discovery, 62, 101, 184, 193
- distribution coordination function, 136
- distribution services, 128
- DoS, *see* denial of service
- dual-mode, 205
- duty cycle, 51, 179, 257
- dynamic frequency selection (DFS), 130

330 INDEX

- eavesdropping, 62
- encryption, 48, 68, 128, 269
- end product listing, 275
- endpoint, 168
- energy harvesting, 261, 320
- enforcement program, 9
- enhanced data rate (EDR), 82, 86
- equivalent isotropically radiated power, 30
- eSCO, *see* extended SCO
- export controls, 269
- extended rate PHY, 139
- extended SCO, 54, 98
- extended service set, 124

- feature creep, 232
- file transfer profile, 108
- filters, 244
- forward error correction, 33, 97
- fractal antenna, 250
- frequency agility, 73, 151
- frequency hopping, 39, 89
- full function devices, 152

- games controllers, 4
- gateway, 203
- general discovery, 193
- generic access profile, 102, 196
- generic attribute profile, 196
- generic object exchange profile, 106
- GoogleHealth, 302
- ground plane, 245, 249

- hacking tools, 79
- handsfree profile, 105
- health device profile, 109
- healthcare, 6, 299
- HealthVault, 302
- helical antenna, 250
- hierarchical network, 47
- high-speed channel, 82
- HiperLAN, 130
- home automation, 7, 314
- host–controller interface, 99, 196
- human interface device, 109, 258
- HVAC, 171, 315

- independent base service set, 123
- indications, 199
- industrial automation, 7, 319
- initiator, 188

- inquiry, 92, 95
- insertion loss, 245
- integration, 128
- intellectual property, 271
- interception, 62
- interference, 37, 130, 141, 253
- Internet connected devices, 5, 316
- Internet of things, 13
- interoperability, 52

- L2CAP, *see* logical link control and adaptation protocol
- latency, 18, 53, 179, 211, 216, 224
- limited discovery, 193
- link budget, 28, 161, 239, 246
- link key, 70
- link layer common adaptation layer, 196
- link manager, 99
- local binding table, 170
- local groups table, 170
- local name, 194
- logical link control and adaptation protocol, 101
- low noise amplifiers, 240

- man-in-the-middle attack, 63
- master–slave role switch, 96
- media access controller, 20, 152
- memory requirements, 217, 235
- mesh network, 47, 220
- modular approval, 266
- modules, 288
- MSDU delivery, 128
- multicast, 165
- multi-channel adaptation protocol, 104
- multipath fading, 42
- multiple input, multiple output (MIMO), 141, 252
- multipoint, 43, 215

- near-field communication, 69, 230
- network allocation vector, 135
- network layer (NWK), 157
- notifications, 199

- OBEX, 106
- object push profile, 108
- observer role, 181
- obsolescence, 295
- open field, 25
- open source, 279

- organisationally unique identifier, 164, 280
- orthogonal frequency division multiplexing, 139
- OUI, *see* organisationally unique identifier
- out of band, 69, 230
- paging, 92, 94
- pairing, 102, 227
- passive scanning, 144
- PCB design, 242, 244
- peer-to-peer, 154
- peripheral role, 182
- personal area networking profile, 108
- physical layer convergence procedure, 138
- piconet, 43, 91, 180
- point to point, 43
- polarisation, 248
- power amplifiers, 240
- power consumption, 49, 111, 256
- power control, 85, 243
- power management, 144
- printed antenna, 250
- privacy, 320
- production test, 281
- profiles, 22, 52, 104, 202, 221
- promiscuous connections, 228
- proprietary wireless, 11
- proximity, 318
- QoS, *see* quality of service
- qualification scheme, 9
- quality of service, 53, 54, 98, 119, 154
- R&TTE, 267
- RAND license, 272
- RANDZ license, 272
- range, 18, 25, 179, 211, 239
- reassociation, 127, 128
- receive sensitivity, 29, 86, 130, 150, 240
- received signal strength indication, 85
- reconnection, 214
- reduced function devices, 152
- reference designs, 287
- regulatory approval, 264
- reliable transmission, 55
- remote control, 7, 171
- repeaters, 34
- response packet, 186
- RF matching, 244
- RF4CE, 171
- RFCOMM, 104
- roaming, 127
- route discovery, 166
- router, 168
- RS-232, 209, 223
- rubber duck antenna, 250
- scatternet, 46, 87
- secure simple pairing, 72, 82, 104
- security, 18, 48, 60, 233
- serial port profile, 105
- service discovery protocol, 101
- shared bandwidth, 216
- sleep modes, 259
- smart energy, 6, 171, 309
- sniff mode, 111
- sniff sub-rating, 112
- specific absorption rate, 268
- spectrum usage, 39
- spoofing, 63
- SSID, 123
- star topology, 153
- start-ups, 3
- station services, 128
- superframe, 54, 155
- synchronous transmission, 53
- telematics, 305
- temperature, 261
- throughput, 18, 34, 211, 239
- time synchronisation, 226
- timeslot, 43, 54, 89, 111
- topology, 12, 18, 42, 121, 154, 180, 209, 260
- transmit power, 29, 50, 86, 150, 180, 239
- transmit power control (TPC), 130
- tree network, 46
- trust centre, 73
- UART, 99
- unicast, 165
- upgradability, 234
- usability, 57
- USB, 99, 209, 223
- video, 56
- voice, 5, 53, 223
- wibree, 176
- Wi-Fi Alliance, 117

332 INDEX

- Wi-Fi Multimedia (WMM), 120
- Wi-Fi Protected Access (WPA),
77, 119
- Wi-Fi protected set-up, 120
- wired equivalent privacy (WEP), 77
- WirelessHART, 174
- WMM power save, 145
- ZigBee cluster library, 168
- ZigBee compliant platforms, 278
- ZigBee coordinator, 157
- ZigBee device object (ZDO),
168
- ZigBee device profile (ZDP),
168
- ZigBee endpoint, 157, 164
- ZigBee PRO, 160
- ZigBee router, 157