

Index

- (110) plane, schematic illustration, 36
- (111) plane, schematic illustration, 35
- $\langle 111 \rangle$ family of directions, 35
- 18 carat gold implant, 515
- 2-D stress state, 259
- 316L stainless steel alloy, 61
- 3D CT scans, 537
- 3-D problem, simplifying, 261
- 510(k), *see also* Pre-Market Notification (510(k))
- AAOS (American Academy of Orthopaedic Surgeons), 620
- AbioCor Replacement Heart, 495
- abrasive wear, 382–3
- abrasive wear particles, 383
- abutment(s), 513, 620
 - designs, 525
 - geometries, 526
 - head, 525
 - of same materials as the implant body, 525
 - screw, 525, 527
 - teeth, 512
- acetabular cup, 620
 - delamination of highly crosslinked UHMWPE, 462–3
 - femoral head penetration into, 237
 - highly resistant to wear, 424
 - socked portion of the joint, 424
 - total hip replacement utilizing an UHMWPE, 117
 - as polymer of choice for, 432
- acetabulum, 620
- ACL, *see* anterior cruciate ligament (ACL)
- AcroFlex design, 455
- AcroFlex lumbar disk
 - replacements, 455, 469–70
- acrylic bone cement (PMMA), 431, 433
- AcrySof IOL, 583
- activation volume, 110, 620
- active materials, 71
- addition reaction, 106, 620
- adhesion, 375
- adhesive wear, 381–2
- adulterated, 620
- adventitia, 155, 481, 620
- age hardening, 48, 620
- aged dentin, 139
- aggregated proteoglycans, loss of, 532
- Albee, Fred, 453
- Alcmaeon of Crotona, 129
- all-ceramic implant bodies, 523
- Allergan, Inc., 586
- Alloderm dermal implant, 577
- allografts, 572, 577
- alloplastic, 620
- alloplastic interpositional materials, 533
- alloplastic material, for dental implants, 505
- alloys, 17, 620, *see also* specific alloys, *see also* medical alloys
- alloys
 - altering structure and properties of, 42
 - imperfections in, 38–42
- AlphaCor implant, 582
- alumina, 80, 86
- alveolar bone, 528
- alveolar crest, 508
- alveolar processes, 508
- American Academy of Orthopaedic Surgeons (AAOS), 620
- American Burn Association, 575
- American National Standards Institute (ANSI), 409
- American Society for Testing and Materials, *see also* ASTM International
- American Society for Testing Methods (ASTM), standard for surgical grade stainless steel, 417
- Amonton's Law, 375
- amorphous ceramics, forming, 83
- amorphous polymers, 98, 620
 - lacking order, 98
 - randomly ordered or entangled chains, 103
 - T_g characterization plot, 103
 - uses of, 106
- amorphous silicate glasses, 71
- amplitude loading, 341, 350
- anabolic, 620
- anabolic functional loads, 527
- anatomical study, 129
- ANCURE Endograft System, 497–8
- aneurysms, 489, 620
- angina, 489
- angioplasty, 620
- angioplasty catheter, 11
- anion coordination number, 72
- anions, 72, 620
- anisotropic, 620
- anisotropic behavior, of an arterial graft, 11

- anisotropic composite systems, 19
- anisotropic material, Hooke's Law for, 184
- ankylosing spondilosis, 458, 620
- ankylosis, 532, 533, 620
- annealing, 46, 48, 621
- annulus, 621
 - composed of concentric sheets of collagen, 457
 - of each disk, 457
 - preserving, 454
- annulus fibrosus, 457
- anode, 55
- anodic materials, 55
- Anonymous Seven from Guidant
- anterior cruciate ligament (ACL), 572
 - 1–2 million cycles per year, 573
 - designs, synthetic, 572–3
 - implants, comparing failure load and stiffness, 574
 - patellar tendon as donor site, 571
 - permanent augmentation devices, 572
 - permanent replacements, 572
 - reconstructive surgeries, 570
- anti-coagulant medications, 487
- AO/ASIF implant, 535
- aorta, 481
- aneurysm in, 489
 - tensile strength, 156
- aortic arch, 156
- aortic valve, 479
- apatite form, of calcium phosphate, 86
- apex, 514, 621
- apical foreman, 508
- Apligraf, composite implant, 578
- apparent modulus, 224
- appendicular, 621
- applied crack driving force, 319
- applied mechanics, 130
- applied stresses, 36, 183
- arbitrary plane, intersecting the y and z axes, 34
- area moment of inertia, 196, 621
- Arrhenius equation, 110
- Arrhenius empirical model, 627
- arterial lumen, reduction of, 477
- arterial tissue, cross-section of, 481
- arterial wall, multi-layered structure of, 155
- arteries, 481, 621
- arthoplasty, early, 416
- arthrodesis, 454, 459, 621
- arthroplasty, 621
- arthroscope, 533, 621
- arthroscopy, 533
- artia, 480
- articular cartilage, 151–4, 621
 - collagen fiber network of, 153
 - composition of, 152, 214, 422
 - limited capacity for self-repair, 151
 - microstructure and ultrastructure of, 152
 - non-equilibrium properties, 154
 - providing lubrication and smooth articulation, 435
 - surgical repair difficult, 152
 - time-dependent strain under deformation, 215
 - viscoelastic behavior of, 214
- articular disks, 533, 534
- articular eminence, 509
- articular surfaces, of the TMJ, 538
- articulation, 276, 621
- artificial intervertebral disk, 180
- artificial skin, 575–6, *see also* skin
 - as a more modern construct, 561
 - current designs for, 576–8
 - functional requirements of, 578
 - uses for, 575
- asperities, 371, 621
- astigmatism, 583, 621
- ASTM D638
 - Standard Test Method for Tensile Properties of Plastics, 409
- ASTM F562 alloy, 62
- ASTM F75, cast form of cobalt-chromium, 62
- ASTM F799 alloy, improved mechanical properties, 62
- ASTM F90 alloy, utilizing addition of tungsten and nickel, 62
- ASTM G115–04
 - Standard Guide for Measuring and Reporting Friction Coefficients, 389
- ASTM International, 61, 408, 621
- ASTM specifications, for wrought Co–Cr alloys
 - used in medical implants, 62
- ASTM Standards E466–E468 (American Society for Testing and Materials), 335
- atherosclerosis, 477, 483, 621
- atlas vertebra, 456
- atomic force microscopy (AFM), 134, 387, 388
- atomically bonded solid, 285
- atoms, extra half plane of, 39
- atria, 479, 621
- austenite, 49, 621
- austenitic stainless steel, 61
- Australia, Therapeutic Goods Association (TGA), 411
- autoclave, 621
- autoclaving, 8
- autogenous, 621
- autogenous bone grafts, 89
- autografts, 487, 572, 577
- auto-immune disease, caused by breast implants, 587
- autologous, 621
- autologous tibial grafts, 453
- autologous transplants, for vascular grafts, 478
- average roughness, 371
- axial load
 - stress due to, 204
 - stressing a part cross-section, 346
- axis vertebra, 456
- Braun Melsungen AG, 589
- bacteria, housed in the human mouth, 510
- bacterial contamination, elimination of, 8

- ball and socket articulation mechanism, of the hip, 425
- balloon angioplasty catheter, properties of, 11
- balloon angioplasty, compressing plaque, 483
 - balloon catheter, 483, 621
 - polymers in, 94
 - stent shipped over outside of, 483
 - used in percutaneous transluminal angioplasty, 493
- balloon-expanded stent delivery, 483, 484
- Barenblatt, 305, 307
- basement membrane, Type IV
 - collagen in, 133
- Basquin equation, 337, 338, 340
- Basquin exponent, 337
- BCC, *see also* body-centred cubic (BCC)
- beam equation, development of, 193–7
- beam theory, 169
- basics of, 193–7
 - derivation for, 194
 - model for certain loading situations *in vivo*, 205
 - solving stresses, 267
- beam, under bending moment, 194
- bearing pair, for the hip, 426
- behavior regimes, for viscoelastic material, 210
- bending load, stress due to, 204
- bending modulus, for hydrated elastic fibers, 134
- bending moment, 193, 194
- Bernoulli, Daniel, 194
- biaxial stress states, 256
- bicuspid, 621
- bicuspid pre-molars, 507
- bileaflet heart valve
 - design, 78, 79
 - inherent stress concentrations, 78
- bileaflet valves, 487
- bioactive, 621
- bioactive ceramics, 71, 85
 - in the form of coatings, 86
 - relying on porosity, 84
 - use of, 433
- bioactive glass, 86, 425, 622
- bioactive polymers, 113
- Biobrane, 577
- Bioceram, recent withdrawal of, 524
- biocompatibility, 7–8, 622
 - analysis of, 7
 - assessment of, 7
 - definition of, 7
 - necessity for, 60
 - of any implantable device, 4
 - of ceramics, 85
 - of cobalt-chromium-molybdenum alloys, 506
 - of polymers, 113
 - studies, 417
- biocompatible, 622
- biocompatible materials, limited number of, 7
- biodegradable, 622
- biodegradable ceramics
 - composed of calcium phosphate, 86
 - used as bone substitutes, 86
- biodegradable materials, 71
- bioglass, 71, 87
- Biolimus, 485
- biological attack, long-term resistance to, 7
- biological inflammatory response, 65
- biological materials, prone to immunorejection or normal resorption processes, 15
- biological system, interactions with mechanically damaged synthetic biomaterial, 8
- biological tissues, 13
- biological valves, reducing risk of clotting, 487
- biomaterials
 - as hard or soft, 13
 - classifying, 13–16
 - complicated mechanical behaviors of, 208
 - exhibiting viscous or fluid-like characteristics, 318
 - experiencing forces or loads, 167
 - overview of, 4
 - restoration of function of a living being, 13
 - specimen configuration requirements for, 303
 - surface contact in, 386–7
 - testing for friction and wear properties, 370
- biomaterials science, 4
- BioMatrix stents, 485
- biomechanics, 130
- bioprosthetics, 486
- bioreactivity, 622
 - customizable, 72
 - illustrating spectrum of, 85
 - polymers range of, 94, 113
 - schematic illustration showing, 85
 - tailoring from inert to fully resorbable, 85
- bioresorbability, of certain polymers, 19
- bioresorbable, *see also* biodegradable
- bioresorbable ceramics 85
- bioresorbable polymer sutures, 124
- bioresorbable polymers, uses of, 94, 113
- bioresorbable suture anchor, 92
- biotribology, study of, 387
- bisphosphonates, 530, 622
- bi-unicondylar knee implants, 437
- Bjork-Shiley Convexo-Concave Heart Valve, 400, 496–7
- blade-form endosteal implants, 513, 518–19
- blockage, 486
- blood cells
 - emerging from a blood vessel, 482
 - types of, 481
- blood circulation, working model of, 130
- blood vessels, 481
 - dimensions and pressures in, 482
 - replacements of small, 156
 - trilaminar structure of, 155
- blood-contacting implants, 478
- blunting region, of the JR curve, 316
- body-centred cubic (BCC), 622
- body-centred cubic (BCC) crystal structure, 32
- body-centred cubic (BCC) crystals, 40

- body-centred cubic (BCC) lattice
 - body-centred atom in, 35
 - close-packed direction in, 35
 - layering of closest packed planes to create, 32
 - tetrahedral site larger than octahedral site, 33
- body-centred cubic (BCC) structure, 32
- body-centred cubic (BCC) systems, secondary slip systems, 40
- bond energy $U(r)$, general form of, 11, 12
- bond, stiffness of, 11
- bonding and crystal structure, of metals and alloys, 28–32
- bonding mechanisms, 16
- bone absorption, 203–5
- bone architecture, remodeling of, 88
- bone cement, 383, 425
- bone drilling, 522
- bone grafts, 622
 - from bone banks, 88
 - need for, 87
 - obtaining, 70
 - physiology of successful, 88
 - stabilizing adjacent vertebrae, 454
- bone healing, 448
- bone marrow, damage to, 447
- bone periosteum, tearing of, 447
- bone resorption, 168, 520
- bone substitutes, 70, 87–9
- bone tissue, 140, 144
- bone(s)
 - arresting cracks, 323
 - building up bone density under higher loading, 167
 - compliance match to adjacent, 11
 - mineral responsible for stiffening, 135
 - nanoscale ceramic reinforcement, 286
 - resorbing, 527
 - taking from elsewhere in the body, 87
 - types of, 140
 - with fracture and intramedullary rod, 177
- bony ingrowth, at the bone-implant interface, 520
- bore, of the femoral head, 429
- Boston Keratoprosthesis, 581, 582
- Boston K-Pro
- boundary lubrication, 379
- boundary work, 310
- bovine serum, 389
- Bowman's layer, 579, 622
- Branemark, Per Ingvar, 522
- Bravais space lattices, 28, 29, 622
- breast augmentations and reconstructions, 584
- breast implants
 - auto-immune disease caused by, 587
 - classified as Class III devices in 1988, 586
 - current designs and functional requirements, 585–6
 - design evolution of, 585
 - development of, 561
 - evolution of, 585
 - legislative history of, 586
 - post-implantation concerns, 586
 - regulatory failure, 587–8
 - second-generation, 585
 - third-generation, 586
- breasts, injecting substances into, 561
- brittle, 622
- brittle materials crack tip in, 356
 - fracture associated with, 284
 - fracturing before yield, 241, 269
 - highly sensitive to tensile stress, 265
 - reducing size to improve strength, 286
 - relying on damage mechanisms, 322
 - stress singularity at the crack tip, 307
- brittle solids, failing, 270
- brittle systems, as weak in tension, 244
- bruxism, 529, 622
- building blocks, of tissue, 131–6
- bulk deformation processes, 51, 52
- bulk erosion, 124
- bulk properties, 371
- bulky side groups, 99
- bundled fibers, 561
- Bureau of Chemistry, 399
- Burger's vector, 39, 40, 622
- burn victim mortality, 575
- burns, 575, 576
- butterfly fracture, 622
- buttock implants, 584
- cadaver autografts, not providing number of needed valve replacements, 487
- cadaveric allografts, 572, 577
- calcium carbonate, 86
- calcium phosphate, 71
- Canada, Therapeutic Products Directorate (TPD), 411
- canaliculi, 141, 622
- cancellous bone, *see* trabecular bone
- cancellous screws, 450
- canine aorta, mechanical properties of, 156
- cannulated, 622
- cannulated screws
 - for femoral neck repair, 451, 452
 - sizes, 450
- capsular contracture, 586
- carbon fiber
 - abrading bone in the knee, 587
 - ligament failure, 587
- carbon fiber-reinforced UHMWPE (Poly II), 444
- carbonate content, of bone, 135
- carbonated hydroxyapatite, 86
- cardiopulmonary bypass machines, 495
- cardiovascular anatomy, 479–83
- cardiovascular applications, of e-PTFE, 94
- cardiovascular biomaterials, 13
- cardiovascular devices, on the horizon, 500
- cardiovascular disease, 477, 478, 622
- cardiovascular implants, 478
- cardiovascular system, 477, 480, 622
- cartilage, 622
 - ability to regenerate *in vivo*, 15

- layer of partially calcified, 153
- normal compared to osteoarthritic, 154
- optimized for compressive loading, 151
- surrounding a synovial joint, 422
- cartilage-on-cartilage contact, 386
- casting, 51, 52, 622
- cataracts, 583, 622
- catgut, 124, 560
- catgut sutures, 565
- catheters, 493, 623
- cathode, 55
- cations, 72, 623
- Cauchy stress (true stress), 245
- cavitating ductile material, fracture surface, 271
- cavities, 510
- CEA (cultured epidermal autograft), 577, 625
- cells, in human blood, 481
- cement line, 623
- cemented hip arthroplasties, 433
- cementum, thin layer, 508
- Center for Devices and Radiological Health (CDRH), 397, 403, 404–8
- Centerpulse Orthopedics, 467
- ceramic abutments, 525
- ceramic coating, surface modifications with, 523
- ceramic heart valve, critical crack length in, 78–9
- ceramic materials, 72, 623
- ceramic systems, 330
- ceramic total hip replacement femoral heads, 284
- ceramics
 - as implant materials, 70, 71
 - bonding and crystal structure, 71–5
 - characteristics of, 241
 - classifying, 85
 - complex crystal structures of, 72
 - drawback of using, 85
 - failure mechanisms in, 272
 - fatigue behavior of, 359
 - forms of, 71
 - fracture mechanisms in, 322
 - high elastic modulus values, 16
 - in a variety of applications, 70
 - in medical implants, 85–7
 - in structural applications, 70
 - ionic bonding, 72
 - low fracture toughness of, 322
 - mechanical behavior of, 75–82
 - processing of, 82–4
 - properties of, 18
 - resistance to fatigue crack growth, 330
 - sensitive to tensile normal stresses, 77
 - stronger in compression than in tension, 273
 - structure and mechanical behavior of, 75
 - susceptibility to fracture, 71
 - toughening mechanisms, 79, 80
 - wear resistance, 433
- Ceravital, 71, 87
- cervical spine, 454, 456, 623
- chain branching, in polymers, 98
- chain length, impeding long-range ordering, 99
- chain scission, 9
- chain structure, one-dimensional, 97
- chains, entanglement of, 107
- characteristic test frequency, inverse of, 227
- Charite implant, design evolution of, 461
- Charite intervertebral disk, 460
- Charnley hip, innovative low-friction, 431
- Charnley, Sir John, 390, 417
- chemical bonds, 16
- Chercheve, Raphael, 522
- chewing, mechanical demands of, 136
- chondrocytes, 151, 623
- chordae tendineae, 481
- Christensen TMJ device, slightly modified, 537
- chromium carbide, precipitation of, 57
- chromium precipitates, 48
- chromium-depleted zones, 58
- ciliary muscles, 580
- Class I devices, 9, 403, 405, 623
- Class I implants
- Class I recall, of all Proplast-Teflon Vitek TMJ total joint prosthesis, 544
- Class II devices, 10, 403, 623
- Class II implants
- Class III devices, 10, 403, 623
- Class III implants
- classifying, biomaterials, 13–16
- cleaning protocols, 7
- Cleaver, Mouse, 561
- clenching, 530
- clinical application, of biomaterials, 13
- clinical concerns, in design of soft tissue replacements, 562
- clinical issues, as paramount, 4
- clinical performance, 10
- clinical trials, 10
- close-packed planes, 30, 31, 34, 75
- close-packed spheres, planar section of, 30
- close-packed structures, 30
- clot formation, reducing blood loss, 483
- cobalt-chrome alloys, replaced stainless steel, 443
- cobalt-chromium (Co-Cr) alloys
 - blade implants, 518
 - cast form limitations, 62
 - elastic modulus, 61, 63
 - femoral head exhibiting surface damage, 463
 - high strength and fatigue resistance, 62
 - in hip implants, 432
 - in the fracture fixation industry, 453
 - intergranular attack of, 66
 - providing enhanced corrosion resistance, 27
 - uses of, 61
- CoCr total TMJ replacement, Kumoona designed, 535
- COD, *see* crack opening displacement (COD)
- coefficient *K*, specifying relative strength of the stress singularity, 288
- coefficient of friction, 373, 623
 - defined, 375
 - for common materials pairs, 375
 - low for UHMWPE, 117

- Coffin-Manson equation, 344
- coherent flaw, 334, 623
- cohesive stress, 307
- cohesive zone, length of, 319
- cold forged stainless steels, 62
- cold rolling, 47, 623
- cold working, 40, 46, 640
- cold-rolled brass, 46
- collagen
 - abundance of, 131
 - known types of, 132
 - variants of, 133
- collagen fibers appearing in a variety of
 - conformations, 132
- composition of, 133
- crimped form of, 151
 - in articular cartilage, 153
 - in dentin, 139
 - schematic of, 132
 - structural hierarchy inside, 140
- collagen fibrils, 133
- collagen molecules, 133, 140, 141
- collagen sub-fiber, hole zones in, 141
- collagenous osteoid, organization of, 141
- comminuted fracture, 448, 623
- compact bone, *see* cortical bone
- compact tension geometry, 290, 349
- compact tension specimen, illustration of, 349
- complex modulus, 228, 230, 623
- compliance, 11, 623
- compliance match to bone, 450
- compliance matrix, 205
- compliant, 623
- compliant materials, stretching at a crack tip, 323
- complications, arising from corrosion, wear, fatigue
 - or fracture, 8
- composite beam
 - bending of, 199
 - finding the neutral axis of, 197–9
 - for a custom implant, 199
- composite materials, 169, 623
- composite systems, 19
- composite(s)
 - characteristics of, 241
 - composed of unidirectional fibers, 200
 - undergoing longitudinal transverse loading, 200
 - with matrices of polymers, metals, or ceramics, 19
- compression fracture, 448, 623
- compression loading, flaws closing, 77
- compression, described by negative values for strain, 171
- compressive portion, of variable amplitude loading, 276
- compressive strength, 623
 - of ceramics, 18, 75
 - of enamel, 138
 - of human dentin, 139
- compressive stresses, 80, 264
- compressive yield strength, 264
- condensation reaction, 106, 623
- condylar, 623
- condylar prosthesis, 534
- condylar type tibial component, 276
- condyles, 10, 623
- conforming, 623
- conforming ball-and-socket joint, 421
- congenital, 623
- congenital defect, 486
- congenital heart defects, blocking, 495
- congestive heart failure, 477, 623
- constant bending moment, 335
- constant stress (creep) response, 217
- constitutive behavior, 181–2
- constrained dislocation loop, around particles, 48
- contact fatigue, 384
- contact lenses
 - as common intervention, 581
 - composition of, 581
 - designs and functional requirements, 580–1
 - tearing during ordinary use, 284
- contact loading, between tibial insert and femoral
 - component, 278
- contact shielding, 320, 355
- contact stresses, 66, 277, 623
- contracture, 586, 624
- contraindications
 - for implants, 530
 - for maxillary and mandibular implants, 530
 - for temporomandibular joint (TMJ) replacements, 538
- cooling, very rapid, 49
- coordinate axes, changing, 173
- coordinate rotation, 260
- coordinate transformation, applying, 175
- coordination number, 30, 624
 - for octahedral site, 33
 - for tetrahedral site, 33
- co-polymerization, with PLA, 125
- co-polymers, 95
- coral, 71, 624
 - as a bone substitute, 70, 87–9
 - as bioresorbable ceramic, 86
 - attributes for bone grafting, 88
 - porosity of, 86
 - structure of, 88, 89
- coral-derived bone substitute
 - widespread clinical success, 89
- coral polyps, hard mineral deposit built up by, 88
- coral secant modulus, 188, 639
- cornea
 - curvature of, 578
 - layers of, 578, 579
 - ultimate tensile strength, 582
- corneal edema, one month after IOL implantation, 588
- corneal replacements, 581–3
- coronal plane, 624
- coronary artery bypass graft (CABG), 489, 624
- coronary heart disease, 477, 624
- coronary stent designs, 485
- corrodibility, scale of, 55

- corrosion, 624
 - at the mechanical junction, 429
 - in metals, 18, 26
 - in modular orthopedic implants, 64–7
 - pathways in metallic systems, 55
- corrosion debris, 53, *see also* wear debris
- corrosion processes, 53–60
 - at the taper connection, 66
 - occurring in a modular total hip replacement, 66
 - resulting from reacting with an aqueous environment, 54
- corrosion resistance designing for, 54
 - of alloys, 27
 - of cobalt-chromium alloys, 62
 - of metals, 60
 - stainless steel known for, 62
- corrosion-induced degradation, 417
- corrosion-resistant materials (cathodic), 55
- corrosive attack, in crevices, 65
- corrosive wear, 383
- cortical bone, 140–3, 624
 - as an example of a hierarchical material, 323
 - composition of, 140
 - coral as a substitute for, 89
 - deformation behavior, 142
 - finding strains in, 186
 - majority of body's calcium in, 144
 - organization into osteons, 142
 - stress-strain curve for, 192
 - tension and compression response of, 143
- cortical screws, 450
- cosmetic breast implants, *see* breast implants
- cosmetic implants, 584–6
- cosmetic surgeries, numbers of invasive, 584
- costs, dictating manufacturing method for an implant, 53
- covalent bonding, 71, 95, 624
- covalent-ionic ceramic structures, 13
- covalently bonded materials, 13
- crack advance correlated to peak value of stress intensity, 356
 - in polymers, 361
 - mechanisms, illustration of, 356, 357
 - rate of, 348
- crack bridging, 81, 320, 624
- crack deflection, 320, 355
- crack driving force coming from stored energy from, 295
 - overcoming, 294
 - work in the system providing, 320
- crack equilibrium, 294
- crack growth
 - ahead of the notch, 268
 - as stable or unstable, 298
- correlation to stress intensity factor, 356
 - energy dissipated by, 295
 - in a material, 320
 - initiation of, 316
 - presence of a notch or small crack, 272
 - primary regimes of, 351
 - rate, 351
 - resistance and, 294–6
 - resistance curves, 295, 316–17
 - under application of tensile stress, 291
- crack initiation criteria, 316
 - designing against, 317
 - failure criterion, 317
 - in Regime II, 316
 - time, 319, 624
- crack loading, Modes I, II, and III, 292
- crack nucleation
 - from a sharp notch, 268
 - in the component, 266
- crack opening displacement (COD), 304–5, 624
- crack propagation
 - in ceramics, 359
 - in most metals, 357
 - intrinsic resistance to, 348
 - value for the onset of, 59
- crack shielding mechanisms, 355
- crack surface, 294
- crack tip
 - brittle materials accommodating stress singularity at, 307
 - compliant materials stretching extensively at, 323
 - compressive stresses retarding growth of the flaw at, 80
 - effective, 301, 304
 - elastic-plastic singularity, 311–14
 - in a ductile metal, 356
 - in brittle materials (ceramics), 356
 - inelasticity, 305
 - physical as blunted, 304
 - plasticity, 304–5
 - stress becoming singular near, 289
 - stresses, 77, 311
 - studying extreme stresses at, 284
 - viscous dissipation at, 318
- crack velocity, 22, 60
- crack wake
 - in a ductile metal, 356
 - inelastic region around, 320
 - mechanisms, 357
- crack wedging, 320
- crack(s)
 - as extreme stress concentrators, 287–8
 - behavior under moderate and severe crack tip plasticity, 307
 - distance from, 288
 - forming during loading, 283
 - nucleated, 269
 - subjected to tensile stress in a ceramic, 77
 - under complicated global stress states, 291
 - under complicated load conditions, 296
- cracked plate, thickness approaching plastic zone size, 301
- crack-opening mode, 291
- craniofacial, 624
- craniofacial features, 506
- craniomaxillofacial, 624
- craze, 624
- crazing, 274, 275, 276

- creep, 19, 208, 210, 624
- creep (time-dependent) strain response for the
 - Kelvin model, 220
 - of the Maxwell model, 218
- creep and cycle strain softening behavior, of UHMWPE, 225
- creep behavior, over a range of applied stresses, 237
- creep compliance of the SLS, 223
 - over time for UHMWPE, 225
- creep response
 - of the SLS, 222
 - vital to assessment of performance, 212
- creep strain, for the Kelvin Model, 220, 221
- creep time constant, for the SLS, 223
- crest, 624
- crest module, 514, 524, 624
- crestal bone
 - loss as marginal, 527
 - supra-physiologic loading of, 527
 - v-shaped resorption around root-form implants, 527
- crevice corrosion, 58, 624
 - in metal components, 26
 - minimizing, 26
 - schematic illustrating, 58
 - stainless steel susceptible to, 62
- crimp, in collagen fibers, 149, 151
- crimped collagen bundles, 193
- critical crack length, 60
 - as an inspection parameter, 78
 - form of, 78
 - resulting in fracture, 297
 - solving for, 353
- critical crack opening displacement, 304
 - critical flaw size, 624
 - defining relative fracture toughness, 297
 - determining, 298
 - for pyrolytic carbon, 79
 - for toughened zirconia ceramic, 79
 - in component loaded in shear, 293
 - ratio of, 298
 - using fracture toughness to determine, 77
- critical flaw, initiation or propagation of, 333
- critical normal stresses, 258
- critical strain, for low cycle fatigue in a tibial plateau, 345–6
- crosslinked system, lightly compared to fully, 112
- crosslinked UHMWPE, sacrificed resistance to fatigue crack propagation, 463
- crosslinking, 9, 624
 - at the expense of fatigue and fracture resistance, 428
 - effect on glass transition temperature of a polymer, 104
 - in the collagen network affected by environment, 213
 - of collagen increasing with age, 133
 - resistance as a function of, 428
- crosslinks
 - compared to entanglements, 108
 - resulting in permanent covalent bonds, 107
- cross-shear articulation, 427
- crown, 136, 507
- crown, natural, 624
- crown, synthetic, 624
- cruciate ligaments, retaining in the unicondylar procedure, 438
- crystal atoms, loading of, 76
- crystal lattices
 - distortion to, 33
 - orienting in a coordinate system, 34
- crystal planes, displacement of atoms across, 36, 37
- crystal structures in structural ceramics, 72, 73
 - of metals, 27
- crystal systems, 622
 - classification of, 28, 29
 - general, 28
- crystal(s)
 - different kinds of constituents in, 74
 - in enamel, 136
- Crystalline Bone Screw (CBS), 523
- crystalline ceramics, 72, 330
- crystalline domains, polymers forming, 98
- crystalline lamellae, 98, 101
- crystalline materials, metals and alloys as, 28
- crystalline solids, 28
- crystalline structure, 625
- crystallinity, 625
 - facilitating through chain folding, 99
 - of polymers, 98, 102
- crystallite development, in polymer systems, 101
- crystallographic planes and directions, 34–5
- cubic structures, more available slip systems, 45
- cubic system, close packed plane, 34
- cultured epidermal autograft (CEA), 577, 625
- curved resorbable collagen scaffold, 411
- curves, *see* specific curves
- curves
 - indicating roughness and waviness
 - resulting from friction tests
- cycles to failure, for a spinal implant, 338–40
- cyclic fatigue exponent, 357
- cyclic loading
 - effects on fatigue or fracture, 261
 - of polymers, 360
- cyclic plastic strain amplitude, 345
- cyclic plastic strains, 335
- cyclic softening, in UHMWPE, 225
- cyclic strain
 - data representing, 343
 - hardening, 625
 - softening, 625
- cyclic stresses
 - resulting from kinematics of the joint, 277
 - with tensile stresses, 426
- cyclic stress-strain loops, evolution of, 334
- cyclic yield stress, 333
- cylindrical designs, more easily implanted, 524
- cylindrical osteons, composition of, 141

- da Vinci, Leonardo, 130
- Dacron, 478, 625
 - fibers, 121
 - grafts, 490
- Dahl, Gustav, 515
- Dalkon Shield, 400
- damage mechanisms, 274, 275
- damage processes, utilized in ceramics, 274
- damper, 217, 230
- dashpot, *see* damper
- De humani corporis fabrica*, 129
- Deborah number, 211
- debridement, 533, 625
- debris, *see also* wear debris, *see also* particulate debris, *see also* corrosion debris
 - deciduous, 625
- deciduous teeth, 507
- deep zone, collagen fibers in, 153
- defect tolerant, 625
- defect-tolerant approach, to fatigue failure, 333
- defect-tolerant method, 297
- defect-tolerant philosophy, 348–62
- defects, presence of, 75
- deformable materials, 171
- deformation plasticity, 308, 625
- deformation(s), 45, 375
 - altering orientation of grains, 45
 - categories, 167
 - enhancing resistance to crack advance, 320
 - important in implant design, 167
 - in response to loading, 169
 - localized and extreme nature of near a sharp flaw, 286
 - micromechanism of, 333
- degradable polymers, 94
- degradation rate, of biodegradable ceramics, 86
- deionized (DI) water, 389
- delamination, 625
 - in total knee replacements, 22, 279
 - on articulating surfaces of knee joint, 277
 - prevalent region of, 463
 - wear, 386
 - with clinical dislocation, 464
- Delrin, disk made of, 486
- dense bone, implantation in more successful, 526
- densification, 147
- density, relationship with crystallinity, 102
- dental applications, from investment casting, 52
- dental biomaterials, 13
- dental caries, 625
 - as a leading cause of tooth loss, 510
 - described, 510
- dental enamel, *see* enamel
- dental implants, 505, 510–30
 - anchoring via osseointegration, 520
 - clinical reasons for, 510–12
 - cylindrical in shape, 82
 - described, 505
 - examples of different types of, 513
 - filling cavities in tooth enamel, 81
 - functional requirements, 530
 - future improvements, 544–5
 - historical development of, 515
 - immediate and early loading of, 545
 - innovation in, 515
 - integrating into underlying bone, 70
 - replacement materials used against enamel, 383
 - thermal stresses or strains, 81, 82
 - types of, 513–15
- dental plaque, 510
- dental prosthesis, 511
- dentin, 136–9, 625
 - as more compliant than enamel, 139
 - decay of, 510
 - middle layer of, 507
 - providing protective cover for pulp, 507
 - secondary, 508
 - structure of, 136
- dental tubules, 138
 - illustration of, 139
- dentino-enamel junction, 138
- dentition, 511, 625
- denture base, 511
- dentures, 512
- deoxyribonucleic acid (DNA), 625
- depressed fracture, 448, 625
- Dermagraft, 577, 578
- dermal acellular implants, 577, 625
- dermal cellular implants, using neonatal fibroblast cells, 577
- dermatome, 577, 625
- dermis, 155, 625
- Descemet's membrane, 580, 625
- design factors, for friction and wear, 389
- deviatoric, 625
- deviatoric component 173
- deviatoric portion of the normal and shear stresses, 250
 - of the stress, 245
- deviatoric stress tensor, 175
- device classifications, 403–4
- diabetic foot ulcers, 575, 577
- diagnostics biomaterials, 13
- dialing hook, in cataract surgery, 588
- diamond cubic lattice, utilizing FCC lattice, 72
- diamond-like carbon (DLC) coatings, 84
- diaphyseal, 625
- diaphyseal (cortical) bone, 450
- diaphysis, 140, 625
- die casting, with steel molds, 52
- diethylene glycol, 399
- differential scanning calorimetry (DSC), 102, 625
- dilatational, 625
 - component 173
 - stress tensor, 174
 - stresses, 249
- dilatational portion, of stress, 249
- directions, within the lattice structure, 34
- disk arthrosis, spinal fusion used to treat, 454
- disk replacement technology, 460
- dislocation, 40, 47, 626
- dislocation force fields, causes of, 42

- dislocation initiation rates, in polymers, 111
- dislocation line, 39
- dislocation movement (slip), 243
- dislocation pile-ups, 42
- dislocation slip, 251
- dislocation theory, full treatment of, 39
- dislocations
 - in ceramic structures, 75
 - in shear processes in metals, 40
 - types of, 39
- disorders, necessitating TMJ replacement, 532
- displacement vector, 39
- dissipated energy, from a single load cycle, 229
- distal, 626
- distortional energy, 243, 249, 250, 626
- distortional energy criterion, 253
- distortional or deviatoric stresses
- distortional portion, of stress, 249
- distortional strain energy, 250
- D-lactide form, of PLA, 123
- DNA disablement, 8
- Dohlman Doane Deratoprosthesis, 581
- double modular hip prosthesis, corrosion-induced fracture of, 463–7
- Dow Corning, lawsuits filed against, 587
- drawing, 51
- drawn glass fibers, experimental testing of, 286
- driving force, 294, 320, 626
- drug efficacy, demonstrating, 400
- drug-eluting stents, reducing restenosis, 483
- ductile materials
 - behavior, 626
 - deforming through shear, 243
 - facilitating dissipation of near-tip crack stresses, 322
 - undergoing fatigue experience cyclic damage, 356
 - yielding before fracture, 241, 269
- ductile metals, 250, 357
- ductile processes, of polymers
- ductile systems, generally utilizing shear deformation, 270
- ductility
 - in metals, 35
 - loss of, 46
- Dugdale, 305, 306
- Dugdale plastic zone, 306
- duocondylar knee, 439
- dynamic compression plate, 451, 452
- dynamic loading, during downhill skiing, 208
- dynamic mechanical analysis (DMA), 227, 626
 - finding upper and lower limit of, 200–3
 - line slope, 187
 - material constant, 181
 - measured value for, 181
 - range for estimates in uniaxial fiber composites, 202
 - range of values for, 181
- edema, 626
- edentulism (tooth loss), 505, 511, 626
- edentulous, 626
- edentulous individuals, biting forces of, 511
- edge dislocations, 39, 271, 626
 - forces between, 41
 - parallel repelling each other, 40
 - visualized as an extra half plane of atoms, 39
- edges, common to two anion polyhedra, 73
- effective crack tip, 301
- effective creep compliance, of the SLS, 223
- effective stress, 626
 - calculating, 241
 - determining, 260
 - independent of coordinate frame, 260
 - using 2-D analysis, 260
- effective stress range, 338
- effective von Mises stress, 345
 - for a compressive loading state, 264
 - for a loading state, 259
- Egyptians, placing hand-shaped prosthesis into deceased, 515
- eigenvalues, 179, 180–1
- eigenvectors, 179, 180–1
- elastic behavior, 109, 245
- elastic collagenous tissues, elastin found in, 133
- elastic component, of the strain amplitude, 344
- elastic deformation, 16, 109, 167
- elastic energy, material's ability to store, 243
- elastic fibers
 - elastin and fibrillin-based microfibrils, 133
 - mechanical properties of, 134
 - recoil in, 134
 - schematic of, 134
- elastic J , dominating in LEFM, 314
- elastic modulus, 15, 181
 - alternative methods for calculating, 188
 - described, 16
 - estimating, 11
 - finding from a stress-strain curve, 189
 - following rule of mixtures, 202
 - for ligaments, 150
 - for skin and blood vessels, 156
 - for stainless steel, 61
 - for viscoelastic material, 211
 - formula for, 13
 - in a fiber-reinforced composite, 202
 - lower reducing complication of stress shielding, 63
 - materials with high, 16
 - materials with lower, 16
 - of articular cartilage, 154
 - of C-Cr alloys, 63
 - of dentin, 139
 - of enamel, 136
 - of human enamel, 138
 - of human trabecular bone, 148
 - of hydrated collagen fibers, 133
 - of materials, 11, 81, 187
 - of tendons, 149
 - of the Maxwell model, 219
 - physical foundation for, 11

- range associated with each material class, 13
- uses of, 205
- values, comparison of, 17
- elastic modulus (E), 626
- elastic strain, 13, 109
- elastic strain energy, storing, 109
- elastic stress, 287
- elastic-plastic behavior, 308
- elastic-plastic crack tip singularity, 311–14
- elastic-plastic fracture handbook, 314
- elastic-plastic fracture mechanics (EPFM), 303–5, 626
 - admitting inelastic behavior, 308
 - deformation plasticity, 308
 - fracture instability in, 316
 - fracture toughness measure, 316
 - J for many engineering problems of interest, 316
 - summary of, 318
 - true conditions, 314
 - valid for moderate yielding, 312
- elastic-plastic generalization, of crack driving force, 303
- elastin, 133–4
 - described, 131
 - in arterial wall, 156
 - in ligament, 148, 151
 - in tendon, 151
 - responsible for stiffness of soft tissues, 134
- elastohydrodynamic lubrication, 377
- elastomeric material, under mixed mode conditions, 470
- elastomeric polymer, time temperature superposition behavior for, 233
- elastomeric-viscoelastic properties, of silicones, 123
- Electric Power Research Institute (EPRI), at General Electric, 314
- electron beam method, 9
- electron disruptions, damaging living cells, 8
- electronegativity, 72, 626
- electrospinning, 157
- electrostatic attraction, 28
- electrostatic valency, 73
- ellipse, equation for, 253
- ellipsoidal pores, in bone, 141
- elongation at break, 187
- elution time, 107
- embedded ellipse, in an infinite plate, 266
- embolus, 483, 626
- embrittlement, caused by cold working, 46
- emulsion, 626
- emulsion methods, used for ceramics, 83
- enamel, 136–9, 626
 - acids in the plaque reacting with, 510
 - brittleness of, 138
 - composition of, 136
 - crystals larger than bone, 135
 - elastic modulus of, 136, 138
 - energetic toughness of, 138
 - energy of fracture of, 138
 - most mineralized tissue in the body, 136
 - outer layer of, 507
 - tensile strength of, 138
 - thermal expansion coefficient for, 82
- endocardium, 479, 626
- endosteal, 626
- endosteal dental implants, 513, 514, 529
- endotenon, 149, 626
- endothelial cells, 155, 157
- endothelium, 580, 626
- endovascular stent-graft, alternative conduit for blood flow, 489
- endurance limit, 626
 - at zero mean stress, 340
 - between test specimens and components, 348
 - compared to the cyclic driving force, 340
 - defined, 336
 - error, 347–8
 - factors affecting, 337
 - for a notched bar, 267
 - for an unnotched bar, 267
 - for certain metals, 336
 - for the material, 329
 - of metals, 330
- endurance limiting factors, 346
- energetic description, of crack growth, 295
- energetic methods, in fracture mechanics, 293–4
- energetic toughness, 49, 626
 - of enamel, 138
 - of UHMWPE, 117
- energy dissipation, 208
- energy of fracture for human dentin, 139
 - of enamel, 138
- energy release rate, 294, 626
 - crack as a growth driving force, 294
 - critical value of, 296
 - describing an energetic condition, 296
 - for an unbounded center-cracked plate, 296
 - form of the negative of the derivative of a potential, 294
 - J as, 309
- energy storage component, 229
- energy, supplying to sustain crack growth to failure, 295
- engineering attributes, of ceramics used in medical implants, 72
- engineering design analysis, for total hip replacement, 435
- engineering materials defined, 14
 - properties remaining unchanged over large durations of time, 209
 - selecting for an implant design, 15
 - used in the body, 13
 - utilizing for medical implants, 4
- engineering mechanics, in tissues, 130
- engineering polymers, overlap with hard and soft tissues, 17
- engineering strain, 191, 205
- engineering stress, 191, 205
- engineering stress-strain
- engineering stress-strain behavior, 242

- engineering stress-strain curve, 191
- entanglements, compared to crosslinks, 107, 108
- enzymes, serving as a solubilizing agent to the polymer, 125
- EPFM, *see* elastic-plastic fracture mechanics (EPFM)
- epicardium, 479, 626
- Epicel, 577
- epidermis, 154, 627
- epiphysis, 627
- epitenon, 149
- epithelium, 579, 580, 627
- EPRI estimation procedure, 315
- e-PTFE, *see also* expanded polytetrafluoroethylene (e-PTFE)
- equal biaxial stress, 256
- equal yet opposite edge dislocations, 40
- equibiaxial stress state, 256
- equilibrium atomic separation, 75
- equilibrium condition, 294
- equilibrium elastic modulus, for articular cartilage, 153, 154
- erosion, 124, 627
- erosive wear, 384
- ethylene oxide (EtO) gas sterilization, 9
- ethylene oxide gas, 627
- Euler, Leonhard, 194
- European Union (EU), Directorate General for Health and Consumers, 410
- eutectoid reaction, microstructure development through, 49
- Elixir Sulfanilimide, for sore throats, 399
- expanded polytetrafluoroethylene (e-PTFE), 113, 490, 627
 - in facial reconstruction implants, 120
 - introduced in the 1970s, 478
 - microporous structure, 120
 - reconstructing ligaments, 94
- expendable mold, 52
- extension, 171, 627
- extension flexion, of the joint, 277
- extracellular matrix, 627
- extrinsic crack-tip shielding effect, 355
- extrinsic mechanisms, altering effective driving force, 320
- extrinsic toughening, 320, 355, 627
- extrusions, 51, 330, 627
- eye
 - anatomy of, 578, 579
 - changes in geometry of, 580
- eyeglasses, 581
- Eyring model, 109, 111, 620, 627
- fabrics, for synthetic grafts, 490
- face-centred cubic (FCC), 30
- face-centred cubic (FCC) lattice, 627
 - close packed direction in, 35
 - metals flowing under stress, 40
 - packing density, 30
 - packing density of, 30–2
- transformation into a HCP structure, 62
- yielding, 30
- faces, common to two anion polyhedra, 73
- facet screws, for spinal stabilization, 453
- facial changes, associated with aging, 511
- facial implants, locations of common, 584
- facial reconstruction implants, 120
 - uses of e-PTFE in, 94
- factor of safety (FS), 627
 - against failure, 241
 - against plastic deformation, 255
 - against yielding, 249, 255, 259
 - determining, 264, 339
- failure assessment diagrams, two-parameter, 305, 317
- failure criterion, basic form of, 265
- failure envelope, 265
- failure mechanisms
 - in ceramics, 272
 - in metals, 271–2
 - in polymers, 274–6
- failure strength (S_f), 187, 627
- failure stress, 251, 265, 340
- failure theories, for ductile materials, 279
- family of directions, denoting, 35
- 1 1 1 family of planes, 34
- far field, 289
- fascicles, 149, 151, 627
- fast fracture criterion, of the implant, 330
- fast fracture regime, 351
- Father of Bioengineering, 130
- fatigue, 331–3, 627
- fatigue behavior
 - difference between ductile and brittle solids, 355
 - of an engineering biomaterial, 333
 - of ceramics, 359
 - of metals, 357–9
 - of polymers, 360–2
 - of structural materials, 354–7
 - under cyclic compressive loading, 277
- fatigue characterization, of a material, 334
- fatigue crack(s)
 - growth rate, 359, 360
 - nucleating under cyclic compression loading, 268
 - propagation, 349–54, 362
 - propagation resistance, 350
 - under cyclic tensile loading in UHMWPE, 277
 - velocity of a moving, 350
- fatigue cycles
 - for a total hip replacement, 329
 - mean stress of, 338
- fatigue damage, mitigating, 330
- fatigue data, from accelerated and idealized tests, 346
- fatigue failures
 - as a consequence of crack nucleation, 333
 - in medical devices, 329
 - occurring well below yield strength of material, 330
- fatigue fracture resistance, loss in, 21
- fatigue fractures

- in trapezoidal hip stems, 362–4
 - of the abutment connection, 528
- fatigue life
 - based on propagation of an initial flaw, 348
 - compared, 329
 - of flawed components, 297
- fatigue loading, 363
- fatigue resistance design centred upon stress-based tests, 335
 - designing for, 333
 - for bearing surfaces in knee arthroplasty, 443
 - in ball-and-socket joint of the hip, 11
 - remaining limited in ceramics, 330
- fatigue resistant implant, 329
- fatigue sensitivity, to notches, 268
- fatigue strength, 336, 337, 627
- fatigue stress concentration factor, 267, 268
- fatigue striations, 358
- fatigue tests, in fully reversed loading, 341
- fatigue threshold, 351
- FCC, *see* face-centred cubic (FCC)
- FDA, *see* Food and Drug Administration (FDA)
- feathered fusion, 453
- Fe-C steel, phase diagram for, 50
- Fe-C system, eutectoid point, 49
- Federal Food, Drug and Cosmetic Act, 399
- femoral head, 627
 - articulating junction with acetabulum, 426
 - penetration into an acetabular cup, 237
 - properties of, 424
 - providing ball portion of the joint articulation, 424
 - utilizing ceramics, 433
- femoral neck, design requirements, 424
- femoral stem, 627
 - design evolving away from sharp corners, 364
 - design requirements, 424
- fractures, 362
 - multiaxial loading, 259–61
 - side crack in, 365
 - total life approximation for, 340–1
- femoral trabeculae, stress lines in, 146
- femoral trabecular bone, stress trajectories in, 146
- femur, compliance matrix for dry, 186
- fenestrations, 516, 627
- ferrous alloys (steel), endurance limit, 336
- fiber recruitment, 151
- fibers, thinner as stronger, 286
- fibril alignment, 149
- fibrillin, 133, 627
- fibrils, in skin and arterial wall, 155
- fibroblasts, 627
 - embedded among collagen fibers, 149
- fibrocartilage, 627
- fibrocartilage callus, 448
- fibrosa, 479, 627
- fibrous peri-implant tissues, formation of, 545
- fibrous pseudo-periodontal membrane, 520
- filling, 627
- filling material, within tooth enamel, 81
- first degree burns, 576, 627
- first moment of molecular weight, 107
- first-order imperfections, 38
- first throw hold, 570, 627
- first-order viscoelastic material models, 217–21
- fixation materials, properties of, 433
- fixation, of knee components, 442
- fixed bridges, 512
- fixed partial bridges, 512
- fixed-hinge-knee design, 437
- flat bone, 140
- flat plane X-ray, to catch strut fracture, 499
- flaw size, reaching critical value, 59
- flaws
 - evaluating in ceramic components, 78
 - in ceramics, 75
 - making cast form of Co-Cr prone to fracture or fatigue failures, 62
 - subjected to a tensile stress in a ceramic, 77
- flexibility, of an arterial graft, 11
- Flexicore device, 461
- flexion, 628
- fluid
 - bearing pressure, 214
 - constituent behavior, 214
- fluid flow, regulating without damaging red blood cells, 477
- fluorocarbon polymers, 119, 628
- fluoroscopy, 499, 628
- fold length, measure of, 102
- food additives, testing of, 398
- Food and Drug Administration (FDA), 399, 628
 - 510(k) guidance document for TMJ implants, 544
 - approval, 7
 - avoiding giving specific test requirements, 408
 - classifying implants, 9
 - final word in medical device regulation, 401
 - gaining approval from, 397
 - guidance contact lenses, 581
 - guidance for keratoprotheses, 582
 - guidance for submission of PMAs for breast implants, 586
 - guidance for sutures, 570
 - guidance for synthetic ligament implants, 574
 - guidance in the submission process, 408
 - history of, 401
 - legislative history, 398–401
 - medical devices regulated by, 92
 - medical devices subject to pre-market approval by, 93
 - not upholding regulatory duties, 544
 - products regulated by, 397
 - reclassified all types of TMJ implants, 544
 - recognizing international testing standards, 408
 - risks characterized for grafts, 491
 - schematic representation of the organization, 405
 - timeline of legislative history, 402
 - types of characterization for mechanical heart valves, 489
- Food and Drug Administration Modernization Act (1997), 400
- Food and Drug and Insecticide Administration, 399

- food and drugs, adulterated and misbranded, 398
- Foods and Food Adulterants experiment, 398
- force vector, resolving, 171
- force(s)
 - for activating yield, 40
 - for the separation of atoms, 11
 - physical definition of, 294
 - translating between a plate, screw and bone, 450
- Ford, Gerald, 400
- foreign body giant cell reaction (FBGCR), 537
- forging, 51, 628
- forming, 51, 628
- fossa prosthesis, 534
- fossa-eminence implant, 534
- Fourier Transform infrared (FTIR) spectroscopy, 21
- Fox and Flory equation, 104
- fractional lifetime, 341, 342
- fractional recovery, 236, 628
- fractography, 290
 - estimating fracture toughness, 290–1
 - insight into mechanism of failure, 270
 - of fractured trapezoidal T-28 stem, 363
- fracture behavior, 303
- fracture callus, 448
- fracture fixation, 446–53, 628
 - broadly defined, 446
 - clinical reasons for, 448
 - designs, 450–1
 - in a spine, 451
 - in a spine using plate and screws, 451
 - materials used in, 451
 - plate, alloy used in, 60
- fracture fixation devices
 - design concerns in, 453
 - functional requirements, 449
 - properties, 450
- fracture healing anatomy of, 447
 - improvement in understanding of, 447
- fracture instability, in EPFM, 316
- fracture mechanics, 628
 - concepts, 348–62
 - described, 284
 - ensuring appropriate structural analysis, 274
 - estimating fatigue life, 329
 - origin of modern, 283
- fracture mechanisms
 - in ceramics, 322
 - in metals, 322
 - in structural materials, 322–3
 - in tissues, 323
- fracture plate, 628
- fracture processes, associated with chronology of failure events, 463
- fracture resistance, of ceramics, 85
- fracture strength, of ceramics, 272
- fracture surface of a cavitating ductile material, 270
 - orientation of, 270
 - with fiber debonding in the UHMWPE matrix, 444
- fracture toughness, 15, 59, 60, 77, 78, 297, 628
 - as different from mechanical strength, 284
 - associated with stress corrosion cracking, 322
 - EPFM measure, 316
 - estimate of, 291
 - estimating from fractography of a tibial implant, 290–1
 - improvement in, 301
 - influencing critical flaw size, 79
 - low for ceramics, 18, 433
 - of ceramics, 75
 - of elephant dentin, 139
 - wide range in polymers, 322
- fracture types, basic classifications associated with, 448
- fracture(s) as catastrophic, 283
 - characterized by types of loads generating, 449
 - compressing, 451
 - critical tensile stress for, 324
 - failure mode distinct from strength, 284
 - governed by localized processes, 284
 - of trabecular bone, 148
- fractured bones, implants used to properly align, 449
- free volume, for polymers
- frequency domain analysis, 227–33
- fretting, 628
 - at the mechanical junction, 429
 - in metals, 17
 - minimizing, 26
 - wear, 384
 - wearing away protective oxide film, 464
- friction, 373–5
 - classic definition, 374
 - kinetic, 628
 - static, 628
 - wear test methods and, 387–9
- friction test, standard curve, 375
- frictional forces, reducing amount of force applied to teeth, 369
- frictionless contact, not existing in the real world, 369
- frontal, 628
- FTIR spectra, showing oxidation of an UHMWPE component, 21
- fully reversed loading, 338, 628
- function, restoring to the tissue or biological component, 14
- functional requirements, 628
 - breast implants, 585–6
 - contact lenses, 580–1
 - corneal replacements, 581–3
 - cosmetic implants, 585
 - for dental implants, 530
 - for temporomandibular joint (TMJ) replacements, 538
 - for TMJ replacements, 538
- fracture fixation devices, 449
 - hip replacement, 424–9
 - intraocular lenses, 583
 - of artificial skin, 578
 - of components of total knee replacement, 443

- of fracture fixation devices, 449
 - of knee replacements, 442–3
 - of sutures, 568–70
 - of synthetic ligaments, 573
 - spinal implants, 459
- G, measured value of, 297
- gait analysis, showing loads on the hip, 425
- Galen, catgut sutures used by, 560
- Galen, Claudius, 129
- Galileo, 130
- galvanic corrosion, 18, 57, 628
- galvanic potential, minimizing, 26
- galvanic series, 55, 56
- gamma (γ) phase, of iron (austenite), 49
- gamma irradiation, generating free radicals in polymers, 20
- gamma process, as deeply penetrating, 9
- gamma radiation, 3, 628
- gamma sterilization process, 8
- gap, at the interface, 65
- gas plasma, 9, 628
- gel permeation chromatography (GPC), 107, 628
- general failure criterion, 251
- general yield criterion, benefit of developing, 255
- generalized Hooke's law, 250, 264
- generalized Kelvin model, 226, 628
- generalized linear models, strength of, 227
- generalized linear viscoelasticity, 226–7, 628
- generalized Maxwell model, 226, 629
- generic composite beam, 198
- geometric parameters, tabulation of, 315
- geometry, of the critical flaw size, 297–8
- Gershkoff, 515
- gingiva, 629
- gingival ligaments, 508
- gingivitis, 510
- glass ceramics, 86
- glass fibers, 283, 286
- glass hip socket, 417
- glass transition temperature, 103, 210, 234, 629
- glasses, 83, 629
- glassy plateau, 210, 629
- glassy polymers, 629
 - characteristics of, 103
 - undergoing shear banding and crazing, 276
- glaucoma, 583, 629
- glenoid, 629
- glenoid components, shoulders, 432
- glenoid fossa, 509, 629
- Global Harmonization Task force, 411
- global loading, stored energy from, 295
- Gluck, Theodoros, 436
- Gluck, Thomas, 416
- glycoprotein, forming a scaffold for elastin deposition, 134
- glycosaminoglycan (GAG), 629
- glycosaminoglycan scaffold, with a semipermeable silicone layer, 577
- glycosylation reactions, 133
- gold, as dental material, 26
- Goldberg, 515
- gold-silver binary system, used in dentistry, 47
- Goodman equation, 340, 341–2
- Goodman line, 339
- Goodman relationship, between endurance limit and mean stress, 339
- Gore-Tex Cruciate Ligament Prosthesis implant, 572
- grafts, 491, 629
- grain boundaries, 42
 - as a nucleation site for dislocation pile-ups, 42, 46
 - chromium-depleted zones at, 62
 - corrosion along, 57
 - creating more, 46
 - dislocations at, 271
 - mismatch modeled with an array of parallel edge dislocations, 42
 - modeled as an array of edge dislocations, 43
 - serving to impede dislocation motion, 42, 43
- grain size
 - making smaller, 42
 - reduction in, 46
 - relating yield strength to, 46
 - smaller increasing yield stress, 44
- grain(s), 42
 - as a source of weakness, 57
 - large reducing strength of Co-Cr alloys, 62
 - larger facilitating the working process, 46
- graphite, structure of, 84
- green body, 83
- Greenfield, Edward, 520
- greenstick fracture, 449, 629
- Griffith energy balance, 294
- Griffith, A.A., 283, 285, 286
- Gruentzig, Andreas, 483
- Guidance Documents, with FDA recommendations, 408
- Gunston, 437
- Hall-Petch equation, 46
- Hall-Petch relationship, 272
- hard (bony) callus phase, 448
- hardenability, 629
 - of metals, 35
- Harvey, Wiley, 398
- Harvey, William, 130
- Havers, Clopton, 141
- Haversian canals, 141, 629
- Haversian system, 141, 629, 635
- HCP structure, *see* hexagonal close packed (HCP) structure
- HDPE, *see* high density polyethylene (HDPE)
- head diameter, optimizing, 390
- healing abutment, 514
- healing, failure during, 526
- healthy hip joint, frontal cross-section of, 423
- heart
 - anatomy of, 479
 - chambers, 479
 - layers, 479
- heart muscle, electrical simulation of, 477

- heart valves, 486–9, 629
 - design, 78, 487
 - replacements currently available, 488
 - representative sample of, 488
 - schematics of, 480
- heat treatments
 - of alloyed titanium, 63
 - tailoring an alloy with, 42, 43, 44
 - thermal processes, 48
- heel region, 134, 629
- helical polypeptide chains, 132
- helical wire implants, 520
- hematoma, formation of, 447
- hematopoiesis, 144, 629
- hemi-osteons, 144
- hemocompatibility, of pyrolytic carbon, 79
- herniated (ruptured)
 - intervertebral disk, 459, 629
- Hertzian contact, 376
- heterogeneous mixtures, of tissues, 323
- heterograft valves, 487
- heterografts, 629
 - using bovine vasculature, 478
- heteroplastic, 629
- heteroplastic material, for dental implants, 505
- hexagonal close packed (HCP), 629
- hexagonal close packed (HCP) structure
 - c/a* ratio for, 31
 - creating, 30
 - FCC lattice transformation into, 62
 - packing density, 30–2
 - titanium, pure existing as, 63
- hexagonal closest packed (HCP) lattices, 30
- hexagonal manner, packing, 30
- hexagonal yield surface, 247
- hexene-based elastomer, 469
- Hibbs, Russell, 453
- hierarchical, 629
- hierarchical structure, of articular cartilage, 152
- hierarchical toughening mechanisms, 89
- high cycle fatigue, 334, 344, 629
- high density polyethylene (HDPE), 94, 116, 117, 629
- high-frequency loading, 208
- high noble metals, 26, 630
- high-strength Ti alloy, 303
- high-toughness Co-Cr alloy, 303
- high-cycle fatigue, withstanding, 477
- highly crosslinked acetabular liners, fracture of, 324–5
- highly crosslinked UHMWPE, fracture toughness test, 303
- hinge mechanism first utilized in total knee reconstruction, 436
 - replicating kinematics of the knee, 436
- hip, 421
 - anatomy of, 422
 - forces of everyday activities, 426
- hip fractures, number of, 431
- hip implants
 - contemporary, 430–1
 - designs, 431
 - fatigue crack propagation in a flawed, 353–4
 - showing signs of moderate-to-severe corrosive attack, 65
 - success rate of, 341
 - taking up much of the loading, 167
- hip joint, anatomy of a healthy, 422
- hip prostheses, bolted design and early ball and socket design, 418
- hip replacements
 - engineering design process for, 434
 - experiencing low contact stresses, 421
 - functional requirements, 424–9
 - material and design evolution in total, 5
 - total, 15
- hip stem
 - circular and rectangular cross-section for, 197
 - cross-section, designing, 196–7
 - factors in the design of, 203
 - fixed into a femur, 204
 - processes involved in machining, 52, 53
- hole zones, 132, 140
- hollow basket root-form implant, schematic of, 521
- homolytic bond cleavage, 20
- homoplastic, 630
- homoplastic material, for dental implants, 505
- homoplastic tooth replacements, utilizing, 515
- homopolymers, 95
- Homsey, Charles, 543
- Hooke's Law, 181, 630
 - 3D, 254
 - applying 3D, 254
 - applying to multiaxial loading, 182
 - developing three-dimensional, 182
 - development of 3D, 182
 - for an orthotropic material, 185
 - for anisotropic material, 184
 - linear portion described by, 187
 - versions of, 205
- horizontal plane, 630
- hot isostatic pressing (HIP), 62
- hot rolling, 46, 630
- hot working, grain size remaining unaltered, 46
- HRR field, 311, 312, 630
- HRR stress singularity, 312
- Hufnagel, Charles, 486
- hyaline cartilage, *see* articular cartilage
- hydrated tissues
 - in articular cartilage, 214
 - multi-phase behavior, 214
- hydration, collagen requiring, 133
- hydrodynamic lubrication, 377
- hydrogels, limited fracture toughness, 284
- hydrogen bonding, 95, 630
- hydrophilic, 630
- hydrophilic ceramics, molding, 83
- hydrophilic nature, of a polymer, 124
- hydrophilic polymers, 125
- hydrophilicity, degree of, 125
- hydrostatic component, *see* dilatational component

- hydrostatic component of stress, 264
- hydrostatic portion, of strain energy, 250
- hydrostatic pressure, 258
- hydrostatic stress, 247, 257, 630
- hydroxyapatite (hydroxylapatite), 71
 - carbonated biologically active, 86
 - composites used as bone substitutes, 81
 - converting coral into, 88
 - described, 131, 135–6
 - implants with coatings of, 523
 - lending itself to substitution, 86
 - platelets spreading out between collagen molecules, 141
 - serving as a reservoir for mineral exchange, 135
 - similar to mineral component of bones and hard tissues, 86
 - wet precipitation techniques yielding, 84
- hydroxyapatite-coated polymer sleeve, cross-section of, 203
- hydroxyl groups, substitutions for, 86
- Hylamer polymer system, 445
- hyperopia, 581, 630
- hyperplasia, 486, 630
- hypothetical yield surface, 245
- hysteresis loops, 630
- hysteretic heating, 333, 361
- idealized stress-strain curves, 192
- immunosuppressant agent, 630
- impacted fractures, 448, 630
- imperfections
 - in ceramics, 75
 - in metals and alloys, 38–42
 - presence of, 75
 - utilized to strengthen metals, 46
- implant body, 513, 514
- implant design, 6
- implant loading, 545
- implant migration, as a serious issue, 560
- implant therapy, time required to complete, 544
- implant tissue system, 125
- implant(s)
 - bodies, width and height of, 525
 - costs dictating manufacturing methods, 53
 - fatigue resistance of, 331
 - in vivo* degradation of, 7
 - mechanical fixation, 424
 - monitoring of, 7
 - partial loosening of, 427
 - restoring function, 462
 - structural requirements of, 7
 - used to treat coronary heart disease, 478
 - utilized in the body, 81
- in vivo*, 631
- in vivo* degradation, 4
 - of implants, 7
 - owing to biological attack or immunological response, 126
- incremental damage, 342
- inelastic zone, engulfing singularity zone, 299, 303
- inert, 630
- inert biomaterials, 71
- inert ceramics, 71, 85, 86
- inert medical polymers, uses of, 113
- inferior, 630
- inferior vena cava, 481
- infinitesimal cube, inside an object under loading, 174
- infinitesimal element, undergoing rotation, 176
- inflammation, around posterior abutments of subperiosteal implants, 517
- inflammatory response, 7, 630
- initial flaw size, from non-destructive evaluation (NDE) techniques, 352
- initial relaxation response, misinterpreting, 237
- initiation, of a critical flaw, 333
- injection molding, 83, 630
- inkjet method, 83, 630
- in-phase component, 229
- instability condition, 296
- Institute of Medicine, 587
- Integra, temporary but immediate skin replacement, 577
- integrity, restoring to the tissue or biological component, 14
- interatomic force potential, assessment of, 11
- interfacial bone tissue growth, 85
- Intergraft carbon fiber composites, 587
- intergranular corrosion, 57, 62, 630
- interlamellar layer, 142
- intermediate crack growth, 351
- intermetallic compounds, fatigue of, 357
- intermetallics, 17, 630
- internal fracture fixation development of, 446
 - for a fractured tibia, 447
- internal tensile stresses, components with, 58
- international regulatory bodies, 410–11
- International Team of Oral Implantology (ITI), 523
- Inter-Op acetabular shells, recall of, 467
- interpositional, 630
- interpositional disk, 509
- Interpositional Proplast Implant, 543
- interstitial defect, 38
- interstitial sites, 32, 38, 630
- interstitial solid solution, 47, 631
- intervertebral disks
 - afflicted with scoliosis and kyphosis., 458
 - between vertebra, 457
 - degenerative disease of, 459
 - primary components of, 458
 - serving as shock absorbers, 457
- intima, 155, 481, 631
- intra-aortic balloon pump (IABP), 493, 494
- intramedullary, 631
- intramedullary rods, 417
 - for fracture in long bones, 451, 452
 - forces in, 176
 - repairing a tibial fracture, 176
 - stabilizing long bones, 193

- intraocular lenses (IOLs), 583, 631
 - currently marketed, 583
 - designs and functional requirements, 583
 - development of, 561
 - foldable, 583
 - fracture, 588
 - haptic fracture, 589
- intraocular pressure, 582, 631
- intrinsic dissipation mechanisms, 320
- intrinsic failure criteria, 297–8
- intrinsic mechanisms, inherent to a material, 320
- intrinsic microstructural process, 320
- intrinsic toughening, 320, 355, 631
- intrusions, initiating flaws, 330
- investigational device exemption (IDE), 406, 408, 631
- Investigational Review Boards (IRBs), 406, 631
- investment casting, 52, 54
- ionic bonds, 72, 631
- ionization (electron disruptions), producing, 8
- ionized gas, deactivating biological organisms, 9
- ionizing radiation sterilization, deterioration of
 - orthopedic-grade UHMWPE due to, 20–2
- iron carbide, precipitating, 49
- iron pins, used in the mid-1800s, 447
- irradiation, 631
 - resulting in chain scission or crosslinking mechanism, 9
 - resulting in cross-linking, 9
 - using for polymeric materials, 9
- irregular bone, 140
- Irwin corrected plane stress plastic zone size, 306
- Irwin Corrected Plastic Zone Size, 301
- Irwin Plastic Zone Size, 300
- Irwin, G.I.
- Irwin, G.R., 283, 286
- ISO (Organization for Standardization), 409
- isotropic, 631
- isotropic case, defined by two independent constants, 184
- isotropic material, 184–6, 255
- isotropic pyrolytic carbon, used in mechanical heart valves, 487
- Ivalon sponge, implantation of, 561
- J , computing for linear elastic solids and fully plastic solids, 314
- Japan, Pharmaceutical and Medical Safety Bureau, 411
- jaw joint, 509, 538
- jaw loading, as dynamic, 538
- jaw sizes, accommodating, 525
- J -integral, 309–11, 631
 - approximating, 314
 - as nonlinear energy release rate, 310
 - at crack initiation, 316
 - integral contour path for, 309
- joint arthroplasty, 533
- joint replacement, implanted to restore function, 14
- joint surface, removal of and replacement with a synthetic component, 152
- joints
 - lubrication in, 379
 - most commonly replaced, 421
- J_R curve, 316, 317
- Jungle, The (Sinclair), 399
 - dependence on global stress and crack length, 289
 - dependent on stress triaxiality, 297
 - for a constant pressure applied to crack tip, 306
- k values, typical, 382
- K_c
 - as a function of plastic constraint, 300–3
 - variations in, 302
- K-dominance, region of, 639
- Kefauver–Harris Amendments of 1962, 400
- Kelvin model, 214, 217, 631
 - as solid-like, 217
 - chained in series, 226
 - complex modulus of, 230
 - equal strain in two parallel elements, 219
 - generalized form of, 226
 - incapable of predicting stress relaxation behavior, 220
 - limitations of, 222, 231
 - parallel network, 217
 - relaxing from a highly stiff response, 220
 - with theoretically infinite instantaneous elastic modulus, 220
- Kelvin-type SLS, 224
- Kennedy Ligament Augmentation Device (LAD), 572
- keratinocytes, 577, 631
- keratoprotheses, currently marketed, 582
- kinetic barriers, preventing or limiting corrosion, 55
- kinetic friction, 373
- knee
 - anatomy of, 152, 435
 - articulation of the non-conforming, 439
 - complex anatomy with relatively low conformity, 421
 - flexion, 437
 - joint, 439
 - ligaments, 150, 151, 570, 571
- knee replacements, functional requirements of, 442–3
- knot security, 569, 631
- knot tie-down, 570, 631
- knot-pull strength, 569, 631
- Knowles pin, 451, 452
- kurtosis, 372
- kyphosis, 458, 631
- laboratories, achieving repeatable results, 168
- lacunae, 141, 631
- LAD (Kennedy Ligament Augmentation Device), 572
- lamellae, 631
 - composition of, 142
 - function of, 457
 - mechanical properties changing, 142
 - of mineralized tissue, 141

- lamina, 457, 631
- Lange, Fritz, 453
- laser etching, 353, 631
- lateral screw rod systems, 454
- lattice atoms, element with a geometric mismatch, 47
- lattice structure, of ceramic materials, 72
- lattice substitution, 45, 47
- layered devices, optimal thicknesses in, 202–3
- LDPE, *see* low-density polyethylene (LDPE)
- lead-coated platinum post, as a dental implant, 515
- leaflets (or cusps), with three layers of tissue, 479
- leakiness, 486
- Leeds–Keio prosthesis, 573
- LEFM, *see* linear elastic fracture mechanics (LEFM)
- left ventricular assist device (LVAD), 493, 494
- lens
 - fibers, 580
 - of the eye, 580
- life-supporting or life sustaining devices, 10
- ligament (material ahead of the crack tip), 289
- Ligament Advanced Reinforcement System (LARS), 573
- ligament reconstructive surgeries, 572
- ligament replacements, carbon fiber composites for, 587
- ligaments, 148–51, 631
 - anatomy of, 570
 - as structures of discrete components, 151
 - attaching femur and tibia and fibula, 435
 - composition of, 148
 - in unaltered state, 135
 - of the knee, 571
 - reconstructing, 94
 - showing relative deformation response, 150
 - structure of, 149
 - transition from compliant to stiff behavior, 151
 - tying bones together, 149
- likelihood of failure, predicting, 255
- line defects, 39–42, 626
- linear chains, facilitating efficient packing of molecules, 99
- linear crack growth, 350, 352
- linear elastic element, 216
- linear elastic fracture mechanics (LEFM), 77, 285–303, 349, 632
 - based on stress and strain field solutions, 308–9
 - COD methods as alternative approach to, 304
 - crack tip effective in modified, 304
 - elastic J dominating in, 314
 - in situations where inelasticity present but limited, 299
 - modified methods in, 299–303
 - summary and limitations of, 298
- linear elastic isotropic materials, 288
- linear elastic strains, 311
- linear individual model elements, 216
- linear low-density polyethylene (LLDPE), 116, 117
- linear polyethylene chains, packing, 118
- linear portion, described by Hooke's Law, 187
- linear region, 134
- linear relationship, between stress and strain, 181
- linear response, representing with complex numbers, 230
- linear spring, dissipating no energy, 230
- linear superposition, 632
 - invoking, 218
 - principle of, 182
 - properties of, 215, 292
- linear viscoelastic elements, 216–17
- linear viscoelastic networks, 214–27
- linear viscoelasticity, 632
- linear viscous response, 216
- linen fibers, used as sutures, 560
- Linkow, Leonard, 517, 518
- lipoma, 561, 632
- liquid phase sintering, 83
- L-lactide form, of PLA, 124
- LLDPE, *see* linear low-density polyethylene (LLDPE)
- load event, duration of, 227
- load-bearing devices, 483–96
- load-bearing human tissue constituents, values for, 137
- load-bearing tissues, 136–56
- loading, 332, 350
- loading Modes, independent, 291
- loading problems, solving variable, 343
- loading scenarios, 255
- loading situations, as three-dimensional, 168
- loads, in the body, 10
- local stresses
 - controlled by presence of a notch, 267
 - exceeding strength of materials under loading, 287
 - finding, 267
- localized crack phenomena, alternative measure of, 294
- long bones
 - anatomy of, 140
 - epiphyses and a shaft, 140
- long neck lengths, resulting in increased stresses, 466
- longitudinal direction, as stiffer than transverse, 143
- longitudinal testing, of cortical bone, 142
- long-term creep tests, on UHWMPE, 225
- Lorentz/Biomet (Warsaw, IN) device, 537
- loss factor, 232, 632
- loss modulus, 228, 229, 230, 232, 632
- lost-wax casting, 52
- low-cycle fatigue, 335, 344, 345–6, 632
- low density polyethylene (LDPE), 116, 117
- low frequency, modulus of Kelvin model purely elastic, 230
- low-carbon steel, heat treatment of, 49
- low-cycle fatigue component failure, 269
- lower back pain, incidence of, 458
- lower bound elastic modulus, 19
- low-friction contact, leading to appreciable wear, 369
- low-friction hip arthroplasty, 417
- lubricant layer, maximizing, 390
- lubricant, choice of, 389

- lubricated articulation, in the healthy body, 369
- lubrication, 377–81, 632
 - boundary, 632
 - elastohydrodynamic, 632
 - hydrodynamic, 632
 - mixed, 632
 - squeeze film, 632
 - types of, 377–81
- lumbar spine, 456
- lumen, 632
- machine coolant, leaking during manufacturing process, 467
- machining, 51, 52, 632
- macromolecular structures mechanical behavior of, 274
 - of polymeric materials, 94
- macrophages, 7, 427, 632
- malleability, of metals, 28
- malocclusion, 511, 632
- mandible, 508, 632
- mandibular bone, schematic of, 509
- mandibular implants, contraindications for, 530
- man-made materials, versus biological materials, 14
- manufacturability, of polymers, 112
- manufacturing methods for implants, 7
 - of ceramic materials, 82
 - run cost, 52
 - utilized in polymeric materials, 114
- marble breast, 561
- Marin factors, 346–8
- Marin, Joseph, 346
- martensite, 49, 632
- martensite-austenite phase transformation, 64
- mastication, 632
 - 1000 chewing cycles/day, 529
 - efficacy of, 510
 - severe mechanical demands of, 136
- masticatory loads, 529
- material behavior, over a range of loading frequencies, 227
- material choices, for orthopedic implants, 203
- material development, used in medical devices, 4
- material failure, process of, 241
- material phase, as a true viscous medium, 214
- material properties
 - measuring in a uniaxial test, 187
 - need for certain, 15
 - processing metals for, 45–50
 - tailoring through heat treatment, 44
 - time-dependent, 209, 210–12
- material resistance, to crack growth, 294
- material selection, as a multifactorial problem, 60
- material symmetry, utilizing, 261
- materials
 - deforming plastically, 299
 - selecting for devices and implants, 7, 14
- materials science, of medical alloys, 27
- Maverick implant, 461
- maxilla (upper jaw), 506, 508, 632
- maxillary and mandibular implants,
 - contraindications for, 530
- maxillofacial, 632
- maxillofacial implants, 506
- maximum bite force (MBF), 529
- maximum contact pressures, experienced in clinical total knee replacement designs, 278
- maximum distortional energy, 249–55
- maximum principal stresses, 324
- maximum shear stress, 38, 245
 - at the center of the contact area, 376
 - criterion, 245
 - determining using Mohr's circle, 178
 - finding, 179
 - found using Tresca yield criteria, 260
 - localized, 243
 - occurrence of, 246
 - planes of oriented, 246
 - reaching yield stress, 245
 - relationship with principal (normal) stress, 246
 - Tresca yield criterion, 245–9
- maximum stress, finding, 196
- Maxwell material, 221
- Maxwell model, 217, 633
 - as fluid-like, 217
 - characteristic time as defined by, 221
 - combined in parallel, 226
 - generalized form of, 226
 - imposed sinusoidal strain in, 231
 - loss modulus, 232
 - series network, 217
 - storage and loss modulus, 232
 - storage modulus of, 231
- Mayan civilization, teeth implanted into live patients, 515
- McKee-Farrar prosthesis, 417
- mean stress, 633
 - effect on fatigue behavior of a material, 338
 - effect on fatigue life of a material, 339
 - endurance limit decreasing with increasing, 339
 - incorporated into the life calculations, 329
 - mechanical behavior of polymers, 109–12
 - of loading cycle, 332
 - of structural tissues, 129–31
- mechanical failure, of Silastic implants, 534
- mechanical heart valve replacement, 486
- mechanical heart valves, 477
- mechanical properties commonly compared, 205
 - concomitant with variations in microstructure, 50
 - describing linear elastic, isotropic deformation, 168
 - describing ratio between stress and strain, 181
 - for tissues, 158
 - for trabecular bone, 147
 - of corals, 89
 - of e-PTFE, 120
 - of eye tissues, 578
 - of inert medical ceramics, 86
 - of metals yield strength, 27
 - sensitivity to different test parameters, 168
- mechanical requirements, on an implant, 14

- mechanical supports, 560
- mechanical test, for material characterization, 241
- mechanical variables, associated with sustained (cyclic) loading, 331
- media, 155, 481, 633
- median, 633
- medical alloys
 - elastic modulus, yield strength and tensile strength for most commonly used, 61
 - fatigue crack propagation behavior of a range, 358
 - materials science of, 27
 - variety of uses in the body, 60
- medical ceramics, summary of, 87
- Medical Device Amendments of 1976, 400, 404
- Medical Device Report (MDR), with the FDA, 498
- Medical Device User Fee and Modernization Act (2002), 400
- medical devices, 633
 - approval, 397
 - brought under FDA control, 399
 - complexity of, 401
 - definition of, 401
 - definitions and classifications, 401–4
 - design, 4
 - early, 3
 - for load-bearing applications in the body, 13
 - for which failure cannot be tolerated, 297
 - fractures, 283
 - long-term success of, 4
 - multifactorial factors contributing to performance, 6
 - regulating advertising of, 400
 - structural requirements of, 6, 10–13
 - subject to pre-market approval, 400
- medical implants
 - ceramics in, 85–7
 - designing, 3
 - metals in, 60–4
 - polymers in, 113–24
 - requiring very specific properties, 11
 - utilized in the body, 14
- medical indications for subperiosteal implants, 530
- for TMJ replacements, 538
- medical polymers, 116
- medium density polyethylene (MDPE), 117
- Medtronic catheter, bursting during an angioplasty, 401
- melt viscosity, scaling with molecular weight, 107
- melting curves, of polymers, 102
- melting temperature, relationship with lamellae thickness, 103
- meniscectomy, 533, 633
- Mentor Corporation, 586
- mers units, in polymers
- meshes, made from nylon and PET, 585
- metal backing, added to polyethylene tibial insert, 443
- metal bonds, breaking and reforming, 35
- metal corrosion, characteristics determining, 55
- metal head, displacement into the polymer cup, 237
- metal ions, 54
- metal processing, 42–53
- metal systems
 - alloying, 47
 - defect types and sources of microstructural features, 272
 - utilized as medical alloys, 27
 - yield stress saturating under sustained loading, 333
- metal(s)
 - altering structure and properties of, 42
 - as intrinsically metastable, 53
 - characteristics of, 241
 - expression for theoretical strength of, 38
 - failure mechanisms in, 271–2
 - fatigue behavior of, 357–9
 - fracture mechanisms in, 322
 - high fracture toughness and resistance to crack propagation, 330
 - imperfections in, 38–42
 - in medical implants, 26–64, 67
 - limitation of using, 17
 - making use of metallic bonding and closely packed planes of atoms, 16
 - mechanical properties for load-bearing medical devices, 17
 - plastically deformed, 35
 - processes strengthening, 45
 - processing for improved material properties, 45–8
 - processing for shape-forming, 53
 - sensitivity to corrosion, 322
 - slip systems in, 36
 - strengthening mechanisms in, 45
 - theoretical shear strength of, 36–8
 - utilizing metallic bonding, 27
 - with limited slip systems, 270
- metal/metal pairings, failed lubrication in, 382
- metallic bonding, 13, 633
 - bonding structure in, 53
 - described, 34
 - material behaviors, 27
- metallic femoral stem, 259, 262, 354
- metallic implants, degradation of, 53
- metallic stent, schematic of, 352
- metal-on-metal conical taper connections, to assist modularity, 64
- metal-on-metal designs, in intervertebral disk replacement, 461
- metal-on-polymer articulation, implant design employing, 439
- metal-oxide passive film, on the metal surface, 55
- metaphyseal, 633
- metaphyseal (trabecular) bone, 450
- microcrack propagation, in young and aged human teeth, 139
- microcracking, 80, 633
- microguidewire, in an artery, 178
- micromechanisms, 321, 330, 633
- micromotion
 - during initial healing, 545
 - experienced by implants, 519

- microscopic flaw, introducing, 284
- microscopic sharp cracks, 287
- microstructure, of metals, 27
- microvoid coalescence, 270, 274
- middle zone, collagen fiber orientation, 153
- migration, 633
- Miller indices, 34, 633
- mineral crystals, in dentin, 136
- misalignment
 - clinical reasons for, 436
 - of the knee, 436
- mitral valve, 479
- mixed lubrication, 380
- mixed-mode condition, 633
- mixed-mode crack propagation, 349
- mixed-mode loading, 292, 293, 297
- mobile bearing designs, 440
- Mode I
 - crack-opening mode, 291
 - equation, 292
 - loading, 77
 - opening mode, 349
 - stress intensity factor, 349
 - strip-yield zones in thin steel sheets in plane stress, 305
 - typically most critical, 297
- Mode II, shear mode, 291, 349
- Mode III
 - out-of plane shear mode, 349
 - twisting (or tearing) mode, 291
- modeling packages, computing J -integral at blunt or sharp crack tips, 311
- modeling techniques, predicting behavior of polymers, 212
- modular hip stems, assembly of, 385
- modular implant design, trade-off in, 466
- modular implants
 - conical press-fit fixation, 65
 - degradation, 65
 - tapered shank, 65
- modular neck
 - added length, 66
 - fracture of, 465
- modularity, benefits, 64, 429
- modulus, 623
- modulus of resilience, 243, 633
- modulus values, for alloy classes used in medical implants, 44
- Mohr, Otto, 176
- Mohr's circle, 176, 633
 - basic equations for, 260
 - coordinate system maximizing shear stress, 178
 - finding principal stresses, 248
 - for uniaxial loading, 246
 - plot for uniaxial loading, 246
 - representation of a stress state, 178, 180
 - representation of a two-dimensional problem, 177
 - showing maximum shear stress, 256
 - using to find principal stresses, 179
- molding, 633
- molds, intricacy of, 52
- molecular bonding level, of structural materials, 15
- molecular characteristics, limiting ability of a polymer to form crystalline structures, 98
- molecular effects, in polymers, 105
- molecular structures, in ceramics, metals, and materials, 18
- molecular variables effect on time-temperature behavior of polymer systems, 112
 - strengthening a polymer system, 112
- tailoring in polymers, 19
- molecular weight, 633
 - affecting glass transition of a polymer system, 104
 - determination of, 108–9
 - distribution in polymers, 106–9
 - effect on structure, 100
 - impeding long-range ordering, 99
- molecule size distribution, in a typical polymer, 106
- moment area of inertia, around the neutral axis, 198
- monofilament, 561
- monomers, 95
- morbidity, 570, 633
- Morse taper, 26, 58, 65, 633
 - achieving junction between femoral head and neck, 429
 - requirements for, 424
 - schematic illustration, 65, 430
- Morse Taper cone, showing burning, fretting and intergranular attack, 66
- Morse Taper junction, burnishing and fretting at, 66
- motion, in knee, 435
- Mouse Cleaver, 561
- multiaxial loading, 182–3, 255–61
- multiaxial stress state, 241
- multiaxial stresses, sources of, 259
- multiaxial testing, of a material, 187
- multifilament designs, increasing suppleness of a suture, 570
- multiphase polymers, toughness of, 323
- muscle, motive action of, 149
- mussel shells, toughness of, 287
- myocardium, 479, 633
- myopia, 581, 633
- natural corneal transplant surgeries, 581
- natural joints, coefficient of friction in, 386
- natural materials, 561
- natural options, for vascular grafts, 490
- natural sutures, 565
- natural tissues, *see* tissues
- natural tissues, dramatic increase in understanding of, 129
 - enabling energy dissipation, 322
 - existing along a continuum, 136
 - mechanical properties of, 129
 - properties of, 158
 - stress-strain curves in, 191–3
- Naval Ordnance Laboratory (NOL), 63
- nearsightedness, 633
- near-tip stresses, maximized, 77
- neck-head junction, 424

- necking, 189, 633
- neck-stem junction, bending stresses, 466
- needle attachment force, 569, 634
- neof ormation, 88, 634
- neonatal fibroblast, 577, 634
- nerve endings, in the cornea, 579
- network polymer, three-dimensional, 97
- neutral axis, 194, 197–9, 634
- Nitinol, 64, 634
- Nitinol Ni-T alloy, 63
- nitinol stent
 - fatigue design of, 352–3
 - strut failure, 498–500
- noble alloys, 26
- noble metals, in structural dentistry, 26
- non-conforming design, 441
- non-conforming surfaces, creating large Hertz contact stress, 442
- non-destruction evaluation (NDE) techniques, 352
- non-enzymatic crosslinks, 133
- non-expendable mold, 52
- nonlinear (NL) elasticity (E), 308
- nonlinear creep functions, 236
- nonlinear elastic material, 308
- nonlinear elasticity, 308
- nonlinear models, common, 235–6
- nonlinear relaxation, 236–7
- nonlinear viscoelasticity, 235–7
- non-resorbable materials, 561
- non-resorbable polypropylene suture, used for wound repair, 121
- non-resorbable sutures, currently marketed in the US, 566
- non-submergible implant, 514
- non-thrombogenic properties, of polyesters, 121
- non-thrombogenic substance, 634
- normal strain, 171, 634
- normal stress, 172, 173, 244
- normal stress criteria, 244, 265, 279
- Not Significantly Equivalent (NSE), 412
- notch sensitivity, 267
- notches, 634
 - materials sensitive to the presence of, 267
 - presence of, 266
 - serving to locally concentrate stresses, 330
- novel device, path to market, 406
- nucleation site
 - for dislocation pile-ups, 42, 46
 - of critical defects, 330
- nucleus, 634
 - of each disk, 457
- nucleus pulposa, 457, 634
- number average molecular weight, 106, 109, 634
- nylon, 121, 124, 337, 585, 634
- nylon balloon, in deployment of a vascular stent, 122
- nylon polymers, tensile strength of, 94
- OA, *see* osteoarthritis (OA)
 - object, under loading
 - oblique fractures, 449, 634
- observer invariance, 173
- occipito-cervical, 634
- occipito-cervical junction, 454
- occlusal, 634
- occlusal forces, 529
- occlusal loads, 506, 516
- occlusal overloads, 529
- octahedral shear plane, 251
 - orientation with respect to principal stress, 251
 - plotted in Mohr space, 252
 - shear stress on, 251
- octahedral shear stress, 251, 634
- octahedral shear yield criterion, 251
- octahedral site, 33, 634
- Office of Combination Products, 401
- oily residue, on defective implants inhibiting osseointegration, 467
- one-dimensional polymers, 113
- one-dimensional systems (chains), 95
- open cell foam, 147
- open pore architecture, of coral, 88
- ophthalmic implants, 560, 561, 578–84
- ophthalmologic, 634
- ophthalmologic disorders, 580
- optical micrographs, 428
- optical properties, of eye tissues, 578
- optic-haptic junction, fracture of IOL at, 588
- oral and maxillofacial implants, demand for, 505
- oral implants, 505
- oral mucosa, 634
- Organization for Standardization (ISO), 409
- orientation factor, for resolved shear stress, 40
- orientation mismatch, 42, 46
- orthopedic biomaterials, 13
- orthopedic implants challenges remaining in the development, 416
 - corrosion in, 64–7
 - described, 416
 - engineering challenges and design constraints of, 462
 - looking forward in, 470
- orthotropic, 634
- orthotropic material, possessing symmetry, 185
- orthotropy, 185
- osmosis, recruiting lubricating fluid into tissue, 151
- osseointegrated implants, failure of, 520
- osseointegration, 634
 - at bone-implant interface, 63
 - efforts to enhance, 545
 - lack of, 519
 - of implants, 505
 - supporting, 86
- osseointegrative ability, of titanium, 506
- osseointegrative potential, of ceramics, 524
- ossification, 448, 634
- ostoclasts, eating away at surrounding bone tissue, 427
- osteoarthritis (OA), 423, 424, 532, 634
- osteoblasts, 634
- osteoclasts, 88, 634
- osteochondron, 88, 634

- osteoconductive properties, of coral, 88
- osteocytes, 141, 634
- osteogenesis, 88, 634
- osteoid, 140, 634
- osteoiduction, 88, 634
- osteolysis, 416, 427, 635
 - complications with, 424
 - due to poor wear resistance, 20–2
 - loosening associated with, 422
 - propensity for, 455
- osteonal system, 141
- osteons, 635
 - as a basic unit, 141
 - composition of, 141
 - in cortical bone, 323
 - organization of cortical bone into, 143
 - resulting from remodeling processes, 144
 - separated by the cement line, 142
- osteoporosis, 70, 448, 635
- osteoporosis-related fractures, increased risk, 144
- outer scaffold layer, 157
- out-of-phase component, 229
- overall strain response, of the SLS in creep, 223
- overall stress response, for Maxwell model, 231
- oxidation, 635
 - as preferable energy state for metals, 53
 - creating structural degradation of UHMWPE, 21
 - long-term, 9
 - subsurface peak in, 21
- oxidation-induced embrittlement, gamma radiation
 - resulting in, 3
- oxidative degradation, enhanced susceptibility of
 - Hylamer, 445
- oxidative reaction, 55
- pacemaker, 635
- package memory, 570, 635
- packing density, determining, 30
- packing efficiency, 30
- Palmgren-Miner accumulated damage model, 341
- Palmgren-Miner's rule, 342, 343
- parafunctional, 635
- parafunctional activities, 529
- parafunctional oral activity, 526
- Parallel Axis Theorem, 198
- parallel network relationship, 217
- Paris equation, 358
- Paris law, 351, 352
- Paris regime, 351
- Paris regime slope, 359
- particulate debris, *see* wear debris
- particulate debris, increased levels of, 440
- Pascals [Pa]
- passivated surface, 58
- passivation, 55, 635
- passive oxide film, 55
- patella, 635
- patellar tendon, 570, 571
- patency, 500, 635
- Patent-Fitted TMJ Reconstruction Prosthesis, 537
- pathways, for corrosion in metallic systems, 55
- patient factors, 5, 525
- Pauling's rules, 72–5, 635
- peak energy, 229
- peak stored energy, 229
- peak stress, 288
- peak stress intensity, 356
- peak-to-valley height, 372
- pearlite, 49, 635
- pedicle screw spinal fixation method, 469
- pedicle screws, 467, 468, 469
- pedicles as fixation points, 453
 - spinal fixation through, 454
- pelvis, foundation of, 456
- percutaneous, 635
- percutaneous procedures, implanting stents, 483
- percutaneous surgeries, increased, 500
- pericardium, 479, 635
- peri-implant, 635
- peri-implant tissues, 519
- periodontal, 635
- periodontal disease, 87, 510, 635
- periodontal ligaments, 508
- periodontal tissues, 508
- periodontitis, 510, 635
- periosteum, 635
- periprosthetic osteolysis, 635
- permanent abutment, 514
- permanent ACL replacements, 572
- permanent augmentation devices, providing support
 - for existing ACL, 572
- PET, *see* polyethylene terephthalate (PET) polymer
- Peterson equation, developed for steels, 268
- PGA-PLA polymers, increased resorption time, 125
- phase diagram, for Fe-C steel, 50
- phase shift, 227, 635
- phase toughening mechanism, for zirconia, 80
- phase transformation toughening, 80, 635
- pHEMA Poly(2-hydroxyethyl methacrylate), contact
 - lenses made of, 581
- physical crack tip, as blunted, 304
- physiological problems, measurement methods in, 130
- physiological stresses, 6, 78, 635
- pile-ups, 635
- pin-on-disk testing, 389
- pins, used in internal fracture fixation, 450
- pitting, 277, 636
- pitting corrosion, 58, 59
- planar defects, 42
- planar organization, of tissues, 155
- planar two-dimensional polymer, 97
- plane sections, remaining plane during bending, 195
- plane strain fracture toughness, 301, 636
 - plastic zone size, 299
- planes
 - arbitrary intersecting the y and z axes, 34
 - describing within the lattice structure, 34
 - of maximum principal stress, 270
 - of the body, 420

- plaque
 - cardiovascular, 636
 - dental, 636
 - formation of, 477
- Plaster of Paris, 70, 636
- plastic blunting, of the crack tip, 303
- plastic component, of the strain amplitude, 344
- plastic constraint
 - in plane stress and plane strain, 307
 - K_c as a function of, 300–3
- plastic deformation
 - associated with hydrostatic loading, 257
 - increasingly severe, 313
 - local, 266
 - of metals, 35
 - onset critically linked to resolved shear stresses, 42
 - within crystal systems, 34
- plastic flow, region of reversed, 268
- plastic strain amplitude, 344
 - avoiding sustained, 344
 - resulting in permanent deformation, 243
 - some portion of the energy lost, 243
- plastic wake, 317
- plastic zone, 636
 - ahead of apparent crack tip, 305
 - correction to, 300
 - growing singular stress extinguished, 306
 - in high toughness materials, 308
 - radius, 315
 - size, 300
 - size affecting distribution of stresses, 304
 - size approximation, 300
- plasticity, 308, 312
- platelets, 482
- plates, 450, 636
- PMMA, *see* polymethylmethacrylate (PMMA)
- point defects, 33, 38
- Poison Squad, 398
- Poisson's ratio, 181, 205, 636
- poly (lactic acid) (PLA), 123
- polyamide polymer, 636
- polyamides, uses of, 121
- polycentric implant design, 438
- polycentric knee, invention of, 437
- polycentric motion, in the knee, 438
- polycentric pathway, rotation about, 437
- polycrystalline aluminum oxide (alumina), 523
- polycrystalline ceramic glasses, 71
- polycrystalline materials, metals as, 42
- polycrystalline metal, 42
- polycrystalline solids, metals more precisely termed, 42
- polydimethylsiloxane (PDMS), 123
- polydispersity index (PDI), 107, 109, 636
- polyester polymers, tensile strength of, 94
- polyesters, 121, 636
- polyetheretherketone (PEEK) polymer, 636
 - carbon fiber reinforced, 19
 - uses of, 123
- polyethylene (UHMWPE), as acetabular linear in a modular total hip replacement, 118
- polyethylene fossa, 536
- polyethylene polymer, 636
- polyethylene polymer systems, 99
- polyethylene terephthalate (PET) polymer, 121, 636
 - dynamic scan of, 231
 - flexible tubes of, 478
 - mechanical properties for, 229
 - meshes made from, 585
 - no endurance limit, 337
- polyethylenes
 - molecular weight of, 116
 - uses of, 116–17
- polyglycolic acid (PGA), 94, 113, 125
 - in sutures, 19
 - polymer, 636
- polylactic acid (PLA) polymer, 94, 113, 485, 636
- polymer chains
 - accommodating through chain folding, 102
 - folding into ordered structures, 95
 - increased length of, 107
 - segments overcoming activation barriers to move, 110
- polymer composites, 19
- polymer crystals, thickness of, 102
- polymer resorption, rate of, 125
- polymer structure, density of, 102
- polymer synthesis, result of basic, 106
- polymer systems
 - crystallinity of, 101
 - elastic modulus, 16
- polymer(s), 636
 - as viscoelastic materials, 212
 - bonding and crystal structure of, 95–106
 - characteristics of, 241
 - deforming elastically under small stresses, 109
 - ethylene oxide sterilization used in, 9
 - failure mechanisms in, 274–6
 - fatigue behavior of, 330, 357, 360–2
 - fracture mechanisms in, 322
 - improvement of, 93
 - in load-bearing applications in medical devices, 93
 - in medical implants, 92, 113–24
 - low elastic modulus values, 16
 - mechanical behavior of, 109–12
 - melting rather than fracturing, 361
 - melting temperature of, 102
 - molecular weight distribution in, 106–9
 - offering lower elastic modulus, 13
 - porous by design, 113
 - processing, 83, 112
 - properties of, 19
 - requiring low temperature methods, 9
 - structural properties of, 95
 - susceptible to creep and strain rate effects, 360
 - tensile loading versus compression loading, 276
 - time-dependent crack propagation in, 305
 - toughening with addition of a second phase, 323

- polymer(s) (*cont.*)
 - tribological behavior, 387
 - uses of, 94
 - varying greatly in molecular weight, crystallinity, and density, 99
 - with high glass transition temperature, 103
- polymeric biomaterials, 19
- polymeric coatings, 94
- polymeric implant, modified yield criteria for, 263–4
- polymeric materials highly dependent upon local stress states, 361
- primary advantage of, 94
- softening, 333
- susceptible to irradiation damage, 9
- polymeric tibial insert, 263
- polymethylmethacrylate (PMMA), 118, 636
 - as load transfer medium and grouting agent, 119
 - biodegradation in, 19
 - button pressed into a two-piece interface grasping a corneal graft, 581
 - condylar head, 534
 - IOLs, 583
 - transparency of, 119
 - uses of, 92
- polyp, 636
- polypropylene (PP) polymer, 120, 636
- polytetrafluoroethylene (PTFE) polymer, 636
 - as a bearing surface, 93
 - cup, 417
 - flexible tubes of, 478
 - in a low-friction bearing pair, 390
 - in dental implants, 93
 - materials for orthopedic implants, 543
 - slippery during handling, 585
- polyurethane (PU) foam disintegration of, 586
 - susceptible to chronic inflammatory response, 93
- polyurethane polymer, 636
- polyurethanes, 94, 122
- polyvinyl chloride (PVC) balloon catheters, 483
- pontics, 511, 636
- pore spaces mineralization spreading into, 140
 - reduction in, 83
- pores, 132
- poroelastic behavior, 637
- porosity
 - of cortical bone, 145
 - of trabecular bone, 145, 147
- porous coatings, 425, 431
- porous components, 561
- porous meshes, 560
- positive values, for stress
- post-amendment devices, 400
- posterior cruciate ligament-retaining design, 441
- posterior cruciate ligament-substituting design, 441
- posterior implants, less success, 526
- post-market surveillance, of a device, 498
- potential energy, 310
- pounds per square inch [psi], 172
- powder metallurgy, 83
- powder sintering, 637
- power-law correlation, 236
- power-law deformation plasticity material, 312
- power-law empirical correlation scheme, 235
- power-law plasticity, near the crack tip, 312
- power-law time-dependent compliance, 319
- power-law viscoplasticity, 236
- PP Polyflex, 570
- precipitates, 48
- precipitation hardening, 47, 620, *see also* age hardening
- predicate creep, 412
- predicate device, 404, 637
- Pre-Market Approval (PMA), 404, 637
- Pre-Market Notification (510(k)), 637
 - device path to market, 406
 - examining approval of and subsequent FDA internal review, 411–13
 - for a device, 404
 - using surgical meshes as predicate devices, 412
- primary body planes (cross-sections), describing anatomical positioning, 420
- primary slip systems, 35
- principal directions, 179, 637
- principal material coordinate system, 145
- principal stresses, 179, 637
- processing of the implant, 7
 - polymers, 112
- Pro-Disk intervertebral implant, 460
- ProFemur Z hip stem, 463
- profilometer, ID curve taken using, 372
- profilometry measurements, 388
- propagation process, of a critical flaw, 333
- Proplants, interpositional implants made of, 534
- Proplast, 536, 570, 637
 - carbon fiber composites, 587
 - coating, 536
- Proplast I, 543
- Proplast Interpositional Implant, 536
- Proplast-Teflon (PT) as TMJ implant material, 506
 - TMJ implants, 536
- Proplast-Teflon Temporomandibular Joint Replacements, 542–4
- prosthesis, *see* specific types
- prosthesis, assessing amount of wear, 237
 - views of Flot's, 536
- prosthetic heart valves, need for, 486
- proteins, in the body's structural tissues, 131
- proteoglycans, 148, 152, 637
- proximal, 637
- proximal-distal slipping, 65
- pterygoid muscles, 509, 637
- PU foam, *see* polyurethane (PU) foam
- pulmonary valve, 479
- pulp, interior of, 507
- pulsatile fatigue, 500
- Pure Food and Drug Act of 1906, 399
- pure shear loading, 256
- pyrogenicity, 637

- pyrolytic carbon, 83, 637
 - fatigue crack propagation rates, 360
 - properties of, 86
 - replacement of Delrin by, 487
 - structural arrangement of carbon in, 84
- pyrolytic carbon coating, 83
- pyrolytic carbon heart valves, fracture of, 284
- quenching, 49, 637
- R* curve shape, sensitive to stress triaxiality, 296
- R* curves, 295
 - for monotonic (quasi-static) loading, 320
- radians, measuring shear strain, 170
- radiation chemistry, of specific polymer systems, 9
- radicular pulp, 508
- radiopacity, for post-surgical monitoring, 489
- radius ratio, 72
- ramus blade, 519
- ramus blade-form implant, schematic of, 519
- ramus frame, 519
- Rankine, 244
- rapid crack growth, 351
- rapid prototyping, 83, 637
- rate sensitivity, of polymer mechanical behavior, 212
- ratio of maximum stresses, 298
- R*-curve (resistance curve) behavior, resistance curve
 - behavior, 360
- reactions, when metals corrode, 55
- real area of contact, 371, 637
- recrystallization, 48, 621, 637
- recrystallization temperature, 46
- rectangular and circular cross-sections, area
 - moments of inertia for, 196
- red blood cells, 481
- red bone marrow, 144
- reduced time, 236, 637
- reduction reaction, 55
- reference temperature, for WLF equation, 234
- ReGen Menaflex Collagen Scaffold (MCS), 411
- region of material breakdown, 289
- regulatory affairs, 397
- regulatory issues, 7, 9
- regurgitation, 486, 637
- rehabilitation period, after surgery, 570
- relative strength, of viscous component of the
 - spectral response, 229
- relative time scale, of relaxation and loading event, 211
- relaxation spectrum, 227, 233
- relaxation time, 208, 210, 637
 - for Silly Putty, 212
- relaxation transitions, in polymers, 233
- remodeling, 140, 637
- removable dentures illustration of, 512
 - primary components, 511
- repeatable data, accumulating large amounts of, 346
- resecting, 533, 637
- residual compression, 269
- residual stresses, developing at notch tip, 268
- residual tensile stress, zone of, 268
- residual tension, created upon unloading, 269
- resilience
 - of polymer structures, 106
 - of polymers, 19
- resolved shear stress, 40
- resorbable, 638
- resorbable (biodegradable) ceramics, 84
- resorbable materials, 71, 561
- resorbable sutures, 11, 124–5
 - made from polymers, 567
 - materials, structures and absorption times, 568
- restenosis, 483, 638
- retrieval studies, providing insight into adverse
 - reactions or complex problems, 10
- retrodiscal, 638
- retrodiscal tissues, 510
- rheopectic, 638
 - as synovial fluid, 380
- rheumatoid arthritis, 532, 638
 - as source of damage in articular cartilage, 424
 - in the knee, 436
- Ridley IOLs, 583
- Ridley, Harold, 561, 583
- Riegel v. Medtronic* (2008), 401
- Riegel, Charles, 401
- Ringer's solution, 389
- RMS roughness, 378
- Roberts, Ralph and Harold, 519
- rods, used in internal fracture fixation, 450
- rolling, 51
- rolling contact fatigue, *see* contact fatigue
- Roosevelt, Theodore, 399
- root, 638
 - of a tooth, 136
- root canal, 508
- root mean squared (RMS) roughness, 371
- root-form endosteal dental implants, 513, 520–9
- root-form implants
 - failures during healing, 526
 - geometries for, 524
 - overtaking bladeform implants in popularity, 528
 - reclassified by the FDA as Class II devices, 528
 - regions of, 514
 - requiring a healthy, intact vertical column of alveolar bone, 514
 - success of, 526
 - susceptible to early bone loss, 527
 - with surfaces roughened, 522
- rough surfaces, coming into contact, 371
- roughened surfaces, particularly in cylindrical
 - bodies, 523
- roughness, 371
 - average, 638
 - calculating, 372–3
 - root mean squared, 638
- roughness measurement methods, 388
- R*-ratio, 332, *see also* stress ratio rubber disk,
 - embedded between two titanium endplates, 455

- rubber particles, nucleating multiple crazes, 277
- rubbery plateau, 210, 638
- rubbery polymers, 104, 638
- S.E. Massengill Co., 399
- Sabins, Gary, 467
- sacrum, 456
- Safe Medical Devices Act, 641
- Safe Medical Devices Act (1990), 400, 640
- safety factor, as proximity to yield boundary, 253
- safety-critical applications, defect-tolerant approach used in, 348
- sagittal plane, 638
- saline, 389
- saline-filled breast implants, 585, 586
- Sandhaus, S., 523
- saphenous vein, 490, 638
- sapphire implant, 524
- sapphire, more favorable survival rates, 524
- saturation crack length, effect of load ratio on, 279
- SB Charité intervertebral disk, 455
- scaffold, creating for tissue engineering, 156–8
- Schulte, Heyer, 585
- scission, 9, 638
- scoliosis, 453, 458, 638
- screw dislocations, 39, 40, 271, 638
- screw type designs, 524
- screw(s), 638
 - types of, 450
 - used in internal fracture fixation, 450
- screw-plate construction, for stabilization of a spine, 454
- screw-rod system, 454
- screw-type implants, 514
- screw-type root-form implant, 520
- sea coral, *see* coral secant modulus, 188, 638
- second degree burns, 576, 638
- second moment of molecular weight, 107
- second-order imperfections, 39
- second phase additions, 80, 638
- second phase particle strengthening mechanism, 48
- second phase particles, 45, *see also* precipitates
- second phase particles, strengthening achieved with, 48
- second-phase particles, 45
- self-expanding stent delivery, 483, 484
- self-interstitial atom, 38
- self-interstitial point defect, 38
- self-similarity, 288, 638
- self-tapping implants designs, 522
- semi-brittle, 638
- semi-brittle processes, of polymers
- semi-brittle solid, cleavage mechanisms in, 273
- semi-brittle system, 241, 269
- semi-constrained dynamic plates, 454
- semi-crystalline polymer, 98
 - having crystalline and amorphous domains, 98
 - prediction of shift factors, 235
 - schematic illustration depicting, 103
 - uses of, 106
 - with glass transition temperatures well below body temperature, 105
- semilunar valves, 479
- septal defects, 638
- septal occluders, 495, 496
- series network relationship, 217
- series representations, for relaxation behavior, 226
- sesamoid bone, 140
- severe stress, 287
- shape memory behavior, 63, 64, 634
- sharp cracks, 273, 288
- sharp fatigue crack, in UHMWPE, 279
- sharp flaws, central role of, 283
- sharp notches, 266
- shear banding, 275, 276
- shear cavitation fracture processes, 257
- shear forces, repetitive high-magnitude, 530
- shear modulus, 182, 638
 - of human dentin, 139
 - relating strain, shear stress, and shear strain, 37
 - solute atom locally altering, 47
- shear plane, 41
- shear processes, deforming metals, 245
- shear strain, 169, 171
- shear stresses, 172, 173
 - common at interfaces, 291
 - necessary to force dislocations between particles, 48
 - plane of greatest, 247
 - relationship with normal stresses, 179
 - required for continued deformation, 45
- shear, as mechanism for plastic deformation, 257
- shearing mode (Mode II), 291
- shift factor, 233, 234, 639
- short bone, 140
- short fibers, 202
- short implant survival, 525
- sigmoidal fatigue crack propagation plot, 351
- Significant Risk Study Protocol, 407
- Significantly Equivalent (SE), 510(k) application, 412
- Silastic (silicone rubber), 639
 - as TMJ implant material, 506
 - compared to Proplast, 544
 - introduction of, 534
- Silastic HP sheeting, 534
- Silastic implants, widespread failure, 534
- Silastic TMJ disk, temporary, 534
- silica glass, 72, 74
- silicone breast implants, 561
 - more realistic feel and not prone to collapse, 586
 - re-approved, 586
 - removed from the biomaterials market, 93
 - utilizing crosslinked form of silicone, 123
- silicone elastomer, in place of a rubber one, 455
- silicone implant design, 123
- silicone polymer
- silicone, slippery during handling, 585
- silicones, 93, 122, 639
- silk, as suture materials, 124, 560
- Silly Putty, 212, 213

- siloxane hydrogels, in contact lenses, 581
- siloxanes, *see* silicones
- similitude, *see* self-similarity
- Sinclair, Upton, 399
- single craze, in a polymer
- single crystal aluminum oxide (sapphire), 523
- single crystal orientation, regions of, 42
- single-stage surgery, 514
- single tooth crowns, cemented to the abutment, 525
- single-root implants, less likely to fail, 526
- singular region, 289
- singularity dominated zone, 289
- singularity stresses, extending beyond crack tip, 288
- singularity-dominated zone, 639
- sintering, 83, 639
- sinusoidal deformation, over a wide range of frequencies, 227–30
- sinusoidal strain input, resulting stress response, 227
- sinusoidal stress displacement curve, 36
- skeletal fractures, incidence of, 446
- skeletal regeneration, of fractured bone tissue, 447
- skeleton, principal structural material of, 140
- skewness, 372
- skin, *see* artificial skin
- skin and blood vessel walls, 154–6
- skin
 - as largest organ in the body, 575
 - cellular structure of the epidermis, 154
 - functions of, 576
 - layers of, 154, 575, 576
 - mechanical properties of, 156
- sleep away implant, 522
- slip, 639
 - atomic movement denoted as, 35
 - defined, 28
 - due to grain orientation mismatch, 45
- slip plane, capturing motion of the dislocation, 39
- slip systems, 35, 36, 639
- slow crack growth, 351
- small-scale plasticity, 299–300, 312, 313, 639
- small-scale yielding, *see* small-scale plasticity
- small-scale yielding, conditions of 348
- S-N curve, generating, 335
- S-N fatigue data, for several polymer systems, 337
- S-N plots
 - for several polymer systems used in medical devices, 337
 - on linear-logarithmic scale, 336
- sodium chloride (NaCl) structure, as lattice of sodium atoms, 72
- soft tissue biomaterials, 13
- soft tissue devices, future of, 588
- soft tissue repair, polymetric suture anchor providing, 124
- soft tissue replacements
 - classifying materials used, 561
 - in facial augmentation, 506
 - materials used classified by chemical makeup, 562
 - materials used classified by structure and device area, 564
 - method for keeping them in place, 560
 - schematics of material structures used in, 563
 - types of, 560
- soft tissues
 - elastically blunting, 323
 - exhibiting an initially low stiffness, 323
- solid blocks, 561
- solid-solution strengthening, 45, 47, 639
- solute atom size, 47
- solution jet, stretched into a thin fiber, 157
- sp³ hybridization
 - facilitating four bonds, 95
 - in carbon, 96
- space fillers, 560
- spatial configuration in polymers, 95
- specific volume, as a function of temperature, 104
- spectrum loading, 331, 341, 639
- spheres, contact between two elastic, 376
- spherulite development, illustration of, 100
- spherulites, 99, 639
- spinal arthroplasty, clinical success of, 454
- spinal canal, 457, 639
- spinal column, composition of, 456
- spinal fixation designs, contemporary, 454
- spinal function, restoring, 459
- spinal fusion, 459
- spinal fusion procedure, performing, 453
- spinal implants, 453–62
 - clinical reasons for, 458
 - cycles to failure for, 338–40
 - design concerns in, 462
 - designs, 460–1
 - functional requirements, 459
 - materials used in, 461
 - Tresca stress, 248–9
- spinal instrumentation, failure of pedicle screws, 467–9
- spinal rods, 639
- spine, 456
 - anatomy of, 456–7
 - biomechanics of, 460
 - degrees of freedom in kinematics of, 459
 - medical devices used in, 453
 - post-operative stabilization of, 469
 - regions of, 456
 - stresses of, 454
- spine disorders, 458
- spinous processes, 453, 639
- spiral fractures, 449, 639
- spiral implant, schematic of, 521
- splint, 639
- splinted restoration, to a healthy adjacent tooth, 528
- split-thickness skin graft (STSG), 577, 639
- spongiosa, 479, 639
- spring, 217
- spring and damper elements, 230
- spring and dashpot, schematic showing, 216
- spring constant, of the bond, 11
- squeeze film lubrication, 379
- stability, addressing for knee replacement, 440

- stabilization, of spine disorders and fractures, 453
- stabilized zirconia, fracture toughness test, 303
- stable crack propagation, 295, 316
- stable equilibrium, 295
- stainless steel alloys as material for fracture fixation devices, 59
 - used medical devices, 61
- stainless steel total hip replacement stem, 347
- stainless steel(s) as implant materials, 26
 - chromium added to facilitate passivation, 57
 - elastic modulus, yield strength and tensile strength for, 61
 - in medical implants for corrosion resistance, 61
 - strengthening by cold working, 61
- standard engineering materials, 169, 639
- standard linear solid (SLS), 639
 - as an improved Kelvin model solid, 222
 - model, 222, 232
- standard metal processing, categories of, 51
- standards development organizations (SDOs), 409, 639
- standards, defined, 408
- STARR Surgical IOL, 583
- Starr-Edwards Silastic Ball Valve, 486
- state of plane stress, 252
- static driving force (mean stress), 340
- static friction, 373
- statics, problems of, 130
- steam, high pressure, 8
- steel plates, as internal fixation devices, 26
- steel rods, in combination with wire to stabilize the spine, 453
- steel(s)
 - concentration of interstitial carbon, 38
 - having near identical elastic modulus values, 44
 - heat treatment of low-carbon, 49
- Steffee, Arthur, 469
- stem-neck design (modularity), contributing to corrosion-induced fracture, 464
- stenosis, 486, 639
- stent characterization, non-clinical tests for, 486
- stent delivery, methods for, 483
- stent device, made of Nitinol, 352
- stent fracture, 499
- stent grafts, 491, 497–8
- stent(s), 483–6, 639
 - composition of, 485
 - fully absorbable, 500
 - improved testing, 500
 - keeping arteries open better and longer, 483
 - marketed in the United States, 485
 - representative sample of, 485
 - sizing as crucial, 483
 - structural requirements of, 485
- sterility, 8–9
- sterilization, 8, 639
 - methods, 3, 9, 10
 - options, 8–9
 - procedure, 126
 - protocols, 7
- stiff tissues, 323
- stiffness evolution, in a viscoelastic biomaterial, 224–6
- storage modulus, 228, 229, 230, 231, 640
- stored energy component, 229
- strain
 - amplitude, 333
 - complete equations for, 171
 - definition of, 169–71
 - definitions, 170
 - enabling, 110
 - equation, 171
 - imposing equal across each element, 217
 - in cortical bone, 186
 - normal (ϵ), 640
 - parameters used in defining types of, 170
 - shear (γ), 640
 - types of normal (or extensional) strain, 169
- strain energy, 250, 310
 - basic form or, 250
 - obtaining the total change in, 229
- strain hardening, 640
 - activated as dislocations interact, 45
 - adding line defects, 45
 - of metals and alloys, 40
 - simple demonstration of, 46
 - source of, 42
- strain rate, 109, 640
 - deceleration with increasing deformation, 236
 - effect of increasing on stress-strain behavior, 111
- strain response, of the Maxwell model, 218
- strain to failure, 27, 187, 640
- strain-based loading, 343–6
- strain-based tests, 334, 343
- strain-based total life philosophy, 344
- strength described, 284
 - designing for, 284
- strength of materials, 284, 640
- strengthening behavior, as a measure of strain hardening, 272
- stress amplitude, 640
 - determining, 338
 - increasing or decreasing, 333
 - of loading cycle, 332
 - relationship with number of cycles to failure, 337
- stress amplitude cycle (S-N) fatigue plots, 334
- stress and strain, local fluctuations in, 189
- stress concentration factor, 266, 267, 287, 640
- stress concentrations
 - cracks as extreme, 287–8
 - in a ceramic system, 273
 - locations of occurrence, 266
- stress corrosion cracking, 640
 - in a medical grade alloy, 59–60
 - in device components, 59
 - in metals, 17
 - metals susceptible to, 330
 - stainless steel susceptible to, 62
- stress criteria, for crazing, 276
- stress distribution, in a total joint replacement, 276–9
- stress intensity, 357

- calculating values of, 60
- for an embedded penny-shaped flaw, 293
- reaching critical value for material, 58
- stress intensity factor (K), 60, 77, 288–91, 348, 640
 - for a flaw, 78
 - formula, 289
 - of an edge-notched crack, 298
 - overall, 293
 - range, 351
 - rewriting for individual loading modes, 292
- stress intensity parameter, 349
- stress invariants used to describe the yield surface, 245
 - utilized in fundamental failure theories, 245
- stress matrix, components of, 259, 260
- stress power law, governing strain rate, 236
- stress range, 332, 640
- stress ratios, 279, 640
- stress relaxation, 210
 - accounting for, 19
 - for the Maxwell model, 219
 - in a polymeric implant, 221
 - Maxwell model illustrating, 218
- stress relaxation response, of the SLS, 224
- stress response, of the SLS, 232
- stress shielding, 167, 640
 - bone loss due to, 416
 - Co-Cr prone to, 63
 - defined, 329
 - leading to bone resorption, 203
- stress states
 - complicated, 291
 - components of, 173
 - contained within the ellipse as safe, 253
 - for pure shear, 258
 - of an object, 173
 - reduced to two dimensions, 259
- stress tensor, 173–81, 640
- stress transformation, 173, 640
- stress triaxiality, 301
- stress(es), 640
 - ahead of plastic zone, 301
 - at which plastic deformation begins, 36
 - complex states of, 243
 - decomposition of, 249
 - definition of, 171–3
 - distributing in the singularity region, 288
 - finding the highest, 179
 - imposing equal across each element, 217
 - in several different sets of coordinate axes, 175
 - in the Maxwell arm of the SLS during creep, 223
 - loads resolved into, 10
 - localization of, 266
 - measured in Pascals [Pa] or pounds per square inch [psi],
 - partitioning into the Maxwell arm of the SLS, 223
 - peak intensity of, 77
 - sharing over time, 222–30
 - upper limit of, 243
 - versus cycles to failure (N) data, 335
- stress-based loading, 334–7
- stress-based test, 334
- stress-corrosion data, 59
- stress-induced transformation, of crystal structure, 80
- stress-strain behavior
 - of several polymers, 109, 110
 - of the human artery, 193
 - showing modulus of resilience, 243
- stress-strain curves, 187–90
 - area under, 626
 - finding elastic, 189
 - for a material undergoing necking, 189
 - for brittle and elastomeric materials, 188
 - for brittle and rubbery materials, 188
 - for cortical bone, 193
 - for skin and artery, 155, 194
 - for tendon and ligament, 149
 - in natural tissues, 191–3
 - plotted data given, 190
 - toe and heel regions of, 323
 - traditional, 187
- stress-strain response, 188, 228
- striation markings, 357
- Stribeck curve, 380, 384
- Stribeck, Richard, 380
- strip-yield zone diagram, 306
- strip-yield crack tip cohesive zones, 305–8
- strip-yield models, 308
- strip-yield shape, of the plastic zone, 307
- strip-yield zones, 307
- Strock brothers, 520
- stroma, 580, 640
- structural analysis, presuming implant materials to be unflawed, 283
- structural aspects
 - of dental implants, 529–30
 - of TMJ replacements, 538
- structural components, as intrinsically flawed, 348
- structural discontinuity, magnitude of stress near, 266
- structural factors, determining elastic interaction with a dislocation, 47
- structural implants examples of, 14
 - sustained loading of, 329
- structural layers, separated by a soft interspersed phase, 323
- structural materials
 - fatigue behavior of, 354–7
 - fracture mechanisms, 322–3
 - under sustained loading, 333
- structural medical ceramics, comparison of mechanical properties of, 76
- structural properties, for materials used in implants, 14
- structural relaxation effects, 210
- structural requirements, of medical devices, 6, 10–13
- structure-property relationships, 16–17
- strut fracture, 487
 - in a mechanical heart valve, 496
 - in a stent, 498
- Styker-Dacron implant, 572

- submergible, 640
- submergible implant, 514
- submissions, types for medical devices, 404–8
- subperiosteal, 640
- subperiosteal dental implants, 513, 514, 515–18, 529
- subperiosteal framework, design of metal in, 516
- subperiosteal implant strut configurations, 517
- substantially equivalent, 640
- substantially equivalent device, 404
- substitutional solid solution, 47, 640
- sulcus, 511, 641
- Sulzer Inter-Op cup
- Sulzer Orthopedics, recall, 467
- super saturated solid solution, creating, 48
- superelastic behavior, 63, 634
- superelastic traits, 64
- superficial tangent zone, 153
- superior, 641
- superposition
 - determining stresses individually, 291
 - of G, 296–7
- supersaturated solid solution, 47, 641
- Supramid, 585
- surface coatings, for fixation, 433
- surface contact mechanics, 375–7
- surface contact, in biomaterials, 386–7
- surface damage, for crosslinked UHMWPE used in the hip, 463
- surface energy, 117, 641
- surface factor, as a function of ultimate tensile strength, 347
- surface features, relative sizes of, 374
- surface finish, 641
- surface properties, 371
- surface roughness
 - controlled through processing, 372
 - curve illustrating, 371
 - of components, 346
 - resulting from conventional machining, 347
- surface topography, 371
- surface treatments, as a protective mechanism, 55
- surgeon, role of a good, 5
- surgeon's knot, 569, 570
- surgical biomaterials, 13
- surgical interventions, for TMJ disorders, 533
- surgical meshes, reinforcing natural tissue, 412
- surgical tools, sterilizing, 8
- sustained loading, 331
- sustained loading cycle, mean stress of, 338
- suture anchors, 92, 124–5, 221, 641
- suture materials employed in biomedical implants, 230
 - examples of, 124
- sutures, 565–70, 641
 - among earliest recorded medical devices, 560
 - as Class II devices, 565
 - clinical uses of, 565
 - current designs, 565–8
 - functional requirements of, 568–70
 - physical characteristics of, 568
 - polymers in, 94
 - properties of, 11
 - with attached needle, 565
 - with structures and suggested indications, 567
- suturing, 560
- switchboard model, 100
- symmetric stress tensor, 249
- symmetry, special cases of, 185
- synovial fluid, 422
 - as example of a lubricant, 380
 - drawing into tissue, 153
 - penetrating articular cartilage, 379
- synovial joint, 422, 641
- synovial membrane (capsule), covering the knee, 435
- synthetic biomaterials attributes and limitations of, 17–20
 - designing an implant using, 130
 - in load-bearing medical devices, 14
- synthetic grafts, 490
- synthetic hydroxyapatites, elastic moduli of, 136
- synthetic ligament replacements concerns associated with development of, 573
 - search for a suitable, 561
- synthetic ligaments, 570–5
 - Class III devices, 574
 - functional requirements of, 573
 - not yet a good solution, 589
- synthetic materials, 561
 - categories based on structure, bonding, and inherent properties, 13
- synthetic non-resorbable sutures, materials used, 565
- synthetic scaffolds, 573
- synthetic sutures, 565
- synthetic vascular grafts, 491
- tailbone (coccyx), 456
- tan (δ), *see* loss factor
- tangent modulus, 187, 641
- tartar, 641
- tartar-induced inflammation, of the gums, 510
- tearing instability, 316
- teeth, *see* tooth
- Teflon, 478, 543
- Teflon products, 543
- temperatures, methods withstanding high, 9
- tempered martensite, 49
- tempering, 49, 641
- temporomandibular joint (TMJ), 509, 641
 - anatomy of, 509
 - ankylosis, box-like stainless steel fossa for relieving, 534
 - articular surfaces, 538
 - as weight-bearing joint, 542
 - devices, refinements in surgical placement of, 545
 - disorder (NIDCR), 532, 533
 - functions of, 533
 - implants, reclassification as Class III devices, 537
 - in the OA, 532
 - loading, 545
 - malocclusion generating super-physiologic loads on, 511
 - mechanics, 506

- prosthesis, Christensen's early, 528
- registry, 545
- resultant forces on from masticatory loads, 538
- temporomandibular joint (TMJ) replacements, 506, 532–9, 545–6
 - clinical reasons for, 532–3
 - contraindications for, 538
 - disorders necessitating, 532
 - first permanent, 534
 - functional requirements for, 538
 - historical development of, 533–8
 - history of, 506
 - medical indications for, 538
 - placement of a partial or total, 533
 - structural aspects of, 538
- tendon(s), 148–51, 641
 - as assemblies of bundled collagen fibers, 129
 - as structures of discrete components, 151
 - composition of, 148
 - hierarchical structure of, 149
 - high load-carrying ability, 149
 - high proportion of Type I collagen in, 133
 - protection from abrasion and wear, 149
 - schematic showing relative deformation response, 150
 - structurally in parallel with muscles, 151
 - structure of, 149
 - transition from compliant to stiff behavior, 151
- tennis players, bone strength of the dominant arm, 167
- tensile force, 201
- tensile strength, 641
 - for elastic fibers, 134
 - of a brittle material, 286
 - of ceramics, 18
 - of Co-Cr alloys, 63
 - of collagen fibers, 133
 - of cortical bone, 142
 - of enamel, 138
 - of human dentin, 139
 - of most ceramic structures, 75
- tensile stress, 172
- tensile stress-strain curve, for articular cartilage, 153
- tensile test, metrics derived from, 168
- tensile testing configuration, 242
- tension-compression stress-strain curve, 192
- test methodology, reporting all aspects of, 169
- test specimen, dimensions, 301
- testing standards anatomy of, 408–9
 - development of, 409–10
 - from international standards development organizations, 168
- tetrahedral site, 33, 641
- tetrahedron, geometry of, 31
- Thalidomide disaster, 400
- theoretical cohesive strength, 75, 641
- theoretical shear strength, 36–8, 75
- theoretical strength, for small displacements, 75
- theoretical value of strength, 75
- thermal expansion coefficient, 81, 82, 641
- thermal strains, 81
- thermal stresses, 81–2
- thermal treatments, controlling grain size, 49
- thermal variation, experienced by dental implants, 81
- thermodynamic driving forces, 55
- thermoplastic polymer, 641
- thermoplastics, characteristics of, 113
- thermosetting plastics, 113
- thermosetting polymers, 112, 641
- thick specimen, plane strain and plane stress, 302
- thin-walled cylindrical pressure vessel, 257
- third degree burns, 576, 641
- third-order imperfections, 42
- thoracic spine, 456, 641
- three-dimensional Tresca yield envelope, 248
- three-dimensional hydrostatic stress, 257
- three-dimensional polymer networks, 95
- threshold regime, 351
- threshold stress intensity factor, 353
- thrombosis, in synthetic grafts, 491
- thrombus, 483, 641
- tibial, 641
- tibial components, in total knee arthroplasty, 241
- tibial plateau, 183, 184
- time power law, 235
- time, under a constant load, 319
- time-dependence, associated with a characteristic time scale, 208
- time-dependent, 641
- time-dependent creep component, 361
- time-dependent fracture mechanics (TDFM), 318–20, 641
- time-dependent material behavior, 210
- time-dependent material properties, 210–12
 - describing viscoelastic materials, 208
 - making design process more challenging, 209
- time-dependent vanishing yield strengths, 318
- time-temperature equivalence, 233
- time-temperature superposition, 233–4, 642
- time-temperature-transformation (TTT) plot, for steel, 50, 51
- time-varying stress, in the Maxwell element during creep of SLS, 223
- tissue drag, 570, 642
- tissue engineering, creating a scaffold, 156–8
- tissue ingrowth, assuring valve placement is secure, 488
- tissue integration, available in ceramic systems, 85
- tissue microstructure, as predictive of material response, 131
- tissue valves, 486
 - currently marketed in the United States, 489
 - vulnerable to calcification, 487
- tissue-engineering solutions, for TMJ disorders, 545
- tissues, *see* natural tissues
- tissues as viscoelastic solids, 213–14
 - building blocks of, 131–6
 - characteristics of, 241
 - fracture mechanisms in, 323
 - hydrated to maintain function, 214
 - load-bearing, 136–56

- titanium
 - as a surgical material, 27
 - elastic modulus compared to Co–Cr, 63
 - forming an outer oxide layer, 18
 - natural propensity for integration with bone, 63
 - offering exceptional strength, 63
 - osseointegrative properties of, 522
 - pure existing as HCP structure, 63
 - susceptible to corrosive wear, 383
- titanium alloys
 - elastic modulus, yield strength and tensile strength for, 61
 - in the fracture fixation industry, 453
 - introduced into orthopedics, 418
 - offering exceptional strength, 63
 - specials surface treatments with, 18
- Ti-6Al-4V, 63, 432
- titanium endplate-rubber core interface, failures occurring at, 455
- titanium implant, Branemark's original, 522
- titanium nitride, in an investigational device, 537
- TMJ, *see* temporomandibular joint (TMJ)
- toe regime behavior, 151
- toe region, 134, 149, 642
- tolerance, 642
- tooth
 - anatomically distinct regions, 507
 - diagram indicating enamel and dentin, 138
 - mineral responsible for stiffening, 135
 - sections of, 136
- tooth crown, 507, 508
- tooth enamel, *see* enamel
- tooth loss, 510, 511
- tooth root
 - below the gum margin, 508
 - schematic of, 508
- Toronto Conference for Osseointegration in Clinical Dentistry, in 1982, 522
- torsional loading, 256
- total artificial heart (TAH), 495
- total condylar knee
 - illustration of, 440
 - in 1974, 439
 - knee design founded upon, 439
- total damage, 342
- total hip arthroplasty, 422–33, 435
- total hip replacements
 - components of, 424
 - constituents of contemporary, 419
 - design of, 429
 - elements of a contemporary, 418
 - endurance limit error, 347–8
 - functional properties of components in, 425
 - historical evolution, 416
 - material properties summarized, 432
 - path to market, 407–8
 - showing porous coating in, 431
 - utilizing an UHMWPE acetabular cup, 117
- total joint arthroplasty (TJA), 421
- total joint replacements, 421–2, 642
 - causes for, 422
 - evolution in design and materials, 419
 - failure rate, 422
 - polymer sleeve assisting with bone ingrowth in, 202
 - stress distribution in, 276–9
 - use of composites in, 390
- total knee arthroplasty, 435–46
 - design concerns, 446
 - materials used in contemporary, 443–6
- total knee reconstruction, in mid-20th century, 437
- total knee replacements design of, 443
 - functional properties of components, 444
 - functional requirements of components, 443
- total life approximation for a femoral stem, 340–1
 - using the Goodman equation, 341–2
- total life design methodology, 333
- total life philosophy, 334–7, 642
- total life tests, specimens utilized in, 335
- total strain amplitude, of the fatigue cycle, 344
- toughening ceramics, in engineering applications, 322
- toughening mechanisms classifications of, 354
 - types of, 320
 - utilized in ceramic structures, 80
 - utilized in ceramics, 79
- toughness, of polymer structures, 106
- trabeculae
 - arrangement of, 144
 - beam or plate-like behavior of, 146
 - excessive remodeling of in old age, 144
 - in vertebrae, 145
 - orientation coordinated, 145
- trabecular bone, 143–8, 642
 - architecture of, 130
 - cellular structure of, 144
 - composition of, 144
 - coral as a substitute for, 89
 - dependence on porosity and trabecular architecture, 147
 - dominant orientation of architecture of, 145
 - exhibiting different architectures, 145
 - increased surface area of, 144
 - macroscopic mechanical performance of, 148
 - mechanical behavior of, 145
 - network structure of, 145
 - open network structure of, 146
 - relationship between ultimate tensile strength and porosity, 148
 - structural performance of, 148
 - structure, schematic of, 144
- traction vector, defining, 172
- Transcyte silicon membrane, 577
- transformation toughened ceramic, 80
- transition region, 210
- transition time, viscoelastic transition around, 233
- transmucosal, 642
- transmucosal abutments, 513
- transparency, of PMMA, 119
- transverse fracture, 449
- transverse isotropy, 185, 186, 642
- transverse plane, 642

- transverse processes, 457, 642
- transverse testing, of cortical bone, 142
- Trapeziodal-28 (T-28) hip stem design
 - failure mechanisms of, 362
 - failures of, 426
- trauma, 424, 642
- trephine, 520, 642
- Tresca stress, 248–9
- Tresca yield criterion, 293
 - determining effective stress, 338
 - developed for a plane stress state, 247
 - expression for, 248
 - for a stress state, 256
 - shear stress needed for plastic deformation, 258
- Tresca yield surface, 247
- Tresca, Henri, 243
- Trevira/Hochfest ligament augmentation device, 572, 573
- triaxial stress state, 258
- tribology, 369, 642
- tricuspid valve, 479
- tripod blade-form ramus frame implant, 519
- tripodal subperiosteal implants, 517
- trobocollagen, 642
- tropocollagen molecules, 132
- true EPFM conditions, 314
- true material properties, 320
- true strain, 191, 642
- true stress, 191, 642
- true stress and strain compared to engineering stress and strain, 192
 - realistic picture of deformation behavior, 205
- true stress–strain behavior, 242
- trunnion, of femoral shaft, 429
- truss-like frameworks, with strategically placed struts, 516
- turbostratic carbon, 84, 642
- turbulent flow, reduction of, 488
- twisting or tearing mode (Mode III), 291
- two-dimensional polymer systems, weak van der Waals forces, 95
- two-stage surgeries, adoption of, 522
- two-stage surgery, 514
- Type I collagen, 132
- Type II collagen, 132
- Type III collagen, 132
- Type IV collagen, 133
- Type IX collagen, 132
- Type V collagen, 133
- Type VII collagen, 132
- Type XI collagen, 133
- Type XII collagen, 133
- Type IX collagen, 133
- UHMWPE, *see* ultra-high molecular weight polyethylene (UHMWPE)
- ultimate strain
 - for elastic fibers, 134
 - of tendon and ligament, 150
- ultimate strength, of metals, 27
- ultimate tensile strength (UTS), 150, 187, 642
- ultra-high molecular weight polyethylene (UHMWPE), 117, 642
 - acetabular cup, delamination of highly cross-linked, 462–3
 - as bearing material, 417
 - as polymer of choice for acetabular cups, 432
 - bearing components in total hip replacements, 284
 - bearings, wear in total joint arthroplasty, 237
 - components sterilizing with EtO or gas plasma methods, 21
 - delamination wear of, 21
 - fatigue crack propagation data for, 361
 - good wear properties, 390
 - highly crosslinked form of, 428
 - in a constraining frame of Co–Cr, 183
 - in total joint joint reconstruction, 225
 - in total joint replacements, 93
 - master curve correction factors for, 225
 - master curve for, 236, 237
 - material properties, 432
 - mechanical characterization of, 361
 - medical grade, 117
 - poor oxidation resistance of, 20, 22
 - subsurface fatigue fracture (delamination) of, 442
 - tibial knee component, oxidation of, 21
- uniaxial yield strength of, 254
 - MPa, 254
- umbilical vein, 478, 490, 642
- umbilical vein homograft, 490
- unhealthy contact, leading to pain and tissue damage, 369
- uniaxial elastic deformation, of an isotropic material, 181
- uniaxial fibers, 201
- uniaxial load, bar placed under, 171
- uniaxial loading analysis of, 175
 - as not a typical stress state, 255
- uniaxial stress, 12
- uniaxial stress state, in an isotropic ductile material, 256
- uniaxial tensile test, 241
- uniaxial tension, bar under, 172
- uniaxial yield strength, 249, 251
- uniaxial yield stress, 241, 255
- unicompartmental designs, 438
- unicondylar, 642
- unicondylar knee arthroplasty, 437
- unicondylar knee implants, 437
- unidirectional composite, example, 19
- unidirectional fiber composite, 20
- uniform attack, 643
- uniform attack mode of corrosion, 55, 56
- United Kingdom, Medicines and Healthcare products Regulatory Agency (MHRA), 410
- upper bound elastic modulus, 19
- upper thoracic spine, 454
- US Pharmacopeia, 569

- vacancies, 39
- vacant lattice site, 38
- VADs (ventricular assist devices), 495
- valence state, increase of during corrosion, 55
- valgus, 643
- valgus (knock-kneed) alignment, 436
- valleys, as lubricant reservoirs, 372
- valve design, requirements in, 488
- valves, in the heart, 479
- valvular disease, 477, 643
- van der Waals forces, 95, 643
- vanadium steel, 417, 643
- variable amplitude loading, Palmgren–Miners rule for, 343
- varus, 643
- varus (bow-legged) knees, 436
- vascular, 643
- vascular grafts, 489–91
 - evolution of materials selection for, 478
 - options, 490
 - representative sample of, 492
 - showing a range of diameters, 492
- vascular implants, development of, 156
- vascular replacement, creating a trilaminate, 157
- vascularization, 88, 643
- vasculature, interruption of the local, 447
- vector components, within the lattice, 34
- veins, 481, 643
- venous homografts, 490
- venous ulcers, 575, 643
- vent-plant implants, 522
- ventricles, 479, 480, 643
- ventricular assist devices (VADs), 495
- ventricularis, 479
- vertebra
 - constituents in individual, 457
 - individual illustration of, 457
 - stacked upon each other, 456
- Vesalius, Andreas, 129
- viscoelastic, 233, 643
- viscoelastic (glass) transition temperature, 210
- viscoelastic behavior, 210, 214
- viscoelastic body
- viscoelastic fracture mechanics (VEFM), 319–20, 643
- viscoelastic materials, 208, 212
- viscoelastic model, 214
- viscoelastic nature, of most polymers
- viscoelastic response, 223
- viscoelastic solids, 209, 213–14
- viscoelastic transition, 210, 643
- viscoelasticity, 109, 643
 - described, 209
 - introduction to, 209–14
 - of polymers, 19
- viscous (fluid) behavior, 109
- viscous dissipation, 229, 318
- viscous loss component, 229
- viscous solids, differing from inelastic solids, 318
- Vitek, failed in responsibilities to rigorously test, 543
- Vitek–Kent PT prostheses, 537, 542
- Vitek–Proplast I prostheses, failure rate, 544
- Vitredent (company), 540
- Vitredent Tooth Replacement System, 542
- Vitredent vitreous carbon root-form dental implant, 541
- vitreous carbon
 - as a potential dental material, 540
 - biocompatibility of implant materials, 540
 - forming, 540
- vitreous carbon implants
 - dismal performance of, 542
 - failure of, 540–2
- vitreous carbon Tooth Replacement System, 541
- VK glenoid fossa component, 536
- VK implants, showing particulate debris, 544
- Volkman's canals, 141, 643
- volumetric expansion, for dental implants, 82
- volumetric thermal expansion, estimating, 82
- von Helmholtz, 130
- von Meyer, 130
- von Meyer, Herman, 146
- von Mises effective stress
- von Mises ellipse yield surface, schematic of, 252
- von Mises ellipse, circumscribing the Tresca hexagon, 253
- von Mises stress effective, 251, 253–5, 260, 290
 - finding, 254
 - large sub-surface, 442
- von Mises yield criteria, 251, 260
 - better matching experimental data, 253
 - capturing complete loading, 261
 - for stress state, 256, 258
 - indicating required shear stress, 258
 - modified, 264
 - modifying, 263
 - writing in general stress component terms, 252
- von Mises yield envelope, 253, 254
- von Mises yield space
- von Mises, Richard, 243
- vulcanizing, to the titanium plates, 455
- water, in articular cartilage, 151
- wax prototype, 52
- wear, 381–6, 643
 - abrasive, 643
 - adhesive, 643
 - as situational, 391
 - contact fatigue, 643
 - corrosive, 643
 - delamination, 643
 - erosive, 643
 - for any long-term implant problem, 370
 - fretting, 643
 - in a clinical setting, 237
 - mechanism resulting in lamellar alignment in UHMWPE, 427
 - properties at expense of fracture properties, 429
 - rates, 237
 - stages of, 381
 - types of, 381
- wear bearings, highly resistant, 424

- wear debris, *see also* particulate debris, *see also* corrosion debris
- wear debris
- from fretting wear, 385
 - generation of, 369
 - particles invoking inflammation response, 381
 - setting off inflammatory cascade, 370
- wear resistance
- improved by enhanced lubrication schemes, 237
 - paramount for knee reconstruction, 11
- wear simulators, 389
- wear testing, standardization of, 370
- wide variety of test methods, 389
- wear-induced osteolysis, associated with loosening, 427
- wedge-shaped cohesive zone, for a propagating crack in UHMWPE, 305
- wedge-shaped plastic zone crack in tip zone, 305
- weight average molecular weight, 107, 109, 643
- wet precipitation techniques, 84
- Wetherill, Charles M., 398
- white blood cells, 482
- Wiles, Phillip, 417
- Wilkes, Clyde, 534
- Williams, Landel, and Ferry (WLF) equation, 234–5
- wire methods, of fixation, 453
- wires, 450, 644
- WLF equation, 234, 644
- wound healing technologies, 575
- woven or knitted materials, 561
- wrought cobalt-chromium based steels, used in orthopedic bearings, 47
- wrought Co-Cr, in hip arthroplasty, 432
- wrought steel, 47, 644
- xenografts, using bovine vasculature, 478
- xenograft, *see* heterograft
- XL-UHMWPE acetabular liners, fractured
- x - y plane, of an infinitesimal element, 175
- yield behavior, of polymer systems, 274
- yield criteria, 243, 261, 263
- yield envelope, for the plane stress case, 253
- yield strain, occurring under uniaxial yielding, 345
- yield strength, 15, 36, 187, 644
- higher, 42
 - information given by, 205
 - normalizing with effective stress, 255
 - of a material, 243
 - of cobalt-chromium, 62
 - of Co-Cr alloys, 63
 - value for a metal, 38
- yield stress, 243
- as a function of grain size, 44
 - as failure criteria, 340
 - calculated for uniaxial loading, 256
 - for 316L stainless steel, 363
 - in compression, 263
 - in tension, 263
 - increasing with increasing strain rate and decreasing temperature, 111
 - measured in uniaxial tension, 251
- yield surfaces, 244–5, 644
- boundary of, 247
 - for a planar (two-dimensional), 245
 - overlay of von Mises and Tresca, 253
- yield, in multiaxial loading conditions, 255–61
- yielding
- criterion in metals based on shear stresses, 42
 - occurring with maximum distortional energy, 249
 - occurrence of, 249
 - onset of, 243
- Young, Thomas, 130
- Young's modulus, 134, 181
- yttria-stabilized zirconium oxide, 523
- z -direction, neglecting stresses acting in, 259
- Ziegler-Natta catalysts, 99, 644
- zirconia
- properties of, 86
 - used as a bearing material, 80
- zirconia implants, manufacturers of, 524
- zirconium oxide, newer devices adopting, 506
- zone of HRR singularity, 312
- zone shielding, 320, 355