

## Index

### Notes:

1. A distinction is made between pure chemical compounds (in principle the single-crystal form of a material), and ceramics based on that compound. Intrinsic properties are listed under the chemical name of the pure material: entries relating to individual ceramic forms are listed under their ceramic names.
2. Specific physical, mechanical and chemical properties, and applications, are generally listed under the ceramics headings.

- Acheson process 175  
 Acheson, Edward 175  
 activation energy, description 7, 27, 330  
 agglomerate, formation 10, 18, 121  
 albite, soda (sodium oxide) feldspar 78  
 alumina, calcined powder 120, 121, 123, 155  
 alumina ceramics (also see aluminium oxide),  
   applications,  
     armour plate 164  
     bearings 158  
     bioceramics 162, 385  
     container material 116, 120  
     conveyor channels 158  
     cutting tool inserts 116, 158  
     cyclonic collectors 158  
     dentistry 15  
     electrical insulation 116, 156  
     femoral head 162  
     grinding media 161  
     joints, hip and knee 162  
     kiln furniture 388  
     laser source 117  
     paper making 158  
     prostheses 161  
     pump seals 158, 160  
     sodium vapour lamp envelope 130, 164  
     spark plug insulator 20, 116, 156  
     substrates 116  
     thread guides 116, 158  
     tiles and plates 158, 160  
     water mixing valves 158  
     wire drawing dies 116, 158  
 $\beta$ -alumina (sodium aluminate) 122  
 classification of materials 135  
 clean-room production 144  
 colour 136  
 composition 136  
 composition-property relationships 141  
 critical quench temperature 147  
 debased alumina, definition 115  
 density 137, 141, 162  
 dental implants 162  
 diamond grinding and polishing 155  
 electrical,  
   conductivity 151  
   properties 116, 151, 156  
 fracture,  
   energy 139  
   toughness 139  
 $\gamma$ -alumina 121, 129, 158  
 grain boundary films 132, 151, 283  
 grain size,  
   control 124, 165  
   distribution 142  
   strength dependence 142  
 hardness 136, 145  
 high alumina, definition 115  
 history 116, 385

- hot-pressed 129
- International Electrotechnical Commission (IEC)  
classification 157, 158
- liquid phase sintered 125, 130
- machining damage 140
- maximum temperature of use 141
- microstructure 5, 116, 130, 132
- plastic deformation 143
- Poisson ratio 139
- pore,  
  bloating 146  
  volume 137
- pressure-sintered, see hot-pressed
- residual stresses 119, 137
- secondary phases 131
- shear modulus 139
- sintering additive systems 124
- slow crack growth 140
- solid state sintered 124, 130
- strength,  
  bend 141  
  compression 140  
  porosity dependence 143
- surface finish 142
- $\tan \delta$  (loss tangent) 152
- thermal,  
  conductivity 145  
  expansion anisotropy 137  
  expansion coefficient 141, 146
- thermal shock,  
  resistance 147  
  *R*-parameters 148
- translucency 124, 130, 164
- velocity of sound 164
- water vapour, attack 142, 154
- wear 136, 148, 158  
  abrasive 149  
  sliding 149, 290  
  tribochemical 149
- work of fracture 164
- Young modulus 137, 141, 164  
  porosity influence 137, 138  
  temperature influence 138
- zirconia toughened alumina composites 342, 356, 364, 365
- aluminium,  
  density 89  
  production from bauxite 120  
  reactivity 261, 277, 297  
  sintering additive for silicon carbide 206, 217  
  thermal conductivity 119, 120  
  Young modulus 96
- aluminium hydroxide 122
- aluminium nitride,  
  polytypes 293  
  sintering aid for silicon carbide 222
- aluminium oxide (also see alumina ceramics),  
  aqueous corrosion 154  
  bond lengths 117  
  chemical reactivity 154  
  colour 117
- crystal,  
  lattice defects 152  
  lattice dimensions 117  
  structure 90, 117
- density 90, 117
- dielectric loss 153
- dispersion of powder in fluid media 48
- electrical conductivity 118, 151
- fracture energy 119
- fracture toughness 119
- Gibbs function, of formation 119
- hardness,  
  Mohs scale 119  
  Vickers 119
- ion lattice diffusion 117
- melting point 118
- permittivity 152
- reactions, with molten alkalis 120
- semiconductivity 118
- sintering additive for,  
  silicon carbide 222  
  silicon nitride 266, 268
- strength,  
  porosity relationship 143
- tensile 118
- theoretical 119
- $\tan \delta$  (loss tangent) 152
- thermal,  
  conductivity 119  
  expansion coefficients 119  
  Young modulus 118, 342
- aluminium silicate, see mullite
- aluminium silicon nitride oxide, see sialon
- aluminium suboxides ( $\text{Al}_2\text{O}$ ,  $\text{AlO}$ ) 119
- aluminium titanate, thermal shock resistant material 54
- aluminosilicate glass, 88, 116  
  intergranular phase 130  
  viscous flow 140
- aluminous porcelain, see porcelain, aluminous
- ammonium aluminium sulphate 123
- anorthite (calcium aluminosilicate) 78, 131
- application areas (also see individual materials) 48, 386
- armour 48, 386
- aspect (axial) ratio, of particle or grain 12, 15
- availability, of raw materials 50
- baddeleyite (mineral zirconium dioxide), 315, 317  
  Mohs hardness 348  
  processing 317
- bauxite (mineral aluminium oxide) 117, 120, 121
- Bayer process 120
- bayerite (hydrated aluminium oxide) 121
- beryllium 49
- beryllium oxide, 49  
  sintering additive for silicon nitride 266
- binders, for powder particles 11
- bioceramics 162, 370, 386
- blast furnace, silicon carbide use 177
- bloating 84, 100

boehmite (hydrated aluminium oxide) 122  
 boron, silicon carbide sintering aid 206, 216  
 boron carbide, wear resistant 48, 54, 386  
 boron nitride,  
   cubic, wear resistant 54  
   inert powder bed in silicon nitride sintering 271  
 Boyle's law 85

calcium carbonate (chalk) 126  
 calcium hexaluminate 131  
 calcium monosilicate 126, 132  
 calcium oxide, 48, 125  
   densification system for alumina 126  
   in  $\alpha'$ -sialon 294  
   stabiliser for zirconia ceramics 317, 359  
 calcium oxide stabilised zirconia, see zirconia,  
   calcium oxide stabilised,  
 calcium zirconate 326  
 carbon 35  
   allotropes 3  
   silicon carbide production 35, 176, 210, 216  
   solubility in liquid silicon 210  
 carbon monoxide (reducing atmosphere) 194  
 carborundum (silicon carbide) abrasive 54, 175, 229  
 carbothermal reduction, of silicon dioxide to silicon  
   nitride 248  
 cast iron, machining 299, 367  
 catalyst supports 54, 387, 388  
 cements, hydraulic 57  
 ceramic, definition 1  
 cerium oxide, stabiliser for zirconia ceramics 363  
 cerium oxide stabilised zirconia, see zirconia, cerium  
   oxide stabilised  
 chemical potential, see Gibbs function  
 chemical vapour deposition (CVD) 201, 224, 249  
 chromium (III) oxide 117, 136  
 clay,  
   analyses 70  
   ball 69  
   china 63, 69  
   classification 9, 11, 69, 70  
   plasticity 69  
 clay-bonded silicon carbide 222  
 close-packing, particle 16  
 coefficient of thermal expansion (also see individual  
   materials) 43  
 colloid, colloidal particle, definition 13  
 composites, 390  
   alumina-zirconia 342, 356, 364, 365, 391  
   alumina-titanium carbide 391  
 container materials 106, 116  
 coordination number, of void 31  
 copper, thermal conductivity 119, 186  
 cordierite (magnesium aluminosilicate), 131, 272  
   catalyst support 54, 388  
 corundum (also see aluminium oxide) 121  
 crack,  
   deflection 340  
   shielding 336, 339  
 creep (also see individual materials) 96  
 cristobalite (silicon dioxide), 50

in porcelain 68, 86  
 critical,  
   quench temperature (also see individual materials)  
   45  
   stress 37  
   stress intensity factor (see also individual materials)  
   39  
 crystal lattice (also see individual materials),  
   defects 4, 202  
   energy 27  
 cutting tool inserts 116, 386  
 CVD, see chemical vapour deposition

deflocculation 12  
 density (also see individual materials),  
   bulk 65  
   green 21  
   theoretical (true solid) 20  
 dentistry 66, 77, 387  
 diamond, 3  
   density 183  
   machining and polishing 9, 16, 297  
   refractive index 347  
   thermal conductivity 186  
 diaspora (hydrated aluminium oxide) 121, 122  
 dicalcium silicate,  
   destructive phase change 50, 325  
 diesel engine components and exhaust gas filters 178,  
   231, 387  
 diffusion (also see oxygen),  
   cations, in porcelain 80  
   coefficients 13, 28  
   grain boundary 203  
   lattice 203  
   surface 203  
 diffusionless (martensitic) transformation 322  
 dispersed oxide ceramics (also see zirconia  
   ceramics) 365  
 duplex structures in zirconia ceramics 358  
 dusting 50

economic factors 297, 390  
 Einstein equation 83  
 electrical properties (also see individual materials),  
   52, 179, 189  
   insulation 13, 54, 66, 99, 106  
 elemental abundance 51, 315  
 emery (corundum) 117  
 engineering ceramics, definition 115  
 enstatite see magnesium monosilicate  
 evaporation-condensation mechanism, in powder  
   sintering 265, 276  
 exhaust gas filtration 178

failure probability 41  
 Faraday, Michael 54  
 feldspar,  
   potash (potassium oxide) 68, 222  
   relicts, in porcelain 80, 86  
   sintering additive for clay-bonded silicon  
   carbide 222

- soda (sodium oxide) 78
- ferroelastic switching in zirconium dioxide 345
- ferroelasticity 345
- ferrous alloys,
  - machining 260
  - reaction with silicon nitride 290
- Fick's first law 28, 192
- fillers, in porcelain 68, 81
- fine china 63
- firing (also see sintering), 11, 74
  - porcelain 75
- flaws 38
- flint (quartz) 81
- fluidised bed, for coating production 201, 224
- fluxes 62, 76
  - aluminosilicate 67
  - feldspathic 68, 71
- forsterite (dimagnesium silicate) 157
- fracture (also see individual materials),
  - surface energy 39
  - toughness 39
- free-radicals, in the CVD process 201
- gas filters 387
- gehlenite (calcium aluminosilicate) 131
- Gibbs function, molar (chemical potential) 24, 26, 32, 329
- gibbsite (hydrated aluminium oxide) 121, 122
- glass, 56, 65, 88
  - aluminosilicate 88
  - expansion coefficients 94
  - in porcelain 65, 67, 88
  - toughened 99, 345
  - transition temperature 67, 88
  - viscosity 90, 139
- glaze, 62, 98, 197
  - compressive stresses 99
  - fit 99
- grain,
  - aspect ratio 12, 15
  - boundary, 5
    - thin films 5, 7, 69, 116, 132
  - growth control 23, 29, 124, 129
  - size, effect on phase stability 332
  - size-strength relationship 23
- graphite, 3
  - second phase in silicon carbide 217
  - substrate material for CVD process 224
- green, explanations,
  - body 62
  - density 21
- Griffith equation 39, 41, 339
- grinding,
  - media 106, 161
  - wheels 177
- hafnium carbide 48
- hafnium dioxide, impurity in zirconium dioxide 318
- hard-metals (cemented carbides) 48
- heat-work 74
- heavy clays 57
- high-voltage insulation 116
- hip joint replacement 386
- history, 385
  - alumina ceramics 116, 385
  - porcelain 62, 385
  - silicon carbide ceramics 175, 385
  - silicon nitride ceramics 249
  - zirconia ceramics 385
- hot-isostatic pressing 267
- hot-pressing 8, 129, 198
- hydrofluoric acid 106, 154
- hydrogen,
  - bonding 28
  - reducing atmosphere 194
  - solubility in aluminium oxide 124
- illite (clay mineral) 70
- in situ* reinforcement, in silicon nitride 283
- injection moulding 12
- interfacial energy 20, 23, 32, 205
- internal combustion engine 55, 116
- International Electrotechnical Commission (IEC)
  - classification 67, 103, 157, 158
- ionic,
  - conductivity 105
  - diffusion 80
  - polarisability 105
- iron, density 89
- iron oxide 49, 85
- isostatic pressing 12
- kaolinite (clay mineral), 70, 71, 73
  - relicts in porcelain 80, 86
  - sintering additive for alumina 127
- kiln furniture 388
- kinetic energy absorption 164
- knee replacement 386
- laboratory ware 66
- lanthanide oxides, in  $\alpha'$ -sialon 294
- laser radiation source 117
- lattice,
  - defects 4, 152, 202, 332, 354
  - energy 27
- layer silicate 69
- lead, in pottery glaze 49
- lead "crystal" (glass) 56
- leucite (potassium aluminium silicate) 78
- lime (calcium oxide) 125
- liquid,
  - filters 387
  - supercooled 89
  - transitory, in sintering 272
  - viscosity 82
- liquid-phase sintering (also see individual materials) 125
- lithium oxide, in  $\alpha'$ -sialon 294
- loss on ignition 84

- magnesium aluminate (spinel) 131, 132  
 magnesium aluminosilicate (cordierite) 54  
 magnesium hydroxysilicate (talc), 13, 126  
   electrical insulator 13, 50  
 magnesium monosilicate (enstatite) 46, 126  
 magnesium nitride, densification system for silicon nitride 266  
 magnesium oxide,  
   densification system for alumina 124, 126, 165  
   densification system for silicon nitride 266, 268  
   hydrolysis 48  
   stabiliser for zirconia ceramics 316  
 magnesium oxide stabilised zirconia, see zirconia, magnesium oxide stabilised  
 magnesium silicates in silicon nitride 266  
 magnesium zirconate 326  
 manganese oxide, in porcelain semiconducting glaze 64  
 martensitic transformation, in zirconium dioxide 322  
 matte, silicon nitride whisker form 273  
 melilite, see yttrium silicon oxynitride  
 melting points, table of values 4  
 metakaolin (dehydrated kaolinite) 72, 80  
 methyltrichlorosilane, in CVD silicon carbide production 201, 224  
 microcline (feldspathic mineral) 69, 78  
 microcrack toughening (also see zirconia ceramics) 343  
 microspheres, free-flowing powders 10, 18  
 microstructure (also see individual materials) 86  
 Mohs hardness scale 119  
 Moissan, Henri 175  
 moissanite, meteoritic silicon carbide 175  
 molochite, mould material 74  
 montmorillonite (clay mineral) 70  
 MOX (mixed oxide) nuclear reactor fuel 49  
 mullite (aluminium silicate), 20, 34, 131  
   applications 388  
   density 90  
   in porcelain 67, 72, 86  
   melting point 54  
   primary 73, 81  
   secondary 81, 86, 102  
   tertiary 100, 102  
   thermal expansion coefficient 93  
 nanopowder, definition 13  
 near net-shaping 9  
 nepheline syanite (aluminosilicate mineral) 78  
 Nernst electrical conductivity 105, 354  
 nickel-based alloys, machining 300  
 nierite, meteoritic silicon nitride 247  
 nitridation, of silicon in production of silicon nitride 248, 273  
 nitrogen,  
   equilibrium pressure over silicon nitride 247  
   in Earth's atmosphere 50  
   glasses 268  
   nuclear power, fuel 182  
   once-firing, of porcelain 62  
   onion skinning 12  
   orthoclase (feldspathic mineral) 69, 78  
   Ostwald ripening 33  
   oxidation (also see silicon carbide, and silicon nitride) 191  
   oxide films, on non-oxide powders 205  
   oxygen diffusion  
     in silicates 264  
     in silicon dioxide 261, 264  
     in zirconium dioxide 352, 355  
     pressure measurement 355  
   parabolic rate law 192  
   particles, see powder particle  
   plutonium dioxide, nuclear fuel material 49  
   Poisson ratio (also see individual materials) 43  
   polytypism, in silicon carbide 180  
   polytypoid, aluminium nitride 293  
   porcelain,  
     aluminous 64, 68, 100, 106  
     strength 103, 115  
     maximum temperature of use 141  
   application areas 107  
   containers 106  
   dental 66, 77, 387  
   electrical insulation 66, 99, 106  
   grinding media 106  
   laboratory ware 66  
   bloating 100  
   classification 103  
   compositions 71  
   creep 96  
   density 89  
   electrical properties 62, 104, 106  
   fillers 68, 81  
   firing schedules 75  
   fluxes 78, 125  
   fracture toughness 97  
   fully vitrified 65, 66  
   glass, 88  
     influence on property 67  
     mean expansion coefficient 94  
   glaze, 98  
     compressive stress 99  
     fit 99  
   hardness 103  
   ionic conductivity 105  
   liquid viscosity 82  
   microstructure 86  
   properties 86  
   relicts 80, 86  
   residual stresses,  
   siliceous 63, 68, 87, 106  
     maximum temperature of use 141  
   strength 98  
     bend 63  
     high temperature 103  
     improvement 100  
     porosity relationship 98

- quartz, influence 98
- surface compressive glazes 100
- thermal,
  - expansion 92
  - mismatch stresses 92, 95, 100, 101
  - shock 104
- translucency 64
- triaxial, compositions 68
- wear rate 103
- Young modulus 96
- porosity, 7, 40
  - relationships with strength 41
  - shrinkage during sintering 205
- potash (potassium) feldspar 68
- potassium oxide, 47
  - basis for aluminosilicates 68, 125
- pottery,
  - glaze 49
  - history 67
  - strength 67
- powder particle,
  - agglomeration 18
  - aspect ratio 15
  - packing,
    - close 16
    - efficiency 15, 17
    - homogeneity 31
  - size 13, 15
    - distribution 13, 17
    - effect on zirconium dioxide phase stability 332
- pressure sintering, see hot-pressing
- pressureless sintered, see sintered,
- probability of failure 41
- processability 10, 51
- prostheses (see also bioceramics) 386
- quartz (silicon dioxide) 50
  - conversion (displacive) 94
  - crystal structure 90
  - in porcelain 68, 81, 86
  - quartz “crystal” glass 56
  - residual stresses 93
  - thermal expansion coefficient anisotropy 93
  - transformation (reconstructive) 94
- R*-curve behaviour 40, 283, 341
- R* (thermal shock resistance) parameters (also see individual materials) 46
- radar 156
- Ramsdell notation, for polytypes 181
- rare earth oxides, sintering additives for silicon nitride 269
- reaction-sintering (reaction bonding) 35, 74
- reactive alumina ( $\gamma$ -alumina) 129
- reconstructive transformation 94, 252, 266
- red mud, waste product from the Bayer process 121
- refractive index (also see individual materials) 65
- refractories 56
- relicts, in porcelain,
  - feldspar 80, 86
  - kaolinite 80, 86
  - ruby (single crystal aluminium oxide) 117, 136
- salt glazing 197
- sand-blasting 48
- sapphire (single crystal aluminium oxide) 117, 118
- sapphirine (magnesium aluminosilicate) 131
- scaling laws 21, 336
- semiconductivity 179, 189
- shear modulus 43, 336
- shrinkage, also see sintering 84
- sialon (silicon aluminium oxynitride), 46, 271, 291
  - $\alpha'$ -sialon phase, 291, 294
    - additive oxides 294
    - composition range 277, 294
    - crystal structure 294
    - hardness 296
    - production 294, 296
    - thermal expansion coefficient 296
    - transformation to  $\beta$ -sialon 295
  - $\beta'$ -sialon phase, 291
    - bond lengths 292
    - composition range 292
    - crystal structure 292
    - system 292
- silica, see silicon dioxide
- silicates,
  - corrosion product 195, 264
  - sintering aid 32
  - thin intergranular film 5, 7, 69, 116, 132
- silicon,
  - liquid in silicon carbide 200, 210
  - melting point 273
  - nitridation, 199, 248, 273
    - heat of reaction 273
    - volume expansion 276
  - oxidation 191
  - reaction with carbon to form silicon carbide 35, 210
  - single crystal 3
- silicon aluminium oxynitride, see sialon
- silicon carbide (also see silicon carbide ceramics), 175
  - $\alpha$ -phase 180
  - atomic structure 178
  - $\beta$ -phase 180
  - blast furnace refractory 177
  - colour 179
  - conduction band gap 189
  - corrosion 195
  - crystal structure 179
  - decomposition 190, 203
  - density 183
  - diffusion,
    - atom self-diffusion coefficients 202
    - grain boundary 203
    - lattice 203
    - surface 203
  - electrical conductivity 179, 189
    - influence of temperature 189
  - epitaxial deposition 212
  - fibres, strength 184
  - fracture

- silicon carbide (cont.)  
 energy 184  
 toughness 184  
 Gibbs function of formation 176, 190  
 hardness,  
 indentation 184  
 Mohs scale 184  
 history 175  
 hot-pressing 198  
 impurity elements 189  
 industrial production 176  
 interfacial energies,  
 grain boundary 205  
 surface 205  
 lattice,  
 defects 202  
 parameters 181  
 melting point 178, 190  
 modulus,  
 bulk 183  
 shear 183  
 Young 183  
 oxidation, 191, 194, 228  
 active 194  
 natural oxide film 195, 205  
 passive 191  
 Poisson ratio 183  
 polytype stability 182, 190  
 polytypism 178, 180  
 pore shrinking, condition for 205  
 production 48, 176, 182  
 refractive index 178  
 single-crystal wafers 182  
 sintering (also see individual materials),  
 liquid phase 32  
 pore shrinkage, critical condition for 205  
 shrinkage 16, 28  
 solid state 20, 22, 29  
 strength, theoretical tensile 184  
 surface energy, see interfacial energy  
 thermal,  
 conductivity 185  
 expansion anisotropy 185  
 expansion coefficient 185  
 thermal shock, 187  
 critical quench temperatures 187  
*R*-parameters 187, 188  
 stability 190  
 unit cell dimensions 181  
 “unsinterability” 198  
 vapour phase species 190  
 velocity of sound 234  
 wear 191  
 whiskers, strength 184  
 Young modulus 183  
 silicon carbide ceramics (also see individual forms),  
 48, 206, 207  
 applications, 225, 226  
 abrasive 48  
 armour 48, 233, 386  
 cutting and grinding 177, 229  
 diesel engine components 178  
 exhaust gas filters 225, 226, 231  
 gas pipeline seals 233  
 gas turbine 178, 234  
 general industrial 225  
 heat exchangers 228  
 heating element 189, 226  
 hot gas filtration 178, 225, 231, 387  
 internal combustion engine 177, 185, 234  
 kiln furniture 199, 225, 388  
 molten metal filter 231  
 maximum temperature,  
 service 195, 207, 227  
 surface 195  
 metal cutting and grinding 177  
 nuclear power industry 177, 200, 201, 234  
 paper-making 233  
 particulate filters 387  
 protective linings 199  
 pump seals 232  
 radiant heating 228  
 tiles, wear resistant 199  
 history 385  
 silicon carbide, chemical vapour deposited, see  
 silicon carbide, CVD  
 silicon carbide, clay-bonded 29, 222, 225  
 silicon carbide, CVD, 201, 224  
 botryoidal morphology 201  
 coatings 224, 234  
 density 225  
 electrical conductivity 225  
 fluidised bed coating 201, 224  
 hardness 225  
 microstructure 201, 224  
 production 224  
 strength 225  
 Young modulus 225  
 silicon carbide, hot-pressed,  
 critical quench temperature 187  
 silicon carbide, liquid phase sintered, 222  
 $\beta$ -phase to  $\alpha$ -phase conversion, 224  
 density 222  
 fracture toughness 223, 224  
 intergranular glass 223  
 microstructure 222  
 production 222  
 sintering additives 222  
 strength 222, 224  
 thermal expansion mismatch 223  
 Young modulus 222  
 silicon carbide, nitride-bonded, 199  
 oxidation 228  
 silicon carbide, pyrolytic, see CVD silicon carbide  
 silicon carbide, reaction-bonded, 200, 232  
 critical quench temperature 187  
 epitaxial growth of silicon carbide 212  
 fracture toughness 215  
 grain size 214  
 high-temperature loss of strength 214  
 microstructure 212  
 oxidation

- production 210
- properties 214
- reaction volume expansion 211
- secondary silicon carbide 210
- silicon content 212, 214
- strength 214
- thermal,
  - conductivity 216
  - shock behaviour 187
- wear 215
- Young modulus 214
- silicon carbide, reaction-sintered, see silicon carbide, reaction-bonded
- silicon carbide, recrystallized, 199
  - bulk density 208
  - electrical conductivity 209
  - microstructure 208
  - oxidation 209
  - porosity 199, 208
  - production 208
  - strength 208
  - thermal conductivity 210
  - Young modulus 208
- silicon carbide, self-bonded, see silicon carbide, reaction-bonded
- silicon carbide, siliconised, 200, 216,
  - microstructure 216
- silicon carbide, solid state sintered, 202, 216, 232
  - bulk density 217
  - fracture toughness 219
  - graphite second phase 217
  - hardness 184
  - maximum temperature of use 219
  - microstructure 195, 212, 217, 233
  - production 216
  - sintering additives,
    - aluminium 206, 217
    - boron 206, 216
    - carbon 206, 216
  - strength 218
  - thermal,
    - conductivity 186, 219
    - shock 219
  - wear 191, 219, 233, 290
  - Young modulus 219
- silicon diimide, source of silicon nitride 248
- silicon dioxide (silica), 13, 50, 124
  - crystalline phases 50, 325
  - impurity, in zirconia ceramics 357
  - in silicon carbide production 176
  - phase conversion (displacive) 94
  - phase transformation (reconstructive) 94
  - protective films during oxidation 261, 263, 288
  - reaction with nitrogen 248
  - structure, schematic 196
  - surface films 195, 205, 261
- silicon monoxide 47, 194, 248
- silicon nitride,
  - $\alpha$ -silicon nitride solid solution, see  $\alpha'$ -sialon
  - band gap 255
  - $\beta$ -silicon nitride solid solution, see  $\beta'$ -sialon
  - bond lengths 292
  - bulk modulus 256
  - colour 255
  - corrosion 263
  - covalency 246
  - critical quench temperature 257
  - crystal structure, 251
    - $\alpha$ -phase 251
    - anisotropy 256
    - $\beta$ -phase 251
    - reconstructive transformation 252, 266
- CVD (also see CVD silicon nitride) 249
- $\gamma$ -phase silicon nitride 246
- densification,
  - additives 267, 269
  - hot-pressing 265
  - systems 268, 269
- density 254, 256
- diffusion coefficients 254, 272
- dissociation 247, 260, 270
- electrical conductivity 258
- fracture toughness 256
- $\delta$ -phase silicon nitride 246
- hardness 256
- hot-isostatic pressing 267
- internal combustion engine components 250
- lattice dimensions 252
- magnesium silicate, intergranular phase 266
- modulus,
  - bulk 256
  - Young 256
- nielite, meteoritic silicon nitride 247
- nitrogen, equilibrium pressure 247
- oxidation, 261
  - active oxidation 261
  - mechanism 261
  - passive oxidation 261
  - volume expansions 290
- oxide protective films 261, 263
- oxygen,
  - internal, in crystal lattice 263
  - powder impurity 249, 253, 263
- phase,
  - in nitride-bonded silicon carbide 199
- Poisson ratio 256
- powder production, 247, 273
  - from silicon diimide 248
  - from silicon dioxide 248
  - from silicon tetrachloride 248
  - oxygen content 263
  - properties 249
- pressureless sintering 270
- production, by silicon nitridation 248, 273
- reactions with,
  - aluminium 261, 277
  - ferrous alloys 260, 290
- reconstructive transformation 252, 266
- single-crystal strength 260
- thermal,
  - conductivity 257
  - expansivity 257



- single-crystal strength (cont.)
  - shock resistance 257, 259
  - stability 260
- thin films 249
- unit cell dimensions 253
- “unsinterability” 265
- volatility, suppression 270
- whiskers from silicon nitridation 273
- Young modulus 256
- silicon nitride, amorphous 18
- silicon nitride, ceramics (also see individual forms),
  - applications, 296
    - aluminium processing 297
    - bearings 291, 300
    - cast iron 299, 300
    - diesel engine components 301
    - electrical heating element support 298
    - gas-turbine 301
    - general industrial 297
    - inert gas welding nozzle 298
    - internal combustion engine 250
    - machining
    - metal cutting 299
    - metal working 299
    - nickel-based alloys 300
    - pump components 297, 301
    - refractory 249
    - thermocouple sheaths 250, 297
    - turbocharger rotor 250, 302
    - valve lifting components 301, 303
  - history 249
- silicon nitride, CVD 249
- silicon nitride, hot-isostatic pressed, 267
  - in ball bearings 300
- silicon nitride, hot-pressed, 265, 291
  - densification additives 266, 268
  - microstructure 266
  - production 265
  - strength 266
- silicon nitride, reaction-bonded, 248, 265, 272
  - $\alpha/\beta$ -silicon nitride ratio 274
  - $\alpha$ -silicon nitride, oxygen content 253
  - $\alpha$ -silicon nitride whiskers 273, 277
  - density, bulk 277
  - electrical conductivity 277
  - exothermic, nitridation reaction 273
  - formation 273
  - fracture,
    - energy 282
    - toughness 282
  - hardness 279
  - microstructure 273, 277
  - oxidation 280
  - pore size 278
  - porosity 277
  - production mechanism 248, 273, 276
  - strength, 279
    - porosity relationships 280
    - temperature relationship 280
  - thermal,
    - conductivity 282
    - expansion coefficient 282
    - shock resistance 282
  - thermocouple sheathing 250
  - volume expansion, during silicon nitridation 276
  - Young modulus 278
- silicon nitride, reaction-sintered, see silicon nitride, reaction bonded
- silicon nitride, sintered, 270, 282
  - annealing, post-densification 286
  - corrosion 288
  - crack bridging 283
  - creep 286
  - densification additives 266, 267
  - density 286
  - fracture toughness 286
  - grain boundary films 5, 7, 283
  - in situ* reinforcement 283
  - intergranular silicate 266, 270, 289
  - microstructure 5, 282
  - oxidation, 288
    - protection 288
    - volume expansion 288
  - powder bed technique 271
  - production 282
  - R-curve behaviour 283
  - strength 286
  - thermal,
    - conductivity 287
    - expansivity 287
    - shock, critical quench temperature 287
  - transitory liquid, during sintering 272
  - wear, 290
    - sliding 290
    - tribochemical 290
  - Young modulus 286
- silicon nitride, solid solutions, see sialons
- silicon oxynitride (silicon nitride oxide),
  - barrier layer 261
  - bond phase in nitride-bonded silicon carbide 199
  - oxidation product of silicon nitride 261
- silicon tetrachloride 248
- silver, thermal conductivity 186
- sintering (also see individual materials), 4, 20
  - liquid phase 32
  - shrinkage 16, 28, 84
  - solid state 20, 22, 29, 124, 357
- skull melting, single crystal growth 347
- slip, description 12
- slip-casting, description 8, 12, 19
- smoke filters 231
- soapstone, see magnesium hydroxysilicate
- sodium chloride,
  - high temperature oxidation 196
  - use in Acheson process 176
- sodium oxide, 47, 122
  - basis for aluminosilicate systems 68, 125
  - corrodant for non-oxide ceramics 196
- sodium zirconate, in zirconium dioxide, extraction 318
- solubility–stress relationship (see also Ostwald ripening) 32

- spalling 99
- special ceramics, definition 56
- specific surface area, definition 15, 71
- spray drying of powders 18
- steatite (soapstone), see magnesium hydroxysilicate steel,
- cutting 367
  - density 347
  - ultimate tensile strength 40
- strain,
- at failure 37
  - energy 335
  - shear 324, 336, 341
- strength (also see individual materials), 37
- bend 37
  - compression 38
  - distribution 41
  - porosity relationship 41
  - tensile 37
  - theoretical 38
  - ultimate tensile 40
- stress,
- critical 37, 39
  - intensity factor 39
  - residual 93, 119, 137
- substrates, electrical 116
- supercooled liquid 89
- superheated water, influence on strength of zirconia ceramics 353
- surface
- compression toughening 344, 345
  - energy see interfacial energy
  - stress 99
- systems,
- $\text{Al}_2\text{O}_3\text{-SiO}_2$  73, 293
  - $\text{Al}_2\text{O}_3\text{-SiO}_2\text{-Si}_3\text{N}_4\text{-AlN}$  292
  - $\text{CaO-Al}_2\text{O}_3\text{-SiO}_2$  32, 78
  - $\text{CaO-SiO}_2$  124
  - $\text{CaO-ZrO}_2$  326
  - $\text{CeO}_2\text{-ZrO}_2$  326
  - $\text{K}_2\text{O-Al}_2\text{O}_3\text{-SiO}_2$  68, 76, 78
  - $\text{MgO-Al}_2\text{O}_3\text{-SiO}_2$  272
  - $\text{MgO-Al}_2\text{O}_3\text{-SiO}_2\text{-Si}_3\text{N}_4$  269, 272
  - $\text{MgO-SiO}_2$  268
  - $\text{MgO-SiO}_2\text{-Si}_3\text{N}_4$  268
  - $\text{MgO-ZrO}_2$  326
  - $\text{Na}_2\text{O-Al}_2\text{O}_3\text{-SiO}_2$  32
  - $\text{Y}_2\text{O}_3\text{-SiO}_2\text{-Si}_3\text{N}_4$  269
  - $\text{Y}_2\text{O}_3\text{-ZrO}_2$  326
- talc, talcum powder (also see magnesium hydroxysilicate) 13, 50
- teeth 386
- thermal barrier layer, see zirconia ceramics
- thermal conductivity, see individual materials
- thermal expansion,
- coefficients (also see individual materials) 43
  - mismatch stresses, 92, 95, 100, 101, 137
  - shock (also see individual materials), 44, 104
    - critical quench temperature 45
    - induced stresses 43, 92
- R*-parameters 46
- “unsinterable” powders 198, 265
- titanium carbide, composites 158, 391
- titanium dioxide, delustrant 158
- titanium tetrachloride 47
- toughened glass 99, 345
- toughening (also see zirconia ceramics, toughening mechanisms) 40
- toxicity 49
- transformation induced plasticity (TRIP) 339
- transition aluminas, see  $\gamma$ -alumina
- translucency 64, 124, 130
- triaxial porcelain system 68
- tribochemical wear see wear
- tridymite (silicon dioxide) 50
- triple point 34, 132
- tungsten carbide 48
- tungsten oxide 47, 48
- twinning, see zirconium dioxide
- uniaxial pressing, of powders 11
- uranium carbide, nuclear fuel material 224, 234
- uranium dioxide,
- in pottery glazes 49
  - melting point 12
  - nuclear fuel material 49, 224, 234
- uranium hexafluoride 47
- van der Waals forces 69
- viscosity, glass and liquid 82, 90
- vitreous china 63
- vitrification, vitrified 34, 65, 66, 83
- void, elimination 21, 30
- water,
- corrosion of alumina ceramics 142, 154
  - degradation of zirconia ceramics 317, 372, 373
  - of crystallisation 22
- wear (also see individual materials), 103, 386
- abrasive 149
  - sliding 149
  - tribochemical 149
- Weibull parameter (modulus) 41
- whiteware, strength 67
- wire-drawing dies 116
- wollastonite (calcium monosilicate) 126
- work of fracture (also see individual materials) 39
- Young modulus (also see individual materials) 37
- yttrium aluminium garnet 270
- yttrium oxide,
- hydrolysis 353
  - in  $\alpha'$ -sialon 294
  - sintering additive for,
    - silicon carbide 222
    - silicon nitride 268, 269, 288
    - zirconium dioxide 362
- yttrium oxide stabilised zirconia, see zirconia, yttrium oxide partly stabilised
- yttrium silicon oxynitride (melilite) 288

- zircon (zirconium silicate) 318
- zirconia, calcium oxide partially stabilised (Ca-PSZ), 317, 359
- aging 362
  - composition 359
  - strength 360
- zirconia, ceramics, 355
- applications, 366
    - ball bearings 370
    - bioceramics 370
    - cutting – fibres, paper 368
    - cutting tool inserts 367
    - degradation 353
    - die linings 316, 367
    - filters – molten metal 367
    - industrial refractory 315
    - internal combustion engines 372
    - knives 368
    - metal working 367
    - prostheses 370
    - pump components 368
    - thermal barrier coatings (TBC) 349, 372
    - transport 372
    - turbine engine, coatings 349, 372
  - composites 342, 356, 365, 367
  - creep 352
  - degradation by water 317, 353
  - dispersed oxide ceramic 365
  - duplex structures 358
  - electrical conductivity 316, 354
  - fracture toughening mechanisms 317, 340
  - fully stabilised 321
  - grinding, influence on strength 345
  - history 385
  - in vitro* stability 373
  - intergranular silicate 347, 357
  - microcracking 343, 351
  - microstructures, duplex 358
  - non-transformable tetragonal phase, see *t*-phase
  - oxide ion mobility 352
  - partially stabilised 317, 322, 359, 360, 362, 363
  - phase stability 352
  - properties 364
  - silicon dioxide, impurity 357
  - sintering 356, 357, 359
  - strength – influence of, 317
    - aging 360
    - temperature 352
    - water 317, 353
  - surface stresses 353
  - terminology 355, 356
  - thermal stability 351
  - transformation toughening 40, 338, 365
  - toughening mechanisms,
    - crack deflection 340
    - crack shielding 339
    - ferroelastic 345
    - microcracking 338, 340, 343, 344
    - surface compression 99, 344, 345
  - wear, 353, 368
    - sliding 353
    - tribochemical 353
- zirconia, cerium oxide partially stabilised (Ce-PSZ), 363
- composition 363
  - critical grain size 363
  - fracture toughness 363
  - microstructure 363
  - strength 363
- zirconia, fully stabilised cubic, 356
- electrical conductivity 354
  - lattice defects 354
  - oxygen mobility 355
  - oxygen pressure measurement 355
- zirconia, magnesium oxide partially stabilised (Mg-PSZ), 316, 360
- aging 360
  - composition 360
  - fracture toughness 361
  - microstructure 360
  - strength 361
- zirconia, partially stabilised (PSZ), 322, 358
- sintering schedules 359
- zirconia, tetragonal polycrystal (TZP), 362
- composition 362
  - fracture toughness 363, 371
  - microstructure 362
  - stability 372
  - strength 363, 371
  - water induced loss of strength 353, 363, 372
  - wear 353
  - yttrium oxide stabilised (Y-TZP) 362
- zirconia, toughened alumina (ZTA), 342, 356, 365, 367, 391
- ceria stabilised, 366
    - fracture toughness 366
    - strength 366
  - commercial ZTA, 366
    - fracture toughness 366, 367
    - strength 366, 367
  - yttria stabilised, 365
    - fracture toughness 366
    - microstructure 365
    - strength 366
- zirconia, toughened ceramics (ZTC), 365
- microcrack toughening 365
  - transformation toughening 365
- zirconia, yttrium oxide partly stabilised (Y-PSZ), 362
- composition 362
  - microstructure 362
- zirconium, oxidation states 315
- zirconium diboride 52
- zirconium diboride, electrical conductor 52
- zirconium dioxide (also see zirconia ceramics),
- athermal transformation 323
  - band gap 354
  - baddeleyite,
    - mineral 315
    - processing 317
  - bond lengths 319
  - covalency 319
  - crack,

- deflection 340
  - shielding 336, 339
- crystal chemistry 319
- cubic phase 319, 321
- $\delta$ -phase ( $\text{Mg}_2\text{Zr}_5\text{O}_{12}$ ) 326
- density 320, 347
- diffusion coefficients 357
- electrical conductivity 316, 354
- enthalpy of formation 330
- entropy of formation 330
- ferroelasticity 345, 325
- ferroelastic switching 346
- Gibbs function,
  - formation 315
  - transformation 329
- hafnium dioxide impurity 318
- hardness 348
- interfacial energy 333, 334
- ionic radii 319
- lattice,
  - defects 332, 354
  - dimensions 320
- martensitic (diffusionless) transformation 322
- melting point 315, 321
- microcracking 336, 340, 343, 351
- monoclinic phase 319, 323
- natural abundance 315
- non-stoichiometry 315
- non-transformable tetragonal phase, see  $t'$ -phase
- orthorhombic phase 320
- oxygen,
  - equilibrium pressure 315
  - ion mobility 354
- phase,
  - equilibrium diagrams 325
  - nucleation 337
  - stabilisation 321, 328
  - stability 321
  - transformation (martensitic) 322
- $\phi$ -phases 326
- Poisson ratio 348
- polymorphism 316
- powder,
  - analyses 357
  - production 317, 318
- $R$ -curve behaviour 341
- refractive index 347
- shear modulus 336, 348
- single-crystal growth 347
- stability 315, 351
- $t'$ -phase (non-transformable tetragonal phase) 322, 363
- temperature,
  - critical transformation 328, 343
  - influence on phase stability 328
- tetragonal phase 319, 322
- tetragonal-to-monoclinic transformation,
  - 50, 317
  - critical temperature 328, 343
  - enthalpy 330
  - grain size influence 332
  - grinding, induction 345
  - shear strain 324, 336, 341
  - strong transformers 342
  - subcritical 341
  - supercritical 341
  - temperature 343
  - toughening 338, 340
  - transformation enthalpy 330
  - volume,
    - change 324
    - strain energy 335
  - weak transformers 342
- thermal,
  - anisometry 349
  - barrier layer 349
  - conductivity 349
  - critical quench temperature 351
  - expansion coefficient 349
  - hysteresis 323
  - $R$ -parameters 350
  - shock 350
- thermodynamic stability 315
- twinning 336, 341
- unit cell,
  - dimensions 320, 324
  - volume change 324
  - volume instability 316
- Young modulus 347
- zirconium oxychloride, in zirconium dioxide
  - extraction 318
- zirconium silicate, see zircon