

Index

- A**
Ackeret’s transformation, 509
Active Aeroelastic Wing project, 732–733
Adiabatic flow, 441–443
 equation for supersonic wind tunnel, 443–444
 one-dimensional, 442–443
Adiabatic-flow relations for a perfect gas, 456
Aerodynamic coefficients, 134
 induced drag factor and lift-curve slope parameter for, 371–372
 monoplane equation for, 367–371
Aerodynamic design philosophy, 789–790
Aerodynamic forces acting on an airplane, 34
Aerodynamic forces and moments,
 characterization of
 aircraft parasite drag, 263–270
 boundary-layer transition, 256–259
 drag coefficient, 252–254
 effects of compressibility, 476–479
 general comments, 227–230
 lift coefficient, 244–248
 local skin friction, 254–255
 long bubble separation, 248
 Mach number, effects of, 257
 moment coefficient, 250–252
 parameters governing, 230–231
 pressure force acting on vehicle surface, 244–245
 pressure gradient, effects of, 257
 resultant force component, 245
 Reynolds number, 245, 248, 256
 shock/shock interactions, 482–484
 shock-wave boundary-layer interaction, 480–482
 short bubble separation, 248
 surface roughness, effects of, 257, 259–262
 surface temperature, effects of, 257
 two-dimensional lift-curve slope, 245
Aerodynamic interaction, 639–642
Aerodynamics
 and aircraft performance, 8
 energy-maneuverability technique, 2–6
 fluid dynamics, 9–26
 Hillaker–Boyd meeting, 8
 need to study, 1–2
 specific excess power, 6–8
Aerodynamic twist, 360
Aft swept wings (ASW), 541–542, 758
Ailerons, 27
Airbus A380, 543
Air combat, Boelcke’s rules, 5
Aircraft performance, 8
Aircraft testing, approach to, 62–63
Airfoil
 aerodynamic center of thin, 235
 in aerodynamics, 235–236
 boundary-layer separation, 235
 center of leading-edge radius, 233
 characteristics, 235–236
 chord line, 233–234
 contour wave drag approaches, 526
 F-104, 560–561
 GA(W)-1, 721–722
 geometric angle of attack, 234
 geometry parameters, 231–236
 leading-edge radius, 233–234
 Mach number for, 61
 maximum lift coefficient, 234
 maximum thickness, 234–235
 mean camber line, 234
 mid-chord region, 235
 NACA geometry nomenclature, 232–233
 optimum thickness, 234
 Reynolds number for, 62
 supercritical, 526–527
 supersonic, 570, 590–591
 supersonic flow around, 454
 thickness distribution, 234–235
 trailing-edge angle, 235
 transonic flow across unswept, 517–525
 viscous boundary layer, 64
Airfoil, finite-span model
 cambered, 306–316
 circulation, 296–298
 flow around a two-dimensional, 295
 high-lift, 321–327
 laminar-flow, 317–321
 lift, 296–298
 in military aircrafts, 334–336
 multi-element sections, 327–334
 starting vortex, 296–298
 symmetric, 301–306
 thin-airfoil theory, 298–301
Airplane, description of, 26–27
Airplane efficiency factor, 283
Angles of attack
 delta wings, 409
 flow fields for aircraft at high, 422–424
 fuselage at high, 418–422
Anhedral angle, 238
Arrow wings, 595–598
Aspect ratio, 237
 of a delta wing, 242
ASSET program, 490
Asymmetric loads on fuselage, 418–422
Asymmetric vortex shedding, 419–422
Average chord, 237
Axial force, 228
Axisymmetric flow, 149–152

B

- B-52 aircraft
 - energy height, 4–5
 - total energy, calculation of, 4
- Barotropic flow, 103–104
- Base drag, 263, 636–638
- Bernoulli’s equation, 74–75, 96, 128, 151, 431
 - calculations using, 93
 - calibrated airspeed (CAS), 94
 - to determine airspeed, 93–95
 - equivalent airspeed (EAS), 95
 - Euler’s equation, 91
 - free-stream dynamic pressure, 92
 - free-stream static pressure, 92
 - indicated airspeed (IAS), 94
 - for inviscid flows, 90–95
 - stagnation (or total) pressure, 92
 - true airspeed (TAS), 95
- Biot-Savart law, 379, 382
- Boattail, 638–639
- Body-force potential, 103
- Boeing 737, 713
- Boeing 747, 543
- Boelcke, Oswald, 2, 5
- Boundary layer
 - shock wave interaction, 480–482, 491
- Boundary-layer fences, 395
 - effect of, 397
- Boundary-layer transition, 256–259
 - adverse pressure gradient, 192
 - in aerodynamics, 190
 - effects on wind-tunnel testing, 262–263
 - finite surface roughness, 192
 - idealized transition process, 191
 - for a NACA 23012 airfoil, 259
 - for NACA 0009 section, 257, 259
 - for NACA 66–009 section, 257–259
 - parameters for, 189–190
 - Reynolds number, 191
 - and stability theory, 192
 - two-dimensional T-S waves, form of, 192
- Boundary-layer transition methodology for hypersonic flows, 702–706
- Boyd, John R., 5
- Bubble separation, 248
- Busemann’s second-order equation, 587, 589
- Busemann’s theory for supersonic flows, 561
 - “biplane” airfoil system, 564–566
 - lift coefficient, 561–564
 - pitch moment coefficient, 561–564
 - wave-drag coefficient, 561–564

C

- Cambered airfoil, finite-span model, 306–316
 - aerodynamic coefficients, 308–311
 - coordinate transformation, 306
 - effect of boundary layer separation, 316
 - lift coefficients, 313
 - maximum thickness, 313
 - moment coefficient, 313

- section lift coefficient, 308
- theoretical aerodynamic coefficients, 311–312
- thickness ratio, 314
- vorticity distribution, 306–308
- zero lift angle of attack, 313, 317
- Canards, 411
- Cauchy-Riemann equations, 114
 - for cylindrical coordinates, 115
- Chance-Vought F-8H Crusader, 714
- Characteristic, defined, 455
- Circulation
 - aerodynamics perspective, 101
 - around a closed curve, 119
 - defined, 99
 - for elementary closed curves, 100
 - flow around a cylinder with, 139–144
 - for a potential vortex, 119
- Circulation control wing (CCW) concept, 725–727
- Closed fluid line, 103
- Closure problem, 198
- Coanda effect, 723
- Coefficient of viscosity, 14–15
- Collocation method, 359
- Commercial airliner, components of modern, 26
- Compressibility corrections, 512–513
- Compressible flow, 66
 - adiabatic, 441–443
 - boundary-layer interactions, 480–482
 - characteristics, 454–457
 - continuity equation, 455
 - for converging–diverging nozzle, 451–454
 - isentropic flow, 445–451, 455
 - n -momentum equation, 455
 - scaling/correction processes, 494–495
 - shock/shock interactions, 482–484
 - shock-wave boundary-layer interaction, 480–482
 - shock waves, 462–472
 - s -momentum equation, 455
 - streamtubes of variable-area, 441–451
 - tests for flow fields, 486–492
 - thermodynamic concepts, 432–441
 - viscous boundary layer, 473–479
- Computational fluid dynamics (CFD),
 - 538, 776–777
 - and aerodynamic design philosophy, 789–790
 - credibility, 783–785
 - Euler codes for, 779
 - flow fields for, 780–781
 - integration of data, 781–782
 - semiempirical methods for, 777–778
 - surface panel methods for, 778–779
 - two-layer flow models, 779–780
- Concorde, 627–629
- Configuration slenderness, 631
- Conical-flow technique, 585–598
 - arrow wings, 595–598
 - delta wings, 595–598
 - rectangular wings, 586–590
 - supersonic flow transition, 585–596
 - swept wings, 591–595

- Conservative form of governing equations, 792–797
- Constant-property flows, 46–52, 56
- Control points, 145
- Convair B-58, 533
- Converging–diverging nozzle
 - area-velocity relationship, at different Mach numbers, 452
 - compressible flow for, 451–454
 - effect of pressure ratio on, 452
 - Prandtl-Meyer, 454–461
 - supersonic conditions, 452–453
 - as a Venturri tube, 453
- Conversation of mass, 36–40
- Couette flow, 50–52
 - boundary conditions, 50
 - shear stress distribution, 51
 - between two parallel walls, 50–51
 - velocity profile for, 51
 - volumetric flow rate, 51
- Critical Mach number, 506, 513–515
- Critical pressure coefficient, 513–515
- Curvefit formula, 214
- C-17 wings, design of, 275–276
- D**
- D’Alembert’s paradox, 133
- Deflection angle, 465
- Delta wings, 404–414
 - aerodynamic coefficients, 409
 - angles of attack, 409
 - canard configurations, 411–412
 - coiled vortex sheets, effect of, 404
 - conical-flow technique, 595–598
 - drag coefficient, 408–410
 - leading-edge vortices, 413
 - lift and the drag-due-to-lift characteristics, 406
 - lift coefficients, 407–408, 410
 - lift-curve slope, 408
 - location of vortices, 413
 - moment coefficient, 411
 - normal-force slope, 406
 - positive attributes of, 414
 - potential-flow lift constant with planform
 - parameters, 406
 - separation points, 407
 - spanwise outflow, 404
 - at subsonic speeds, 404
 - with supersonic leading and trailing edges, 582
 - total lift coefficient, 406
 - vortex breakdown and, 413–414
 - vortex-lift constant with planform parameters, 407
 - vortex trajectory, 404–405
- Design of aircraft
 - camber-changing flaps, 723–724
 - circulation control wing (CCW) concept, 725–727
 - circulation effect, 723
 - drag reduction concepts, 731–741
 - dumping effect, 723
 - EA-6B, 742–745
 - F-15, 763
 - F-16, 745–752, 755
 - F-22, 764–767
 - F-35, 767–770
 - F-105D, 752–753
 - features required for operational requirements, 758
 - flap systems, 716–719
 - fresh-boundary-layer effect, 723
 - high-lift configurations, 712–725
 - Kutta condition, 720, 722
 - laminar-flow control (LFC), 734–735
 - lift coefficient, increase in, 713–716
 - multi-element airfoils, 329–331, 719–723
 - off-the-surface pressure recovery effect, 723
 - pitch moments, 723
 - power-augmented lift, 723–725
 - SCAMP/F-16XL configurations, 754
 - slat effect, 723
 - for tactical military operations, 727–731
 - trailing-edge flaps, 713
 - upper-surface-blowing (USB) concept, 723
 - variable-area concepts, 713
 - variable-twist, variable-camber wings, 731–734
 - weapon carriage concepts, 752–757
 - wing area, increase in, 712–713
 - wing/canard, wing/tail, and tailless configurations, 758–763
 - winglets, 737–740
 - wing planform, 740–741
 - wingtip devices, 737–740
- Diatomic gas, 435
- Dihedral angle, 238
- Dimensionless pressure coefficient, 128
- Direct Simulation Monte Carlo (DSMC), 655
- Displacement thickness, 203
- Doppler effect, 439
- Doublet flows, 116–117
 - axis of, 116
 - equipotential lines and streamlines for, 117
 - stream function for, 117
 - two-dimensional (line), 116
 - velocity components for, 116
 - velocity potential for an axisymmetric, 150
- Downwash velocity, 348–351
 - downwash angle, 349, 353
- Drag
 - acting on sharp cone, 678–682
 - aircraft parasite, 263–270
 - for an F-16 in steady, level, unaccelerated flight, 284–286
 - base, 263
 - due-to-lift at subsonic speeds, 401–404
 - for F/A-18E, 789
 - for finite-span wing, 279–283
 - on a flat-plate airfoil, 53–55
 - force per unit span of cylinder, 140
 - form (or pressure), 263
 - induced, 263
 - interference, 263
 - parasite, 263
 - per unit span, 133
 - pressure (or form), 133
 - profile, 263

Drag (*continued*)
 skin-friction, 133, 263
 sources of aircraft, 264
 at transonic and supersonic speeds, 527–528
 trim, 263
 wave, 263
Drag bucket, 257
Drag coefficient, 55
 for an incompressible flow, 354
 flat-plate boundary layer, 207
 induced, 353–354
 for a NACA 23012 airfoil, 259
 per unit span for a cylinder, 133
 for a smooth sphere, 152
 for a sphere, 152
 of a sphere, 668–669
 for various shapes and flows, 137
 vortex, 353–354
Drag divergence Mach number, 516–517
Drag-divergence Mach number, 537
Drag force
 induced downwash velocity, 350
‘Drooped’ leading edge, 374
Dynamic pressure, 53, 92, 461

E
Earth’s mean atmospheric temperature, 22
Eddy viscosity, 202–204
 for boundary layer, 204
 for the inner region, 203
 use of, 202
Elementary flow functions, 113–126
Elevators, 27
Elliptic circulation distribution, 351–355
Elliptic lift distribution, 355–356
Energy equations for fluid dynamics, 68–75
 application of the integral form of, 74
 Bernoulli’s equation, 74–75
 flow work, 72–73
 integral form of, 71
 internal energy (u_c), 71
 kinetic energy (ke), 71
 potential energy (pe), 71
 shaft work, 73
 viscous work, 73
Energy height, 4–6
Energy-maneuverability technique, 2–6
Entropy change for a reversible process, 436–437
Equation of state, 12
Equipotential lines for inviscid flows, 109–111
Equivalent airspeed (EAS), 95
 as a function of altitude, 95
Euler’s equation, 89, 91, 103, 442, 553
 for an irrotational flow with no body forces, 451

F
Falkner-Skan equation, 174
F-5 fighter
 applications of area rule, 535–536

 specific excess power, calculation of, 6
 total energy, calculation of, 4
Fighter pilots, 2
FIRE program, 491
Flat-plate boundary layer, integral equations for a
 application, 208–211
 drag coefficient, 207
 for incompressible flow, 205
Karman-Schoenherr relation, 209
momentum thickness for an incompressible
 flow, 207
Prandtl-Schlichting relation, 209
Reynolds number, 191
Schultz-Grunow relation, 209
streamlines, 207
Flight-test programs, 490–492, 788–789
Flow fields
 scaling/correction processes, 494–495
 tests for, 486–492
 wind-tunnel simulation of supersonic missile,
 492–494
Flow separation, 130
Fluid dynamics, 9–26
 around geometrically similar configurations, 57
 Bernoulli’s equation, 74–75
 compressible flows, 66
 constant-property flows, 46–56
 conversation of mass, 36–40
 Couette flow, 50–52
 dimensionless boundary-condition
 values, 58
 energy equations for, 68–75
 fluid, definition, 9
 fluid as continuum, 9–10
 free-stream boundary conditions, 57–58
 fully developed flow, 47
 integral equations to a flow problem, 52
 linear momentum, conservation of, 40–46
 Mach number (M) for, 59–63
 Poiseuille flow, 46–50
 principles for a nonaccelerating, hydrostatic,
 or shear-free, flow, 21
 Reynolds number (Re) for, 59–63
 thermodynamics, first law of, 66–67
 types of fluid, 9
Fluid properties
 density, 12–13
 hydrostatic stress condition, 9
 kinematic viscosity, 15–17
 pressure, 10–11
 speed of sound, 17, 23
 standard atmospheric pressure at sea level, 11, 18–20,
 22–26
 static medium, 17–22, 35
 temperature, 10
 viscosity, 14–17
Force coefficient, 135
Forced vortex (rotational vortex), 120–121
Forward swept wing (FSW), 758
Forward swept wings (FSW), 540–543
Fowler flap, 713, 721

Free-stream flow, 145
dynamic pressure, 92
Mach number, 59, 283, 512
Reynolds number, 59–60
speed of sound, 58
static pressure, 92
velocity, 57
Free vortex (irrotational vortex), 119, 121
Full potential equation, 507
Fully developed flow, 47
Fuselage, 27
asymmetric loads on, 418–422
at high angles of attack, 418–422
method for subsonic aircraft drag, 267–269
and transonic flow, 540
F-16XL aircraft, 736

G

Gage pressure, 11
Galilean transformation, 35, 465
Gates Learjet Model 28/29, 737
Geometric twist, 238–239
Göthert’s transformation, 509–512
Gradient operator, 21
Green’s lemma, 100
Ground-based test programs, 785–787
Ground-based tests, 486–489
Ground-fixed coordinate system, 35
Gulfstream Aerospace, 630

H

Heat-transfer coefficient, 217, 219
Heat-transfer rate, 220–221
in terms of Stanton number, 219
for a turbulent boundary layer, 219–220
High-lift airfoil, finite-span model, 321–327
Boeing 777, 333
boundary condition, 323
chord distribution, 329–330
development of, 326
flap system, 326
Krueger flap, 330
Kutta condition, 321
lift coefficients, 324–325
Mach numbers, 328
maximum lift efficiency, 330
in military aircrafts, 334–336
multi-element sections, 327–334
NACA GA(W)-1 series, 325, 327
point of separation, formula for, 321
pressure distributions, 323–324
science, 321
thickness distribution, 329–330
trailing edge systems, 334
two-dimensional multi-element flow issues, 329
upper-surface acceleration region, shape of, 321–322
velocity distribution, 321–322
High-speed aircraft designs, 631–634

High-speed civil transport (HSCT), 629–630
Holloman High Speed Test Track (HHSTT), 788
Horseshoe vortex, 347
Hydrostatic stress condition, 9
HYFLEX vehicle, 491
Hypersonic cruiser, 697–700
Hypersonic flows
aerodynamic heating, 691–697
basic assumption, 650
boundary-layer transition methodology for, 702–706
characteristics, 650
computational fluid dynamic (CFD) data, 700–702
entropy layers, 653
flight-test data for, 700–702
ground-test data for, 700–702
high temperature effects, 654
lift/drag, high configurations for, 682–690
low-density flows, 655
modified Newtonian flow, 665–682
Newtonian flow model for, 657–660
shock layers, 652
slender configurations, 651
small-density-ratio assumption, 650
stagnation-region flow-field properties, 660–665
trajectories for Reynolds numbers, 651
viscous-inviscid interactions, 653–654
waveriders, 682–690
Hyper-X Launch Vehicle (HXLV) stack, 489
Hyper-X program, 489

I

Immelman, Max, 2
Incompressible, two dimensional flow
in Cartesian coordinates, 107
stream function (ψ), 107–109, 149
Incompressible flow, wings of finite span
aerodynamic load distribution, 343
delta wings, 404–414
factors affecting drag due-to-lift at subsonic speeds, 401–404
flow fields at high angles of attack, 422–424
formation of a wing-tip vortex, 344
fuselage at high angles of attack, 418–422
general comments, 342–344
leading-edge extensions, 414–418
lifting-line theory for unswept wings, 346–375
panel methods, estimation using, 375–379
spanwise lift distribution, 343–344
streamwise vortices, 342
three-dimensional flow field around a wing, 343
unmanned air vehicles (UAV), 424–426
vortex lattice methods, estimation using, 379–401
vortex system, 345–346
Induced drag, 263
Integral equations to a flow problem, 52
Integral form of continuity equation, 54–55
Integral form of the energy equation, 71
Interference drag, 263

Intermittency factor, 204
Inviscid flows, 14, 89–90
 across symmetric airfoil, 303
 around cylinders, 128–130
 axisymmetric, 149–152
 Bernoulli’s equation for, 90–95
 boundary conditions, 105
 circulation, 99–101
 doublet, 116–117
 elementary flow functions, 113–126
 equipotential lines for, 109–111
 Euler equations for, 89
 Euler’s equation for a steady, 456
 incompressible, 149–152
 irrotational, 102–103, 105
 Kelvin’s theorem for, 103–104
 lift, 130–139
 momentum equation, 442
 momentum equation for, 103
 multielement airfoils, 331
 potential vortex, 117–120
 pressure coefficient for, 96–99
 source density distribution, 144–148
 source or sink, 114–115
 stream function, 107–109, 118
 superposition of, 112
 two-dimensional flows, 107–109
 uniform, 113–114
 velocity field, 126–128
 vortex theorems, 120–121
Irrotational flow, 102–103
 appropriate transformation, 509–510
 condition, 105
 line integral, 102
 with no body forces, Euler’s equation, 451
 velocity, 104
 velocity field, 102
 velocity potential, 102
 velocity potential relations, 105
Isentropic flow
 across a shock wave, 450
 choked flow, 449
 mass-flow rate, 447
 one-dimensional steady, 446, 448–449, 801–802
 relations for low Mach numbers, 446, 450
 stagnation density, 445
 stagnation pressure, 445–446
 streamtubes of variable-area, 441–451

J
Jane’s All the World’s Aircraft, 238
Jet engines, supersonic conditions for, 453
Joint Strike Fighter (JSF) Program, 767–769

K
Karman-Tsien rule, 512
Kelvin’s theorem, 103–104
 implications of, 104
Kelvin’s theorem for a frictionless flow, 296–297

Kinematic viscosity, 15, 202
 in English units, 16–17
Kinetic energy, rate of change of, 7
Kinetic theory of gases, 435
Knudsen number, 670
Krueger flap, 330
Kutta condition, 720, 722
Kutta-Joukowski theorem, 141
Kutta- Joukowski theorem for steady flow, 302, 346, 350, 352, 358

L
Laitone’s rule, 512
Laminar boundary layer, incompressible
 Blasius solution, 172, 175
 boundary conditions, 173
 boundary-layer separation, 178
 boundary layer thickness, 178
 dimensionless coordinate, 172–173
 dimensionless skin-friction coefficient, 177
 drag coefficient, 180
 Falkner-Skan equation, 173–181
 on a flat plate, 179
 momentum thickness for, 179–180
 Reynolds number, 177, 180
 shock wave, interaction with, 481
 skin-friction drag coefficient for, 180–181
 stream function, 172
 transformed shear function, 176–177
 velocity profiles, 171
Laminar-flow airfoil, finite-span model, 317–321
 Blasius laminar skin-friction relation, 317
 drag characteristics, 318
 fluid dynamic characteristics, 319–320
 for micro UAVs, 319
 NACA developed, 317–319
 P-51 aircraft, 318–319
 Prandtl turbulent skin-friction relation, 317
 for radio-controlled sailplanes, 320
 Reynolds numbers, 319
 uses, 320
 in wind tunnel, 317
 and wind-tunnel testing, 320
Laminar-flow section, 257
Laplace’s equation, 105, 112, 509
Leading-edge extensions (LEXs), 414–418
 for F-18C, 417
 for F-5E, 418
 impact on maximum angle of attack and maximum lift, 418
 Reynolds number, 415–416
Leading-edge suction force, 303, 406
 Reynolds number, 402–404
 at supersonic speeds, 401–402
Lennard-Jones model for the potential energy, 15
L’Hospital’s rule, 302
Lift, 146
 coefficient per unit span of cylinder, 141
 for F/A-18E, 789
 force per unit span of cylinder, 140

per unit span of cylinder for pressure, 131	
per unit span on NACA 23012 airfoil section, 249	
Lift coefficient	
aerodynamic forces and moments, 244–248	
NACA 2412 airfoil, 314	
NACA 23012 airfoil section, 247	
for thin-airfoil theory, 314–315	
Lift/drag ratio, 283–287, 716–719	
Lifting-line theory for unswept wings, 346–375	
aspect ratio, effect of, 354	
birds fly in formation, 399–401	
bound-vortex system at any spanwise location, 346	
comments, 373–375	
coordinate transformation, 352	
downwash angle, 353	
downwash velocity, 348–351	
drag coefficient for induced component, 353	
‘drooped’ leading edge, 374	
effective angle of attack, 349–350	
effective lift of section of interest, 350	
elliptic circulation distribution, 351–355	
horseshoe vortex, 347	
induced drag coefficient, 353–354	
Kutta-Joukowski theorem, 346	
lift coefficient for wing, 353	
lifting line, defined, 346	
lift on wing, 362	
method of Rasmussen and Smith, 373	
Prandtl lifting-line theory (PLLT), 347	
spanwise circulation distribution, 357–362	
spanwise lift distribution, 346	
starting vortex, 347	
streamwise vorticity filaments, 347	
total vortex (or induced) drag for wing, 353	
trailing-vortex system, 346–347	
trailing vortices, 348–351	
vortex drag, 350–351	
vortex drag coefficient, 353–354	
vortex-induced drag, 362–367	
Linear theory, 594, 642	
basic assumption, 553	
change in pressure, 553	
drag force, 556–557	
lift coefficient, 558–560	
lift force, 555–556	
pitch moment, 558	
pitch moment coefficient, 558–560	
pressure coefficients, 553–554	
pressure on airfoil surface, 553	
wave-drag coefficient, 558–560	
Lombardi, Vince, 26	
Long bubble separation, 248	
M	
Mach cone, 439–440, 611	
Mach forecone, 611–612	
Mach number independence principle, 651	
Mach-number/lift-coefficient flight, 526	
Mach number (<i>M</i>), 431, 492–493, 802–805	
area-velocity relationship, 452	
calculation, 60	
critical, 513–515	
drag divergence, 516–517	
dynamic pressure in terms of, 462	
for fluids, 59–63, 90	
regimes and characteristics for an airfoil, 61	
shock waves, 468–470	
for static pressure variation across the boundary layer, 65	
subsonic leading-edge normal, 582	
at supercritical, 526	
in wind-tunnel facilities, 487	
Mach wave, 463	
Maxwell’s theory, 116	
Mean aerodynamic chord (mac), 238	
Mean camber line, 234	
Military aircraft, 334–336	
Mixing length concept, 202–204	
MK-82 bombs, 754	
Modified Reynolds analogy, 219	
Momentum efflux, 54	
Momentum influx, integral, 52	
Momentum shape factor, 214	
Monatomic gas, 435	
Monoplane equation, 362	
for aerodynamic coefficients for a wing, 367–371	
Multielement airfoils, aerodynamic characteristics of,	
330–331, 719–723	
chord distribution, 329–330	
confluent boundary layer, 331	
flow models, 332	
inviscid, potential flow, 331	
maximum lift efficiency, 330	
Navier-Stokes and Euler codes, 333–334	
thickness distribution, 329–330	
two-dimensional multi-element flow issues, 329	
viscous effects, 331–332	
Multi-Role Fighter (MRF), 752	
MX-1626, 533	
N	
Nacelle, 27	
NASA flight testing centres, 488–489	
National Aerospace Plane (NASP), 702, 704	
Navier-Stoke equations, 46	
Navier-Stoke flow solver, 544–545	
Navier-Stokes equations, 198, 578, 642, 655, 781	
Newtonian flow model for hypersonic flows, 657–660	
modified, 665–682	
Newton’s Law, 6	
Non-linear flow, 525–526	
Northrop Grumman F-5E aircraft, 631	
Nusselt number	
defined, 219	
Nusselt number for turbulent flow, 220	
O	
Open test-section wind tunnel, flow in an, 97–99	
Oswald efficiency factor, <i>see</i> Airplane efficiency factor	
Over-expanded nozzle, 254	

P

Panel methods for swept wings, 375–379
 aerodynamic coefficients, 377–378
 basic concept, 375
 boundary conditions, 376–377
 computer codes used, 377
 Dirichlet boundary conditions, 376–377
 equivalency between vorticity distributions and doublet distributions, 377
 incompressible pressure coefficient, 376
 Neumann boundary conditions, 376
 set of control points, 377
 strength parameters, 375
Parabolized Navier-Stokes (PNS) equations, 781
Parasite drag, 263
Parasite drag coefficient, 713, 716
PARD Area-Rule Design, 534
Pegasus™, 781
Perfect gas, 12, 59, 432, 441, 650
Pitch moment coefficient, 621, 676
 Busemann's theory for supersonic flows, 561–564
 linear theory, 558–560
 shock-expansion technique for supersonic flows, 566–569
 symmetric airfoil, finite-span model, 304
Pohlhausen values, 218
Poiseuille flow, 46–50
 shear stress distribution, 49
Potential flow, *see* Irrotational flow
Potential flow theory, 142–144
Potential vortex, 117–121
 circulation for a, 119
 equipotential lines and streamlines for, 118
Prandtl formula, 209
Prandtl–Glauert correction, 512–513, 515
Prandtl–Glauert equation, 509
Prandtl–Glauert formula, 511–512
Prandtl lifting-line theory (PLLT), 347
Prandtl–Meyer expansion fan, 481
Prandtl–Meyer function, 456
Prandtl–Meyer relations, 552
 in aerodynamic coefficients for a thin airfoil, 459–461
 Mach number and Mach angle as a function of, 457–458
Prandtl number, 217, 219
Prandtl–Schlichting turbulent skin-friction relation, 210
Pressure coefficient, 96–99
 in an open test-section wind tunnel, 97–99
 at the stagnation point, 96
 variations, 96
Pressure distribution
 for a flat-plate delta wing planform, 613–618
 high-lift airfoil, finite-span model, 323–324
 singularity-distribution method, 608–622
 for a swept-wing/fuselage configuration, 546–547
Pressure (or form) drag, 133
PRIME program, 490
Profile drag, 263
Pylon, 27

Q

Quiet Spike, 630
Quonset hut, 137–139

R

Rate of climb (ROC), 7
Ratio of specific heats, 435
Rayleigh pitot formula, 666
Real vortex, 121–123
Reattachment shock, 481
Recovery temperature, 476
Reentry F flight, 492
Reusable launch vehicle (RLV), 488
Reynolds analogy, 476
Reynolds' analogy, 681
Reynolds averaging, 195
Reynolds number, 492–493
 unmanned air vehicles (UAV), 424
 in wind-tunnel facilities, 487
Reynolds number for fluids, 59–63, 65, 128–130, 135
 based on momentum thickness, 204
 based on the momentum thickness, 214
 boundary-layer equations, 63–65
 calculation, 60–61
 drag coefficient, 134
 of drag coefficient for a smooth sphere, 152
 flow regions, 63
 inviscid flows, 130
 regimes and characteristics for an airfoil, 62
Reynolds stress, 203, *see* Turbulent shear stress
Reynolds stress tensor, 198
Root chord, 237
Rudder, 27

S

Schlieren photography system, 474–475
Section coefficient, 135
Section lift coefficient, 359
 for a cylinder, 132
Separation bubble, 130, 248
Shaft work, 73
Shaped Sonic Boom Demonstration (SSBD) Program, 630
Sharp cone
 aerodynamic coefficients for, 672–678
 drag acting on, 678–682
Shear stress, 14
 at wall for a boundary layer, 216
Shock capturing, 792
Shock-expansion technique for supersonic flows, 566–572
 lift coefficient, 566–569
 pitch moment coefficient, 566–569
 wave-drag coefficient, 566–569
Shock/shock interactions, 482–484
 type I, 484–485
 type IV, 485–486
Shock waves, 462–472
 angle, 470
 bow, 466

- curved, 463
- difference between normal and oblique, 467–468
- downstream properties, 466
- energy, 464
- features influencing, 526
- flow across a normal, 464
- flow downstream of, 463
- flow upstream of, 463
- formation of, 462
- interactions between impinging and bow, 491
- Mach number, 468–470
- normal component of momentum, 464
- oblique, 463–465
- pressure coefficient, 469–470
- properties, 463
- relation with deflection angle, 465–466
- semivertex angle, 471
- strong, 465
- sweepback principle, 465
- tangential component of momentum, 464
- transonic aircraft, 546
- upstream Mach number, 469–470
- vs Mach wave, 463
- weak, 465, 469
- Short bubble separation, 248
- Short takeoff and landing (STOL) airplane, 724
- Similar solutions, 174
- Simpson’s rule, 399
- Singularity-distribution method, 598–625
 - camber distribution, 622–625
 - centerline or wingtip grid element weighting factor, 621–622
 - design lift-coefficient factor, 623
 - drag coefficient at cruise lift coefficient, 624
 - leading-edge field-point-element weighting factor, 621
 - lifting pressure distribution, 609–611
 - pressure distribution, 608–622
 - suction parameter, 622
 - supersonic wing for given cruise conditions, 624–625
 - trailing-edge field-point-element weighting factor, 621
- Skin-friction coefficient, 217, 219
 - experimental, 478–479
 - for a flat plate, 216
 - for a turbulent boundary layer, 479–480
- Skin-friction drag, 133
- Slender body theory for aircraft design, 634–636
- Sonic boom, reduction strategy for, 630–631
- Source density distribution, 144–148
 - application of, 146–148
- Source or sink flow, 114–115
 - flow field, 123–126
 - two-dimensional (planar), 114
- Space Shuttle Orbiter, 411, 444–445, 642–643, 682
- Space Shuttle Thermal Protection System (TPS), 491
- Spalding-Chi correlation, 479
- Spanwise circulation distribution for unswept wings, 346, 348, 357–362
 - equivalent lift-curve slope, 360
 - induced angle of attack, equation for, 360–362
 - local lift per unit span, 359
 - N* -resultant linear equations, 358
 - parameters in equation, 360
- Spanwise flow on swept wing, 395, 625
- Specific enthalpy, 434
- Specific excess power, 6–8
 - and accerelation, 6
 - application to change energy height, 7–8
- Specific heat
 - at constant pressure, 434
 - at constant volume, 433
- Specific internal energy, 432
- Speed brakes, 27
- Speed of sound, 17, 23, 438–441, 507
- Stability theory, 192, 257
- Stagnation points, 128
- Stagnation temperature, 442, 476
- Standard atmosphere
 - atmospheric layers in, 23
 - defined, 22
 - in English units, 24–26
 - U.S., 18–20, 798–800
- Standard atmospheric pressure at sea level, 11
- Stanton number, 219
 - definition, 216–217
 - for laminar flow over a flat plate, 219
- Starting vortex, 347
- Static fluid medium, 17–22, 35
- Static pressure, 128
- Steady, two-dimensional, incompressible flow, 167–170
- Stokes’s theorem, 100–102, 119
- Strake/wing configurations
 - benefits, 414
 - vortex model for, 414–415
- Stream function, 107–109, 118
 - for an incompressible, two dimensional flow, 107–109, 149
 - for doublet flows, 117
 - for elementary flows, 118
 - significance of, 108
 - for a uniform flow, 113
 - velocity components for a two-dimensional flow, 108–109
- Streamlines
 - boundary layer on a flat plate, 207
 - and equipotential lines, 109–111
 - in a two-dimensional flow, 107–108
 - for a uniform flow, 114
- Subsonic aircraft drag, approaches to determining
 - basic, 263–264
 - fuselage method, 267–269
 - sources of aircraft drag, 264
 - total, 269–270
 - wing method, 264–267
 - zero-lift drag coefficient, 264, 270
- Subsonic drag-due-to-lift parameter, 403
- Subsonic flow, 439
- Subsonic flow, compressible, 506–517
 - corrections, 512–513
 - critical Mach number, 513–515

Subsonic flow, compressible (*continued*)
 drag divergence Mach number, 516–517
 Göthert’s transformation, 509–512
 lift-curve slope with Mach number, 511
 linearized theory for, 507–509
 pressure coefficient for, 510
Superposition of inviscid flows, 112
 boundary conditions, 112
Supersonic aircraft, design considerations, 625–627
 inboard shock separation, 625, 627
 leading-edge shock, 626
 trailing-edge shock separation, 626–627
Supersonic airfoils, 552
Supersonic Cruise and Maneuver Program (SCAMP), 754
Supersonic flow
 aircraft, example, 590–591
 arrow wings, 582
 boundary conditions, 583–584
 comments, 579–580
 conical-flow technique, 585–598
 delta wings, 582
 governing equations, 583–584
 leading edge, 581
 lift/drag polar for, 579
 linear nature, impact of, 584
 perturbation potential, 583–584
 singularity-distribution method for, 598–625
 skin-friction drag, 579
 solution methods for equation, 585
 trailing edge, 581
 wing of arbitrary planform in, 581
Supersonic flow, 439, 518–519, 552
 stagnation point of a vehicle in, 464
 at zero angle of attack, 471–473
Supersonic Mach number, 588
Supersonic transport (SST), 525, 627–629
Sutherland’s equation, 14–15, 23
Sweep angle, 238
Sweepback principle, 465
Swept wings
 aft (ASW), 541–542
 area rule, 529–537
 conical-flow technique, 591–595
 forward, 540–543
 second-order area-rule considerations, 538–540
 supersonic flow over, 527–543
 at transonic speeds, 527–543
 weighting functions and, 540
 wing–body interactions, 529–537
 X-29 configuration, 542–543
Symmetric airfoil, finite-span model
 coordinate transformation, 301–303
 Kutta condition, 302
 leading-edge suction force, 303
 lift-generating circulation of an element, 304
 pitch moment coefficient, 304
 quarter chord, 304
 section lift coefficient, 303
 section moment coefficient, 304
 theoretical aerodynamic coefficients, 305–306

T
Taper ratio, 237–238
Taylor’s series expansion, 20
Thermal conductivity of air, 217–218
Thermodynamics
 adiabatic process, 436
 entropy, 436–437
 first law of, 434
 isentropic process, 437, 440
 perfect-gas law, 433, 435, 441
 reversibility, 435–437
 second law of, 435–438
 specific heats, 432–435
 speed of sound, 438–441
Thin-airfoil theory, 298–301
Time-rate-of-change of the energy height, *see* specific excess power
Tip chord, 237
Total energy, calculation of, 3–4
 of B-52 aircraft, 4
 of F-5 fighter, 4
Trailing vortex system, 401
TranAir program, 544
Transformed stream function, 218
Transition-promoting phenomena, 192
Transonic aircraft, 543–548
 boundary conditions for wing, 546
 Euler and Navier-Stokes equations for three-dimensional flows, 547, 792–797
 flow-field solutions, 547
 multi-disciplinary design optimization (MDO) methods, 544–545
 pressure distributions for a swept-wing/fuselage configuration, 546–547
 problem of grid generation, 548
 shock waves, 546
 sweep angles, 546
 transonic equations, 545
Transonic flow, 517–525
 for a B-1B, 523
 lift coefficients for Schlieren technique, 522
 for Mach numbers differences, 517–520, 524
 over a NACA 0012 airfoil, 520–522
 for Reynolds number differences, 520
 Schlieren photographs, findings from, 517–519
 section lift coefficient, 520
 shock wave at the trailing edge, 518
 shock-wave/boundarylayer interaction, 520
 unswept airfoils, past, 517–525
Transonic flows, 506
Transonic speeds
 aft swept wings (ASW), 541–542
 forward swept wings (FSW), 540–543
 fuselage changes and, 540
 second-order area-rule considerations, 538–540
 Whitcomb’s area rule, 532–533
 wing–body interactions, 529–537
Trim drag, 263
True airspeed (TAS), 95
Turbulent boundary layer, incompressible
 in aerodynamics, 193–194

algebraic turbulence models, 198
and boundary-layer separation, 193
direct numerical simulations (DNS) model, 197–199
for a flat plate, 199–202
large-eddy simulations (LES) model, 197–199
momentum equation for, 195–197
RANS-LES hybrid model, 199
Reynolds-averaged Navier-Stokes (RANS) model, 197–199
Reynolds averaging, 195
Reynolds shear stress, 199
skin-friction drag, 193
Spalart-Allmaras model, 198
time-averaged flux of momentum per unit time, 197
time-averaged value of velocity, 195
time-varying velocity, 194
turbulence kinetic energy (k), 198
turbulent inertia, 197
turbulent modeling, approaches, 197–199
turbulent shear stress, 197
turbulent skin-friction drag, 202
zero-equation models, 198
Turbulent shear stress, 170, 197
Two-dimensional flows, 107–109
Two-dimensional source flow, 114
equipotential lines and streamlines for, 115
flow rate for, 116

U

Under-expanded nozzle, 254
Uniform flows, 113–114
 Cartesian coordinate system, 113
 flow field formed from, 123–126
 stream function (ψ), 113
 streamlines, 114
 velocity potential, 126
Unmanned air vehicles (UAV), wings of, 424–426
Upper-surface-blowing (USB) concept, 723
U.S. standard atmosphere, 18–20, 798–800

V

Van Driest damping parameter, 203
Vehicle-fixed coordinate system, 36
Velocity
 boundary conditions, 105
 rate of change of, 7
 wall-friction, 200
Velocity-defect law, 200
Velocity field
 constant-density potential flow, 112
 irrotational flow, 102
Velocity potential
 for an axisymmetric doublet flows, 150
 relation with irrotational flow, 105
 for a vortex, 117
Velocity potential equation, 507
Viscous boundary layers
 boundary conditions for, 170–171
 boundary-layer transition, 189–192

eddy viscosity, 202–204
flat plates (walls), 204–215
heat-transfer rate, 219–221
incompressible flows, 171–189
laminar boundary layer, 171–189
mixing length concept, 202–204
modified Reynolds analogy, 219
Reynolds analogy, 216–217
steady, two-dimensional, incompressible flow, 167–170
thermal boundary layer, 215–221
turbulent flow, incompressible, 193–202
Viscous work, 73
Volume of space, concept of, 9
Vortex filaments, statements about, 120–121
Vortex lattice method (VLM) for incompressible flow, 378–389
 for aerodynamic coefficients for a swept wing, 389–395
 airplane drag direction, 396
 application of, 389
 boundary conditions, 386–387
 control points, 381–382
 downwash velocity, 382
 induced incidence, numerical form for, 399
 influence coefficients, 380
 magnitude of induced velocity, 382
 relations for planar wings, 387–389
 section lift coefficient for panel, 395
 spanwise lift distribution, 398
 symmetric load distribution, 398
 tangency requirement, 388
 velocity induced by a vortex filament, 382–386
 vortex circulation strengths, 381
Vortex system, incompressible flow, wings of finite span
 load distribution and, relation, 345
 Prandtl’s approach, 345–346
 trailing vortex system, impact of, 345
Vortex theorems, 120–121
Vortex theorems of Helmholtz, 348
Vorticity, 106–107
 in cylindrical coordinates in two dimensions, 120

W

Wakelike flows, axial-flow component of, 422
Wall-friction velocity, 200, 203
Wave drag, 263, 525, 577, 594
 reduction by design, 526–527
Whitcomb’s area rule, 532–533
Wind tunnel testing, 55–56
 high-speed drag variations in, 514
Wing area, 236
Wing-geometry parameters, 236–242
 anhedral angle, 238
 aspect ratio, 237
 average chord, 237
 Boeing Airborne Traversing Probe, 255–256
 dihedral angle, 238
 geometric twist, 238–239
 incidence angle, 238
 mean aerodynamic chord (mac), 238
 root chord, 237

Wing-geometry parameters (*continued*)
for the Space Shuttle Orbiter, 243–244
sweep angle, 238
taper ratio, 237–238
tip chord, 237
wing area, 236
wing span, 237
Wings of finite span
of C-17, 275–276
drag, 279–283
drag due to lift, 283
of F-16C, 277–279
lift-curve slope, 274–275
lift/drag ratio, 283–284
wave drag, 283
zero-lift drag, 282–283
Wing span, 237

X
X-51A Waverider, 690–691
X-31 highly maneuverable aircraft, 412
X-15 program, 655–656

Y
YC-14 AMST (Advanced Medium STOL Transport),
723

Z
Zero-lift angle of attack, 326, 704
Zero-lift drag coefficient, 516
Zero-pressure-gradient (flat-plate) boundary layers,
199