

INDEX

- AC (alternating current) circuit fundamentals, 88–91
- access (construction), 239
- active stall, 79, 80
- actuator disc, 34–37
- aerodynamic damping, 155–57
- aerodynamic damping coefficient, 377
- aerodynamic loading
 - deterministic, 147–50
 - reference frames, 144–46
 - steady, 146
 - stochastic, 150–51
- aerodynamic theory
 - actuator disc, 34–37
 - BEM, 41–44
 - blade element, 38–41
 - drag, 46–47
 - dynamic inflow, 60–63
 - momentum theory correction, 47–48
 - multiple streamtube, 37–38
 - radial flow and stall delay, 48
 - rotor wake, 50–55
 - stall effects, 59–60
 - tangential induction factor, 47
 - tip loss correction, 48–50
- aerodynamics, large offshore arrays
 - blockage, 338–39
 - wake steering, 339–41
- aeroelastic codes, 169
- aerofoil, 11
- ailerons, 82
- anchors, 365
 - drag-embedment, 385
 - suction bucket, 384
- anisotropy, 177
- annual energy output, 84
- annual wind speed, 22, 23
- Archimedes’ Law, 352
- array interactions
 - array losses, 222–26
 - wake turbulence, 226–30
- aviation
 - collision risk, 263–64
 - radar interference, 265–68
- banking crisis of 2007–2008, 299
- bat deterrent system, 251
- batteries, 403
- Beatrice Demonstrator, 306, 307
- BEM theory
 - as combined theory, 41–44
 - modifications to, 46–50
- bending analysis (blade), 192–94
- Betz limit, 36
- binning, 11
- bird impacts, 248–51, 343–45
- blade balancing, 203–5
- blade edgewise vibration, 158–62
- blade element theory, 38–41
- blade manufacture
 - balancing in, 203–5
 - GFRP (glass fibre reinforced plastic), 199–201
 - wood-epoxy, 201–3
- blade number, 73
- blade structure
 - bending analysis, 192–94
 - cantilever beam model, 182–86
 - composite elements, 188–92
 - compressive buckling in, 186–88
 - shear, 188
- blade testing, 205–8
- blade twist, 71–73
- Block Island windfarm, 308
- blockage, 338–39
- Blyth, James, 5–6
- boundary layer, 15
- brakes, mechanical, 133
- Campbell diagram, 158
- cantilever beam model, 182–86
- capacity factor, 11
- carbon fibre reinforced plastic (CFRP), 177
- Carter, President Jimmy, 1
- catenary, 382
- centrifugal loading, 154
- collision risk, 263–64
- composites
 - anistropy, 177
 - elements of, 188–92
 - fibre-reinforced, 177–82
- compressive buckling, 186–88
- constant speed, variable pitch (CSVP), 122–25
- construction (wind turbine)
 - access, 239
 - crane operations, 239–43
 - crane road weight, 243–45
 - foundations, 230–37
 - transport, 236–39

430

control
 sector management, 134–35
 starting and stopping, 130–34
 yaw, 119–20
control, power limiting
 constant speed, variable pitch (CSVP), 122–25
 stall regulation, 122
 variable speed, variable pitch (VSVP), 125–29
control-induced instability, floating platforms, 376–78
Coriolis effect, 14
cost (wind energy)
 calculations, 274–75
 installation, 275–77
 intermittent generation affecting, 278
 operational, 277
 total, 278–79
crane operations (construction), 239–43
crane road weight, 243–45
current loading, 332
currents, 320–22

dampers, mechanical, 160
damping, 155–57
day rates (offshore), 336
deterministic loading, 144, 147–50, 167–68
disposal of blades, 405
distributed ownership, 288–90
diurnal wind variation, 22–24
Donghai Bridge array, 308
double/multiple stall, 59–60
doubly fed induction generator (DFIG), 11, 95–96
downwind rotor design (HAWT), 83–84
drag, 46–47
drivetrain architecture, 325–29
 fully integrated, 327
 hybrid, 327
dynamic inflow, 60–63
dynamic loading, 139
dynamic response measurement
 load spectra, 166–67
 mean loads, 164–66
 for stochastic and deterministic loading, 167–68
dynamic response, offshore wind turbine, 334–35
dynamic stall, 59–60

ecological impacts, 248–51
economics (wind turbine)
 cost, 274–79
 price, 279–81
 supply and demand, 282–88
electrical generator types
 doubly fed induction generator, 95–96
 gearless, 96–97
 history of, 97–101
 induction generator, 93–95
 permanent magnet generator (PMG), 92–93
 synchronous generator, 93
 variable-speed generator, 95–96

Index

electrical principles
 fundamentals, 88–91
 metering, 91
electricity generation history (wind turbine), 5–6
electromechanical loading, 154
energy crisis (1970s), 1
energy storage, 393
 pumped hydro storage (PHS), 402
 storage profiles, 394
 Texas (case study), 395–97
 UK National Grid (case study), 394–95
environment
 ecological, 248–51
 noise, 256–63
 pollution risk, 255–56
environmental impacts (offshore)
 birds, 343–45
 marine mammals, 346–48
European windmills
 early sail, 4
 windfarm revolution in, 7–9

fatigue prediction, 170–73
fault level (electrical), 103
fault protection, 109
fibre-reinforced composites, 177–82
fixed base foundations (offshore), 351
 gravity, 352–53
 jackets, 361–66
 monopiles, 353–61
 other types, 366–68
fixed pitch (HAWT), 75
flicker
 defined, 105–7
 shadow, 255
floating foundations
 control-induced instability, floating platforms, 376–78
 mooring and connection, 382–86
 semi-submersible and barge platforms, 378–81
 spar buoy, 371–76
 stability analysis, free-floating platforms, 368–71
 tension-leg platform (TLP), 381
floating wind turbine, 307
foundation overturning loads (offshore), 324
foundations (construction), 230–37

gearless generators, 96–97
Gedser wind turbine, 6
generators, 91–101
geostrophic wind, 13–15
GFRP (glass fibre reinforced plastic) blade manufacture, 199–201
Gigha Community windfarm, 290–94
global offshore resource, 310–12
gradient wind speed, 13–15
gravitational loading, 151
gravity-based foundations, 352–53
gravity caisson, 307

- grid capacity, 110–13
- grout, 355
- grouted joint, 357
- gust factor, 24–26
- gust measurement, 24–26
- gyroscopic loading, 152–53
- habitat disruption, 343
- harmonics, 109–10
- Heronemus, William, 303
- horizontal-axis wind turbines (HAWT)
 - blade element theory, 38–41
 - cantilever beam model for, 182–86
 - composite blade structure, 188–92
 - Costa Head wind turbine, 7
 - defined, 11
 - drag and, 46–47
 - Gedser wind turbine, 6
 - lightning protection for, 113
 - near-wake measurements of, 53–55
 - tangential induction factor 47
 - tip loss correction, 48–50
 - vibration and resonance 154–55
 - wood-epoxy blade manufacture, 201–3
 - yaw operation in, 58–59
- horizontal-axis wind turbines rotor
 - aerodynamic control
 - aileron, 82
 - fixed pitch, 75
 - pitch control, 75–80
 - spoilers, 81
 - tip brakes, 81, 82
- horizontal-axis wind turbines rotor design
 - blade twist and pitch, 71–73
 - downwind, 83–84
 - number of blades in, 73
 - power efficiency, 67–68
 - power, thrust, and torque, 65–66
 - tip speed ratio and solidity, 69
- horizontal mooring stiffness, 383
- Horns Rev I, 305
- Hütter, Ulrich, 177
- Hywind Demonstration project, 307, 372
- IEC Wind Class, 215–16
- induction generator, 93–95
- installation cost, 275–77
- instantaneous voltage, 88
- inter-annual wind speed, 21
- intermittency, 390–93
- intermittent generation, 278
- jacket foundations, 361–66
- jackup crane barge, 336
- Jonswap spectrum, 317, 349
- Juul, Johannes, 6
- Keulegan Carpenter number, 329
- Kincardine Offshore array, 379
- la Cour, Poul, 6
- Lely, 304, 353
- levelised cost of energy (LCoE), 274, 400–3
- lidar, 120
- lift, aerodynamic, 40, 41
- lightning protection, 113–15
- load spectra, 166–67
- loading (structural)
 - aerodynamic, 144–51
 - deterministic, 144, 167–68
 - dynamic, 139
 - dynamic response measurement, 162–68
 - dynamic response of simple system, 139–41
 - electromechanical, 154
 - gravitational, 151
 - gyroscopic and centrifugal, 152–54
 - modal analysis, 141–44
 - predicting, 169–73
 - static, 139
 - stochastic, 144, 167–68
 - vibration and resonance, 154–55
- loading prediction
 - aeroelastic codes for, 169
 - fatigue, 170–73
 - pitch control, fatigue impact of, 173–74
- mammal impacts, 251
- marine mammal impacts, 346–48
- marinisation, 322–23
- material safety factor, 193, 194
- MCP analysis, 217–21
- mean load measurement, 164–66
- metacentric height, 370
- metering, 91
- metocean data, 316
 - currents, 320–22
 - wave characteristics, 317–20
 - wind speeds, 316–17
- microwave interference, 268–70
- modal analysis, 141–44
- momentum theory correction, 47–48
- monopile foundations, 304, 353–61
 - structural failure of, 361
- monopod bucket, 368
- Morison’s equation, 329, 332
- multiple streamtube theory, 37–38
- nacelle, 11
- network characteristics (electrical), 101–3
- noise
 - origins of, 256–57
 - planning limits to, 261–63
 - predicting, 258–61

offshore WECs, forces on
 current loading, 332
 dynamic response, 334–35
 wave loading, 329–32
 wind, wave and current loading, 332–34
offshore wind characteristics
 detailed, 312–16
 global resource, 310–12
 metocean data, 316–22
offshore wind foundations
 fixed base foundations, 351–68
 floating foundations, 368–86
offshore wind power
 aerodynamics, large arrays, 338–41
 wind characteristics, 310–22
 first installation, 304
 history of, 303–10
 installation, 335–38
offshore wind turbine blades, 323
 cyclic loading, 323
 pre-bend, 323
oil prices, 1, 2
operational costs, 277
overbooking, 392
ownership
 distributed, 288–90
 Gigha Community windfarm, 290–94

panemones, 3
particle image velocimetry (PIV), 53
performance of offshore arrays, 341–43
permanent magnet generator (PMG), 11, 92–93, 326–27
persistence, 314
pin piles, 364
pitch (HAWT), 71–73
pitch angle, 72
pitch control (HAWT), 75–80
pitch/roll frequency, spar buoy, 374–76
planning
 aviation, 263–68
 microwave interference, 268–70
 public safety, 251–52
 shadow flicker, 255
 television, 270–71
 visual impact, 252–55
platform pitching motion, 374
policy (wind energy)
 ownership, 288–94
 renewables (UK), 294–98
pollution risk, 255–56
porpoises, 346
post mills, 4
power
 HAWT rotor, 65–68
 limiting, 121–29
power coefficient, 11
power density, 391
power factor, 11

power quality
 fault protection, 109
 flicker, 105–7
 grid capacity, 110–13
 harmonics, 109–10
 lightning protection, 113–15
 network characteristics, 101–3
 statcoms and SVCs, 107–9
 steady-state voltage, 103–4
Prandtl, Ludwig, 52
pricing (wind energy), 279–81
public safety, 251–52
p-y method, 360

radar interference, 265–68
radial flow, 48
Rainflow algorithm, 170, 171
rated power, 12
Rayleigh distribution, 26, 82–83
recyclable blades, 403–5
reference frames, 144–46
renewables policy (UK), 294–98
resonance
 loading, 154–55
 tower, 157–58
Riisager turbine, 8
rock anchors, 234
root attachment method, 194–98
rotational sampling, 150
rotor aerodynamic control
 fixed pitch, 75
 pitch control, 75–80
 spoilers, 81
 tip brakes, 82
rotor blade technology
 anisotropy, 177
 blade manufacture, 198–205
 blade structure, 182–94
 fibre-reinforced composites, 177–82
 root attachment method, 194–98
 testing, 205–8
 weight, 208–11
rotor design
 blade twist and pitch, 71–73
 downwind rotor, 83–84
 number of blades, 73
 power curve and energy capture, 84–85
 power efficiency, 67–68
 power, thrust, and torque, 65–66
 tip speed ratio and solidity, 69
rotor wake
 schematics of, 50–51
 vortex wake analysis, 52–53
roughness length, 15

sails (wind power), 3–4
scaling (of wind turbines), 9–10
Scheer, Hermann, 390

- Scoraig community, 393
- scour, 361
- seals, 346
- sector management, 134–35
- semi-submersible, 368, 376
- shadow flicker, 255
- shear keys, 357
- significant wave height, 317
- siting (wind turbine)
 - array interactions, 222–30, 336
 - wind assessment, 214–21
- slenderness ratio, 355
- Smeaton, John, 4, 5
- smock mills, 4
- solar energy, 13
- solidity
 - defined, 12
 - HAWT rotor, 69
- space scales (wind variation), 21–23
- spar buoy, 307, 368, 371–76
- splash zone, 322
- spoilers, 81
- square-cube law, 9
- stall delay, 48
- stall effects, 59–60
- stall regulation
 - HAWT rotor, 75
 - for power control, 122
- starting sequence, 130–34
- statcoms, 107–9
- static loading, 139
- static VAR compensator (SVC), 107–9
- steady loading, 146
- steady-state platform pitch, 373
- steady-state voltage, 103–4
- stochastic loading, 144, 150–51, 167–68
- stopping sequence, 130–34
- subsea jacket, 306, 359
- subsea soil, 359
- suction caissons, 365
- suction piles, 365
- supply and demand
 - background of, 282–83
 - for on-site generation, 283–85
 - wide scale generation, 286–88
- sustainability, 403
 - decommissioning and disposal, 405–7
 - manufacture, 404–5
- synchronous generator, 93
- tangential induction factor, 47
- television interference, 270–71
- tension-leg platform (TLP), 368, 381
- Texas, energy storage, 395–97
- Thornton Bank I array, 352
- thrust (HAWT), 65–66
- tides, 316
- time scales (wind variation), 21–23
- tip brakes (HAWT), 81, 82
- tip loss correction, 48–50
- tip speed ratio
 - defined, 12
 - HAWT rotor, 69
- topography
 - effects on wind, 28–31
 - wind shear estimation and, 15
- torque (HAWT), 65–66
- tower height, 324–25
- tower resonance, 157–58
- tower shadow, 147
- transition piece, 355, 357
- transport (wind turbine), 236–39
- tripod foundation, 367
- turbulence, 18
 - defined, 18–20
 - site assessment of, 221
 - wake, 226–30
- turbulence intensity, 19–20
- UK National Grid, energy storage, 394–95
- vacuum resin infusion moulding (VRIM)
 - blade manufacturing, 198
 - defined, 12
- variable speed, variable pitch (VSVP), 125–29
- variable-speed generator, 95–96
- vertical-axis wind turbines (VAWT), 12
- vibration
 - blade edgewise, 158–62
 - loading, 154–55
- Vindeby, 304, 322, 352
- visual impact, 252–55
- voltage (steady-state), 103–4
- voltage control, 104
- vortex wake
 - analysis, 52–53
 - near-wake measurements of, 53–55
- wake steering, 339–41
- wake turbulence, 226–30
- wake velocity deficit, 53–55, 338
- wave characteristics, 317–20
 - extreme wave height, 317
 - fetch, 317
 - maximum wave height, 317
 - significant wave height, 317
 - wave velocity profile, 319
- wave loading, 329–32
 - extreme, 330
- Weibull wind distribution, 26–27
- weight (rotor blade), 208–11
- wet mate connectors (WMCs), 386
- whale, 347
- winch erection, 242–43
- wind and solar, combining renewables, 397–403

434

- wind assessment
 - MCP analysis, 217–21
 - site measurement, 216–17
 - turbulence and shear, 221
 - wind resource, 214–15
- wind characteristics
 - geostrophic wind, 13–15
 - gradient wind speed, 14–15
 - gust measurement, 24–26
 - offshore, 310–22
 - time and space scales, 21–23
 - topographic factors, 28–31
 - turbulence, 18–20
 - Weibull wind distribution, 26–27
 - wind shear, 15–17
- wind energy converter (WEC), 12, 329–32
- wind shear, 12, 15
 - defined, 15–17
 - diurnal, 23–24

Index

- profiles, 16
 - for site assessment, 221
 - wind speeds (offshore) , 316–17
 - wind turbine generator (WTG), 12
 - wind turbine history
 - archaeology, 3–5
 - scaling, 9–10
 - start of electric generation, 5–6
 - windfarms, 7–9
 - windfarms
 - Gigha Community, 290–94
 - revolution, 7–9
 - Windfloat 1, 379
 - wooden tower, 405
 - wood-epoxy blade manufacture, 201–3
- yaw
- control, 119–20
 - operation in, 58–59