

NAME INDEX

Acopian, S., 492n	Danyuk, D., 320n	Kazemi, V., xxi
Alpert, D., 568	Einstein, A., 539n, 580n, 585, 622n, 634	Keeth, G., xix
Andrew, E.R., 304	Ely, D., xix	Kelvin, Lord, 51n
Aoyagi, T., 637	Esaki, L., 92n	Kirchhoff, G., 432
Archinard, M., 603n		Kirchhoff, G., 51n
		Kjær, V., 574
Baker, W.O., 631	Faraday, M., 583	Ladd, W., 639n
Baxandall, P.J., 579n	Feynman, R., 17	Lanczos, C., 441n
Bayard, R.T., 568	Fletcher, H., 571	Larkin, J., xxi
Bayer, B., 632	French, W.G., 617n	Larkin, John, 27
Beranek, L., 580		Liles, W., 588n
Beucler, B., 418n	Garwin, R.L., 15n, 441n, 602n	Lin, C., 617n
Bevis, S., 486	Gauss, C.F., 441n	Lisell, E., 565n
Billam, J., xxi	Geiger, H., 620n	Lorenz, L., 51n
Billings, K., xxi, 61	Gertner, J., 631	Lu, P., xxi
Blackman, R.B., 443	Gilbert, Barrie, 304	Lundberg, K., xxi
Bode, H.W., 70g, 293r	Goldie, E.A.G., 636	
Bourdon, E., 566n	Graham, M., 10n	MacArthur, J.P., xix, xxi, 161, 552, 598n, 610n
Bourns, M., 493p	Griesinger, D., 566n, 579n	Maxwell, J.C., 51n, 52
Bourns, R., 493p	Grover, F.W., 10n	McFee, M., xxi
Boyle, W.S., 631		McLeod, H., 567
Brüel, P.V., 574	Hackman, G., 588n	Mehmed, A., xxi
Bragg, W.H., 541n, 565	Hall, E., 547n	Michelson, A.F., 539, 539n
Bragg, W.L., 541n, 565	Hamming, R.W., 443n	Miller, J.M., 323, 415
Bridgman, P.W., 551n, 565n	Harris, F.J., 443, 443n	Miller, J.W., 493p
Brown, R., 580n	Hayes, T.C., xxi	Millikan, G.A., 636
Burns, M., xxi	Heinzel, G., 443	Milliken, H., 11n, 12
Butler, J.R., 365	Hergert, E., xix, 619n	Mindell, D., xix
	Hertz, H., 622n	Mouser, J.D., 159
Caldwell, J., 418	Higgins, R.J., 441n	Mulder, F., xxn
Cerwin, S., xxi	Hobbs, P.C.D., xxi, 535n, 606, 619n	Munson, W.A., 571
Chase, A., xxi	Hooke, R., 551	
Christie, S.H., 552n	Horowitz, P., xxi	Nagaoka, 51g
Chua, L., 151n	Howland, B., 418	Neumann, G., 575g
Cohen, L.G., 617n		Newton, I., 561
Cooley, J.W., 441n	Iams, H., 622n	Norton, E.L., 3r
Courtney-Pratt, J.S., 634, 635		
Cowles, J., 304	Johnson, J.B., 316	Orfield, S., 580
Čuk, S., 446r	Johnson, H., 10n	Ott, H., 10n
Danielson, G.C., 441n		

Pascal, B., 561
Pease, Bob., 143
Philbrick, G., **294**ff
Pilotte, M., 305
Pirani, M., 567
Poisson, S.D., 551n
Purcell, E.M., 53n

Rayleigh, Lord., 51n
Rogalski, A., 611n
Rubin, V., 632
Rutherford, E., 620n

Salzberg, B., 622n
Scully, D., xxn
Sellers, L., 69n
Sennheiser, F., 575g
Shure, S.N., 571, 575g
Simmons, G., 575n
Smith, G.E., 631
Smith, W., 606n
Stern, A., xix, 440n
Streckeisen, G., 585n
Stubbs, C., 632

Tellerman, J., 546n
Terman, F.E., 10n, 64n
Thévenin, L.C., 3r
Thompson, J., xxi
Torricelli, E., 566
Tranah, D., xix, xxi
Trefethen, L.N., 17
Tukey, J., 441n

von Hann, J., 443

Wheatstone, C., 551, 552n
Wheeler, H.A., 51, 64n
Widlar, Bob, 421
Widlar, R., 140n, 294
Wielandt, E., 585n
Wien, M., 51n
Williams, J., 402n
Williams, T., 203n
Williamson, R., 573n
Willison, J., 570n
Woodward, S., xxi

Zener, C., 84

PARTS INDEX

KEY		
suffixes	ff	“and pages following”
	n	footnote
	g	graph
	r	review section
	p	photograph
	s	screen shot (‘scope or spectrum analyzer)
	t	table
	T	tabular
boldface		main entry, folios following
(box)		in a box

0531 (Agilent), 567, 567p	1N4148, 78, 80g, 81, 81, 82g, 83, 84g, 92, 92s, 167, 509	241-8-xx (Signal Transformer), 514, 515p, 517s
1.5KE, 527, 531, 533, 533, 534g	1N4154, 165n	241-x-24 (Signal Transformer), 465t
1.5KE10A, 529	1N4448, 84g	2486-L3 (JDSU), 522, 522p
1.5KE200CA, 529	1N4734, 250	2801-1, 485
1.5KE220CA, 467	1N4742, 499	2N2222, 193n
1.5KEvvv, 77	1N4937, 89g	2N2866, 165
1.5KExxA, 449	1N5221-81, 76	2N2907, 295
1211 (Ithaco), 316n	1N5240, 76	2N3391, 146g
12AX7, 294, 294	1N5242, 497, 497s, 498, 498s	2N3553, 148g
1433507C (TDK), 491s	1N5245, 449	2N3904, 80, 81g, 85, 86g, 105, 105g, 125, 126, 126, 127, 127, 128g, 132g, 142T, 143, 146g, 147, 148g, 149T, 207, 222t, 250, 514, 515p, 517s
1455J1201, 328p	1N5271, 76	2N3906, 86g, 105, 105g, 127, 128g, 142T, 146g, 148g, 149T
1455N1201 (Hammond), 161	1N5400, 88s, 449	2N4117, 80, 81g, 180t
15FR020 (Ohmite), 275	1N5554, 85g	2N4117-19, 180, 182
15KP30A, 531, 531	1N5711, 80–82g, 84g, 88	2N4124, 148g
1776 (Caddock), 30	1N5817, 374	2N4126, 148g, 514, 515p, 517s
1776-C68 (Caddock), 29	1N5819, 80–82g, 89g, 94, 250, 255, 313, 313g, 484	2N4391, 180
1786B (BK Precision), 517s	1N5820, 82g, 449, 511, 512s	2N4401, 105g, 133t, 134, 135s, 136, 142g, 142T, 146g, 147, 148g, 149T, 193n
1HNK60, 485	1N758, 85g	2N4401-03, 192
1I305A, 95, 95, 95s	1N914, 80–82g, 84g, 512s	
1N3595, 80, 81g, 83, 83g, 400, 400	1N916, 84g	
1N4001, 86, 87, 87, 88s, 89g, 464, 465s, 467	1NB4-5035, 391	
1N4002, 80, 81g	202PS1J (Littelfuse), 399	
1N4004, 85g, 497, 497s, 498, 498s, 499, 510, 511, 512s	2211 (Coto), 72p	
1N4007, 467, 481, 481s	2270 (B&K), 574	
	241-4-10 (Signal Transformer), 465s	
	241-5-xx (Signal Transformer), 514, 515p, 517s	

644	PARTS INDEX	<i>Art of Electronics – The x-Chapters</i>
2N4403, 132g, 133t, 134, 135s, 136, 142T, 148g, 149T, 184, 185	2SA1162GR, 142T	30014x (Vishay), 30
2N4416, 177, 179	2SA1175, 142T	30019x (Vishay), 30
2N4868A, 179g	2SA1312, 142T	3140-0665 (Pittman), 459, 459s
2N5086, 148g	2SA1514K, 142T	34401 (HP), 389
2N5087, 101, 102, 120, 121, 123, 136, 142T, 148g, 149T, 184n, 186	2SA1837, 166t, 167, 271T	3C90, 60
2N5088, 106, 107, 113, 113, 114, 115, 118, 119, 121–123, 136, 142T, 146g, 148g, 149T	2SA1859, 166t, 167, 167, 168g	3C94, 60
2N5089, 113, 115, 142T, 148g, 152, 334	2SA1962, 271T	3C94 (Ferrocube), 60g
2N5210, 142T	2SB1184, 149T	3F3, 60
2N5401, 142T, 146g, 148g, 149T	2SB1197KR, 142T	3FS-216 (Tamura), 467
2N5457, 105g, 174, 176g, 177, 177g, 178, 179, 180g, 182, 184g, 184t, 188g, 190g, 190t, 191g, 329, 329, 330g	2SB1241, 142T	3FS-356 (Tamura), 510
2N5457-58, 183g	2SB1243, 148g	4000B-series, 232
2N5457-59, 175T, 177g, 178, 188n, 189g	2SB1243Q, 142T	4069UB, 232, 233g
2N5458, 174, 177, 180g	2SB1424, 142T	4145 (B&K), 574
2N5459, 174, 177, 180g	2SB1690K, 142T	4179 (B&K), 579, 580
2N5460, 105g, 174, 179, 329, 329, 330g	2SB737, 142T	4939 (B&K), 575g
2N5460-62, 175T	2SB74BL, 105g	5080.1 (Wavetek), 305
2N5461, 179, 180g, 191g	2SC2412, 142T, 150g	5082-0112, 89, 90, 90, 91s
2N5484, 180g, 250, 514, 515p, 517s	2SC2413, 150g	5082-0180, 89, 90s
2N5484-6, 175T, 183g	2SC2712, 142T	529801b02500 (Aavid), 467
2N5484-86, 176g, 178g	2SC2714, 149	530001b02100 (Aavid), 467
2N5486, 184g, 250	2SC3324, 142T	53100 (Murata), 425
2N5550, 142T, 146g, 149T	2SC3601, 142T	5501-12-1 (Coto), 74p
2N5583, 165	2SC3837, 150g	5KP26, 281
2N5961, 142T, 148g	2SC3906, 142T	5KP30A, 531, 531
2N5962, 127g, 142T, 148g	2SC3955, 142T	6260D (Makita), 458p, 458s
2N5963, 127, 128g, 142g, 148g	2SC4082, 146g, 148g, 149T	640440 (Tyco), 22
2N5963LS301, 142T	2SC4083, 150g	640AA (Western Electric), 580g
2N6667, 511, 511g, 512s	2SC4793, 166t, 167, 271g, 271T, 272g	6514 (Keithley), 105
2N6668, 511g	2SC4883, 166t, 167, 167, 168g	6N137, 29
2N7000, 78, 193n, 197, 198g, 262	2SC5110, 148g	7000 (Coto), 79
2N7000-02, 193n	2SC5242, 271g, 271T, 272, 273g	7101 (Coto), 72p
2N7002, 198, 416	2SC6102, 142T	7123-RC, 493p
2N760, 295	2SD1760, 149T	725B (Shibusoku), 42
2N930, 295	2SD1863, 142T	731A, 587, 588
2SA1016, 142T	2SD2653, 142T	740B02, 558
	2SD786, 142T	740M04, 558
	2SJ162, 168, 168t, 271T	74429 (Wurth), 489
	2SJ74, 174, 189, 189g, 190t	7474A (HP), 459n
	2SK1058, 168, 168t, 271, 271g, 271T, 272g	74AUP1GU04, 232, 233g
	2SK117, 183g	74HC04, 233
	2SK1317, 200T	74HC1G14, 259
	2SK1412, 200T, 201g, 412, 413t	74HC221, 284
	2SK147, 180g, 183g	74HC2G02, 259
	2SK170, 174, 175T, 177, 180g, 183, 184g, 184t, 189g, 189n, 190g, 190t, 191g	74HC2G86, 259
		74HC4052, 396n
		74HCU04, 232, 233g
		74LVC1G04, 262, 491, 491s
		74LVC1G3157, 430
		74LVC1GU04, 232, 233g
		74LVC2G86, 262

74LVC3157, 314, 314	AD8011, 353, 358T	ADA4637, 312, 313, 313g, 314, 316, 318g, 348T
74LVC86, 158	AD8017, 358T	ADA4700, 508n
786A, 588	AD8021, 349T	ADA4817, 348T
78L05, 29	AD8022, 349T	ADA4841-1, 350T
78L12, 313, 313g, 514, 515p, 517s	AD8023, 358T	ADA4851-1, 350T
79L12, 313, 313g, 514, 515p, 517s	AD8027, 350T	ADA4853-1, 350T
7xxx (C&K), 71, 75p	AD8029, 350T	ADA4855, 350T
81 (Lionel), 460p	AD8031, 350T	ADA4857, 351T
817D, 484	AD8033, 348T	ADA4860-1, 358T
835C (Gordos), 72p	AD8037, 350T	ADA4891, 348T
8761B (HP), 73p	AD8038, 342, 342g, 350T	ADA4891-3, 348T
9007 (Coto), 79, 159	AD8045, 350T	ADA4895, 351T
90J, 25g	AD8051, 350T	ADA4897, 350T
93J, 25g	AD8055, 350T	ADA4898, 349T
95J, 25g	AD8057, 350T	ADA4899, 350T
	AD8061, 350T	ADA8616, 373g
	AD8065, 348T	ADG794, 545
	AD8067, 348T	ADL5530, 63, 64
3157, 314	AD8079, 337, 338T	ADM1075, 481T
A1265 (Apple), 482p, 482s, 483p	AD8091, 350T	ADN8834, 595
A8000sc (FLIR Systems), 592p	AD8099, 351T	ADP3623-25, 256T
AB4X2X8 (Toshiba), 489, 490s	AD812, 358T	ADR400-series, 447r
AC05 (Vishay), 27n, 29g	AD817, 342n, 349T	ADR441, 508, 508n, 509
ACPL-332, 475	AD818, 349T	ADS8698, 509
ACPL-772L, 487	AD820, 373g	ADuM6132, 258, 262, 263, 263T
ACPL-P346, 270	AD825, 348T	ADXL1001, 588
ACPL61, 262	AD826, 349T	AFB1212 (Delta), 457, 459s
AD5222, 34g	AD829, 349T	AFBR-POC404L (Broadcom), 521
AD5290, 32	AD8302, 304	AFBR-POC406L (Broadcom), 521, 522g
AD5291-92, 35	AD844, 340, 358T	AFBR-S4N22P, 623
AD5292, 34g	AD846, 354, 354g, 357n	AFBR-S4P11P012R, 622
AD5293, 32, 35	AD8495, 595	AFG31000, 155
AD548, 421, 422, 422, 423	AD8510, 322	AG20 (Aromat), 72p
AD5686, 509	AD8572, 373g	ALD210800, 204g, 204 , 205g
AD598, 543, 543	AD8603, 478, 479	ALD210804, 204g
AD698, 543, 544	AD8605, 229, 230g, 348T	ALD210808, 204g
AD706, 390	AD8616, 330, 331, 331g, 332t, 348T, 373, 374s	ALD210814, 204g
AD7190, 585	AD8628, 371	ALD214804, 204g
AD7192, 545	AD8675, 514, 515p, 516, 517s	ALD214808, 204g
AD7294, 481T	AD9631, 350T	ALD214813, 204g
AD734, 279n, 397	AD9632, 350T	Amobead, 61, 61s
AD7376, 32	ADA2200, 545	AMP03, 397
AD797B, 349T	ADA4075, 349T, 365	AP2156, 476T
AD8000, 358T	ADA4075-2, 365	Approach Z82 (Garmin), 549n
AD8001, 355t, 358T	ADA4310, 358T	AQY221N, 321
AD8004, 358T	ADA4522, 344	AQY221N5, 322
AD8007, 358T	ADA4530-1, 325n, 326, 330t	Aranet4, 640p
AD8009, 355g, 355s, 358T	ADA4627, 348T	
AD8010, 358T		

646	PARTS INDEX	<i>Art of Electronics – The x-Chapters</i>
ArrayJ-16P-PCB, 630	BFT25A, 142T, 146g, 147, 148g, 149, 149T	CCR (TE), 29g
ATF-50189, 246	BFT46, 175T, 183g	CCR (Tyco), 27
ATF-55143, 247	BFT93, 146g, 148g, 149T	CD143, 85, 86g
B2902, 271	BGA2874, 385	CD143A, 527
B82720S2601N040, 493p	BLM (Murata), 61	CD4052, 396n
B82727E6403A040, 493p	BMP384, 563	CDZV10B, 85g
BAS21, 84g	BOP36-1.5M (Kepco), 16	CE3514, 247
BAT15, 84g, 332, 333	BQ24070, 450, 450, 451	CG75, 529
BAT165, 264	BQ29410, 452, 452	Christmas Oratorio, 296n
BAT17, 84g	BQ77905, 452	Citiroc1A (Weeroc), 382
BAT54, 413, 503, 504p	Brown Devil, 23	CM300DY, 436
BAT68, 159	BS250, 78	CM300DY-24H, 281
BC846, 148	BSS123, 198n	CMA (Vishay), 28, 29g, 32s
BC847, 128n, 147g, 148, 148g, 149T	BSS126, 207, 207n, 208, 211, 215g, 218, 218, 219, 416	CMEJ-0415-42-P, 580n
BC848, 148	BSS84, 198, 198n, 477	CMS3-14, 489
BC849, 148	BTS410, 476T	CMT3-1, 489
BC850, 148	BTS432, 476T	CN0371, 545
BC850C, 142T	BTS442, 476T	connector
BC857, 139, 148g, 149T	BTS452, 476T	1.0mm, 19t
BC860, 142T	BTS555, 476T	7mm, 19t
BCM61, 108	BTS611, 476T	Coolshot Lite, 549n
BCM62, 108	BTS6133, 476T	COP940, 500
BCM857, 139, 139, 506	BTS6142, 476T	COSMOS-66 (Teledyne), 633
BCM860, 139	BTS6144, 476T	CP-5, 25g
BCW61, 146g	BUF602, 338T	CPC3982, 215g, 217
BCX70, 148g, 149T	BUF632, 336s	CPH3910, 320n, 323, 333
BCX70J, 142T	BUF634, 261, 262, 278, 335, 336, 338T, 339g, 411, 435	CPH6904, 320n
BCX71, 149T	BUK202-50, 476T	CRCW (Vishay), 23, 24, 32s, 76
BD139, 489, 490s, 514, 515p, 517s	BUZ50B, 200T	CRCW-HP (Vishay), 28
BD140, 489, 490s	BWV198, 296n	CRCW-hp (Vishay), 29g, 32s
BD437, 142T	BWV213-215, 296n	CRCW2512 (Vishay), 391
BF511, 175T	BWV54, 296n	CRCW2512-HP, 391n
BF545C, 175T	C10372, 628	CS005, 537
BF720, 166t, 167	C11202, 620	CS10, 537
BF721, 166t, 167	C11204 (Hamamatsu), 508	CX240D5 (Crydom), 73p
BF861, 105g	C13366, 624	D1213A, 85g, 322, 413
BF861B, 175T, 183g	C16910, 634n	D2425 (Crydom), 79
BF862, 105g, 175T, 179, 183, 184g, 191g, 222t, 313, 313g, 332, 333n	C2M0280120, 477n	D2440 (Crydom), 73p
BFG35, 146g, 149T	C2M0280120D, 261, 261s	DAC8564, 508n
BFG410, 149, 149n	C30617, 612n	DC2042, 453
BFG591, 146g, 148g, 149T	C5750X7T2J (TDK), 261, 261s	DCP0207P, 487
BFP620, 149	CA3080, 341	DCP021515, 488s
BFP650, 148	CA3145, 148g	DF06M, 467, 510
BFR93, 146g, 148g, 149T	capaNCdT (Micro-Epsilon), 537	DF17 (Hirose), 21p
BFS17, 148g, 149T	CBT-120-R (Luminus), 519	DG85B (Durakool), 74p
		Disto D2, 548, 549, 549p, 550s
		DK-136M (Luminus), 277
		DMMT3904, 322
		DMMT3906, 506

- DN2470, 217
 DN2530, 217
 DN2540, 217
 DN3545, 264
 DNLS350, 218, 219
 DPS368, 562, 562p, 563
 DR334-105BE, 493p
 DRV5053, 15n
 DRV5055, 547g
 DS18B20, 593
 DS2762, 450, 451
 DS2E (Aromat), 72p
 DSA815TG, 91, 91s
 DSMZ (Vishay), 30
 DSS20200, 146g
 DSS20200L, 149T
 DSS20201, 146g
 DSS20201L, 149T
 DSS20201L2SD1684, 142T
 DT3060, 538
 DW3000, 548

 ECW20N20, 273
 ECW20P20, 273
 EL5100, 366
 EL5104, 350T, 366
 EL5151, 350T
 EL5162, 358T
 EL5164, 358T
 EL5166, 358T
 EL8101, 350T
 EP1W (TE), 497, 497, 497s, 498, 498s
 ERA (Panasonic), 23
 ERJ (Panasonic), 23
 ERJ-T08 (Panasonic), 29g
 ERZ-V20D201, 467
 ES-S1, 538
 ES-U8, 538
 ES1C, 167

 F-PD-30-A-H-FCS, 611n
 F120-020 (Triad), 510
 F16-070 (Magnetek), 467
 FAN3100, 256T
 FAN3111, 256T
 FAN3121-22, 256T
 FAN3180, 256T
 FAN3213-14, 256T
 FAN3216-17, 256T

 FAN3223-25, 256T
 FAN3226-29, 256T
 FAN7371, 475
 FAN7382, 263T
 FAN7390, 263T
 FAN7392, 263T
 FANDURONTB (StarTech), 516
 FB43-110, 143
 FBA06A12 (NMB), 516
 FCH47N60, 271g, 271T, 272g
 FCI-InGaAs-75, 612n
 FCP650N80, 264
 FDB9503, 449
 FDBL86361, 449
 FDC1004, 537, 538
 FDG6323, 476T
 FDP7N60, 285n, 286, 434, 434
 FJA4213, 271n
 FJA4313, 271n
 FJAF6810, 91n
 FJP1943, 166t, 167
 FJP5200, 166t, 167
 FMMT458, 425
 FPF2110, 476T
 FPF2123, 476T
 FPF2702, 476T
 FQA19N60, 259, 263
 FQD1N60, 413t
 FQD1N80, 200T, 413t
 FQD2N100, 200T, 416
 FQN1N60, 286
 FQP13N10, 514, 515p, 517s
 FQP2N60, 413t
 FQP2N90, 200T
 FQP4P40, 500
 FQPF8N80, 257, 263
 FR802, 91n
 FRG-700, 570
 FSV20100, 81g
 FZT458, 166t, 167, 422, 423
 FZT558, 166t, 167, 422, 423

 G14858, 620
 G2RL (Omron), 78
 G2SC4793, 273g
 G5CA (Omron), 72, 73
 G5LE (Omron), 72p
 G5V (Omron), 72p, 76, 76s, 77t, 78, 79
 G6L (Omron), 72p

 G7L (Omron), 73p, 79
 GB01SLT06, 84g
 GC2-230L, 529
 GD4200, 565
 GI750, 88s
 GLM400C, 549
 GS-1, 585
 GT2 (Keyence), 545, 546
 GT20D101, 271, 271g, 271T, 272g
 GT20D200, 269n
 GT20D201, 271T

 H11870, 629n
 H13223, 621
 H7546B, 630
 HA2505, 365, 365t
 HA2605, 365, 365t
 HA4600, 338T
 HA5002, 338T
 HA5141, 365
 HA5151, 365
 HCPL-2201, 276
 HDC1010, 594
 HDC3020, 603, 604
 HE3600 (Hamlin), 79
 HFA1112, 338T
 HFA1130, 358T
 HFA1135, 358T
 HFA3046, 146g, 148g, 149T
 HFA3096, 146g, 148g
 HFA3127, 146g, 148g
 HFA3128, 146g, 148g, 149T
 HGJM-51111 (Clare), 72p
 HGJM2MT (Clare), 72p
 HMA2, 547
 HP3561A, 125, 584
 HP4192A, 317
 HP47201, 636, 637p
 HP8012, 155, 155p
 HP8082A, 155
 HPT200, 570
 HS12SP, 605, 605g
 HS3001, 604
 HS4001, 604
 HUF75652, 275, 276, 276g, 514, 515p, 517s
 HVCB (Stackpole), 321
 HVD (Caddock), 29
 HVD5 (Caddock), 30

HX711, 553, 558	IR22141, 263T	IRS2109, 263T
IDD60R600, 415, 415	IR25600, 256T	IRS44273, 256T
IF3601, 183g	IRF1405, 252, 252g, 253, 254g	ISL22xxx (Intersil), 33t
IFN146, 175T, 180g	IRF1407, 201g	ISL23xxx (Intersil), 33t
IG120, 267	IRF4905, 449, 449	ISL28190, 350T
IG120-20, 261, 261s	IRF510, 235, 514, 515p, 517s	ISL45xxx (Intersil), 33t
ILD2300, 538	IRF520, 89g, 235	ISL55001, 349T
IM73D122, 575g	IRF520N, 521	ISL55110, 274, 274s
IMG-CA, 640n	IRF530, 234n, 235	ISL89160-62, 256T
IMR420, 570	IRF531, 235	ISL89367, 256T
IMR430, 570	IRF540, 235, 236t	ISL90xxx (Intersil), 33t
IMS5600, 540	IRF540N, 198, 533	ISO7220, 487
IMX411, 633	IRF5x0, 234ff, 234, 235t	IsoVu (Tektronix), 522, 523
IMX455, 633	IRF640, 168t, 271g, 271T, 272, 272g, 273, 273n	IXCP10M90, 211g
INA106, 397	IRF6x0, 234ff, 234, 235t	IXDD602, 256T
INA133, 405, 406, 406g, 410, 411s, 481T	IRF730, 234n	IXDD604, 256T
INA138, 481T	IRF740, 202	IXDD609, 256T
INA139, 481T	IRF7x0, 234ff, 234, 235t	IXDD614, 256T
INA149, 418	IRF810, 234n	IXDD630, 256T
INA154, 158n	IRF820, 235	IXDx609, 270
INA170, 481T	IRF830, 234	IXFH400N075, 29, 435
INA193-95, 481T	IRF830N, 234	IXFK26N120, 259
INA199, 481T	IRF8x0, 234ff, 234, 235t	IXTA05N100, 77t
INA200-02, 481T	IRF9640, 168t, 271T	IXTA06N120, 435
INA206-08, 481T	IRFB20, 201g	IXTA1N120, 223, 223n, 225, 225g, 405, 406g, 408, 408g, 410, 411s
INA210-15, 478, 481T	IRFBG20, 200T	IXTH02N250, 200T
INA220, 481T	IRFP2907, 531	IXTH03N400, 200T
INA223, 481T	IRFPG50, 269t	IXTH10P60, 271T
INA225, 481T	IRFZ14, 235, 235t, 236, 236t, 511, 512s	IXTH2N170, 210
INA226, 481T	IRFZ24, 235, 236t	IXTK120N25, 271g, 271T, 272g, 273
INA240, 481T	IRFZ34, 235t, 236, 236t	IXTK90P20, 271T
INA250, 481T	IRFZ44, 235, 235t, 236, 236t, 237	IXTN40P50, 271T
INA270-71, 481T	IRFZ44E, 236t	IXTN60N50, 271g, 271T, 272g
INA282-86, 481T	IRFZ44N, 236t	IXTP01N100, 201g
IPP47N10, 514, 515p, 517s	IRFZ44V, 236t	IXTP01N100D, 229, 230g, 231
IPP80R1K4P7, 264	IRFZ44VZ, 236t, 237	IXTP01N120, 231
IPS511, 476T	IRFZ44Z, 236t, 237	IXTP02N120, 200T, 201g, 413t
IPS6011, 476T	IRFZ46, 503, 504p	IXTP02N250, 201g
IPS6031, 476T	IRFZx4, 236	IXTP02N50, 217
IPT007N06, 449	IRG4PH50S, 269t	IXTP03N400, 201g
IPZ60R017, 242	IRL2203N, 271g, 271T, 272g	IXTP05N100, 200T, 201g
IR2085, 502, 503	IRL2505, 271g, 271T, 272g	IXTP06N120, 200T, 201g, 413t
IR2101, 263T	IRL520, 86g	IXTP08N100, 218, 219
IR2113, 257, 258, 258, 259, 259, 263T, 284, 286	IRL5xx, 235	IXTP1N100, 200T, 201g
IR2121, 256T	IRL6xx, 235	
IR21531, 263T	IRLZ44N, 201g, 248, 249s, 250, 251, 251g	
IR2213, 258, 258, 259, 259, 263T	IRS2108, 263T	

IXTP1N120, 198, 198ff , 199, 200g, 200T, 201g, 405, 405n, 406g, 408, 408g, 410, 411s	L4-2486-005 (Lumentum), 521	LM7321, 349T
IXTP2N100, 201g	L6565, 484, 485	LM7322, 489, 490s
IXTP2NK100, 201g	LB200, 436	LM7332, 489, 490s
IXTP3N120, 200T, 201g	LCA-4K-1G, 321n	LM7372, 349T
IXTP3N150, 201g	LCE-series TVS, 527	LM741, 140
IXTP3N50D, 481, 481s	LCE10A, 529	LM7705, 374, 375
IXTP3NK100, 201g	LCG H9RM-LXLZ-1 (Osram), 519n	LM7805, 499
IXTP4N150, 201g	LCT540, 579	LM78Lxx, 446r
IXTU01N100, 200T	LF355, 294, 378s, 379t	LM78xx, 446r
IXTY01N100, 223, 226, 413t	LF355-57, 378	LM7905, 498n, 499, 500
IXTY02N120P, 229	LF356, 294, 348T, 378, 378s, 379t	LM79xx, 446r
J105, 175T, 180, 180g, 183g	LF357, 294, 348T, 378, 378, 379s, 379t	LM8261, 318g, 319, 349T
J106, 175T, 183g	LF411, 294, 310, 310, 360, 361, 364, 364t, 365g, 365t, 367, 382, 382s, 383g, 383s, 387, 401, 402g, 402s	LMC6001, 400
J107, 175T, 180g, 183g, 222, 222t, 453, 453s	LF412, 336, 336s, 393, 394, 394s	LMC6081, 373g
J108, 175T, 183g	LM13700, 341, 341	LMC6482, 187, 294, 372, 373, 373g, 374s
J109, 175T, 180g	LM2575, 63	LMC6xxx, 294
J110, 175T, 183g	LM301, 140n, 294, 340	LME49710, 349T
J111, 174, 175T, 180g, 183g	LM317, 206, 446r, 510	LME49720, 349T
J112, 175T, 180g, 183g	LM317HV, 503, 504p	LME49860, 349T
J113, 175T, 180g, 183g	LM317L, 446r	LME49870, 349T
J174, 174, 175T	LM321, 435	LME49990, 349T
J175, 105g, 175T	LM334, 110, 209, 209, 210, 211, 230, 231, 448r, 514, 515p, 517s, 587	LMF (Vishay), 547
J176, 175T, 189g	LM337, 446r	LMG1210, 270
J177, 175T	LM34, 593n	LMG5200, 270
J210, 180g	LM3480-3.3, 261, 261s	LMH6321, 338T
J23-18I-R01M-2.4, 614n	LM35, 593	LMH6559, 338T
J308, 175T	LM358, 373g, 435	LMH6601, 348T
J309, 105g, 175T, 180g, 183, 183g	LM385, 83, 83g, 107, 159	LMH6611, 350T
J310, 175T, 183g	LM385-2.5, 509	LMH6622, 350T
JFE2140, 324n	LM394, 142T, 146g	LMH6624, 351T
JR13003, 484	LM4132, 218, 219	LMH6628, 350T
K2-W, 294, 294p	LM4562, 336, 336s, 349T, 489, 490s	LMH6629, 351T
KM184, 575g	LM5110, 256T	LMH6642, 350T
KP235, 562	LM5112, 256T	LMH6654, 350T
KRP11 (P&B), 76, 77t	LM5114, 255n, 256T	LMH6657, 350T
KSA1142, 166t, 167	LM6171, 192, 192, 349T, 353, 355, 434	LMH6702, 358T
KSA1381, 166t, 167	LM6181, 358T	LMH6704, 338T, 339g
KSC2682, 166t, 167	LM7121, 349T	LMH6720, 358T
KSC3503, 166t, 167	LM7171, 345, 349T, 366	LMH6723, 354g, 358T
KTY82 (NXP), 399	LM723, 446r	LMH6732, 358T
KUL-11D15D-24 (P&B), 467		LMP7701, 330, 331, 331g, 332t, 372, 373g
L1357, 379s		LMP7717, 348T
L4-2486 (Lumentum), 522		LMP7721, 229, 230, 230g, 400
		LMP7731, 372, 373g
		LMP8480-81, 481T
		LMP8601-03, 481T
		LMP8640, 481T
		LMP8645, 481T

650	PARTS INDEX	<i>Art of Electronics – The x-Chapters</i>
LMP8671, 349T	LT1351, 349T, 361	LTC2946, 481T
LMV43, 470	LT1351-63, 353, 355, 366	LTC2947, 481T
LMV861, 348T	LT1354, 349T, 387, 387s	LTC3107, 453
LND150, 182n, 205, 205g, 207, 207, 207g, 208, 209, 210, 210, 211, 212g, 215g, 405, 406, 406g, 410, 411s, 419, 509	LT1357, 349T, 378, 379, 379t	LTC3108, 453, 453, 454
LPS151 (Leader), 517s	LT1360, 349T	LTC3109, 453
LPS22DF, 560	LT1363, 261, 262, 345, 349T	LTC3534, 450, 451
LPS25, 594	LT1395, 353, 358T	LTC4070, 451
LS5912, 175T, 180g, 183g	LT1399HV, 358T	LTC4151, 481T
LS840, 183g	LT1468, 349T	LTC4160, 450n
LS840-42, 175T	LT1494, 373g	LTC6078, 330, 332t, 372g, 373, 374s
LS843, 178	LT1630, 349T	LTC6087, 331, 331g
LSK170, 174, 175T, 178, 180g, 183g, 189n	LT1638, 481T	LTC6090, 404, 508, 509
LSK170B, 105g	LT1783, 478, 479	LTC6101, 477, 478, 481T
LSK389, 175T, 180g, 183g, 184t, 192, 324n	LT1792, 396, 397	LTC6101HV, 478
LSK389B, 105g	LT1794, 342, 349T	LTC6240HV, 330, 331, 331g, 332t, 373g
LSK843-45, 175T	LT1800, 350T	LTC6244, 348T
LT1007, 364, 364t, 365g, 365t	LT1803, 350T	LTC6268, 344, 348T
LT1010, 292, 335, 336, 338T, 339g	LT1807, 350T	LTC6268-10, 348T
LT1012, 368, 369, 370, 371, 371n, 378s, 379, 379t, 380s	LT1809, 350T	LTC6416, 338T
LT1013, 370, 373g	LT1812, 350T	LTC6417, 338T
LT1027, 514, 515p, 516, 517s	LT1815, 345, 350T	LTC8043, 367
LT1028, 125, 125p, 345, 349T, 368, 368t, 370, 371	LT1818, 351T	LVR-3 (Dale), 531, 531
LT1055, 360, 361, 361g	LT1970, 388	LVR-5, 25g
LT1097, 360, 360, 360g, 370, 371n, 378s, 379, 379t, 380s	LT2940, 481T	
LT1128, 584	LT3092, 206, 587	
LT1178, 373g	LT3743, 277, 277s	
LT1206, 358T	LT3999, 488s	M160, 575g
LT1208, 349T	LT5400, 30	MAG470, 570
LT1209, 349T	LT6010, 368, 370, 370, 371, 371n, 379, 379g, 379t	MAX15070, 255n
LT1210, 353, 358T, 366	LT6200, 350T	MAX16818, 277
LT1217, 312, 313, 313g, 358T	LT6200-10, 351T	MAX16819, 277
LT1220, 349T, 388	LT6200-5, 351T	MAX17600-05, 256T
LT1221, 349T	LT6202, 350T	MAX293, 301n
LT1222, 349T	LT6205, 350T, 353	MAX294, 301n
LT1223, 353, 354, 354g, 355, 358T	LT6205-07, 356	MAX297, 301n
LT1224, 349T, 379t, 380, 381s	LT6211, 358T	MAX31723, 593
LT1226, 344, 349T	LT6220, 343, 343g, 350T	MAX31856, 595, 596
LT1227, 358T	LT6230, 344, 350T	MAX31865, 593, 595
	LT6230-10, 344, 351T	MAX4014, 337
	LT6233, 343, 344, 350T	MAX4014-22, 338T
	LT6233-10, 344, 351T	MAX4104, 351T
	LT6236, 350T	MAX4105, 351T
	LT6559, 358T	MAX4200, 338T
	LTC1550, 374, 375	MAX4214-22, 338T
	LTC1844, 44, 44	MAX4223, 357, 358T
	LTC1968, 425	MAX4224, 357, 358T
	LTC2050, 398	MAX4231, 348T
	LTC2645, 430	MAX4236, 373g
	LTC2945, 481T	MAX4239, 348T
		MAX4285, 338T

- MAX4304, 351T
 MAX4305, 351T
 MAX4389, 350T
 MAX44280, 348T
 MAX4451, 350T
 MAX4488, 348T
 MAX5048, 255n, 256T
 MAX5054-57, 256T
 MAX5490, 30
 MAX6682, 595
 MAX9632, 349T
 MBR10100, 514, 515p, 517s
 MBR1060, 514, 515p, 517s
 MC34151, 256T
 MCA (Vishay), 29g
 MCP42xxx, 35
 MCP4921, 430
 MCP6293, 348T
 MCP6V06, 371
 MCP9808, 593
 MD421, 575g
 MegaPAC (Vicor), 468
 MIC2514, 476T
 MIC44F18-20, 256T
 MIC5207, 286
 MIC920, 344, 349, 350T
 MicroFC-SMTPA-30035, 630
 MJD340, 419, 425
 MJD350, 419, 425
 MJE15032, 166t, 167, 168, 168g
 MJE15033, 166t, 167, 168g
 MJE340, 166t, 167
 MJE350, 166t, 167
 MJH11000, 272
 MJH11021, 271T
 MJH11022, 271g, 271T, 272, 273g
 MJL21195, 166t, 167
 MJL21196, 166t, 167
 MKP338 (Vishay), 416, 417
 MLX90614, 592
 MMBD1403, 396, 397
 MMBD5004, 500
 MMBF170, 193n
 MMBF4117, 390, 400
 MMBF4392, 176, 390
 MMBF4416, 175T, 177, 180g
 MMBF5103, 180g, 183g
 MMBF5457, 329, 329, 330g
 MMBF5460, 105, 329, 329, 330g
 MMBF5461, 390
 MMBFJ110, 514, 515p, 517s
 MMBT3904, 313, 313g
 MMBT4401, 405, 406g, 408, 408g, 410, 411s
 MMBT5089, 477
 MMBT5962, 334
 MMBT6429, 142T, 334
 MMBT6520, 390
 MMBT918, 146g, 148g, 149T
 MMBTA42, 422
 MMBTA92, 405, 406g, 408, 408g, 410, 411s, 422
 MMBTH81, 149T, 153, 153n, 153s
 MOX resistors (Ohmite), 26g
 MP240D4 (Opto-22), 73p
 MPS5179, 148g, 149T
 MPS8098, 142T
 MPS8099, 142T, 146g, 149T
 MPS8599, 142T, 146g, 149T, 313, 313g
 MPSA18, 142T, 334
 MPSA42, 105g, 128g, 128n, 142T, 147, 250, 392, 422, 479
 MPSA4250, 142T
 MPSA92, 128n, 250, 392, 422, 478, 478, 479
 MPY634, 393, 394, 394s
 MRA4004, 500
 MSO4104, 90
 MTP3N120, 200T
 MUR2020, 81g
 NCP1117, 264
 NCP1392, 263T
 NCP5111, 263T
 NCP51530, 264
 NCP51705, 270
 ND210, 563
 NE-2, 294, 294
 NE535, 365
 NE538, 365, 365g
 NE85634, 148g
 NKE (MuRata), 285
 nRF52840, 548
 NT1A, 579
 NV6113, 270
 NXFT15XV103FA2B150, 594n
 OD (Ohmite), 28, 29g
 OF (Ohmite), 29g
 OFM-1501 (Astrodyne), 469, 470
 OP-07, 294
 OP-37, 349T
 OP-97, 129n
 OP37, 322
 OP535, 618
 OP560, 618
 OP657, 630
 OP97, 370, 371n
 OPA129, 368, 368t
 OPA140, 348T, 373g, 419
 OPA1604, 489, 490s
 OPA1611, 349T, 376
 OPA1632, 349T
 OPA1641, 348T
 OPA1664, 489, 490s
 OPA1688, 348T
 OPA172, 319, 322, 348T
 OPA189, 348T
 OPA192, 348T, 398
 OPA197, 315, 316, 318g, 319, 320
 OPA209, 349T
 OPA211, 349T
 OPA2140, 326, 329, 329, 330g, 330t
 OPA2188, 373g
 OPA2192, 400, 400, 400n
 OPA2227, 516
 OPA2277, 397, 405, 406, 406g, 408, 408g, 410, 411s
 OPA228, 349T
 OPA2604, 348T
 OPA2674, 358T
 OPA2677, 358T
 OPA275, 365
 OPA277, 354, 370, 387s
 OPA2810, 348T
 OPA2846, 351T
 OPA285, 365
 OPA2889, 350T
 OPA300, 348T
 OPA316, 348T
 OPA338, 348T
 OPA350, 348T
 OPA354, 348T
 OPA355, 348T
 OPA357, 332, 333, 348T
 OPA358, 348T

652	PARTS INDEX	<i>Art of Electronics – The x-Chapters</i>
OPA365, 348T	P1811, 491p	PR02-FS (Vishay), 29g
OPA369, 372g	P3019, 491p	PSMN7R8, 195g
OPA375, 348T	P3622, 491p	PSPL5542, 64, 66g, 67p
OPA376, 373g, 478, 479, 509	P65, 294	PSS2-16 (Microtran), 467
OPA380, 348T	P65A, 295, 295p	PSV (Polytec), 542
OPA445, 508n	P6KE, 527	PT7, 565
OPA454, 348T, 366, 366s, 367, 367, 367g, 367s, 404, 508n	P6KEvvvA, 76	PVI5033, 521
OPA4637, 322	P6KEvvvCA, 77n	PWC (Welwyn), 29g
OPA552, 348T	P6SMB10JA, 29	PWR220T-20 (Bourns), 29g
OPA606, 348T	PA95, 404	PYD1378, 625
OPA627, 294, 310, 312, 326, 330t, 365, 368	PA97, 404n	
OPA633, 338T	PA99, 404	QA01C, 261, 261s
OPA637, 310, 312, 313, 313g, 314, 314, 320	PASCO2, 640	QA10C, 267
OPA655, 294	PC412S, 487	QPAC (Vicor), 511
OPA656, 294, 310, 348T	PCAN (Vishay), 24, 28, 29g, 32s	QPDI-80, 630
OPA657, 311, 348T	PDA015A, 630	QSE (Samtec), 21p
OPA659, 348T	PDA40, 624	
OPA660, 411	PDP90A, 625	R-175A, 64
OPA690, 350T, 366	PDQ30C, 625	R10467, 621
OPA691, 358T	PDQ80A, 624	R11322, 621
OPA692, 337, 338T, 339g	PDV-P8001, 609, 610s	R12860, 627n
OPA693, 337, 338T	PE-50502 (Pulse Engng), 491s	R14713, 621
OPA694, 358T	PESD12V, 219	R1527, 628
OPA695, 338T, 358T	PF5103, 175T	R15P21503, 267
OPA698, 350T	PG508, 155	R175A, 66g
OPA699, 351T	PG508 (Tektronix), 163, 163, 164, 165, 166s	R2295, 628
OPA827, 348T, 365	PH9455.826NL, 493p	R3550, 623, 628
OPA828, 317, 318, 322	PIN-13D, 332, 332	R3809, 627
OPA832, 338T	PIN-5D, 309	R7110U, 621, 630
OPA835, 350T	PM5786, 155	R7400 (Hamamatsu), 274s
OPA836, 350T	PMBF4395, 105g	R7400P, 630
OPA837, 350T	PMBFJ110, 514, 515p, 517s	R9880, 627
OPA838, 350T	PMEG4010, 85g	Rad-57, 639
OPA846, 351T	PMFJ108, 183g	RB161, 503, 504p
OPA855, 351T	PN2369, 146g	RC07, 26g, 28, 31p, 32s
OPA858, 348T	PN3563, 146g	REF200, 448r
OPA859, 348T	PN4117, 229, 230g, 400	RFR 50-250, 266
OPA860, 278	PN4117-19, 175T, 183g	RG-174, 9n
OPA860-61, 341	PN4117A, 180g	RG-316, 9n
OPA861, 341	PN4118, 180g	RG-58, 9n, 266g
OS-CON, 39g, 40	PN4119, 180g, 184g	RG-59, 9n
os9120, 565	PN4250, 146g	RG-6, 9n
OX (Ohmite), 27	PN4391, 189, 190g	RG142, 91
OY (Ohmite), 27	PN4391-3, 175T, 183g	RH-250, 25g
	PN4392, 176, 192	RHRG75120, 89
	PN4393, 180g, 184g, 186, 188, 188g, 189, 190, 190g, 190t	RIS-254, 531n
	PN5179, 146g, 148g	RIS-617, 312
		RIS-688, 263
		RJK6024, 413t
		RM10, 488, 489, 490s, 491p

RM12, 491p	SER2800 (Coilcraft), 138g, 138p	STP3NK100, 200T
RM12 (Ferroxcube), 60	SER2814H-103 (Coilcraft), 504p	STP4N150, 200T, 278, 411
RM8, 491p	SFH1212, 452	STP80NF55, 271g, 271T, 272g
RN55D, 311	SHT30-DIS-B, 594	STP80PF55, 271T
RP7631 (Clare), 72p	SHT4x, 604	STW9N150, 263
RPS500 (Vishay), 29g	Si7021, 594	SUP75P03-07, 271T
RS-2B (Dale), 264, 265p, 266	Si8610, 259, 261, 261s	SUP90P06-09, 271T
RS-5 (Dale), 266	SKY65050, 247	
RS-7 (Dale), 266	SL11, 588	T103, 314
RS2B, 25g	SLA580, 274s	T220 (Highland Technology, 91, 92s
RS2B (Dale), 264	SLD840, 540	T90S5D (P&B), 73p
RT8522-6-10M0, 493p	SLS130, 547	T92 (P&B), 79
RXM42AF, 611n	SLS320, 547	T92 (Tyco), 71
	SM-24, 584, 584p	TC4420, 256T, 262, 262, 263, 521
S1133, 330, 331, 331g	spectra from, 584g	tc4420, 255
S12013, 619g	SM-58, 581	TC4421, 255n
S12023, 619	SM102032004F (Ohmite), 262	tc4421, 255
S1223, 309	SM103 (Ohmite), 25	TC4421-22, 256T
S13360, 623n	SM27, 579	TC4422, 255n, 260
S13360 (Hamamatsu), 385g	SM58, 571	TC4423-25, 256T
S13360-3025CS (Hamamatsu), 386s	SM7B, 575g, 579	TC4424, 276
S13360-3025PE, 630	SP490, 563, 564	TC4426-28, 256T
S13360-3050CS, 630	SPAD512 ² , 621	TC4429, 29, 256T
S13361, 623	SPCM (Thorlabs), 620	TC4431, 255n
S13361-3050AE-08, 630	SPD800, 564	TC4432, 255n
S13720 (Hamamatsu), 385	SPDM (Thorlabs), 620	TC4451, 255n
S13720-1325CS, 630	SPP02N80, 200T	TC4452, 255n
S15415, 619n, 620g	SQM40031, 449	TDS3044, 250, 305, 380
S16835, 620	SR560, 554	Tek TDS3000-series, 631
S1K-60 (NCC), 74p	SR570, 316	THAT2181, 34
S2035K, 467	SRS530, 15n, 16	THS3001, 358T
S2055M, 467	SS10X7X4.5W (Toshiba), 61	THS3061, 358T
S2065K, 467	SS4 (Samtec), 21p	THS3091, 156, 156g, 156s, 358T
S2386, 614n	SSM2212, 398	THS3095, 358T
S2387, 330, 331, 331g	SST4392, 176	THS3120, 358T
S3A, 85g	SST4416, 183g	THS3122, 358T
S67R5 (P&B), 74p	SSTJ210, 180g	THS3201, 358T
S9014, 484	ST-6A, 585	THS3491, 358T
S9055, 612n	St. Mark Passion, 296n	THS4021, 349T
SA110, 270, 270n	STD1HN60, 413t	THS4031, 349T
SB1197KQ, 142T	STD704, 95	THS4061, 349T
SCD34, 485	STE2300 (Ramsey), 125	THS4081, 349T
SCR584, 294	STHS34PF80, 626	THS4211, 350T
SCT2450, 261, 261s	STMP52151, 476T	THS4221, 350T
SD101, 84g, 88, 159, 379	STP27N3, 251, 251g, 251s	THS4275, 351T
SD103, 82g, 85g, 88, 92, 92s, 159, 274, 274s, 375, 489, 490s, 514, 515p, 517s	STP2N105, 413t	THS4304, 351T
SDS2104 Plus, 302	STP2N80, 264	THS4601, 348T
	STP2NK100, 200T	THS4631, 318, 348T
	STP2NK90, 200T	THS6012, 358T
	STP3N150, 200T	

654	PARTS INDEX	<i>Art of Electronics – The x-Chapters</i>
TIP147, 511, 512s	UCC2753x, 259	ZXGD3004, 255n
TIP50, 499	UCC28610, 469–471	ZXTN19020, 142T
TL011, 108	UCC37321-22, 256T	ZXTN19100, 142T
TL081, 294	UCC37323-25, 256T	ZXTN2018, 142T
TL431, 125, 125, 126, 466, 470, 484, 485	UCC5320, 270n	ZXTP2027, 142T
TL783, 510, 510	ULN2003, 500	
TLC2272, 373g	UM30, 538, 538	
TLCT1008, 219	USVD (Caddock), 29	
TLE2141, 365, 379, 379g, 379t	USVD2 (Caddock), 30	
TLP3906, 415, 416	V130LA20C, 467, 527	
TLV1701, 477	V23026 (P&B), 79	
TLV172, 348T	VFCD (Vishay), 30	
TLV3541, 348T	VFD (Vishay), 30	
TLV431, 159, 424, 466, 467, 470, 512	VN2222, 193, 193g, 193 , 193n, 194, 194g, 195, 196, 196g, 197, 197g, 198	
TLV6741, 348T	VN920, 476T	
TLV9062, 348T	VP0550, 478	
TM500 (Tektronix), 163	VP2450, 478	
TMD-52 (Amprobe), 596	VP89L, 576, 577	
TMP006, 591	VSH (Vishay), 30	
TMP117, 593, 594g	VSMP (Vishay), 23, 24	
TMP125, 508	VTL-5C3, 607	
TMP35, 593		
TMUX7219, 322	W211CPSRX (Magnecraft), 74p	
TNPU (Vishay), 23	WSR5R (Vishay), 29g	
TOP201, 469, 470		
Tour V5, 549n	X9xxx (Intersil), 33t	
TPH3207, 242	XFR7.5-130 (Xantrex), 517s	
TPH3208, 242	XLR, 580, 581	
TPiD-1T-0x22, 625	XPR56C, 554	
TPS2041, 476T		
TPS22960, 476T	Z-foil (Vishay), 24	
TPS7A78, 499	ZFBT-282, 67p	
TS431, 470	ZMSW-1211 (MiniCircuits), 73p	
TS5A23157, 429n	ZTP-135BS, 625	
TSH350, 358T	ZTX450, 142T, 167	
	ZTX458, 151, 152g	
uA709, 294	ZTX550, 142T	
Ua741, 364	ZTX618, 132g, 133, 133t, 142T	
uA741, 294, 340	ZTX650, 151, 151g	
UC3708, 256T	ZTX718, 133t, 142T, 167, 481, 481s	
UCC21520, 478	ZTX851, 126, 139, 142T, 467	
UCC21732, 270	ZTX949, 467	
UCC27516-19, 256T	ZTX951, 139, 142T	
UCC27517, 256T	ZX85-12G, 67p	
UCC27523-26, 256T	ZXGD3002, 255n	
UCC27531, 255n	ZXGD3002-04, 256T	
UCC27538, 255n, 259, 261, 261s, 270, 477		

SUBJECT INDEX

KEY

page number font	boldface	main subject treatment
	<i>italic</i>	figure
suffixes	ff	“and pages following”
	n	footnote
	g	graph
	r	review section
	p	photograph
	s	screen shot (‘scope or spectrum analyzer)
	t	table
	T	tabular
	boldfaceff	main entry, folios following
	(box)	in a box

absolute-value circuit, 290r
ac powered
 efficient dc power supply,
 469, **469**
accelerometer, *see also* sensor,
 586
 dynamic range, 586
 MEMS, 586, 587
 noise, 586
 piezoelectric, 586, 586p, 587
ACRF, 13t
active
 rectifier, 291r
admittance, 3
amplifier
 class-AB, 479
 CMOS, **232ff**, 233
 bandwidth, 233g
 gain, 232g
 common-base, 143
 cascode as, 221, 221
 common-emitter, 103r, 113
 degenerated, 118
 distortion, 116–118g,
 124g
 frequency response, 114,
 115
 linearity, 116–118g, 124g

amplifier (cont.)
 common-gate
 cascode as, 221, 221
 composite, 315
 Bode plot, 336
 stability, 335, **335ff**, 336s
 current-feedback, 414
 difference
 vacuum tube, 294p
 differential, 103r, **117**, 118
 and cascode, 111, 112
 Caprio’s quad, 122, 122g,
 122, 124g
 degenerated, 119, **119**
 distortion, **117ff**, 118,
 119g, 119s, 124g
 emitter-input, **138ff**, 140
 linearity, 118g, 124g
 low-noise, 191, 192
 Sziklai-connected, 120,
 120g, **120**, 121, 121g,
 124g
 transfer function, 119g,
 119s
 distortion
 SPICE simulation, **113ff**
 error, 445, 446r
 grounded-emitter, 113

amplifier, high-voltage (cont.)
 high-voltage, 198, 214, 410,
 411s
 bipolarity current monitor,
 479, 479
 Bode plot, 406g, 414g
 current monitor, 478, 478
 faster, **412ff**
 MOSFET choices, 413t
 precision, **404ff**, 405,
 412ff
 slew rate, 410
 SPICE, 409, 409
 stability, 413
 variations, 411, 412
JFET
 differential, 191, 192
 low-noise, 191, 192
laboratory, **165ff**
lock-in, 15n
logarithmic, 398, 398
 temperature compensation,
 398, 398g
low-noise, 125, 125p, 191,
 192
microphone, 580
MOSFET power, 172r
photodiode, **309**, 310, **312ff**,
 313, 332, **332**, 333, 333

- amplifier, high-voltage (cont.)
 precision, 198
 stability
 decoupling resistor, 409
 summing, **393**, 394, 395
 transconductance, 341
 transimpedance, 307, **307ff**, 315, **315**, *see also* transimpedance amplifier, 332, **332**, 333, **333**, 341
- amplitude
 rms, 2r
- analog
 adder-subtractor, **393**, 395
 computer, 393, 394, 394s
 function circuits, **393**, 394, 394s
- analog switch, 79
 in TIA, **313**, 314
- anechoic chamber, 580p
- APD, 618
 excess noise, 619n, 620g
 gain
 vs total noise, 620g
 gain stabilized, 619n, 620g
 gain vs bias, 619g
 gain vs temp, 619g
 InGaAs, 620
 speed, 619
- aspirin
 of electronics, 111, 112
- audio recording
 microphone placement, 582, 583
- avalanche
 energy, 253
 in diodes, 4r
 photodiode, 384, **384**, 385
 voltage, 210
- Ayrton–Perry, 24
- B-H curve, 54s
 and core loss, 54
 square-loop, 54s
 transformer, 54s
- balanced
 drive, 488
- bandwidth
 equivalent noise, 437
 narrowing
 bandwidth narrowing (cont.)
 lock-in detection, 15
 of cascode, **221ff**
 of source follower, 223, 224, **224ff**, 225g, 226, 226g
 resolution, 437
 bang–bang control, 446r
 Barkhausen noise, 53n
 barometric pressure
 sensor, 594
 units, 594n
 basket weave, 63
 battery
 Li-ion
 cautions, **450**
 charging, 450, **450**
 series connection, 452, 452
 reverse polarity protection, 449, **449**
 Beranek’s box, 580p
 bias tee, **64**, 66, 66g, 67p
 BJT (bipolar junction transistor)
 amplifier distortion, **113ff**
 as zener, 85, 86g, 207n
 bandwidth, **145ff**
 beta, 142g, 273g
 capacitance, 104r, 146, 146g, 149t, 222n
 cascode, *see* cascode
 collector output resistance, 127, 127, 128g, **129ff**
 collector-base time constant, 149, 150g
 current source, 102r
 canceling base-current error, 392, 392
 Darlington, 104r
 transconductance, 272g
 transfer characteristics, 271, 272g
 Ebers–Moll model, 101r
 emitter resistance
 intrinsic, 102r
 gain-bandwidth product, **145ff**, 149t
 vs current, 147–149g
 hybrid- π model, 145
 leakage current, 105g, **105**
- BJT (cont.)
 maximum oscillation frequency, 149
 maximum voltage gain, 129
 micropower wideband, 148
 MOSFET substitute, 140
 operating modes, 100r
 pin labels, 100r
 polarities, 100r
 power, 271, 271T
 rules of thumb, 101r
 switch, 100, 101r
 Sziklai connection, 104r, **131ff**, 132, 132g, 273
 differential amplifier, 120, 120, 120g, **120**, 121, 121g, 124g
 enhanced, 131
 push-pull follower, 133, 133
 transconductance, 100, 101r, 272g
 transfer characteristics, 271, 272g
- Bode plot, 293, 296, **296ff**, **301–306**, 335, 402, 406g, 407, 408g, 414g
 composite amplifier, 336
 high speed, 304
 in amplifier design, 298
 of TIA, 308
 pole-zero network, 305, 306s
 test circuit, 305
- bolometer, *see* sensor, light
- bone
 dog, 554
- bootstrap
 cascode, in TIA, 333, 333
 leakage cancelation, diode, 391
 of bias resistor, 229, 230, 230s
 of power supply, 470
 of TIA, 332, **332**, 333, 333
- Bragg cell, 541
- bridge
 converter, 446r
 Kelvin, 567
 rectifier, 445r
- Brooks coil, 52

- Brownian motion, 580
- buffer
- unity-gain, **335ff**, 338T
 - applications, 336
 - cautions, 338
 - input resistor, 339g
 - output resistor, 339g
 - peaking, 339g
- bus
- converter, 502, **502**, 503, 504, 505p
 - isolated, 505, 505
- cable, *see also* transmission line
- cat-5, 9, 13, 13p, 13t, 14p
 - cat-6, 9
 - coax, 9
 - configurations, **9ff**
 - driving, 335
 - FFC, 14p
 - HV pulse generator, **263**, 264, 264, 265p, 266s
 - Milliken, 11p, 12, 12
 - multiwire, 9
 - RG-402, 20
 - RG-58
 - deficiency, 20
 - ribbon, 10, 14p
 - shielded, 9
 - STP, 14p
 - twisted-pair, 13
 - inductance of, 10
- camera
- FLIR, **590ff**, 590–592p
 - thermal, **590ff**, 590–592p
- capacitance
- as villain, 312
 - digitizer, 537, 538
 - dynamic, 87n
 - junction, 104r
 - multiplier, 97, 98, 470, 511, 511, 512, 512s
 - of diode, 83, 84, 84, 85g, 86, 529
 - of resistor, 23, **23**, 24g
 - of zener, 84, 85g, 86, 529
 - PCB, 7, 8g
 - to-digital converter, 537
- capacitive
- isolator, 261
- capacitor, 2r, **37ff**
- ac line filter, 47
 - ac powerline rated, 483, 484
 - ac voltage coefficient, **42**, 43g
 - aging, **43**
 - at cryogenic temperatures, 48
 - blocking, 3r
 - bypass, 3r, 45
 - ceramic, 37t, 38g, 39t
 - aging, 43g
 - micro-cracks, 47n
 - voltage coefficient, 41g
 - choices, **45**
 - compensation, 260, 446r
 - tunable, 333
 - cryogenic, 601n
 - decoupling, 45
 - departure from ideal, 37ff
 - dielectric absorption, **44**, 45g, 46, 46g, 287
 - dissipation factor, 39, 40, **40**, 41t
 - electrolytic
 - derating, 47
 - energy storage, 46
 - ESL, 37, **39**, 40g, 531
 - ESR, 37, **38**, 531
 - vs size, 39, 39g
 - vs temperature, 39g
 - exploding, 46n
 - family tree, 38
 - frequency dependence, **43**, 44g
 - gimmick, 47, 48n
 - high frequency, 46
 - high voltage, 47
 - impedance
 - vs frequency, 40g
 - loss tangent, **40**
 - mechanical resonance, **43**, 44g, 44, 45s
 - microphone, 572
 - microphonic, **43**, 44, 45s
 - miscellany, 47
 - model, 37
 - non-ideal, 37ff
 - nonlinearity, 42g
 - piezoelectric, 44g
- capacitor (cont.)
- PPS, 48p
 - selecting, **45**
 - silicon, 48, 48p
 - solid polymer, 39
 - storage, 3r, 257, 267, 445r
 - sub-picofarad, 311, 311, 312
 - tempco, **37**, 37t, 38g, 39t, 41g
 - timing, 3r, 46
 - types, 38, 47
 - ultra, 48
 - voltage coefficient, 41g, **41**, 42, 42g
- capacity
- thermal, 534
- Caprio's quad, 122, 122g, **122**, 124g
- with folded cascode, 122, 123, 123, 123, 124g
- carbon dioxide
- infrared absorption, 639g
- cascode, **111ff**, 112, 164, 186, 187, 188, 189, 190t, 191, 192, 192, 206, 207g, 209, 209, 209g, 210, 210, 211g, 285, 368, 369, 369
- and differential amplifier, 111, 112
 - and Early effect, 111, 112
 - and high voltage, 111, 424
 - and Miller effect, 111, 112
 - and transimpedance amplifier, 111, 112
 - as common-gate amplifier, 221, 221
 - bandwidth, **221ff**, 222
 - folded, 122, 123, 123, 123, 124g, 134, 135, 163, 164
 - in current mirror, 107, 107
 - in current source, 207, 208
 - in differential amplifier, **120**
 - series stack, 231
- CERN, 25
- charge
- dispenser, **284ff**
 - MOSFET gate, 172r

- charge (cont.)
 pump, 258, 259, 270, 285n, 445r, 499
 Marx generator, 499
- choke, **62ff**, 64, 65p, 66g
 bank-winding, 65
 common-mode, 488, 492, 493, 494p
- circuit breaker, 528, 529
- clamp
 anti-soar, 516
 low-capacitance, 527, 529
 low-voltage, **466**, 467
- CMOS
 imager, 630, 632p
 lens, 633
 linear amplifier, **232ff**, 233
 bandwidth, 233g
 gain, 232g
- CO₂ sensor, **638**
- Cockcroft–Walton generator, 499
- coil
 Helmholtz, 15, 16p
- cold-junction compensation, 595
- common-mode choke, *see also* choke
- comparator, 103r, 291r, 446r, 478
- compensation, **296ff**
 cold-junction, 595
 pole-zero, 516
- conduction
 angle, 270
 class-A, 248
- confidence
 misplaced, 516
- connector, **17ff**, 21p
 0.9mm, 19t
 1.85mm, 19t
 2.4mm, 19t
 2.92mm, 19t
 APC-7, 19t
 audio, 18
 avoid these, 18
 BNC, 18, 19, 19g, 19t
 deficiency, 20
 D-sub, 18, 21, 21p
 DIN, 18
 F, 18
 FFC, 21p
 header, 21p
- connector (cont.)
 high-density, **21**
 high-voltage, 18
 K, 64
 MCX, 19t
 microphone, 580
 MMCX, 19t
 power-entry, 18
 RCA, 18
 rectangular, 18
 reflection from, 19, 19g
 RF and shielded, 18, **18ff**, 19g, 19t
 RM, 18
 SC, 19g
 SHV, 18
 SMA, 18, 19, 19g, 19t, 20, 64
 SMB, 18, 19t
 SMC, 19t
 3.5mm, 19, 19t
 SSMA, 19g, 19t
 superSMA, 19t
 TNC, 19g, 19t
 type N, 19g, 19t
 UHF, 18, 19, 19g, 19t
 V, 64
 XLR, 18, 580
- contactor, 282
- control
 bang–bang, 446r
- coplanar waveguide, 8
- coupling
 electrostatic, 12
 magnetic, 12
 mitigation, 13
 test circuit, 13, 13s
 unwanted, **12ff**
 mitigation, 13
- creepage, 483, 484, 486, 486p
- cricket
 as thermometer, 589
- crosstalk, 12, 13, 13s, 13t
- crowbar, 389
 overvoltage, 446r, 448r
 low-voltage, **466**, 467
- cryogenic temperatures
 operation at, 48n
- current, 2r
 bound, 49n, 53
 conduction, 49n, 53
- current (cont.)
 dynamic, 423
 eddy, 10, 15
 free, 53
 harmonic, 472n
 high-side sensing, **477ff**
 ICs, 481T
 in wires, 5
 inrush, 472, 472–474s
 junction leakage, 4r
 leakage, 80, 80g
 actual, **105**
 diode, 4r
 diode, eliminating, 400, 400
 vs temperature, 80, 81g
 vs voltage, 81g
 limiting, 446r, 478
 foldback, 151, 151, 151, 152g
 recombination, 141g
 saturation, 194
 sensing
 ICs, 481T
 shoot-through, 257, 259, 261, 273
 tunnel, 93
- current mirror, 102r, **108**, 421, 424
 bipolarity, 134, **134ff**, 135s
 high ratio, 138, **138**, 139
 monolithic, 108
 multiple output, 108, 108
 piezo driver, 287, 287
 ratio, 108, 109, 109, 109g
 Widlar, 108, 109, 109, 109g
 Wilson, 107, 109
 monolithic, 108
- current source, 106, **106ff**, 390, 448r
 V_{BE}-referenced, 108
 2-terminal, 422
 bipolarity, 134, **134ff**, 135, 135s, 421, **421ff**, 422
 high voltage, 135, 136
 precision, **136**, 137
 canceling base-current error, 392, 392
 cascode in, 107, 107
 deficiencies of, **106ff**

- current source (cont.)
 depletion-mode, 206, **206ff**, 207, 207g, 419
 dissipation, 422
 errors, 422
 fast-switching, 530, 531
 floating, **206ff**, 218, **218**, 219, 220g
 gain, 434
 high-side monitor, 424, 424–426
 high-voltage, 210, **210ff**, 211, 212g, 214–216g, 217, 218, **218**, 219, 220g, 421, **421ff**, 422, 434, 435, 479
 “perfect”, 217
 Howland
 bootstrapped, **418**, 418–419, 419–420s
 HV Howland, **418**
 LM334, 110
 magnet
 fast-switching, 530, 531
 monitor, 424, 424–426
 MOSFET, 284
 output resistance, 107, **130**, 207g
 dynamic, 207, 208
 programmable, 110
 programmed cascode, 209, 209
 pulsed, 435, 436p
 reducing power dissipation, 208, 208, 209, 209g, 210, 211g
 slew rate of, 423
 tempco, 106, 107
 current-crowding, 141
- damping
 ratio, 308
- dB, 2r
- dc motor model, 461, **461**
- decapot, *see* resistor, digital
- delta function, 90
- depletion region, 611
- Designs by the masters
 Apple 5 W charger, **482ff**
- Designs by the masters (cont.)
 bulletproof input protection, **389ff**, 390
 Monticelli output stage, **375ff**
 PG508 pulse generator, 163, **163ff**, 164, 165, 166s
 wide-range linear TIA, **325ff**, 329
- desk wart, 492
- dielectric
 absorption, **44**, 45g, 46, 46g
 constant, 41, 43, 43n
- digipot
 frequency response, 34g
 log approximation, 34g
- diode, 4r, **80ff**
 back, 95
 capacitance, 83, 84, 84, 85g, 86, 529
 characteristics, 80
 clamp, 155, 155
 cryogenic temperature sensor, 598
 fast-recovery, 88, 281
 FERD, 88
 forward current, 80, 81, 82g
 forward drop
 cancellation, 156
 tempco, 82g
 forward dynamic impedance, 82, 82g
 forward recovery, 91, 92s
 freewheel, 281
 input protection, 84, 529
 leakage, 80, 80, 81g
 eliminating, 400, 400
 peak current, 83, 84g
 reverse recovery, **86ff**, 87s, 88g, 88s, 89g, 464, 464, 465s, 484, 516
 test circuit, 86, 86
 Schottky, 82g, 88, 158, 464
 soft-recovery, 88
 step-recovery, **89**, 90s, 91, 92s
 test circuit, 89
- diode (cont.)
 stored charge, **86ff**, 87s, 88, 89g, 464, 464, 465s, 484, 516
 test circuit, 86, 86
 transient thermal resistance, 84g
 tunnel, **92**, 93
 VI curve, 93, 93, 94, 95s
 test circuit, 94, 94, 95p
 trigger, 95, 95, 95s
 zener, 447, 529
 VI plot, 83g
 2-stage protection, 85, 86
 bidirectional, 525, 526
 BJT as, 85, 86g
 capacitance, 84, 529
 input protection, 84, 527, 529
 TVS, **527**, 529
 zero-voltage dynamic impedance, 83, 83g
- discharge
 of high-voltage supply, 481, 481, 481s
- displacement, *see* sensor
- distance, *see* sensor
- distortion
 crossover, 414
 in BJT amplifiers, **113ff**
- DMM, 389, 390
- duolateral, 63
- dynode, 626
- Early effect, 101r, 106, 127g, **127ff**, 128g, 187, 188, 197
 and cascode, 111, 112
 configurations that avoid, 101r
 feedback factor, 128
 formulas, 128
 measuring, 127
 MOSFET analog, 209
- Earth
 quietest place on, 580
- EEpot, 31, 32, 33t
 parameters, **31**
- electro-optic shutter, 263

- electromagnetic
 - conversion factors, 49t
 - electromagnetic interference (EMI), 344
 - EMF
 - back, 49, 460
 - emitter
 - degeneration, 101–103r
 - emitter follower, 102r
 - inductive output, **153**, 153s, 154
 - oscillations in, 143, **143ff**, 143s
 - output impedance, **153**, 153s, 154
 - EnergyStar, 469, 471
 - Ethernet
 - power over, 582
 - eye diagram, 363s

 - fan
 - brushless, 516, 517s
 - ceiling, 498
 - ramp-up, 459s
 - Faraday cage, 14
 - Faraday's law, 49
 - feedback, 104r
 - PID, 595
 - motor control, 460
 - stability, 296, **296ff**
 - ferrite
 - bead, 143, 143, 517
 - cores, 491p
 - ferromagnetic, 53
 - FET
 - avalanche, 198, 198g
 - drain characteristics, 193, 193, 194g
 - enhancement and depletion, 170r
 - gate current, 171r
 - linear region, 171r
 - operating regions, 170r
 - output resistance
 - variation, 197g
 - polarities, 170r
 - resistive region, 193
 - saturation region, 170r, 193
 - FET (cont.)
 - subthreshold region, 171r, 194g, **195ff**, 196g
 - switch, 171r
 - threshold voltage (V_{th}), 194g, 196, 196g, 199g
 - transconductance (g_m), 170r
 - transfer characteristics, 194g, 196g
 - triode region, 193, 194
 - FFT, 437, 441n
 - from time series, **440**
 - filter
 - active
 - lowpass, 314, 314g
 - bandpass, 490
 - Bessel, 301
 - Bode plot, 302s, 303g, **301–306**
 - Bode shootout, 301
 - Butterworth
 - poles of, 70
 - Chebyshev, 301
 - elliptic, 301
 - frequency response, 304s
 - linear frequency sweep, 302s
 - log frequency sweep, 301s
 - phase response, 303g
 - phase wrap, 302s
 - power-supply, 445r
 - RC highpass, 3r
 - RC lowpass, 3r
 - step response, 303s
 - stopband ripple, 302s
 - Fletcher–Munson curves, 572g
 - frequency
 - comb, 90, 91s
 - complex, 68
 - fretting, 21
 - FTIR, 638
 - fuse, 445r
 - thermal, 528
 - galvo–mirror, 624
 - gas discharge tube, 389
 - GDT, 525, 526, **526**, 526p, 529
 - geophone, 583, 584p
 - damping resistor, 584n
 - spectra from, 584g
 - germanium
 - IR lens, 626
 - gimmick, 47
 - Guinness
 - record (not beer), 580
 - Gummel plot, 101r, 141, 142g

 - H-bridge, 595
 - half bridge, 284
 - Hanna curve, 59
 - harmonic
 - comb, 91s
 - harmonic current, 472
 - heat, 447r
 - heatsink, 447r
 - Helmholtz coil, 15, 16p, 280
 - high-voltage
 - amplifier, 198, 410, 411s
 - Bode plot, 414g
 - precision, **404ff**, 405, **412ff**
 - stability, 413
 - circuits and cascode, 111
 - creepage, 486
 - current source, **421**, **422ff**
 - 2-terminal, 422
 - low noise, **416**, 417s
 - monitor, 260, 262
 - pulse generator, 257, 259
 - bipolarity, 262, 263
 - reversible, 260
 - ramp, 278, 278
 - step-and-hold, 416, **416**, 417s
 - switch, 415, **415**
- hole
 - rabbit, 557n, 610
- honeycomb, 63
- Howland
 - bootstrapped current source, **418**, 418–419, 419–420s
 - HV current source, **418**
- humidity, *see* sensor
 - absolute vs relative, 604g
- humidity sensor, 603p, **603–605**
- hygrometer
 - capacitive, 603, 604
 - deformation, 603
 - fiber Bragg grating, 605
 - hair, 603n
 - optical, 605

- hygrometer (cont.)
 piezoelectric, 603n
 resistive, 603n, 604
 curves, 605g
- hysteresis
 magnetic, 53, 54s
- IGBT (insulated-gate bipolar transistor), 173r, 269, 280, 280, 281, 282p
 fault protection, 269
 linear applications, 271, 271T
 transconductance, 272g
 transfer characteristics, 271, 272g
 vs BJT, 271
 vs MOSFET, 269t, 532
- image intensifier, 630, 631
- impedance, 2r
 loading effect of, 3r
 motional, 579n
 negative, 460
 of PCB transmission line, 7
- inductance, 10ff
 formulas, 10
 leakage, 465t
 spike, 464, 464, 465s, 484, 516
 mutual, 50
 of resistor, 23, **23**, 24, 25g
 of wire, 10, 10g
 PCB, 7, 8g
 scaling, 50
 self, 50
- inductive
 transient
 TVS suppressor, 530, 531
- inductor, 2r, **49ff**, 491p
 N-turn loop, 52
 air core, **49**
 coefficient, 51g
 copper loss, 57
 core
 thermal resistance, 58g
 core loss, 54, 57, 57g, 460
 core materials, 52
 core size
 nomogram, 62
 examples, **62**
- inductor (cont.)
 for switching converters, 63
 gapped core, 58, **58**, 59, 60g, 60t
 lossy, 61, 61s
 magnetic-core, 52
 RF choke, **62ff**, 64, 65p, 66g
 saturation, 56, 138, 138g, **138**, 139
 shortcuts, **56**
 solenoid, 50
 air-core, 50
 ferrite core, 55g, **55**, 55p, 56g
 inductance of, 50
 square-loop, 61, 61s
 stored energy, 446r
 TVS suppressor, 530, 531
 tapered, 66p
 toroid, 52, **52**
 ferrite core, **55**
 transient isolator, 261
 tunable, 60
 types, 50p
 Wheeler's formula, 51
- inductors
 for power converters, 61
- infrared
 optics materials, 626
- input
 protection, 228, 229, 230s, 315, **389ff**, 390
- instrumentation amplifier, 290r
 autozero, 478
- integrator
 reset, 290r, 315
 windup, 414
- interface
 weird, 559n
- JFET (junction field-effect transistor), **174ff**, 175t
 $G_{\max}$, **188ff**, 191, 191
 R_{ON} , 177
 V_{GS} spread, 176, 177g
 amplifier
 biasing, 171r
 common-source, **188ff**, 189, 190t, 221
- JFET amplifier (cont.)
 low-noise, 191, 192
 vs switch, 177
 bandwidth, 222t
 capacitance, 178, 180t, 222t
 cascode, 186, 187, 188, 189, 190t
 dual, 178
 families, 174
 gain
 maximum, **188ff**, 189g, 190t
 gate current, 105g, **105**, **179**, 180g, 180t, 326
 gate leakage, 331
 impact-ionization current, 179, 180g
 proportional to drain current, 179, 180g
 manufacturing spread, 332
 output resistance, 188g, **188ff**, 189, 189g, 190, 190g, 190t, 191, 191
 packages, 174, 174
 parameter interaction, 177g
 pinch-off voltage, V_p , 176
 source degeneration, 189, 189
 source follower, 185
 switch, 171r
 vs amplifier, 177
 transconductance, **182ff**, 189, 222t
 enhancer, 183, 184t, 185, 191, 192
 equations, 182
 maximum gain, 178
 measuring, 187, **187**
 of source follower, 185, 186
 vs BJT, 182, 182
 vs drain current, **182**, 183, 184g
 vs drain voltage, **183**, 184g
 within a family, 177, 178g
 transfer characteristics, 176, 177g
- Johnson noise, 516
- Kelvin connection, 139

- kickstart, 470
- Kirchhoff's laws, 2r, 432
 - nodal analysis, **431ff**, 432
- laser diode, 521, 522g, 522p
- lattice-wound, 63
- LC*
 - resonant circuit, 3r
 - series, 490, 491
- leading-edge detector, 97, 97
- LED
 - VI* plot, 83g
 - chip-on-board (COB), 523, 523p, 524g, 524p
 - forward drop, 82g
 - infrared, 639
 - pulser, 274, **274ff**, 275, 276
- level shifter, 406
- light, *see* sensor
 - breaking the speed limit of, 634
- light sensor, **606–640**
- linear
 - circuit, 2r
- litz wire, *see also* wire, *see* wire, 12
- LNB, 64
- load
 - capacitive, 407, 408, 408, 408g
 - op-amp, **401ff**, 402g, 402s
- load cell, 553p, 554, 554p, 555p, **551–560**
 - circuit, 558, 560
- loading, 3r
- lock-in, 618
- logic
 - CMOS, 172r
 - linear amplifier, 232g, **232ff**, 233, 233g
 - oscillator, 233
 - transfer characteristics, 232g
 - unbuffered, 232, 232g
 - isolator, 261
 - parasitic coupling, 13s
 - timing skew, 9, 9
 - wired-OR, 478
- Lorenz attractor, **393**, 394, 394s
- loss
 - switching, 460, 470
- LSST, 632
- Lumen, 519
- luminous efficiency, 519g, 520T
- magnet
 - fast shutoff, 280, 280, 282, 283p
 - fast-switching, 530, 531
 - transient suppression, 530, 531
- magnetic
 - core
 - gapped, 58, **58**, 59, 60g, 60t
 - thermal resistance, 58g
 - wire capacity, 58g
 - core loss, 54, 57, 57g, 460
 - domain, 53, 54
 - hysteresis, 53, 54s
- Mandelbrot set, 393
- Marx generator, 499, 500
- Maxwell's equations, 52, 55n
- MEMS, 561n
- microchannel plate, 630, 631
- microphone, *see* sensor, *see also* sensor, **571–583**
 - condenser, 578p
 - amplifier, 580
 - binaural, 578
 - capacitor, 572
 - condenser, 578p
 - frequency response, 575g
 - connector, 580
 - dynamic, 572
 - frequency response, 575g
 - electret, 580, 581
 - frequency response, 575g
 - measurement, 574
 - MEMS, 574
 - noise floor, 579
 - phantom power, 581, 582, 583
 - placement, 582, 583
 - response, 580g
 - response pattern, 576, 576, 577g
 - selectable, 577p
 - ribbon, 573
- microphone (cont.)
 - sensitivity, 579
 - shotgun, 577
 - SNR scatterplot, 574
 - stereo, 577
- microphone placement, 583
- microstrip, 8
 - impedance, 8g
- Miller effect, 104r, 134, 145, 149, 164, 192, 241, 248, 250
 - and cascode, 111, 112
- modulator
 - acousto-optic, 541
- modulus
 - of elasticity, 551
 - Young's, 551
- Monticelli output circuit, 375, **375**, 376g
 - SPICE simulation, **375**
- MOSFET
 - R_{ON} vs temperature, 268g, **268ff**
 - R_{ON} vs voltage, 235
 - at high voltage, 197
 - at low voltage, 196
 - avalanche, 198, 198g
 - avalanche rated, 198, 252, 253, 253
 - bandwidth, 222
 - capacitance, 201g, 222, 521
 - choosing, 237
 - current source, 431
 - enhancement-mode, 217
 - nodal analysis, **431ff**, 432
 - depletion-mode, 173r, 246, 266
 - as bias source, 218
 - as current source, 206, **206ff**, 207, 207g, 209, 209, 209g, 419, 419
 - extending voltage of, 210, **210ff**, 211, 212g, 214–216g
 - high-voltage current source, 210, **210ff**, 211, 212g, 214–216g, 217
 - HV discharge, 481, 481, 481s

MOSFET, depletion-mode (cont.)

programmed current source, 209, 209
 SMPS startup, 470
 transfer characteristics, 215g
 die size, 235
 drain characteristics, 193, 193, 194g, 251g
 E-HEMT, 246
 extending voltage of, 210, **210ff**, 211, 212g, 214–216g
 feedback factor, 209
 figure of merit, 236, 236t
 flying, 257, 259, 261, 477
 gallium nitride, 237, 242g, 270
 gate charge
 depends on I_{load} , 248
 depends on V_{drain} , 249
 measuring, 248
 test circuit, 249, 250
 gate driver, 255, 255, 256T, 261, 264, 478
 explosion, 260
 half-bridge, 257, 258, 259, 263T
 high-side, 257
 high-voltage, 198, 200T, 413t
 transconductance, 200T
 history, **234ff**
 inductive load, 253
 IRF-series, **234ff**, 234t, 273
 IRFZ-series, 235, 235t
 lateral, 246, 271, 272
 tempco, 271
 transconductance, 272g
 transfer characteristics, 271, 272g
 leakage, 285n
 linear applications, **193ff**, 271, 271T, 435
 low-voltage, 204, 204, 205g
 maximum current, 172r, 235, 235t
 maximum ratings, 172r

MOSFET (cont.)

output characteristics, 193, 193, 194g, 251g
 output resistance
 variation, 197g
 paralleling, 195
 pass transistor, 515
 pentode region, 194
 pHEMT, 246
 power
 gate charge, 172r, 248, 249s, 251g, 251s, 257
 gate charge datasheet errors, 250
 linear applications, 271, 271T
 paralleling, 173r
 silicon carbide, 477
 switch, 172r
 transient, 252g, **252ff**, 254g
 pulse energy, 252g, **252ff**, 254g
 pulsed current source, 435
 resistive region, 193
 RF, 246
 $R_{DS(ON)}$, 172r
 saturation region, 193
 series string of, 210, **210ff**, 211, 212g, 214–216g, 231
 shrink, **236**
 in linear amplifier, 237, 273
 silicon carbide, 237, 242g, 261, 261s, 270, 477, 477n
 die size, 260g
 gate driver, 270
 SOA, 195, 195g
 source follower, 228, 229
 bootstrapped, 228, 229, 230s
 capacitive load, 224, **224ff**, 225g, 226, 226g
 SPICE models, 199g, **199ff**, 201, 202, **202ff**, 202n, 203, 204
 capacitances, 203
 circuit, 202

MOSFET (cont.)

Spirito effect, 195, 195g
 substitute for BJT, 140
 subthreshold region, 194g, **195ff**, 196g, 198, 199, 204, 205g, 209
 super-junction, 204, 237, 238, 242g, 266g
 die size, 260g
 superjunction, 266
 switch
 bidirectional, 262
 threshold voltage (V_{th}), 194g, 196, 196g, 199g
 selectable, 204, 204g
 transconductance, 199, 200T, 201g, 272g
 vs BJT, 199, 199–201g
 transfer characteristics, 194g, 196g, 199g, 271, 272g
 transient thermal resistance, 252, 252g, 254g
 triode region, 193, 194
 turn-off delay, 258n
 vertical, **234ff**, 236, 236
 vs BJT, 271
 vs IGBT, 269t, 532
 zero-threshold, 204, 204, 205g
 motor
 drive, 462, 462g
 model, 461, **461**
 op-amp analogy, 462, 462, 463
 rheostat controller, 462, 462g
 motor driver
 PWM, **457ff**, 458, 458s
 motor-generator, 459s
 MOV
 vs TVS, 528
 NDIR, 638, 640p
 network analyzer
 on a chip, 304
 NEXT, 13t
 nodal analysis, **431ff**, 432
 node
 equations, 432
 noise
 brushless fan, 516, 517s

noise (cont.)

- canceler, 396
- common-mode, 487, 488, 492
- equivalent bandwidth, 437
- faulty SPICE model, 125
- Johnson, 579, 584
- pink, 439
- power density, 437
- power supply, 487, **487ff**, 488s, 490s, 490T, 491s, 492, 495, 517s
- spectral density, 437
- suppression, 61, 61s, 492, 495
 - faulty, 125
- unit conversions, 437
- units, 437
- white, 439

Noise equivalent power (NEP), 614

Norton equivalent circuit, 3r

octave

- spectral analysis, 437

op-amp

- active clamp, 291r
- active rectifier, 291r
- bandwidth, 292r, 342, 342g
- basic circuits, 290r
- bias canceled, 343g, **368ff**, 369, 370
 - current noise, 371
- BJT, 292
 - input current, 292
- Bode plot, 292r
- capacitive load, 336, 387, **401ff**, 402g, 402s
 - frequency of oscillation, 401
- cautions, 291r
- charge dispenser, 286, 287
- CMOS, 292r
 - input current, 292r
- common-mode input range, 292r
- compensation, 292r
- current feedback, 156, 156s, 159, 340, **340**, **341**, **352ff**, 353, 356, 358T, 388

op-amp, current feedback (cont.)

- applications, 356
- bandwidth, 352, 354g, 357
- Bode plot, 156g
- cautions, 354
- input capacitance, 355g
- input current, 353
- modeling, 356
- output current, 352
- output swing, 359
- precision, 353
- slew rate, 352, 366
- stability, 352, 354, 355g, 355s, 355t

current source, 431

MOSFET, 431

decoupled, 314

departure from ideal, 291r

difference amplifier, 290r

differentiator, 290r

discrete, 295, 295p

distortion, 344

electrometer, 292r

follower, 290r

full-power bandwidth, 342

gain, 292r

gain–bandwidth product, 342
 vs quiescent current, 344, 345g

golden rules, 290r

high-speed, 299, **340ff**, 348–351T, **352ff**, 358T

history, **294ff**

ideal, 290r

inductive output, **401ff**, 402g, 402s

input current, 291r, 343, 345, **368ff**, 368t, 369, 370

vs GBW, 346g

vs slew rate, 346g

input protection, 228, 229, 230s, **389ff**, 390

integrator, 290r

inverting amplifier, 290r

noise, 291r, 343, 346, 368t

vs quiescent current, 346g

noninverting amplifier, 290r

nonlinear circuits, 291r

offset voltage, 291r, 335, 368t

op-amp (cont.)

- offset voltage drift, 291r
- output current, 292r, 344
 - limiting, 387, **387ff**, 387s, 388
- output impedance, 292r, 376g
- output impedance vs frequency, **401ff**, 402g, 402s
- output swing, 292r
- peak detector, 291r
- phase shift, 292r
- PSRR, 360, 360g, **360ff**, 361, 361g
- quiescent current, 343
- rail-to-rail, 291, 292r, **372ff**
 - distortion, **375ff**, 376g
 - input crossover, 372g
 - output crossover, **375ff**, 376g
 - output impedance, 372
 - output linearity, **375ff**
 - output saturation, 330, **372ff**, 373g, 374s, 375
 - when it isn't, **372ff**, 373g, 374s
- resistorless gain stage, 382, **382**, 382s, 383g, 383s
- sample-and-hold, 291r
- settling time, 346, **378ff**, 378, 379s, 379t, 380s
 - vs f_T , 378
 - vs GBW, 347g
 - vs output step, 379, 379g
 - vs slew rate, 347g
- single-supply, 291r
- slew rate, 292r, 345, **364ff**, **378ff**, 378, 379s, 379t, 380s
- Butler circuit, 365, 366
- CFB, 366
- cross-coupled input stage, 366
- enhanced, **379**
- increasing, 364
- transconductance reduction, 365
- vs f_T , 378

- op-amp, slew rate (cont.)
 - vs GBW, 346g, 364, 364, 365t
 - vs input error, 365g, 367g
 - vs quiescent current, 345g
- SPICE model, 297, 299
 - frequency response, 299g
 - step response, 300g
- split feedback, 261
- vacuum tube, 294, 294p
- VFB+CFB, 355
- voltage feedback, 340, **340ff**, 348–351T, 356
 - bandwidth, 354g
- optical
 - conversion factors, 520
 - power, 519
 - power transmission, **521ff**, 522g, 522p, 524g, 524p
 - units, 519
- optical sensor, **606–640**
- optocoupler
 - for isolated feedback, 470, 483
 - linearity, 610g
 - photoconductive, 609T
- optoelectronics
 - detectors, **606–640**
 - optocoupler
 - linearity, 610g
 - photoconductor, 609T
 - photoconductor, 608p, **606–611**
 - infrared, 610, 611g
 - linearity, 607, 610g
 - resistance vs illumination, 607g
 - spectral response, 607g
 - speed, 608g, 609, 610s
 - streetlight circuit, 608
 - tempco, 609g
 - photodiode, 522g, 522p
 - photomultiplier
 - silicon, 508
 - photovoltaic stack, 415, 521, 522, 524g, 524p
- ORTF, 577
- oscillator, 291r, 446r
 - blocking, 483
- oscillator, blocking (cont.)
 - CMOS, 233
 - phase-shift, 489, 489
 - sinewave
 - Wien bridge, 41
 - trapezoidal, 490
 - triangle, 490
 - Wien bridge, 607
- oscilloscope
 - overdrive artifacts, **379**, 380, 381s
 - probe
 - opto-fiber isolated, 522, 522p, 523
- output
 - decoupling, 414
- overtemperature
 - shutdown, 484
- overvoltage
 - shutdown, 448r
- parallel
 - impedances, 3r
- paramagnetic, 53
- patents, 570n
- PCB
 - capacitance, 7, 8g
 - inductance, 8g
 - maximum current, 7, 7g
 - meandering trace, 9
 - parasitic coupling, 12
 - traces, **6**
- PCB transmission line
 - attenuation, 7
 - characteristic impedance, 7
 - geometries, 8
 - impedance, 8g, 9t
- peak detector
 - eliminating diode leakage in, 400, 400
- peaking, 165
 - vs phase margin, 298g
- permeability, 49, 53
 - effective, 58, 58, 59, 60g
- PET scan, 623
- phase detector, 304
- phase margin, **296ff**, 297g, **297**, 298g, 407
- photoconductor, *see also* sensor; light, 608p, **606–611**
- photoconductor (cont.)
 - infrared, 610
 - wavelength tuning, 611g
 - linearity, 607, 610g
 - resistance vs illumination, 607g
 - spectral response, 607g
 - speed, 608g, 609, 610s
 - streetlight circuit, 608
 - tempco, 609g
- photodiode, *see also* sensor; light, 612p, 616p, 616T, **611–625**, 630p
- e_nC noise, 617
 - avalanche, 384, **384**, 385, 618
 - excess noise, 619n, 620g
 - gain stabilized, 619n, 620g
 - gain vs bias, 619g
 - gain vs temp, 619g
 - gain vs total noise, 620g
 - hybrid, 621, 622
 - InGaAs, 620
 - speed, 619
- biased, 308
- capacitance vs bias, 613g
- cooling, 615
- current linearity, 613g
- figure of merit, 611
- germanium, 617
- HgCdTe, 617
- infrared, 617
- InGaAs, 617
- IR
 - spectral response, 614g
- lateral-effect, 624
- leakage, 615
- LiTaO₃, 617
- lock-in detection with, 618
- noise, 614
- position sensitive, 624
- segmented, 624
- shunt resistance, 613g, 615, 615g
- silicon, **616–617**
- solar cell, 617
- voltage nonlinearity, 613g
- zero bias, 617

- photometer
 starlight-to-sunlight, **327ff**,
 331, 331g
- photometric units, 519
- photomultiplier, **626**, *see also* sensor; light, 630p
- base, 628
- configuration, 627p
- dark count, 627, 629g
- dark current, 627
- giant, 628p
- pulse shape, 629s
- quantum efficiency, 627g
- silicon, **384ff**, 384p, 385,
 385g, 386s, 622
- size and shape, 627
- spectral response, 627g
- speed, 627, 629s
- photon sensor, **606–640**
- phototransistor, 611, *see also* sensor; light
- piezo
 charge-dispensing driver,
 284ff, 285, 286
- nonlinearity, 284g
- piezoresistivity, 551, 561
- PIN diode, *see also* sensor; photo-
 diode, 612p, 616p
- PMT
 dark count
 compared with SiPM, 623
- PoE, 582
- Poisson ratio, 551n
- pole, 3r
 dominant, 314
- pair, 224
- pole-zero
 network, 69, 69
- poles and zeros, **68ff**, 69
 of Butterworth filter, 70
- potentiometer
 digital, 31, 32, 33t
- parameters, **31**
- gang matching, 34
- nonlinearity, 35
- taper, 33, 158
- tempco, 35
- volatility, 32
- power
 converter, 494p
- power (cont.)
 entry module, 445r
- factor
 correction in offline
 SMPS, 445r, **472ff**,
 472s, 473
- in offline SMPS, 445r
- linear, 472
- in resistor, 26, 29g
- on a beam of light, **521ff**,
 522p, 524g, 524p
- optical, **519**
- phantom, 581, 582, 583
- spectrum, 488s, 490s
- transient, **26**, 29g
- transistor
 mounting, 167
- power supply
 Apple charger, 483p, 485
- common-mode noise, 487,
 487ff, 488s, 490s, 490T,
 491s, 492, 492s, 494s,
 495
- counterfeit, **482ff**, 482p,
 482s, 483p, 483s, 484
- crowbar, **466**, 467
- current limit
 foldback, 455, 455, 456
- efficient, 469, **469**
- high-voltage
 discharge circuit, 481,
 481, 481s
- inexpensive, 495
- laboratory, 513, **513ff**, 514,
 515p, 517s
- low-noise, 513, **513ff**, 514,
 515p, 517s
- negative, 508, 509
- low-voltage, 453, **453**, 453s,
 454
- negative, 510, 510
- noise, 492, 495, 517s
- offline
 non-isolated, 497, 497,
 497s, 498, 498s, 499,
 500
- output impedance, 517
- ripple voltage, 470, 482, 482,
 483s
- safety, **482ff**
- power supply (cont.)
 split, 502
- splitter, 336, 337
- stability, 517
- switchmode, 492, 495
- efficient, 469, **469**
- noise, **492**, 492s, 494s,
 495, 495s, 496, 496s
- noise test circuit, 493
- ultra-isolated, 487, **487ff**,
 489
- unregulated, 445r, 515
- powerline
 transients, 525g
- pressure, *see* sensor
- unit conversion, 562T
- units, **561**
- pressure sensor, 559, 560, **561**
- probe
 active, 134, **228ff**
- high impedance, **228ff**
- high-voltage, **228ff**
- scope, 260
- protection
 reverse polarity, 449, **449**
- PSACRF, 13t
- PSNEXT, 13t
- pulse
 generator, **155**, 155p, 160s,
 161p, 161s
- adjustable rise/fall, **155**
- bipolarity, 262, 263
- cable, **263**, 264, 264, 265p,
 266s
- fast, 163, **163ff**, 164, 165,
 166s
- high-voltage, 91, 92s, 257,
 257ff, 259, 261, 261s,
 262, 263, 366, 366s,
 367
- HV, **263**, 264, 264, 265p,
 266s
- monitor, 260, 262
- offset circuit, 158
- output stage, 158, 159
- overcurrent limit, 477, **477**
- overshoot, 166s
- reversible, 260, 262
- step response, 165, 166s
- transition control, 155

- pulse, generator (cont.)
 waveform generation, 156
 waveform generator, 157
 integrity, **19**
 reflection, 19, 20s
 standard test, 526, **532**, 533g
 pulse oximeter, 637g, 637p, **635–637**, 638, 639p
 spectral absorption, 636g
 push-pull
 BJT output stage, 103r, 273
 MOSFET output stage, 273
 shoot-through, 266
 PWM, 445r
 motor drive, **457ff**, 458, 458s
 ripple reduction in, 428, **428**, 429s, 430
 sensitivity, 430g
 settling time, **428**, 429s
 pyroelectric, *see* sensor, light
- rabbit hole, 557n, 610
 radiometer, 521, 521p
 ramp
 generator, 158
 high-voltage, 278, 278
 RC circuit, 68
 poles and zeros, 69
 rectifier
 active, 291r
 bridge, 445r
 leakage, 81g
 recovery spike, 464, 464, 465s, 484, 516
 synchronous, 291r
 reference
 design, 484
 relay, **71ff**, 72, 73p
 ac coil, 77
 advantages, 71
 arcing, 72
 coax, 74p
 coil suppression, **74**, 75, 76s, 77, 77t
 contact erosion, 75
 contact protection, **72**
 contactor, 282
 disadvantages, 71
 dry-switching, 71
 kickstart, 77, 78, 78s
- relay (cont.)
 lifetime, 71
 mechanical, 72, 73p
 mercury-wetted, 72p
 overdriving, 77, 78, 78s
 parameters, 78
 reed, 72p, 79, 159
 life expectancy, 159
 RF, 73p
 time-delay, 74p
 timing, 76s, 77, 77t, 78s
- resistance
 negative, 93, 460
 2-terminal, 151, 151, 151g, **151**, 152g
 sheet, 7
 temperature sensor (RTD), **592**, 594g
- resistor, 2r, **23ff**
 4-wire, *see also* resistor, Kelvin, **26**, 27, 28p
 Ayrton–Perry, 24
 current-sensing, 478
 dead, 31p
 departure from ideal, **23ff**
 digital, **31**, 32, 33t
 cautions, 35
 frequency response, 34g
 gang matching, 34
 log approximation, 34g
 parameters, **31**
 tempco, 35
 volatility, 32
 wiper resistance, 35, 35
- divider, **29**
 exploding, 528
 Kelvin, **26**, 27, 28p
 noise, 25
 non-inductive, 266, 266p
 nonlinearity, **24ff**, 26g, 35
 power
 derating, 27
 precision, 23, **29**
 self capacitance, **23**
 self inductance, **23**, 24, 25g, 266
 canceling network, 266
 tempco, 23, 592
 testing to failure, 27, 29, 30, 31p, 32s
- resistor (cont.)
 transient power, **26ff**, 29g
 voltage coefficient, **24ff**, 26g
 wirewound, 24, 25g
- RF
 choke, **62ff**, 64, 65p, 66g
 bank-winding, 65
 driving cable, 337, 337
- ripple, 445r
 PWM
 reduction, 428, **428**, 429s, 430, 430g
- roll-your-own, 544n
 root locus, 68n
 RTD, 93, **592**, 594g
 RTG, 596
- s-plane, **68ff**, 69, 224
 visualizing, 70
- safe operating area (SOA), 168g, 448r, 511, 511g
- saturation
 current vs voltage, 194
 of magnetic core, 56
 voltage vs current, 194
- Schmitt trigger, 102r, 291r
 SCR, 269, 389, 466
 second breakdown, 272, 448r
 Seebeck effect, 595, 595g
 seismometer, 585
 sensor, **535**
 accelerometer, *see also* accelerometer
 barometric pressure, 594
 CCD, 630
 CMOS
 lens, 633
 CMOS imager, 630, 632p
 CO₂, 638
 displacement, 536T
 distance, 536T
 ~meter-scale, 548
 capacitive, 537, 537, 538
 confocal chromatic, 540, 540
 displacement, **537–550**
 distance, **537–550**
 fiber Bragg grating, 541
 Hall-sensor, 547, 547, 547g, 547n

sensor, distance (cont.)

- inductive, 538
 - interferometry, 539, 539, 540
 - laser doppler vibrometry, 540, 541, 542, 543p
 - laser ranging, 548, 549p, 550s
 - laser triangulation, 538, 539
 - linear potentiometer, 547
 - LVDT, 542, 543–545
 - magnetostrictive, 546, 546
 - patterned inductive, 544, 545
 - patterned magnetic, 545
 - patterned optical, 545, 546
 - RF, 548, 548
 - ultrasonic, 538, 538
- geophone, 583
- humidity, 594, 603p, **603–605**
- fiber Bragg grating, 605
- imaging
- CCD, 630
 - CMOS, 630, 632p
 - infrared, 626, 626g
 - visible light, 630, 632p
- infrared
- long wavelength, 625
 - medium wavelength, 638, 639g
 - non-dispersive, 639
- light, 536T, 630p, 632p, **606–640**
- D^* (D-star), 615
 - APD, 618, 619, 620g
 - bolometer, 625
 - capacitance vs bias, 613g
 - cooling, 615
 - current linearity, 613g
 - figure of merit, 611
 - Geiger mode, 620
 - giant photomultiplier, 628p
 - hybrid avalanche detector, 621, 622
 - IR photoconductor, 610, 611g
 - IR photodiode, 617

sensor, light (cont.)

- IR SPAD, 621
 - IR spectral response, 614g
 - long-wavelength IR, 625
 - MPPC, 622, 630p
 - NEP, 614
 - noise, 614
 - photoconductor, 608p, **606–611**
 - photodiode, 612p, 616p, 616T, **611–625**
 - photomultiplier (PMT), **626**, *see also* photomultiplier
 - phototransistor, 611, 618
 - position sensitive, 624
 - pulse oximeter, **635–637**
 - pyroelectric, 625
 - responsivity, 613
 - shunt resistance, 613g
 - single-photon avalanche, 620
 - SPAD, 620
 - SPAD array, 621
 - streaktube *see* streaktube
 - thermal, 625
 - thermopile, 625
 - voltage nonlinearity, 613g
 - with gain, 618
- location, **537**
- microphone, *see also* microphone, **571–583**
- ORTF, 577
- optical, **606–640**
- passive IR, 625
 - photodiode, 630p
 - photon, **606–640**
- pressure, 536T, 559, 560, **561**
- absolute, 560–562
 - capacitive, 561, 562, 562p, 563
 - differential, 560, 561, 564p
 - gauge, 561
 - manganin, 561, 565
 - MEMS, 561n
 - optical, 561, 565
 - piezoelectric, 561
 - piezoresistive, 563, 565, 565

sensor, pressure (cont.)

- ruby fluorescence, 561, 566, 566g
 - thermal-flow, 561, 564, 565
 - tire monitor, 562, 564
- proximity, 536T
- pulse oximeter, **635–637**
- rotation, 536T
- sections in previous editions, 536T
- seismometer, 585
- sound, 536T, **571–583**
- anechoic chamber, 580p
 - level meters, 574
 - loudness curves, 572g
 - microphone types, 572, 573
 - pressure units, 571, 571
 - SNR scatterplot, 574
- temperature, 536T, **589ff**, 597T
- capacitive, 601g
 - change-of-state, 589
 - crickets, 589
 - cryogenic, **597**, 598g, 599t, 600, 601g
 - cryogenic, GaAs, 598g, 600g
 - effect of leads, 602g
 - finger test, 589
 - FLIR, **590ff**, 590–592p, 597T
 - NTC, 600g
 - PTC, 600g
 - pyrometer, 591, 597T
 - RTD, **592**, 594g, 597T
 - semiconductor, 508
 - silicon, 593, 594g, 597T, 598g, 600g
 - thermal cutout, 590
 - thermistor, **594**, 597T
 - thermocouple, **595**, 596, 596g, 597T, 601g
- vacuum, 561
- Bayard–Alpert, 568
 - Bayard–Alpert, 569, 569p
 - cold-cathode, 570
 - hybrid, 570
 - inverted-magnetron, 570

- sensor, vacuum (cont.)
 ionization, 568, 569, 569p
 MEMS, 567
 Pirani, 566, 567, 567, 568p
 thermocouple, 566, 567, 567p
 vibration, **583–588**
- series
 impedances, 3r
- SETI, 386
- sewing machine, 457
 rheostat controller, 459p
- shielded enclosure, **14ff**, 15, 16p
 attenuation, 15g
 screened, **17**
 test circuit, 16
- shielding, **14ff**
 electrostatic, 488
 field contours, 18
 magnetic, 16g, 16t
 RF, 17, 17p
- signal
 amplitude, 2r
- sinewave
 from square wave, 233, 490, 491
- single-photon avalanche detector (SPAD), *see also* sensor; light
- SiPM, *see also* sensor; light, 630p
 afterpulsing, 623
 vs overvoltage, 624g
 crosstalk, 623
 vs overvoltage, 624
 dark count, 623
 compared with PMT, 623
 vs overvoltage, 624g
 vs temperature, 623g
 gain
 vs overvoltage, 624
- skin depth, 10, 11g, 11p, 12g, 14
- slew rate, 155
 limiter, 161, 162
 of current source, 423
 of high-voltage amplifier, 410
- smoke, 526, 527p
- SMU, 194, 196, 271
- snubber, 281, 464, 469, 484
- solar cell, 617
- solenoid, 50
 air-core, 50
 ferrite core, 55g, **55**, 55p, 56g
 inductance of, 50
- sound, *see* sensor
- sound sensor, **571–583**
- source follower
 bandwidth, 223, 224, **224ff**, 225g, 226, 226g
 capacitive load, 224, **224ff**, 225g, 226, 226g
 gain, 433
- JFET
 output impedance, 185, 186
 transconductance of, 185, 186
- MOSFET, 228, 229, 230s
 bootstrapped, 228, 229, 230s
- resistive load, 433
- transimpedance gain, 226g
- specific detectivity, D^* , 614
- spectral analysis
 from time series, **440**
 third-octave, 437
 bands, 440T
- spectral conversions, **437**, 439T
- spectrum
 from time series, **440**
 third-octave, 439
 vibration, 440
- SPICE, 125
 amplifier analysis, **113ff**
 BJT bandwidth vs current, 147g
 BJT model, 115g, **147**
 MOSFET models, 199g, **199ff**, 201, 202, **202ff**, 202n, 203, 204
 capacitances, 203
 circuit, 202
 op-amp model, 297, 299
 frequency response, 299g
 step response, 300g
 problems with, 114, 124
- Spirito effect, 195, 195g, 272n
- square wave
 from sine, 233
- square-loop
 B-H curve, 54s
- SSR, 79
- Stanford Research Systems
 excellent manuals, 570n
- STB (set-top box), 64
- step
 response, 297g
- step response
 vs phase margin, 298g
- strain, *see* sensor, 551
 apparent, 554
- strain gauge, 552p, 553p, 555g, **559, 551–560**
 bonding, 558, 559
 calibration, 558
 factor, 555
 fatigue, 557
 hysteresis, 557
 lead-wire compensation, 557
 maximum elongation, 557
 minimum radius of curvature, 557
 optical, 558
 quartz, 558
 residual strain, 555g
 self heating, 557
 semiconductor, 558
 transverse sensitivity, 556
 wiring, 556
 wrinkles, 556
- streak tube, 634, *see also* sensors, invention, 635
 speed, 634
- stress
 compressive, 551
 tensile, 551
- stripline, 8
- summing junction, 290r
- Super Kamiokande, 623n
- swarf, 547n
- switch
 analog, 79
 arcing, 72
 choices, 75
 contact protection, **72**
 dry-switching, 71

- switch (cont.)
 high-side, 415, **415**, 475, **475**, 476T
 high-voltage, 415, **415**
 lifetime, 71
 mechanical, 71ff
 parameters, 78
 thermal cutout, 590
- switching
 hard, 264
 loss, 248
- switchmode (SMPS), 445r
 boost, 446r, 502
 bridge converter, 446r
 buck, 446r, 502
 buck–boost, 446r
 burst mode, 470
 bus converter, **502**, 503, 504, 505p
 isolated, 505, 505
 common-mode noise, 492, 492s, 494s, 495, 495s, 496, 496s
 test circuit, 493
 continuous-conduction mode, 471
 Ćuk, 446r
 current pulsation, 504
 current-mode, 447r
 pros and cons, 447r
 efficiency, 469, **469**, 471g
 flyback, 446r, 483
 forward converter, 446r
 hysteretic, 446r
 inductor selection, 63
 inductorless, 445r
 inverting, 446r
 isolated, 446r
 kickstart, 470
 multiphase, 504, 505p
 negative output, 506, **506**, 507
 PWM, 446r
 regulation, 446r
 ripple, 470
 SEPIC, 446r
 topologies, 446r
 voltage-mode, 447r
- temperature, *see* sensor
- temperature coefficient
 BJT leakage current, 105
 FET gate current, 105
 offset voltage, 291r
- temperature compensation
 bandgap reference, 447r
- termination
 back, 263
 series, 263
- Thévenin equivalent circuit, 3r
- thermal
 capacity, 534
 thermal emissivity, 591
 thermal resistance, 167, 447r
 pathetic, 212
 transient, **26**, 29g, 84g, 448r, 533g, **533**, 534g
 thermal scar, 591p
 thermistor, **594**
 thermocouple, **595**, 596, 596g
 thermoelectric cooler, 595
 thermometry, **589ff**
 thermopile, 596
- third-octave
 bands, 440T
 spectral analysis, 437
- thyristor, 269
- toroid
 ferrite core, **55**
- tracking, 486p
- train
 electric, 457
 rheostat controller, 460p
- transformer
 audio, 582, 583
 B-H curve, 54s
 dc, 502, **502**, 503, 504, 505p
 isolated, 505, 505
 in switchmode converter, 445r
 leakage inductance, 465t
 parasitics, 465t
 powerline, 445r
 toroidal, 516
 ultra-isolated, 488
- transient
 edge, 488
 power-on, 516
 protection, 526, 527p
- transient (cont.)
 suppressor, 445r, **525ff**, 526, 526, 527p, 528, 529
 inductive circuit example, 530, 531
 non-sacrificial, 529
 series-mode, 529, 530
 test circuit, **531**, 532
 test pulses, 526, **532**, 533g
 thermal resistance, 198, 252, 252g, 254g, 448r, **525ff**, 533g, **533**, 534g
- transimpedance amplifier, 192, 290r, **315**, *see also* amplifier
 R_f Johnson noise, 315
 R_f capacitance, 321
 $e_n C$ noise, 315, 319
 “RCR” trick, 318g, 319, 321
 and cascode, 111, 112
 autoranging linear, 332, **332**
 Bode plot, 308, 318g, 320g
 capacitive feedback, 362, **362**, 363s
 reset, 362
 comparison, 326
 compensation, 315, 326
 composite, 318, 319, 328p
 Bode plot, 318g, 320g, 325g
 pulse response, 320s
 spectral noise density, 320g, 324g
 step response, 324, 325s
 current ratio, **396**, 397
 damping ratio, 308, 309t
 frequency response, 309g, 309t
 gain-switching, **313**, 314, 333, **333**
 hybrid composite, 321g, 322
 multi-range, 324
 noise filter, 312, 314
 response, 314g
 noise gain, 317
 normalizing, **396**, 397
 photodiode, **312ff**, 313
 response, 313s
 PIN diode, **309**, 310
 post-TIA gain, 315, 316

- transimpedance amplifier (cont.)
 - post-TIA shaper, 321
 - range-switching, 327
 - spectral noise density, 320g, 324g
 - speed, 310
 - stability, **307ff**, 310
 - stabilizing, 308, 309g
 - starlight-to-sunlight, **327ff**, 331, 331g
 - step response, 309g
 - transimpedance gain, 317, 318g
 - wide-range linear, **325ff**, 329, 329, 330g, 332, **332**, 333
 - wideband, **332**, 333, **333**
 - wideband low-noise, 321g, 322
- transistor
 - mounting, 167
 - pass, 445r
 - perfect, 341
 - switch, 101r
- transmission line, *see also* cable
 - characteristic impedance, 19
 - matching, 19
 - PCB, *see also* PCB
 - reflection, 19, 266s
 - termination, 19, 20s
 - back, 257, 263
 - velocity factor, 265
- triac, 269
- trimmer
 - capacitance, 46, 47, 260, 311, 333, 415, 491
 - compensation, 315, 415
 - gain, 382
 - offset, 204, 261, 295, 312, 368, 396, 398
 - pole-zero, 516
 - resistance, 31, 35, 36, 136, 165, 228, 229, 285
- TRRS, 580
- TVS, 525, 526, **526**, **527**, 529
 - circuit example, 530, 531
 - for fast-switching magnet, 530, 531
 - test circuit, **531**, 532
 - vs MOV, 528
- undervoltage
 - lockout, 447r, 478
- varactor, 83, 84, 85g
- varistor, 389, 525, 526, **526**, 527p, 528, 529
- vibration, 440
- vibration sensor, **583–588**
- video
 - differential, 337
 - driver, 337, 337
- voltage, 2r
 - “let-through”, 525
 - arc, 526
 - burden, 425
 - divider, 29, 260
 - high-voltage, 414, 415
 - wideband, 414, 415
 - Early, 127, 127, 128g
 - formulas, 128
 - measuring, 127
 - firing, 526
 - holdover, 526
 - inverter
 - for RRO op-amp, 374, 375
 - protection, **525ff**
 - startup transient, 516
- voltage reference, 446, 447r, 470, 516
 - bandgap, 447r
 - JFET pinchoff, 447r
 - MOSFET floating gate, 447r
 - noise, 125, 447r, 516
 - series, 447r
 - tempco, 447r, 516
 - VI plot, 83g
 - zener, 447r
- voltage regulator
 - 3-terminal, 446r
 - 317-style, 206, 446r
 - current limit
 - foldback, 455, 455, 456
 - dropout, 446r
 - in current source, 206
 - linear, 445r
 - low-dropout (LDO)
 - stability, 446r
 - taxonomy, 445r
- wah-wah pedal, 609
 - circuit, 610
- wall wart, 492
- water
 - dielectric constant of, 604g
- wave
 - ring, 532
- Wheatstone bridge, 556, 561
- Widlar transconductance configuration, 421, 421
- Wien bridge, 607
- window
 - Blackman–Harris, 437, 442
 - DFT function, 437
 - flat-top, 443n
 - Hann, 437, 442
 - parameters, 443T
- windows
 - coefficients, 442
- wire, **5ff**, 6t
 - current in, 5, 5g
 - gauge, 5
 - inductance of, 10, 10g
 - insulation, **5ff**
 - Kynar, 5
 - litz, 5, 12
 - magnet, 5
 - resistance, 5
 - solid, 5
 - stranded, 5, **5**
 - Teflon, 5
 - tinned, 6
- year
 - miraculous, 580n
- zener
 - BJT as, 207n
 - capacitance, 84, 85g, 86, 529
 - low-capacitance, 413
- zero-voltage switching, 484