

Index

- additive white Gaussian noise, *see*
 AWGN
- AGN, 14, 331
- AM–GM inequality, 323
- analysis filter bank, 95
- autocorrelation
 - CWSS, 331
 - estimate, 330
 - function, 329
 - matrix, 329
 - WSS, 329
- AWGN, 14, 18, 331
- bandwidth efficiency, 119
- bandwidth expansion ratio, 99,
 119
- baseband communication, 12, 18
- BER, 19
 - PAM, 19
 - QAM, 24
- BER minimization, 193
- bias removal, 43
- biased estimate, 41, 150
- biased SNR, 41, 206
 - SC-CP, 158
 - ZP-OFDM, 150
- binary phase shift keying (BPSK),
 21
- bit allocation, *see* bit loading
- bit loading, 3, 29
 - gain, 231
 - OFDM, 232
 - SC-CP, 234
 - integer, 30, 174, 235
 - optimal, 229
- bit stream, 1
- bits-to-symbol mapping, 1
- block transceiver, 105
- blocked version, 76
- blocking, 76
 - random process, 334
- C/D converter, 11
 - random process, 337
- carrier frequency offset (CFO),
 179
- carrier modulation, 12
- CFO, 179
- channel capacity, 20
- channel dependence, 4, 135
 - OFDM, 139
 - precoded OFDM, 202
 - SC-CP, 153
- channel diagonalization, 137
- channel equalization, 16
- channel model, 9
 - AGN, 14
 - AWGN, 14
 - continuous-time, 10
 - discrete-time, 10
 - FIR, 14
 - frequency-nonselective, 15
 - iid channel, 16
 - random channel, 15
 - SIMO, 68
- channel noise, 13
 - baseband transmission, 13
 - passband transmission, 13
- channel shortening, 59, 120
- channel spectral null, 144, 156,
 203, 206
- channel state information, 3, 135
- circulant, 108–111, 137, 160
 - definition, 109
 - diagonalization, 111
- circular convolution, 111
- circularly symmetric complex Gaus-
 sian, 13, 136, 328
- complexity
 - OFDM, 138
 - SC-CP, 154
 - SC-ZP, 161

- zero-padded OFDM, 149
- concave function, 325
- congruous zero, 297
 - almost congruous, 305
 - definition, 298
 - minimum-redundancy, 303
- convex function, 325
- crosstalk, 169, 172
- CWSS
 - continuous-time, 337
 - discrete-time, 331
- cyclic prefix, 2, 136
 - OFDM, 139
 - SC-CP, 152
- cyclic-prefixed systems, 115–119
- cyclo wide sense stationary, *see* CWSS
- D/C converter, 10
 - random process, 337
- decimation filter, 79
- decimator, 71
- DFT bank, 164
 - implementation, 266, 277
 - receiver, 277
 - transmitter, 266
- DFT decomposition, 295
- DFT filter, 164, 272
- DFT-based transceiver, 3, 135
- digital modulation, 18
- discrete multitone, *see* DMT
- DMT, 3, 135, 168, 260
 - bit allocation, 174
 - filter bank representation, 169
 - subfilter, 259
 - time domain equalizer, 169
 - tone, 169
 - tone SNR, 174
- downsampler, 71
- DSL, 3, 135, 172
- egress, 259
- equalization, 16
- equalizer, 16
 - linear equalizer, 16
- equivalent discrete-time channel, 12
 - passband, 13
- expander, 71
- exponential power delay profile, 16
- FEQ, 137, 174
- FEXT crosstalk, 172
- filter bank representation, 263
- filter bank transceiver, 5, 95, 291
 - distortion, 100
 - DMT, 169
 - no redundancy, 301
 - OFDM, 163
 - polyphase representation, 90
 - redundant, 97
 - ZP-OFDM, 168
- FIR channel, 14
 - least-squares equalizer, 35
 - MMSE equalizer, 45
 - zero-forcing equalizer, 34
- FIR equalizer, 17, 33
 - MMSE, 45
 - zero-forcing, 34
- FIR transceiver, 291
 - minimal, 301
 - minimum-redundancy, 303
 - solution, 303
- Fischer inequality, 324
- flatness, 233
- fractionally spaced equalizer (FSE), 122, 128
- frequency division multiplexing (FDM), 172, 259
- frequency domain equalizer (FEQ), 3, 137
- frequency-division multiplexing (FDM), 97
- frequency-selective channel, 15
- frequency-shifting property, 164, 263, 266, 272, 276, 277
- Gaussian, 13
 - AGN, 14
 - AWGN, 14
 - circularly symmetric complex, 13
 - real, 13
- Gaussian noise, 13, 328
- guard interval, 2, 147
 - subfilter, 266, 276
- Hadamard inequality, 324

INDEX

357

- IBI, 2, 136, 147
- IIR minimal transceiver, 301
- ingress, 259
- integer bit allocation, 30, 175
- inter subchannel interference, 100
- interblock interference (IBI), 2, 102, 136
- interference, 12
- interpolator, 80
- intersymbol interference, *see* ISI
- intra subchannel interference, 100
- intrablock interference, 2
- ISI, 2, 12, 16, 33
- ISI-free property, 16, 102, 291, 293
- least-squares problem, 35
- linear estimate, 39
 - MMSE, 44
 - multiple random variables, 44
- linear estimator, 39
- lower triangular Toeplitz matrix, 35
- minimal transceiver, 100
- minimum mean squared error, *see* MMSE
- minimum redundancy, 291
- minimum-redundancy
 - congruous zero, 303
- MMSE, 39
 - precoded OFDM, 203
 - SC-ZP, 161
 - zero-padded OFDM, 150
- modulation symbol, 1, 18
- Monte Carlo simulation, 20
- nearest neighbor decision rule, *see* NNDR
- NNDR, 19
 - MMSE equalizer, 56
- noble identity, 75
- Nyquist frequency, 261
- Nyquist(M) filter, 82
- OFDM, 3, 135, 193
 - bandwidth expansion, 139
 - bit error rate, 142
 - channel diagonalization, 139
 - cyclic prefix, 139
 - MMSE, 142
 - oversampling, 188
 - PAPR, 139
- one-shot transmission, 136, 147, 224
- optimal precoder, 207
- orthogonal frequency division multiplexing, *see* OFDM
- orthogonality principle, 39
- PAM, 18
 - BER, 19
 - SER, 19
 - SNR gap, 20
- PAPR
 - definition, 139
 - OFDM, 139
 - SC-CP, 154
- parallel subchannels, 28, 137
- parallel to serial conversion ($P/S(M)$), 77
- passband communication, 12, 18
- peak to average power ratio, *see* PAPR
- phase shift keying (PSK), 26
- pilot, 178
- pilot tone, 178
- polyphase
 - matrix, 135
- polyphase component, 84
- polyphase decomposition, 84, 87
- polyphase identity, 76
- polyphase implementation, 87
- polyphase matrix, 90
 - analysis filter bank, 90
 - synthesis filter bank, 90
- polyphase representation, 90, 292
 - analysis bank, 90
 - synthesis bank, 90
- power delay profile, 16
- power loading, 3
- power spectrum, 330
 - CWSS, 332
 - DMT, 170
 - OFDM, 166
- precoded OFDM, 193
 - MMSE, 203

- zero-forcing, 194
- precoder, 144, 193
- pseudocirculant, 106–108, 293
 - definition, 106
 - determinant, 296
 - properties, 293–295
 - rank, 297
 - Smith form, 308
 - zeros, 296
- PSK, 26
- pulse amplitude modulation, *see* PAM
- Q function, 19
- QAM, 22
 - BER, 24
 - SER, 24
 - SNR gap, 25
- QPSK, 23, 25
- quadrature amplitude modulation, *see* QAM
- quadrature phase shift keying, *see* QPSK
- radio frequency interference, *see* RFI
- random channel, 15
- Rayleigh–Ritz principle, 62, 324
- receiving filter, 260
- receiving pulse, 11
- redundant sample, 2
- redundant transceiver, 97, 100
- RFI, 173, 259
- SC-CP, 5, 135, 152, 193
 - MMSE, 157
 - zero-forcing, 155
- SC-ZP, 153, 160
 - MMSE, 161
 - zero-forcing, 160
- SER, 19
 - PAM, 19
 - QAM, 24
- serial to parallel conversion ($S/P(M)$), 77
- sidelobe, 259, 260
- signal constellations, 18
- signal to interference ratio (SIR), 61
- signal to noise interference ratio, *see* SINR
- signal to noise ratio (SNR), 17
- single-carrier system with cyclic prefix, *see* SC-CP, 152
- single-carrier system with zero padding, *see* SC-ZP
- single-carrier system with zero padding (SC-ZP), 160
- single-input multi-output channel, 68
- singular value decomposition (SVD), 323
- SINR, 17, 62
- SIR, 61
- Smith form, 294
- Smith form decomposition, 294
- SNR, 17
- SNR gap, 20
 - PAM, 20
 - QAM, 25
- spectral leakage, 6, 261, 272
- spectral rolloff, 6
- spectrum mask, 172
- subchannel gain, 137
- subfilter, 259
 - BER performance, 274
 - DFT bank, 266, 277
 - FEQ coefficients, 276
 - ISI-free condition, 263
 - receiver, 276
 - receiver complexity, 278
 - receiver design, 280
 - transmitter, 265
 - transmitter complexity, 271
 - transmitter design, 272
- SVD, 226, 323
- symbol detection, 1, 18
 - MMSE receiver, 56
- symbol error rate, *see* SER
- symbol spaced equalizer (SSE), 122
- symbol-to-bits mapping, 18
- synchronization, 179
- synthesis filter bank, 95
- TEQ, 60–62, 169, 174
- time domain equalizer, *see* TEQ

INDEX

359

- time domain Nyquist(M) property, 279
- time multiplexing, 97
- time-division multiplexing (TDM), 97
- tone, 169
- transmitting filter, 260
- transmitting pulse, 261
- transmultiplexer, 95
- unbiased estimate, 41, 43
- unbiased SNR, 41, 205
 - SC-CP, 158, 183
 - ZP-OFDM, 150
- unblocking, 77
 - random process, 335
- unitary precoder, 194
- upsampler, 71
- wide sense stationary property, *see* WSS
- windowing, 260
- WSS, 13, 33
 - continuous-time, 336
 - discrete-time, 329
- zero padding, 2, 112, 136
 - OFDM, 147
 - single carrier, 160
- zero-forcing, 2, 16
 - precoded OFDM, 194
 - OFDM, 137
 - SC-CP, 153, 156
 - SC-ZP, 160
- zero-jamming system, 225
- zero-padded OFDM, 147
 - efficient receiver, 149
 - MMSE, 150
 - pseudo-inverse receiver, 148
 - zero forcing, 147
- zero-padded system, 112–115, 225
- ZJ system, *see* zero-jamming system
- ZP system, *see* zero-padded system