

Index

antenna	sphere detector, 84
downtilt, 118 , 152 , 205 , 332 , 370	effective channel, 44 , 110 , 183 , 202 , 220 ,
pattern, 112 , 156 , 219 , 252 , 370 , 380 ,	229 , 251 , 343 , 354 , 398
401 , 446	energy efficiency, 423
backhaul, 25 , 244	equalization, 14 , 19
capacity, 32 , 55 , 87 , 102 , 109 , 130 , 251	IRC, 30 , 44 , 52 , 228 , 264 , 323 , 324 ,
, 262 , 268 , 277 , 291 , 293 , 332 , 375	356 , 389
, 387 , 391 , 396 , 406 , 444	MMSE, 45 , 74 , 84 , 98 , 211 , 230 , 315 ,
latency, 55 , 63 , 69 , 108 , 116 , 163 , 275 ,	324 , 344
300 , 303 , 307 , 333 , 341 , 396 , 404 ,	MRC, 30 , 45 , 52 , 74 , 229 , 264 , 389
458	ZF, 98 , 191
signaling, 64	exchange
technologies, 301	CSI, 57 , 122 , 245 , 292 , 298 , 331 , 340 ,
topology, 300	449
broadcast channel, 74 , 108 , 131	data, 331
clustering, 71 , 94 , 115 , 208 , 294 , 333 , 385	IQ samples, 83 , 297 , 332 , 392 , 448
, 457	precoded signals, 130
dynamic, 118 , 148 , 259 , 391 , 397	scheduling information, 56 , 63
static, 141	soft coded bits, 90 , 298 , 392
computational complexity, 57 , 83 , 97 , 129 ,	user data, 121 , 130 , 299 , 333
265 , 317	fairness, 48 , 57
cost efficiency, 148 , 162 , 191 , 242 , 268 ,	feedback
303 , 340 , 377 , 423 , 444 , 457	CQI, 43 , 116
CS/CB, 396	CSI, 67 , 69 , 110 , 116 , 122 , 166 , 203 ,
CSI	208 , 251 , 332 , 353 , 355 , 369 , 397 ,
exchange, 57 , 122 , 245 , 292 , 298 , 331 ,	447 , 449
340 , 449	decision, 239
feedback, 67 , 69 , 110 , 116 , 122 , 166 ,	PMI, 43 , 51 , 396
203 , 208 , 251 , 332 , 353 , 355 , 369 ,	WCI, 396 , 398
397 , 447 , 449	geometry factor, 50 , 141 , 153 , 351 , 358 ,
feedback latency, 166	375 , 384
hierarchical, 124 , 355	Hadamard matrices, 46 , 322
quantization, 71 , 79	HARQ, 52 , 66 , 116 , 257 , 259 , 268 , 275 ,
deployment	299 , 315 , 338 , 368 , 370 , 389
heterogeneous, 401	interference channel, 78 , 131 , 278
homogeneous, 401	interpolation gain, 198 , 236
detection	latency
ML, 83	
PIC, 84 , 98	
SIC, 84 , 314 , 324 , 425	

backhaul, 63 , 69 , 108 , 116 , 163 , 275 , 300 , 303 , 307 , 333 , 341 , 396 , 404 , 458	network, 334 , 415
CSI exchange, 333	X2 interface, 63 , 116 , 151 , 301 , 307 , 333 , 406 , 440
CSI feedback, 166	
decoding, 34 , 84 , 239 , 266 , 274 , 315	Zadoff-Chu sequences, 205 , 322
signaling, 116 , 333	
macro diversity, 93	
multiple access channel, 81 , 132	
pilots, <i>see</i> reference signals	
power control, 30 , 51 , 62 , 92 , 178 , 207 , 246 , 258 , 391 , 426	
precoding, 14 , 19 , 43	
DFT-based, 44	
DPC, 111 , 135	
EOC, 114	
ICIN, 71	
linear, 123	
MET, 114	
THP, 109	
Wiener filter, 221	
ZF, 113 , 221	
reference signals, 26 , 46 , 64 , 197 , 233 , 258 , 292 , 321 , 389 , 415 , 432 , 448	
cell- and antenna-specific, 116 , 204 , 331 , 336 , 347 , 354 , 448	
LTE Release 8 CRS, 200 , 236 , 419	
positioning, 418	
stream-specific, 119 , 204 , 331 , 343 , 354 , 448	
S1 interface, 159 , 340	
scheduling, 56 , 246 , 256 , 292 , 294 , 388 , 398 , 403	
proportional fair, 58 , 256	
score-based, 46	
self organizing network (SON), 157	
signaling	
delay, 297	
for clustering, 157	
latency, 333	
source coding, 32 , 87	
spatial channel model, 48 , 73 , 112 , 152	
standardization impact, 92 , 157 , 205 , 209 , 260 , 317 , 458	
superposition coding, 20 , 30 , 32 , 92 , 131 , 284	
synchronization, 45 , 161 , 221 , 321 , 331 , 334 , 356 , 377	
channels, 413	
in frequency, 162 , 181 , 407 , 419 , 458	
in time, 162 , 173 , 412	
local, 94	