

Index

- abelian. *See* commutative group
- aberration function
 - of an out-of-focus lens, 33
- absorption, 179
- absorption meter, 75
- adaptive optics, 194
 - system layout, 194
- ADC. *See* analog to digital converter
- additive white Gaussian noise, 230, 232
- aerosol, 160, 161, 277
 - complex refractive index of, 280
- Airy, 25
 - definition of an Airy pattern, 25
 - disk, 196
- amospheric transmittance, 179
- amplitude-shift keying, 142
- analog to digital converter, 67, 68, 69, 80
- Andrews, 184, 185, 190, 197, 199, 210
- Andrews/Phillips Strehl ratio, 209
- angle-of-arrival tilt variance, 200
 - definition of, 200
- angular spreading, 251
- angular tracking error, 243
- annual Korean turbulence statistics, 183
- AO. *See* adaptive optics
- AOptix, 205
- APD. *See* avalanche photo-detectors
- apparent optical properties, 254, 262
- ASK. *See* amplitude shift keying
- asymmetry factor, 251
 - definition of, 251, 256
- asymptotic radiance attenuation coefficient
 - definition of, 256
- asymptotic radiance distribution for plane wave illumination
 - for unbounded medium with uniform scattering and absorption properites, 256
- atmospheric log-amplitude fluctuations. *See* scintillation
- automatic optical gain control, 223
- avalanche photo-detectors, 115
- average cosine, 82
 - for the scalar phase function, 256
- average probability of error, 59
- AWGN. *See* additive white Gaussian noise
- background-noise-limited communications, 250
 - in the optical scatter channel, 250
- backscatter, 160
 - aerosol, 161
 - coefficients from Mie theory, 160, 163
 - return from, 56, 75, 77, 157, 158, 159, 163, 164
 - volume cross section of, 158
- band-limited signals, 14
- bandwidth, 16, 102
 - electrical, 116
 - for subcarrier, 103
 - optical, 116
- baseband and subcarrier direct detection, 103
- BCH, 135
- BCH codes, 135
- Beacon, 238
- beam slew rate, 183
- beam wander, 194
- Becker, Olsson and Simpson, 115
- Beer’s law, 179
- Belmonte and Kahn, 230, 231, 232, 234, 235
- BER. *See* bit error rate
- binary differential phase shift keying, 232
- binary phase modulation, 110
- binary phase shift key. *See* binary phase modulation
- binary signal modulation, 122
- binary symmetric channel, 122, 125
- bit error rate, 122, 225, 232
- black body, 5, 7, 8, 55
 - law, 7
 - quantum mechanical equipartition energy, 55
 - radiation from astronomical sources, 8, 10
 - theory, 11
- block codes, 121

- block coding techniques, 124–135
- block encoder, 123
 - rate, 124
 - the basic system layout, 123
- block error, 274
- Boltzmann, 5
- Boltzmann’s constant, 102
- Bose-Chaudhuri-Hocquenghem. *See* BCH
- BPM. *See* binary phase modulation
- BPSK. *See* binary phase shift key
- branch point, 198
 - ambiguity of, 198, 199
 - definition of, 198
- Brillouin scattering, 151
- BSC. *See* binary symmetric channel
- Buften model, 185
- capacity, xi, 15, 16, 45, 46, 63, 78, 100, 140
 - definition of, 14
 - for signal shot-noise communications, 100
- capacity theorem, 14
- carrier-suppressed return-to-zero, 143
- carrier-to-noise ratio, 102
 - definition of, 102
- CDF. *See* cumulative density function
- centroid, 239
 - of an extended/unresolved target, 238
- centroid tracking, 238
 - positives and negatives, 240
- channel coding. *See* forward error correction
- channel effect on the signal, 31
- Claude Shannon, 100
- CNR. *See* carrier-to-noise ratio
- code book, 126
- code word, 121, 123, 125, 128
- coding gain, 115, 123
- coherent binary communications. *See* coherent digital optical communications
- coherent digital optical communicaitons, 111
- coherent M-PSK, 232
- coherent system with amplitude shift keying, 117
- collision rate, 273
- commutative group, 129
- compensation factor, 255
- complementary error function, 110
 - definition of, 110
- complex refractive index, 72, 85, 280
- conditional probabilities, 122
- contrast, 65, 68, 69, 75, 240
 - definition of, 67
 - Michelson definition of, 71, 72
 - Weber definition of, 71, 72
- contrast sensitivity
 - inverse of contrast threshold, 71
- contrast threshold, 71
- convolutional codes, 139
- corner cube, 153, 154, 156, 290
- coset or coset array, 130
- cosine to the fourth, 37, 38, 39
- cosine to the fourth law, 39
- covariance, 15
- covariance function
 - definition of, 28
 - relationship with Karhunen-Loeve expansion, 47
 - temporal, 29
- crossover probability, 122
- cross section, 153, 251
 - extinction, 73
 - geometric cross section of a particle, 162
 - isotropic, 154
 - of a corner cube, 156, 290
 - of a diamond, 154
 - of a Lambertian surface, 290
 - of a mirror, 154
 - of a target, 152
 - of the Earth, 4
 - scattering cross section of an isotropic molecule, 159
- CS-RZ-OOK, 143
- cumulative density function, 213
- cumulative distribution for cloud optical thickness, 269
- curvature AO system, 195, 197, 198
- data rate, 62, 264, 271
- David Fried, 193, 217
- daytime sky radiance, 8
- DBPSK or 2-DPSK. *See* binary differential phase-shift keying
- deformable mirror, 195
- degrees of freedom, 6, 49, 232
 - spatial, 55
 - temporal, 51
- depth of modulation, 46
- detectivity
 - definition of, 58
- diagnostic lidar, 157, 158, 163
- differential phase-shift keying, 142, 143, 144, 232
- diffraction limited
 - definition of, 32
- diffraction pattern
 - of a circular aperture, 25–27
 - of a rectangular aperture, 24
- Diffserv QoS capabilities, 227
- diffuse, 35, 56, 85, 169, 259
- diffuse attenuation coefficient, 92, 254, 256, 257, 268
 - definition of, 76, 256
- diffuse reflection coefficient, 56, 77, 83, 92
 - definition of, 56, 77
- diffuser, 255
- diffusion pattern, 256
- diffusion regime, 254
- diffusion regimes of scattering, 251
- diffusion stream

- definition of, 256
- diffusion thickness, 85, 252
 - definition of, 251
- dimensions, 7, 14, 19, 20, 32, 42, 48, 50, 51, 73, 104, 105, 154, 155, 290
- directional cosines, 20, 22, 23
- directional reflectance
 - definition of, 255
- discrete memory-less channel, 121
- distance from the Sun to the Earth, 4
- DMC. *See* discrete memory-less channel
- downwelling irradiance, 255
- downwelling irradiance attenuation coefficients, 256
- downwelling radiance, 255, 257
- DPSK. *See* differential phase shift keying
- dynamic range, 84, 88, 90, 94, 96, 144, 225
 - instantaneous, 71
 - of the eye, 71
- EDFA. *See* erbium-doped fiber amplifier
- eigenfunction, 48, 51, 256
- eigenvalues, 48, 49, 50, 256
- EKF. *See* extended Kalman filter
- electric field, 2
- electrical signal-to-noise ratio, 99, 101, 103, 116, 117, 118, 121
 - background-limited operation, 102
 - for homodyne detection receivers, 108
 - for multi-mode heterodyne receivers, 107
- emissivity
 - definition of, 56
- energy, 2, 6, 15
- energy per bit per unilateral spectral noise density, 99, 100
 - definition of, 100
- entropy, 1, 11, 12, 13, 30
- erbium-doped fiber amplifier, 115, 223
- extended Kalman filter, 241
- eye, 71, 72, 79, 80, 86, 91
 - safety requirements, 151, 212
- eye diagram, 235
- FASCODE, 180
- FEC. *See* forward error correction
- fiber optic communications, 179
- field of view, 5, 7, 51, 85, 108
- First Law of Thermodynamics, 1, 43
- first order Bessel function, 25
- flatness, 155, 156, 157, 290
- FM. *See* frequency modulation
- FM modulation index, 103
- F*-number of the lens, 32
- FOC. *See* fiber optic communications
- FOCAL. *See* Free-Space Optical Communications Airborne Link
- forward error correction, 115, 121, 144, 218, 219, 223, 225, 267, 273
 - applied to the turbulent channel, 121
- FOV. *See* field of view
- FOV_{pixel}. *See* pixel field of view
- frame, 113
- Fraunhofer, 211
- Fraunhofer approximation, 22–28
- Fraunhofer spreading loss
 - definition of, 211
- free space optical communications, 115, 179
- Free-Space Optical Communications Airborne Link, 218
- frequency modulation, 112
- frequency shift keying, 111
- Fresnel approximation, 21
- Fresnel distance, 212
- Fresnel length from diffraction theory. *See* Fresnel distance
- Fresnel-Kirckhoff approximation, 48
- Fresnel-Kirkoff diffraction, 19
 - solution to, 21
- Fried parameter, 182, 184, 201, 205, 211, 217, 218
 - definition for spherical waves, 190
 - definition of, 189
- FSK. *See* frequency shift key
- FSL. *See* Fraunhofer spreading loss
- FSOC. *See* free-space optical communications. *See* free space optical communications pointing, acquisition and tracking for
- FSOC link budget, 210, 214
- gain, 66
 - definition of, 3
- Galois field, 135
- gate, 239
 - definition of, 238
- Gaussian distribution, 257
- Gaussian noise, 15
- Gaussian random process, 266
- generator matrix, 127
 - for a Hamming (7, 4) code, 131
 - transpose of, 127
- geometical optics
 - Lambertian source analysis, 35–39
- glint. *See* specular reflection
- global positioning system, 152, 174, 175, 236
- GPS/INS. *See* global positioning system and inertial navigation system
- Green’s theorem, 19
- Greenwood frequency, 190
 - definition of, 190
- Greenwood time constant, 190
 - definition of, 190
- group, 129
 - definition of, 129
- group theory, 126, 129
- Hamming code, 121
- Hamming distance, 125, 129

- Harald T. Friis, 211
Helmholtz equation, 19
heterodyne detection receivers, 103–108
heterodyne efficiency
 in turbulence, 193
higher order aberrations, 194
histogram, 86, 88, 94
 equalization, 88
HITRAN, 180
homodyne detection receivers, 108
homodyne PSK, 230
Hufnagle-Andrews-Phillips model, 184, 205, 207
Hufnagle-Valley 5/7 model, 182
Hufnagle-Valley model, 214
Huygens wavelets, 21
Huygens-Fresnel-Kirchoff integral, 23
HV. *See* Hufnagle-Valley 5/7 model
HV 5/7. *See* Hufnagle-Valley 5/7 model
HV 5/7 vertical profile for wind speed, 183
hybrid optical-RF network, 227
- ideal gas law, 6
IM. *See* intensity modulation
imaginary Bessel function, 60
imaging through a brownout, 94. *See* Figure Web-10
imaging through a fog bank, 94. *See* Figure Web-11
imaging through smoke, 94. *See* Figure Web-9
imperfections, 155–156
impulse response. *See* point spread function
inclinometer, 157, 174
incomplete gamma function, 109
 definition, 109
index of refraction, 181
inertial navigation system, 236
information, xi, xii, xiv, xvii, 1, 13, 15, 17, 61, 64, 65, 78, 80, 99, 100, 104, 112, 121, 122, 124, 128, 135, 136, 140, 141, 144, 151, 153, 157, 180, 194, 229, 229, 238, 263, 273
 amount of energy to transmit an information bit, 16
 choice of base, 14
 content of an image, 78
information theory, xi
inherent contrast, 65, 66
inherent optical properties, 249, 256, 262
inner scale of the turbulence, 180, 192
instantaneous field of view, 32, 54
intensity modulation, 109
intensity threshold, 239
 binary, 239
 intensity Type I, 239
 intensity Type II, 239
interleaving, 219
inter-platform communications manager, 227
inter-symbol interference, 146, 234
interweaving, 218
inversion parameter, 116
IP. *See* internet protocol
IPCM, 227, 237. *See* Inter-Platform Communications Manager
irradiance, 2, 28, 34, 39
 of the Sun, 4, 7
irradiance attenuation coefficients, 255
irradiance ratio, 255
ISI. *See* inter-symbol interference
isoplanatic angle, 182, 184, 190
 definition of, 190
isotropic, 3
isotropic scattering, 257
IXIA, 229
- Jacobian, 4
James Clerk Maxwell, 2
Jeans. *See* Rayleigh-Jeans
Jerlov water types, 257
 Type I, IA, IB, II and III, 257
John W. Hardy, 194
Johns Hopkins University Applied Physics Laboratory, 205
Johnson noise, 115
Juan Juarez, 207, 218, 223
- Karhunen-Loeve analysis, 47, 50
Kennedy, 249
Kirchoff diffraction theory, 19–21
Kirkhoff-Fresnel solution, 19
Kolmogorov, 180, 181, 231
- l’Hopital’s rule, 24
Lambertian, 35, 37, 82, 153, 250, 251
Lamberts’ law, 36
LAP. *See* local area processing
laser dead time, 264
laser frequency linewidth, 116
lateral coherence distance in turbulence. *See* Fried parameter
law of cosines, 187
law of sines and cosines, 187
Legendre polynomials, 72
lens law, 32
lidar ratio, 160
linear transmission channel, 30–31
load resistor, 102
local area processing, 66
low-density parity-check codes, 139
LOWTRAN, 180
lunar irradiance
 relationship to solar irradiance, 269
- magnetic field, 2
Manchester code, 60
Manchester encoding, 123
MANET. *See* Mobile Ad hoc Network
manhole effect, 163, 250
Marcum Q function, 112
 definition, 112
maritime aerosol model, 180
maximal ratio combining, 232

- maximum likelihood decoding
 - for a binary symmetric channel, 125
- maximum likelihood function, 58
- Maxwell's equations, xi, 1, 2, 19, 72
- MCF. *See* mutual coherence function
- Michael C. Roggemann, 194
- Mie scattering, 249
- Mie theory, 72–75
 - absorption cross section, 73–73
 - definition of the Mie parameter, 72
 - definition of single scatter albedo, 73
 - definition of total concentration of particles, 74
 - density of particles, 73
 - extinction cross section ii, 73
 - extinction efficiency, 73
 - Mie coefficients, 72
 - normalized scattering phase function, 73
 - parallel component of the scattered field, 72
 - particle size distribution, 73
 - perpendicular component of the scattered field, 72
 - scattering cross section ii, 73
- minimum resolvable spot, 32
- MIT Lincoln Laboratory, 218
- Mobile Ad hoc Network, 227
 - definition of, 227
- modified Bessel function of the first kind, 231
- modified von Karmon spectrum, 182
- MODTRAN, 180
- modulation transfer function, 189
- Monte Carlo simulations, 75, 163, 251, 252, 257, 259
- MRC. *See* maximal ratio combining
- MTF. *See* modulation transfer function
- multi-path time spreading. *See* temporal spreading
- mutual coherence function, xiv, 28, 29, 31, 94
 - coherence separable definition, 28
 - coherence separability, 47
 - definition of, 28
 - for forward scattering approximation, 75
 - homogeneous definition, 28
 - relationship to covariance function, 28
 - wide-sense stationary definition, 28
- narrow field of view, 236
- NEP. *See* noise equivalent power
- network stack, 227
- NFOV. *See* narrow field of view
- nighttime sky radiance, 10
- noise equivalent power, 58
- noise power, 14, 16, 57, 99, 268
- Noll, 202, 210, 231
- non-binary BCH codes. *See* Reed-Solomon coding
- non-central chi-squared distribution, 231, 232
- non-return-to-zero, 141, 146, 147, 148
 - definition of, 142
- normalized received power for an underwater receiver, 258
- NRZ. *See* non-return-to-zero
- NRZ-DPSK, 142
- NRZ-OOK, 142, 224, 225
- Nyquist, 13, 14
- Nyquist sampling, 211, 212
- OAGC. *See* optical automatic gain control
- on-off keying, 108, 122, 142, 143
- OOK. *See* on-off keying
- optical automatic gain control, 144, 224, 225
- optical communications over the horizon, 277
 - multiple scatter model, 277
 - particulate single scatter model, 277
 - transmittance, 277
- optical diversity, 218
- optical ducting, 277
- optical modem, 221–227
- optical RF communications adjunct, 210
- optical signal-to-noise ratio, 118, 119, 142, 223, 225
- optical thickness, 85, 161, 251, 252, 253, 269
- optical transfer function, 33, 34, 35, 94
- OSNR(t) or OSNR. *See* optical signal-to-noise ratio
- OTF, xvi, 33, 94, 189. *See* optical transfer function
- outer scale of the turbulence, 180, 192
- packet error rate, 227
- parallel concatenated convolutional code, 140
- parity check, 124
 - codes, 124
 - digits, 124
 - matrix, 127
- Parseval's theorem, 45, 79
- PAT. *See* pointing acquisition and tracking
- PCLNWIN, 180
- PCM. *See* pulse code modulation
- peak power detection, 112, 263
- percent relative humidity, 280
- permeability, 2
- permittivity, 2
- phase conjugation, 195
- phase management feed-forward carrier phase estimation, 236
- phase-shift keying, 111, 232
- phase variations, 231
- Phillips, 184, 190, 197, 199, 210
- photo-electron, 57
- photo-electrons per bit, 234
- physical thickness, 85, 251, 269
- PIB. *See* power in the bucket
- PIF. *See* power in the fiber
- PIN photo-detectors, 115
- pixel field of view. *See* instantaneous field of view
- Planck, 7, 8
- Planck's constant, 102
- plane wave coherence radius, 189
- point source coherence function, 31
- point spread function, 35, 183, 189, 203
 - of a particulate scattering medium, 163
- pointing, acquisition and tracking, 236–244

- Poisson, 43
 - counting, 58, 283, 284
 - distribution, 41
 - noise, 60
 - probability density function for, 78
 - process, 78, 283
- Poisson statistics, 59
- power, 4
- power in the bucket, 195, 197, 205, 213, 217, 218
 - definition of, 213
- power in the fiber, 195, 196, 205, 213, 217, 218
 - definition of, 213
- power out of the fiber, 223
 - definition of, 224
- power spectral density, 15, 45, 57, 64, 66
 - white noise, 16
- power spectrum, 181
 - for turbulence, 181
- PPM. *See* pulse position modulation
- PRF. *See* pulse repetition frequency
- probability density function, 231, 232
 - of scattering, 73
- probability of a word decoding error
 - for a group code, 134
- probability of bit error, 99, 102, 266
 - for binary AM subcarrier IM communications, 111
 - for binary phase shift key, 110
 - for binary pulse PPM, 113
 - for block code, or M -ary, PPM, 113
 - for intensity- and frequency-modulated heterodyne detection systems, 112
 - for intensity modulation / OOK, 109
 - for PPM direct detection communications, 113
 - for signal-shot-noise-limited PPM, 113
 - for thermal noise-limited PPM communications, 113
 - relationship to probability of symbol error, 266
 - relationship with probability of word error, 62
- probability of error, 275
- probability of symbol error, 266
 - for an RS (n,k) code, 273
 - in PPM, 266
 - relationship to probability of bit error, 266
- probability of word error, 61
 - relationship with probability of bit error, 62
- PSD. *See* power spectral density
- PSK. *See* phase shift key
- pulse amplitude modulation, 232
- pulse code modulation receivers, 108–110
- pulse position modulation, 61, 112–113, 230, 263, 273
 - frame, 263
 - slot width, 264
 - slots, 263
- pulse repetition frequency, 113, 268, 269, 271
- QAM. *See* quadrature amplitude modulation
- quadrature amplitude modulation, 232
- quantum efficiency, 42, 43, 294
- quantum mechanical equipartition energy, 7
- quantum-limited. *See* Signal Shot-Noise Limit
- quantum-limited communications
 - in the optical scatter channel, 250
- radiance, 2
- radiance distribution
 - at depth, 255
- radiant emittance, 2, 4. *See* radiant exitance
- radiant energy, 2
- radiant exitance, 2
- radiant flux, 2
- radiant intensity, 2, 4, 55, 56
- radiant power. *See* radiant flux
- radiation transfer by atmospheric aerosols, 277
- radiative transfer equation
 - solution in the small-angle scattering approximation, 277
- radiative transport equation
 - irradiance at depth solution, 262
 - solution in the small-angle scattering limit, 260
- radio frequency (RF) communications, 179
- radius of the Earth, 280
- Raman scattering, 151, 158, 161, 163
- range equation, xv, 3, 27, 28, 72, 152, 153, 158, 160
- range height indicator, 162
- Rayleigh, 6, 27
 - distribution, 95
 - scattering, 73, 151, 158
- Rayleigh range, 211, 214
 - definition of, 211
- Rayleigh-Jeans law, 6, 7
- received radiance at depth
 - as a function of angle of incidence, 259
- receiver field-of-view in water, 259
- receiver sensitivity, 115
 - definition of, 100
 - for coded M -ary orthogonal modulation, 144
 - for quantum-limited systems, 144
- receiver temperature, 102
- redistribution function, 256
 - definition of, 256
- Reed-Solomon
 - coding, 135–138
- Reed-Solomon, 121, 219, 224, 225, 274, 275
- Reed-Solomon codes, 136, 145
 - burst noise, 138
- reflectance of a water column, 255
- refractive index covariance function, 181
- refractive index structure function, 181
 - definition of, 181
- refractive index structure parameter, 181, 182, 184, 185, 214, 218
- relationship between frequency and wavelength, 5
- relationship between the bit error and symbol error probabilities, 137
 - for M -ary frequency shift keying, 137
- resolution, 40, 56, 80, 151

- bits of, 68, 80, 87
- retarded time, 2
- return-to-zero, 141, 146, 147
 - definition of, 141
- Ricean distribution, 95
- Richard Hamming, 121
- RMS scatter angle, 85, 287
 - definition of, 256
- Robert K. Tyson, 194
- Roddier, 201, 210
- Roddier Strehl ratio, 209
- roughness, 153, 155, 156, 157, 290
- R-S. *See* Reed-Solomon coding
- rural aerosol model, 180
- Rytov Number, 191, 198, 199
 - definition of, 191
- Rytov variance, 191
- RZ. *See* return-to-zero
- RZ DPSK, 142
- RZ-DPSK, 142, 143, 145
- RZ-OOK, 142

- Sackur-Tetrode equation, 11
- saturation regime, 194
 - definition of, 192
- scalar phase function, 251, 256, 281
- scattering, 179
- scattering length, 253
- scintillation, 192
- Secchi depth, 75
- Secchi disc, 74
- Second Law of Thermodynamics, xi, 1
- self-referencing interferometer, 199
- self-referencing interferometric AO system, 197, 199
- Shack-Hartmann AO system, 197
- Shannon, 14, 63, 121, 122
- Shannon limit, 267
- Shannon's theorem, 15
- Shannon-limited SNR, 144
- short-wave infrared, 236
- Siebert Q. Duntley, 75, 80, 81, 84
- signal carrier frequency, 103
- signal power, 14, 15, 57, 58, 69, 80, 83, 99, 108, 148, 273
- signal shot-noise limit, 102, 103, 115
- signal-signal beat noise, 115
- signal-spontaneous beat noise, 115, 117
- signal-to-noise ratio, xii, 15, 30, 44, 46, 57, 58, 64, 65, 66, 67, 68, 69, 75, 94, 99, 100, 108, 116, 118, 170, 172, 225, 231, 239
 - electrical. *See* electrical signal-to-noise ratio
 - for baseband and subcarrier direct detection receivers, 103
 - for digital PPM, 101
 - in the quantum limit, 45
 - in the signal and background shot noise limit, 268
 - In the signal shot-noise limit, 99
 - instantaneous received SNR per bit, 230
 - of a lidar system, 156
 - optical. *See* optical signal-to-noise ratio
 - Shannon definition of, 63
- single-scatter albedo, 250, 253, 256
- slot, 113
- SNR. *See* signal to noise ratio
- soft tissue imaging in X-rays. *See* Figure Web-8
- solar constant, 4, 91
- solar irradiance, 269
 - mid-day value of, 269
- spatial coherence, 30
- spatial coherence function. *See* spatial covariance function
- spatial covariance function, 30
 - definition of, 30
- spatial diversity, 218, 219
- spatial frequency, 29
- spatial intensity, 32
- spatial modulation index, 65, 66
- spatial spreading, 251
 - definition of, 251
- speckles, 199
- spectral, 2
- spectral albedo, 10
- spectral efficiency, 99, 100–101, 144, 234
 - definition of, 100
 - for homodyne receivers, 101
 - for the Shannon limit, 144
- spectral irradiance, 11
- spectral radiance, 4, 7, 36, 37, 54
 - spectral radiant emittance, 11, 36, 37
- spectral radiant energy, 3
- specular reflection, 154
- speed of light, 2
- spontaneous-spontaneous beat noise, 115, 117
- sp-sp. *See* spontaneous-spontaneous beat noise
- SRI. *See* self-referencing interferometer
- s-sp. *See* signal-spontaneous beat noise
- Stefan-Boltzmann constant, 5
- Stefan-Boltzmann law. *See* Boltzmann
- Strehl ratio, 35, 190, 199, 211, 212, 218
 - alternate calculation, 207
 - definition of, 35
 - for AO gain, 201
 - for strong turbulence (Andrews), 205
 - for strong turbulence (Noll), 203
 - for turbulence, 191
 - for weak turbulence (Andrews), 205
 - for weak turbulence (Noll), 203
- strong turbulence, 181
 - definition of, 181
- Sun diameter, 4
- Sun temperature, 7
- SWIR. *See* short wave infrared
- syndrome, 128, 129, 130
 - definition of, 128

- Tatarski, 182
- TASS. *See* three-aperture scintillometer system
- temperature, 5
- temporal modulation index, 46, 66
 - definition of, 46
- temporal spreading, 251, 263, 271
 - from particulate scattering, 253
- theory of atmospheric turbulence, 180–188
- thermal, 55
- thermal noise, 16, 99
- thermal noise variance, 109
 - for thermal-noise limited IM/OOK, 109
- Thermodynamics
 - First Law, 1, 43
 - Second Law, 1, 11
 - Third Law, 1
- thin lens theory, 31–35
- Third Law of Thermodynamics, 1
- three-aperture scintillometer system, 205
- three laws of thermodynamics, 1
- threshold, 60, 96, 109, 112, 113, 122, 123, 239, 240, 270, 271
 - damage threshold of the detector, 223
 - definition of intensity thresholds, 239
 - exterior, 240
 - interior, 240
- tilt jitter variance, 200
 - definition of, 200
- tip/tilt, 194, 199
- tracker, 157
 - leading edge, 157
- tracking error angle, 243
- transmission, 179
- transmission loss, 251
 - definition of, 252
- transmittance, 252
 - of a absorptive cloud, 253
 - of a non-absorptive thick cloud, 252
 - of an absorptive thick cloud, 252
 - though the air/sea interface, 259
- TT Strehl ratio, 203
 - for strong turbulence (Andrews), 205
 - for weak turbulence (Andrews), 203
- turbo codes, 140
- turbules, 180
- U.S. Standard Atmosphere, 159
- upwelling irradiance, 255
- upwelling irradiance attenuation coefficient, 256
 - definition of, 256
- upwelling radiance, 255, 257
- variable optical attenuator, 218
 - block diagram of, 218
 - example data from, 218
- visibility, xii, 66, 68, 71, 80, 94
 - contrast threshold, 71
 - definition of, 68
 - meteorological, 71, 72
 - sub-visibility imaging, xii, 75, 86, 90, 96, 170
 - Weber definition of, 72
- visibility limit, 80
- visible to near infrared, 236
- VNIR. *See* visible-to-near infrared
- VOA. *See* variable optical attenuator
- volume absorption coefficient, 73, 179
- volume extinction coefficient, 73, 179, 185, 256
- volume scattering coefficient, 73, 179
- Von Cittert-Zernike theorem, 29
- water reflectivity, 257
- wave equation, 2
 - solution of, 2
- wave front sensor, 194, 197, 211, 236, 241
- waveform, 2
- weak turbulence, 181
 - definition of, 181
- WFOV. *See* wide field of view
- WFS. *See* wave front sensor
- white noise power spectral density, 16
- wide field of view, 236
- Wien, 5
- Wien's displacement law, 6
- Wien's law, 6, 7
- WOOD. *See* World-wide Ocean Optics Database
- World-wide Ocean Optics Database, 257
- XFUSION Interface Assembly, 227
- XIA. *See* XFUSION Interface Assembly
- Zernike polynomials, 197, 231
- zeroth order Bessel function, 25
- Zhu and Kahn, 121