

Index

- 3GPP, 7, 9, 145
- Access control, 9, 87, 102
 - exception, 100
- Access mechanism, 221, 227, 320
 - closed, 9, 88, 95, 97, 112, 113, 119, 121, 125, 126, 221, 228
 - hybrid, 9, 88, 95, 97, 221
 - open, 9, 88, 95, 112, 113, 119, 122, 125, 128, 221, 228
- Ad hoc network, 410
 - cognitive, 410
- Almost blank subframe, 11, 168, 193, 194, 196, 246, 273
 - pattern, 194, 196, 197, 209
 - reduced power, 198, 209, 211
 - zero power, 211
- Amplify-and-forward, 284
- Antenna
 - combining weights, 199
 - electrical tilt, 70
 - gain, 69
 - pattern, 68
 - tilt optimization, 169
- Automatic neighbor relation, 152, 156
 - interfrequency, 154
 - inter-RAT, 154
 - relay node, 155
 - UTRAN, 156, 158
- Backhaul, 12, 219, 224, 312, 318–321, 324, 329, 333–335, 347, 348, 432
 - low latency, 11
- Base station, 5, 284
 - aggressor, 181, 184, 194
 - connectivity, 149
 - X2 establishment, 154
- Beacon signals, 393
 - cognitive pilot channel, 393
 - broadcast, 394
 - combined, 394
 - harmonized, 393
 - in-band, 393
 - non-harmonized, 393
 - on demand, 394
 - out-band, 393
- Bit error rate, 377
- Blind standard recognition sensor, 389
- Burlington model, 31
- Capacity, 3
- CAPEX, 8, 427, 435
- Carrier aggregation, 7, 188
- Carrier allocation, 227
 - partially shared carrier, 228
 - separated carrier, 227
 - shared carrier, 228
- Cell, 5
- Cell boundary, 183
- Cell identity, 148–150, 152, 155
 - assignment, 148, 156, 158
- Cell individual offset, 249
- Cell outage, 170
- Cell range expansion, *see* Range expansion
- Cell reselection, 246, 263, 266
- Cell selection, 91, 95, 96, 99, 179, 181, 182, 184, 185, 197, 203, 263, 266
 - R criterion, 264
 - S criterion, 263
- Cell selection offset, *see* Range expansion
 - bias
- Cell spectral efficiency, 104
- Cell splitting gain, 104
- Cell-specific reference symbol, 198, 210
- Centralized SON, *see* Self-organizing network, centralized
- Channel sounding, 189
- Channel state information, 194, 197, 198, 286, 315, 318, 319
 - global, 323, 328
 - local, 323, 326, 344
 - receiver-side, 369
- Cholesky decomposition, 64
- Closed access, *see* Access mechanism, closed

- Closed subscriber group, 9, 88, 89, 95, 99, 101, 154, 165, 180, 181, 190, 192, 193, 196, 200
 - allowed CSG list, 88
 - identity, 88, 95
 - inbound mobility, 97
 - indicator, 88, 95, 100
 - manual selection, 88
 - operator CSG list, 88
 - reserved PCI range, 96, 97
 - whitelist, 88, 95
- Cluster angular spread, 49
- Cluster delay spread, 49
- Cluster process, 116
- Cluster visibility region, 49
- Clustering, 321, 338
- Clutter data, 40
- Co-tier interference, 118
- Codebook, 322, 323, 347
- Coding gain, 353
 - necessary condition, 358
 - upper bound
 - geometry considered, 356
 - geometry not considered, 354, 355
- Coding opportunity detection, 378
- Cognitive radio, 11, 383
 - false alarm, 386
 - missed detection, 386
 - scenarios, 409
 - ad hoc networks, 410
 - cellular networks, 411
 - direct UE-to-UE, 411
 - dynamic backhaul, 410
 - femtocells, 412
 - rural broadband, 410
 - SNR wall, 386
 - spectrum hole, 385
 - techniques, 385, 407
 - cross-layer design, 407
 - white space, 385
- Control channel interference, 188, 192
- Control plane, 90, 94, 250
- Cooperative communication, 314
- Cooperative relaying, 12
- Cooperative spectrum sensing, 390
 - centralized, 391
 - distributed, 391
 - hard combination methods, 391
 - AND-rule, 391
 - K-out-of-N-rule, 391
 - majority-rule, 391
 - OR-rule, 391
 - hidden-UE problem, 390
 - reporting, 390
 - sensing, 390
 - soft combination methods, 391
 - equal gain combining, 391
 - maximal ratio combining, 391
- Coordinated multi-point, 194, 315
- Coordination, 11, 194
- Core network, 87, 89
- Cornu spiral, 31
- COST 2100 channel model, 44, 48
- COST 231 Hata model, 19
- COST 259 channel model, 44, 48
- COST 273 channel model, 44, 48
- Cost efficiency, 434
- Covariance-based detection, 388
- Coverage, 3
- Coverage and capacity optimization, 169
- Coverage hole, 106, 173
- Coverage imbalance, 179, 180
- Cross-carrier scheduling, 188
- Cross-tier interference, 111, 113, 118, 180, 181, 200
- Cyclostationary feature detection, 388
- Decentralized SON, *see* Self-organizing network, decentralized
- Decode-and-forward, 284
- Demodulate-and-forward, 284
- Dense multipath components, 51
- Deployment
 - co-channel, 219, 220, 228
 - orthogonal, 220
- Deployment model
 - heterogeneous, 73
 - homogeneous, 72
- Desensitization, 190
- Detected cells, 156
- Deygout model, 33
- Digital subscriber line, 224
- Direct UE-to-UE communication, 411
- Distributed antenna system, 217
- Distributed multi-cell processing, 324
 - distributed implementation, 313, 324, 327, 329, 330, 333, 344
- Diversity and multiplexing tradeoff, 366, 370, 375, 376
- Diversity gain, 375
- Domain manager, 146
- Dominant path model, 27
- Donor eNodeB, 7, 149, 293
- Downlink/uplink coverage imbalance, 183
- Dual strip model, 81
- Dynamic spectrum access, 383
 - primary user, 383
 - secondary user, 383
 - space dimension, 383
 - time dimension, 383
- eICIC, *see* Inter-cell interference coordination, time based
- Element manager, 146

- Energy consumption, 426, 431
- Energy detection, 387
- Energy efficiency, 12, 426, 431
 - cross-layer techniques, 427
 - definition, 434
 - fundamental tradeoffs, 432
 - network architecture, 436
 - pricing scheme, 448
 - scheduling, 445
 - standardization, 447
- Energy saving, 433
 - capacity improvement, 433
 - dynamic antenna optimization, 442
 - infrastructure reduction, 433
- eNodeB, 5, 92
- Epstein–Peterson model, 32
- Escape carrier, 189
- Estimate-and-forward, 284
- Event entry condition, 248, 249, 259, 276
- Evolved cell global identifier, 100
- Evolved cell global identity, 148, 150, 155
- Evolved packet core, 92
- Evolved UMTS terrestrial radio access network, 92
- Exponential effective SINR mapping, 70, 71
- Feature group indicator, 154
- Femto node, 7
- Femtocell, 7, 11, 77, 217
- Femtocell access point, 7
 - enterprise, 220
 - home, 220
 - integrated, 224
 - outdoor, 221
 - stand-alone, 224
- Finite-difference time-domain model, 19, 39, 40
- Fixed-point iteration, 330, 331
- Fresnel zones, 29, 30
- Fresnel’s wave, 28
- Generalized butterfly network, 357, 358, 360, 378
- Geo-localization, 9, 172
- Geolocation databases, 392
- Geometry model, 23
- Geometry theory of diffraction, 25, 27
- Geometry-based stochastic channel models, 44
- Global navigation satellite system, 151, 172
- Global positioning system, 226
- Grail network, 361
- Green metrics, 431
- Green transmission techniques, 443
- Greenhouse effect, 426
- Handover, 9, 93, 95, 154, 182, 245, 247, 266
 - command, 252, 254
 - complete, 252, 254
 - completion, 253
 - execution, 253
 - failure, 157, 161, 246, 249, 254, 255, 276
 - failure causes, 166
 - failure rate, 255
 - hysteresis, 249
 - inter-RAT, 161
 - margin, 183
 - packet forwarding, 254
 - ping-pong, 246, 249, 254, 258, 276
 - ping-pong rate, 258
 - preparation, 253
 - prepared, 161
 - procedure, 250
 - seamless, 253
 - short stay, 164
 - time to trigger, 249
 - time-of-stay, 258
 - to wrong cell, 163, 257
 - too early, 162, 256
 - too late, 163, 255
 - unnecessary, 161, 246, 258
 - unnecessary inter-RAT, 164
- Hata model, 34
- Heterogeneous cellular network, 5
- HNB management system, 146
- Home eNodeB, 7, 93, 146
- Home NodeB, 7, 89
- Home NodeB/eNodeB gateway, 7, 89, 93, 224
- Huygens principle, 23
- Hybrid access, *see* Access mechanism, hybrid
- Hybrid SON, *see* Self-organizing network, hybrid
- Indoor coverage, 28, 217
- Indoor-to-outdoor model, 40
- Inter-cell coordination, 313, 314, 323, 324, 412
 - dynamic clustering, 322
 - full cooperation, 319, 320
 - information exchange, 315, 321, 324, 325, 326, 329, 333, 335, 339
 - limited feedback, 323
 - parameter exchange, 333
- Inter-cell interference, 10, 179, 181, 200, 219, 312, 319
 - control channel, 188
- Inter-cell interference coordination, 179, 182, 186, 206, 246, 279
 - antenna adjustments, 11
 - carrier based, 187, 188
 - frequency domain, 11, 186
 - power control, 11
 - power domain, 189, 199, 200
 - time domain, 11, 192, 193, 196, 198–200, 202, 204, 209
- Intersite distance, 71
- Intertier interference, 320

- Interference cancellation, 129, 210, 211, 365
 - partial, 368, 376
- Interference covariance matrix, 199
- Interference leakage, 326
- Interference management, 444
 - dynamic, 11, 179
 - spectrum assignment, 11
 - uncoordinated, 11
- Interference mitigation, 227
 - antenna-based techniques, 236
 - frequency-based techniques, 239
 - power-based techniques, 231
- Interference modeling, 112, 113
- Interference rejection combining, 199
- Intracell interference, 317
- Intrafrequency measurements, 183
- Itf-N, 146
- ITU, 9
- Jain's fairness index, 185
- Key performance indicator, 147
- Knife-edge model, 31
- L1 filtering, 248
- L3 filtering, 248
- Limited feedback, 322
- Line of sight, 28, 75
- Linear network coding, 354
- Link adaptation, 286
- Link to system model
 - lookup table, 58
 - SINR to BLER mapping, 58
- Load balancing, 238
- Load indication, 167
 - inter-RAT, 167
- Load sharing, 188
- Localization, 225
- Location management, 245
- Long Term Evolution/System Architecture Evolution, 87
- Low-power node, 6
- LTE, 7
- LTE-Advanced, 7, 293
- Machine learning, 446
- Macro base station, 5, 6
- Macrocell, 6, 217
- Maintenance, 145
- Management architecture, 146
- Management system, 146, 153, 196
 - discovery, 149, 151
- Matched filter signal detection, 387
- Maxflow mincut bound, 354
- Maximal ratio combining, 70
- Measurement report, 248, 250
- Measurement resource restriction, 195, 197
- Medium access control, 90, 94
- Membership verification, 93
- Micro base station, 6
- Microcell, 6
- MIMO channel model, 42
 - physical, 43
 - stochastic, 43
- Minimization of drive test, 171
 - accessibility, 172
 - immediate, 171
 - location information, 172
 - logged, 171
- Minimum mean square error (optimal) combining, 199
- Mobile data, 2
- Mobility, *see also* Handover, 87, 245
 - closed subscriber group, 87
 - idle, 95
 - inbound, 87, 97
 - management, 246, 272
 - model, 83
 - hotspot, 84
 - large area, 84
 - outbound, 87, 97
- Mobility load balancing, 166, 245, 263, 266, 268
- Mobility management entity, 92, 155, 247, 250
- Mobility robustness optimization, 10, 161, 246
- Mobility state, 279
- Multi-cell processing, 313–318, 321
- Multi-resolution frequency-domain ParFlow model, 22, 40
- Multicast, 352
- Multipath components, 16, 17, 23, 50
- Multipath fading, 62, 65
 - channel model, 66
 - precomputed map, 67
- Multiplexing gain, 375
- Multiuser MIMO, 318, 322
- Multiwall model, 36
- Mutual information effective SINR mapping, 71
- Neighbor relation, 148, 149, 152, 155–158
 - covered by, 171
- Network architecture, 436, 445
 - LTE/SAE, 92
 - relaying, 293
 - UMTS, 88
- Network coding, 12, 352, 354
 - average energy constraint, 371, 372
 - decoding at destination, 370
 - distributed, 378
 - penalty, 358, 360
 - saving, 358, 360
 - wireless, 365

Network evolution, 8	downlink, 191
Network management system, 146	uplink, 184, 186, 190
Network MIMO, 12, 313, 318–321, 323, 346–348	Power headroom, 172
Network monitoring, 9	Precision time protocol, 226
Network monitoring mode, 222	Precoding, 315, 322
basic carrier detection, 223	coordinated beamforming, 319, 323, 337, 338
LTE cell identification and power measurement, 223	distributed beamforming, 319
LTE cell information retrieving, 223	multiuser precoding, 318
Network-channel coding, 305	Tomlinson–Harashima precoding, 318
NGMN, 10, 145	Primary scrambling code, 101, 149
Node, 5	Proximity indication, 99, 165
NodeB, 5, 89	
Non-line-of-sight, 39, 75	Radio access network, 87
Non-convex problem, 337	Radio link control, 90, 94
	Radio link failure, 158, 162, 246, 254, 255
OFDM symbol shift, 192	in sync, 254
Okumura–Hata model, 18	out of sync, 254
Open access, <i>see</i> Access mechanism, open	T310 timer, 254
Operational carrier, 187	Radio network controller, 89, 152
Operational carrier selection, 148, 169	Radio propagation effects, 23
OPEX, 8, 427, 435	Radio propagation model, 15
Optimization, 259	calibration, 42
Outage probability, 373	large scale, 17
Outdoor-to-indoor model, 40	deterministic, 17, 19
Overhearing, 377	empirical, 17
	hybrid, 17, 39
Packet data convergence protocol, 90, 94	semi-deterministic, 17, 34
ParFlow model, 21	semi-empirical, 17
Path loss, 17, 114	path loss, 17
PCI collision, 157, 158	shadow fading, 17
PCI confusion, 97, 102, 156	small scale, 17
Performance information, 146	Radio propagation models, 8
data reduction, 173	Radio resource control, 90, 94
Performance metric, 115, 117	Radio resource management, 89
area spectral efficiency, 117	Radiometric detection, 387
outage probability, 117	Random access, 155, 189, 252
spatial throughput, 117	access delay probability, 160
transmission capacity, 117	access probability, 160
Physical cell identity, 96, 148, 149, 153, 155, 156	optimization, 158
Pico base stations, 6	parameter optimization, 160
Picocell, 6, 74, 217	preamble, 158
Pilot-based coherent detection, 387	procedure, 158
Planning, 145, 148	resource sharing, 161
Point process, 114	transmission power control, 159
binomial, 115	Range expansion, 166, 179, 181, 182, 184, 185, 188,
homogeneous, 114	190, 192, 196, 199, 203, 204, 206, 273, 320,
non-homogeneous, 115	338, 344
Poisson cluster process, 115	Range expansion bias, 166, 181, 182
Poisson point process, 112, 114	Range expansion region, 181
Policies, 146	Rate fairness, 324, 326, 339
Power amplifier, 432	Ray launching, 27
Power constraint, 317, 318, 326, 327, 330, 331, 337,	intelligent ray launching, 28
338, 340, 344, 345	Ray tracing, 26
Power consumption, 431, 432	Rayleigh distribution, 17
Power control	Rayleigh fading, 367
	Received signal quality, 180

- Received signal strength, 180, 181, 182
- Reduced power subframe, 168, 198, 209
- Reference signal received power, 182, 248
- Reference signal received quality, 182, 248
- Reference symbol, 192, 198
- Relay function, 285
- Relay node, 7, 78, 149, 284
- Relay-aided X network, 364
- Relaying
 - access link, 287
 - backhaul link, 287
 - coded cooperation, 304
 - decoding at destination, 370
 - Layer 1, 284
 - Layer 2, 284
 - Layer 3, 284
 - MMSE symbol estimation, 301
 - SISO decoding, 299
 - SISO re-encoding, 299
 - soft symbol calculation, 300
 - Un bearer handling, 296
- Remote radiohead, 6
- Report triggering, 183
- Resource block, 186, 187
- Ricean distribution, 17
- RIM
 - SON transfer, 164, 167, 170
- RRC, 94
 - cell individual offset, 182
 - closed subscriber group identity, 88, 95, 100
 - connected, 246
 - ECGI, 148
 - evolved cell global identifier, 100
 - idle, 246, 263
 - measurement report, 161, 248, 250
 - measurement subframe pattern, 197
 - neighbor cells, 195
 - serving cell, 195
 - measurement subframe sets, 194
 - mobility control info, 252
 - RACH report, 160, 172
 - radio link failure report, 258
 - report triggering, 183
 - RLF report, 163, 164, 172
 - RRC connection re-establishment, 163
 - RRC connection reconfiguration, 100, 153, 252
 - RX–TX time difference, 172
 - SIB1, 95
 - SIB4, 96
 - system information, 95
 - UE ANR procedure, 154, 155, 157
 - UE information, 163, 172
- S1 interface, 92, 93
- S1AP, 93, 296
 - cell identity, 148
 - configuration transfer, 155
 - path switch, 253
 - SON information, 155
- Saving of transmissions, 358, 360
- Scattering loss, 25
- Self-organizing network, 10, 145, 446
 - antenna tilt optimization, 169
 - automatic cell identity management, 156
 - automatic neighbor relation, 152, 154, 156
 - centralized, 147, 152
 - closed subscriber group, 154, 165
 - coverage and capacity optimization, 169
 - distributed, 147, 152
 - hybrid, 147
 - mobility load balancing, 166, 245, 268
 - mobility robustness optimization, 161
 - mobility robustness optimization, 246
 - monitoring, 171
 - random access optimization, 158
 - reduced power subframes, 168
 - relay node, 149, 155
 - self-configuration, 147
 - self-healing, 170
 - self-optimization, 151
 - transmission power tuning, 167
 - X2 establishment, 154
- Self-configuration, 10, 145, 147
- relay node, 150
- Self-healing, 10, 145, 170
 - triggering condition, 170
- Self-optimization, 10, 145, 151
- Self-organization, 219
- Serving gateway, 93
- Shadow fading, 17, 18, 62
 - autocorrelation, 63
 - cross-correlation, 63, 64
 - precomputed map, 64
- Signal to interference ratio, 120
- Simulation
 - 3GPP assumptions, 71
 - dynamic, 60
 - link level, 58
 - model, 9
 - static, 59
 - system level, 58
- Single-cell processing, 316
- SINR
 - wideband, 254
- SINR balancing, 329
- Site, 5
- Sleep mode, 441
 - aggressive, 442
 - passive, 441
- Small Cell Forum, 222
- Small scale fading, 17
- Snell's law of refraction, 27

- Soft estimate and forward, 302
- Software-defined radio, 383
- Source cell, 247
- Spatial channel model, 43, 46
- Spectral efficiency, 287, 312, 314, 319, 320, 348, 431
- Spectrum allocation, 11, 112, 118
- Spectrum analysis, 395
 - combined metrics, 398
 - primary activity metrics, 397
 - arrival rate of busy/idle periods, 397
 - duty cycle, 397
 - expected occupancy/vacancy duration, 397
 - radio frequency metrics, 396
 - bandwidth, 396
 - emission limits, 396
 - frequency, 397
 - interference, 396
- Spectrum awareness, 386
- Spectrum decision, 398
 - capacity based
 - maximum capacity based, 399
 - minimum variance based, 399
 - delay based, 399
 - efficiency based, 399
 - error based, 399
 - multi-objective optimization, 399
- Spectrum handoff, 404
 - proactive, 405
 - reactive, 405
 - space dimension, 404
 - time dimension, 404
- Spectrum mobility, 404
- Spectrum selection, 395
- Spectrum sensing, 386
 - cooperative, 390
- Spectrum sensing architectures, 389
 - dual radio, 390
 - single radio, 389
- Spectrum sharing, 399
 - horizontal, 401
 - centralized, 402
 - cooperative, 402
 - distributed, 402
 - internetwork, 402
 - intranetwork, 402
 - non-cooperative, 402
 - vertical, 399
 - interweave, 399
 - overlay, 400
 - underlay, 400
- Star network, 362
- State
 - CELL_DCH, 91
 - IDLE, 91
 - RRC_CONNECTED, 95, 246
 - RRC_IDLE, 94, 263
- Stochastic geometry, 112–114
- Stochastic local area channel, 16, 24
- Subchannel allocation
 - disjoint, 112, 118, 126, 129
 - general, 119
 - joint, 112, 119, 126, 128
- Subframe alignment, 192
- Success probability, 124
 - downlink, 121
- Synchronization, 225
- Synchronization symbol, 192
- System information, 91, 95, 148, 154, 192
- Target cell, 247
- Terrain information, 40
- Time to trigger, 183, 249
- Trace, 171
- Trace collection entity, 171
- Traditional butterfly network, 360
- Traffic
 - density, 78
 - forecast, 1
 - hotspot, 74, 173, 273
 - model, 9, 82
 - FTP, 83, 210
 - full buffer, 82
 - VoIP, 83
 - offload, 105, 181, 182, 184, 185, 209
 - uneven distribution, 5
- Transmission power difference, 180
- Transmission power tuning, 167
- Two-tier network, 111
 - downlink throughput analysis, 124
 - model, 117
 - throughput optimization, 125
- Two-way exchange network, 360, 365
- UE aggressor, 181, 184, 189
- UE cell detection capability, 166
- UMTS terrestrial radio access network, 88
- Unicast, 353
- Uniform theory of diffraction, 17, 25, 27
- Universal Mobile Telecommunication System, 87
- Uplink interferer identification, 189
- Uplink received power, 190
- User equipment, 87
 - cooperation, 303
 - velocity, 246, 259
- User plane, 90, 253
- Victim base station, 181, 184, 189, 194
- Victim UE, 181, 184, 190, 192–194, 196, 198
- Virtual channel, 289

Walfisch–Ikegami model, 34, 36	handover request acknowledge, 252
Wall penetration attenuation, 37	high-interference indicator, 187
WiFi, 8	invoke indication, 194
WINNER I channel model, 44, 46	last visited cell information, 164
WINNER II channel model, 44, 47	load information, 168, 187, 194
Wireless fidelity, 218	mobility change, 267, 269
Wireless network coding, 365, 366	mobility information, 165
Wraparound, 60	overload indicator, 187
	radio link failure indication, 257
X2 interface, 93, 152	relative narrowband transmit power,
X2AP, 93, 297	187
ABS information, 194	resource status, 167
ABS status, 194	resource status update, 194
cell activation, 170	RLF indication, 164
cell identity, 148	served cell information, 155, 157
deactivation indication, 170	status transfer, 252
eNB configuration update, 170	UE history information, 164
eNB configuration update, 155, 157	UE information, 160
handover report, 164	UE ontext release, 253
handover request, 250	X2 setup, 101, 155