

Index

- accumulation 15–21
 - back-surface 124, 170
 - charge density 19, 93
 - in floating body cell 97–100
- band/subband 25–30, 53–58
 - bending 25
 - diagram 26
 - energy 26, 55
- bandgap 32
- body/UTB doping 1, 13
 - in FD/SOI MOSFETs 113, 115
 - in TG FinFETs 139–141
 - intrinsic/undoped 14–25, 116, 139
 - V_t control 115
- body/UTB thickness 13
 - DICE dependence 48, 51
 - mobility dependence 68
 - QM-effect dependence 25, 53
 - SCE dependence 33, 35, 116
- Boltzmann's constant 19
- BOX 1, 89, 103
 - thick 42, 104, 109, 120
 - thin 4, 101, 103, 120
- bulk (or volume) inversion 14, 20, 63, 141
- capacitance 13, 93
 - body 16, 107
 - C-V characteristics 14, 93
 - depletion 16, 17
 - fringe 89
 - gate 60, 159
 - gate-oxide 13
 - inversion-layer 39, 159
- carrier confinement 25, 53, 71, 93
 - electrical 25, 56
 - structural 25, 56, 67
- carrier scattering 67
 - Coulomb 68
 - phonon 68
 - surface-roughness 71
- carrier velocity 46
 - overshoot 46
 - saturated-drift 46
 - thermal-injection 50
- channel 31
 - effective length 31, 42, 78
 - length modulation 46
 - metallurgical length 78
- charge dynamics 93
- charge neutrality 93
- charge sheet 13, 16, 31, 42
- CMOS 1, 31
 - high-performance 37, 120, 130
 - low-power 37, 120, 128
 - scaling 1, 30, 78
 - speed 46, 66, 92, 160
- current 42
 - diffusion 42, 82
 - drift 42
- Debye length 15, 79
- delay time 52, 91, 108, 161
- density of states 14, 25, 56
 - effective 26, 57
 - effective-mass 26, 57
- depletion
 - approximation 13, 15
 - capacitance 16
 - charge 15, 39, 73
 - region (or layer) 31
- DIBL (drain-induced barrier lowering) 32
 - in DG FinFET 34, 166
 - in FD/SOI MOSFET with thick BOX 105, 112, 116
 - in FD/SOI MOSFET with thin BOX 122, 125
- DICE (drain-induced charge enhancement) 46
- dielectric permittivity 89, 91, 166
- DRAM (dynamic random-access memory) 97
- effective electric field 72
- effective mass 26, 27, 55, 58
- eigenfunction (QM wave function) 54, 55

- eigenvalues (QM energies) 26, 55
- energy gap (*see* bandgap)
- Fermi-Dirac distribution function 14, 54
- Fermi level 95, 100
- Fermi potential 13, 32
- flat-band voltage 13, 35
- floating-body effects 94
- fully depleted body 1, 95
- gate capacitance (*see* capacitance)
- gate length 1, 78
- gate work function 13
- gate-oxide
 - capacitance (*see* capacitance)
 - charge 13
 - thickness 13
- gate-source/drain overlap 78
- gate-source/drain underlap 8, 78
 - capacitance 89
 - design 128, 165
 - effective channel length 79
 - performance 92, 179
 - V_t adjustment 37, 176
- Gauss's law 15, 16
- GIDL (gate-induced drain leakage) 82
- gradual channel 39, 48, 93
- ground plane 1, 125
- high-field region 47
- high- k dielectric 165
- inversion
 - bulk (*see* bulk (or volume) inversion)
 - moderate 17
 - strong 17, 39, 42, 82
 - surface 64, 65
 - weak 17, 37, 42, 79
- inversion-layer 17
 - capacitance (*see* capacitance)
 - charge centroid 24, 31, 56, 125, 158, 159
 - charge density 15, 43
 - thickness (*see* inversion-layer charge centroid)
- ITRS (SIA International Technology Roadmap for Semiconductors) 1
- lateral source/drain doping profile/gradient 37, 84, 176
- leakage current 82
 - drain (*see* GIDL)
 - gate (*see* tunneling current)
- Matthiessen's rule 73
- Maxwell-Boltzmann statistics 26
- midgap (work function) gate 34, 116, 165
- mobility (*see* carrier scattering)
- MOSFET
 - ADG (asymmetrical double-gate) 12, 23, 34, 154
 - IG (independent-gate) 12, 14, 23, 173
 - SDG (symmetrical double-gate) 12, 14, 22, 154
 - SG (single-gate) 11, 14, 22
 - TG (triple-gate) 4, 138
- off-state current 5, 145
- on-state current 5, 14, 51, 143
- oxide
 - buried 1
 - gate 13, 165
- parasitic BJT 95
- parasitic capacitance (*see* capacitance)
- partially depleted body 1, 95
- Planck's constant 26
- Poisson's equation 16, 42, 53
- potential
 - electrostatic 17, 43
 - surface 15, 42
- propagation delay (*see* CMOS speed)
- quantum effect 25, 53
 - on gate capacitance 53, 60
 - on inversion charge 53, 56
 - on mobility 71
 - on threshold voltage 25
- quasi-Fermi level 95, 100
- quasi-static approximation 93
- random dopant fluctuation (RDF) 35
- ring oscillator (*see* CMOS speed)
- Schrödinger wave equation 26, 53
- short-channel effect 1, 31
 - control 33
 - in DG FinFET 34
 - in FD/SOI MOSFET with thick BOX 116
 - in FD/SOI MOSFET with thin BOX 124
 - in TG FinFET 34
 - scale/natural length 32
- SOI 1
- SRAM 96, 176
- straggle 37, 78, 152, 181
- subthreshold slope 11, 110
- surface potential (*see* potential)
- thermal voltage 20
- threshold voltage 13, 15
 - adjustment via S/D doping 37, 176
 - in long-channel ADG MOSFET 82
 - in long-channel SDG MOSFET 37

threshold voltage (cont.)	transcapacitance 52, 93
in long-channel thick-BOX FD/SOI MOSFET 37	tunneling current
in long-channel thin-BOX FD/SOI MOSFET 23	gate 166
increase from QM effect 26	junction 116, 151
lowering from 2-D effects 31	
random-dopant effect 35	wave function (<i>see</i> eigenfunction)