

Index

- Black's equation, 101, 122, 332, 381, 400, 410
 - apparent activation energy, 101, 368
 - current density exponent, 101, 103, 372, 382
- Blech "short length" effect, xii, 4
 - Blech strip test structure, 322
 - critical product, 111, 313
 - line edge drift, 104, 321
- Cu damascene structures, xi, 3–4, 63, 129, 234, 280
 - "via first" dual damascene process, 48
- Cu electroplating, 49, 138, 187, 229
- Cu trench, 169
- dielectric barrier, 81, 102, 255, 277, 279, 322, 325
- dielectric capping layer, 39
- differential equation, 93, 315
 - boundary conditions (BC), 264, 412
 - cosine series expansion, 393
- Initial Boundary Value Problem (IBVP), 93
- initial conditions, 93, 264, 280, 290, 402
- linear time-invariant (LTI) system, 404
- ordinary differential equations (ODE), 94, 404
- partial differential equation, 93
- steady state solution, 94
- diffusion mechanism, 26, 81, 85, 89–90, 113, 191, 354, 369
 - atomic flux, 2, 10–11, 66, 84, 86, 89, 91, 97, 104, 107, 110, 116–117, 127, 252–253, 255, 257, 269, 300, 303, 322–323, 383, 398, 400, 402
- bulk diffusion, 36, 177–178, 180, 183
- continuity equation, 87, 92, 255, 268, 319, 392
- correlation factor, 11
- diffusion barrier, 53, 63, 84, 127–128, 135, 147, 158, 176, 181, 200, 296–297, 378
- effective atomic diffusivity, 91, 102, 401
- Einstein relation, 252, 304
- energy of vacancy diffusion, 85, 254
- Fisher's model, 269
- flux divergence, 2, 86–88, 90–91, 104, 128, 255, 257, 270, 305, 323–324, 352
- flux divergence site, 2
- generation/annihilation term, 87, 92, 258
- grain boundary atomic diffusivity, 89
- grain boundary diffusion, 61–62, 71, 89, 121, 183, 186, 189, 195, 269–270, 296–297, 303, 329, 331, 350, 369
- interface diffusion, 64, 66, 68, 79, 115, 172, 180, 189, 201, 203, 243, 257, 271, 290, 296–297, 303, 329, 350, 369, 371
- interstitial diffusion, 29
- mass conservation condition, 9, 113, 305
- surface mass transport, 303
- uncorrelated diffusion coefficients, 11
- vacancy mechanism of diffusion, 89
- electric circuit, 402
 - bipolar (bidirectional) pulse current (BPC), 394
- circuit solver, 402
- direct current (DC), 99, 381
- electric current density, 131, 308, 401
- electric potential, 127, 135, 199, 305
- electric potential gradient, 127, 135
- line resistance change, 111–112, 118, 138, 143, 156, 164, 177, 179–180, 186, 190, 195
- pulse current, 392, 394, 412
- time-dependent current, 392–393
- VLSI circuits, 380, 401, 406
- electromigration (EM), xi, 2, 127, 203, 380
 - atomic diffusion, 1, 8, 61, 86, 89, 112, 115–116, 120, 249, 254, 257, 295, 301, 306, 310, 403, 409, *See* diffusion mechanism
- drift velocity measurement, 22
- effective charge, 9, 15–16, 18–20, 26, 29, 57, 89, 102, 135, 142, 244, 269, 304, 401
- electrical failures, 97
- electron wind force, 26, 28, 112, 142, 252, 302, 313, 321–322, 345
- electron-ion interaction, 26, 29
- electrostatic force, 1, 9, 15–16, 29, 142
- EM induced stress evolution, 81, 306, *See* EM induced stress
- equilibrium concentration of vacancies, 82, 253–254, 258, 283
- evolution of vacancy concentration, 92, 266, 293, 392

- generation/annihilation of vacancy-plated atom pairs, 258
- in-situ EM studies, 275
- Korhonen's equation, xii, 91–93, 96–97, 104–105, 266
- vacancy flux method, 1–2, 10, 21
- EM induced failure, 74
 - down-flow samples, 362, 365, 368, 370
 - EM early failure, 363, 373
 - failure criterion, 111, 138, 141–142, 146, 179, 185, 189, 343, 345, 352–353, 355, 360, 374, 390
 - late failure, 355, 357–358, 365–366, 368
 - parametric failure, 390
 - up-flow samples, 368, 370
- EM induced stress, 81, 266, 272, 313
 - back-flow stress, 36
 - biaxial stress, 38, 59, 73
 - compliance matrix, 42
 - critical stress, 93, 97–98, 100–101, 103–104, 118, 271, 273, 290, 325, 367, 398–400, 403–404
 - deformation tensor, 259
 - dilatational strain, 287
 - effective biaxial modulus, 230
 - effective bulk modulus, 70, 99, 102, 267, 401–404
 - effective triaxial elastic modulus, 240
 - elastic anisotropic, 230, 273
 - elastic deformation, 269, 271, 303
 - elastic stress, 88, 90
 - force balance equation, 268, 287, 289
 - inelastic strain components, 267
 - Lame's constants, 268
 - laser deflection technique, 41
 - passivation effect on thermal stress, 39
 - plastic deformation, 40, 55, 218, 252, 273, 278, 336
 - residual stress, 44, 46, 93, 100, 289, 382, 403–404
 - traction, 271, 310, 312
 - triaxial stress, 4, 41, 49, 54, 73–74, 233
 - volumetric strain, 88, 90, 253, 266–267, 274
 - wafer curvature method, 41
 - zero-stress temperature, 82, 101, 282, 284–285
- EM statistics, 354
 - bimodal distribution, 213, 358, 375
 - lifetime tests, 383
 - lognormal distribution, 115, 224, 347, 350–356, 367, 377, 382
 - mean-time-to-failure (MTTF), 381
 - normal distribution, 147, 170, 175
 - not a completely blocking boundary, 151
 - operating conditions, 288, 343, 353–354, 358, 370, 374, 382–383, 400
 - series model, 383, 385, 388, 390, 404
 - standard deviation, 141, 346, 351, 354–355, 382
 - stress conditions, 370, 382, 404, 412
 - time-to-failure, 381
 - upstream and downstream EM test-structures, 381
- weakest link approximation, 116, 383, 390
- weakest link statistics, 382
- Weibull distribution, 350, 382
- EM test structure, 146, 159–160, 172, 266, *See* EM statistics
- EM void, 367
 - EM induced void formation, 281, 360
 - heterogeneous void formation, 58
 - saturated void, 104–107, 109–110, 290, 403, 408
 - slit-like void, 295, 326
 - void detachment, 314
 - void drift velocity, 113–114
 - void migration, 115, 200, 272, 308, 315, 331, 336
 - void nucleation mode, 103
 - void nucleation time, 99–102, 104, 106, 109, 294
 - void shape evolution, 113, 272, 306, 312, 315, 328
 - void trapping, 313
 - voiding statistics, 73
 - wedge-shaped void, 308
- Extended Korhonen's Model, 401
- extrusion, 146, 148, 152–153, 158, 174, 186
- Gibbs free energy, 208, 212, 226
 - chemical potential, 9, 64, 66, 73, 269, 271, 289, 302–303, 312–313, 323–324
 - chemical potential of a surface atom, 303
 - elastic strain energy, 208–209, 213, 218, 223–224, 231–234, 241, 246, 269, 303, 312
 - free energy functional, 323
 - free energy of the surface, 302
 - grain boundary energy, 208, 212, 216–218, 225–227, 232–234, 239–240, 246
 - interface energy, 204, 211, 213, 216, 218, 223, 225, 229, 234–235, 237, 240–241, 246
 - surface energy, 57, 98, 113, 209, 213, 215, 224–225, 229–230, 232–234, 240–241, 246, 248, 250, 269, 289, 303, 309, 311–312, 314, 323, 325
- grain boundary (GB), 97, 136
 - coherent twin boundary, 217, 219
 - grain boundary migration, 226, 271, 313
 - grain boundary mobility, 128–129, 226, 229
 - grain-boundary energy functions, 227
 - incoherent twin boundaries, 217
- grain growth mechanism, 128
 - abnormal grain growth, 152, 172, 187, 211, 213, 215–217, 223–225, 229, 231, 234, 237, 239, 241, 246
- bimodal lognormal statistics, 216, 239, 241
 - coincidence site lattice (CSL) model, 217
- grain orientation map, 129, 208, 235–236, 238
- grain size distribution, 132, 213, 215–217, 224, 226, 229, 231, 233–234, 237, 239, 241, 243, 246, 281, 290, 353

- grain growth mechanism (cont.)
 - kinetics of grain growth, 209
 - normal grain growth, 212, 216, 225–226, 229, 234, 249, 377
 - polycrystalline thin films, 64, 77, 208, 226, 247
- grain microstructure, 186
 - bamboo-like segments, 115
 - bamboo-polygrain segments, 215, 217, 223, 239, 244
 - crystallographic orientation, 248, 266, 275–277, 279
 - Cu face-center-cubic (fcc) lattice structure, 213
 - electron backscatter diffraction (EBSD), 272
 - evolution in Cu nanolines, 234–235
 - hexagonal closed packed (hcp) structure, 220
 - inverse pole figure (IPF) orientation maps, 207
 - Miller indices (hkl), 239
 - multiples of random distribution (MRD), 206–207
 - Orientation Distribution Function (ODF), 207
 - orientation-mapping of grain structures, 204
 - poly-grain clusters, 81, 86, 115, 117–118, 243, 255
 - scaling effect on microstructure evolution, xii, 4, 203–204, 209, 212, 214, 217, 223, 225, 235, 245–246
 - triple point, 57, 353
- Hall-Petch relationship, 218
- hillock, 37, 97, 120, 174, 190, 380
- imbedded via, 158
- incubation time, 103, 138–139, 142–144, 190, 343–345, 348, 352–353
 - Boro-Phospho-Silicate Glass (BPSG), 38
 - MSQ (methyl silsesquioxane), 49
- inter-layer/inter-metal dielectric (ILD/IMD), 115
 - OSG (organosilicate glass), 54
 - PAE (poly-arylene ether), 46
 - Plasma-Enhanced Silicon Nitride (PEN), 38
 - TEOS (Tetraethyl orthosilicate), 38
- Joule heating, 22, 362, 402
 - Miller-Bravais indices (hkil), 239
- Monte Carlo simulation, xii, 5, 204, 209, 212, 220, 225, 230–231, 235, 239, 241–242, 244–246, 250
 - modified Potts model, 232
 - simulation algorithm, 226, 231, 233, 239–240
- Moore's Law, 2–3, 34
- multilayered conductor structures, 34
 - hierarchical wiring structure, 34
 - multilayered Cu wiring structure, 34
 - Non Metallic Impurities, ix, 169
 - photolithographic patterning, 38
 - sidewall Ta/TaN barrier layers, 212
 - subtractive etching process, 34, 38–39, 48
- surface treatments, 129, 169
- very large-scale integration (VLSI), 34
- Cu damascene lines, 3, 48–49, 51–52, 54–55, 63, 80, 131, 133–134, 142, 164, 169, 172, 185, 193, 201, 203, 206, 209, 212–214, 219, 225, 244, 274
- Multiphysics models, 329
- numerical technique, 268, 272, 313, 401
 - curvature gradient, 306, 308, 310
 - diffuse interface model, 272, 322, 325, 330
 - Finite element analysis (FEA), 118
 - front tracking algorithms, 309
 - level-set method, 309
 - moving boundary problems, 271
 - order parameter field, 309
 - phase field model, 225, 317, 323–324, 329, 331, 336
 - sharp interface model, 315–316, 323
- on-chip interconnect, 96, 105, 165–166, 197–198, 249, 328, 330, 381
 - Al metallization, 127, 295–296
 - anode end of line, 255
 - cathode end of line, 97, 108, 163, 257
 - CNT composite lines, 172, 174, 196
 - Copper interconnect, 77
 - current ports, 96
 - flip-chip bumps, 385
 - interconnect segment, 96–97, 115, 120, 263, 266, 272, 282, 284, 382
 - interconnect tree, 96, 105, 383–386, 398–399, 403, 409
 - power-ground grid, 97, 105, *See power/ground grid*
 - self-healing, 390
 - tungsten via, 324
- power/ground grid, 103
 - effective direct current, 381
 - mesh structure, 385
 - power grid benchmark circuits, 400
 - power grid EM assessment, 5, 380
 - redundancy, xii, 5, 138, 172, 339, 346, 374, 380, 385, 388, 390, 401
 - transient source currents, 391
 - voltage drop degradation, 389–390
- resistivity size effect, 128
- scaling effects, xii, 4, 80, 197, 219, 239
 - EM lifetime, 3, 10, 15, 63, 70, 116, 129, 138, 144–147, 150–151, 153, 155, 162, 165–168, 174–175, 183, 185, 188, 194–196, 203, 215, 217, 223, 242, 244, 280, 330, 390
 - Scaling effect on twin formation, viii, 217, 219

- scanning electron microscopy (SEM), 272
- scanning transmission electron microscopy (STEM), 296
- solute effects on EM, 13
- carrier-density modulation effect, 18
 - Gibbs-Duhem relations, 11
 - irreversible thermodynamics, 4, 8, 10
 - liquid binary alloys, 19, 31
- Soret effect, 33, 253
- stress effects, xii, 4, 358, 412
- dielectric confinement, 37, 40, 55–56
 - effect of elastic anisotropy, 43, 115
 - plastic yield, 40, 55, 62–63
 - von Mises yield criterion, 56
- stress induced voiding (SIV), 72, 325
- stress migration, 55, 71, 383, 403
- stress relaxation in Cu interconnects, 62
- long-term relaxation rates, 59
 - McPherson and Dunn model, 73–74
 - passivation effect on stress relaxation, 70
 - short-term stress relaxation kinetics, 59
- Stress relaxation processes and deformation mechanisms, 63
- stress-induced void formation, 3, 7, 36–37, 62, 75, 122, 358
- temperature distribution, 253, 282, 308, 402–403
- compact thermal model, 402
 - heat equation, 282
 - heat propagation, 402
 - thermal capacitor, 402
 - thermal cells, 402
 - thermal netlist, 402
 - thermal properties, 316, 402
 - Thermal resistors, 402
- transmission electron microscopy (TEM), 195, 203, 296
- trapping model, 191, 194
- Wheatstone bridge, 367
- X-ray diffraction measurements, xii, 37, 41–42, 44, 54
- Synchrotron X-ray sources, 54